Delhi Buses: Static Data - DTC, DoT

Link to dataset:
https://delhi.transportstack.in/data-services/datadetails/1

About the dataset:
The static GTFS feed consists of text files in CSV (Comma-Separated Values) format, compressed into a ZIP file, providing details about the public transit bus system of Delhi - schedule, routes, stops, and fare structures.

1. Summary

Number of stops	10,559
Number of routes	2,403
Number of trips	89,393
Average number of stations per trip	41

2. Agency Metadata

Field Name	Type	Description
agency_id	ID	Identifies a transit agency. A dataset may contain data for multiple transit agencies.
agency_name	Text	Full name of the transit agency.
agency_url	URL	URL of the transit agency's website.
agency_timezone	Time zone	The time zone in which the transit agency operates.
agency_lang	Text	Language used by the agency in the dataset (e.g., "en" for English).
agency_phone	Phone Number	Telephone number for the transit agency.
agency_fare_url	URL	URL directing to fare information for the agency.

3. Calendar Metadata

Field Name	Type	Description
service_id	ID	Identifies a set of dates when a service is available for one or more routes.
monday	Integer	Indicates whether the service is valid on Mondays (1 = service available, 0 = no service).
tuesday	Integer	Indicates whether the service is valid on Tuesdays (1 = service available, 0 = no service).
wednesday	Integer	Indicates whether the service is valid on Wednesdays (1 = service available, 0 = no service).
thursday	Integer	Indicates whether the service is valid on Thursdays (1 = service available, 0 = no service).
friday	Integer	Indicates whether the service is valid on Fridays (1 = service available, 0 = no service).
saturday	Integer	Indicates whether the service is valid on Saturdays (1 = service available, 0 = no service).
sunday	Integer	Indicates whether the service is valid on Sundays (1 = service available, 0 = no service).
start_date	Date	Start date for the service (YYYYMMDD format).
end_date	Date	End date for the service (YYYYMMDD format).

4. Fare Attributes Metadata

Field Name	Type	Description
fare_id	ID	Identifies a fare class.
price	Float	Fare price, in the unit specified by currency_type.
currency_type	Currency	ISO 4217 alphabetic currency code specifying the unit of the fare.
payment_method	Integer	When the fare is paid (0 = on board, 1 = before boarding).
transfers	Integer	Number of transfers permitted (e.g., 0, 1, 2).

agency_id	ID	Identifies the agency associated with this fare ID (if multiple agencies are present).
transfer_duration	Integer	Time in seconds that a transfer is valid (optional).

5. Fare Rules Metadata

Field Name	Type	Description
fare_id	ID	Identifies a fare class.
route_id	ID	Identifies a route associated with the fare ID (optional).
origin_id	ID	Identifies an origin zone (optional).
destination_id	ID	Identifies a destination zone (optional).
contains_id	ID	Identifies a zone the fare ID is valid for (optional).

6. Routes Metadata

Field Name	Type	Description
route_id	ID	Identifies a route.
agency_id	ID	Identifies the agency for the route (optional).
route_short_name	Text	Short name of the route.
route_long_name	Text	Full name of the route.
route_desc	Text	Description of the route (optional).
route_type	Integer	Type of transportation used on the route (e.g., 3 for bus).
route_url	URL	URL for a web page about the route (optional).
route_color	Color	Route color (optional).
route_text_color	Color	Text color used on route (optional).

7. Stop Times Metadata

Field Name	Type	Description
trip_id	ID	Identifies a trip.
arrival_time	Time	Arrival time at a stop.
departure_time	Time	Departure time from a stop.
stop_id	ID	Identifies a stop.
stop_sequence	Integer	Order of the stop in the trip.
stop_headsign	Text	Headsign at the stop (optional).
pickup_type	Integer	Indicates if passengers can board (optional).
drop_off_type	Integer	Indicates if passengers can alight (optional).
shape_dist_traveled	Float	Distance traveled along shape (optional).
timepoint	Integer	Indicates if times are exact (optional).

8. Stops Metadata

Field Name	Type	Description
stop_id	ID	Identifies a stop.
stop_code	Text	Short code for the stop (optional).
stop_name	Text	Name of the stop.
stop_desc	Text	Description of the stop (optional).
stop_lat	Latitude	Latitude of the stop.
stop_lon	Longitude	Longitude of the stop.
zone_id	ID	Identifies a fare zone (optional).
stop_url	URL	URL for a web page about the stop (optional).
location_type	Integer	Type of location (e.g., 0 for stop, 1 for station).
parent_station	ID	Identifies the parent station (optional).
stop_timezone	Timezone	Timezone of the stop (optional).
wheelchair_boarding	Integer	Indicates if wheelchair boarding is possible (optional).

9. Trips Metadata

Field Name	Type	Description
route_id	ID	Identifies a route.
service_id	ID	Identifies a set of dates when a service is available.
trip_id	ID	Identifies a trip.
trip_headsign	Text	Headsign for the trip (optional).
trip_short_name	Text	Short name for the trip (optional).
direction_id	Integer	Direction of travel for the trip (optional).
block_id	ID	Identifies a block of trips (optional).
shape_id	ID	Identifies a shape for the trip (optional).
wheelchair_accessible	Integer	Indicates if the trip is wheelchair accessible (optional).
bikes_allowed	Integer	Indicates if bikes are allowed on the trip (optional).

More information about GTFS data can be found here - https://gtfs.org/documentation/schedule/reference/