

Week 3

Synchronization Primitives

Max Kopinsky 21 January, 2025

Teams Registration is Open






Teams Registration is Open

- You **must** fork the repository. You won't be able to submit your work to my repository. You can change the name of your fork if you want.
- If you want to work alone, you must submit a team registration with no teammate. Otherwise our autograder doesn't know about you.
- Your registration must be a plain text file with some information about your team. Read the directions carefully. The submissions are processed by a script. You will consume a lot of TA time if we have to track you down to correct errors.

Recap from Week 2

- Process
- Linux process tree
- Process switch
- Process scheduler

Recap from Week 2 Process = Program in execution




Recap from Week 2 Linux Process Primitives

- pid = fork()
- exec(filename)
- exit()
- wait()


Recap from Week 2 Process = Environment + Code

environment code

Recap from Week 2 After a fork()




Recap from Week 2 After an exec() in the Child




Recap from Week 2 Process Switch

- Change of process using the CPU
- Save and restore registers and other info



Recap from Week 2 **Process Scheduling**



11

Questions from last week?

Before we begin with today's topic

- Concurrency is a large sub-field of computer science
- In this course, we get a small taste of it
- If you enjoy this lecture, consider **COMP-409 Concurrent programming**
 - Highly recommend for a strong systems background

Real world concurrency

- Millions of drivers on highway at once.
- Student does homework while watching Netflix.
- Faculty has lunch while grading papers


Real world concurrency

- Millions of drivers on highway at once.
- Student does homework while watching Netflix.
- Faculty has lunch while grading papers... and watching Netflix.

Key Concepts for Today


- Process vs Thread
- Mutual Exclusion
- Locking
- Deadlocks
- Conditional variables

Motivation for Concurrency – Moore's Law




Motivation for Concurrency

- CPU trend: Same speed, but multiple cores
- Goal: write applications that fully utilize many cores




Concurrency Abstraction vs Reality



- Build apps from many communicating processes
- Communicate through message passing
 - No shared memory
- Pros
 - If one process crashes, other processes unaffected
- Cons
 - High communication overheads
 - Expensive context switching

- Build apps from many communicating processes
- Communicate through message passing
 - No shared memory
- Pros
 - If one process crashes, other processes unaffected
- Cons
 - High communication overheads
 - Expensive context switching



- New abstraction: thread
- Multiple threads in a process
- Threads are like processes except
 - Multiple threads in the same process share an address space
 - Communicate through shared address space
 - If one thread crashes,
 - the entire process, including other threads, crashes

Will see synchronization principles **today**

- New abstraction: thread
- Multiple threads in a process


Will see practical examples later

- Threads are like processes except
 - Multiple threads in the same process share an address space
 - Communicate through shared address space
 - If one thread crashes,
 - the entire process, including other threads, crashes

Two Processes

code code globals globals heap heap stack stack registers registers PC PC


Two Threads in a Process



In General

- Processes provide separation
 - In particular, memory separation (no shared data)
 - Suitable for coarse-grain interaction
- Threads do not provide separation
 - In particular, threads share memory (shared data)
 - Suitable for tighter integration

Where Things Reside



shared variable (e.g., shared counter, shared flag)

Shared Data

- Advantage:
 - Many threads can read/write it
- Disadvantage:
 - Many threads can read/write it

Shared Data

- Advantage:
 - Many threads can read/write it
- Disadvantage:
 - Many threads can read/write it
 - Can lead to data races

Data Race

- Unexpected/unwanted access to shared data
- Result of interleaving of thread executions
- Program must be correct for all interleavings
 - (another COMP 525 topic)

A Common Mistake/Misunderstanding: A Single Line of Code is not Atomic

- a = a + 1
- Is in reality
 - Load a from memory into register
 - Increment register
 - Store register value in memory
- Instruction sequence may be interleaved
- (Some machines have atomic increments)

balance = balance + 1; // balance in shared memory at 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: ?

%rip = 0x195

process

control

blocks:

Thread 1

%eax: ?

%rip: 0x195

Thread 2

%eax: ?



- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 100

%rip = 0x19a

process

control

blocks:


Thread 1

%eax: ?

%rip: 0x195

Thread 2

%eax: ?



- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 101

%rip = 0x19d

process

control

blocks:

Thread 1


%eax: ?

%rip: 0x195

Thread 2

%eax: ?

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax





balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x1a2

process

control

blocks:

Thread 1

%eax: ?

%rip: 0x195

Thread 2

%eax: ?

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x1a2

process

control

blocks:

Thread 1

%eax: ?

%rip: 0x195

Thread 2

%eax: ?

%rip: 0x195

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



Thread context switch!

state of T1 saved in T1 pcb upon context switch

balance = balance + 1; // balance in shared memory at 0x9cd4

state of T2 loaded in CPU State:

0x9cd4: 101

%eax: ?

 $%rip = \frac{0x195}{}$

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x1a2

Thread 2

%eax: ?

%rip: 0x195

T2

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

note that code region is common to T1 & T2

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: ?

%rip = 0x195

____'

process

blocks:

Thread 1

%eax: 101

%rip: 0x1a2

Thread 2

%eax: ?

%rip: 0x195

T2

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x19a

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x1a2

Thread 2

%eax: ?

%rip: 0x195



- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 102

%rip = 0x19d

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x1a2

Thread 2

%eax: ?

%rip: 0x195

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax



0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

Desired result ©

State:

0x9cd4: 102

%eax: 102

%rip = 0x1a2

Thread 1

%eax: 101

%rip: 0x1a2

Thread 2

%eax: ?

%rip: 0x195

• 0x195 mov 0x9cd4, %eax

process

control

blocks:

- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



Another schedule

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: ?

%rip = 0x195

process

control

blocks:

Thread 1

%eax: ?

%rip: 0x195

Thread 2

%eax: ?

%rip: 0x195



- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 100

%rip = 0x19a

_

control

process

blocks:

Thread 1


%eax: ?

%rip: 0x195

Thread 2

%eax: ?

%rip: 0x195



- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 101

%rip = 0x19d

process

control

blocks:

Thread 1


%eax: ?

%rip: 0x195

Thread 2

%eax: ?

%rip: 0x195



- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



Thread context switch!

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: ?

%rip = 0x195

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: ?

%rip: 0x195

T2

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 100

%rip = 0x19a

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: ?

%rip: 0x195



• 0x195 mov 0x9cd4, %eax

process

control

blocks:

- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 100

%eax: 101

%rip = 0x19d

process

control

blocks:

%eax: 101

Thread 1

%rip: 0x19d

Thread 2

%eax: ?

%rip: 0x195

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax



0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x1a2

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: ?

%rip: 0x195

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x1a2

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: ?

%rip: 0x195

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



Thread context switch!

balance = balance + 1; // balance in shared memory at 0x9cd4

State:

0x9cd4: 101

%eax: 101

%rip = 0x19d

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: 101

%rip: 0x1a2







0x19d mov %eax, 0x9cd4

balance = balance + 1; // balance in shared memory at 0x9cd4

WRONG Result!
Final value of balance is 101

State:

0x9cd4: 101

%eax: 101

%rip = 0x1a2

process

control

blocks:

Thread 1

%eax: 101

%rip: 0x19d

Thread 2

%eax: 101

%rip: 0x1a2

- 0x195 mov 0x9cd4, %eax
- 0x19a add \$0x1, %eax
- 0x19d mov %eax, 0x9cd4



Non-Determinism

Concurrency leads to non-deterministic results

- Different results even with same inputs
- Race conditions

Whether bug manifests or not depends on CPU schedule!

How to program?

- Assume scheduler is malicious
- Assume scheduler will pick bad ordering at some point...

Basic Approach to Multithreading

- 1. Divide "work" among multiple threads &
- 2. Share data
 - Which data is shared?
 - Global variables and heap
 - Not local variables, not read-only variables
 - Where is shared data accessed?
 - Put shared data access in critical section

Critical Section

- Want 3 instructions to execute as an uninterruptable group
- We say we want them to be "atomic"

mov 0x123, %eax add %0x1, %eax mov %eax, 0x123

critical section

Need **mutual exclusion** for critical sections

- If thread A is in critical section C, thread B can't enter C
- Ok if other processes/threads do unrelated work

Aside: Non-Atomic Single Instructions

• We just implemented x = x + 1 with:

mov 0x123, %eax add \$0x1, %eax mov %eax, 0x123

But x86 has this instruction:

add \$0x1, 0x123

Aside: Non-Atomic Single Instructions

• We just implemented x = x + 1 with:

mov 0x123, %eax add \$0x1, %eax mov %eax, 0x123

But x86 has this instruction:

add \$0x1, 0x123

- No difference! This single instruction is not atomic.
 - (The similar `lock add` instruction is atomic.)

Mutual Exclusion

- Prevents simultaneous access to a shared resource.
 - In this case, shared resource = shared memory region
- How can we achieve mutual exclusion?
 - Today we will first see library support (pthreads)
 - Then, we will see implementation of synchronization primitives.

Why this (mostly) works

- Critical section:
 - No other thread can change data
- So you are (mostly) ok

Synchronization

Build higher-level synchronization primitives in OS

Operations that ensure correct ordering of instructions across threads

Motivation: Build them once and get them right

Software

Monitors Locks (mutex) Semaphores
Condition Variables

Hardware

Loads Stores Test&Set Disable Interrupts

POSIX Thread Libraries (pthreads)

- Thread API for C/C++
- User-level library:
 - #include <pthread.h>
 - Compile and link with -pthread.
- Support for thread creation, termination, synchronization.
- See more details here: https://man7.org/linux/man-pages/man3/

Pthreads: Thread Creation and Destruction

- pthread create()
- pthread exit()
- pthread join()

pthread_create()

```
int pthread_create(
   pthread_t * thread, pthread_attr_t * attr,
   void *(*start_routine)(void *), void * arg
);
```

- Create thread, in thread.
- Run start_routine with arguments arg.
- attr points to a pthread_attr_t structure. If attr is NULL, then the thread is created with default attributes (ok in most cases).
- On success, return 0; on error, return an error number.

```
pthread_exit()
```

void pthread_exit(void *retval);


- Terminate calling thread.
- Returns a value via retval.

```
pthread_join()
```

int pthread_join(pthread_t thread, void **retval);

- Join with a terminated thread.
- Waits for the thread specified by thread to exit.
- If *retval* is not NULL, then **pthread_join**() copies the return value of the target thread into the location pointed to by *retval*.
- On success, return 0; on error, return an error number.

Fork-Join Pattern for threads



Main thread creates (forks) collection of sub-threads passing them args to work on... ... and then joins with them, collecting the results

Note: In this example, start_routine is the same for all threads; only args are different.

Fork-join example

```
void *mythread(void *arg) {
 printf("%s\n", (char *) arg);
return NULL;
int main(int argc, char *argv[]) {
 pthread_t p1, p2;
 printf("main: begin\n");
 pthread_create(&p1, NULL, mythread, "A");
 pthread_create(&p2, NULL, mythread, "B");
 pthread_join(p1, NULL);
 pthread_join(p2, NULL);
 printf("main: end\n");
```

Counting example – What is the final answer?

```
int count;
void *mythread(void *arg) {
int j;
 for (j = 0; j < 1000000; j++){
  count +=1;
 return NULL;
int main(int argc, char *argv[]) {
 pthread_t p1, p2;
count = 0;
 pthread_create(&p1, NULL, mythread, NULL);
 pthread_create(&p2, NULL, mythread, NULL);
 pthread_join(p1, NULL);
 pthread_join(p2, NULL);
 printf("%d \n", count);
```

Pthreads: Locks

- Pthread_mutex_lock(mutex)
- Pthread_mutex_unlock(mutex)

Pthread_mutex_lock(mutex)

- If lock is held by another thread, block
- If lock is not held by another thread
 - Acquire lock
 - Proceed

Pthread_mutex_unlock(mutex)

Release lock

Counting example revisited – What is the final answer?

```
pthread mutex t count mutex
int count;
void *mythread(void *arg) {
int j;
 for (j = 0; j < 1000000; j++){
  pthread_mutex_lock(&count_mutex);
  count +=1;
  pthread mutex unlock(&count mutex);
 return NULL;
int main(int argc, char *argv[]) {
 pthread_t p1, p2;
 pthread mutex init(&count mutex, NULL);
count = 0;
 pthread_create(&p1, NULL, mythread, NULL);
 pthread_create(&p2, NULL, mythread, NULL);
 pthread join(p1, NULL);
 pthread_join(p2, NULL);
 printf("%d \n", count);
```

Deadlocks

- Threads are stuck waiting for blocked resources and no amount of retry (backoff) will help.
- Classic example:

Thread A

1 lock(object1)

2 lock(object2)

3 //do stuff

4 unlock(object2)

5 unlock(object1)

• •

Thread B

1 lock(object2)

2 lock(object1)

3 //do stuff

4 unlock(object1)

5 unlock(object2)

•••





Deadlocks

- Threads are stuck waiting for blocked resources and no amount of retry (backoff) will help.
- Classic example:

Thread A

1 lock(object1)

2 lock(object2)

3 //do stuff

4 unlock(object2)

5 unlock(object1)

••

Thread B

1 lock(object2)

2 lock(object1)

3 //do stuff

4 unlock(object1)

5 unlock(object2)

•••






Deadlocks

- Threads are stuck waiting for blocked resources and no amount of retry (backoff) will help.
- Classic example:

Thread A 1 lock(object1) 2 lock(object2) 3 //do stuff 4 unlock(object2) 5 unlock(object1)





Deadlock example

```
pthread_mutex_t lock1;
pthread_mutex_t lock2;

void *a_func(void *arg) {
    long j;
    for (j = 0; j < 100000000; j++) {
        pthread_mutex_lock(&lock1);
        pthread_mutex_lock(&lock2);
        printf("A");
        pthread_mutex_unlock(&lock2);
        pthread_mutex_unlock(&lock1);
    }
    return NULL;
}</pre>
```

```
void *b_func(void *arg) {
long j;
for (j = 0; j < 100000000; j++) {
   pthread_mutex_lock(&lock2);
   pthread_mutex_lock(&lock1);
   printf("B");
   pthread_mutex_unlock(&lock1);
   pthread_mutex_unlock(&lock2);
}
return NULL;
}</pre>
```

```
int main(int argc, char *argv[]) {
  pthread_t a, b;
  pthread_mutex_init(&lock1, NULL);
  pthread_mutex_init(&lock2, NULL);
  pthread_create(&a, NULL, a_func, NULL);
  pthread_create(&b, NULL, b_func, NULL);
  pthread_join(a, NULL);
  pthread_join(b, NULL);
  printf("End!\n");
}
```


Week 3 Synchronization Primitives

Max Kopinsky 23 January, 2025

Assignment 1 Release – Clone

- Clone your fork
 - on mimi
 - (+ your machine, if you want)
 - Use your SOCS user+passwd

This command (with your own repo link)



\$ git clone https://gitlab.cs.mcgill.ca/mkopin/operating-systems-w25 Cloning into 'operating-systems-w25'... Username for 'https://gitlab.cs.mcgill.ca': mkopin Password for 'https://mkopin@gitlab.cs.mcgill.ca': warning: redirecting to https://gitlab.cs.mcgill.ca/mkopin/operating-systems-w25.git/ You can ignore this warning if you get it remote: Enumerating objects: 6, done. remote: Counting objects: 100% (6/6), done. remote: Compressing objects: 100% (4/4), done. remote: Total 6 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0) Receiving objects: 100% (6/6), done.


Assignment 1 Release – Visibility Settings


- From the GitLab page for your repository
- Left panel > settings > General > Visibility
 - Change "Project Visibility" to private
 - If you do not do this, other students can copy your work. You would **both** be in trouble.

Add your partner, myself, and the autograding TA to members:

- Partner role: developer
- Also add: @mkopin (me!) with role Reporter
- And add @mohamad.danesh as Reporter too

Visibility, project features, permissions
 Choose visibility level, enable/disable project features and their permissions, disable email notifications, and show default emoji reactions.





Assignment 1 Release – Git Merge

- Finally whenever we release an assignment, you must update your fork with the changes from our "upstream" fork to get the materials (instructions, test cases, code, ...) for that assignment.
- These commands will also be posted on Discord.

```
$ git remote add staff https://gitlab.cs.mcgill.ca/mkopin/operating-systems-w25
$ git fetch staff
$ git checkout main
$ git merge staff/main
```

This one must be to my repository

Synchronization

Build higher-level synchronization primitives in OS

Operations that ensure correct ordering of instructions across threads

Motivation: Build them once and get them right

Software

Monitors Locks (mutex) Semaphores
Condition Variables

Hardware

Loads Stores Test&Set Disable Interrupts

Condition Variables

- Used when thread A needs to wait for an event done by thread B
- A waits until a certain condition is true
 - First test condition,
 - If condition not true, call pthread cond wait()
 - A blocks until another thread "signals" the condition variable
- At some point B makes the condition true
 - Then B calls pthread cond signal(), which unblocks A.

Advantage of Condition Variable of Locks

- A waits until a certain condition is true
 - A goes to sleep here.
 - Does not keep CPU busy.

Thread A

```
x = f(a, b);
if (x < 0 \mid \mid x > 9)
pthread_cond_wait (&cv);
```

Thread B

```
//change a and b;

x = f (a , b);

if (x >= 0 && x <= 9)

pthread_cond_signal (&cv);
```

Find the data race.

Thread A

Thread B

```
//change a and b;

x = f (a , b);

if (x >= 0 && x <= 9)

pthread_cond_signal (&cv);
```

Thread A

Thread B

```
//change a and b;

x = f (a , b);

if (x >= 0 && x <= 9)

pthread_cond_signal (&cv);
```

Thread A

```
x = f(a,b);
if(x < 0 | | x > 9)
    pthread_cond_wait(&cv);
Interrupt
```

Thread B

```
//change a and b;

x = f (a , b);

if (x >= 0 && x <= 9)

pthread_cond_signal(&cv);
```

:(Broadcast missed by A

Thread A

```
x = f ( a , b );
if ( x < 0 | | x > 9)
pthread_cond_wait (&cv);
```

A waits forever...

Thread B

```
//change a and b;

x = f(a, b);

if (x \ge 0 \&\& x \le 9)

pthread_cond_signal (&cv);
```

Thread A

```
pthread_mutex_lock(&mutex );
x = f ( a , b );
if ( x < 0 | | x > 9)
  pthread_cond_wait (&cv, &mutex);
pthread_mutex_unlock(&mutex);
```

Thread B

```
pthread_mutex_lock(&mutex );
//change a and b;
x = f (a , b);
if (x >= 0 && x <= 9)
  pthread_cond_signal (&cv);
pthread_mutex_unlock(&mutex);</pre>
```

Remember: Condition variable is a shared resource between A and B

→ Every time you use a condition variable you must also use a mutex to prevent the race condition.

One more issue...

Sometimes, the wait function might return even though the condition variable has not actually been signaled. **This is part of the API** as an unfortunate necessity.

Thread A Thread B

```
pthread_mutex_lock(&mutex );
x = f ( a , b );
if ( x < 0 | | x > 9)
  pthread_cond_wait (&cv, &mutex);
pthread_mutex_unlock(&mutex);
```

```
pthread_mutex_lock(&mutex );
//change a and b;
x = f (a , b);
if (x >= 0 && x <= 9)
  pthread_cond_signal (&cv);
pthread_mutex_unlock(&mutex);</pre>
```

Example:

If process P running A and B receives an OS signal

Any thread in P can be chosen to process the signal.

- How can we fix this?
- → A might be chosen to process the signal handling function
- → wait returns with an error code → A runs even if condition is not true...

- Retest the condition after pthread_cond_wait() returns.
 - This is most easily done using a loop.

Thread A

```
pthread_mutex_lock(&mutex);
while (1) {
  x = f (a,b);
  if (x < 0 | | x > 9) {
    pthread_cond_wait (&cv, &mutex);
  } else {
    break;
  }
}
pthread_mutex_unlock(&mutex);
```

Thread B

```
pthread_mutex_lock(&mutex );
//change a and b;
x = f (a , b);
if (x >= 0 && x <= 9)
  pthread_cond_signal (&cv);
pthread_mutex_unlock(&mutex);</pre>
```

Conditional Variables Interface

- pthread_cond_init(pthread_cond_t *cv, pthread_condattr_t *cattr)
 - Initialize the conditional variable, cattr can be NULL
- pthread_cond_wait(pthread_cond_t *cv, pthread_mutex_t *mutex)
 - Block thread until condition is true, and atomically unlock mutex.
 - When the thread is unblocked, reacquire the mutex as if by pthread_mutex_lock
 - Might cause thread to block again!
- pthread_cond_signal(pthread_cond_t *cv)
 - Unblock one thread at random that is blocked by the condition variable
- pthread_cond_broadcast(pthread_cond_t *cv)
 - Unblock all threads that are blocked on the condition variable pointed to by cv.

Condition Variable Example

```
pthread cond t is zero;
                                                                  int main (void){
pthread mutex t mutex;
int shared data = 100;
                                                                   pthread t tid;
                                                                   void * exit status;
                                                                   int i;
void *thread_func(void *arg){
 while(shared data > 0) {
                                                                   pthread cond init(&is zero, NULL);
  pthread_mutex_lock(&mutex);
                                                                   pthread mutex init(&mutex, NULL);
  shared data--;
  printf("%d ", shared_data);
                                                                   pthread create(&tid, NULL, thread func, NULL);
  pthread mutex unlock(&mutex);
                                                                   pthread mutex lock(&mutex);
                                                                   printf("Start waiting in main\n");
 printf("Signaling main\n");
                                                                   while(shared data!=0)
                                                                    pthread cond wait(&is zero, &mutex);
 pthread cond signal(&is zero);
                                                                   pthread mutex unlock(&mutex);
 return NULL;
                                                                   printf("Done waiting in main!\n");
                                                                   pthread join(tid, &exit status);
                                                                   return 0;
```

Synchronization

Build higher-level synchronization primitives in OS

Operations that ensure correct ordering of instructions across threads

Motivation: Build them once and get them right


Monitors Locks (mutex)

Condition Variables

Loads Stores Test&Set

Disable Interrupts

Semaphores



What are Semaphores?

- A shared, non-negative counter.
- Two primary operations:
 - Wait \rightarrow attempts to decrement the counter; blocks when counter is 0.
 - Post (or Signal) → attempts to increment the counter.
- #include<semaphore.h>

Changes are atomic

unsigned int

Semaphore

unsigned int

Changes are atomic 2 operations

wait()

post()

Semaphore

unsigned int

Semaphore


Changes are atomic 2 operations

wait()


try to decrement semaphore value block if value = 0

post()


increment semaphore value



Semaphore



Semaphore




```
wait() {

while(1){
    if (v>0){
    v--;
    return;
    }
}

Wait until semaphore value becomes positive again
```

Semaphore





wait() {

```
while(1){
    if (v>0){
        v--;
        return;
    }
}
Atomic execution


return;
}
```


Once the value is positive, the thread that Was waiting is able to decrement the value.





Semaphore





Semaphore

unsigned int

One last thing:

 Semaphore value can be initialized upon creation to a positive value

• or 0

Semaphore

Semaphore Uses

Mutual exclusion

• A semaphore with its counter initialized to 1 can be used as a lock.

Bound the concurrency

Only allow X threads out of N to proceed.

Producer-consumer problem

• More complex use of semaphores. Will see in 2 weeks.

Semaphores interface

```
    int sem_init(sem_t *sem, int pshared, unsigned value);
```

```
int sem_post(sem_t *sem);
```

int sem_wait(sem_t *sem);

For more details: https://man7.org/linux/man-pages/man0/semaphore.h.0p.html

int sem_init(sem_t *sem, int pshared, unsigned value);

- Initializes the semaphore * sem. The initial value of the semaphore is value.
- If pshared is 0, the semaphore is shared among all threads of a process.
- If *pshared* is not zero, the semaphore is shared *between processes* but
 - Must be stored somewhere that multiple processes can see, e.g. file-mapped memory.
 - Don't worry about this use case. We won't discuss process-shared memory in this course.
- Return 0 on success, -1 on failure.

int sem_wait(sem_t *sem);

- If the sem has a value > 0, decrement the value by 1.
- If sem has value 0, the caller will be blocked until sem has a value larger than 0.
- Return 0 on success, -1 on failure.

int sem_post(sem_t *sem);

- Increment the value of sem by 1.
- If threads are blocked waiting for the semaphore, one of them (at random) will return successfully from its call to *sem_wait*(); the semaphore value is immediately decremented.
 - (this doesn't happen until one of those threads is next scheduled but focus on concepts!)
- Return 0 on success, -1 on failure.

Semaphores example

Note: If 2 is changed to 1, we have a lock behavior

```
#include <pthread.h>
#include <semaphore.h>
pthread_t threads[5];
int tid[5];
sem t sem;
void * thread func(void *arg){
 int tid_ = tid[* (int *) arg];
 printf("Thread %d created\n", tid_);
 int i:
 sem wait(&sem);
 for (j=0; j<3; j++){
  printf("T%d run %d\n", tid , j);
  sleep(2);
 sem post(&sem);
```


```
int main(){
 sem_init(&sem, 0, 2);
 //sem initialized for all threads in the process; allow only 2 threads in
the critical section at a time;
 int i;
 for (i=0; i<5; i++){
  tid[i]=i;
  pthread_create(&threads[i], NULL, thread_func, &tid[i]);
 for (i=0; i<5; i++){
  pthread_join(threads[i], NULL);
 sem_destroy(&sem);
 return 0;
```

Synchronization

Build higher-level synchronization primitives in OS

Operations that ensure correct ordering of instructions across threads

Motivation: Build them once and get them right



Monitors

- Collection of variables and functions
- Threads can only access monitor functions
 - Variables are private to the monitor
- Only one process at a time can execute code inside the monitor.

Monitors

- Pthreads does not offer a monitor primitive 😊
- ... but possible to implement monitor semantics using mutex and condition variables ©
- We won't get into this in this course. Investigate if you're curious! ©

Synchronization

How are locks, semaphores, cond var, etc implemented?

Software

Monitors Locks (mutex)

Condition Variables

Hardware

Loads Stores Test&Set Disable Interrupts

Reminder of Assumptions:

- Multitasking OS
 - "Tasks" can be threads or processes

- Single-processor system
 - Only one task runs at any time
- Not assuming OS helps with synchronization
 - Of course, all the modern OSes do
 - But if you need to know how to implement... its because you don't have one.

Lock implementation motivating example "Too much milk"

- Alice and Bob are roommates
- They want to coordinate grocery shopping
 - Need to be careful to not buy too much of perishable items, like milk.



Schedule that leads to too much milk

Time	Alice	Bob
3:00	Look in Fridge. Out of milk.	
3:05	Leave for store.	
3:10	Arrive at store.	Look in Fridge. Out of milk.
3:15	Buy milk.	Leave for store.
3:20	Arrive home, put milk away.	Arrive at store.
3:25		Buy milk.
3:30		Arrive home, put milk away.

Problem specifications

Safety

Never more than one person buys

Liveness

Someone buys if needed

Lock implementation: first attempt

Restrict ourselves to use only atomic load and store operations as building blocks.

Idea: Use a note to avoid buying too much milk:

- Leave a note on fridge before buying (kind of "lock")
- Remove note after buying (kind of "unlock")
- Don't buy if note (wait)

Synchronization

How are locks, semaphores, cond var, etc implemented?

Monitors Locks (mutex)

Condition Variables

Loads Stores Test&Set

Disable Interrupts

```
if (noMilk) {
 if (noNote) {
  leave Note;
  buy milk;
  remove note;
```



```
if (noMilk) {
  if (noNote) {
    leave Note;
    buy milk;
    remove note; }
}
```



```
Thread A

if (noMilk) {

if (noMilk) {

if (noNote) {
```

Aside: when I want to anthropomorphize threads/processes like this, thread A will be "Alice" and thread B will be "Bob."

```
Thread A
if (noMilk) {
 if (noNote) {
  leave Note;
  buy milk;
  remove note;
```

Thread B

if (noMilk) {
 if (noNote) {

```
Thread A
                                                     Thread B
if (noMilk) {
                                                     if (noMilk) {
                                                      if (noNote) {
 if (noNote) {
  leave Note;
  buy milk;
  remove note;
                                                       leave Note;
                                                       buy milk;
  Buy milk twice 🕾
                                                       remove note; }
  Remember: scheduler can create any interleaving
  We must assume a malicious scheduler
```

First attempt result

- Still too much milk but only occasionally!
 - This is worse than a consistent error, because it is harder to catch.
- Thread can get context switched after checking milk (and note)

but before buying milk!

How about labeled notes?

```
Thread A

leave note A;

if (noNote B) {

if (noMilk) {

buy milk;

}

}

remove note A;

Thread B

leave note B;

if (noNote A) {

if (noMilk) {

buy milk;

}

remove note A;
```

Problem solved?

How about labeled notes?

```
Thread A

leave note A;

if (noNote B) {

if (noMilk) {

buy milk;

}

remove note A;

Thread B

leave note B;

if (noNote A) {

if (noMilk) {

buy milk;

}

remove note A;

remove note B;
```

Not quite...

How about labeled notes?

```
Thread A

leave note A;

if (noNote B) {

if (noMilk) {

buy milk;

}

}

remove note A;

Thread B

leave note B;

if (noNote A) {

if (noMilk) {

buy milk;

}

remove note A;
```

Not quite...

How about labeled notes?

```
Thread A
leave note A;
if (noNote B) {
  if (noMilk) {
    buy milk;
  }
}
remove note A;
```

```
Thread B

leave note B;

if (noNote A) {

if (noMilk) {

buy milk;

}
```

Not quite...

remove note B;

How about labeled notes?

```
Thread A
leave note A;
if (noNote B) {
  if (noMilk) {
  buy milk;
  }
}
Proc switch

Thread A
leave note A;
```

Thread B leave note B; if (noNote A) { if (noMilk) { buy milk; } } remove note B;

Not quite...

How about labeled notes?

```
Thread A

leave note A;

if (noNote B) {

if (noMilk) {

buy milk;

}

Proc switch

Thread B

leave note B;

if (noNote A) {

if (noMilk) {

buy milk;

}

Proc switch

remove note A;
```

How about labeled notes?

```
Thread A
leave note A;
if (noNote B) {
  if (noMilk) {
    buy milk;
  }
}
remove note A;
```

```
Thread B
leave note B;
if (noNote A) {
  if (noMilk) {
    buy milk;
  }
}
remove note B;
```

Not quite...

Nobody buys milk

How about labeled notes? (similar to Peterson, 1981)

```
Thread A

leave note A;

while (note B)

do nothing;

if (noMilk)

buy milk;

buy milk;

remove note A;

This works!

B has priority to buy

buy milk;

buy milk;

remove note A;

remove note B;
```

```
Thread A

leave note A;

while (note B)

do nothing;

if (noMilk)

buy milk;

remove note A;

Thread B

leave note B;

if (noNote A) {


if (noMilk)

buy milk;

remove note A;
```


```
Thread A
                                           Thread B
                      Happened before
leave note A;
                                           leave note B;
while (note B)
                                           if (noNote A) {
 do nothing;
                                            if (noMilk)
                                             buy milk;
                                           remove note B;
if (noMilk)
 buy milk;
remove note A;
```

```
Thread A
                                           Thread B
                       Happened before
leave note A;
                                           leave note B;
while (note B)
                                           if (noNote A) {
 do nothing;
                                            if (noMilk)
                                              buy milk;
           Wait for note B
           to be removed
                                           remove note B;
if (noMilk)
 buy milk;
remove note A;
```



```
Thread A
                                           Thread B
                                           leave note B;
                      Happened before
                                           if (noNote A) {
leave note A;
                                            if (noMilk)
while (note B)
                                             buy milk;
 do nothing;
if (noMilk)
                                           remove note B;
 buy milk;
remove note A;
```

```
Thread A
                                           Thread B
                                           leave note B;
                      Happened before
                                           if (noNote A) {
leave note A;
                                            if (noMilk)
while (note B)
                                             buy milk;
 do nothing;
if (noMilk)
                                           remove note B;
 buy milk;
remove note A;
```



Prove Correctness?

- By hand, surprisingly hard and often requires insight
- Mechanical tool exists: "Linear Temporal Logic"
- I can show an LTL specification + proof of solution 3 in OH if interested
- Even with LTL, still surprisingly tricky!
- If this kind of automated proof is interesting, try take 525
 - (Hopefully, it's taught again soon ☺)

Attempt 3 discussion

Solution 3 works, but it's really unsatisfactory.

- Complex, even for this simple example.
 - Hard to convince yourself that this really works.
- What we have guarantees that A or B can enter critical section
 - But we usually want to know that they both can, eventually
 - (In this case, we just know that they are trying to do the same thing)
- A's code is different from B's –what if lots of threads?
 - Code would have to be slightly different for each thread.
- While A is waiting, it is consuming CPU time.
 - This is called "busy-waiting".

There must be a better way!

- Version of Solution 3 where both threads have same code exists
 - See Peterson's Algorithm (1981)
- Have higher-level hardware primitives than atomic load & store
 - Compare-and-swap, test&set, LL/SC
- Build higher-level abstractions on this hardware support
- Or: implement abstractions at OS level

Fun Fact: It Gets Worse

- Modern multicore processors execute instructions out of order
- Normally not possible to notice
 - Hardware is carefully designed so that single thread can't tell
- But multiple threads can observe re-ordered memory accesses
- Re-ordering note bookkeeping breaks Solution 3
- With only atomic loads/stores (and nothing "stronger"), mutual exclusion on modern processors would be impossible.

Synchronization

How are locks, semaphores, cond var, etc implemented?

Software

Monitors Locks (mutex)

Condition Variables

Hardware

Loads Stores Test&Set

Disable Interrupts

Disabling interrupts

- Idea: lock implementation code executed in kernel mode.
 - No need for "spinlock" when we have a scheduler!
- Key idea: maintain a lock variable and impose mutual exclusion only during operations on that variable
- Thread that can't take a lock goes to sleep
- Danger! What if preemption timer fires during lock implementation?
- (Again: this idea is for single-processor systems.)

Disabling interrupts

```
int value = FREE;
Lock() {
 disable interrupts;
 if (value == BUSY) {
  put thread on wait queue;
  Go to sleep();
  // Enable interrupts?
 else {
  value = BUSY;
 enable interrupts;
```

```
Unlock() {
  disable interrupts;
  if (anyone on wait queue) {
    take thread off wait queue;
    place on ready queue;
  }
  else {
    value = FREE;
  }
  enable interrupts;
}
```

Disabling interrupts discussion

Why do we need to disable interrupts?

- Avoid preemption between checking and setting lock value
- Otherwise, two threads could think that they both have lock

```
Lock() {
    disable interrupts;
    if (value == BUSY) {
        put thread on wait queue;
        Go to sleep();
        // Enable interrupts?
    }
    else {
        value = BUSY;
    }
    enable interrupts;
}
```

Critical section is short in kernel mode

```
Lock() {
    disable interrupts;
    if (value == BUSY) {
        put thread on wait queue;
        Go to sleep();
        // Enable interrupts?
    }
    else {
        value = BUSY;
    }
    enable interrupts;
}
```

Enable interrupts here?

⊗ Release can check the queue and not wake up thread

```
Lock() {
  disable interrupts;
  if (value == BUSY) {
    put thread on wait queue;
    Go to sleep();
    // Enable interrupts?
  }
  else {
    value = BUSY;
  }
  enable interrupts;
}
```

Enable interrupts here?

- Release puts the thread on the ready queue, but the thread still thinks it needs to go to sleep
- Misses wakeup, but still holds lock (deadlock!) ☺☺

```
Lock() {
disable interrupts;
if (value == BUSY) {
 put thread on wait queue;
                                                    Want to enable interrupts after sleep()
 Go to sleep();
                                                      But how?
  // Enable interrupts?
else {
 value = BUSY;
enable interrupts;
```


```
Lock() {
  disable interrupts;
  if (value == BUSY) {
    put thread on wait queue;
    Go to sleep();
    // Enable interrupts?
  }
  else {
    value = BUSY;
  }
  enable interrupts;
}
```

Want to enable interrupts after sleep()

But how? In scheduler.

In scheduler, since interrupts are disabled when you call sleep():

- Responsibility of the next thread to re-enable interrupts
- When the sleeping thread wakes up, returns to lock() and re-enables interrupts





```
waiters
                                                         READY
                    Value: 0
                                          owner
  Running
                                                                 Ready
                       INIT
                          int value = 0;
                                                               Thread B
Thread A
                       Lock() {
                         disable interrupts;
lock.Lock();
                                                             lock.Lock();
                         if (value == 1) {
                           put thread on wait-queue;
                           go to sleep() //??
critical section;
                                                               critical section;
                         } else {
                           value = 1;
lock.Unlock();
                                                             lock.Unlock();
                         enable interrupts;
                       Unlock() {
                         disable interrupts;
                         if anyone on wait queue {
                           take thread off wait-queue
                           Place on ready queue;
                         } else {
                           value = 0;
                         enable interrupts;
```

```
READY
                                waiters
                    Value: 1
                                          owner
                                                                 Ready
  Running
                       INIT
Thread A
                          int value = 0;
                                                               Thread B
                       Lock() {
                         disable interrupts;
lock.Lock();
                                                             lock.Lock();
                         if (value == 1) {
                           put thread on wait-queue;
                           go to sleep() //??
critical section:
                                                               critical section;
                         } else {
                           value = 1;
lock.Unlock();
                                                             lock.Unlock();
                         enable interrupts;
                       Unlock() {
                         disable interrupts;
                         if anyone on wait queue {
                           take thread off wait-queue
                           Place on ready queue;
                         } else {
                           value = 0;
                         enable interrupts;
```

```
waiters
                                                         READY
                    Value: 1
                                          owner
  Readying
                                                                 Reading
                       INIT
Thread A
                          int value = 0;
                                                               Thread B
                       Lock() {
                         disable interrupts
lock.Lock();
                                                             lock.Lock();
                         if (value = 1)
                         __put thread on wait-queue;
critical section:
                           go to sleep() //??
                                                              critical section;
                         } else {
                           value = 1;
lock.Unlock();
                                                             lock.Unlock();
                         enable interrupts;
                       Unlock() {
                         disable interrupts;
                         if anyone on wait queue {
                           take thread off wait-queue
                           Place on ready queue;
                         } else {
                           value = 0;
                         enable interrupts;
```

```
waiters
                                                          READY
                    Value: 1
                                           owner
  Readying
                                                                  Ryantimg
                       INIT
Thread A
                           int value = 0;
                                                                Thread B
                       Lock() {
                         disable interrupt
lock.Lock();
                                                             \forall lock.Lock();
                         if (value===1)
                         __put thread on wait-queue;
critical section:
                           go_to_sleep()-7/??
                                                               critical section;
                         } else {
                           value = 1;
lock.Unlock();
                                                              lock.Unlock();
                         enable interrupts;
                       Unlock() {
                         disable interrupts;
                         if anyone on wait queue {
                           take thread off wait-queue
                           Place on ready queue;
                         } else {
                           value = 0;
                         enable interrupts;
```





Further Optional Reading

Operating Systems: Three Easy Pieces by R. & A. Arpaci-Dusseau

Chapters 25 – 31 (inclusive) https://pages.cs.wisc.edu/~remzi/OSTEP/

Reading on concurrency: Herlihy & Shavit: The Art of Multiprocessor Programming, 2nd edition.

Credits:

Some slides adapted from the OS courses of Profs. Remzi and Andrea Arpaci-Dusseau (University of Wisconsin-Madison), Prof. Willy Zwaenepoel (University of Sydney), and Prof. Maurice Herlihy (Brown University), Prof. Natacha Crooks (UC Berkeley).

