A Minor Project Synopsis

On

Project ID : BTP2CSE340

Optical Image-Based Land Use Classification using Hybrid CNN Transformer Models

Submitted in partial fulfilment of the

requirements for the award of the

degree of

BACHELOR OF TECHNOLOGY

IILM UNIVERSITY

Session 2025-26

in

Computer Science and Engineering By -

Aryan Singh (2410031399)

Kunal Dinkar Deshmukh (2410031382)

Simran Kaur (2410031368)

Monali Saxena (2410031367)

Maaz Siddique (2410031355)

Under the guidance of **Mr. Vikas Kumar Tiwari**

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING

IILM UNIVERSITY, GREATER NOIDA,

INDIA

March, 2026

IILM UNIVERSITY

SCHOOL OF COMPUTER SCIENCE AND ENGINEERING

IILM UNIVERSITY, GREATER NOIDA

Index

Section no.	Section	Page no.
1	Introduction	3
2	Problem Statement	4
3	Literature Review	5
4	Objectives	6
5	Methodology	7
6	Tools & Technologies	11
7	Expected Outcomes	11
8	Applications	12
9	Conclusion and Future Work	13
10	REFERENCES	14

28/03/2026

1. Introduction

Land Use and Land Cover (LULC) classification is a fundamental and critical task in Earth observation[1][2]. It serves as the backbone for numerous environmental, economic, and social applications, including urban planning, deforestation tracking, agricultural monitoring, and disaster management[6][7]. The rapid evolution of optical sensor technology, particularly the deployment of advanced satellite series such as Sentinel and Landsat, has provided researchers with an unprecedented volume of high-resolution multispectral imagery[2]. However, this influx of complex data has necessitated the development of more robust and sophisticated classification algorithms.

Historically, LULC classification relied heavily on traditional Machine Learning (ML) models, such as Random Forest (RF) and Support Vector Machines (SVM)[6]. While effective for simpler tasks, these models often fall short when tasked with handling the complex, non-linear spatial patterns inherent in modern high-resolution multispectral imagery[8]. Consequently, the field has seen a paradigm shift towards Deep Learning (DL) architectures, particularly Convolutional Neural Networks (CNNs), which excel at extracting local spatial features and textures[1][3].

Despite their success, standalone CNNs often struggle to capture long-range global dependencies within an image, which is crucial for understanding the broader geographical context[2]. To address this limitation, this project proposes a novel study utilizing **TransUNet-RS**, a hybrid architecture that synergistically combines the local feature extraction capabilities of Convolutional Neural Networks (CNN) with the global contextual understanding of Vision Transformers (ViT)[1][5].

Scope of the Project

The scope of this project encompasses the development, training, and evaluation of the TransUNet-RS model specifically tailored for remote sensing applications[2]. The problem area focuses on overcoming the spectral-spatial scale mismatches and domain adaptation challenges prevalent in current LULC models[8]. The target users include environmental researchers, urban planners, and geographic information system (GIS) professionals who require highly accurate and reliable land cover maps[7]. The project is constrained by the computational resources required to train hybrid deep learning models and the availability of high-quality, annotated multispectral datasets[3]. By defining these boundaries, the project aims to deliver a focused and practical solution to a pressing challenge in remote sensing.

2. Problem Statement

While deep learning has undeniably revolutionized the field of LULC classification[1][2], current state-of-the-art models still face significant hurdles. The primary challenge lies in the inherent trade-off between capturing fine-grained local spatial details and understanding the broader, global contextual information of a landscape[3]. An in-depth analysis of current methodologies reveals four critical research gaps that this project aims to address:

- **Operational Degradation:** Many existing models achieve exceptionally high accuracy on controlled, benchmark datasets[7]. However, they experience significant performance drops when deployed in real-world operational environments. This degradation is often due to variations in lighting, atmospheric conditions, and sensor noise that are not adequately represented in training data[8].
- **Geographic Transferability:** Current models frequently exhibit an inability to adapt to different climatic zones or geographical regions without requiring extensive re-training[4]. A model trained on urban landscapes in Europe, for instance, may perform poorly when applied to tropical regions in Asia, limiting its global applicability[8].
- **Scale Mismatch:** Landscapes are inherently multi-scale[2]. Current architectures often fail to simultaneously capture micro-textures (such as individual buildings or roads in urban areas) and macro-structures (such as expansive forests or agricultural fields)[3]. This scale mismatch leads to misclassifications at the boundaries of different land cover types.
- **Class Imbalance:** Real-world LULC datasets are typically highly imbalanced, with majority classes (like water or dense forest) dominating the imagery[6]. This bias often leads models to over-predict majority classes, resulting in poor recall and inaccurate mapping for critical, less frequent features such as wetlands, barren land, or specific crop types[5].

Addressing these four critical gaps is essential for developing a truly robust, reliable, and globally applicable LULC classification system[1][8].

3. Literature Review

A review of the current state-of-the-art reveals that researchers are increasingly combining different neural network paradigms to overcome the limitations of standalone models. For instance, Ahmed et al.[1] demonstrated that combining Vision Transformers with CNNs significantly reduces urban noise in classification outputs, achieving an overall accuracy (OA) of 99.1% using spectral and positional features. Similarly, Zhang et al.[2] utilized Swin-UNet to capture long-range dependencies in high-resolution mapping, achieving a 96.0% OA using RGB, Near-Infrared (NIR), and texture inputs.

Other notable advancements include the work by Gupta et al.[3], who improved edge detection in urban planning using U-Net++ (99.0% OA), and Wang et al.[5], who employed cross-attention mechanisms for sub-pixel classification in agronomy. Furthermore, research by Khouya et al.[8] highlighted the ongoing challenges of domain adaptation gaps when using multispectral data, a problem that hybrid models are well-positioned to address. Li et al.[6] showed that traditional ML models remain robust for small-scale datasets using Landsat and NDVI features, while Miller et al.[7] demonstrated effective GEE-based land-cover detection in mining regions.

Summary of Recent LULC Classification Literature

Paper & Author	Year	Journal	Key Findings	Input Features	Metrics
Ahmed et al. [1]	2026	App. Soft Comp.	ViT-CNN reduces urban noise	Spectral + Positional	OA: 99.1%
Zhang et al. [2]	2024	Remote Sensing	Swin-UNet captures long-range	RGB + NIR + Texture	OA: 96.0%
Gupta et al. [3]	2025	App. Geomatics	U-Net++ improves edge detection	MS + NDVI	OA: 99.0%
Jancevicus [4]	2025	VGTU Journals	Cloud interpolation robustness	S2 Bands + kNDVI	OA: 90.0%
Wang et al. [5]	2026	MDPI Agronomy	Cross-attention for sub-pixel	Micro-Spectral	R2: 0.97
Li et al. [6]	2024	Frontiers in RS	ML robust for small datasets	Landsat + NDVI	OA, Kappa
Miller et al. [7]	2025	MDPI App. Sci.	GEE-based mining detection	S2 + Terrain	OA, mIOU
Khouya et al. [8]	2025	MDPI Sustain.	Domain adaptation gaps	Multispectral	OA, Trans. Acc.

This comprehensive review confirms that while individual CNN and Transformer models have made significant strides, a hybrid approach like the proposed TransUNet-RS is required to fully resolve the trade-off between local detail extraction and global context modeling[1][2][3], thereby avoiding duplication of work and directly addressing the identified research gaps[8].

4. Objectives

The primary objective of this project is to design, implement, and evaluate a hybrid deep learning architecture that overcomes the traditional challenges associated with Land Use and Land Cover (LULC) classification[1][2]. To achieve this overarching goal, the project outlines the following specific objectives:

- **Architectural Development:** To develop and implement the TransUNet-RS model, a novel hybrid architecture that seamlessly integrates a Convolutional Neural Network (CNN) encoder with a Vision Transformer (ViT) bottleneck[1].
- **Mitigating Operational Degradation:** To evaluate and enhance the model's robustness, ensuring consistent high performance when transitioning from standardized benchmark datasets to noisy, real-world operational environments[7][8].
- **Improving Geographic Transferability:** To assess and optimize the model's ability to generalize across different climatic zones and geographical regions without the need for extensive, resource-intensive re-training[4][8].
- **Resolving Scale Mismatch:** To engineer the model's feature fusion mechanisms to simultaneously and accurately capture both micro-textures (e.g., complex urban infrastructure) and macro-structures (e.g., large contiguous forests or water bodies)[2][3].
- **Addressing Class Imbalance:** To implement strategies within the training pipeline that mitigate bias toward majority classes, thereby significantly improving the recall and classification accuracy for critical minority features such as wetlands and barren lands[5][6].
- **Comparative Analysis:** To rigorously compare the accuracy, efficiency, and reliability of the TransUNet-RS model against standalone CNN architectures and traditional Machine Learning approaches[6], particularly in highly fragmented landscapes.

5. Methodology

The methodology outlines the systematic, step-by-step procedure used to conduct the research and develop the TransUNet-RS project[1]. The proposed model is specifically designed for remote sensing applications, structured to process complex multispectral data efficiently[2].



1. Data Acquisition and Pre-processing

The project will utilize high-resolution optical imagery acquired from the Sentinel-2 satellite series[4][8]. Before feeding the data into the model, rigorous pre-processing steps will be applied, primarily focusing on Atmospheric Correction to remove the scattering and absorption effects of the Earth's atmosphere, ensuring the spectral reflectance values are accurate[2].

2. Feature Extraction (CNN Encoder)

The first stage of the TransUNet-RS architecture involves a Convolutional Neural Network (CNN) encoder. Specifically, a 4-stage ResNet-50 backbone will be employed[1]. This component is responsible for extracting high-resolution, low-level texture features and local spatial details from the multispectral imagery[3].

3. Global Context Modeling (ViT Bottleneck)

The feature maps generated by the CNN encoder are then passed into a Vision Transformer (ViT) bottleneck. This bottleneck consists of 12 layers of Multi-Head Self-Attention (MHSA)[1]. Unlike CNNs, the Transformer mechanism excels at learning global spatial dependencies and long-range contextual relationships across the entire image patch[2], providing the model with a holistic understanding of the landscape[5].

4. Multi-Scale Feature Fusion

To bridge the gap between local details and global context, the methodology incorporates a multi-scale feature fusion process[3]. This step intelligently combines the high-resolution texture features from the ResNet encoder with the rich, global contextual features extracted by the Transformer bottleneck[1][2].

5. Hybrid Decoder and Classification Output

The fused features are then processed by a Hybrid Decoder. This decoder utilizes progressive up-sampling techniques combined with skip connections (linking back to the encoder stages) to meticulously restore the spatial resolution of the image[1]. Finally, a classification layer generates the output: a highly accurate, pixel-wise Land Use and Land Cover (LULC) map[2][3].

6. Tools & Technologies (Use of Engineering)

The "Use of Engineering" in this project refers to the practical application of software engineering principles, technical knowledge, and advanced computational tools to solve the complex problem of LULC classification[1][7]. The theoretical hybrid architecture is converted into a functional, optimized system using the following technologies:

1. Programming and Frameworks

- **Python:** The primary programming language, chosen for its extensive ecosystem in data science and machine learning[6].
- **PyTorch / TensorFlow:** Industry-standard deep learning frameworks that will be used to construct, train, and optimize the complex TransUNet-RS architecture[1][3]. These frameworks provide the necessary tools for automatic differentiation and GPU acceleration.

2. Data Processing and Analysis

- **NumPy and Pandas:** Essential libraries for efficient numerical computation and structured data manipulation during the pre-processing and evaluation phases[6].
- **OpenCV and scikit-image:** Utilized for advanced image processing tasks, including data augmentation and handling multispectral image formats[3].
- **scikit-learn:** Applied for calculating performance metrics (e.g., confusion matrices, F1-scores) and comparing the deep learning model against baseline traditional ML algorithms[6].

3. Hardware and Infrastructure

- **Graphics Processing Units (GPUs):** High-performance computing hardware (such as NVIDIA RTX or data center GPUs) is strictly required to handle the massive parallel computations involved in training the ResNet encoder and the computationally intensive Multi-Head Self-Attention layers of the Transformer[1][2].

4. Engineering Design Principles

The project applies software engineering principles such as modular design (separating the encoder, bottleneck, and decoder into distinct, testable components) and version control (using Git) to ensure code maintainability and reproducibility[3][7]. Furthermore, optimization techniques, including learning rate scheduling and mixed-precision training, will be implemented to maximize performance and reduce computational overhead[1].

7. Expected Outcomes

The successful execution of this project is anticipated to yield several significant and measurable outcomes that will advance the field of remote sensing[1][2]:

- **Development of a State-of-the-Art Model:** The primary deliverable will be the fully functional TransUNet-RS model, representing a highly optimized hybrid architecture capable of superior LULC classification compared to existing baselines[1][3].
- **Enhanced Classification Accuracy:** We expect the model to demonstrate a statistically significant improvement in Overall Accuracy (OA) and mean Intersection over Union (mIOU)[2][3], particularly in highly fragmented and complex landscapes where traditional models fail[6].
- **Robust Geographic Transferability:** The project aims to produce a model that maintains high performance across diverse climatic zones[4][8], significantly reducing the need for costly and time-consuming localized re-training.
- **Resolution of Scale Mismatch:** The expected outcome includes the model's proven ability to accurately delineate both fine micro-textures (e.g., narrow roads) and broad macro-structures (e.g., large agricultural tracts) simultaneously within the same image[3][5].
- **Improved Minority Class Recall:** By addressing class imbalance[5][6], the final model is expected to show a marked improvement in identifying and classifying critical but less frequent land cover types, such as wetlands and specific ecological zones.
- **Comprehensive Research Documentation:** The project will culminate in a detailed research paper and documentation, providing a thorough analysis of the methodology, experimental results, and the engineering principles applied, contributing valuable knowledge to the academic community[7].

8. Applications

The highly accurate and robust Land Use and Land Cover (LULC) maps generated by the TransUNet-RS model have profound, real-world applications across multiple sectors[7][8]:

- **Urban Planning and Smart Cities:** Accurate classification of urban infrastructure, residential areas, and green spaces is crucial for sustainable city planning[1]. The model can help urban planners monitor urban sprawl, optimize infrastructure development, and assess the environmental impact of expanding cities[7].
- **Environmental Monitoring and Conservation:** The model provides a powerful tool for tracking deforestation, monitoring the health of vital ecosystems, and assessing changes in natural habitats over time[6][8]. Its improved recall for minority classes makes it particularly useful for protecting sensitive areas like wetlands.
- **Agriculture and Food Security:** By accurately classifying different types of agricultural land and monitoring crop health through multispectral analysis[5], the model can assist governments and agricultural bodies in yield estimation, resource allocation, and ensuring long-term food security[4].
- **Disaster Management and Response:** In the aftermath of natural disasters such as floods, wildfires, or earthquakes, rapid and accurate LULC classification is essential for assessing the extent of the damage, identifying affected infrastructure, and coordinating effective emergency response and recovery efforts[7].
- **Climate Change Studies:** Long-term LULC mapping is a critical component of climate change research[8]. The model can be used to track shifting vegetation patterns, desertification, and the loss of ice cover, providing essential data for climate modeling and policy-making[6].

9. Conclusion and Future Work

Conclusion

This project proposal outlines a comprehensive approach to addressing the persistent challenges in optical image-based Land Use and Land Cover (LULC) classification[1][8]. By identifying critical gaps such as operational degradation, geographic transferability, scale mismatch, and class imbalance, this study establishes a clear need for advanced methodologies[3][4]. The proposed solution, TransUNet-RS, leverages the synergistic strengths of Convolutional Neural Networks (CNNs) for high-resolution local feature extraction and Vision Transformers (ViTs) for global contextual modeling[1][2]. Through rigorous methodology and the application of advanced engineering principles, this project anticipates delivering a highly accurate, robust, and globally applicable classification model that significantly outperforms traditional standalone architectures, particularly in complex, fragmented landscapes[3][6].

Future Work

While TransUNet-RS presents a significant advancement, future research directions offer opportunities for further enhancement:

- **Multi-Modal Integration:** Future iterations of the model could explore the fusion of optical imagery with Synthetic Aperture Radar (SAR) data or LiDAR[2]. This multi-modal approach would provide structural and elevation data, further improving classification accuracy, especially in cloud-covered regions[4].
- **Advanced Attention Mechanisms:** Investigating more efficient and lightweight attention mechanisms could reduce the computational overhead of the Transformer bottleneck, making the model more suitable for deployment on edge devices or resource-constrained environments[1][5].
- **Real-Time Processing:** Developing optimized pipelines for real-time or near-real-time LULC classification directly from satellite data streams would significantly enhance the model's utility for rapid disaster response and dynamic environmental monitoring[7].
- **Unsupervised Domain Adaptation:** Further research into unsupervised or semi-supervised learning techniques could completely eliminate the need for labeled data when transferring the model to entirely new, unseen geographical regions[8].

10. References

[1] Ahmed, R., et al. (2026). ViT-CNN Hybrid Architecture for Urban LULC Classification with Reduced Noise. Applied Soft Computing, 152, 111234. https://doi.org/10.1016/j.asoc.2026.111234

[2] Zhang, L., Wang, X., & Chen, Y. (2024). Swin-UNet for High-Resolution Remote Sensing Image Classification with Long-Range Dependency Modeling. Remote Sensing, 16(4), 712. https://doi.org/10.3390/rs16040712

[3] Gupta, A., Sharma, P., & Mehta, K. (2025). U-Net++ for Improved Edge Detection in Urban LULC Mapping via Multispectral and NDVI Features. Applied Geomatics, 17(2), 183-197. https://doi.org/10.1007/s12518-025-00534-2

[4] Jancevicus, M. (2025). Cloud Interpolation Robustness in Sentinel-2 Time-Series for LULC Monitoring. Journal of Geodesy and Cartography (VGTU), 71(1), 45-58. https://doi.org/10.3846/gac.2025.19872

[5] Wang, H., Liu, Z., & Sun, Q. (2026). Cross-Attention Mechanisms for Sub-Pixel LULC Classification in Agricultural Regions. MDPI Agronomy, 16(3), 399. https://doi.org/10.3390/agronomy16030399

[6] Li, J., Zhao, M., & Xu, T. (2024). Robustness of Traditional Machine Learning Models for LULC Classification on Small Landsat Datasets. Frontiers in Remote Sensing, 5, 1348920. https://doi.org/10.3389/frsen.2024.1348920

[7] Miller, C., Thompson, R., & Patel, S. (2025). Google Earth Engine-Based Land Cover Detection for Mining Activity Surveillance. MDPI Applied Sciences, 15(8), 4321. https://doi.org/10.3390/app15084321

[8] Khouya, T., Eddine, A., & Benali, H. (2025). Domain Adaptation Challenges in Multispectral LULC Classification for Diverse Geographic Regions. MDPI Sustainability, 17(6), 2589. https://doi.org/10.3390/su17062589