 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

Aim :- Implement CloudFront for caching and application security.

Lab overview and objectives

In this lab, you will create an Amazon CloudFront distribution to reduce network latency for café website users and deliver the website securely over HTTPS. You will also secure access to the website and REST API endpoints using AWS WAF, which is a service that provides a web application firewall. Finally, you will configure a CloudFront function on the website and adjust the cached file expiration time on the website content.

After completing this lab, you should be able to:

- Create a CloudFront distribution to cache Amazon Simple Storage Service (Amazon S3) objects
- Configure a website hosted on Amazon S3 to be available through HTTPS using CloudFront
- Secure access to the CloudFront distribution based on the network origin of the request
- Secure a REST API endpoint based on the network origin of the request using AWS WAF
- Configure a CloudFront function to affect website behavior from the edge
- Adjust max-age caching settings on a CloudFront distribution

AWS service restrictions

In this lab environment, access to AWS services and service actions might be restricted to the ones that are needed to complete the lab instructions. You might encounter errors if you attempt to access other services or perform actions beyond the ones that are described in this lab.

Scenario

Sofia is pleased with how the café website development project is coming along. She has developed the core serverless application that displays menu items on the website. She also integrated the coffee suppliers web application into the main site and is using Amazon ElastiCache features for the suppliers part of the site.


However, she knows that some essential features are still missing. One feature is that the website still runs on HTTP and does not yet support HTTPS. Sofia also wants to ensure that the website will load quickly for users globally. She knows that AWS has many Regions and Availability Zones, but they also have edge locations, which are even closer to users around the globe. She decides to host the café website on a proper content delivery network (CDN), and she has opted to use the CloudFront service.

In this lab, you will again play the role of Sofia to continue to develop the café's web application.


Task 1: Preparing the lab

Connect to the VS Code IDE.


1. At the top of these instructions, choose Details followed by **AWS: Show**
2. Copy values from the table **similar** to the following and paste it into an editor of your choice for use later.
 - a. **LabIDEURL**

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

b. LabIDEPassword





3. In a new browser tab, paste the value for **LabIDEURL** to open the VS Code IDE.
4. On the prompt window **Welcome to code-server**, enter the value for **LabIDEPassword** you copied to the editor earlier, choose **Submit** to open the VS Code IDE.




5. Download and extract the files that you need for this lab.
 - In the VS Code bash terminal (located at the bottom of the IDE), run the following commands:


```
wget https://aws-tc-largeobjects.s3.us-west-2.amazonaws.com/CUR-TF-200-ACCDEV-2-91558/09-lab-cloudfront/code.zip -P /home/ec2-user/environment
```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



6. You should see that the **code.zip** file was downloaded to the VS Code IDE and is now in the left navigation pane.
- Extract the file by running the following command:
unzip code.zip



 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

7. Run a script that upgrades the version of the AWS CLI installed on the VS Code IDE.
 - To set permissions on the script and then run it, run the following commands in the Bash terminal:


```
chmod +x ./resources/setup.sh && ./resources/setup.sh
```

When prompted for an IP address, enter the IPv4 address that the internet uses to contact your computer. You can find your IPv4 address at <https://whatismyipaddress.com>.


```
[ec2-user@ip-10-0-1-150 environment]$ chmod +x resources/setup.sh && resources/setup.sh
Please enter a valid IP address:
152.58.63.192
IP address:152.58.63.192
upload: resources/website/all_products_on_offer.json to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/all_products_on_offer.json
upload: resources/website/callback.html to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/callback.html
upload: resources/website/all_products.json to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/all_products.json
upload: resources/website/beans.json to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/beans.json
upload: resources/website/images/beans/excelsa.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/beans/excelsa.png
upload: resources/website/config.js to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/config.js
upload: resources/website/images/items/blueberry_bagel.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/blueberry_bagel.png
upload: resources/website/images/items/apple_pie.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/apple_pie.jpeg
upload: resources/website/images/items/blueberry_jelly_doughnut.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/blueberry_jelly_doughnut.jpeg
upload: resources/website/images/beans/robusta.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/beans/robusta.png
upload: resources/website/images/items/boston_cream_doughnut.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/boston_cream_doughnut.jpeg
upload: resources/website/images/expanded.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/expanded.png
upload: resources/website/images/beans/liberica.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/beans/liberica.png
upload: resources/website/images/items/apple_pie_slice.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/apple_pie_slice.png
upload: resources/website/images/items/apple_pie.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/apple_pie.png
upload: resources/website/images/beans/arabica.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/beans/arabica.png
upload: resources/website/images/items/boston_cream_doughnut.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/boston_cream_doughnut.png
upload: resources/website/favicon.ico to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/favicon.ico
upload: resources/website/images/items/apple_pie_slice.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/apple_pie_slice.jpeg
upload: resources/website/images/items/cherry_pie.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/cherry_pie.png
upload: resources/website/images/items/blueberry_bagel.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/blueberry_bagel.jpeg
upload: resources/website/images/items/blueberry_jelly_doughnut.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/blueberry_jelly_doughnut.png
upload: resources/website/images/items/cherry_pie_slice.png to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/cherry_pie_slice.png
upload: resources/website/images/items/cherry_pie.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/cherry_pie.jpeg
upload: resources/website/images/items/cherry_pie_slice.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/cherry_pie_slice.jpeg
upload: resources/website/images/items/chocolate_chip_cupcake.jpeg to s3://c168617a434024811142234t1w184333714729-s3bucket-1wvveyyvhv5l/images/items/chocolate_chip_cupcake.jpeg
Layout: US
```

8. Verify the AWS CLI version and also verify that the SDK for Python is installed.
 - Confirm that the AWS CLI is now at version 2 by running the **aws --version** command.
 - In the VS Code Bash terminal (at the bottom of the IDE), run the following command: **pip3 show boto3**

```
[ec2-user@ip-10-0-1-234 environment]$ aws --version
aws-cli/2.28.6 Python/3.13.4 Linux/6.1.147-172.266.amzn2023.x86_64 exe/x86_64.amzn.2023
[ec2-user@ip-10-0-1-234 environment]$ pip3 show boto3
Name: boto3
Version: 1.40.6
Summary: The AWS SDK for Python
Home-page: https://github.com/boto/boto3
Author: Amazon Web Services
Author-email:
License: Apache License 2.0
Location: /usr/local/lib/python3.11/site-packages
Requires: botocore, jmespath, s3transfer
Required-by:
[ec2-user@ip-10-0-1-234 environment]$
```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030


9. Note the metadata settings on the objects stored in the S3 bucket, and then verify that you can access the café website.
 - Navigate to the Amazon S3 console.
 - Choose the link for the bucket that has *-s3bucket* in the name.
 - Choose the **index.html** link.
 - Scroll down to the **Metadata** section.
 - Two key-value pairs are listed. The **Cache-Control** key-value pair has a value of **max-age=0**. This was set when you ran *setup.sh* in an earlier step. Line 21 of that script ran the command `aws s3 cp ./resources/website s3://$bucket/ --recursive --cache-control "max-age=0"` to set this metadata value on every file that it uploaded to the bucket. You'll learn about the significance of this setting later in the lab.
 - At the top of the page, open the **Object URL** in a new browser tab.
 - The café website displays. If it doesn't, see the following troubleshooting tip.




Task 2: Configuring a distribution for static website content

In this task, you will configure the café website, which is hosted on Amazon S3, to be available through a CloudFront distribution. With the distribution, you can enable HTTPS access to the website.


10. Begin to configure a CloudFront distribution for the café website hosted on Amazon S3.
 - Navigate to the CloudFront console.
 - Choose **Create a CloudFront distribution**.


 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



11. Configure the **Origin** settings for the distribution.

- **Note:** If a setting is not specified in the following steps, use the default.
- **Origin domain:** Search for and choose the S3 bucket that has *-s3bucket* in the name. This bucket contains the website code.
- In the **Origin access** settings.
- Choose **Legacy access identities**.
- Choose **Create new OAI**.
- **Name:** Enter access-identity-cafe-website
- Choose **Create**.
- **Bucket policy:** Choose **Yes, update the bucket policy**.
- In the **Add custom header** section, choose **Add header** and configure:
- **Header name:** Enter cf
- **Value:** Enter 1
- **Note:** The custom header is not an important requirement for this lab, but it will be useful in a later lab.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



12. Configure the **Default cache behavior** settings.

- Path pattern:** Keep the **Default (*)** setting. This means that all requests will go to the origin.
- Viewer protocol policy:** Choose **Redirect HTTP to HTTPS**. This will help users find the website, even if they load the HTTP URL.
- Allowed HTTP methods:** Keep the default **GET, HEAD** setting.
- Restrict viewer access:** Keep the default **No** setting. This will be a public website.

13. Configure the **Cache key and origin requests** settings.

- Choose **Legacy cache settings**.
- Keep the settings for **Headers, Query strings, and Cookies** as **None**.
- Object caching:** Choose **Use origin cache headers**.

Note: Recall the metadata key-value pair with key **Cache-Control** and value **max-age=0**. This metadata is set on all of the objects stored in the origin S3 bucket. By choosing **Use origin cache headers** for this distribution, you ensure that this distribution will inherit this setting applied to all of the objects in the Amazon S3 origin.

- Under **Web Application Firewall (WAF)** choose **Do not enable security protections**.


14. Configure the **Settings** section of the distribution.

- Price class:** Keep the default **Use all edge locations** setting.
- Alternative domain name (CNAME):** Do not enter anything.

Note: You could specify a unique domain name here; however, this lab doesn't have one.


- Custom SSL certificate:** Choose **None** from dropdown.

Note: If you owned a domain and had a TLS or SSL certificate from a certificate authority, you would upload it here. For this lab, you will use the default CloudFront certificate (*.cloudfront.net), so you do not need to specify a custom certificate.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

- d. **Supported HTTP versions:** Select **HTTP/2**.
- e. **Default root object:** Enter index.html
- f. **IPv6:** Off

Note: This is the café website homepage hosted in the S3 bucket.



Edit settings

Settings

Anycast static IP list
 Deliver traffic from a small set of IP addresses.
 There are no eligible static IP lists available.
 There are no eligible static IP lists available.
 Create an Anycast static IP list

Price class
 Choose the price class associated with the maximum price that you want to pay.
☒ Use all edge locations (Best performance)
☐ Use only North America and Europe
☐ Use North America, Europe, Asia, Middle East, and Africa

Alternate domain name (CNAME) - optional
 Add the custom domain names that you use in URLs for the files served by this distribution.
 Add item
 To add a list of items, use the bulk editor.

Custom SSL certificate - optional
 Associate a certificate from AWS Certificate Manager. The certificate must be in the US East (N. Virginia) Region for use with CloudFront.
 Choose certificate
 Request certificate


Supported HTTP versions
 Add support for additional HTTP versions. HTTP/1.0 and HTTP/1.1 are supported by default.
☒ HTTP/2
☐ HTTP/3

Default root object - optional
 The object (file name) to return when a viewer requests the root URL (/) instead of a specific object.
 index.html

IPv6
☒ Off
☐ On

Description - optional

Cancel Save changes



Successfully updated distribution settings.

access-identity-cafe-website Standard View metrics

General Security Origins Behaviors Error pages Invalidations Tags Logging

Details

Name: access-identity-cafe-website

Distribution domain name: d5supgrra2fip.cloudfront.net

ARN: arn:aws:cloudfront:us-east-1:92200133030:distribution/E155RQOZBWVXYT

Last modified: Deploying

Settings Edit

Description: -

Price class: Use all edge locations (best performance)

Supported HTTP versions: HTTP/2, HTTP/3, HTTP/1.0

Alternate domain names: Add domain


Standard logging: Off

Cookie logging: Off

Default root object: index.html


Continuous deployment info

Create staging distribution

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

15. Update the bucket policy.

- In a new browser tab, navigate to the Amazon S3 console.
- Choose the link for the bucket that has *-s3bucket* in the name.
- Choose the **Permissions** tab.
- In the **Bucket policy** section, choose **Edit**.
- In the **Policy** code section, delete lines 4 through 17




Task 3: Securing network access to the distribution using AWS WAF


16. First, create an IP set for your IP address.

- In the AWS Management Console, search for **waf** and choose **WAF & Shield**.
- In the left navigation pane, choose **IP sets**.
- Choose **Create IP set** and configure:
 - IP set name:** Enter **office**
 - Description:** Enter **office IP**
 - Region:** Choose **Global (CloudFront)**.
 - IP addresses:** Enter **<ip-address>/32** where **<ip-address>** is your public IPv4 address, as identified by whatismyipaddress.com.

Note: Be sure to include the **/32** at the end of the IP address.

- Choose **Create IP set**.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030




The screenshot shows the AWS IAM console interface for creating an IP set. The 'IP set details' section includes the following fields:


- IP set name:** office
- Description - optional:** office IP
- Region:** Global (CloudFront)
- IP version:** IPv4 (selected), IPv6
- IP addresses:** 119.160.199.0/24

At the bottom of the form, there are 'Cancel' and 'Create IP set' buttons.

17. Begin to create a web ACL.


- In the left navigation pane, choose **Web ACLs**.
- Choose **Create web ACL**.
- In the **Web ACL details** section, configure:
 - Resource type:** Choose **CloudFront distributions**.
 - Name:** Enter `cafe-website-office-only-during-dev`
 - Description:** Enter `Allow access to the cafe website through CloudFront from the cafe office`
 - CloudWatch metric name:** Enter `cafe-website-office-only-during-dev`
- In the **Associated AWS resources** section, configure:
 - Choose **Add AWS resources**.
 - Select the CloudFront distribution that you created.
 - Choose **Add**.
 - Select the CloudFront distribution again, and then choose **Next**.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030




The screenshot shows the AWS IAM console 'Describe web ACL' page. The left sidebar contains a navigation menu with steps: Step 1: Describe web ACL and associate it to AWS resources, Step 2: Add rules and rule groups, Step 3: Set rule priority, Step 4: Configure metrics, and Step 5: Review and create web ACL. The main content area is titled 'Describe web ACL details' and includes sections for 'Resource type' (Global resources), 'Name' (cafe-website-office-only-during-day), 'Description' (optional), 'CloudWatch metric name' (cafe-website-office-only-during-day), 'Associated AWS resources' (optional), and 'Web request body inspection' (optional).


18. Add a rule to the web ACL configuration to allow requests from the *office* IP set.
 - a. In the **Rules** section, choose **Add rules, Add my own rules and rule groups**.
 - b. **Rule type:** Choose **IP set**.
 - c. **Name:** Enter **only_office_please**
 - d. **IP set:** Choose the *office* IP set that you just created.
 - e. **IP address to use as the originating address:** Keep the default **Source IP address** setting.
 - f. **Action:** Choose **Allow**.
 - g. Choose **Add rule**.



The screenshot shows the AWS IAM console 'Add my own rules and rule groups' page. The left sidebar contains a navigation menu with steps: Step 1: Describe web ACL and associate it to AWS resources, Step 2: Add my own rules and rule groups, Step 3: Set rule priority, Step 4: Configure metrics, and Step 5: Review and create web ACL. The main content area is titled 'Add my own rules and rule groups' and includes sections for 'Rule type' (IP set), 'Rule' (only_office_please), 'IP set' (office), 'IP address to use as the originating address' (Source IP address), and 'Action' (Allow).

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

19. Update the new web ACL rule to block any requests that don't match the rule.
 - a. In the **Rules** section, select the **only_office_please** rule.
 - b. In the **Default web ACL action** section, for **Default action**, choose **Block**.
 - c. Choose **Next**.



Add rules and rule groups

A rule defines attack patterns to look for in web requests and the action to take when a request matches the patterns. Rule groups are reusable collections of rules. You can use managed rule groups offered by AWS and AWS Marketplace sellers. You can also write your own rules and use your own rule groups.

Rules (1/1)	Capacity	Action
<input checked="" type="checkbox"/> only_office_please	1	Allow

Web ACL capacity units (WCUs) used by your web ACL

The WCUs used by the web ACL will be less than or equal to the sum of the capacities for all of the rules in the web ACL.

The total WCUs for a web ACL can't exceed 5000. Using over 1000 WCUs affects your costs. [AWS WAF Pricing](#)

1/2000 WCUs

Default web ACL action for requests that don't match any rules

Default action

☐ Allow

☒ Block

[Custom response - optional](#)

Token domain list - optional


Enables the use of tokens across multiple protected applications by entering the application domains here. Tokens are used by the Challenge and CAPTCHA rule actions, the application integration SAML, and the ATP and Bot Control managed rule groups. [Learn more](#)

[Add token domain](#)

You can add 10 token domains

[Cancel](#) [Previous](#) [Next](#)

20. Set the rule priority, configure metrics, and create the web ACL.
 - a. Choose the **only_office_please** rule.
 - b. Choose **Next**.
 - c. Keep all of the default metrics settings, and choose **Next** again.
 - d. Review the settings, and at the bottom of the page, choose **Create web ACL**.




Set rule priority

Rules (1/1)

If a request matches a rule, take the corresponding action. The rules are prioritized in order they appear.


Name	Capacity	Action
<input checked="" type="radio"/> only_office_please	1	Allow

[Cancel](#) [Previous](#) [Next](#)

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

21. Confirm that the web ACL configuration has been applied to the CloudFront distribution.

- Return to the CloudFront console.
- In the left navigation pane, choose **Distributions**.
- Note:** The **Last modified** column might display *Deploying* for the distribution. The deployment will complete within about 5 minutes; however, you can proceed to the next step without waiting.
- Choose the link for the distribution ID.
- In the **Security** section, notice that the distribution now has an **AWS WAF** value.




Task 4: Securing a REST API endpoint using AWS WAF


22. Create a *regional* AWS WAF IP set.

- Return to the WAF & Shield console.
- In the left navigation pane, choose **IP sets**.
- Choose **Create IP set** and configure:
 - IP set name:** Enter `office_regional`
 - Description:** Enter IP of the office for API Gateway
 - Region:** Choose **US East (N. Virginia)**.
 - IP addresses:** Enter `<ip-address>/32` where `<ip-address>` is your public IPv4 address, as identified by `whatismyipaddress.com`.

Note: Be sure to include the `/32` at the end of the IP address.


- Choose **Create IP set**.


 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



23. Begin to create a *regional* web ACL.


- a. In the left navigation pane, choose **Web ACLs**.
- b. Choose **Create web ACL**.
- c. In the **Web ACL details** section, configure:
 - i. **Resource type**: Choose **Regional resources**.
 - ii. **Region**: Choose **US East (N. Virginia)**.
 - iii. **Name**: Enter `website-api-gw-office-only-during-dev`
 - iv. **Description**: Enter `To allow us to access the API GW calls used by the website from the office`
 - v. **CloudWatch metric name**: Enter `website-api-gw-office-only-during-dev`
- d. In the **Associated AWS resources** section, configure:
 - i. Choose **Add AWS resources**.
 - ii. For Resource type, select **Amazon API Gateway**.
 - iii. Select the **ProductsApi - prod** API Gateway resource.
 - iv. Choose **Add**.
 - v. Select the **ProductsApi - prod** resource again, and then choose **Next**.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030




The screenshot shows the AWS WAF console 'Describe web ACL' page. The left sidebar contains a navigation menu with steps: Step 1: Describe web ACL and associate it to AWS resources, Step 2: Add rules and rule groups, Step 3: Set rule priority, Step 4: Configure metrics, and Step 5: Review and create web ACL. The main content area is titled 'Describe web ACL and associate it to AWS resources'. It includes sections for 'Web ACL details' (Resource type, Region, Name, Description, CloudWatch metric name), 'Associated AWS resources - optional', and 'Web request body inspection - optional'. The 'Web ACL details' section shows 'Global resources' selected, 'US East (N. Virginia)' as the region, and 'website-api-gw-office-only-during-dev' as the name and description. The 'Associated AWS resources' section shows a table with one resource: 'ProductsApi - prod' of type 'API Gateway' in 'US East (N. Virginia)'.

24. Add a rule to the web ACL configuration to allow requests from API Gateway.
 - a. In the **Rules** section, choose **Add rules, Add my own rules and rule groups**.
 - b. **Rule type:** Choose **IP set**.
 - c. **Name:** Enter **ip_for_apigw**
 - d. **IP set:** Choose the **office_regional** IP set that you just created.
 - e. **IP address to use as the originating address:** Keep the default **Source IP address** setting.
 - f. **Action:** Choose **Allow**.
 - g. Choose **Add rule**.




The screenshot shows the AWS WAF console 'Add my own rules and rule groups' page. The left sidebar contains a navigation menu with steps: Step 1: Describe web ACL and associate it to AWS resources, Step 2: Add my own rules and rule groups, Step 3: Set rule priority, Step 4: Configure metrics, and Step 5: Review and create web ACL. The main content area is titled 'Add my own rules and rule groups'. It includes sections for 'Rule type' (IP set, Rule builder, Rule group), 'Rule' (Name, IP set), and 'Action' (Allow, Block, Count, CAPTCHA, Challenge). The 'Rule type' section shows 'IP set' selected. The 'Rule' section shows 'ip_for_apigw' as the name and 'office_regional' as the IP set. The 'Action' section shows 'Allow' selected.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

25. Update the new web ACL rule to block any requests that don't match the rule.

- In the **Rules** section, select the **ip_for_apigw** rule.
- In the **Default web ACL action** section, for **Default action**, choose **Block**.
- Choose **Next**.



Step 2: Add rules and rule groups

A rule defines attack patterns to look for in web requests and the action to take when a request matches the patterns. Rule groups are reusable collections of rules. You can use managed rule groups offered by AWS and AWS Marketplace sellers. You can also write your own rules and use your own rule groups.

Name	Capacity	Action
ip_for_apigw	1	Allow

Web ACL capacity units (WCUs) used by your web ACL

The WCUs used by the web ACL will be less than or equal to the sum of the capacities for all of the rules in the web ACL.

The total WCUs for a web ACL can't exceed 5000. Using over 1500 WCUs affects your costs. [AWS WAF Pricing](#)

1/5000 WCUs

Default web ACL action for requests that don't match any rules

Default action

☒ Allow

☐ Block

[Custom request - optional](#)

Token domain list - optional

Enable the use of tokens across multiple protected applications by entering the application domains here. Tokens are used by the Challenge and CAPTCHA rule actions, the application integration SDKs, and the ATP and Bot Control managed rule groups. [Learn more](#)


[Add token domain](#)


You can add 10 more domains

Cancel Previous **Next**


26. Set the rule priority, configure metrics, and create the web ACL.


- Choose the **ip_for_apigw** rule.
- Choose **Next**.
- Keep all of the default metrics settings, and choose **Next** again.
- Review the settings, and at the bottom of the page, choose **Create web ACL**.

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



27. When the web ACL creation process is complete, check the resources associated with the ACL.
 - a. Choose the link for the *website-api-gw-office-only-during-dev* ACL, which you just created.
 - b. Choose the **Associated AWS resources** tab.
 - c. Confirm that the *ProductsApi - prod* resource is listed. If it isn't, add it:
 - i. Choose **Add AWS resources**.
 - ii. Choose the *ProductsApi - prod* resource.
 - iii. Choose **Add**.



 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

28. Test the new ACL from your computer.

- In a new browser tab, go to the API Gateway console.
- Choose the link for the **ProductsApi**.
- In the left navigation pane, choose **Stages**.
- In the **Stages** navigation pane, expand the **prod** stage.
- Under **/bean_products**, choose **GET**.
- Copy the **Invoke URL**, which has the format *https://execute-api.us-east-1.amazonaws.com/prod/bean_products*, and load the URL in a new browser tab.
- A JSON-formatted document with product information displays. This is the expected behavior.

```


Pretty-print ☒
[
  {
    "id": 1,
    "supplier_id": 1,
    "type": "Arabica",
    "product_name": "Best bean",
    "price": "18.00",
    "description": "Delicious, smooth coffee.",
    "quantity": 1000
  },
  {
    "id": 2,
    "supplier_id": 1,
    "type": "Robusta",
    "product_name": "Great bean",
    "price": "12.00",
    "description": "Full bodied, good to the last drop.",
    "quantity": 800
  },
  {
    "id": 3,
    "supplier_id": 2,
    "type": "Robusta",
    "product_name": "Top bean",
    "price": "10.00",
    "description": "Great all around bean.",
    "quantity": 500
  },
  {
    "id": 4,
    "supplier_id": 2,
    "type": "Liberica",
    "product_name": "Better bean",
    "price": "14.00",
    "description": "This bean stands above the rest.",
    "quantity": 600
  },
  {
    "id": 5,
    "supplier_id": 3,
    "type": "Excelsa",
    "product_name": "Premiere bean",
    "price": "18.00",
    "description": "The best bean in all the land",
    "quantity": 200
  },
  {
    "id": 6,
    "supplier_id": 4,
    "type": "Arabica",


```

Task 5: Configuring a CloudFront function on the website

29. Create a CloudFront function.


- Navigate to the CloudFront console.
- In the left navigation pane, choose **Functions**.
- Choose **Create function**.
- For **Name**, enter `random_image_header`
- Choose **Create function**.


 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030



30. Publish the CloudFront function, and associate it with the CloudFront distribution.

- Choose the **Publish** tab.
- Choose **Publish function**.
- A message at the top of the page indicates that the *random_image_header* function was successfully published.
- In the **Associated distributions** section, choose **Add association** and configure:
 - **Distribution:** Choose the distribution.
 - **Event type:** Choose **Viewer Response**.
 - **Cache behavior:** Select **Default (*)**.
 - Choose **Add association**.
- In the left navigation pane, choose **Distributions**.
- Notice that the distribution is being deployed again.



 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

Task 6: Adjusting the cache duration

31. Edit the Cache-Control header set on each object in the S3 bucket.

- Go to the VS Code IDE bash terminal and run the following command:

```

BUCKET_NAME=$(aws s3api list-buckets --query "Buckets[?contains(Name, 's3bucket')].Name" --output text)
echo $BUCKET_NAME
aws s3 ls s3://$BUCKET_NAME/ | awk '{print $4}' | xargs -I {} aws s3api copy-object \
    --bucket $BUCKET_NAME \
    --copy-source $BUCKET_NAME/{} \
    --key {} \
    --cache-control "max-age=180" \
    --metadata-directive REPLACE


```

```

[ec2-user@ip-10-0-1-85 environment]$ BUCKET_NAME=$(aws s3api list-buckets --query "Buckets[?contains(Name, 's3bucket')].Name" --output text)
echo $BUCKET_NAME
aws s3 ls s3://$BUCKET_NAME/ | awk '{print $4}' | xargs -I {} aws s3api copy-object \
    --bucket $BUCKET_NAME \
    --copy-source $BUCKET_NAME/{} \
    --key {} \
    --cache-control "max-age=180" \
    --metadata-directive REPLACE
c168617a4340258111162044t1w924862108750-s3bucket-aehrygm2pxkg
{
  "ServerSideEncryption": "AES256",
  "CopyObjectResult": {
    "ETag": "\"c48c724eb92f40d709def7b78287c101\"",
    "LastModified": "2025-08-18T08:36:51+00:00",
    "ChecksumCRC64NME": "EnA++ofso+s="
  }
}
{
  "ServerSideEncryption": "AES256",
  "CopyObjectResult": {
    "ETag": "\"3f315cd9e47907bd20dc7df12ade94a7\"",
    "LastModified": "2025-08-18T08:36:51+00:00",
    "ChecksumCRC64NME": "pX/YJ87xU4k="
  }
}
{
  "ServerSideEncryption": "AES256",
  "CopyObjectResult": {
    "ETag": "\"321967ab269bfed0fc67ef8adba2ae80\"",
    "LastModified": "2025-08-18T08:36:52+00:00",
    "ChecksumCRC64NME": "WQ0xi08sxhE="
  }
}
}

```

Ln 1, Col 78 Spaces: 4 UTF-8 LF Plain Text Layout: US

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Cloud Developing (01CT0720)	Aim: Implement CloudFront for caching and application security.	
Experiment No: 10	Date:	Enrolment No: 92200133030

Conclusion:-

- I connected to the AWS IDE and set up the lab environment.
- I downloaded the required files and upgraded the AWS CLI.
- I verified the S3 bucket and opened the café website.
- I created a CloudFront distribution for the website.
- I enabled HTTPS access using CloudFront.
- I updated the S3 bucket policy for secure access.
- I created an IP set in AWS WAF for my system IP.
- I created a Web ACL to allow only my IP to access the site.
- I secured the API Gateway endpoint using AWS WAF.
- I tested the API Gateway URL and verified it was working.
- I created and deployed a CloudFront function.
- I updated cache settings on S3 objects for better performance.