



Vivekanand Education Society's

Institute of Technology

An Autonomous Institute Affiliated to University of Mumbai,, Approved by AICTE & Recognized by Govt. of Maharashtra
Hashu Advani Memorial Complex, Collector Colony, Chembur East, Mumbai - 400074.

Department of Information Technology

A.Y. 2024-25

Advance DevOps Lab

Experiment 04

Aim: To install Kubectl and execute Kubectl commands to manage the Kubernetes cluster and deploy Your First Kubernetes Application.

Roll No.	53
Name	ARYAN DEEPAK SARAF
Class	D15B
Subject	Advance DevOps Lab
LO Mapped	LO1: To understand the fundamentals of Cloud Computing and be fully proficient with Cloud based DevOps solution deployment options to meet your business requirements. LO2: To deploy single and multiple container applications and manage application deployments with rollouts in Kubernetes
Grade:	

Aim : To install Kubectl and execute Kubectl commands to manage the Kubernetes cluster and deploy Your First Kubernetes Application.

Theory :

kubectl is the command-line interface (CLI) tool that allows users to interact with a Kubernetes cluster. As a central component of Kubernetes, **kubectl** provides the functionality needed to manage applications, inspect cluster resources, and perform administrative tasks through simple commands executed in a terminal.

Importance of Kubectl in Kubernetes Management

kubectl is essential for effective Kubernetes management for several reasons:


1. **User-Friendly Interface:** **kubectl** offers a command-line interface that simplifies complex operations, making it accessible for developers and administrators.
2. **Resource Management:** Users can create, update, and delete Kubernetes resources such as pods, deployments, services, and namespaces with straightforward commands.
3. **Deployment and Scaling:** **kubectl** facilitates the deployment of containerized applications and allows users to easily scale them up or down based on current demands.
4. **Monitoring and Troubleshooting:** The tool enables users to monitor the health and status of applications running in the cluster. It provides commands to view logs, describe resources, and check the current state of pods and services, which aids in troubleshooting issues.
5. **Configuration Management:** **kubectl** supports YAML configuration files that define the desired state of applications and resources, allowing users to apply changes consistently and repeatedly across different environments.

Key Features of Kubectl


- **Resource Discovery:** **kubectl** can list all resources in a Kubernetes cluster, providing an overview of what is running and its current status.
- **Detailed Resource Descriptions:** The tool can display detailed information about specific resources, including configuration, current state, events, and resource utilization.
- **Access to Container Logs:** Users can view the logs generated by application containers, helping diagnose issues and understand application behavior.

Namespace Management: **kubectl** allows for the management of namespaces, which help organize resources and provide isolation within a cluster.


Launch an EC2 Instance





Choose Ubuntu Server 20.04 LTS (HVM), SSD Volume Type as your AMI.




Select t2.medium as the instance type (2 CPUs).




Select Create a new key pair, name it (e.g., **aryan04**), and click Download Key Pair. This will download a **.pem** file to your computer.



Launch the EC2 instance.






The screenshot shows the AWS Management Console for the 'us-east-1' region. The 'Instances' page displays a list of EC2 instances. The instance 'aryan04' with ID 'i-03fa6b8134357702f' is in the 'Running' state. A tooltip indicates that the 'Public IPv4 address' has been copied.

Name	Instance ID	Instance state	Instance type	Status check	Alarm status
master	i-07cc19a675699739b	Shutting-d...	t2.micro	-	View alarms +
aryan04	i-03fa6b8134357702f	Running	t2.medium	Initializing	View alarms +
node-2	i-0f5b475b5d37019a8	Shutting-d...	t2.micro	-	View alarms +
node-1	i-0a046f2c07b79b441	Shutting-d...	t2.micro	-	View alarms +


Click on the instance id of the newly created ec2 instance and copy the public url of it.



The screenshot shows the 'Instance details' page for the instance 'aryan04'. The 'Public IPv4 address' is 54.92.219.25. A tooltip indicates it has been copied.

Instance ID	Instance state	Private IPv4 addresses	Public IPv4 DNS
i-03fa6b8134357702f (aryan04)	Running	172.31.94.165	ec2-54-92-219-25.compute-1.amazonaws.com

Click on connect and copy the command as shown



The screenshot shows the 'Connect to instance' page for the instance 'aryan04'. The page provides instructions for connecting to the instance using an SSH client. The command to connect is shown: `ssh -i 'aryan-exp04.pem' ubuntu@ec2-54-92-219-25.compute-1.amazonaws.com`. A tooltip indicates the command has been copied.

```
ssh -i "aryan-exp04.pem" ubuntu@ec2-54-92-219-25.compute-1.amazonaws.com
```

If you are using Windows, you might need a terminal like **Git Bash** or **PuTTY**.
Use the `cd` command to navigate to the folder where your downloaded key is located.

```

Command Prompt
Microsoft Windows [Version 10.0.22631.4169]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Admin>cd C:\Users\Admin\Documents\Labs\advance devops\aryan-aws

C:\Users\Admin\Documents\Labs\advance devops\aryan-aws>ls
aryan-exp04.pem

C:\Users\Admin\Documents\Labs\advance devops\aryan-aws>

```

Run the following command, replacing the placeholder with your actual EC2 public DNS:

`ssh -i "aryan-exp04.pem" ubuntu@ec2-54-92-219-25.compute-1.amazonaws.com`

```

ubuntu@ip-172-31-94-165: ~
C:\Users\Admin\Documents\Labs\advance devops\aryan-aws>ssh -i "aryan-exp04.pem" ubuntu@ec2-54-92-219-25.compute-1.amazonaws.com
The authenticity of host 'ec2-54-92-219-25.compute-1.amazonaws.com (54.92.219.25)' can't be established.
ED25519 key fingerprint is SHA256:rnfbJWmtqs0zputob8IEX4NIXXnY90JuPJH1Uq8psd4.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added 'ec2-54-92-219-25.compute-1.amazonaws.com' (ED25519) to the list of known hosts.
Welcome to Ubuntu 24.04.1 LTS (GNU/Linux 6.8.0-1016-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Sun Oct  6 16:51:26 UTC 2024

System load:  0.0          Processes:      112
Usage of /:   22.8% of 6.71GB Users logged in:  0
Memory usage: 5%          IPv4 address for enX0: 172.31.94.165
Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

```

To install Docker, Run the Following Commands:

`curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo apt-key add -`

```

ubuntu@ip-172-31-94-165: ~
ubuntu@ip-172-31-94-165:~$ curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo apt-key add -
Warning: apt-key is deprecated. Manage keyring files in trusted.gpg.d instead (see apt-key(8)).
OK

```

`curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo gpg --dearmor -o /etc/apt/trusted.gpg.d/docker.gpg`

`sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu $(lsb_release -cs) stable"`

```

ubuntu@ip-172-31-94-165: ~$ curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo gpg --dearmor -o /etc/apt/trusted.gpg.d/docker.gpg
ubuntu@ip-172-31-94-165:~$ sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu $(lsb_release -cs) stable"
Repository: 'deb [arch=amd64] https://download.docker.com/linux/ubuntu noble stable'
Description:
Archive for codename: noble components: stable
More info: https://download.docker.com/linux/ubuntu
Adding repository.
Press [ENTER] to continue or Ctrl-c to cancel.
Adding deb entry to /etc/apt/sources.list.d/archive_uri=https.download.docker.com.linux.ubuntu-noble.list
Adding disabled deb-src entry to /etc/apt/sources.list.d/archive_uri=https.download.docker.com.linux.ubuntu-noble.list
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease [126 kB]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease [126 kB]
Get:4 http://security.ubuntu.com/ubuntu noble-security InRelease [126 kB]
Get:5 https://download.docker.com/linux/ubuntu noble InRelease [48.8 kB]
Get:6 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 Packages [15.0 MB]
Get:7 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe Translation-en [5982 kB]
Get:8 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 Components [3871 kB]
Get:9 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 c-n-f Metadata [301 kB]
Get:10 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse amd64 Packages [269 kB]
Get:11 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse Translation-en [118 kB]
Get:12 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse amd64 Components [35.0 kB]
Get:13 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse amd64 c-n-f Metadata [8328 B]
Get:14 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 Packages [537 kB]
Get:15 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main Translation-en [132 kB]
Get:16 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 c-n-f Metadata [8860 B]
Get:17 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 Packages [384 kB]
Get:18 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe Translation-en [159 kB]
Get:19 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 Components [45.0 kB]
Get:20 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 c-n-f Metadata [14.9 kB]
Get:21 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Packages [14.4 kB]
Get:22 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse Translation-en [3608 B]
Get:23 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Components [212 B]
Get:24 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 c-n-f Metadata [532 B]
Get:25 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/main amd64 Components [208 B]
Get:26 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/main amd64 c-n-f Metadata [112 B]
Get:27 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 Packages [10.6 kB]
Get:28 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe Translation-en [10.8 kB]
Get:29 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 Components [17.6 kB]
Get:30 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 c-n-f Metadata [1104 B]
Get:31 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports/restricted amd64 Components [216 B]

```

sudo apt-get update

```

ubuntu@ip-172-31-94-165:~$ sudo apt-get update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu noble InRelease
Hit:5 http://security.ubuntu.com/ubuntu noble-security InRelease
Reading package lists... Done
ubuntu@ip-172-31-94-165:~$

```

sudo apt-get install -y docker-ce

```

ubuntu@ip-172-31-94-165:~$ sudo apt-get install -y docker-ce
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  containerd.io docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras
  docker-compose-plugin libltdl7 libslirp0 pigz slirp4netns
Suggested packages:
  aufs-tools cgroupfs-mount | cgroup-lite
The following NEW packages will be installed:
  containerd.io docker-buildx-plugin docker-ce docker-ce-cli
  docker-ce-rootless-extras docker-compose-plugin libltdl7 libslirp0 pigz
  slirp4netns
0 upgraded, 10 newly installed, 0 to remove and 6 not upgraded.
Need to get 123 MB of archives.
After this operation, 442 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 pigz amd64 2.8-1 [65.6 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 libltdl7 amd64 2.4.7-7build1 [40.3 kB]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 libslirp0 amd64 4.7.0-1ubuntu3 [63.8 kB]
Get:4 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 slirp4netns amd64 1.2.1-1build2 [34.9 kB]
Get:5 https://download.docker.com/linux/ubuntu noble/stable amd64 containerd.io amd64 1.7.22-1 [29.5 MB]
Get:6 https://download.docker.com/linux/ubuntu noble/stable amd64 docker-buildx-plugin amd64 0.17.1-1~ubuntu.24.04~noble [30.3 MB]
Get:7 https://download.docker.com/linux/ubuntu noble/stable amd64 docker-ce-cli amd64 5:27.3.1-1~ubuntu.24.04~noble [15.0 MB]
Get:8 https://download.docker.com/linux/ubuntu noble/stable amd64 docker-ce amd64 5:27.3.1-1~ubuntu.24.04~noble [25.6 MB]
Get:9 https://download.docker.com/linux/ubuntu noble/stable amd64 docker-ce-rootless-extras amd64 5:27.3.1-1~ubuntu.24.04~noble [9588 kB]
Get:10 https://download.docker.com/linux/ubuntu noble/stable amd64 docker-compose-plugin amd64 2.29.7-1~ubuntu.24.04~noble [12.7 MB]
Fetched 123 MB in 1s (89.5 MB/s)
debconf: unable to initialize frontend: Dialog
debconf: (Dialog frontend requires a screen at least 13 lines tall and 31 columns wide.)
debconf: falling back to frontend: Readline
Selecting previously unselected package pigz.
(Reading database ... 67836 files and directories currently installed.)
Preparing to unpack .../0-pigz_2.8-1_amd64.deb ...
Unpacking pigz (2.8-1) ...
Selecting previously unselected package containerd.io.
Preparing to unpack .../1-containerd.io_1.7.22-1_amd64.deb ...
Unpacking containerd.io (1.7.22-1) ...
Selecting previously unselected package docker-buildx-plugin.
Preparing to unpack .../2-docker-buildx-plugin_0.17.1-1~ubuntu.24.04~noble_amd64.deb ...
Unpacking docker-buildx-plugin (0.17.1-1~ubuntu.24.04~noble) ...
Selecting previously unselected package docker-ce-cli.

```

Configure Docker

sudo mkdir -p /etc/docker


```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ sudo mkdir -p /etc/docker  
ubuntu@ip-172-31-94-165:~$
```

cat <<EOF | sudo tee /etc/docker/daemon.json

```
{  
  "exec-opts": ["native.cgroupdriver=systemd"]  
}  
EOF
```

```
ubuntu@ip-172-31-94-165:~$ cat <<EOF | sudo tee /etc/docker/daemon.json  
> {  
  "exec-opts": ["native.cgroupdriver=systemd"]  
}  
EOF  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$
```

sudo systemctl enable docker

```
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ sudo systemctl enable docker  
Synchronizing state of docker.service with SysV service script with /usr/lib/s  
ysemd/systemd-sysv-install.  
Executing: /usr/lib/systemd/systemd-sysv-install enable docker  
ubuntu@ip-172-31-94-165:~$
```

sudo systemctl daemon-reload

sudo systemctl restart docker

```
ubuntu@ip-172-31-94-165:~$ sudo systemctl daemon-reload  
ubuntu@ip-172-31-94-165:~$ sudo systemctl restart docker  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$
```

To Install Kubernetes, Add the Kubernetes Repository

curl -fsSL https://pkgs.k8s.io/core:/stable:/v1.31/deb/Release.key | sudo gpg --dearmor -o /etc/apt/keyrings/kubernetes-apt-keyring.gpg

```
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ curl -fsSL https://pkgs.k8s.io/core:/stable:/v1.31/deb/Release.key | sudo  
gpg --dearmor -o /etc/apt/keyrings/kubernetes-apt-keyring.gpg  
ubuntu@ip-172-31-94-165:~$
```

echo 'deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg]

https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /' | sudo tee /etc/apt/sources.list.d/kubernetes.list


```

ubuntu@ip-172-31-94-165: ~$ echo 'deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg] https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /' | sudo tee /etc/apt/sources.list.d/kubernetes.list
deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg] https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ |

```

sudo apt-get update

```

ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ sudo apt-get update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu noble InRelease
Hit:6 http://security.ubuntu.com/ubuntu noble-security InRelease
Get:5 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb InRelease [1186 B]
Get:7 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb Packages [4865 B]
Fetched 6051 B in 1s (10.8 kB/s)
Reading package lists... Done

```

sudo apt-get install -y kubelet kubeadm kubectl

```

ubuntu@ip-172-31-94-165:~$ sudo apt-get install -y kubelet kubeadm kubectl
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  conntrack cri-tools kubernetes-cni
The following NEW packages will be installed:
  conntrack cri-tools kubeadm kubectl kubelet kubernetes-cni
0 upgraded, 6 newly installed, 0 to remove and 6 not upgraded.
Need to get 87.4 MB of archives.
After this operation, 314 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 conntrack amd64 1:1.4.8-1ubuntu1 [37.9 kB]
Get:2 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb cri-tools 1.31.1-1.1 [15.7 MB]
Get:3 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubeadm 1.31.1-1.1 [11.4 MB]
Get:4 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubectl 1.31.1-1.1 [11.2 MB]
Get:5 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubernetes-cni 1.5.1-1.1 [33.9 MB]
Get:6 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubelet 1.31.1-1.1 [15.2 MB]
Fetched 87.4 MB in 1s (90.2 MB/s)
debconf: unable to initialize frontend: Dialog
debconf: (Dialog frontend requires a screen at least 13 lines tall and 31 columns wide.)
debconf: falling back to frontend: Readline
Selecting previously unselected package conntrack.
(Reading database ... 68102 files and directories currently installed.)
Preparing to unpack .../0-conntrack_1%3a1.4.8-1ubuntu1_amd64.deb ...
Unpacking conntrack (1:1.4.8-1ubuntu1) ...
Selecting previously unselected package cri-tools.
Preparing to unpack .../1-cri-tools_1.31.1-1.1_amd64.deb ...
Unpacking cri-tools (1.31.1-1.1) ...
Selecting previously unselected package kubeadm.
Preparing to unpack .../2-kubeadm_1.31.1-1.1_amd64.deb ...
Unpacking kubeadm (1.31.1-1.1) ...
Selecting previously unselected package kubectl.
Preparing to unpack .../3-kubectl_1.31.1-1.1_amd64.deb ...
Unpacking kubectl (1.31.1-1.1) ...
Selecting previously unselected package kubernetes-cni.
Preparing to unpack .../4-kubernetes-cni_1.5.1-1.1_amd64.deb ...
Unpacking kubernetes-cni (1.5.1-1.1) ...
Selecting previously unselected package kubelet.
Preparing to unpack .../5-kubelet_1.31.1-1.1_amd64.deb ...
Unpacking kubelet (1.31.1-1.1) ...
Setting up conntrack (1:1.4.8-1ubuntu1) ...

```

sudo apt-mark hold kubelet kubeadm kubectl

```

ubuntu@ip-172-31-94-165:~$ sudo apt-mark hold kubelet kubeadm kubectl
kubelet set on hold.
kubeadm set on hold.
kubectl set on hold.
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ |

```

Enable and Start Kubelet:

sudo systemctl enable --now kubelet

```

ubuntu@ip-172-31-94-165: ~
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ sudo systemctl enable --now kubelet
ubuntu@ip-172-31-94-165:~$

```

To Initialize the Kubernetes Cluster, Run the Command

`sudo kubeadm init --pod-network-cidr=10.244.0.0/16`

```

ubuntu@ip-172-31-94-165:~$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16
[init] Using Kubernetes version: v1.31.0
[preflight] Running pre-flight checks
W1006 17:08:23.289361 4350 checks.go:1080] [preflight] WARNING: Couldn't create the interface used for talking to the container runtime: failed to create new CRI runtime service: validate service connection: validate CRI v1 runtime API for endpoint "unix:///var/run/containerd/containerd.sock": rpc error: code = Unimplemented desc = unknown service runtime.v1.RuntimeService
[WARNING FileExisting-socat]: socat not found in system path
[preflight] Pulling images required for setting up a Kubernetes cluster
[preflight] This might take a minute or two, depending on the speed of your internet connection
[preflight] You can also perform this action beforehand using 'kubeadm config images pull'
error execution phase preflight: [preflight] Some fatal errors occurred:
failed to create new CRI runtime service: validate service connection: validate CRI v1 runtime API for endpoint "unix:///var/run/containerd/containerd.sock": rpc error: code = Unimplemented desc = unknown service runtime.v1.RuntimeService
[preflight] If you know what you are doing, you can make a check non-fatal with `--ignore-preflight-errors=...`
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$

```

If you encounter errors, run the following commands to fix containerd issues:

`sudo apt-get install -y containerd`

```

ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ sudo apt-get install -y containerd
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following packages were automatically installed and are no longer required:
  docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras
  docker-compose-plugin libltdl7 libsdl2-1.2-0 libslirp0 pigz slirp4netns
Use 'sudo apt autoremove' to remove them.
The following additional packages will be installed:
  runc
The following packages will be REMOVED:
  containerd.io docker-ce
The following NEW packages will be installed:
  containerd runc
0 upgraded, 2 newly installed, 2 to remove and 6 not upgraded.
Need to get 47.2 MB of archives.
After this operation, 53.1 MB disk space will be freed.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 runc amd64 1.1.12-0ubuntu3.1 [8599 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 containerd amd64 1.7.12-0ubuntu4.1 [38.6 MB]
Fetched 47.2 MB in 1s (83.4 MB/s)
(Reading database ... 68139 files and directories currently installed.)
Removing docker-ce (5:27.3.1-1ubuntu.24.04=noble) ...
Removing containerd.io (1.7.22-1) ...
Selecting previously unselected package runc.
(Reading database ... 68139 files and directories currently installed.)
Preparing to unpack .../runc_1.1.12-0ubuntu3.1_amd64.deb ...
Unpacking runc (1.1.12-0ubuntu3.1) ...
Selecting previously unselected package containerd.
Preparing to unpack .../containerd_1.7.12-0ubuntu4.1_amd64.deb ...
Unpacking containerd (1.7.12-0ubuntu4.1) ...
Setting up runc (1.1.12-0ubuntu3.1) ...
Setting up containerd (1.7.12-0ubuntu4.1) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

```

`sudo mkdir -p /etc/containerd`

`sudo containerd config default | sudo tee /etc/containerd/config.toml`

```

ubuntu@ip-172-31-94-165: ~$ sudo mkdir -p /etc/containerd
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ sudo containerd config default | sudo tee /etc/containerd/config.toml
disabled_plugins = []
imports = []
oom_score = 0
plugin_dir = ""
required_plugins = []
root = "/var/lib/containerd"
state = "/run/containerd"
temp = ""
version = 2

[cgroup]
path = ""

```

sudo systemctl restart containerd

sudo systemctl enable containerd

sudo systemctl status containerd

```

ubuntu@ip-172-31-94-165:~$ sudo systemctl restart containerd
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ sudo systemctl enable containerd
ubuntu@ip-172-31-94-165:~$ sudo systemctl status containerd
● containerd.service - containerd container runtime
   Loaded: loaded (/usr/lib/systemd/system/containerd.service; enabled; preset: enabled)
   Active: active (running) since Sun 2024-10-06 17:11:31 UTC; 21s ago
     Docs: https://containerd.io
   Main PID: 4859 (containerd)
      Tasks: 8
     Memory: 13.5M (peak: 14.4M)
        CPU: 146ms
    CGroup: /system.slice/containerd.service
            └─4859 /usr/bin/containerd

Oct 06 17:11:31 ip-172-31-94-165 containerd[4859]: time="2024-10-06T17:11:31.193190478Z" level=>
Oct 06 17:11:31 ip-172-31-94-165 containerd[4859]: time="2024-10-06T17:11:31.193620259Z" level=>
Oct 06 17:11:31 ip-172-31-94-165 containerd[4859]: time="2024-10-06T17:11:31.193650970Z" level=>
Oct 06 17:11:31 ip-172-31-94-165 containerd[4859]: time="2024-10-06T17:11:31.193658249Z" level=>
Oct 06 17:11:31 ip-172-31-94-165 containerd[4859]: time="2024-10-06T17:11:31.193700461Z" level=>

```

sudo apt-get install -y socat

```

ubuntu@ip-172-31-94-165:~$ sudo apt-get install -y socat
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following packages were automatically installed and are no longer required:
  docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras docker-compose-plugin libltdl7
  libslirp0 pigz slirp4netns
Use 'sudo apt autoremove' to remove them.
The following NEW packages will be installed:
  socat
0 upgraded, 1 newly installed, 0 to remove and 6 not upgraded.
Need to get 374 kB of archives.
After this operation, 1649 kB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 socat amd64 1.8.0.0-4build
3 [374 kB]
Fetched 374 kB in 0s (14.2 MB/s)
Selecting previously unselected package socat.
(Reading database ... 68203 files and directories currently installed.)
Preparing to unpack .../socat_1.8.0.0-4build3_amd64.deb ...
Unpacking socat (1.8.0.0-4build3) ...
Setting up socat (1.8.0.0-4build3) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ |

```

Re-run the Init Command:

`sudo kubeadm init --pod-network-cidr=10.244.0.0/16`

```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16  
[init] Using Kubernetes version: v1.31.0  
[preflight] Running pre-flight checks  
[preflight] Pulling images required for setting up a Kubernetes cluster  
[preflight] This might take a minute or two, depending on the speed of your internet connection  
[preflight] You can also perform this action beforehand using 'kubeadm config images pull'  
W1006 17:14:17.430128 5141 checks.go:846] detected that the sandbox image "registry.k8s.io/pause:3.8" of the container runtime is inconsistent with that used by kubeadm. It is recommended to use "registry.k8s.io/pause:3.10" as the CRI sandbox image.  
[certs] Using certificateDir folder "/etc/kubernetes/pki"  
[certs] Generating "ca" certificate and key  
[certs] Generating "apiserver" certificate and key  
[certs] apiserver serving cert is signed for DNS names [ip-172-31-94-165.kubernetes.kubernetes.default.kubernetes.default.svc.kubernetes.default.svc.cluster.local] and IPs [10.96.0.1 172.31.94
```

To Configure kubectl, Set Up kubeconfig

`mkdir -p $HOME/.kube`

`sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config`

`sudo chown $(id -u):$(id -g) $HOME/.kube/config`

```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ mkdir -p $HOME/.kube  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config  
ubuntu@ip-172-31-94-165:~$ sudo chown $(id -u):$(id -g) $HOME/.kube/config  
ubuntu@ip-172-31-94-165:~$ |
```

Install Flannel (a networking plugin):

`kubectl apply -f`

<https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml>

```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ kubectl apply -f https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml  
namespace/kube-flannel created  
clusterrole.rbac.authorization.k8s.io/flannel created  
clusterrolebinding.rbac.authorization.k8s.io/flannel created  
serviceaccount/flannel created  
configmap/kube-flannel-cfg created  
daemonset.apps/kube-flannel-ds created  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ |
```

To Deploy Nginx Server, Create a Deployment:

`kubectl apply -f https://k8s.io/examples/application/deployment.yaml`

```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ kubectl apply -f https://k8s.io/examples/application/deployment.yaml  
deployment.apps/nginx-deployment created  
ubuntu@ip-172-31-94-165:~$ |
```

Check Pods:

`kubectl get pods`

```

ubuntu@ip-172-31-94-165: ~
ubuntu@ip-172-31-94-165:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-qbx25    0/1     Pending   0           43s
nginx-deployment-d556bf558-tlkt5    0/1     Pending   0           43s
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ |

```

If the pod status is pending, you might need to remove the control-plane taint:

`kubectl taint nodes --all node-role.kubernetes.io/control-plane-`

```

ubuntu@ip-172-31-94-165: ~
ubuntu@ip-172-31-94-165:~$ kubectl taint nodes --all node-role.kubernetes.io/control-plane-
node/ip-172-31-94-165 untainted
ubuntu@ip-172-31-94-165:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-qbx25    1/1     Running   0           119s
nginx-deployment-d556bf558-tlkt5    1/1     Running   0           119s
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ |

```

Port Forward to Access Nginx: Find the Pod name

`POD_NAME=$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}")`

`kubectl port-forward $POD_NAME 8080:80`

```

ubuntu@ip-172-31-94-165: ~
ubuntu@ip-172-31-94-165:~$ echo aryan
aryan
ubuntu@ip-172-31-94-165:~$ POD_NAME=$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}")
ubuntu@ip-172-31-94-165:~$ kubectl port-forward $POD_NAME 8080:80
Forwarding from 127.0.0.1:8080 -> 80
Forwarding from [::1]:8080 -> 80

```

Open a New Terminal and SSH back into your EC2 instance.

```

C:\Users\Admin>cd C:\Users\Admin\Documents\Labs\advance devops\aryan-aws
C:\Users\Admin\Documents\Labs\advance devops\aryan-aws>ssh -i "aryan-exp04.pem" ubuntu@ec2-54-92-219-25.compute-1.amazonaws.com
Welcome to Ubuntu 24.04.1 LTS (GNU/Linux 6.8.0-1016-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Sun Oct  6 17:24:16 UTC 2024

System load:  0.12          Processes:      151
Usage of /:   55.5% of 6.71GB Users logged in:    1
Memory usage: 20%          IPv4 address for enX0: 172.31.94.165
Swap usage:   0%

 * Ubuntu Pro delivers the most comprehensive open source security and
  compliance features.

  https://ubuntu.com/aws/pro

Expanded Security Maintenance for Applications is not enabled.

6 updates can be applied immediately.
5 of these updates are standard security updates.
To see these additional updates run: apt list --upgradable


Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

Last login: Sun Oct  6 16:51:27 2024 from 103.251.51.24
ubuntu@ip-172-31-94-165:~$ |

```

Use Curl to Check Nginx:

curl --head http://127.0.0.1:8080



```
ubuntu@ip-172-31-94-165: ~  
ubuntu@ip-172-31-94-165:~$ curl --head http://127.0.0.1:8080  
HTTP/1.1 200 OK  
Server: nginx/1.14.2  
Date: Sun, 06 Oct 2024 17:25:14 GMT  
Content-Type: text/html  
Content-Length: 612  
Last-Modified: Tue, 04 Dec 2018 14:44:49 GMT  
Connection: keep-alive  
ETag: "5c0692e1-264"  
Accept-Ranges: bytes  
  
ubuntu@ip-172-31-94-165:~$ echo aryan  
aryan  
ubuntu@ip-172-31-94-165:~$ |
```

If you see **200 OK**, your Nginx server is successfully running.

Conclusion :

Understanding **kubectl** is crucial for anyone working with Kubernetes, as it serves as the primary interface for managing applications and resources. Through `kubectl`, users can effectively deploy, monitor, and troubleshoot applications, ensuring that they run smoothly in a Kubernetes environment.