

6.Foreign Key and Joins

-- Creating the customers and orders tables

```
CREATE TABLE customers(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    first_name VARCHAR(100),  
    last_name VARCHAR(100),  
    email VARCHAR(100)  
);  
CREATE TABLE orders(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    order_date DATE,  
    amount DECIMAL(8,2),  
    customer_id INT,  
    FOREIGN KEY(customer_id) REFERENCES customers(id)  
);
```

-- Inserting some customers and orders

```
INSERT INTO customers (first_name, last_name, email)  
VALUES ('Boy', 'George', 'george@gmail.com'),  
       ('George', 'Michael', 'gm@gmail.com'),  
       ('David', 'Bowie', 'david@gmail.com'),  
       ('Blue', 'Steele', 'blue@gmail.com'),  
       ('Bette', 'Davis', 'bette@aol.com');  
  
INSERT INTO orders (order_date, amount, customer_id)  
VALUES ('2016/02/10', 99.99, 1),  
       ('2017/11/11', 35.50, 1),  
       ('2014/12/12', 800.67, 2),  
       ('2015/01/03', 12.50, 2),  
       ('1999/04/11', 450.25, 5);
```

-- This INSERT fails because of our fk constraint. No user with id: 98

```
INSERT INTO orders (order_date, amount, customer_id)  
VALUES ('2016/06/06', 33.67, 98);
```

-- Finding Orders Placed By George: 2 Step Process

```
SELECT id FROM customers WHERE last_name='George';  
SELECT * FROM orders WHERE customer_id = 1;
```

-- Finding Orders Placed By George: Using a subquery

```
SELECT * FROM orders WHERE customer_id =  
    (  
        SELECT id FROM customers  
        WHERE last_name='George'  
    );
```

-- Cross Join Crazyiness

```
SELECT * FROM customers, orders;
```

-- IMPLICIT INNER JOIN

```
SELECT * FROM customers, orders  
WHERE customers.id = orders.customer_id;
```

-- IMPLICIT INNER JOIN

```
SELECT first_name, last_name, order_date, amount  
FROM customers, orders  
    WHERE customers.id = orders.customer_id;
```

-- EXPLICIT INNER JOINS

```
SELECT * FROM customers  
JOIN orders  
    ON customers.id = orders.customer_id;
```

```
SELECT first_name, last_name, order_date, amount  
FROM customers  
JOIN orders  
    ON customers.id = orders.customer_id;
```

```
SELECT *  
FROM orders  
JOIN customers  
    ON customers.id = orders.customer_id;
```

-- ARBITRARY JOIN - meaningless, but still possible

```
SELECT * FROM customers  
JOIN orders ON customers.id = orders.id;
```

-- Getting Fancier (Inner Joins Still)

```
SELECT first_name, last_name, order_date, amount
FROM customers
JOIN orders
    ON customers.id = orders.customer_id
ORDER BY order_date;

SELECT
    first_name,
    last_name,
    SUM(amount) AS total_spent
FROM customers
JOIN orders
    ON customers.id = orders.customer_id
GROUP BY orders.customer_id
ORDER BY total_spent DESC;
```

-- LEFT JOINS

```
SELECT * FROM customers
LEFT JOIN orders
    ON customers.id = orders.customer_id;

SELECT first_name, last_name, order_date, amount
FROM customers
LEFT JOIN orders
    ON customers.id = orders.customer_id;

SELECT
    first_name,
    last_name,
    IFNULL(SUM(amount), 0) AS total_spent
FROM customers
LEFT JOIN orders
    ON customers.id = orders.customer_id
GROUP BY customers.id
ORDER BY total_spent;
```

-- OUR FIRST RIGHT JOIN (seems the same as a left join?)

```
SELECT * FROM customers
RIGHT JOIN orders
    ON customers.id = orders.customer_id;
```

-- ALTERING OUR SCHEMA to allow for a better example (optional)

```
CREATE TABLE customers(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    first_name VARCHAR(100),  
    last_name VARCHAR(100),  
    email VARCHAR(100)  
);  
CREATE TABLE orders(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    order_date DATE,  
    amount DECIMAL(8,2),  
    customer_id INT  
);
```

-- INSERTING NEW DATA (no longer bound by foreign key constraint)

```
INSERT INTO customers (first_name, last_name, email)  
VALUES ('Boy', 'George', 'george@gmail.com'),  
       ('George', 'Michael', 'gm@gmail.com'),  
       ('David', 'Bowie', 'david@gmail.com'),  
       ('Blue', 'Steele', 'blue@gmail.com'),  
       ('Bette', 'Davis', 'bette@aol.com');  
  
INSERT INTO orders (order_date, amount, customer_id)  
VALUES ('2016/02/10', 99.99, 1),  
       ('2017/11/11', 35.50, 1),  
       ('2014/12/12', 800.67, 2),  
       ('2015/01/03', 12.50, 2),  
       ('1999/04/11', 450.25, 5);  
  
INSERT INTO orders (order_date, amount, customer_id) VALUES  
('2017/11/05', 23.45, 45),  
(CURDATE(), 777.77, 109);
```

--A MORE COMPLEX RIGHT JOIN

```
SELECT  
    IFNULL(first_name, 'MISSING') AS first,  
    IFNULL(last_name, 'USER') as last,  
    order_date,  
    amount,  
    SUM(amount)  
FROM customers  
RIGHT JOIN orders  
    ON customers.id = orders.customer_id
```

```
GROUP BY first_name, last_name;
```

-- WORKING WITH ON DELETE CASCADE

```
CREATE TABLE customers(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    first_name VARCHAR(100),  
    last_name VARCHAR(100),  
    email VARCHAR(100)  
);
```

```
CREATE TABLE orders(  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    order_date DATE,  
    amount DECIMAL(8,2),  
    customer_id INT,  
    FOREIGN KEY(customer_id)  
        REFERENCES customers(id)  
        ON DELETE CASCADE  
);
```

```
INSERT INTO customers (first_name, last_name, email)  
VALUES ('Boy', 'George', 'george@gmail.com'),  
('George', 'Michael', 'gm@gmail.com'),  
('David', 'Bowie', 'david@gmail.com'),  
('Blue', 'Steele', 'blue@gmail.com'),  
('Bette', 'Davis', 'bette@aol.com');
```

```
INSERT INTO orders (order_date, amount, customer_id)  
VALUES ('2016/02/10', 99.99, 1),  
('2017/11/11', 35.50, 1),  
('2014/12/12', 800.67, 2),  
('2015/01/03', 12.50, 2),  
('1999/04/11', 450.25, 5);
```

-- The Schema

```
CREATE TABLE students (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    first_name VARCHAR(100)  
);
```

```
CREATE TABLE papers (  
    title VARCHAR(100),
```

```

        grade INT,
        student_id INT,
        FOREIGN KEY (student_id)
            REFERENCES students(id)
            ON DELETE CASCADE
    );

```

-- The Starter Data

```

INSERT INTO students (first_name) VALUES
('Caleb'),
('Samantha'),
('Raj'),
('Carlos'),
('Lisa');

INSERT INTO papers (student_id, title, grade ) VALUES
(1, 'My First Book Report', 60),
(1, 'My Second Book Report', 75),
(2, 'Russian Lit Through The Ages', 94),
(2, 'De Montaigne and The Art of The Essay', 98),
(4, 'Borges and Magical Realism', 89);

```

-- EXERCISE 1

```

SELECT first_name, title, grade
FROM students
INNER JOIN papers
    ON students.id = papers.student_id
ORDER BY grade DESC;

```

-- ALT SOLUTION

```

SELECT first_name, title, grade
FROM students
RIGHT JOIN papers
    ON students.id = papers.student_id
ORDER BY grade DESC;

```

-- PROBLEM 2

```

SELECT first_name, title, grade

```

```
FROM students
LEFT JOIN papers
    ON students.id = papers.student_id;
```

-- PROBLEM 3

```
SELECT
    first_name,
    IFNULL(title, 'MISSING'),
    IFNULL(grade, 0)
FROM students
LEFT JOIN papers
    ON students.id = papers.student_id;
```

-- PROBLEM 4

```
SELECT
    first_name,
    IFNULL(AVG(grade), 0) AS average
FROM students
LEFT JOIN papers
    ON students.id = papers.student_id
GROUP BY students.id
ORDER BY average DESC;
```

-- PROBLEM 5

```
SELECT first_name,
    Ifnull(Avg(grade), 0) AS average,
    CASE
        WHEN Avg(grade) IS NULL THEN 'FAILING'
        WHEN Avg(grade) >= 75 THEN 'PASSING'
        ELSE 'FAILING'
    end AS passing_status
FROM students
LEFT JOIN papers
    ON students.id = papers.student_id
GROUP BY students.id
ORDER BY average DESC;
```