

QUIZ3

1. Decision Tree

Impurity functions play an important role in decision tree branching. For binary classification problems, let μ_+ be the fraction of positive examples in a data subset, and $\mu_- = 1 - \mu_+$ be the fraction of negative examples in the data subset. The Gini index is $1 - \mu_+^2 - \mu_-^2$. What is the maximum value of the Gini index among all $\mu_+ \in [0, 1]$?

- A. 0.5
- B. 0.75
- C. 0.25
- D. 0
- E. 1

2. Following Question 1, there are four possible impurity functions below. We can normalize each impurity function by dividing it with its maximum value among all $\mu_+ \in [0, 1]$. For instance, the classification error is simply $\min(\mu_+, \mu_-)$ and its maximum value is 0.5. So the normalized classification error is $2 \min(\mu_+, \mu_-)$. After normalization, which of the following impurity function is equivalent to the normalized Gini index?

- A. the squared regression error (used for branching in classification data sets), which is by definition $\mu_+(1 - (\mu_+ - \mu_-))^2 + \mu_-(-1 - (\mu_+ - \mu_-))^2$.
- B. the entropy, which is $-\mu_+ \ln \mu_+ - \mu_- \ln \mu_-$, with $0 \log 0 \equiv 0$.
- C. the closeness, which is $1 - |\mu_+ - \mu_-|$.
- D. the classification error $\min(\mu_+, \mu_-)$.
- E. none of the other choices

3. Random Forest

If bootstrapping is used to sample $N' = pN$ examples out of N examples and N is very large. Approximately how many of the N examples will not be sampled at all?

- A. $(1 - e^{-1/p}) \cdot N$
- B. $(1 - e^{-p}) \cdot N$
- C. $e^{-1} \cdot N$
- D. $e^{-1/p} \cdot N$
- E. $e^{-p} \cdot N$

4. Consider a Random Forest G that consists of three binary classification trees $\{g_k\}_{k=1}^3$, where each tree is of test 0/1 error $E_{\text{out}}(g_1) = 0.1$, $E_{\text{out}}(g_2) = 0.2$, $E_{\text{out}}(g_3) = 0.3$. Which of the following is the exact possible range of $E_{\text{out}}(G)$?

- A. $0 \leq E_{\text{out}}(G) \leq 0.1$
- B. $0.1 \leq E_{\text{out}}(G) \leq 0.6$
- C. $0.2 \leq E_{\text{out}}(G) \leq 0.3$
- D. $0.1 \leq E_{\text{out}}(G) \leq 0.3$

E. $0.1 \leq E_{\text{out}}(G) \leq 0.3$

5. Consider a Random Forest G that consists of K binary classification trees $\{g_k\}_{k=1}^K$, where K is an odd integer. Each g_k is of test 0/1 error $E_{\text{out}}(g_k) = e_k$. Which of the following is an upper bound of $E_{\text{out}}(G)$?

- A.** $\frac{2}{K+1} \sum_{k=1}^K e_k$
- B.** $\frac{1}{K} \sum_{k=1}^K e_k$
- C.** $\frac{1}{K+1} \sum_{k=1}^K e_k$
- D.** $\min_{1 \leq k \leq K} e_k$
- E.** $\max_{1 \leq k \leq K} e_k$

6. Gradient Boosting

Let ϵ_t be the weighted 0/1 error of each g_t as described in the AdaBoost algorithm (Lecture 208), and $U_t = \sum_{n=1}^N u_n^{(t)}$ be the total example weight during AdaBoost. Which of the following equation expresses U_{T+1} by ϵ_t ?

- A.** none of the other choices
- B.** $\prod_{t=1}^T \epsilon_t$
- C.** $\sum_{t=1}^T (2\sqrt{\epsilon_t(1-\epsilon_t)})$
- D.** $\sum_{t=1}^T \epsilon_t$
- E.** $\prod_{t=1}^T (2\sqrt{\epsilon_t(1-\epsilon_t)})$

7. For the gradient boosted decision tree, if a tree with only one constant node is returned as g_1 , and if $g_1(\mathbf{x}) = 2$, then after the first iteration, all s_n is updated from 0 to a new constant $\alpha_1 g_1(\mathbf{x}_n)$. What is s_n ?

- A.** 2
- B.** none of the other choices
- C.** $\max_{1 \leq n \leq N} y_n$
- D.** $\min_{1 \leq n \leq N} y_n$
- E.** $\frac{1}{N} \sum_{n=1}^N y_n$

8. For the gradient boosted decision tree, after updating all s_n in iteration t using the steepest η as α_t , what is the value of $\sum_{n=1}^N s_n g_t(\mathbf{x}_n)$?

- A.** none of the other choices
- B.** $\sum_{n=1}^N y_n g_t(\mathbf{x}_n)$
- C.** $\sum_{n=1}^N y_n^2$
- D.** $\sum_{n=1}^N y_n s_n$
- E.** 0