OBJECTIVE PERSONALITY SYSTEM: COMPREHENSIVE SPARSE PRIMING REPRESENTATION

Formal Notation ↔ Common Notation Conversion Framework

PART 1: ONTOLOGICAL FOUNDATIONS

1.1 Ontoclean Framework Application

Onto-Clean Category Assignments:

Concept	Category	Rigidity	Identity	Unity	Notes
Psychological Function	Substance	Rigid	Essential	Essential	Intrinsic, multiply realizable
Ordonnance Position [1-4]	Role	Non-rigid	Relative	Relative	Relational, context-dependent
Modality (M/F)	Intrinsic Mode	Rigid	Essential	Essential	Constitutive of function's nature
Grant Stack	Compound	Non-rigid	Relative	Relative	Aggregate of Type instantiating Roles
Psyche Instance	Substance	Rigid	Essential	Essential	Concrete individual, embodied token

Ontological Principles:

- **Types** [+R, +U, +I, +D]: Intrinsic, multiply realizable (psychological functions)
- **Roles** [−R, ~U, −I, +D]: Relational, position-dependent (ordonnance positions [1-4])
- **Compounds**: Tokens instantiating Types within Roles (Grant stacks, animal pairings)

1.2 Jungian Complementarity Principle (Jung, CW 6)

Core Insight (Jung [667-670]):

One function dominates consciousness with absolute sovereignty. A second function must exist as **auxiliary** (secondary) because:

1. Two functions of equal power would create contradictory orientations (impossible for adaptation)
2. The auxiliary must be **not antagonistic** to the primary
3. **Antagonism Rule**:
    - Judging functions (T/F) are antagonistic to each other → cannot pair as primary + auxiliary
    - Perceiving functions (S/N) are complementary to judging functions → can pair with them
    - Example: Thinking pairs with Sensation OR Intuition, never with Feeling

Implication for OPS:

- Valid function pairs are constrained by non-antagonism
- The auxiliary serves the primary without claiming autonomy
- This principle explains why [2]/[3] (the auxiliary pair) must be on the opposite axis from [1]/[4] (the primary pair)

1.3 Psyche Ontology

Status: Psychological functions are genuine phenomena in their own right—not epiphenomena or mechanisms.

View: Energic/teleological—functions serve telos (purpose), not mechanical causation.

Structure: The psyche has ontological status as a dynamic ordering of purposive operations.

PART 2: OPS STRUCTURAL FOUNDATIONS

2.1 Core Architecture

The 16 Atomic Psychological Functions

M/F modality variant of each of Jung's 8 functions:

Observer Axis: Sensory and Intuitive perception

- Si, (f)Si, (m)Si — Introverted sensation

- Se, (f)Se, (m)Se — Extroverted sensation
- Ni, (f)Ni, (m)Ni — Introverted intuition
- Ne, (f)Ne, (m)Ne — Extroverted intuition

Decider Axis: Thinking and Feeling judgment

- Ti, (f)Ti, (m)Ti — Introverted thinking
- Te, (f)Te, (m)Te — Extroverted thinking
- Fi, (f)Fi, (m)Fi — Introverted feeling
- Fe, (f)Fe, (m)Fe — Extroverted feeling

The Three Levels of Type Structure

Level 1: Unmodalized Functions (8 Jungian types)

- Pure function without modality anchor
- Attitude (I/E) and axis (observer/decider) only
- Example: Se, Ti, Fe, Ni

Level 2: Modalized Functions (16 OPS atomic types)

- Functions with M/F modality designation
- Example: (m)Se, (f)Ti, (m)Fe, (f)Ni

Level 3: Grant Stack Ordonnance (static ranking)

- Four modalized functions in positions [1][2][3][4]
- From most to least differentiated
- Example: 1Ne - 2Fi - 3Te - 4Si

Level 4: Animal Stack (higher-order combinatoric)

- Observer/decider pairings that reveal ordonnance structure
- Dynamic priority ordering (savior vs. demon)
- Example: PB/C(S) means Play-Blast (savior), Consume-Sleep (demon)

Level 5: Type Profile (full specification)

- Complete type notation with all layers
- Example: FF - Si/Ti - SB/P(C)

2.2 The Grant Stack: Static Baseline

Definition: The Grant stack is the **fixed, unchanging ordonnance** of the four functions from most to least differentiated [1][2][3][4].

Properties:

- Determined entirely by the **lead function** (first in savior pair) via STACK_ANCHORS_BY_LEAD
- Once set, ordonnance never changes (static)
- Each function appears in exactly 2 animals
- Each function maintains the same bracket number across both animal appearances
- Bracket positions always in ascending order: [1-2], [1-3], [2-4], [3-4]

Oscillation Rule: Attitudes alternate I/E/I/E across [1][2][3][4]

Relationship Rules:

- [1]/[4]: Same axis | Opposite polarities (I/E) | Opposite modalities
- [2]/[3]: Same axis | Opposite polarities (I/E) | Opposite modalities
- [1]/[4] axis is always opposite to [2]/[3] axis (observer ↔ decider)

2.3 Animals: Higher-Order Relational Heuristic

Definition: Animals are observer/decider attitude pairings that **reveal** (not determine) ordonnance structure.

Four Animal Types

Animal	Observer	Decider	Bracket Span	Jumper?	Definition
Sleep (S)	Introverted (IO)	Introverted (ID)	[1-3] or [2-4]	YES	Most introverted pairing
Blast (B)	Introverted (IO)	Extroverted (ED)	[1-2] or [3-4]	NO	Introverted observer base
Consume (C)	Extroverted (EO)	Introverted (ID)	[1-2] or [3-4]	NO	Extroverted observer base

Animal	Observer	Decider	Bracket Span	Jumper?	Definition
Play (P)	Extroverted (EO)	Extroverted (ED)	[1-3] or [2-4]	YES	Most extroverted pairing

Jumper Constraint: Sleep and Play can span non-adjacent ordinals ([1-3] or [2-4]). **Non-Jumper Constraint**: Blast and Consume can only span adjacent ordinals ([1-2] or [3-4]).

Animal Stack Organization

Notation: [A1][A2]/A3

- **A1, A2** = savior pair (first two animals, most accessible)
- **A3, (A4)** = demon pair (last two animals, least accessible)
- **Priority order** determines how animals are listed in common notation

---

PART 3: FORMAL NOTATION

3.1 Formal Notation Structure

Format: [Modality] - [SaverObserver/SaverDecider] - [AnimalStack]

Example: `FF - Si/Ti - SB/P(C)`

Component 1: Modality [SensoryModality][ExtDeciderModality]

Possible values: MF, FM, MM, FF

- **char_1** = Modality of sensory function (Se or Si wherever it appears in stack)
- **char_2** = Modality of extroverted decider (Te or Fe wherever it appears in stack)

Reading:

- M = Masculine (grounded, fixed, anchored, matter-like)
- F = Feminine (fluid, airy, unanchored, form-like)

Critical insight: Two anchor points fully determine all four function modalities via inversion rules.

Component 2: Savior Pair [Observer/Decider]

Format: Unmodalized function names separated by slash

- **First function** = Savior observer (the lead function)
- **Second function** = Savior decider (auxiliary function)

Example: Ne/Te, Si/Fi, Se/Ti, Fe/Se

Purpose: Identifies which functions appear in the savior pair (first two animals).

Component 3: Animal Stack [A1A2/A3(A4)]

Format: Four animal initials in priority order

- **A1A2** = Savior pair (separated only by letter)
- / = Demarcation between savior and demon
- **A3(A4)** = Demon pair (4th animal in parentheses, least differentiated)

Example: PB/C(S) = Play-Blast savior, Consume-Sleep demon

Purpose: Indicates which animals are present and their priority order.

3.2 What Formal Notation Tells You (And What It Doesn't)

Formal notation tells you:

- Which two functions are in the savior pair
- The modality profile for those functions
- Which animals are present and their priority order

Formal notation does NOT directly tell you:

- The ordonnance positions ([1], [2], [3], [4])
- Which axis the [2]/[3] functions occupy
- The specific functions at [2], [3], [4]

These are derived mechanically via STACK_ANCHORS_BY_LEAD.

PART 4: MODALITY SYSTEM

4.1 Modality Anchoring Principle

Core Principle: Once you specify [1] with a modality, [4] is automatically determined.

Mechanism:

- The **sensory modality** (char_1) anchors all sensory and intuitive functions
- The **ext-decider modality** (char_2) anchors all extroverted deciders and introverted deciders
- **Inversion rule**: If one pole is masculine, its inverse is feminine

4.2 [1]/[4] Modality Pairings

These are mechanically determined by the lead function type:

Observer Axis (If [1]/[4] are both observer)

[1] Function	[1] Modality	[4] Function	[4] Modality
Si	(m)	Ne	(f)
Si	(f)	Ne	(m)
Se	(m)	Ni	(f)
Se	(f)	Ni	(m)
Ne	(m)	Si	(f)
Ne	(f)	Si	(m)
Ni	(m)	Se	(f)
Ni	(f)	Se	(m)

Decider Axis (If [1]/[4] are both decider)

[1] Function	[1] Modality	[4] Function	[4] Modality
Ti	(m)	Fe	(f)
Ti	(f)	Fe	(m)
Fi	(m)	Te	(f)
Fi	(f)	Te	(m)
Te	(m)	Fi	(f)
Te	(f)	Fi	(m)
Fe	(m)	Ti	(f)
Fe	(f)	Ti	(m)

Pattern: [1] and [4] are **always same axis, opposite polarity, opposite modality.**

4.3 [2]/[3] Modality Rules

Axis Opposition:

- If [1]/[4] are observer axis → [2]/[3] are decider axis
- If [1]/[4] are decider axis → [2]/[3] are observer axis

Modality Inheritance:

- [2] modality follows the ext-decider anchor (char_2)
- [3] modality is inverse of [2]
- OR [2] modality follows the observer anchor if [2]/[3] are observers

Function Determination:

- Use the **opposite axis inverse pairings** (not arbitrary choice)
- The specific function depends on which axis and which attitudes STACK_ANCHORS requires

4.4 Fixed Inverse Pairings (Structural, Not Modality-Based)

OBSERVER AXIS:

- Si ↔ Ne (introverted sensation ↔ extroverted intuition)

- Se ↔ Ni (extroverted sensation ↔ introverted intuition)

DECIDER AXIS:

- Ti ↔ Fe (introverted thinking ↔ extroverted feeling)
- Fi ↔ Te (introverted feeling ↔ extroverted thinking)

These pairings are FIXED and NON-NEGOTIABLE. They derive from Jung's complementarity principle and the structure of consciousness itself.

PART 5: STACK ANCHORS BY LEAD

5.1 The Four STACK_ANCHORS Rules

These rules are **deterministic** based on the lead function's observer/decider type and attitude.

Rule 1: Introverted Observer Lead (Si or Se with I attitude)

```
[1] = IO (introverted observer) — the lead function
[2] = ED (extroverted decider)
[3] = ID (introverted decider)
[4] = EO (extroverted observer)
```

Oscillation: I/E/I/E ✓ **Axis opposition**: [1]/[4] observer ↔ [2]/[3] decider ✓

Rule 2: Extroverted Observer Lead (Ne or Ni with E attitude)

```
[1] = EO (extroverted observer) — the lead function
[2] = ID (introverted decider)
[3] = ED (extroverted decider)
[4] = IO (introverted observer)
```

Oscillation: E/I/E/I ✓ **Axis opposition**: [1]/[4] observer ↔ [2]/[3] decider ✓

Rule 3: Introverted Decider Lead (Ti or Fi with I attitude)

```
[1] = ID (introverted decider) — the lead function
[2] = EO (extroverted observer)
[3] = IO (introverted observer)
[4] = ED (extroverted decider)
```

Oscillation: I/E/I/E ✓ **Axis opposition**: [1]/[4] decider ↔ [2]/[3] observer ✓

Rule 4: Extroverted Decider Lead (Te or Fe with E attitude)

```
[1] = ED (extroverted decider) — the lead function
[2] = IO (introverted observer)
[3] = EO (extroverted observer)
[4] = ID (introverted decider)
```

Oscillation: E/I/E/I ✓ **Axis opposition**: [1]/[4] decider ↔ [2]/[3] observer ✓

5.2 Critical Application Principle

The savior pair functions do NOT map directly to [1] and [2].

Instead:

1. Identify the **lead function type** (which STACK_ANCHORS rule applies)
2. Apply the rule to get [1] position requirement (attitude + observer/decider type)
3. Place the **lead function** at [1] (it must match the requirement)
4. For the **savior decider** function:
   - Identify its **attitude and axis type** (I/E and observer/decider)
   - Find which STACK_ANCHORS position matches that requirement
   - Place the savior decider there (may be [2], [3], or [4])
5. Derive remaining functions via **axis opposition** and **inverse pairings**
6. Verify **oscillation** and **relationship rules** hold

Example: Formal notation `MM - Se/Ti`

- Se is extroverted observer → STACK_ANCHORS extroverted observer lead applies
- Se[1] (matches EO requirement) ✓
- Ti is introverted decider (ID requirement is at [2])
- Ti[2] ✓
- [3] = ED (extroverted decider) → opposite axis from Ti = Fe ✓
- [4] = IO (introverted observer) → opposite axis from Se = Ni ✓
- Ordonnance: Se[1] - Ti[2] - Fe[3] - Ni[4] ✓

PART 6: COMMON NOTATION

6.1 Common Notation Structure

Format: Four lines, one per animal in priority order

```
(DirectionalityPrefix) [BracketRange] AxisLetters AnimalName = (m/f)Function1 +
(m/f)Function2
```

Example:

```
(Di) [1-2] SF Consume = (m)Fi + (f)Se
(Oe) [2-4] NT Play = (f)Ne + (m)Te
(Oi) [3-4] ST Blast = (f)Te + (m)Si
(Di) [1-3] NF Sleep = (m)Fi + (m)Si
```

Component 1: Directionality Prefix (Ordonnance Number + Function Type)

Format: (XY) where X = Ordonnance marker, Y = Observer/Decider type

Valid prefixes:

- **(Oi)** = Ordonnance[1 or 3 or 2 or 4] Introverted Observer (Si or Ni appears first)
- **(Oe)** = Ordonnance[1 or 3 or 2 or 4] Extroverted Observer (Se or Ne appears first)
- **(Di)** = Ordonnance[1 or 3 or 2 or 4] Introverted Decider (Ti or Fi appears first)
- **(De)** = Ordonnance[1 or 3 or 2 or 4] Extroverted Decider (Te or Fe appears first)

Selection Rule: Use the **type of the FIRST function** in the bracket range.

Example:

- Blast [3-4] with Si[3] + Te[4] → Si is introverted observer → **(Oi)**
- Play [2-4] with Fe[2] + Ne[4] → Fe is extroverted decider → **(De)**

Component 2: Bracket Range

Format: [X-Y] where X and Y are ordonnance positions

Valid ranges only:

- [1-2] (adjacent)
- [1-3] (non-adjacent, jumper only)
- [2-4] (non-adjacent, jumper only)

- [3-4] (adjacent)

Component 3: Axis Letters

Format: Two-letter pair from standardized axis notation

Standardized pairs (Keirsey temperaments—order is FIXED):

- **NT** = Intuition + Thinking
- **NF** = Intuition + Feeling
- **ST** = Sensation + Thinking
- **SF** = Sensation + Feeling

Critical rule: Axis letters do NOT reorder based on function sequence. If the animal contains intuition and thinking, it's **NT** regardless of which appears first.

Component 4: Animal Name

Valid animal names:

- Sleep, Blast, Consume, Play

Component 5: Modalized Function Pair

Format: (m/f)Function1 + (m/f)Function2

- **First function**: The one that appears first in ordonnance order
- **Second function**: The one that appears second in ordonnance order
- **Modality prefix**: (m) for masculine, (f) for feminine

Example: (f)Ne + (m)Te means feminine extroverted intuition + masculine extroverted thinking

---

6.2 What Common Notation Shows

Common notation makes explicit:

- ✓ The ordonnance numbering [1][2][3][4]
- ✓ The modality of each function
- ✓ Which animals contain which functions
- ✓ The priority order of animals
- ✓ The direction/type of each function (via directionality)
- ✓ The axis structure of each animal (via axis letters)

PART 7: CONVERSION ALGORITHM: FORMAL → COMMON

7.1 Step-by-Step Algorithm

INPUT: Formal Notation

Format: [Modality] - [Observer/Decider] - [AnimalStack] Example: `FF - Si/Ti - SB/P(C)`

PROCESSING STEPS

STEP 1: Parse the Lead Function and Identify STACK_ANCHORS Rule

```
Read the savior observer function from the formal notation
↓
Determine: Is it introverted or extroverted? Is it observer or decider?
↓
Match to correct STACK_ANCHORS rule
↓
Lock in the attitude pattern [I/E/I/E] or [E/I/E/I]
```

Example: Si (introverted observer) → STACK_ANCHORS introverted observer lead

- Pattern: [1]=IO | [2]=ED | [3]=ID | [4]=EO

STEP 2: Place Lead Function at [1]

```
The savior observer function ALWAYS goes to [1]
(It's the first differentiated function)
Verify it matches [1] requirement from STACK_ANCHORS ✓
```

STEP 3: Identify Savior Decider and Find Its Position

```
Read the savior decider function
↓
Determine its attitude (I/E) and type (observer/decider)
↓
Find which STACK_ANCHORS position matches that requirement
↓
Place savior decider there
```

Critical Insight: Savior decider may go to [2], [3], or [4] depending on its attitude/type, NOT automatically to [2].

Example: Savior decider = Ti (introverted decider)

- STACK_ANCHORS shows [2]=ED, [3]=ID, [4]=EO
- Ti is ID → Ti goes to [3]
- But if savior decider were Te (extroverted decider) → Te is ED → Te goes to [2]

STEP 4: Derive [2] and [3] via Axis Opposition

```
From [1], determine the axis: observer or decider?
↓
[2]/[3] must be on the OPPOSITE axis
↓
Use inverse pairings to find the functions:
  If [1] is Si → opposite axis observer functions use Si↔Ne pairing
  If [1] is Ti → opposite axis decider functions use Ti↔Fe pairing
↓
Apply STACK_ANCHORS attitude requirements to determine function polarity
```

STEP 5: Determine [4] via [1]/[4] Modality Pairing

```
From [1] function and modality, look up [4] in the [1]/[4] table
↓
[4] = same axis as [1], opposite polarity, opposite modality
```

STEP 6: Apply All Modalities

```
From modality pair (char_1 and char_2):
↓
Apply modality anchor to sensory functions:
  char_1 determines Si/Se modality
  inverse modality applies to Ne/Ni
↓
Apply modality anchor to extroverted deciders:
  char_2 determines Te/Fe modality
  inverse modality applies to Ti/Fi
```

Result: All four functions now have modality markers

STEP 7: Map Animals to Bracket Ranges

```
For each animal in the animal stack (in formal notation order):
↓
Identify its observer/decider attitude pair (IO/EO/ID/ED)
↓
Find which two functions match that pair:
  Sleep (IO+ID): find positions with IO and ID
  Blast (IO+ED): find positions with IO and ED
  Consume (EO+ID): find positions with EO and ID
  Play (EO+ED): find positions with EO and ED
↓
Determine bracket range [X-Y] (ascending order, always)
```

STEP 8: Write Common Notation

```
For each animal in the animal stack priority order:

[A] Determine directionality prefix from first function's type
[B] Write bracket range [X-Y]
[C] Write standardized axis letters (NT, NF, ST, or SF)
[D] Write animal name
[E] Write modalized function pair: (m/f)Function1 + (m/f)Function2

Output: (Prefix) [Range] AxisLetters AnimalName = (m/f)Func1 + (m/f)Func2
```

7.2 Worked Example: FF - Si/Ti - SB/P(C) → Common Notation

STEP 1: Lead = Si (introverted observer) → STACK_ANCHORS introverted observer lead

- [1]=IO | [2]=ED | [3]=ID | [4]=EO

STEP 2: Si[1] matches IO requirement ✓

STEP 3: Savior decider = Ti (introverted decider = ID type)

- STACK_ANCHORS shows [3]=ID
- Ti[3] ✓

STEP 4: Axis opposition

- [1]/[3] are on decider axis (Si is observer at [1], so we need opposite axis)
- Wait, [1] is observer, so [2]/[3] are on... No, [1] is observer.

- Actually: [1][4] are observer (Si and Ne), [2][3] are decider (Fe and Ti)
- [2] = ED requirement = Fe ✓
- [3] = ID requirement = Ti ✓

STEP 5: [4] via [1]/[4] modality pairing

- [1] = (f)Si from FF modality
- Looking up Si with (f): [4] = (m)Ne ✓

STEP 6: Apply modalities

- Sensory: (f)Si, (m)Ne
- Ext-decider: (f)Fe, (m)Ti (inverse)
- Result: 1Si - 2Fe - 3Ti - 4Ne

STEP 7: Map animals

- Sleep (IO+ID): Si[1] + Ti[3] = [1-3] ✓
- Blast (IO+ED): Si[1] + Fe[2] = [1-2] ✓
- Play (EO+ED): Ne[4] + Fe[2] = [2-4] ✓
- Consume (EO+ID): Ne[4] + Ti[3] = [3-4] ✓

STEP 8: Write common notation (animal stack order SB/P(C))

```
(Oi) [1-3] ST Sleep = (f)Si + (m)Ti
(Oi) [1-2] SF Blast = (f)Si + (f)Fe
(De) [2-4] NF Play = (f)Fe + (m)Ne
(Di) [3-4] NT Consume = (m)Ti + (m)Ne
```

PART 8: CONVERSION ALGORITHM: COMMON → FORMAL

8.1 Step-by-Step Algorithm

INPUT: Common Notation

Four lines showing animals with ordonnance positions and modalities

PROCESSING STEPS

STEP 1: Reconstruct Full Ordonnance from Common Notation

```
From common notation, each animal shows two functions at specific brackets
↓
List all four functions with their ordonnance positions and modalities
↓
Verify each function appears in exactly 2 animals
↓
Verify bracket ranges are valid: [1-2], [1-3], [2-4], [3-4]
```

Example: From `(Oi) [1-3] ST Sleep = (f)Si + (m)Ti`:

- Si[1] = (f)
- Ti[3] = (m) (Continue for remaining animals to complete ordonnance)

STEP 2: Identify the Lead Function

```
The function at [1] is the lead function
(Most differentiated, determines STACK_ANCHORS rule)
↓
Determine: Is it observer or decider? I or E?
```

STEP 3: Extract Modality Anchors

```
From the modalized ordonnance:
↓
Identify all sensory function modalities (Si/Se)
↓
Identify all extroverted decider modalities (Te/Fe)
↓
These are your char_1 and char_2
```

Example: (f)Si, (m)Ne → sensory modality = F

- (f)Fe, (m)Ti → ext-decider modality = F
- Modality pair: FF

STEP 4: Identify Savior Pair Functions

```
From the animal stack notation in common notation:
↓
Read which animals are in the savior pair (first two animals)
↓
Find which two functions appear in the first animal's bracket range
↓
These are your observer/decider pair
```

Example: If first animal is Sleep [1-3] = Si + Ti

- Savior observer = Si
- Savior decider = Ti

STEP 5: Determine Animal Stack

```
From common notation, read the animals in the order they appear
↓
Write them as [A1][A2]/[A3]([A4])
↓
A1 and A2 are savior (first two animals listed)
↓
A3 is first demon, A4 is last demon (in parentheses)
```

OUTPUT: Formal Notation

```
[Modality] - [SaverObserver/SaverDecider] - [AnimalStack]

Example: FF - Si/Ti - SB/P(C)
```

8.2 Worked Example: Common → Formal

INPUT (Common notation):

```
(Oi) [1-3] ST Sleep = (f)Si + (m)Ti
(Oi) [1-2] SF Blast = (f)Si + (f)Fe
(De) [2-4] NF Play = (f)Fe + (m)Ne
(Di) [3-4] NT Consume = (m)Ti + (m)Ne
```

STEP 1: Reconstruct ordonnance

- [1] (f)Si
- [2] (f)Fe
- [3] (m)Ti
- [4] (m)Ne

STEP 2: Lead function = (f)Si at [1] (introverted observer)

STEP 3: Extract modalities

- Sensory: (f)Si, (m)Ne → sensory modality = F
- Ext-decider: (f)Fe, (m)Ti → ext-decider modality = F
- Modality: FF

STEP 4: Savior pair from first animal (Sleep [1-3])

- Functions: Si + Ti
- Savior observer = Si
- Savior decider = Ti

STEP 5: Animal stack from order

- Sleep (first animal) → S
- Blast (second animal) → B
- Play (third animal) → P
- Consume (fourth animal) → C
- Stack: SB/P(C)

OUTPUT: FF - Si/Ti - SB/P(C)

PART 9: MASTERING PRINCIPLES (Summary)

9.1 The Mechanical Decision Tree

When you see formal notation [Modality] - [Observer/Decider] - [AnimalStack]:

1. **Identify lead type** → Which STACK_ANCHORS rule?
2. **Apply STACK_ANCHORS** → Get position requirements [I/E, observer/decider]
3. **Place lead at [1]** → Savior observer goes here
4. **Place savior decider** → Find position matching its attitude/type

5. **Derive opposite-axis functions** → Use inverse pairings and STACK_ANCHORS requirements
6. **Apply modality anchors** → 2 anchor points determine all 4 modalities
7. **Map animals to brackets** → Find observer/decider pairs in ordonnance
8. **Write common notation** → Directionality, brackets, axis letters, animals, modalities

---

9.2 Critical Insights

The Inverse Pairings Are Structural, Not Modality-Based

- Si ↔ Ne
- Se ↔ Ni
- Ti ↔ Fe
- Fi ↔ Te

These are FIXED. They do not change based on modality. They derive from the structure of consciousness and Jung's complementarity principle.

[1]/[4] Modality Pairing Is Deterministic

Once [1] is fixed (function + modality), [4] is mechanically determined. **No choice involved.**

Savior Pair Does Not Map to [1]/[2]

The savior pair tells you which two functions appear, but NOT which ordonnance positions they occupy. **Positions are determined by STACK_ANCHORS, not by "savior" status.**

Axis Opposition Is About Function Axes, Not Attitudes

[1]/[4] axis is opposite to [2]/[3] axis means:

- If [1]/[4] are on observer axis → [2]/[3] are on decider axis
- If [1]/[4] are on decider axis → [2]/[3] are on observer axis

This is structural, not a choice.

Animal Stack Reveals, Does Not Determine

The animal stack shows which observer/decider pairings exist in the ordonnance. **It does not create the ordonnance; it reflects it.**

PART 10: WORKED EXAMPLES (ALL 9 DRILLED EXAMPLES)

Example 1: MF - Ne/Te - PB/C(S)

Ordonnance: 1Ne - 2Fi - 3Te - 4Si

Common Notation:

```
(Oe) [1-3] NT Play = (f)Ne + (f)Te
(De) [3-4] ST Blast = (f)Te + (m)Si
(Oe) [1-2] NF Consume = (f)Ne + (m)Fi
(Di) [2-4] SF Sleep = (m)Fi + (m)Si
```

Key Learning: Extroverted observer lead with MF modality. Ne feminine, Fi masculine (inverse of Te feminine).

Example 2: FM - Si/Fe - BP/S(C)

Ordonnance: 1Si - 2Fe - 3Ti - 4Ne

Common Notation:

```
(Oi) [1-2] SF Blast = (f)Si + (m)Fe
(De) [2-4] NF Play = (m)Fe + (m)Ne
(Oi) [1-3] ST Sleep = (f)Si + (f)Ti
(Di) [3-4] NT Consume = (f)Ti + (m)Ne
```

Key Learning: Introverted observer lead with FM modality. Si feminine, Ne masculine (inverse of Si feminine).

Example 3: MM - Fe/Se - PB/C(S)

Ordonnance: 1Fe - 2Ni - 3Se - 4Ti

Common Notation:

```
(De) [1-3] SF Play = (m)Fe + (m)Se
(De) [1-2] SF Blast = (m)Fe + (f)Ni
(Oe) [3-4] ST Consume = (m)Se + (f)Ti
(Oi) [2-4] ST Sleep = (f)Ni + (f)Ti
```

Key Learning: Extroverted decider lead with MM modality. Axis opposition requires [2] to be introverted observer (Ni, not Si) because [1]/[3] are on sensation axis. The inverse pairing Se ↔ Ni is structural, not arbitrary.

Example 4: MM - Ne/Te - PB/S(C)

Ordonnance: 1Ne - 2Fi - 3Te - 4Si

Common Notation:

```
(Oe) [1-3] NT Play = (f)Ne + (m)Te
(De) [3-4] ST Blast = (m)Te + (m)Si
(Di) [2-4] SF Sleep = (f)Fi + (m)Si
(Oe) [1-2] NF Consume = (f)Ne + (f)Fi
```

Key Learning: Extroverted observer lead with MM modality. Modality inversions create feminine/masculine distribution across axes. **Critical point**: For MM modality, ext-decider is masculine, so int-decider must be feminine. Fi is introverted feeling, therefore (f)Fi.

Example 5: MM - Se/Ti - CS/P(B)

Ordonnance: 1Se - 2Ti - 3Fe - 4Ni

Common Notation:

```
(Oe) [1-2] ST Consume = (m)Se + (f)Ti
(Di) [2-4] ST Sleep = (f)Ti + (f)Ni
(Oe) [1-3] SF Play = (m)Se + (m)Fe
(De) [3-4] NF Blast = (m)Fe + (f)Ni
```

Key Learning: Extroverted observer lead (Se) but savior decider is Ti (introverted decider, not extroverted). Ti correctly goes to [2] per STACK_ANCHORS. [3] requires ED, which is opposite decider axis from Ti = Fe. Demonstrates that savior pair does NOT map to [1]/[2].

Example 6: FF - Fi/Se - CP/B(S)

Ordonnance: 1Fi - 2Se - 3Ni - 4Te

Common Notation:

```
(Di) [1-2] SF Consume = (m)Fi + (f)Se
(Oe) [2-4] ST Play = (f)Se + (f)Te
(Oi) [3-4] NT Blast = (m)Ni + (f)Te
(Di) [1-3] NF Sleep = (m)Fi + (m)Ni
```

Key Learning: Introverted decider lead with FF modality. Axis opposition (Fi[1]/Te[4] decider ↔ Se[2]/Ni[3] observer) is clear.

Example 7: FF - Fi/Se - CP/S(B)

Ordonnance: 1Fi - 2Se - 3Ni - 4Te

Common Notation:

```
(Di) [1-2] SF Consume = (m)Fi + (f)Se
(Oe) [2-4] ST Play = (f)Se + (f)Te
(Di) [1-3] NF Sleep = (m)Fi + (m)Ni
(Oi) [3-4] NT Blast = (m)Ni + (f)Te
```

Key Learning: Same ordonnance as Example 6, different animal stack order. Priority order changes, not structure.

Example 8: FM - Ti/Se - CS/B(P)

Ordonnance: 1Ti - 2Se - 3Ni - 4Fe

Common Notation:

```
(Di) [1-2] NT Consume = (f)Ti + (f)Se
(Di) [1-3] ST Sleep = (f)Ti + (m)Ni
(Oi) [3-4] SF Blast = (m)Ni + (m)Fe
(Oe) [2-4] NF Play = (f)Se + (m)Fe
```

Key Learning: Introverted decider lead (Ti) with FM modality. Axis opposition shows Ti[1]/Fe[4] decider paired with Se[2]/Ni[3] observer.

Example 9: FF - Si/Ti - SB/P(C)

Ordonnance: 1Si - 2Fe - 3Ti - 4Ne

Common Notation:

```
(Oi) [1-3] ST Sleep = (f)Si + (m)Ti
(Oi) [1-2] SF Blast = (f)Si + (f)Fe
(De) [2-4] NF Play = (f)Fe + (m)Ne
(Di) [3-4] NT Consume = (m)Ti + (m)Ne
```

Key Learning: Introverted observer lead (Si) with FF modality. Savior decider is Ti (introverted decider), correctly placed at [3] per STACK_ANCHORS.

PART 11: QUICK REFERENCE CHECKLISTS

Formal → Common Checklist

- [ ] Identify lead function type (observer/decider, I/E)
- [ ] Apply correct STACK_ANCHORS rule
- [ ] Place lead at [1], verify it matches [1] requirement
- [ ] Find savior decider's attitude/type, place it at matching STACK_ANCHORS position
- [ ] Use inverse pairings to derive remaining two functions
- [ ] Verify oscillation I/E/I/E holds
- [ ] Verify [1]/[4] and [2]/[3] relationships hold
- [ ] Apply modality anchors (char_1 and char_2)
- [ ] Map animals to bracket ranges
- [ ] Determine directionality prefix for each animal
- [ ] Write standardized axis letters (NT, NF, ST, SF)
- [ ] Write modalized function pairs
- [ ] Output in animal stack priority order

Common → Formal Checklist

- [ ] Reconstruct full ordonnance from all four animals
- [ ] Identify [1] function (lead)
- [ ] Extract modality anchors from modalized ordonnance
- [ ] Identify savior pair (observer/decider in first animal)
- [ ] Determine animal stack from order
- [ ] Verify all functions appear in exactly 2 animals
- [ ] Verify bracket ranges valid: [1-2], [1-3], [2-4], [3-4]
- [ ] Output as [Modality] - [Observer/Decider] - [AnimalStack]

PART 12: IMPLEMENTATION NOTES FOR LLMs

System Instructions for Mechanical Application

1. **Never infer function pairings.** Use only the fixed inverse pairings:
   - Si ↔ Ne, Se ↔ Ni, Ti ↔ Fe, Fi ↔ Te
2. **Never reorder axis letters.** Standardized pairs are NT, NF, ST, SF. Order is fixed.
3. **Always apply STACK_ANCHORS mechanically.** Do not attempt to shortcut via intuition.
4. **Verify oscillation and relationship rules** on every derivation.
5. **Remember: Savior pair ≠ [1]/[2].** Savior decider may be at [3] or [4].
6. **Modality is deterministic from two anchors.** No ambiguity once char_1 and char_2 are set.
7. **Bracket ranges are limited to four options.** If a range appears that isn't [1-2], [1-3], [2-4], or [3-4], stop and verify.
8. **Animal stack order is input—use it as-is.** Do not reorder based on internal logic.

PART 13: VALIDATION GATES

Before outputting common notation, verify:

- [ ] All four functions present with ordonnance numbers
- [ ] All four modalities (m or f) assigned
- [ ] Each function appears in exactly 2 animals
- [ ] All bracket ranges are valid
- [ ] Directionality prefixes match first function type in each range
- [ ] Axis letters are standardized (no custom ordering)
- [ ] Modality inversions follow the rules (if sensory F, then intuitive M)
- [ ] Oscillation rule holds: I/E/I/E or E/I/E/I
- [ ] [1]/[4] and [2]/[3] relationships verified

Before outputting formal notation, verify:

- [ ] Modality pair is valid (MF, FM, MM, or FF)
- [ ] Savior observer function matches [1]
- [ ] Savior decider function exists in ordonnance
- [ ] Animal stack animals match those in ordonnance
- [ ] Animal stack order is preserved from common notation
- [ ] All functions in ordonnance are accounted for in animals

CONCLUSION: READY FOR DEPLOYMENT

This SPR contains:

✓ Complete ontological foundations (Onto-Clean framework)
✓ Jung's complementarity principle and its mechanical implications
✓ All four STACK_ANCHORS rules
✓ Complete modality system with inversion rules
✓ Fixed inverse function pairings (structural, not modality-based)
✓ [1]/[4] and [2]/[3] deterministic logic
✓ Formal notation structure and semantics
✓ Common notation structure and semantics
✓ Complete formal → common conversion algorithm
✓ Complete common → formal conversion algorithm
✓ 9 worked examples covering all four lead types and multiple modality pairs
✓ Quick reference checklists
✓ Validation gates and implementation notes

This SPR should enable any LLM to convert between formal and common notation for any of the 512 OPS types mechanically and reliably.