

Week 04 Task 11

Ingest Logs into SIEM + Basic Searches

Candidate Name: Asad Ali
Reference Number: TBS-INT-2026-445
Submission Date: 09|11|2026
Submitted To: TechBiz Security

Table of Contents

1) Executive Summary 3
2) Ingest Logs into SIEM From Windows 3
    2.1) Run a basic search 5
    2.2) Filter a Failed logins and get a count 5
    2.3) Use a time range filter to view results 6
3) Ingest Logs into SIEM From Linux 6
    3.1) Run a basic search 7
    3.2) Filter a Failed logins and get a count 8
    3.3) Use a time range filter to view results 8
4) TryHackMe Room Intro to SIEM: 9
5) Conclusion 9

1) Executive Summary

This task focuses on log ingestion and basic search operations using Wazuh SIEM (Security Information and Event Management). The objective is to understand how logs can be collected, centralized, and monitored through a SIEM platform for security analysis. The practical work involves configuring log ingestion into Wazuh, performing basic searches, filtering failed login events, retrieving event counts, and applying time-range filters to examine results. This exercise provides hands-on experience with fundamental SIEM operations and demonstrates how Wazuh can be used to monitor and investigate security-related events.

2) Ingest Logs into SIEM From Windows

The Wazuh Windows agent is already configured to collect Security, System, and Application event logs. These configurations can be verified through the agent's **ossec.conf** file. The following steps demonstrate how to verify the existing log collection configuration..

Step 01: Execute the command shown below in PowerShell to open the Wazuh agent configuration file (**ossec.conf**) in Notepad in image below.




Step 02: The configuration file shows that the Security, System, and Application event channels are enabled for collection through the Wazuh agent. These logs are forwarded to the Wazuh Manager for centralized monitoring and analysis shown in image below.






The above figure shows a failed login attempt generated by entering an incorrect password on the Windows login screen. This test generates a failed authentication event that can subsequently be investigated through Wazuh.




The above figure shows After generating the failed login event, navigate to **Threat Hunting → Events** in the Wazuh Dashboard to investigate the collected security events.

2.1) Run a basic search




The above figure demonstrates the execution of a basic search query to retrieve security events associated with the Windows endpoint. The query returned 360 matching event records within the selected 24-hour time range. These records include different security-related activities generated by the Windows endpoint, providing an overview of the events monitored by Wazuh. The returned count represents matching event records rather than the number of security incidents or attacks.

2.2) Filter a Failed logins and get a count



The above figure demonstrates how Windows failed authentication events can be filtered using Event ID **4625**. The search returned one matching event, indicating a failed login attempt recorded by Wazuh.

2.3) Use a time range filter to view results




The above figure demonstrates the application of a time-range filter to investigate failed authentication events within a specific period. The search was restricted to events recorded between 11:00 AM and the current time, returning one matching event.


3) Ingest Logs into SIEM From Linux


The Wazuh Linux on Ubuntu agent was configured to collect authentication and system logs from the Ubuntu endpoint. The agent's **ossec.conf** configuration file was updated to include the relevant log sources, allowing Wazuh to forward these events to the Wazuh Manager for centralized monitoring and analysis.

Step 01: Execute the following command in the Ubuntu terminal to open the Wazuh agent configuration file (**ossec.conf**) using the Nano text editor.




Step 02: The configuration file shows that the **/var/log/auth.log** and **/var/log/syslog** files are configured for collection through the Wazuh Linux agent. These log sources contain authentication-related and system events, which are forwarded to the Wazuh Manager for centralized monitoring and analysis, as shown in the image below.






The above figure shows a failed login attempt generated by entering an incorrect password on the SSH login . This test generates a failed authentication event that can subsequently be investigated through Wazuh.

3.1) Run a basic search




The above figure demonstrates a basic search in the Wazuh Dashboard to retrieve security events collected from the Ubuntu endpoint. The results display events forwarded by the Wazuh Linux agent, confirming that the configured Linux log sources are being ingested and can be queried centrally for monitoring and analysis.

3.2) Filter a Failed logins and get a count




The above figure demonstrates how linux SSH failed authentication events can be filtered using keyword **"Failed password"**. The search returned one matching event, indicating a failed login attempt recorded by Wazuh.

3.3) Use a time range filter to view results



The above figure demonstrates the application of a time-range filter to investigate failed authentication events within a specific period. The search was restricted to events recorded from last 30 minutes returning one matched failed event.

4) TryHackMe Room Intro to SIEM:



In the above figure it is shown that I have completed the TryHackMe Room Introduction to SIEM. This task helped me to understand SIEM fundamentals, log management, log sources and ingestion, alerting processes and log analysis. This room also included practical lab work, strengthening my understanding of how SIEM solutions centralize logs and support security monitoring and investigation.

5) Conclusion

This task provided practical experience in ingesting and investigating logs from both Windows and Linux endpoints using Wazuh SIEM. On Windows, the Wazuh agent collected Security, System, and Application event logs, while the Ubuntu agent collected authentication and system logs from /var/log/auth.log and /var/log/syslog. After verifying log collection, basic searches were performed to review incoming events. Failed authentication attempts were then identified using Windows Event ID 4625 and the Linux keyword “Failed password”. Time-range filters were also applied to narrow the searches and examine events within specific periods. In addition, completing the TryHackMe Introduction to SIEM room strengthened my understanding of SIEM fundamentals, log sources, ingestion, alerting, and log analysis. Overall, this exercise improved my ability to use Wazuh for centralized log monitoring, event filtering, and basic security investigations across different operating systems.