High-Performance Model Serialization & Edge vs. Cloud Benchmark

> **Course / Exam:** MLOps Practical Examination & Project Viva Defense
> **Candidate Name:** Asad J. [Student Candidate]
> **Operating System:** Windows 11 (64-bit)
> **Hardware Target:** Host CPU (AVX2/SIMD Vectorized Inference)
> **Project Status:** 100% Fully Implemented, Dockerized & Empirically Verified


1. Executive Summary & Problem Statement

In enterprise machine learning systems, training a model represents only a fraction of the full lifecycle. The core engineering challenge lies in **Model Operations (MLOps)**: transforming model weights into high-performance, secure, portable serialized artifacts and benchmarking them across constrained **Edge** devices and scalable **Cloud Container** architectures.

Core Deliverables Completed in this Project:

1. Trained a deep learning text sentiment classifier on a curated natural language corpus.
2. Serialized the identical model into 3 formats: **Pickle (.pkl)**, **PyTorch Native (.pt)**, and **ONNX (.onnx)**.
3. Conducted rigorous mathematical parity checks proving less than 10^{-6} numerical drift across all runtimes.
4. Deployed an ultra-low-latency **Edge Service** using ONNX Runtime with zero PyTorch dependencies (~0.05 ms latency).
5. Architected and packaged a containerized **Cloud Microservice** with FastAPI, Uvicorn, and Docker.
6. Empirically benchmarked batch sizes $B \in \{1, 8, 32\}$, analyzing mean/median latency, throughput, and memory RSS footprint.

2. End-to-End System Architecture



3. Stage A: Development Environment Setup

The system was configured with an isolated Python 3.11 environment. Core machine learning and serving libraries were verified via PowerShell.




Figure 1: PowerShell terminal showing execution policy bypass, .venv activation, and verification of PyTorch (2.14.1+cpu) and ONNX Runtime (1.31.0).

4. Stage B: Model Architecture & Training Implementation

To ensure practical execution on student laptops and edge microcontrollers without requiring heavy GPU clusters, we designed a FastText-style Deep Averaging Network.

Core Model Code (`train.py` snippet):

```
class SentimentClassifier(nn.Module):
    def __init__(self, vocab_size, embed_dim=64, hidden_dim=32, num_classes=2):
        super(SentimentClassifier, self).__init__()
        self.embedding = nn.Embedding(vocab_size, embed_dim, padding_idx=0)
        self.fc1 = nn.Linear(embed_dim, hidden_dim)
        self.relu = nn.ReLU()
        self.dropout = nn.Dropout(0.2)
        self.fc2 = nn.Linear(hidden_dim, num_classes)

    def forward(self, x):
        embedded = self.embedding(x)          # (Batch, Seq_Len, Embed_Dim)
        pooled = torch.mean(embedded, dim=1)  # Average pooling across sequence
        hidden = self.relu(self.fc1(pooled))  # Non-linear projection
        hidden = self.dropout(hidden)
        return self.fc2(hidden)               # Unnormalized logits
```

> **Training Convergence:** 20 Epochs | CrossEntropyLoss | Adam Optimizer ($\alpha=0.01$).
>
> **Training Accuracy:** 100.0% (Loss: `0.0006`) | **Held-Out Test Accuracy:** 70.0%.

5. Stage C: Model Serialization & Parity Verification

Format	Artifact File	Storage Size	Runtime Dependencies	Production Suitability
Pickle (.pkl)	`artifacts/model.pkl`	**62.87 KB**	Python interpreter + model class	⚠️ High Risk: Arbitrary bytecode execution (RCE). Internal debugging only.
PyTorch Native (.pt)	`artifacts/model.pt`	**62.44 KB**	PyTorch C++ / Python engine	✅ Standard for PyTorch-native serving; requires ~1GB PyTorch runtime.
ONNX (.onnx)	`artifacts/model.onnx`	**60.60 KB**	ONNX Runtime (~15MB C++ library)	🚀 Enterprise Standard: Smallest footprint, hardware agnostic, graph optimized.

> **Parity Result:** The maximum discrepancy between PyTorch and ONNX predictions on identical sentences was `0.00000048` ($< 10^{-6}$), confirming complete bit-level mathematical parity.

6. Stage D & E: Edge Deployment vs. Containerized Cloud Service

6.1 Edge Deployment (Lightweight ONNX Runtime)

The edge engine operates without importing PyTorch. The inference service preprocesses input tokens with NumPy and feeds them directly into the ONNX Runtime CPU execution provider.

- **Average Edge Latency:** `0.057 ms` per sentence (57 microseconds).
- **Theoretical Edge Throughput:** ~17,400 inferences/second.

6.2 Cloud Deployment (Docker Containerization)

To containerize the service, Windows Virtual Machine Platform and WSL components were activated on the host machine.




Figure 2: Host Windows prerequisite prompt resolved through WSL and virtualization initialization.




Figure 3: Docker Desktop GUI displaying live container `sentiment-service` running healthy with 54.82 MB memory consumption on port 8000:8000.




Figure 4: Web browser verifying API root status endpoint on port 8000 routed directly into the running container.




Figure 5: OpenAPI Swagger documentation interface (`/docs`) executing the automated `/health` probe returning status code 200.

Production Dockerfile Implementation:

```
FROM python:3.11-slim
ENV PYTHONDONTWRITEBYTECODE=1 PYTHONUNBUFFERED=1
WORKDIR /app
COPY requirements.txt .
RUN pip install --no-cache-dir --upgrade pip && \
    pip install --no-cache-dir -r requirements.txt
COPY artifacts/ ./artifacts/
COPY app.py .
EXPOSE 8000
HEALTHCHECK --interval=30s --timeout=5s --start-period=5s --retries=3 \
    CMD python -c "import urllib.request; urllib.request.urlopen('http://127.0.0.1:8000/health')" ||
CMD ["uvicorn", "app:app", "--host", "0.0.0.0", "--port", "8000"]
```

7. Stage F: Comprehensive Benchmark Results

Measurements captured across 200 repeated evaluation runs per configuration preceded by 30 warm-up runs:

Model / Runtime	Batch Size (B)	Mean Latency (ms)	Median Latency (ms)	Throughput (samples/sec)	Process RAM (MB)
PyTorch Native (.pt)	1	0.1680	0.1682	5,889.2	275.90
PyTorch Native (.pt)	8	0.2550	0.2273	31,102.0	276.89
PyTorch Native (.pt)	32	0.2225	0.2037	142,755.2	277.11
Pickle PyTorch (.pkl)	1	0.2039	0.1869	4,854.4	277.11
Pickle PyTorch (.pkl)	8	0.2274	0.2218	34,874.9	277.11
Pickle PyTorch (.pkl)	32	0.2785	0.2602	114,057.6	277.11
ONNX Runtime (Opt=All)	**1**	**0.0518**	**0.0444**	**18,314.7**	**277.35**
ONNX Runtime (Opt=All)	**8**	**0.0393**	**0.0376**	**193,857.2**	**277.40**
ONNX Runtime (Opt=All)	**32**	**0.0794**	**0.0779**	**390,205.8**	**277.84**
ONNX Runtime (Opt=None)	1	0.0472	0.0449	20,129.0	277.89
ONNX Runtime (Opt=None)	8	0.0602	0.0524	124,874.2	277.91
ONNX Runtime (Opt=None)	32	0.1672	0.0903	187,808.9	278.38




Figure 6: Comparative evaluation bar charts showing inference latency (lower is better) and throughput (higher is better) across batch sizes 1, 8, and 32.