

# API Documentation

## TECHNICAL DOCUMENTATION

This document will provide instructions on how to quickly integrate MiMSMS communication services into various solutions by using MiMSMS REST API interface. Please use the Contents table for faster and easier navigation through HTTP API specifications, examples, and tutorials.

For detailed specifications, fully featured examples in various programming languages and interactive testing environment please visit our developer hub at:

[mim.digital](https://mim.digital)

### Base URL

Submit all requests to the base URL. All the requests are submitted thorough POST and some requests are GET method. Although you can use HTTP protocol, we strongly recommend you to submit all requests to MiMSMS SMS API over HTTPS so the traffic is encrypted and the privacy is ensured.

Base URL: <https://api.mimsms.com>

### Parameters

| Parameter       | Type     | Requirements                         | Description                                                                                                                                                                                  |
|-----------------|----------|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UserName        | String   | Mandatory                            | Your Username.                                                                                                                                                                               |
| Apikey          | String   | Mandatory                            | Your API Key.                                                                                                                                                                                |
| MobileNumber    | String   | Mandatory                            | Destination mobile number.                                                                                                                                                                   |
| CampaignId      | String   | Optional (Mandatory for Promotional) | Approved campaign ID of your promotional Bulk Messages.                                                                                                                                      |
| SenderName      | String   | Mandatory                            | Your registered sender id.                                                                                                                                                                   |
| TransactionType | String   | Mandatory                            | T: for transactional SMS P: for promotional SMS D: for dynamic SMS                                                                                                                           |
| Message         | String   | Mandatory                            | Your messages body.                                                                                                                                                                          |
| txnId           | String[] |                                      | Each message successfully submitted to MiMSMS platform is uniquely identified with the txnId. Furthermore, the Transaction ID can be used for checking delivery status or sent messages logs |

### Content-Type

MiMSMS SMS API supports JSON Content-Types and Accept criteria that should be specified in the header. If the Content-Type is not specified you will receive a general error. Depending which Accept type is chosen in the header for the request, the same one will be applied in the response.

Content-Type: [application/json](#)

### Authorization

We support basic authorization using a username and API Key.

#### Example:

Username: [you@example.com](#)

API Key: [XXXXXXXXXXXXXXXXXX](#)

## SEND SMS

In a few simple steps, we will explain how to send an SMS using [MiMSMS HTTP API](#).

Firstly, you'll need a valid MiMSMS account. When you [sign up for the account](#), your email address will set as your username

and the [API Key](#) can be generated from your Developer Option of MiM SMS Portal.

## Authorization Section:

The message will be sent only to a valid phone number (numbers), written in **international format** e.g.8801844909020. We strongly recommend using the **international format** without + (plus sign), followed by a *country code*, *network code* and the *subscriber number*. Phone numbers that are not recommend formatted may not work properly.

Now, you are ready to send your first SMS message using:

POST <https://api.mimsms.com/api/SmsSending/SMS>

The request body contains the message you wish to send with from, to and text parameters. Full **JSON request** is shown below:

```
1  {
2  "UserName": " you@example.com ",
3  "Apikey": " xxxxxxxxxxxxxxxxxxxxxx",
4  "MobileNumber": "88018xxxxxxx",
5  "CampaignId": "null",
6  "SenderName": "MiM Digital",
7  "TransactionType": "T",
8  "Message": " My first API SMS from MiM Digital"
9  }
```

## Send SMS (JSON Format)

After the "Send SMS" HTTP request was submitted to the MiMSMS SMS API, you will get a response containing some useful information. If everything went well, it should provide a **200 OK** response with message details in the response body.

Here is an example of a request for sending a single SMS:

POST /api/SmsSending/SMS

Host: api.mimsms.com

Content-Type: application/json

Accept: application/json

```
1  {
2  "UserName": " you@example.com ",
3  "Apikey": " xxxxxxxxxxxxxxxxxxxxxx",
4  "MobileNumber": "88018xxxxxxx",
5  "CampaignId": "null",
6  "SenderName": "MiM SMS",
7  "TransactionType": "T",
8  "Message": " My first API SMS from MiM Digital"
9  }
```

And the appropriate response is shown below:

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxnId": "10SY3FSZ7H4IH0U",
5  "responseResult": "SMS Send Successfully"
6  }
```

- Multiple numbers can be **separated by a comma only for promotional SMS**.
- **Sending promotional messages must require prior approval from the regulatory.**
- Each message successfully submitted to the **MIMSMS** platform is uniquely identified with the **trxnId**. Furthermore, the **Transaction ID** can be used for checking delivery status or sent message logs.
- **status** is the object that further describes the state of sent message. For a full list of available statuses, please check.

## Send One to Many SMS (JSON Format)

After the "Send SMS" HTTP request was submitted to the MiMSMS SMS API, you will get a response containing some useful information. If everything went well, it should provide a **200 OK** response with message details in the response body.

Here is an example of a request for sending a single SMS:

POST /api/SmsSending/OneToMany

Host: api.mimsms.com

Content-Type: application/json

Accept: application/json

```
1  {
2  "UserName": "you@example.com ",
3  "Apikey": "XXXXXXXXXXXXXXXXXXXX",
4  "MobileNumber": "88018xxxxxxx,88017xxxxxxx,88019xxxxxxx",
5  "CampaignId": "null",
6  "SenderName": "MiM SMS",
7  "TransactionType": "T",
8  "Message": "My first API SMS from MiM Digital"
9  }
```

And the appropriate response is shown below:

```
1 {
2   "statusCode": "200",
3   "status": "Success",
4   "txnId": "133585142743231481",
5   "responseResult": "SMS Send Successfully"
6 }
```

- Multiple numbers can be separated by a comma.
- Each message successfully submitted to MiSMS platform is uniquely identified with the **txnId**. Furthermore, the Transaction ID can be used for checking delivery status or sent message logs.
- **status** is the object that further describes the state of sent For a full list of available statuses, please check.

## Send Dynamic SMS (JSON Format)

Send specific messages to multiple destinations by calling one API method only once. Your request should be like this:

*POST / api/SmsSending/DSMS*

*Host: api.mimsms.com*

*Content-Type: application/json*

```
1 {
2   "UserName": "masum@mimsms.com",
3   "ApiKey": "XXXXXXXXXXXXXXXXXXXX",
4   "SenderName": "ABCD",
5   "TransactionType": "D",
6   "SmsData": [
7     {
8       "MobNumber": "8801844909020",
9       "Message": "Hello Dear Mohammad"
10    },
11    {
12      "MobNumber": "8801844909021",
13      "Message": "Hello Dear Abdur Rahman"
14    }
15  ]
16 }
```

This way you'll send specific SMS messages to multiple destinations in a single request. The response you get will contain information about all the messages sent out:

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1 {
2   "statusCode": "200",
3   "status": "Success",
4   "txnId": "ZICU7TMXV9B6ZG8_C28",
5   "responseResult": "SMS Send Successfully"
6 }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1 {
2   "statusCode": "200",
3   "status": "Success",
4   "txnId": "ZICU7TMXV9B6ZG8_C28",
5   "responseResult": "SMS Send Successfully"
6 }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxnId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxnId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxnId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

*HTTP/1.1 200 OK*

*Content-Type: application/json*

```
1  {
2  "statusCode": "200",
3  "status": "Success",
4  "trxnId": "ZICU7TMXV9B6ZG8_C28",
5  "responseResult": "SMS Send Successfully"
6  }
```

## Send SMS (Using HTTP Plain, Query)

similar to the previous method, this method allows sending SMS messages passing parameters directly as query string variables.

Here is an example of a HTTP Plain (POST) request for sending a single SMS: The URL used to send messages using HTTP GET or POST is:

Access point: <https://api.mimsms.com/api/SmsSending/Send?>