Kingdom of Saudi Arabia
Ministry of Education
Umm Al-Qura University
031

المملكة العربية السعودية
وزارة التعليم
جامعة أم القرى
٠٣١

AI Project

Project Title: Bank Marketing Dataset

Group members:

Name	ID
Rawan Qader	445013919
Asail hamdan	445000051
Atheer Alfahmi	443001237
Hajer Sayah	445013975

Task Distribution Table:

Name	Task Distribution
Rawan Qader	OneR & AdaBoostM1 & Bagging & personal analysis for each model I used & conclusion
Asail hamdan	BayesNet & Naive Bayes & IBK & Introduction: The purpose project, the learning objective and summary of the report The graph and its description
Atheer Alfahmi	Random forest, Stacking, SMO. The decription about the dataset, personal anysis for the models.
Hajer Sayah	REPT TREE & JRip & J48 & Arranging comparison tables & data cleaning & reference

supervision by: Dr.Amirah Alharbi

1– Introduction:

1.1 Purpose of the Project:

The purpose of this project is to apply machine learning techniques to better understand the factors that influence whether a customer will subscribe to a term deposit. By analyzing patterns in the data, we aim to help improve marketing strategies and target the right customers more effectively.

1.2 Learning Objectives:

This project provides an opportunity to strengthen our practical skills in working with real data. We'll focus on cleaning and preparing the dataset, experimenting with different machine learning models, and evaluating their performance in a meaningful way Additionally, it will help us build our ability to interpret model results, understand feature importance, and draw conclusions that support business decision-making. We'll also gain experience handling class imbalance, selecting suitable models, and visualizing results skills that are essential when working with real-world marketing data.

1.3 Summary of the Report:

This project uses a marketing dataset from a Portuguese bank to predict whether a customer will subscribe to a term deposit. We applied machine learning techniques, focused on classification models, and evaluated their performance. The goal is to support better marketing decisions using data-driven insights.

2– The Goal

The ultimate goal is to build a predictive model that can accurately classify customers into two groups: those who are likely to subscribe and those who are not. This can support banks in making smarter marketing decisions and improving their campaign results

3– About the Dataset

The dataset selected for this project is the **Bank Marketing** Dataset obtained from the **UCI Machine Learning Repository**.
This dataset contains comprehensive customer-related data collected from various banking campaigns, encompassing:

- **Demographic Details**: Age, job, marital status, and education level of the clients.
- **Socioeconomic Factors**: Information such as housing loan status, personal loan, and account balance, which may influence financial behavior.
- **Contact Information**: Details about the type and outcome of marketing contacts.
- **Campaign Details**: Records of marketing efforts (e.g., number of contacts, days since last contact, and duration of contact) provided to the clients.
- **Outcomes**: Information on whether the client subscribed to a term deposit.

With data from **thousands of clients**, this dataset is structured to support detailed statistical and machine-learning analyses. It serves as a valuable resource for researchers aiming to identify customer segments, predict campaign outcomes, and generate actionable insights for improving bank marketing strategies. The dataset contains a total of **11162 instances** and **17 attributes**, such as age, job, and other personal or contact details of the clients.

Feature	Description
Age	Age of the client (numeric).
Job	Type of job (e.g., admin., technician, entrepreneur, etc.).
Marital	Marital status of the client (e.g., married, single, divorced).
Education	Education level of the client (e.g., primary, secondary, tertiary, unknown).
Default	Whether the client has credit in default (yes/no).
Balance	Average yearly balance in euros (numeric).
Housing	Whether the client has a housing loan (yes/no).
Loan	Whether the client has a personal loan (yes/no).
Contact	Type of communication contact (e.g., cellular, telephone).
Day	Last contact day of the month (numeric).
Month	Last contact month of the year (e.g., jan, feb, mar, etc.).
Duration	Duration of the last contact in seconds (numeric).
Campaign	Number of contacts performed during this campaign (numeric).
Pdays	Number of days since the client was last contacted (-1 means not previously).
Previous	Number of contacts performed before this campaign (numeric).
Poutcome	Outcome of the previous marketing campaign (e.g., success, failure, unknown).

Deposit	Whether the client subscribed to a term deposit (yes/no).

Data Cleaning



Missing values,outliers, and class imbalance were among the first problems in ,the data that impacted the model's quality.To guarantee the best data quality we thus went through a cleaning phase with WEKA filters

Unsupervised → Attribute → ReplaceMissingValues

It is filter to fill in the blanks in columns like default, education, and employment.
The filter substitutes a suitable statistical value (like the median or the most frequent value) for missing values.

Unsupervised → Attribute → Discretize

It was applied to numeric columns such as age, balance, duration, pdays, and campaign to classify them into categories. It helped improve the accuracy of classification algorithms such as J48 and Naive Bayes.

Supervised → Instance → Resample

The target class deposit was unbalanced (mostly "no"), which impacted the model's performance.
Resample was used to generate a balanced distribution between the two classes, which helped improve recall for the "yes" class and made the model more predictive.

• REPT TREE



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	89.8495%	0 .886	0.915	0.900	0.946
NO		0.912	0.882	0.897	0.946
Avg		0.899	0.898	0.898	0.946

Classified as	a	b
a = yes	5107	474
b = no	659	4922

Personal Analysis:

The model had a lot of freedom to explore every branch since the tree could be constructed with no pruning (**Unpruned** = True). Noise from tiny data points was decreased by increasing **MinNumObj**. A **factor** of 0.25

provided an appropriate balance between complexity and ease of use & It was the highest accuracy.

- **JRip**



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	86.9647	0 .845	0.905	0.874	0.902
NO		0.898	0.834	0.865	0.902
Avg		0.871	0.870	0.869	0.902

Confusion Matrix		
Classified as	a	b
a = yes	5050	531
b = no	924	4657

Personal Analysis:

I used a small **MinNo** value (2) to allow the model to generate more precise and detailed rules. This is very useful when I have data with a specific pattern for a small class, such as "yes." A few **optimizations** (2) helped reduce training time while maintaining performance. Choosing 3 **Folds** is a good balance between speed and accuracy.

- **J48**



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	89.4195%	0 .882	0.910	0.896	0.951
NO		0.907	0.879	0.893	0.951
Avg		0.895	0.894	0.894	0.951

Confusion Matrix		
Classified as	a	b
a = yes	5076	505
b = no	676	4905

Personal Analysis:

In order to give the model a detailed depth, I reduced **MinNo** to 1. I allowed the tree to use deep structures to find every detail in the data by setting a large **MaxDepth** (50). Because the number of **folds 3** allowed for internal validation of the model, this modification improved the classification ability without overfitting.

- **BayesNet**



AUC ROC	F1-Score	Recall	Precision	Accuracy	Class
0.160	0.850	0.846	0 .690	84.4831%	Yse
0.150	0.840	0.844	0.690		NO
0.155	0.848	0.845	0.690		Avg

	Matrix	Confusion
b	a	Classified as
4742	839	a = yes
4688	893	b = no

Personal Analysis:

I modified the **estimator** from **0.5 to 2.0** to give the model more flexibility in handling the data, and I also changed the **search algorithm from K2 to TAN**, which improved the network structure and boosted accuracy. I kept all other settings unchanged, and these simple adjustments led to better performance for our complex dataset.

• NaiveBayes



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	78 .5701%	0 .572	0.780	0.758	0.187
NO		0.572	0.791	0.813	0.242
Avg		0.572	0.786	0.786	0.214

	Matrix	Confusion
b	a	Classified as
4230	1351	a = yes
1041	4540	b = no

Personal Analysis:

I experimented with several parameter settings in the Naive Bayes classifier, and found that disabling the **kernel estimator (setting it from true to false)** significantly improved performance. By keeping all other default settings unchanged, this simple adjustment led to a more accurate and stable model for our dataset.

• IBK



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	94.3917%	0 .888	0.944	0.948	0.060
NO		0.888	0.944	0.940	0.052
Avg		0.888	0.944	0.944	0.056

	Matrix	Confusion
b	a	Classified as
5290	291	a = yes
335	5246	b = no

Personal Analysis:

gave the best performance **K values (1, 2, 3, 4, and 8) and found that K = 8** I tested multiple **changed the distance weighting from "no distance weighting" to** for our dataset. I also

which helped the model give more importance to closer neighbors. **,”“weight by 1/distance**
All other settings were kept as default. This configuration not only improved accuracy but in terms of (BayesNet two algorithms (Naive Bayes and previous also outperformed the .overall performance

- **OneR**



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	71.5463%	0 .708	0.734	0.721	0.715
NO		0.724	0.697	0.710	0.715
Avg		0.716	0.715	0.715	0.715

	Matrix	Confusion
b	a	Classified as
1487	4094	a = yes
3892	1689	b = no

Personal Analysis:

OneR gave an accuracy of 71.5463% with the default minBucketSize – 6. Changing it to 2 or 10, and adjusting batchSize had no effect. OneR is simple and fast but limited, as it builds rules using only one attribute.

• AdaBoostM1



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	95.9595%	0 .955	0.965	0.960	0.982
NO		0.964	0.954	0.959	0.977
Avg		0.960	0.960	0.960	0.973

	Matrix	Confusion
b	a	Classified as
197	5384	a = yes
5327	254	b = no

Personal Analysis:

The default accuracy was 71.6269% with numIterations = 10. Increasing to 50 improved accuracy to 81.3922% and to 83.0138% with 100. The biggest jump came

when switching the base classifier to J48, reaching 95.9595%. NumIterations controls how many boosting rounds are done; using J48 made the model much stronger.

• Bagging



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	91.6592%	0 .892	0.940	0.919	0.966
NO		0.944	0.005	0.914	0.966
Avg		0.910	0.917	0.917	0.966

	Matrix	Confusion
b	a	Classified as
291	5290	a = yes
4941	640	b = no

Personal Analysis:

Bagging achieved 91.6592% accuracy using J48 as the base classifier, with 100 Iterations and a bag size of 100%. It builds multiple models on different subsets of data and averages their results, improving accuracy and reducing overfitting. It was one of the most effective models in the project.

• SMO



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	84.5458%	0 .846	0.845	0.845	0.915
NO		0.845	0.846	0.845	0.915
Avg		0.845	0.845	0.845	0.915

	Matrix	Confusion
b	a	Classified as
864	4717	a = yes
4720	861	b = no

Personal anlysis :

I used the RBF kernel to help the model find more complex patterns in the data. I set C to 1.0 for a good balance between accuracy and simplicity. I turned on calibration

to get better probability results. I also set epsilon and tolerance to 0.001to make training faster. These changes helped the model perform better overall

• Stacking



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	94.8396%	0 .951	0.946	0.948	0.969
NO		0.946	0.951	0.949	0.969
Avg		0.948	0.948	0.948	0.969

	Matrix	Confusion
b	a	Classified as
304	5277	a = yes
5309	272	b = no

Personal anlysis :

I used a stacking method that combines J48, Naive Bayes, and IBK classifiers to improve overall accuracy. On top of them, I added JRip as a meta-classifier to generate easy-to-follow

rules. The model reached 94.8% accuracy using 10-fold cross-validation and performed well for both “yes” and “no” outcomes. Even with multiple classifiers, it was fast and efficient, building the model in just a few seconds.

. Random forest



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	96.2014%	0 .955	0.969	0.962	0.994
NO		0.969	0.955	0.962	0.994
Avg		0.962	0.962	0.962	0.994

	Matrix	Confusion
b	a	Classified as
172	5409	a = yes
5329	252	b = no

Personal anlysis :

I used the RandomForest model with 100 trees to help find detailed patterns in the data, especially for the "yes" class. I tested it using 10-fold cross-validation and got a high

accuracy of 96.2%. The model was also very good at telling the difference between the classes. Even with these detailed settings, it trained quickly.

- **ZeroR**



Class	Accuracy	Precision	Recall	F1-Score	AUC ROC
Yse	49.991%	0 .500	0.900	0.643	0.500
NO		0.500	0.100	0.167	0.500
Avg		0.500	0.500	0.405	0.500

Matrix		Confusion
b	a	Classified as
559	5022	a = yes
558	5023	b = no

Hajer algorithms:

Name	Accuracy
REPT TREE	89.8495 %
JRip	86.9647
J48	89 .4195%
The Best One is REPT TREE	

Asail algorithms:

Name	Accuracy
BayesNet	84.4831 %
NaiveBayes	78.5701
IBK	94 .3917%
The Best One is IBK	

Rawan algorithms:

Name	Accuracy
OneR	71.5463 %
AdaBoostM1	95.9595%
Bagging	91 .6592%
The Best One is Bagging	

Atheer algorithms:

Name	Accuracy
SMO	84.5458 %
Stacking	94.8396%

Random forest	96 .2014%
The Best One is Random Forest	

Name	Accuracy
REPT TREE	89.8495 %
IBK	94 .3917%
Random forest	96 .2014%
AdaBoostM1	95.9595%
ZeroR	49.991%
The Best One is Random Forest	



The Random Forest algorithm outperformed other models in this project because it combines the results of multiple decision trees built randomly with resampling, which reduces bias and improves the model's generalization ability. Thanks to the diversity of features in the bank dataset—demographic, economic, and contact-related—Random Forest was able to capture complex patterns and achieve the highest accuracy of 96.2%.

Conclusion:

Through this project, we were able to explore and analyze real-world data from banking marketing campaigns using various machine learning techniques. The models applied helped us evaluate the key factors influencing whether customers subscribe to term deposits. We enhanced model performance by handling missing values, discretizing numerical data, and balancing class distribution.
The results showed that the **Random Forest** algorithm achieved the highest accuracy of 96.2014%, making it a powerful tool for supporting data-driven marketing decisions. This project not only improved our technical skills but also deepened our understanding of applying machine learning in real business contexts

reference:

https://www.kaggle.com/datasets/janiobachmann/bank-marketing-dataset?resource=download&select=bank.csv

https://machinelearningmastery.com/how-to-handle-missing-values-in-machine-learning-data-with-weka/

https://www.tutorialspoint.com/weka/weka_classifiers.htm

https://www.geeksforgeeks.org/introduction-to-weka-key-features-and-applications/

https://www.youtube.com/playlist?list=PL9FfW__Sm3pIyyakq22P2mMi82neT2LWS&si=RaWBtUHxXxRo8Vw-

https://www.youtube.com/playlist?list=PL86JZGzAEh4ud3JaPNvU3EFD_Z22peVSH&si=cgEujXx5-u8POJMh