

Partner Data API

Base URL: `https://sandbox.octaneobit.com/orb/api/octanev4/partner`

Read-only endpoints. All GET. All JSON. Results are automatically scoped to your account — you don't need to pass a site ID.

1. Authentication

Send your token in the `Authorization` header on every request:

```
Authorization: Bearer YOUR_TOKEN_HERE
```

Watch the spacing. Exactly one space after "Bearer". Two spaces breaks it silently.

2. The 4 endpoints

Endpoint	What it returns	Required params
<code>/fuelstations</code>	Your fuel stations	none
<code>/pumps</code>	Pumps, with nozzles included	none
<code>/fuelsales</code>	Fuel sale transactions	none
<code>/merchants</code>	Merchant / company records	none

GET `/fuelstations`

```
curl "https://sandbox.octaneobit.com/orb/api/octanev4/partner/fuelstations" \
-H "Authorization: Bearer YOUR_TOKEN_HERE"
```

GET `/pumps`

```
curl "https://sandbox.octaneobit.com/orb/api/octanev4/partner/pumps" \
-H "Authorization: Bearer YOUR_TOKEN_HERE"
```

Optional: `?fuelStationId=` to filter to one station (value must be base64, see below).

GET `/fuelsales`

```
curl "https://sandbox.octaneobit.com/orb/api/octanev4/partner/fuelsales" \
-H "Authorization: Bearer YOUR_TOKEN_HERE"
```

Optional: `?fuelStationId=`, `&pump=`, `&pumpNozzleId=` (each value base64-encoded).

GET `/merchants`

```
curl "https://sandbox.octaneobit.com/orb/api/octanev4/partner/merchants" \
-H "Authorization: Bearer YOUR_TOKEN_HERE"
```

3. Filter values must be base64-encoded

If you add any filter (like `fuelStationId=`), encode the value first. Plain text will not match.

```
# bash
echo -n "FS018" | base64

# python
base64.b64encode(b"FS018").decode()

# node
Buffer.from("FS018").toString("base64")

# powershell
[Convert]::ToBase64String([Text.Encoding]::UTF8.GetBytes("FS018"))
```

4. Response format

```
{
  "status": "success",
  "message": "...",
  "data": [ /* rows */ ],
  "pagination": {
    "total_records": 42,
    "page_count": 3,
    "current_page": 1,
    "page_size": 20
  }
}
```

5. Pagination & sorting (optional, plain text — no encoding)

Param	Example
<code>pageNo</code>	<code>?pageNo=2</code>
<code>pageSize</code>	<code>?pageSize=50</code> (max 2000, default 20)
<code>orderBy</code>	<code>?orderBy=saleDate</code>
<code>orderType</code>	<code>?orderType=DESC</code>

6. Errors

Status	Meaning
403	Bad, missing, or expired token
500	Server error

```
{
  "status": "unauthorized",
  "message": "Invalid signature"
}
```

Questions or need a token? Contact us directly — don't share tokens over email/chat that isn't secure.