

# numpy file input/output, matplotlib

## numpy file input/output

- so far we've been generating values in code to fill arrays
- in reality you load data from disk, and save results (and figures) back to disk
- two broad types of files: **text** and **binary**
  - **text files** are familiar, easy to view in a plain text editor, just a bunch of printable characters
    - what's a printable char? basically any available on your keyboard
    - like any other data, these chars are stored in bytes in memory and on disk
    - computers have to agree on which bytes represent which chars
    - encoding is used to map byte values to characters
    - standard encoding is ASCII: American Standard Code for Information Interchange
    - ASCII uses 1 byte per character, but only uses the first 128 integer values (0 to 127) to represent various characters, plus outdated "characters" that controlled direct output to printers and communications with old modems
    - see [ASCII-Conversion-Chart.pdf](#)
    - a newer increasingly common encoding is UTF-8, an extension of ASCII that can encode many more characters from more languages
    - in a text file, if you want to save the number `100`, you need to save 3 characters to disk (one `1`, two `0`s), so this takes up 3 bytes of space.
      - in reality, file sizes are usually rounded up to the nearest multiple of 4 KB
    - what's the smallest integer data type that can represent `100`? How many bytes does it take up?
  - **binary files** are much more space efficient for storing numbers, faster to load/save, but require a hexadecimal ("hex") editor to view them directly
    - trying to open a binary file with a plain text editor will either show a bunch of nonsense text, or it will refuse to open it at all
    - open-source hex editors:
      - windows, mac and linux: [wxHexEditor](#)
      - windows: [HexEdit](#) [WinHex](#), mac: [Hex Fiend](#), linux: [ghex](#)
    - mostly you load/save them programmatically anyway, no need to directly edit them
  - which file type to use depends on your data source, and your data size
  - for large numeric data sets, like images or electrophysiology, binary files are critical, text files aren't appropriate
  - text files are really just a subset of binary files
- **text files**: loading/saving arrays
  - this involves loading the entire file into a big string, splitting the string up into lots of substrings (based on separators and line endings), then converting each substring into a numeric value
  - `np.loadtxt(fname)` - load from a text file, interpret as an array
    - use the `delimiter=','` kwarg to handle e.g. comma separated values, see `test_1D.csv`
    - `test1D = np.loadtxt('test1D.csv', delimiter=',')` - interprets text file as comma separated values
    - dtype defaults to float64 for safety. to force int:
    - use the `dtype` kwarg to force some other dtype, e.g. `dtype=np.int64`
    - `test2D = np.loadtxt('test2D.csv', delimiter=',')` - 2D array!
  - `np.savetxt(fname, a)` - save to a text file
    - use the `delimiter=','` kwarg to create comma separated values
    - `np.savetxt('test1D.txt', test1D)`
    - int vs float dtype information can be lost using the above, `fmt=%g` kwarg helps
    - binary files handles dtype better...

- **binary files:** loading/saving arrays

- `np.load(fname)` - from a binary `.npy` file
  - `V = np.load('V.npy')` - load some fake voltage data
  - `t = np.load('t.npy')` - load corresponding timepoints
  - also loads `.npz` files, which are just `.zip` files containing multiple `.npy` files
- `np.save('V2', V*2)` - to a binary `.npy` file
- `np.savez()` & `np.savez_compressed()` - save multiple arrays to an uncompressed or compressed `.npz` file (just a `.zip` file)

```
np.savez('Vt', V=V, t=t) # save both arrays to .npz, pass as kwargs
d = np.load('Vt.npz') # load from .npz, returns ~ dict
V, t = d['V'], d['t'] # index into dict to get the values
```

- reading and writing binary MATLAB `.mat` files
  - `scipy.io.loadmat()` and `scipy.io.savemat()` functions in the `scipy` package
  - read and writes using a dictionary, where each key:value pair is the `variable_name:variable_value`. Variable values are typically arrays

```
import scipy.io
d = scipy.io.loadmat('Vt.mat')
V, t = d['V'], d['t'] # extract voltage and time from dict
d2 = {}
d2['V'] = V*2 # modify voltage
d2['t'] = t
scipy.io.savemat('Vt2.mat', d2) # save new voltage data to new file
```

- for loading/saving from/to **any** binary file (not just `.npy` or `.mat`):
  - `a = np.fromfile()`
  - `a.tofile()`
  - watch out: you'll have to interpret the `dtype` and `shape` yourself, not ideal

## numpy file input/output exercises:

1. Create an array `a = np.arange(10)`, and save it to a text file named `exercise.txt` using `np.savetxt()`. What folder will it be saved to? How can you check in IPython?
2. Open the file in your text editor. Does it look the way you'd expect? Resave it using the `fmt` kwarg (keyword argument), e.g. try `fmt='%g'` to format it as a general number that should look OK for both int and floats.
3. In your text editor, change the `9` to a `99`. Save it.
4. Create an array named `b` by loading in the data from `exercise.txt` using `np.loadtxt()`. Compare the contents of arrays `a` and `b`. Is `b` an integer array as you'd expect? Find a way to force `np.loadtxt()` to give you an integer array.
5. Save `a` again, but this time to a binary file named `exercise.npy` using `np.save()`
6. Create an array named `c` by loading in the data from `exercise.npy` using `np.load()`. Compare the contents of arrays `a` and `c`

## plotting with matplotlib (MPL)

- main plotting library for python, others exist, but often based on MPL
- typical usage: `import matplotlib.pyplot as plt`
  - now all the common plotting functions are available as `plt.something`
- line plots:

- let's create a data array using `np.linspace()` to get a set of evenly spaced time points, and then `np.sin()` or `np.cos()` to create sinusoids as a function of time

```
t = np.linspace(0, 4*np.pi, 100) # 100 evenly spaced timepoints, 2 cycles
s = np.sin(t) # calculate sine as a function of t
plt.plot(t, s) # plot points in t on x-axis vs. points in s on y-axis
```

- compare `np.linspace(start, stop, npoints)` with `np.arange(start, stop, step)`
    - `np.linspace()`
      - lets you specify the number of points you want to get out
      - defaults to end-inclusive ( `stop` value is included in the output)
    - `np.arange()`
      - lets you specify the step size between points
      - is end-exclusive ( `stop` value is excluded in the output)
  - `np.logspace()` is the logarithmic equivalent of `np.linspace()`, it creates requested number of points equally spaced on a logarithmic scale instead of linear scale
- if no existing plot window ("figure") exists, a new one will pop up, or will be embedded in your jupyter notebook
  - figure toolbar:
    - pan tool:
      - left button drag: pan horizontally and vertically
      - right button drag: zoom horizontally and vertically
      - back and forward buttons skip between recent views
      - home button returns to default view
      - magnifying glass: zoom to rectangle
        - left button drag to zoom to rectangle
        - right button drag to zoom out the view to fit rectangle
    - configure subplots: change borders, spacing between subplots (if any)
      - tight layout button minimizes borders and maximizes data, good for saving to file
    - edit plot params: titles, labels, limits, scales, line and marker formatting
    - save: save figure to disk, typically `.pdf` or `.png`
  - everything you can do interactively with the toolbar, you can also do programmatically in code
    - `plt.xlim()`, `plt.ylim()`, `plt.xlabel()`, `plt.ylabel()`, `plt.title()`
    - `plt.savefig()`

- add another line to the same plot:

```
c = np.cos(t) # calculate cosine as a function of the same timebase t
plt.plot(t, c) # plot points in t on x-axis vs. points in c on y-axis
```

- by default, MPL adds the new line plot to the existing figure's axes, using a new colour
- create a new empty figure with `plt.figure()`
- multiple figures open? new plots go on most recently used figure
- `plt.close()` closes current figure, `plt.close('all')` closes all figures
- to specify color, marker type and line style with kwargs:
  - `color: 'red', 'green', 'blue'` etc.

- `marker: '.', 'o', 'x', '+', '*',` or `''` to turn off markers
- `linestyle: 'solid', 'dashed', 'dotted',` or `''` to turn off the line
- e.g. `plt.plot(t, c, color='red', marker='.', linestyle='solid')` `plt.plot(t, c, 'r.-')` is shorthand for the above
- check `plt.plot?` docstring for more options, including color, marker and line abbreviations
- `label` kwarg lets you give each line a name, which then shows up if you call `plt.legend()`

- histogram plot is useful for getting a graphical overview of all the values in your data

- `a = np.random.random(1000) - 0.5`
- `plt.hist(a)`, defaults to 10 bins
- `plt.hist(a, bins=100)` specifies desired number of bins
- `plt.hist(a, bins='auto')` automatically finds an reasonable number of bins
- can also specify the exact locations of all the bin edges by passing a sequence instead of a scalar to `bins`:
  - `plt.hist(a, bins=np.arange(-1, 1, 0.1))`
- similar plotting options as for `plt.plot()` for controlling e.g. colour

- anatomy of a MPL figure

- <http://matplotlib.org/examples/showcase/anatomy.html>
- axes, markers, lines, labels, titles, legends, ticks, grids, spines
- spines are inexplicably complicated to toggle, for now use:
  - `plt.gca().spines['top'].set_visible(False)`
  - `plt.gca().spines['right'].set_visible(False)`
  - can set them permanently in your `matplotlibrc` file (see below)
- `plt.axhline(y)` let's plot a horizontal line at `y` across the whole plot
- `plt.axvline(x)` does the same for a vertical line
- `plt.text(x, y, s)` places text `s` at `(x, y)`
- `plt.Circle(xy, radius)` draws a circle at `(x, y)`
- `plt.annotate()` should let you "annotate" a particular `(x, y)` point with some text (currently broken?)

- other kinds of plots:

- scatterplots: `plt.scatter()`
- error bars: `plt.errorbar()`
- bar plots: `plt.bar()`

- plotting issues:

```
import matplotlib.pyplot as plt
plt.plot() # should pop up a figure window with axes
```

- figures not popping up in **ipython**?
  - turn on interactive mode by calling `plt.ion()`
  - permanently enable interactive mode in matplotlib settings file:
    - linux: `~/.config/matplotlib/matplotlibrc`
    - mac + windows: `~/.matplotlib/matplotlibrc`
    - uncomment `#interactive: False` line and set to `True` instead
- figures in **jupyter** not automatically displaying inline?
  - type `%matplotlib inline` in a cell, all cells that follow will do inline plots
  - make this setting permanent in `~/.ipython/ipython_config.py` file
  - uncomment `#c.InteractiveShellApp.matplotlib = None` line and set to `'inline'`
  - for interactive plotting in jupyter, type `%matplotlib notebook`

- make this setting permanent with `c.InteractiveShellApp.matplotlib = 'notebook'` in `ipython_config.py` file
  - NOTE: this only works in more recent versions of matplotlib/jupyter?
  - quite a bit slower than interactive plots in ipython
- missing toolbar?
  - set `toolbar : toolbar2` in `matplotlibrc` file
- the button for "edit axes/curve/image params" in figure window might be missing, not sure why

## matplotlib exercises:

1. Create three arrays:
  - i. an array `t` that represents time in seconds, from `0` to `4*np.pi` in steps of `0.1`.
  - ii. an array `s` that is two times the sine of `t`
  - iii. an array `c` that is the cosine of `t` plus `2`
2. Plot both `s` and `c` vs. `t` in the same figure, using `plt.plot()`
3. Give the figure a title, and label the x axis `time (s)` and the y axis `position`, and save it to disk as either a PNG or a PDF. If you're missing the save button on the toolbar, try the `plt.savefig()` function
4. Create a new figure with `plt.figure()` and repeat 2., but now give each line a label by specifying the `label` kwarg when calling `plt.plot()`. Then call `plt.legend()` to add a legend to the figure. Now label it and save it as in 3.
5. Put all of your plot commands for 4. in a script named `plot_exercise.py` so you don't have to keep re-typing them. Make sure it runs when you type `run plot_exercises.py` in IPython.
6. By default, your above plots (should) have markers (dots) at each data point. Repeat 4 (use your script) but now turn off the markers by specifying the `marker` kwarg (hint: give it an empty string).
7. Initialize a second figure in your script with `plt.figure()` after your code for the first figure.
8. Plot a histogram of `s` with 20 bins, and give it a label during the `plt.hist()` call. Now do the same for `c`. Label the x and y axes and add a legend.
9. Add two `plt.savefig()` calls in the appropriate places in your script to automatically save your two figures to file every time the script is run. Give the files the names `plot_example.png` and `hist_example.png` respectively. What folder will these files be saved to by default? What happens when you run the script multiple times?

## more matplotlib

- MATLAB style vs. OOP style:
  - we've learned the MATLAB "procedural" style of plotting:

```
import matplotlib.pyplot as plt
t = np.linspace(0, 4*np.pi, 100) # 100 evenly spaced timepoints, 2 cycles
s = np.sin(t) # calculate sine as a function of t
c = np.cos(t) # calculate cosine as a function of t
plt.plot(t, s) # plot points in t on x-axis vs. points in s on y-axis
plt.plot(t, c) # plot cosine as well
```

- MPL also has an alternative, more Pythonic, object-oriented programming (OOP) style, with very similar commands
- first, you explicitly create a figure and an axes
- `f, ax = plt.subplots()` - by default creates a new figure with one set of x-y axes, and returns objects representing them
  - notice the `s` in `plt.subplots()`, `plt.subplot()` is a slightly different MATLAB-style procedural command which you shouldn't need to use
- now, we can do most of our plot commands as methods of this particular axes `ax`:
  - `ax.plot(t, s)`
  - common formatting commands in OOP style:

- `ax.set_xlim()`, `ax.set_ylim()`, `ax.set_xlabel()`, `ax.set_ylabel()`, `ax.set_title`
- compare with MATLAB style:
  - `plt.xlim()`, `plt.ylim()`, `plt.xlabel()`, `plt.ylabel`, `plt.title()`, `plt.legend()`
- OOP style is slightly more wordy, but much more explicit, gives better control over multiple figures
- `spines` are more easily accessible through the OOP interface:
  - `ax.spines['top'].set_visible(False)`
  - `ax.spines['right'].set_visible(False)`
- with multiple figures and axes open, we can refer to them directly by name, no longer have to worry about which is the "current" figure:
- `f2, ax2 = plt.subplots()`
- `ax2.hist(s)` - plot a histogram of `sin(t)` this time
- to clear a particular axes: `ax.clear()`
- if you created your figures/axes with the MATLAB style commands:
  - use `f = plt.gcf()` to get a reference to the current figure
  - use `ax = plt.gca()` to get a reference to the current axes

- subplots: create multiple axes in a single figure

- `f, axs = plt.subplots(nrows=2, ncols=2)`
- `axs` is now a 2D array, choose your axes by indexing into `axs` with row and col indices:
  - `axs[0, 1].plot(t, s)` # plot `s` vs. `t` in axes in 1st row 2nd column
  - `axs[1, 0].plot(t, c, color='r')` # plot `c` vs. `t` in red in axes in 2nd row 1st column
- optional kwargs `sharex`, `sharey`

```
plt.close('all')
f1, ax1 = plt.subplots(2, 1, sharex=True, sharey=False) # ax1 is 1D array
ax1[0].plot(t, s) # plot s vs. t
ax1[1].plot(t, c, color='r') # plot c vs. t in red, shared x axis with sin plot
f2, ax2 = plt.subplots(2, 1, sharex=True, sharey=False) # ax2 is 1D array
ax2[0].hist(s) # plot hist of s
ax2[1].hist(c, color='r') # plot hist of c in red, shared x axis with sin hist
```

- change the name of a figure, i.e. its window title bar and its default filename in the save dialog box:

```
f1.canvas.set_window_title('time series')
f2.canvas.set_window_title('histograms')
```

- some other kinds of plots:

- scatterplots:
  - `ax.scatter(x, y)` - very similar to `ax.plot()`
    - allows each point to be formatted differently (colour, marker, size)
    - defaults to not drawing a line between points
- errorbar plot
  - `ax.errorbar(x, y, yerr=5, xerr=2)` - again similar to `a.plot()`, but with errorbars
- bar charts
  - `ax.bar(left, height)` - vertical bars, `left` and `height` are sequences
  - `ax.bar(bottom, width)` - horizontal bars