


Chapter 9: Memory Management

■ Logical vs. Physical Address Space

- ☞ The concept of a logical *address space* that is bound to a separate *physical address space* is central to proper memory management.
 - 📄 *Logical address* – generated by the CPU; also referred to as *virtual address*.
 - 📄 *Physical address* – address seen by the memory unit.
- ☞ Logical and physical addresses are the same in compile-time and load-time address-binding schemes; logical (virtual) and physical addresses differ in execution-time address-binding scheme.

Memory-Management Unit (MMU)


- Hardware device that maps virtual to physical address.
- In MMU scheme, the value in the relocation register is added to every address generated by a user process at the time it is sent to memory.
- The user program deals with *logical* addresses; it never sees the *real* physical addresses.



Dynamic relocation using a relocation register

Swapping


- A process can be *swapped* temporarily out of memory to a *backing store*, and then brought back into memory for continued execution.
- Backing store – fast disk large enough to accommodate copies of all memory images for all users; must provide direct access to these memory images.
- *Roll out, roll in* – swapping variant used for priority-based scheduling algorithms; lower-priority process is swapped out so higher-priority process can be loaded and executed.
- Major part of swap time is transfer time; total transfer time is directly proportional to the *amount* of memory swapped.
- Modified versions of swapping are found on many systems, i.e., UNIX, Linux, and Windows.



Schematic View of Swapping

Contiguous Allocation


- Main memory usually into two partitions:
 - ☞ Resident operating system, usually held in low memory with interrupt vector.
 - ☞ User processes then held in high memory.
- Single-partition allocation
 - ☞ Relocation-register scheme used to protect user processes from each other, and from changing operating-system code and data.
 - ☞ Relocation register contains value of smallest physical address; limit register contains range of logical addresses – each logical address must be less than the limit register.



Contiguous Allocation (Cont.)

■ Multiple-partition allocation

- ☞ *Hole* – block of available memory; holes of various size are scattered throughout memory.
- ☞ When a process arrives, it is allocated memory from a hole large enough to accommodate it.
- ☞ Operating system maintains information about:
a) allocated partitions b) free partitions (hole)



Dynamic Storage-Allocation Problem

How to satisfy a request of size n from a list of free holes.

- **First-fit:** Allocate the *first* hole that is big enough.
- **Best-fit:** Allocate the *smallest* hole that is big enough; must search entire list, unless ordered by size. Produces the smallest leftover hole.
- **Worst-fit:** Allocate the *largest* hole; must also search entire list. Produces the largest leftover hole.

First-fit and best-fit better than worst-fit in terms of speed and storage utilization.

Fragmentation

- **External Fragmentation** – total memory space exists to satisfy a request, but it is not contiguous.
- **Internal Fragmentation** – allocated memory may be slightly larger than requested memory; this size difference is memory internal to a partition, but not being used.
- Reduce external fragmentation by compaction
 - ☞ Shuffle memory contents to place all free memory together in one large block.
 - ☞ Compaction is possible *only* if relocation is dynamic, and is done at execution time.
 - ☞ I/O problem
 - 📄 Latch job in memory while it is involved in I/O.
 - 📄 Do I/O only into OS buffers.

Non- Contiguous Paging


- Logical address space of a process can be noncontiguous; process is allocated physical memory whenever the latter is available.
- Divide physical memory into fixed-sized blocks called **frames** (size is power of 2, between 512 bytes and 8192 bytes).
- Divide logical memory into blocks of same size called **pages**.
- Keep track of all free frames.
- To run a program of size n pages, need to find n free frames and load program.
- Set up a page table to translate logical to physical addresses.
- Internal fragmentation.

Address Translation Scheme

- Address generated by CPU is divided into:


- ☞ *Page number (p)* – used as an index into a *page table* which contains base address of each page in physical memory.

- ☞ *Page offset (d)* – combined with base address to define the physical memory address that is sent to the memory unit.




Address Translation Architecture


Paging Example



Paging Example



Free Frames



Before allocation

After allocation

Implementation of Page Table

- Page table is kept in main memory.
- *Page-table base register* (PTBR) points to the page table.
- *Page-table length register* (PRLR) indicates size of the page table.
- In this scheme every data/instruction access requires two memory accesses. One for the page table and one for the data/instruction.
- The two memory access problem can be solved by the use of a special fast-lookup hardware cache called *associative memory* or *translation look-aside buffers* (TLBs)

Associative Memory


■ Associative memory – parallel search

Page #	Frame #

Address translation (A' , A'')

- ☞ If A' is in associative register, get frame # out.
- ☞ Otherwise get frame # from page table in memory

Paging Hardware With TLB




Effective Access Time

- Associative Lookup = ε time unit
- Assume memory cycle time is 1 microsecond
- Hit ratio – percentage of times that a page number is found in the associative registers; ration related to number of associative registers.
- Hit ratio = α
- Effective Access Time (EAT)

$$\begin{aligned} \text{EAT} &= (1 + \varepsilon) \alpha + (2 + \varepsilon)(1 - \alpha) \\ &= 2 + \varepsilon - \alpha \end{aligned}$$

Memory Protection

- Memory protection implemented by associating protection bit with each frame.
- *Valid-invalid* bit attached to each entry in the page table:
 - ☞ “valid” indicates that the associated page is in the process’ logical address space, and is thus a legal page.
 - ☞ “invalid” indicates that the page is not in the process’ logical address space.



Valid (v) or Invalid (i) Bit In A Page Table

Page Table Structure


- Hierarchical Paging
- Hashed Page Tables
- Inverted Page Tables

Hierarchical Page Tables

- Break up the logical address space into multiple page tables.
- A simple technique is a two-level page table.


Two-Level Paging Example

- A logical address (on 32-bit machine with 4K page size) is divided into:
 - ☞ a page number consisting of 20 bits.
 - ☞ a page offset consisting of 12 bits.
- Since the page table is paged, the page number is further divided into:
 - ☞ a 10-bit page number.
 - ☞ a 10-bit page offset.
- Thus, a logical address is as follows:




where p_1 is an index into the outer page table, and p_2 is the displacement within the page of the outer page table.

Two-Level Page-Table Scheme



Address-Translation Scheme


- Address-translation scheme for a two-level 32-bit paging architecture



Hashed Page Tables


- Common in address spaces > 32 bits.
- The virtual page number is hashed into a page table. This page table contains a chain of elements hashing to the same location.
- Virtual page numbers are compared in this chain searching for a match. If a match is found, the corresponding physical frame is extracted.

Hashed Page Table



Inverted Page Table

- One entry for each real page of memory.
- Entry consists of the virtual address of the page stored in that real memory location, with information about the process that owns that page.
- Decreases memory needed to store each page table, but increases time needed to search the table when a page reference occurs.
- Use hash table to limit the search to one — or at most a few — page-table entries.



Inverted Page Table Architecture


Shared Pages

■ Shared code

- ➞ One copy of read-only (reentrant) code shared among processes (i.e., text editors, compilers, window systems).
- ➞ Shared code must appear in same location in the logical address space of all processes.

■ Private code and data


- ➞ Each process keeps a separate copy of the code and data.
- ➞ The pages for the private code and data can appear anywhere in the logical address space.



Shared Pages Example


Segmentation

- Memory-management scheme that supports user view of memory.
- A program is a collection of segments. A segment is a logical unit such as:
 - ☞ **main program,**
 - ☞ **procedure,**
 - ☞ **function,**
 - ☞ **method,**
 - ☞ **object,**
 - ☞ **local variables,**
 - ☞ **global variables,**
 - ☞ **common block,**
 - ☞ **stack,**
 - ☞ **symbol table,**
 - ☞ **arrays**




User's View of a Program

Logical View of Segmentation




user space



physical memory space

Segmentation Architecture

- Logical address consists of a two tuple: $\langle \text{segment-number}, \text{offset} \rangle$,
- *Segment table* – maps two-dimensional physical addresses; each table entry has:
 - ☞ *base* – contains the starting physical address where the segments reside in memory.
 - ☞ *limit* – specifies the length of the segment.
- *Segment-table base register (STBR)* points to the segment table's location in memory.
- *Segment-table length register (STLR)* indicates number of segments used by a program; segment number s is legal if $s < \text{STLR}$.



Segmentation Hardware


Segmentation Architecture (Cont.)

- Relocation.
 - ☞ dynamic
 - ☞ by segment table
- Sharing.
 - ☞ shared segments
 - ☞ same segment number
- Allocation.
 - ☞ first fit/best fit
 - ☞ external fragmentation

Segmentation Architecture (Cont.)

- Protection. With each entry in segment table associate:
 - ☞ validation bit = 0 \Rightarrow illegal segment
 - ☞ read/write/execute privileges
- Protection bits associated with segments; code sharing occurs at segment level.
- Since segments vary in length, memory allocation is a dynamic storage-allocation problem.
- A segmentation example is shown in the following diagram

Example of Segmentation



Sharing of Segments

