

Public

```
<svg xmlns="http://www.w3.org/2000/svg" width="1200" height="1200" fill="none"><rect
width="1200" height="1200" fill="#EAEAEA" rx="3"/><g opacity=".5"><g opacity=".5"><path
fill="#FAFAFA" d="M600.709 736.5c-75.454 0-136.621-61.167-136.621-136.62 0-75.454 61.167-
136.621 136.621-136.621 75.453 0 136.62 61.167 136.62 136.621 0 75.453-61.167 136.62-136.62
136.62Z"/><path stroke="#C9C9C9" stroke-width="2.418" d="M600.709 736.5c-75.454 0-
136.621-61.167-136.621-136.62 0-75.454 61.167-136.621 136.621-136.621 75.453 0 136.62 61.167
136.62 136.621 0 75.453-61.167 136.62-136.62 136.62Z"/></g><path stroke="url(#a)" stroke-
width="2.418" d="M0-1.209h553.581" transform="scale(1 -1) rotate(45 1163.11 91.165)"/>
<path stroke="url(#b)" stroke-width="2.418" d="M404.846 598.671h391.726"/><path
stroke="url(#c)" stroke-width="2.418" d="M599.5 795.742V404.017"/><path stroke="url(#d)"
stroke-width="2.418" d="m795.717 796.597-391.441-391.44"/><path fill="#fff" d="M600.709
656.704c-31.384 0-56.825-25.441-56.825-56.824 0-31.384 25.441-56.825 56.825-56.825 31.383
0 56.824 25.441 56.824 56.825 0 31.383-25.441 56.824-56.824 56.824Z"/><g clip-
path="url(#e)"><path fill="#666" fill-rule="evenodd" d="M616.426 586.58h-
31.434v16.176l3.553-3.554.531-.531h9.068l.074-.074 8.463-8.463h2.565l7.18 7.181V586.58Zm-
15.715 14.654 3.698 3.699 1.283 1.282-2.565 2.565-1.282-1.283-5.2-5.199h-6.066l-5.514
5.514-.073.073v2.876a2.418 2.418 0 0 0 2.418 2.418h26.598a2.418 2.418 0 0 0 2.418-2.418v-
8.317l-8.463-8.463-7.181 7.181-.071.072Zm-19.347 5.442v4.085a6.045 6.045 0 0 0 6.046
6.045h26.598a6.044 6.044 0 0 0 6.045-6.045v-7.108l1.356-1.355-1.282-1.283-.074-.073v-
17.989h-38.689v23.43l-.146.146.146.147Z" clip-rule="evenodd"/></g><path stroke="#C9C9C9"
stroke-width="2.418" d="M600.709 656.704c-31.384 0-56.825-25.441-56.825-56.824 0-31.384
25.441-56.825 56.825-56.825 31.383 0 56.824 25.441 56.824 56.825 0 31.383-25.441 56.824-
56.824 56.824Z"/></g><defs><linearGradient id="a" x1="554.061" x2="-.48" y1=".083" y2=".087"
gradientUnits="userSpaceOnUse"><stop stop-color="#C9C9C9" stop-opacity="0"/><stop
offset=".208" stop-color="#C9C9C9"/><stop offset=".792" stop-color="#C9C9C9"/><stop
offset="1" stop-color="#C9C9C9" stop-opacity="0"/></linearGradient><linearGradient id="b"
x1="796.912" x2="404.507" y1="599.963" y2="599.965" gradientUnits="userSpaceOnUse">
<stop stop-color="#C9C9C9" stop-opacity="0"/><stop offset=".208" stop-color="#C9C9C9"/>
<stop offset=".792" stop-color="#C9C9C9"/><stop offset="1" stop-color="#C9C9C9" stop-
opacity="0"/></linearGradient><linearGradient id="c" x1="600.792" x2="600.794"
y1="403.677" y2="796.082" gradientUnits="userSpaceOnUse"><stop stop-color="#C9C9C9"
stop-opacity="0"/><stop offset=".208" stop-color="#C9C9C9"/><stop offset=".792" stop-
color="#C9C9C9"/><stop offset="1" stop-color="#C9C9C9" stop-opacity="0"/>
</linearGradient><linearGradient id="d" x1="404.85" x2="796.972" y1="403.903" y2="796.02"
gradientUnits="userSpaceOnUse"><stop stop-color="#C9C9C9" stop-opacity="0"/><stop
offset=".208" stop-color="#C9C9C9"/><stop offset=".792" stop-color="#C9C9C9"/><stop
offset="1" stop-color="#C9C9C9" stop-opacity="0"/></linearGradient><clipPath id="e"><path
fill="#fff" d="M581.364 580.535h38.689v38.689h-38.689z"/></clipPath></defs></svg>
```

Allow: /

User-agent: Bingbot

Allow: /

User-agent: Twitterbot

Allow: /

User-agent: facebookexternalhit

Allow: /

User-agent: *

Allow: /

src

```
import * as React from "react";
```

```
import * as AccordionPrimitive from "@radix-ui/react-accordion";
```

```
import { ChevronDown } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
const Accordion = AccordionPrimitive.Root;
```

```
const AccordionItem = React.forwardRef<
```

```
  React.ElementRef<typeof AccordionPrimitive.Item>,
```

```

React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>

>(({ className, ...props }, ref) => (

  <AccordionPrimitive.Item ref={ref} className={cn("border-b", className)} {...props} />

));

AccordionItem.displayName = "AccordionItem";

const AccordionTrigger = React.forwardRef<

  React.ElementRef<typeof AccordionPrimitive.Trigger>,

  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>

>(({ className, children, ...props }, ref) => (

  <AccordionPrimitive.Header className="flex">

    <AccordionPrimitive.Trigger

      ref={ref}

      className={cn(

        "flex flex-1 items-center justify-between py-4 font-medium transition-all hover:underline
        [&[data-state=open]>svg]:rotate-180",

        className,

      )}

      {...props}

    >

      {children}

    <ChevronDown className="h-4 w-4 shrink-0 transition-transform duration-200" />

  </AccordionPrimitive.Trigger>

</AccordionPrimitive.Header>

));

AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName;

```

```

const AccordionContent = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Content
    ref={ref}
    className="overflow-hidden text-sm transition-all data-[state=closed]:animate-accordion-up data-[state=open]:animate-accordion-down"
    {...props}
  >
    <div className={cn("pb-4 pt-0", className)}>{children}</div>
  </AccordionPrimitive.Content>
));

```

```

AccordionContent.displayName = AccordionPrimitive.Content.displayName;

```

```

export { Accordion, AccordionItem, AccordionTrigger, AccordionContent };

```

```

import * as React from "react";

```

```

import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog";

```

```

import { cn } from "@lib/Utils";

```

```

import { buttonVariants } from "@components/ui/button";

```

```

const AlertDialog = AlertDialogPrimitive.Root;

```

```
const AlertDialogTrigger = AlertDialogPrimitive.Trigger;
```

```
const AlertDialogPortal = AlertDialogPrimitive.Portal;
```

```
const AlertDialogOverlay = React.forwardRef<
```

```
  React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
```

```
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
```

```
>(({ className, ...props }, ref) => (
```

```
  <AlertDialogPrimitive.Overlay
```

```
    className={cn(
```

```
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
    ref={ref}
```

```
  />
```

```
));
```

```
AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName;
```

```
const AlertDialogContent = React.forwardRef<
```

```
  React.ElementRef<typeof AlertDialogPrimitive.Content>,
```

```
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
```

```
>(({ className, ...props }, ref) => (
```

```
  <AlertDialogPortal>
```

```
    <AlertDialogOverlay />
```

```

<AlertDialogPrimitive.Content
  ref={ref}

  className={cn(
    "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-from-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
    className,
  )}
  {...props}
/>

</AlertDialogPortal>

));

AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName;

const AlertDialogHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
  <div className={cn("flex flex-col space-y-2 text-center sm:text-left", className)} {...props} />
);

AlertDialogHeader.displayName = "AlertDialogHeader";

const AlertDialogFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
  <div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)} {...props} />
);

```

```
AlertDialogFooter.displayName = "AlertDialogFooter";
```

```
const AlertDialogTitle = React.forwardRef<  
  React.ElementRef<typeof AlertDialogPrimitive.Title>,  
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>  
>(({ className, ...props }, ref) => (  
  <AlertDialogPrimitive.Title ref={ref} className={cn("text-lg font-semibold", className)}  
    {...props} />  
));
```

```
AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName;
```

```
const AlertDialogDescription = React.forwardRef<  
  React.ElementRef<typeof AlertDialogPrimitive.Description>,  
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>  
>(({ className, ...props }, ref) => (  
  <AlertDialogPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground",  
    className)} {...props} />  
));
```

```
AlertDialogDescription.displayName = AlertDialogPrimitive.Description.displayName;
```

```
const AlertDialogAction = React.forwardRef<  
  React.ElementRef<typeof AlertDialogPrimitive.Action>,  
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>  
>(({ className, ...props }, ref) => (  
  <AlertDialogPrimitive.Action ref={ref} className={cn(buttonVariants(), className)}  
    {...props} />  
));
```

```
AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName;
```

```
const AlertDialogCancel = React.forwardRef<  
  React.ElementRef<typeof AlertDialogPrimitive.Cancel>,  
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>  
>(({ className, ...props }, ref) => (  
  <AlertDialogPrimitive.Cancel  
    ref={ref}  
    className={cn(buttonVariants({ variant: "outline" }), "mt-2 sm:mt-0", className)}  
    {...props}  
  />  
));
```

```
AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName;
```

```
export {  
  AlertDialog,  
  AlertDialogPortal,  
  AlertDialogOverlay,  
  AlertDialogTrigger,  
  AlertDialogContent,  
  AlertDialogHeader,  
  AlertDialogFooter,  
  AlertDialogTitle,  
  AlertDialogDescription,  
  AlertDialogAction,  
  AlertDialogCancel,
```



```

};

import * as React from "react";

import { cva, type VariantProps } from "class-variance-authority";

import { cn } from "@lib/utils";

const alertVariants = cva(
  "relative w-full rounded-lg border p-4 [>svg~*]:pl-7 [>svg+div]:translate-y-[-3px] [>svg]:absolute [>svg]:left-4 [>svg]:top-4 [>svg]:text-foreground",
  {
    variants: {
      variant: {
        default: "bg-background text-foreground",
        destructive: "border-destructive/50 text-destructive dark:border-destructive [>svg]:text-destructive",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  },
);

```

```

const Alert = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement> & VariantProps<typeof alertVariants>
>(({ className, variant, ...props }, ref) => (

```

```
<div ref={ref} role="alert" className={cn(alertVariants({ variant }), className)} {...props} />

));

Alert.displayName = "Alert";

const AlertTitle = React.forwardRef<HTMLParagraphElement,
React.HTMLAttributes<HTMLHeadingElement>>(

  ({ className, ...props }, ref) => (

    <h5 ref={ref} className={cn("mb-1 font-medium leading-none tracking-tight", className)}
    {...props} />

  ),

);

AlertTitle.displayName = "AlertTitle";

const AlertDescription = React.forwardRef<HTMLParagraphElement,
React.HTMLAttributes<HTMLParagraphElement>>(

  ({ className, ...props }, ref) => (

    <div ref={ref} className={cn("text-sm [&_p]:leading-relaxed", className)} {...props} />

  ),

);

AlertDescription.displayName = "AlertDescription";

export { Alert, AlertTitle, AlertDescription };

import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio";

const AspectRatio = AspectRatioPrimitive.Root;

export { AspectRatio };
```

```
import * as React from "react";

import * as AvatarPrimitive from "@radix-ui/react-avatar";

import { cn } from "@lib/utils";

const Avatar = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Root
    ref={ref}
    className={cn("relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full",
  className)}
    {...props}
  />
));

Avatar.displayName = AvatarPrimitive.Root.displayName;

const AvatarImage = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Image>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Image>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Image ref={ref} className={cn("aspect-square h-full w-full", className)}
  {...props} />
));

AvatarImage.displayName = AvatarPrimitive.Image.displayName;
```

```

const AvatarFallback = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Fallback>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Fallback>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Fallback
    ref={ref}
    className={cn("flex h-full w-full items-center justify-center rounded-full bg-muted",
  className)}
    {...props}
  />
));

AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName;

export { Avatar, AvatarImage, AvatarFallback };

import * as React from "react";

import { cn } from "@lib/utils";

const Card = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>
(({ className, ...props }, ref) => (
  <div ref={ref} className={cn("rounded-lg border bg-card text-card-foreground shadow-sm",
  className)} {...props} />
));

Card.displayName = "Card";

const CardHeader = React.forwardRef<HTMLDivElement,
React.HTMLAttributes<HTMLDivElement>>(

```

```
({ className, ...props }, ref) => (  
  <div ref={ref} className={cn("flex flex-col space-y-1.5 p-6", className)} {...props} />  
),  
);
```

```
CardHeader.displayName = "CardHeader";
```

```
const CardTitle = React.forwardRef<HTMLParagraphElement,  
React.HTMLAttributes<HTMLHeadingElement>>(  
  ({ className, ...props }, ref) => (  
    <h3 ref={ref} className={cn("text-2xl font-semibold leading-none tracking-tight",  
className)} {...props} />  
  ),  
);
```

```
CardTitle.displayName = "CardTitle";
```

```
const CardDescription = React.forwardRef<HTMLParagraphElement,  
React.HTMLAttributes<HTMLParagraphElement>>(  
  ({ className, ...props }, ref) => (  
    <p ref={ref} className={cn("text-sm text-muted-foreground", className)} {...props} />  
  ),  
);
```

```
CardDescription.displayName = "CardDescription";
```

```
const CardContent = React.forwardRef<HTMLDivElement,  
React.HTMLAttributes<HTMLDivElement>>(  
  ({ className, ...props }, ref) => <div ref={ref} className={cn("p-6 pt-0", className)}  
  {...props} />,  
);
```

```
CardContent.displayName = "CardContent";
```

```
const CardFooter = React.forwardRef<HTMLDivElement,  
React.HTMLAttributes<HTMLDivElement>>(  
  
  ({ className, ...props }, ref) => (  
  
    <div ref={ref} className={cn("flex items-center p-6 pt-0", className)} {...props} />  
  
  ),  
  
);
```

```
CardFooter.displayName = "CardFooter";
```

```
export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent };
```

```
import * as React from "react";
```

```
import useEmblaCarousel, { type UseEmblaCarouselType } from "embla-carousel-react";
```

```
import { ArrowLeft, ArrowRight } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
import { Button } from "@components/ui/button";
```

```
type CarouselApi = UseEmblaCarouselType[1];
```

```
type UseCarouselParameters = Parameters<typeof useEmblaCarousel>;
```

```
type CarouselOptions = UseCarouselParameters[0];
```

```
type CarouselPlugin = UseCarouselParameters[1];
```

```
type CarouselProps = {
```

```
  opts?: CarouselOptions;
```

```
  plugins?: CarouselPlugin;
```

```
orientation?: "horizontal" | "vertical";

setApi?: (api: CarouselApi) => void;

};
```

```
type CarouselContextProps = {

  carouselRef: ReturnType<typeof useEmblaCarousel>[0];

  api: ReturnType<typeof useEmblaCarousel>[1];

  scrollPrev: () => void;

  scrollNext: () => void;

  canScrollPrev: boolean;

  canScrollNext: boolean;

} & CarouselProps;
```

```
const CarouselContext = React.createContext<CarouselContextProps | null>(null);
```

```
function useCarousel() {

  const context = React.useContext(CarouselContext);

  if (!context) {

    throw new Error("useCarousel must be used within a <Carousel />");

  }

  return context;

}
```

```
const Carousel = React.forwardRef<HTMLDivElement,  
React.HTMLAttributes<HTMLDivElement> & CarouselProps>(  
  
  ({ orientation = "horizontal", opts, setApi, plugins, className, children, ...props }, ref) => {  
  
    const [carouselRef, api] = useEmblaCarousel(  
  
      {  
  
        ...opts,  
  
        axis: orientation === "horizontal" ? "x" : "y",  
  
      },  
  
      plugins,  
  
    );  
  
    const [canScrollPrev, setCanScrollPrev] = React.useState(false);  
    const [canScrollNext, setCanScrollNext] = React.useState(false);  
  
  
    const onSelect = React.useCallback((api: CarouselApi) => {  
  
      if (!api) {  
  
        return;  
  
      }  
  
  
      setCanScrollPrev(api.canScrollPrev());  
      setCanScrollNext(api.canScrollNext());  
  
    }, []);  
  
  
    const scrollPrev = React.useCallback(() => {  
  
      api?.scrollPrev();  
  
    }, [api]);
```



```
const scrollNext = React.useCallback(() => {  
  api?.scrollNext();  
}, [api]);
```

```
const handleKeyDown = React.useCallback(  
  (event: React.KeyboardEvent<HTMLDivElement>) => {  
    if (event.key === "ArrowLeft") {  
      event.preventDefault();  
      scrollPrev();  
    } else if (event.key === "ArrowRight") {  
      event.preventDefault();  
      scrollNext();  
    }  
  },  
  [scrollPrev, scrollNext],  
);
```

```
React.useEffect(() => {  
  if (!api || !setApi) {  
    return;  
  }
```

```
  setApi(api);  
}, [api, setApi]);
```

```
React.useEffect(() => {
```

```
if (!api) {  
    return;  
}  
  
onSelect(api);  
api.on("reInit", onSelect);  
api.on("select", onSelect);  
  
return () => {  
    api?.off("select", onSelect);  
};  
}, [api, onSelect]);  
  
return (  
    <CarouselContext.Provider  
        value={{  
            carouselRef,  
            api: api,  
            opts,  
            orientation: orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),  
            scrollPrev,  
            scrollNext,  
            canScrollPrev,  
            canScrollNext,  
        }}  
    >
```

```

    <div
      ref={ref}
      onKeyDownCapture={handleKeyDown}
      className={cn("relative", className)}
      role="region"
      aria-roledescription="carousel"
      {...props}
    >
      {children}
    </div>
  </CarouselContext.Provider>
);
},
);

Carousel.displayName = "Carousel";

const CarouselContent = React.forwardRef<HTMLDivElement,
React.HTMLAttributes<HTMLDivElement>>(>
  ({ className, ...props }, ref) => {
    const { carouselRef, orientation } = useCarousel();

    return (
      <div ref={carouselRef} className="overflow-hidden">
        <div
          ref={ref}
          className={cn("flex", orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col",
            className)}

```

```

    {...props}

  />

</div>

);

},

);

CarouselContent.displayName = "CarouselContent";

const CarouselItem = React.forwardRef<HTMLDivElement,
React.HTMLAttributes<HTMLDivElement>>(

  ({ className, ...props }, ref) => {

    const { orientation } = useCarousel();

    return (

      <div

        ref={ref}

        role="group"

        aria-roledescription="slide"

        className={cn("min-w-0 shrink-0 grow-0 basis-full", orientation === "horizontal" ? "pl-4" :
"pt-4", className)}

        {...props}

      />

    );

  },

);

CarouselItem.displayName = "CarouselItem";

```

```

const CarouselPrevious = React.forwardRef<HTMLButtonElement,
React.ComponentProps<typeof Button>>(

  ({ className, variant = "outline", size = "icon", ...props }, ref) => {

    const { orientation, scrollPrev, canScrollPrev } = useCarousel();

    return (

      <Button

        ref={ref}

        variant={variant}

        size={size}

        className={cn(

          "absolute h-8 w-8 rounded-full",

          orientation === "horizontal"

            ? "-left-12 top-1/2 -translate-y-1/2"

            : "-top-12 left-1/2 -translate-x-1/2 rotate-90",

          className,

        )}

        disabled={!canScrollPrev}

        onClick={scrollPrev}

        {...props}

      >

        <ArrowLeft className="h-4 w-4" />

        <span className="sr-only">Previous slide</span>

      </Button>

    );

  },

```

```
);
```

```
CarouselPrevious.displayName = "CarouselPrevious";
```

```
const CarouselNext = React.forwardRef<HTMLButtonElement,  
React.ComponentProps<typeof Button>>(  
  ({ className, variant = "outline", size = "icon", ...props }, ref) => {  
    const { orientation, scrollNext, canScrollNext } = useCarousel();  
  
    return (  
      <Button  
        ref={ref}  
        variant={variant}  
        size={size}  
        className={cn(  
          "absolute h-8 w-8 rounded-full",  
          orientation === "horizontal"  
            ? "-right-12 top-1/2 -translate-y-1/2"  
            : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",  
          className,  
        )}  
        disabled={!canScrollNext}  
        onClick={scrollNext}  
        {...props}  
      >  
        <ArrowRight className="h-4 w-4" />  
        <span className="sr-only">Next slide</span>
```

```

    </Button>

    );

  },

);

CarouselNext.displayName = "CarouselNext";

export { type CarouselApi, Carousel, CarouselContent, CarouselItem, CarouselPrevious,
CarouselNext };

import * as React from "react";

import * as RechartsPrimitive from "recharts";

import { cn } from "@lib/utils";

// Format: { THEME_NAME: CSS_SELECTOR }
const THEMES = { light: "", dark: ".dark" } as const;

export type ChartConfig = {
  [k in string]: {
    label?: React.ReactNode;
    icon?: React.ComponentType;
  } & ({ color?: string; theme?: never } | { color?: never; theme: Record<keyof typeof THEMES,
string> });
};

type ChartContextProps = {
  config: ChartConfig;
};

```

```
const ChartContext = React.createContext<ChartContextProps | null>(null);
```

```
function useChart() {
```

```
  const context = React.useContext(ChartContext);
```

```
  if (!context) {
```

```
    throw new Error("useChart must be used within a <ChartContainer />");
```

```
  }
```

```
  return context;
```

```
}
```

```
const ChartContainer = React.forwardRef<
```

```
  HTMLDivElement,
```

```
  React.ComponentProps<"div"> & {
```

```
    config: ChartConfig;
```

```
    children: React.ComponentProps<typeof RechartsPrimitive.ResponsiveContainer>  
["children"];
```

```
  }
```

```
>(({ id, className, children, config, ...props }, ref) => {
```

```
  const uniqueId = React.useId();
```

```
  const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`;
```

```
  return (
```

```
    <ChartContext.Provider value={{ config }}>
```



```

<div

  data-chart={chartId}

  ref={ref}

  className={cn(

    "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-muted-foreground [&_.recharts-cartesian-grid_line[stroke='#ccc']]:stroke-border/50 [&_.recharts-curve.recharts-tooltip-cursor]:stroke-border [&_.recharts-dot[stroke='#fff']]:stroke-transparent [&_.recharts-layer]:outline-none [&_.recharts-polar-grid_[stroke='#ccc']]:stroke-border [&_.recharts-radial-bar-background-sector]:fill-muted [&_.recharts-rectangle.recharts-tooltip-cursor]:fill-muted [&_.recharts-reference-line_[stroke='#ccc']]:stroke-border [&_.recharts-sector[stroke='#fff']]:stroke-transparent [&_.recharts-sector]:outline-none [&_.recharts-surface]:outline-none",

    className,

  )}

  {...props}

>

  <ChartStyle id={chartId} config={config} />

  <RechartsPrimitive.ResponsiveContainer>{children}
</RechartsPrimitive.ResponsiveContainer>

</div>

</ChartContext.Provider>

);

});

ChartContainer.displayName = "Chart";

const ChartStyle = ({ id, config }: { id: string; config: ChartConfig }) => {

  const colorConfig = Object.entries(config).filter(([_, config]) => config.theme || config.color);

  if (!colorConfig.length) {

```

```

    return null;
}

return (
  <style
    dangerouslySetInnerHTML={{
      __html: Object.entries(THEMES)
        .map(
          ([theme, prefix]) => `
${prefix} [data-chart=${id}] {
  ${colorConfig
    .map(([key, itemConfig]) => {
      const color = itemConfig.theme?.[theme as keyof typeof itemConfig.theme] ||
itemConfig.color;

      return color ? ` --color-${key}: ${color};` : null;
    })
    .join("\n")}
  }
  `,
    )
    .join("\n"),
  }}
  />
);
};

```

```
const ChartTooltip = RechartsPrimitive.Tooltip;
```

```
const ChartTooltipContent = React.forwardRef<
```

```
  HTMLDivElement,
```

```
  React.ComponentProps<typeof RechartsPrimitive.Tooltip> &
```

```
  React.ComponentProps<"div"> & {
```

```
    hideLabel?: boolean;
```

```
    hideIndicator?: boolean;
```

```
    indicator?: "line" | "dot" | "dashed";
```

```
    nameKey?: string;
```

```
    labelKey?: string;
```

```
  }
```

```
>(  
  
(  
  
{
```

```
  active,
```

```
  payload,
```

```
  className,
```

```
  indicator = "dot",
```

```
  hideLabel = false,
```

```
  hideIndicator = false,
```

```
  label,
```

```
  labelFormatter,
```

```
  labelClassName,
```

```
  formatter,
```

```
  color,
```

```

    nameKey,

    labelKey,

  },

  ref,

) => {

  const { config } = useChart();

  const tooltipLabel = React.useMemo(() => {

    if (hideLabel || !payload?.length) {

      return null;

    }

    const [item] = payload;

    const key = `${labelKey || item.dataKey || item.name || "value"}`;

    const itemConfig = getPayloadConfigFromPayload(config, item, key);

    const value =

      !labelKey && typeof label === "string"

      ? config[label as keyof typeof config]?.label || label

      : itemConfig?.label;

    if (labelFormatter) {

      return <div className={cn("font-medium", labelClassName)}>{labelFormatter(value,
payload)}</div>;

    }

    if (!value) {

```

```

    return null;
}

return <div className={cn("font-medium", labelClassName)}>{value}</div>;
}, [label, labelFormatter, payload, hideLabel, labelClassName, config, labelKey]);

if (!active || !payload?.length) {
    return null;
}

const nestLabel = payload.length === 1 && indicator !== "dot";

return (
    <div
        ref={ref}
        className={cn(
            "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-
background px-2.5 py-1.5 text-xs shadow-xl",
            className,
        )}
    >
        {!nestLabel ? tooltipLabel : null}
        <div className="grid gap-1.5">
            {payload.map((item, index) => {
                const key = `${nameKey || item.name || item.dataKey || "value"}`;
                const itemConfig = getPayloadConfigFromPayload(config, item, key);

```

```

const indicatorColor = color || item.payload.fill || item.color;

return (
  <div
    key={item.dataKey}
    className={cn(
      "flex w-full flex-wrap items-stretch gap-2 [>svg]:h-2.5 [>svg]:w-2.5 [>svg]:text-
muted-foreground",
      indicator === "dot" && "items-center",
    )}
  >
    {formatter && item?.value !== undefined && item.name ? (
      formatter(item.value, item.name, item, index, item.payload)
    ) : (
      <>
        {itemConfig?.icon ? (
          <itemConfig.icon />
        ) : (
          !hideIndicator && (
            <div
              className={cn("shrink-0 rounded-[2px] border-[--color-border] bg-[--color-bg]",
                "h-2.5 w-2.5": indicator === "dot",
                "w-1": indicator === "line",
                "w-0 border-[1.5px] border-dashed bg-transparent": indicator === "dashed",
                "my-0.5": nestLabel && indicator === "dashed",
              )}}
            {

```

```

        style={
          {
            "--color-bg": indicatorColor,
            "--color-border": indicatorColor,
          } as React.CSSProperties
        }
      />
    )
  })
<div
  className={cn(
    "flex flex-1 justify-between leading-none",
    nestLabel ? "items-end" : "items-center",
  )}
>
  <div className="grid gap-1.5">
    {nestLabel ? tooltipLabel : null}
    <span className="text-muted-foreground">{itemConfig?.label || item.name}
</span>
  </div>
  {item.value && (
    <span className="font-mono font-medium tabular-nums text-foreground">
      {item.value.toLocaleString()}
    </span>
  )}
</div>

```

```

        </>
    )}
</div>

);

}}

</div>

</div>

);

},

);

ChartTooltipContent.displayName = "ChartTooltip";

const ChartLegend = RechartsPrimitive.Legend;

const ChartLegendContent = React.forwardRef<
    HTMLDivElement,
    React.ComponentProps<"div"> &
        Pick<RechartsPrimitive.LegendProps, "payload" | "verticalAlign"> & {
            hideIcon?: boolean;
            nameKey?: string;
        }
>(({ className, hideIcon = false, payload, verticalAlign = "bottom", nameKey }, ref) => {
    const { config } = useChart();

    if (!payload?.length) {
        return null;
    }

```



```
}
```

```
return (
```

```
<div
```

```
  ref={ref}
```

```
  className={cn("flex items-center justify-center gap-4", verticalAlign === "top" ? "pb-3" :  
"pt-3", className)}
```

```
>
```

```
  {payload.map((item) => {
```

```
    const key = `${nameKey || item.dataKey || "value"}`;
```

```
    const itemConfig = getPayloadConfigFromPayload(config, item, key);
```

```
    return (
```

```
      <div
```

```
        key={item.value}
```

```
        className={cn("flex items-center gap-1.5 [&>svg]:h-3 [&>svg]:w-3 [&>svg]:text-muted-  
foreground")}
```

```
      >
```

```
        {itemConfig?.icon && !hideIcon ? (
```

```
          <itemConfig.icon />
```

```
        ) : (
```

```
          <div
```

```
            className="h-2 w-2 shrink-0 rounded-[2px]"
```

```
            style={{
```

```
              backgroundColor: item.color,
```

```
            }}
```

```
          />
```

```

    }}

    {itemConfig?.label}

</div>

);

}}

</div>

);

});

ChartLegendContent.displayName = "ChartLegend";

// Helper to extract item config from a payload.

function getPayloadConfigFromPayload(config: ChartConfig, payload: unknown, key: string) {

    if (typeof payload !== "object" || payload === null) {

        return undefined;

    }

    const payloadPayload =

        "payload" in payload && typeof payload.payload === "object" && payload.payload !== null

        ? payload.payload

        : undefined;

    let configLabelKey: string = key;

    if (key in payload && typeof payload[key as keyof typeof payload] === "string") {

        configLabelKey = payload[key as keyof typeof payload] as string;

    } else if (

```

```

    payloadPayload &&

    key in payloadPayload &&

    typeof payloadPayload[key as keyof typeof payloadPayload] === "string"
  ) {

    configLabelKey = payloadPayload[key as keyof typeof payloadPayload] as string;

  }

  return configLabelKey in config ? config[configLabelKey] : config[key as keyof typeof config];
}

```

```

export { ChartContainer, ChartTooltip, ChartTooltipContent, ChartLegend,
ChartLegendContent, ChartStyle };

```

```

import * as React from "react";

```

```

import * as CheckboxPrimitive from "@radix-ui/react-checkbox";

```

```

import { Check } from "lucide-react";

```

```

import { cn } from "@lib/utils";

```

```

const Checkbox = React.forwardRef<

```

```

  React.ElementRef<typeof CheckboxPrimitive.Root>,

```

```

  React.ComponentPropsWithoutRef<typeof CheckboxPrimitive.Root>
>(({ className, ...props }, ref) => (

```

```

  <CheckboxPrimitive.Root

```

```

    ref={ref}

```

```

    className={cn(

```

```

      "peer h-4 w-4 shrink-0 rounded-sm border border-primary ring-offset-background data-
[state=checked]:bg-primary data-[state=checked]:text-primary-foreground focus-

```

visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-not-allowed disabled:opacity-50",

```
    className,  
  })  
  {...props}  
>  
  <CheckboxPrimitive.Indicator className={cn("flex items-center justify-center text-current")}>  
    <Check className="h-4 w-4" />  
  </CheckboxPrimitive.Indicator>  
</CheckboxPrimitive.Root>  
));
```

Checkbox.displayName = CheckboxPrimitive.Root.displayName;

export { Checkbox };

import * as CollapsiblePrimitive from "@radix-ui/react-collapsible";

const Collapsible = CollapsiblePrimitive.Root;

const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger;

const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent;

export { Collapsible, CollapsibleTrigger, CollapsibleContent };

import * as React from "react";

import { type DialogProps } from "@radix-ui/react-dialog";

import { Command as CommandPrimitive } from "cmdk";

```
import { Search } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
import { Dialog, DialogContent } from "@components/ui/dialog";
```

```
const Command = React.forwardRef<
```

```
  React.ElementRef<typeof CommandPrimitive>,
```

```
  React.ComponentPropsWithoutRef<typeof CommandPrimitive>
```

```
>(({ className, ...props }, ref) => (
```

```
  <CommandPrimitive
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
  />
```

```
));
```

```
Command.displayName = CommandPrimitive.displayName;
```

```
interface CommandDialogProps extends DialogProps {}
```

```
const CommandDialog = ({ children, ...props }: CommandDialogProps) => {
```

```
  return (
```

```
    <Dialog {...props}>
```

```

<DialogContent className="overflow-hidden p-0 shadow-lg">

  <Command className="[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-heading]]:text-muted-foreground [&_[cmdk-group]:not([hidden])_~[cmdk-group]]:pt-0 [&_[cmdk-group]]:px-2 [&_[cmdk-input-wrapper]_svg]:h-5 [&_[cmdk-input-wrapper]_svg]:w-5 [&_[cmdk-input]]:h-12 [&_[cmdk-item]]:px-2 [&_[cmdk-item]]:py-3 [&_[cmdk-item]_svg]:h-5 [&_[cmdk-item]_svg]:w-5">

    {children}

  </Command>

</DialogContent>

</Dialog>

);

};

```

```

const CommandInput = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Input>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Input>
>(({ className, ...props }, ref) => (
  <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
    <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
    <CommandPrimitive.Input
      ref={ref}
      className={cn(
        "flex h-11 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-muted-foreground disabled:cursor-not-allowed disabled:opacity-50",
        className,
      )}
      {...props}
    />

```

```
</div>
```

```
));
```

```
CommandInput.displayName = CommandPrimitive.Input.displayName;
```

```
const CommandList = React.forwardRef<
```

```
  React.ElementRef<typeof CommandPrimitive.List>,
```

```
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.List>
```

```
>(({ className, ...props }, ref) => (
```

```
  <CommandPrimitive.List
```

```
    ref={ref}
```

```
    className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
```

```
    {...props}
```

```
  />
```

```
));
```

```
CommandList.displayName = CommandPrimitive.List.displayName;
```

```
const CommandEmpty = React.forwardRef<
```

```
  React.ElementRef<typeof CommandPrimitive.Empty>,
```

```
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Empty>
```

```
>((props, ref) => <CommandPrimitive.Empty ref={ref} className="py-6 text-center text-sm"
  {...props} />);
```

```
CommandEmpty.displayName = CommandPrimitive.Empty.displayName;
```

```

const CommandGroup = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Group>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Group>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Group
    ref={ref}
    className={cn(
      "overflow-hidden p-1 text-foreground [&_cmdk-group-heading]:px-2 [&_cmdk-group-heading]:py-1.5 [&_cmdk-group-heading]:text-xs [&_cmdk-group-heading]:font-medium [&_cmdk-group-heading]:text-muted-foreground",
      className,
    )}
    {...props}
  />
));

```

```

CommandGroup.displayName = CommandPrimitive.Group.displayName;

```

```

const CommandSeparator = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Separator ref={ref} className={cn("-mx-1 h-px bg-border", className)}
    {...props} />
));

```

```

CommandSeparator.displayName = CommandPrimitive.Separator.displayName;

```



```

const CommandItem = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Item>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm
outline-none data-[disabled=true]:pointer-events-none data-[selected=true]:bg-accent
data-[selected=true]:text-accent-foreground data-[disabled=true]:opacity-50",
      className,
    )}
    {...props}
  />
));

```

```

CommandItem.displayName = CommandPrimitive.Item.displayName;

```

```

const CommandShortcut = ({ className, ...props }:
  React.HTMLAttributes<HTMLSpanElement>) => {
  return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground",
className)} {...props} />;
};

```

```

CommandShortcut.displayName = "CommandShortcut";

```

```

export {
  Command,

```

```
CommandDialog,  
CommandInput,  
CommandList,  
CommandEmpty,  
CommandGroup,  
CommandItem,  
CommandShortcut,  
CommandSeparator,  
};  
  
import * as React from "react";  
  
import * as ContextMenuPrimitive from "@radix-ui/react-context-menu";  
  
import { Check, ChevronRight, Circle } from "lucide-react";  
  
  
import { cn } from "@lib/utils";  
  
  
const ContextMenu = ContextMenuPrimitive.Root;  
  
  
const ContextMenuTrigger = ContextMenuPrimitive.Trigger;  
  
  
const ContextMenuGroup = ContextMenuPrimitive.Group;  
  
  
const ContextMenuPortal = ContextMenuPrimitive.Portal;  
  
  
const ContextMenuSub = ContextMenuPrimitive.Sub;  
  
  
const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup;
```

```

const ContextMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubTrigger> & {
    inset?: boolean;
  }
>(({ className, inset, children, ...props }, ref) => (
  <ContextMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-
none data-[state=open]:bg-accent data-[state=open]:text-accent-foreground focus:bg-accent
focus:text-accent-foreground",
      inset && "pl-8",
      className,
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </ContextMenuPrimitive.SubTrigger>
));

ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName;

```

```

const ContextMenuSubContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubContent>

```

```

>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground shadow-md data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
      className,
    )}
    {...props}
  />
));

```

ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName;

```

const ContextMenuContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Portal>
    <ContextMenuPrimitive.Content
      ref={ref}
      className={cn(
        "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground shadow-md animate-in fade-in-80 data-[state=open]:animate-in data-
[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-

```

```
top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
```

```
    className,
```

```
  )}
```

```
  {...props}
```

```
/>
```

```
</ContextMenuPrimitive.Portal>
```

```
));
```

```
ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName;
```

```
const ContextMenuItem = React.forwardRef<
```

```
  React.ElementRef<typeof ContextMenuPrimitive.Item>,
```

```
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Item> & {
```

```
    inset?: boolean;
```

```
  }
```

```
>(({ className, inset, ...props }, ref) => (
```

```
  <ContextMenuPrimitive.Item
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-accent focus:text-accent-foreground",
```

```
      inset && "pl-8",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
/>
```

```
));
```

```
ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName;
```

```
const ContextMenuCheckboxItem = React.forwardRef<
```

```
  React.ElementRef<typeof ContextMenuPrimitive.CheckboxItem>,
```

```
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.CheckboxItem>
```

```
>(({ className, children, checked, ...props }, ref) => (
```

```
  <ContextMenuPrimitive.CheckboxItem
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-accent focus:text-accent-foreground",
```

```
      className,
```

```
    )}
```

```
    checked={checked}
```

```
    {...props}
```

```
>
```

```
  <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
```

```
    <ContextMenuPrimitive.ItemIndicator>
```

```
      <Check className="h-4 w-4" />
```

```
    </ContextMenuPrimitive.ItemIndicator>
```

```
  </span>
```

```
    {children}
```

```
</ContextMenuPrimitive.CheckboxItem>
```

```
));
```

```
ContextMenuCheckboxItem.displayName =  
ContextMenuPrimitive.CheckboxItem.displayName;
```

```
const ContextMenuRadioItem = React.forwardRef(  
  React.ElementRef<typeof ContextMenuPrimitive.RadioItem>,  
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.RadioItem>  
>(({ className, children, ...props }, ref) => (  
  <ContextMenuPrimitive.RadioItem  
    ref={ref}  
    className={cn(  
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm  
outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-  
accent focus:text-accent-foreground",  
      className,  
    )}  
    {...props}  
  >  
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">  
      <ContextMenuPrimitive.ItemIndicator>  
        <Circle className="h-2 w-2 fill-current" />  
      </ContextMenuPrimitive.ItemIndicator>  
    </span>  
    {children}  
  </ContextMenuPrimitive.RadioItem>  
>));  
  
ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName;
```

```

const ContextMenuLabel = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Label> & {
    inset?: boolean;
  }
>(({ className, inset, ...props }, ref) => (
  <ContextMenuPrimitive.Label
    ref={ref}
    className={cn("px-2 py-1.5 text-sm font-semibold text-foreground", inset && "pl-8",
className)}
    {...props}
  />
));

```

```

ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName;

```

```

const ContextMenuSeparator = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-border",
className)} {...props} />
));

```

```

ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName;

```

```

const ContextMenuShortcut = ({ className, ...props }:
  React.HTMLAttributes<HTMLSpanElement>) => {

```



```
    return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground",
className)} {...props} />;
```

```
};
```

```
ContextMenuShortcut.displayName = "ContextMenuShortcut";
```

```
export {
```

```
  ContextMenu,
```

```
  ContextMenuTrigger,
```

```
  ContextMenuContent,
```

```
  ContextMenuItem,
```

```
  ContextMenuCheckboxItem,
```

```
  ContextMenuRadioItem,
```

```
  ContextMenuLabel,
```

```
  ContextMenuSeparator,
```

```
  ContextMenuShortcut,
```

```
  ContextMenuGroup,
```

```
  ContextMenuPortal,
```

```
  ContextMenuSub,
```

```
  ContextMenuSubContent,
```

```
  ContextMenuSubTrigger,
```

```
  ContextMenuRadioGroup,
```

```
};
```

```
import * as React from "react";
```

```
import * as DialogPrimitive from "@radix-ui/react-dialog";
```

```
import { X } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
const Dialog = DialogPrimitive.Root;
```

```
const DialogTrigger = DialogPrimitive.Trigger;
```

```
const DialogPortal = DialogPrimitive.Portal;
```

```
const DialogClose = DialogPrimitive.Close;
```

```
const DialogOverlay = React.forwardRef<
```

```
  React.ElementRef<typeof DialogPrimitive.Overlay>,
```

```
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
```

```
>(({ className, ...props }, ref) => (
```

```
  <DialogPrimitive.Overlay
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
  />
```

```
));
```

```
DialogOverlay.displayName = DialogPrimitive.Overlay.displayName;
```

```

const DialogContent = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DialogPortal>
    <DialogOverlay />
    <DialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-from-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
        className,
      )}
      {...props}
    >
      {children}
      <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background transition-opacity data-[state=open]:bg-accent data-[state=open]:text-muted-foreground hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:pointer-events-none">
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </DialogPrimitive.Close>
    </DialogPrimitive.Content>
  </DialogPortal>

```

```
));
```

```
DialogContent.displayName = DialogPrimitive.Content.displayName;
```

```
const DialogHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (  
  <div className={cn("flex flex-col space-y-1.5 text-center sm:text-left", className)} {...props}  
  />
```

```
);
```

```
DialogHeader.displayName = "DialogHeader";
```

```
const DialogFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (  
  <div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",  
    className)} {...props} />
```

```
);
```

```
DialogFooter.displayName = "DialogFooter";
```

```
const DialogTitle = React.forwardRef<
```

```
  React.ElementRef<typeof DialogPrimitive.Title>,
```

```
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
```

```
>)(({ className, ...props }, ref) => (  
  <DialogPrimitive.Title
```

```
    ref={ref}
```

```
    className={cn("text-lg font-semibold leading-none tracking-tight", className)}
```

```
    {...props}
```

```
  />
```

```
));
```

```
DialogTitle.displayName = DialogPrimitive.Title.displayName;
```

```
const DialogDescription = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground",
  className)} {...props} />
));

DialogDescription.displayName = DialogPrimitive.Description.displayName;

export {
  Dialog,
  DialogPortal,
  DialogOverlay,
  DialogClose,
  DialogTrigger,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
};

import * as React from "react";

import { Drawer as DrawerPrimitive } from "vaul";

import { cn } from "@lib/utils";
```

```
const Drawer = ({ shouldScaleBackground = true, ...props }: React.ComponentProps<typeof DrawerPrimitive.Root>) => (  
  <DrawerPrimitive.Root shouldScaleBackground={shouldScaleBackground} {...props} />  
);  
  
Drawer.displayName = "Drawer";  
  
const DrawerTrigger = DrawerPrimitive.Trigger;  
  
const DrawerPortal = DrawerPrimitive.Portal;  
  
const DrawerClose = DrawerPrimitive.Close;  
  
const DrawerOverlay = React.forwardRef<  
  React.ElementRef<typeof DrawerPrimitive.Overlay>,  
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>  
>(({ className, ...props }, ref) => (  
  <DrawerPrimitive.Overlay ref={ref} className={cn("fixed inset-0 z-50 bg-black/80",  
    className)} {...props} />  
));  
  
DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName;  
  
const DrawerContent = React.forwardRef<  
  React.ElementRef<typeof DrawerPrimitive.Content>,  
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>  
>(({ className, children, ...props }, ref) => (  
  <DrawerPortal>  
    <DrawerOverlay />  
    <div>
```

```

<DrawerPrimitive.Content
  ref={ref}

  className={cn(
    "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-
background",
    className,
  )}

  {...props}
>

  <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />

  {children}

</DrawerPrimitive.Content>

</DrawerPortal>

));

DrawerContent.displayName = "DrawerContent";

const DrawerHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
  <div className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)} {...props} />
);

DrawerHeader.displayName = "DrawerHeader";

const DrawerFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
  <div className={cn("mt-auto flex flex-col gap-2 p-4", className)} {...props} />
);

DrawerFooter.displayName = "DrawerFooter";

```

```
const DrawerTitle = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold leading-none tracking-tight", className)}
    {...props}
  />
));

DrawerTitle.displayName = DrawerPrimitive.Title.displayName;

const DrawerDescription = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground",
  className)} {...props} />
));

DrawerDescription.displayName = DrawerPrimitive.Description.displayName;

export {
  Drawer,
  DrawerPortal,
  DrawerOverlay,
  DrawerTrigger,
```



```
DrawerClose,  
  
DrawerContent,  
  
DrawerHeader,  
  
DrawerFooter,  
  
DrawerTitle,  
  
DrawerDescription,  
  
};  
  
import * as React from "react";  
  
import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu";  
  
import { Check, ChevronRight, Circle } from "lucide-react";  
  
  
  
import { cn } from "@lib/utils";  
  
  
  
const DropdownMenu = DropdownMenuPrimitive.Root;  
  
  
  
const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger;  
  
  
  
const DropdownMenuGroup = DropdownMenuPrimitive.Group;  
  
  
  
const DropdownMenuPortal = DropdownMenuPrimitive.Portal;  
  
  
  
const DropdownMenuSub = DropdownMenuPrimitive.Sub;  
  
  
  
const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup;  
  
  
  
const DropdownMenuSubTrigger = React.forwardRef<
```

```

React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,

React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
  inset?: boolean;
}

>(({ className, inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}

    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-
none data-[state=open]:bg-accent focus:bg-accent",

      inset && "pl-8",

      className,
    )}

    {...props}
  >

    {children}

    <ChevronRight className="ml-auto h-4 w-4" />
  </DropdownMenuPrimitive.SubTrigger>

));

DropdownMenuSubTrigger.displayName = DropdownMenuPrimitive.SubTrigger.displayName;

const DropdownMenuSubContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.SubContent

```

```

    ref={ref}

    className={cn(

      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground shadow-lg data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",

      className,

    )}

    {...props}

  />

));

```

```

DropdownMenuSubContent.displayName =
DropdownMenuPrimitive.SubContent.displayName;

```

```

const DropdownMenuContent = React.forwardRef<

  React.ElementRef<typeof DropdownMenuPrimitive.Content>,

  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>

>(({ className, sideOffset = 4, ...props }, ref) => (

  <DropdownMenuPrimitive.Portal>

    <DropdownMenuPrimitive.Content

      ref={ref}

      sideOffset={sideOffset}

      className={cn(

        "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground shadow-md data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",

```

```

        className,

    })

    {...props}

/>

</DropdownMenuPrimitive.Portal>

));

DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName;

const DropdownMenuItem = React.forwardRef<

  React.ElementRef<typeof DropdownMenuPrimitive.Item>,

  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {

    inset?: boolean;

  }

>(({ className, inset, ...props }, ref) => (

  <DropdownMenuPrimitive.Item

    ref={ref}

    className={cn(

      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm

outline-none transition-colors data-[disabled]:pointer-events-none data-[disabled]:opacity-

50 focus:bg-accent focus:text-accent-foreground",

      inset && "pl-8",

      className,

    )}

    {...props}

  />

));

DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName;

```

```

const DropdownMenuCheckboxItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <DropdownMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
outline-none transition-colors data-[disabled]:pointer-events-none data-[disabled]:opacity-
50 focus:bg-accent focus:text-accent-foreground",
      className,
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.CheckboxItem>
));

DropdownMenuCheckboxItem.displayName =
DropdownMenuPrimitive.CheckboxItem.displayName;

```

```

const DropdownMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <DropdownMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
outline-none transition-colors data-[disabled]:pointer-events-none data-[disabled]:opacity-
50 focus:bg-accent focus:text-accent-foreground",
      className,
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Circle className="h-2 w-2 fill-current" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.RadioItem>
));

DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName;

```

```

const DropdownMenuLabel = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {

```

```

    inset?: boolean;

}

>(({ className, inset, ...props }, ref) => (

  <DropdownMenuPrimitive.Label

    ref={ref}

    className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}

    {...props}

  />

));

DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName;

```

```

const DropdownMenuSeparator = React.forwardRef<

  React.ElementRef<typeof DropdownMenuPrimitive.Separator>,

  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>

>(({ className, ...props }, ref) => (

  <DropdownMenuPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted",

    className)} {...props} />

));

DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName;

```

```

const DropdownMenuShortcut = ({ className, ...props }:

  React.HTMLAttributes<HTMLSpanElement>) => {

  return <span className={cn("ml-auto text-xs tracking-widest opacity-60", className)}

    {...props} />;

};

DropdownMenuShortcut.displayName = "DropdownMenuShortcut";

```

```
export {  
  
  DropdownMenu,  
  
  DropdownMenuTrigger,  
  
  DropdownMenuContent,  
  
  DropdownMenuItem,  
  
  DropdownMenuCheckboxItem,  
  
  DropdownMenuRadioItem,  
  
  DropdownMenuLabel,  
  
  DropdownMenuSeparator,  
  
  DropdownMenuShortcut,  
  
  DropdownMenuGroup,  
  
  DropdownMenuPortal,  
  
  DropdownMenuSub,  
  
  DropdownMenuSubContent,  
  
  DropdownMenuSubTrigger,  
  
  DropdownMenuRadioGroup,  
  
};  
  
import * as React from "react";  
  
import * as LabelPrimitive from "@radix-ui/react-label";  
  
import { Slot } from "@radix-ui/react-slot";  
  
import { Controller, ControllerProps, FieldPath, FieldValues, FormProvider, useFormContext }  
from "react-hook-form";  
  
  
import { cn } from "@lib/utils";  
  
import { Label } from "@components/ui/label";
```



```
const Form = FormProvider;
```

```
type FormFieldContextValue<
```

```
  TFieldValues extends FieldValues = FieldValues,
```

```
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>,
```

```
> = {
```

```
  name: TName;
```

```
};
```

```
const FormFieldContext = React.createContext<FormFieldContextValue>({} as  
FormFieldContextValue);
```

```
const FormField = <
```

```
  TFieldValues extends FieldValues = FieldValues,
```

```
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>,
```

```
>({
```

```
  ...props
```

```
): ControllerProps<TFieldValues, TName>) => {
```

```
  return (
```

```
    <FormFieldContext.Provider value={{ name: props.name }}>
```

```
      <Controller {...props} />
```

```
    </FormFieldContext.Provider>
```

```
  );
```

```
};
```

```
const useFormField = () => {
```

```
const fieldContext = React.useContext(FormFieldContext);

const itemContext = React.useContext(FormItemContext);

const { getFieldState, formState } = useFormContext();

const fieldState = getFieldState(fieldContext.name, formState);

if (!fieldContext) {

  throw new Error("useFormField should be used within <FormField>");

}

const { id } = itemContext;

return {

  id,

  name: fieldContext.name,

  formItemId: `${id}-form-item`,

  formDescriptionId: `${id}-form-item-description`,

  formMessageId: `${id}-form-item-message`,

  ...fieldState,

};

};

type FormItemContextValue = {

  id: string;

};
```

```
const FormItemContext = React.createContext<FormItemContextValue>({} as
FormItemContextValue);
```

```
const FormItem = React.forwardRef<HTMLDivElement,
React.HTMLAttributes<HTMLDivElement>>(</div>
```

```
  ({ className, ...props }, ref) => {
```

```
    const id = React.useId();
```

```
    return (
```

```
      <FormItemContext.Provider value={{ id }}>
```

```
        <div ref={ref} className={cn("space-y-2", className)} {...props} />
```

```
      </FormItemContext.Provider>
```

```
    );
```

```
  },
```

```
);
```

```
FormItem.displayName = "FormItem";
```

```
const FormLabel = React.forwardRef<
```

```
  React.ElementRef<typeof LabelPrimitive.Root>,
```

```
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root>
```

```
>)(({ className, ...props }, ref) => {
```

```
  const { error, formItemId } = useFormField();
```

```
  return <Label ref={ref} className={cn(error && "text-destructive", className)} htmlFor=
{formItemId} {...props} />;
```

```
});
```

```
FormLabel.displayName = "FormLabel";
```

```

const FormControl = React.forwardRef<React.ElementRef<typeof Slot>,
React.ComponentPropsWithoutRef<typeof Slot>>(

  ({ ...props }, ref) => {

    const { error, formItemId, formDescriptionId, formMessageId } = useFormField();

    return (

      <Slot

        ref={ref}

        id={formItemId}

        aria-describedby={!error ? `${formDescriptionId}` : `${formDescriptionId}
${formMessageId}`}

        aria-invalid={!!error}

        {...props}

      />

    );

  },

);

FormControl.displayName = "FormControl";

```

```

const FormDescription = React.forwardRef<HTMLParagraphElement,
React.HTMLAttributes<HTMLParagraphElement>>(

  ({ className, ...props }, ref) => {

    const { formDescriptionId } = useFormField();

    return <p ref={ref} id={formDescriptionId} className={cn("text-sm text-muted-
foreground", className)} {...props} />;

```

```

    },
  );

  FormDescription.displayName = "FormDescription";

const FormMessage = React.forwardRef<HTMLParagraphElement,
React.HTMLAttributes<HTMLParagraphElement>>(
  ({ className, children, ...props }, ref) => {

    const { error, formMessageId } = useFormField();

    const body = error ? String(error?.message) : children;

    if (!body) {

      return null;

    }

    return (

      <p ref={ref} id={formMessageId} className={cn("text-sm font-medium text-destructive",
className)} {...props}>

        {body}

      </p>

    );

  },
);

FormMessage.displayName = "FormMessage";

export { useFormField, Form, FormItem, FormLabel, FormControl, FormDescription,
FormMessage, FormField };

import * as React from "react";

```

```
import * as HoverCardPrimitive from "@radix-ui/react-hover-card";

import { cn } from "@lib/utils";

const HoverCard = HoverCardPrimitive.Root;

const HoverCardTrigger = HoverCardPrimitive.Trigger;

const HoverCardContent = React.forwardRef<
  React.ElementRef<typeof HoverCardPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof HoverCardPrimitive.Content>
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  <HoverCardPrimitive.Content
    ref={ref}
    align={align}
    sideOffset={sideOffset}
    className={cn(
      "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md
outline-none data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
      className,
    )}
    {...props}
  />
));
```

```
HoverCardContent.displayName = HoverCardPrimitive.Content.displayName;
```

```
export { HoverCard, HoverCardTrigger, HoverCardContent };
```

```
import * as React from "react";
```

```
import { OTPInput, OTPInputContext } from "input-otp";
```

```
import { Dot } from "lucide-react";
```

```
import { cn } from "@lib/Utils";
```

```
const InputOTP = React.forwardRef<React.ElementRef<typeof OTPInput>,  
React.ComponentPropsWithoutRef<typeof OTPInput>>(  
  ({ className, containerClassName, ...props }, ref) => (  
    <OTPInput  
      ref={ref}  
      containerClassName={cn("flex items-center gap-2 has-[:disabled]:opacity-50",  
containerClassName)}  
      className={cn("disabled:cursor-not-allowed", className)}  
      {...props}  
    />  
  ),  
);  
InputOTP.displayName = "InputOTP";
```

```
const InputOTPGroup = React.forwardRef<React.ElementRef<"div">,  
React.ComponentPropsWithoutRef<"div">>(  
  ({ className, ...props }, ref) => <div ref={ref} className={cn("flex items-center", className)}  
    {...props} />,  
);
```

);

InputOTPGroup.displayName = "InputOTPGroup";

const InputOTPSlot = React.forwardRef<

React.ElementRef<"div">,

React.ComponentPropsWithoutRef<"div"> & { index: number }

>(({ index, className, ...props }, ref) => {

const inputOTPContext = React.useContext(OTPInputContext);

const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index];

return (

<div

ref={ref}

className={cn(

"relative flex h-10 w-10 items-center justify-center border-y border-r border-input text-sm transition-all first:rounded-l-md first:border-l last:rounded-r-md",

isActive && "z-10 ring-2 ring-ring ring-offset-background",

className,

)}

{...props}

>

{char}

{hasFakeCaret && (

<div className="pointer-events-none absolute inset-0 flex items-center justify-center">

<div className="animate-caret-blink h-4 w-px bg-foreground duration-1000" />

</div>


```

    })

  </div>

);

});

InputOTPSlot.displayName = "InputOTPSlot";

const InputOTPSeparator = React.forwardRef<React.ElementRef<"div">,
React.ComponentPropsWithoutRef<"div">>(<
  ({ ...props }, ref) => (
    <div ref={ref} role="separator" {...props}>
      <Dot />
    </div>
  ),
);

InputOTPSeparator.displayName = "InputOTPSeparator";

export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator };

import * as React from "react";

import { cn } from "@lib/utils";

const Input = React.forwardRef<HTMLInputElement, React.ComponentProps<"input">>(<
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}

```

```

    className={cn(
      "flex h-10 w-full rounded-md border border-input bg-background px-3 py-2 text-base
ring-offset-background file:border-0 file:bg-transparent file:text-sm file:font-medium file:text-
foreground placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-
2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-not-allowed
disabled:opacity-50 md:text-sm",
      className,
    )}
    ref={ref}
    {...props}
  />
);
},
);

Input.displayName = "Input";

export { Input };

import * as React from "react";

import * as LabelPrimitive from "@radix-ui/react-label";

import { cva, type VariantProps } from "class-variance-authority";

import { cn } from "@lib/utils";

const labelVariants = cva("text-sm font-medium leading-none peer-disabled:cursor-not-
allowed peer-disabled:opacity-70");

const Label = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,

```

```
React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> & VariantProps<typeof labelVariants>
```

```
>(({ className, ...props }, ref) => (
```

```
  <LabelPrimitive.Root ref={ref} className={cn(labelVariants(), className)} {...props} />
```

```
));
```

```
Label.displayName = LabelPrimitive.Root.displayName;
```

```
export { Label };
```

```
import { cn } from '@lib/utils';
```

```
import { Loader2 } from 'lucide-react';
```

```
interface LoadingSpinnerProps {
```

```
  size?: 'sm' | 'md' | 'lg';
```

```
  className?: string;
```

```
}
```

```
export function LoadingSpinner({ size = 'md', className }: LoadingSpinnerProps) {
```

```
  const sizeClasses = {
```

```
    sm: 'h-4 w-4',
```

```
    md: 'h-6 w-6',
```

```
    lg: 'h-10 w-10',
```

```
  };
```

```
  return (
```

```
    <Loader2
```

```
      className={cn('animate-spin text-primary', sizeClasses[size], className)}
```

```
    />

  );
}

import * as React from "react";

import * as MenubarPrimitive from "@radix-ui/react-menubar";

import { Check, ChevronRight, Circle } from "lucide-react";

import { cn } from "@lib/utils";

const MenubarMenu = MenubarPrimitive.Menu;

const MenubarGroup = MenubarPrimitive.Group;

const MenubarPortal = MenubarPrimitive.Portal;

const MenubarSub = MenubarPrimitive.Sub;

const MenubarRadioGroup = MenubarPrimitive.RadioGroup;

const Menubar = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Root
    ref={ref}
```

```
    className={cn("flex h-10 items-center space-x-1 rounded-md border bg-background p-1",
className)}
```

```
    {...props}
```

```
/>
```

```
));
```

```
Menubar.displayName = MenubarPrimitive.Root.displayName;
```

```
const MenubarTrigger = React.forwardRef<
```

```
  React.ElementRef<typeof MenubarPrimitive.Trigger>,
```

```
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
```

```
>(({ className, ...props }, ref) => (
```

```
  <MenubarPrimitive.Trigger
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "flex cursor-default select-none items-center rounded-sm px-3 py-1.5 text-sm font-
medium outline-none data-[state=open]:bg-accent data-[state=open]:text-accent-foreground
focus:bg-accent focus:text-accent-foreground",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
/>
```

```
));
```

```
MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName;
```

```
const MenubarSubTrigger = React.forwardRef<
```

```
  React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
```

```
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
```

```

    inset?: boolean;
  }
>(({ className, inset, children, ...props }, ref) => (
  <MenubarPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-
none data-[state=open]:bg-accent data-[state=open]:text-accent-foreground focus:bg-accent
focus:text-accent-foreground",
      inset && "pl-8",
      className,
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </MenubarPrimitive.SubTrigger>
));

```

```

MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName;

```

```

const MenubarSubContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.SubContent
    ref={ref}
    className={cn(

```

```

    "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",

    className,

  )}

  {...props}

/>

));

```

```

MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName;

```

```

const MenubarContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
>(({ className, align = "start", alignOffset = -4, sideOffset = 8, ...props }, ref) => (
  <MenubarPrimitive.Portal>
    <MenubarPrimitive.Content
      ref={ref}
      align={align}
      alignOffset={alignOffset}
      sideOffset={sideOffset}
      className={cn(
        "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
foreground shadow-md data-[state=open]:animate-in data-[state=closed]:fade-out-0 data-
[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-
[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
        className,

```

```

    })

    {...props}

  />

</MenubarPrimitive.Portal>

));

MenubarContent.displayName = MenubarPrimitive.Content.displayName;

const MenuItem = React.forwardRef<

  React.ElementRef<typeof MenubarPrimitive.Item>,

  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {

    inset?: boolean;

  }

>(({ className, inset, ...props }, ref) => (

  <MenubarPrimitive.Item

    ref={ref}

    className={cn(

      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm
outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-
accent focus:text-accent-foreground",

      inset && "pl-8",

      className,

    )}

    {...props}

  />

));

MenuItem.displayName = MenubarPrimitive.Item.displayName;

```



```

const MenubarCheckboxItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <MenubarPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-
accent focus:text-accent-foreground",
      className,
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.CheckboxItem>
));
MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName;

```

```

const MenubarRadioItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.RadioItem>,

```

```

React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (

  <MenubarPrimitive.RadioItem

    ref={ref}

    className={cn(

      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50 focus:bg-
accent focus:text-accent-foreground",

      className,

    )}

    {...props}
  >

    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">

      <MenubarPrimitive.ItemIndicator>

        <Circle className="h-2 w-2 fill-current" />

      </MenubarPrimitive.ItemIndicator>

    </span>

    {children}

  </MenubarPrimitive.RadioItem>

));

MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName;

const MenubarLabel = React.forwardRef<

  React.ElementRef<typeof MenubarPrimitive.Label>,

  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {

    inset?: boolean;

  }

```

```

>(({ className, inset, ...props }, ref) => (

  <MenubarPrimitive.Label

    ref={ref}

    className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}

    {...props}

  />

));

MenubarLabel.displayName = MenubarPrimitive.Label.displayName;

const MenubarSeparator = React.forwardRef<

  React.ElementRef<typeof MenubarPrimitive.Separator>,

  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>

>(({ className, ...props }, ref) => (

  <MenubarPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted",

    className)} {...props} />

));

MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName;

const MenubarShortcut = ({ className, ...props }:

  React.HTMLAttributes<HTMLSpanElement>) => {

  return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground",

    className)} {...props} />;

};

MenubarShortcut.displayName = "MenubarShortcut";

export {

  Menubar,

```

```
MenubarMenu,  
MenubarTrigger,  
MenubarContent,  
MenubarItem,  
MenubarSeparator,  
MenubarLabel,  
MenubarCheckboxItem,  
MenubarRadioGroup,  
MenubarRadioItem,  
MenubarPortal,  
MenubarSubContent,  
MenubarSubTrigger,  
MenubarGroup,  
MenubarSub,  
MenubarShortcut,  
};  
  
import * as React from "react";  
  
import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu";  
  
import { cva } from "class-variance-authority";  
  
import { ChevronDown } from "lucide-react";  
  
  
import { cn } from "@lib/utils";  
  
  
const NavigationMenu = React.forwardRef(  
  React.ElementRef<typeof NavigationMenuPrimitive.Root>,  
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Root>
```

```

>(({ className, children, ...props }, ref) => (

  <NavigationMenuPrimitive.Root

    ref={ref}

    className={cn("relative z-10 flex max-w-max flex-1 items-center justify-center",
className)}

    {...props}

  >

    {children}

    <NavigationMenuViewport />

  </NavigationMenuPrimitive.Root>

));

NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName;

```

```

const NavigationMenuList = React.forwardRef<

  React.ElementRef<typeof NavigationMenuPrimitive.List>,

  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.List>

>(({ className, ...props }, ref) => (

  <NavigationMenuPrimitive.List

    ref={ref}

    className={cn("group flex flex-1 list-none items-center justify-center space-x-1",
className)}

    {...props}

  />

));

NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName;

```

```

const NavigationMenuItem = NavigationMenuPrimitive.Item;

```

```
const navigationMenuTriggerStyle = cva(
  "group inline-flex h-10 w-max items-center justify-center rounded-md bg-background px-4
  py-2 text-sm font-medium transition-colors hover:bg-accent hover:text-accent-foreground
  focus:bg-accent focus:text-accent-foreground focus:outline-none disabled:pointer-events-
  none disabled:opacity-50 data-[active]:bg-accent/50 data-[state=open]:bg-accent/50",
);
```

```
const NavigationMenuTrigger = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <NavigationMenuPrimitive.Trigger
    ref={ref}
    className={cn(navigationMenuTriggerStyle(), "group", className)}
    {...props}
  >
    {children}{" "}
    <ChevronDown
      className="relative top-[1px] ml-1 h-3 w-3 transition duration-200 group-data-
      [state=open]:rotate-180"
      aria-hidden="true"
    />
  </NavigationMenuPrimitive.Trigger>
));

NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName;
```

```

const NavigationMenuContent = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.Content
    ref={ref}
    className={cn(
      "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-
[motion^=from-]:fade-in data-[motion^=to-]:fade-out data-[motion=from-end]:slide-in-from-
right-52 data-[motion=from-start]:slide-in-from-left-52 data-[motion=to-end]:slide-out-to-
right-52 data-[motion=to-start]:slide-out-to-left-52 md:absolute md:w-auto",
      className,
    )}
    {...props}
  />
));

NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName;

```

```

const NavigationMenuLink = NavigationMenuPrimitive.Link;

```

```

const NavigationMenuViewport = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Viewport>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Viewport>
>(({ className, ...props }, ref) => (
  <div className={cn("absolute left-0 top-full flex justify-center")}>
    <NavigationMenuPrimitive.Viewport
      className={cn(

```

```
"origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidden rounded-md border bg-popover text-popover-foreground shadow-lg data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-90 md:w-[var(--radix-navigation-menu-viewport-width)]",
```

```
  className,
```

```
  )}
```

```
  ref={ref}
```

```
  {...props}
```

```
/>
```

```
</div>
```

```
));
```

```
NavigationMenuViewport.displayName = NavigationMenuPrimitive.Viewport.displayName;
```

```
const NavigationMenuIndicator = React.forwardRef<
```

```
  React.ElementRef<typeof NavigationMenuPrimitive.Indicator>,
```

```
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Indicator>
```

```
>(({ className, ...props }, ref) => (
```

```
  <NavigationMenuPrimitive.Indicator
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-[state=visible]:animate-in data-[state=hidden]:animate-out data-[state=hidden]:fade-out data-[state=visible]:fade-in",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
>
```



```
    <div className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
```

```
  </NavigationMenuPrimitive.Indicator>
```

```
));
```

```
NavigationMenuIndicator.displayName = NavigationMenuPrimitive.Indicator.displayName;
```

```
export {
```

```
  navigationMenuTriggerStyle,
```

```
  NavigationMenu,
```

```
  NavigationMenuList,
```

```
  NavigationMenuItem,
```

```
  NavigationMenuContent,
```

```
  NavigationMenuTrigger,
```

```
  NavigationMenuLink,
```

```
  NavigationMenuIndicator,
```

```
  NavigationMenuViewport,
```

```
};
```

```
import * as React from "react";
```

```
import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
import { ButtonProps, buttonVariants } from "@components/ui/button";
```

```
const Pagination = ({ className, ...props }: React.ComponentProps<"nav">) => (
```

```
  <nav
```

```
    role="navigation"
```

```

    aria-label="pagination"

    className={cn("mx-auto flex w-full justify-center", className)}

    {...props}

  />

);

Pagination.displayName = "Pagination";

const PaginationContent = React.forwardRef<HTMLUListElement,
React.ComponentProps<"ul">>(

  ({ className, ...props }, ref) => (

    <ul ref={ref} className={cn("flex flex-row items-center gap-1", className)} {...props} />

  ),

);

PaginationContent.displayName = "PaginationContent";

const PaginationItem = React.forwardRef<HTMLLIElement, React.ComponentProps<"li">>(({
  className, ...props }, ref) => (

    <li ref={ref} className={cn("", className)} {...props} />

  ));

PaginationItem.displayName = "PaginationItem";

type PaginationLinkProps = {

  isActive?: boolean;

} & Pick<ButtonProps, "size"> &

  React.ComponentProps<"a">;

const PaginationLink = ({ className, isActive, size = "icon", ...props }: PaginationLinkProps) => (

```

```

<a
  aria-current={isActive ? "page" : undefined}
  className={cn(
    buttonVariants({
      variant: isActive ? "outline" : "ghost",
      size,
    }),
    className,
  )}
  {...props}
/>
);

PaginationLink.displayName = "PaginationLink";

const PaginationPrevious = ({ className, ...props }: React.ComponentProps<typeof
PaginationLink>) => (
  <PaginationLink aria-label="Go to previous page" size="default" className={cn("gap-1 pl-
2.5", className)} {...props}>
    <ChevronLeft className="h-4 w-4" />
    <span>Previous</span>
  </PaginationLink>
);

PaginationPrevious.displayName = "PaginationPrevious";

const PaginationNext = ({ className, ...props }: React.ComponentProps<typeof
PaginationLink>) => (

```

```
<PaginationLink aria-label="Go to next page" size="default" className={cn("gap-1 pr-2.5",
className)} {...props}>
```

```
<span>Next</span>
```

```
<ChevronRight className="h-4 w-4" />
```

```
</PaginationLink>
```

```
);
```

```
PaginationNext.displayName = "PaginationNext";
```

```
const PaginationEllipsis = ({ className, ...props }: React.ComponentProps<"span">) => (
```

```
<span aria-hidden className={cn("flex h-9 w-9 items-center justify-center", className)}
{...props}>
```

```
<MoreHorizontal className="h-4 w-4" />
```

```
<span className="sr-only">More pages</span>
```

```
</span>
```

```
);
```

```
PaginationEllipsis.displayName = "PaginationEllipsis";
```

```
export {
```

```
  Pagination,
```

```
  PaginationContent,
```

```
  PaginationEllipsis,
```

```
  PaginationItem,
```

```
  PaginationLink,
```

```
  PaginationNext,
```

```
  PaginationPrevious,
```

```
};
```

```
import * as React from "react";
```

```
import * as PopoverPrimitive from "@radix-ui/react-popover";
```

```
import { cn } from "@lib/utils";
```

```
const Popover = PopoverPrimitive.Root;
```

```
const PopoverTrigger = PopoverPrimitive.Trigger;
```

```
const PopoverContent = React.forwardRef<
```

```
  React.ElementRef<typeof PopoverPrimitive.Content>,
```

```
  React.ComponentPropsWithoutRef<typeof PopoverPrimitive.Content>
```

```
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
```

```
  <PopoverPrimitive.Portal>
```

```
    <PopoverPrimitive.Content
```

```
      ref={ref}
```

```
      align={align}
```

```
      sideOffset={sideOffset}
```

```
      className={cn(
```

```
        "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md  
outline-none data-[state=open]:animate-in data-[state=closed]:animate-out data-  
[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-  
[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-  
from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
```

```
        className,
```

```
      )}
```

```
      {...props}
```

```
    />
```

```

    </PopoverPrimitive.Portal>

  ));

  PopoverContent.displayName = PopoverPrimitive.Content.displayName;

export { Popover, PopoverTrigger, PopoverContent };

import * as React from "react";

import * as ProgressPrimitive from "@radix-ui/react-progress";

import { cn } from "@lib/Utils";

const Progress = React.forwardRef<
  React.ElementRef<typeof ProgressPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ProgressPrimitive.Root>
>(({ className, value, ...props }, ref) => (
  <ProgressPrimitive.Root
    ref={ref}
    className={cn("relative h-4 w-full overflow-hidden rounded-full bg-secondary",
      className)}
    {...props}
  >

    <ProgressPrimitive.Indicator
      className="h-full w-full flex-1 bg-primary transition-all"
      style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
    />

  </ProgressPrimitive.Root>

));

```

```
Progress.displayName = ProgressPrimitive.Root.displayName;
```

```
export { Progress };
```

```
import * as React from "react";
```

```
import * as RadioGroupPrimitive from "@radix-ui/react-radio-group";
```

```
import { Circle } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
const RadioGroup = React.forwardRef<
```

```
  React.ElementRef<typeof RadioGroupPrimitive.Root>,
```

```
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Root>
```

```
>(({ className, ...props }, ref) => {
```

```
  return <RadioGroupPrimitive.Root className={cn("grid gap-2", className)} {...props} ref={ref} />;
```

```
});
```

```
RadioGroup.displayName = RadioGroupPrimitive.Root.displayName;
```

```
const RadioGroupItem = React.forwardRef<
```

```
  React.ElementRef<typeof RadioGroupPrimitive.Item>,
```

```
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Item>
```

```
>(({ className, ...props }, ref) => {
```

```
  return (
```

```
    <RadioGroupPrimitive.Item
```

```
      ref={ref}
```

```
      className={cn(
```

```
"aspect-square h-4 w-4 rounded-full border border-primary text-primary ring-offset-background focus:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-not-allowed disabled:opacity-50",
```

```
  className,  
  
  })  
  
  {...props}  
  
>  
  
  <RadioGroupPrimitive.Indicator className="flex items-center justify-center">  
  
    <Circle className="h-2.5 w-2.5 fill-current text-current" />  
  
  </RadioGroupPrimitive.Indicator>  
  
</RadioGroupPrimitive.Item>  
  
);  
  
});
```

```
RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName;
```

```
export { RadioGroup, RadioGroupItem };
```

```
import { GripVertical } from "lucide-react";
```

```
import * as ResizablePrimitive from "react-resizable-panels";
```

```
import { cn } from "@lib/Utils";
```

```
const ResizablePanelGroup = ({ className, ...props }: React.ComponentProps<typeof ResizablePrimitive.PanelGroup>) => {
```

```
  <ResizablePrimitive.PanelGroup  
  
    className={cn("flex h-full w-full data-[panel-group-direction=vertical]:flex-col",  
className)}  
  
    {...props}
```



```

/>

);

const ResizablePanel = ResizablePrimitive.Panel;

const ResizableHandle = ({
  withHandle,
  className,
  ...props
}: React.ComponentProps<typeof ResizablePrimitive.PanelResizeHandle> & {
  withHandle?: boolean;
}) => (
  <ResizablePrimitive.PanelResizeHandle
    className={cn(
      "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0
after:left-1/2 after:w-1 after:-translate-x-1/2 data-[panel-group-direction=vertical]:h-px data-
[panel-group-direction=vertical]:w-full data-[panel-group-direction=vertical]:after:left-0
data-[panel-group-direction=vertical]:after:h-1 data-[panel-group-direction=vertical]:after:w-
full data-[panel-group-direction=vertical]:after:-translate-y-1/2 data-[panel-group-
direction=vertical]:after:translate-x-0 focus-visible:outline-none focus-visible:ring-1 focus-
visible:ring-ring focus-visible:ring-offset-1 [&[data-panel-group-
direction=vertical]>div]:rotate-90",
      className,
    )}
    {...props}
  >
    {withHandle && (
      <div className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-
border">

```

```

    <GripVertical className="h-2.5 w-2.5" />

  </div>

  )}

</ResizablePrimitive.PanelResizeHandle>

);

export { ResizablePanelGroup, ResizablePanel, ResizableHandle };

import * as React from "react";

import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area";

import { cn } from "@lib/utils";

const ScrollArea = React.forwardRef<
  React.ElementRef<typeof ScrollAreaPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.Root>
>(({ className, children, ...props }, ref) => (
  <ScrollAreaPrimitive.Root ref={ref} className={cn("relative overflow-hidden", className)}
    {...props}>
    <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">{children}
  </ScrollAreaPrimitive.Viewport>
    <ScrollBar />
    <ScrollAreaPrimitive.Corner />
  </ScrollAreaPrimitive.Root>
));

ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName;

const ScrollBar = React.forwardRef<

```

```

React.ElementRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>,
React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>
>(({ className, orientation = "vertical", ...props }, ref) => (
  <ScrollAreaPrimitive.ScrollAreaScrollbar
    ref={ref}
    orientation={orientation}
    className={cn(
      "flex touch-none select-none transition-colors",
      orientation === "vertical" && "h-full w-2.5 border-l border-l-transparent p-[1px]",
      orientation === "horizontal" && "h-2.5 flex-col border-t border-t-transparent p-[1px]",
      className,
    )}
    {...props}
  >
    <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border"
    />
  </ScrollAreaPrimitive.ScrollAreaScrollbar>
));

ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName;

export { ScrollArea, ScrollBar };

import * as React from "react";

import * as SelectPrimitive from "@radix-ui/react-select";

import { Check, ChevronDown, ChevronUp } from "lucide-react";

import { cn } from "@lib/utils";

```

```
const Select = SelectPrimitive.Root;
```

```
const SelectGroup = SelectPrimitive.Group;
```

```
const SelectValue = SelectPrimitive.Value;
```

```
const SelectTrigger = React.forwardRef<
```

```
  React.ElementRef<typeof SelectPrimitive.Trigger>,
```

```
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
```

```
>(({ className, children, ...props }, ref) => (
```

```
  <SelectPrimitive.Trigger
```

```
    ref={ref}
```

```
    className={cn(
```

```
      "flex h-10 w-full items-center justify-between rounded-md border border-input bg-background px-3 py-2 text-sm ring-offset-background placeholder:text-muted-foreground focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:cursor-not-allowed disabled:opacity-50 [&>span]:line-clamp-1",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
>
```

```
  {children}
```

```
<SelectPrimitive.Icon asChild>
```

```
  <ChevronDown className="h-4 w-4 opacity-50" />
```

```
</SelectPrimitive.Icon>
```

```
</SelectPrimitive.Trigger>
```

```
));  
  
SelectTrigger.displayName = SelectPrimitive.Trigger.displayName;
```

```
const SelectScrollUpButton = React.forwardRef(  
  React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,  
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>  
>(({ className, ...props }, ref) => (  
  <SelectPrimitive.ScrollUpButton  
    ref={ref}  
    className={cn("flex cursor-default items-center justify-center py-1", className)}  
    {...props}  
  >  
    <ChevronUp className="h-4 w-4" />  
  </SelectPrimitive.ScrollUpButton>  
));  
  
SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName;
```

```
const SelectScrollDownButton = React.forwardRef(  
  React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,  
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>  
>(({ className, ...props }, ref) => (  
  <SelectPrimitive.ScrollDownButton  
    ref={ref}  
    className={cn("flex cursor-default items-center justify-center py-1", className)}  
    {...props}  
  >
```

```

    <ChevronDown className="h-4 w-4" />

  </SelectPrimitive.ScrollDownButton>

));

SelectScrollDownButton.displayName = SelectPrimitive.ScrollDownButton.displayName;

const SelectContent = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>
>(({ className, children, position = "popper", ...props }, ref) => (
  <SelectPrimitive.Portal>
    <SelectPrimitive.Content
      ref={ref}
      className={cn(
        "relative z-50 max-h-96 min-w-[8rem] overflow-hidden rounded-md border bg-popover
        text-popover-foreground shadow-md data-[state=open]:animate-in data-
        [state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
        [state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-
        top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-
        [side=top]:slide-in-from-bottom-2",
        position === "popper" &&
        "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-
        [side=right]:translate-x-1 data-[side=top]:-translate-y-1",
        className,
      )}
      position={position}
      {...props}
    >
      <SelectScrollUpButton />

```

```

<SelectPrimitive.Viewport
  className={cn(
    "p-1",
    position === "popper" &&
      "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]",
  )}
>
  {children}
</SelectPrimitive.Viewport>
<SelectScrollDownButton />
</SelectPrimitive.Content>
</SelectPrimitive.Portal>
));

```

```

SelectContent.displayName = SelectPrimitive.Content.displayName;

```

```

const SelectLabel = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.Label ref={ref} className={cn("py-1.5 pl-8 pr-2 text-sm font-semibold",
    className)} {...props} />
));

```

```

SelectLabel.displayName = SelectPrimitive.Label.displayName;

```

```

const SelectItem = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Item>,

```

```

React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>

>(({ className, children, ...props }, ref) => (

  <SelectPrimitive.Item

    ref={ref}

    className={cn(

      "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2
text-sm outline-none data-[disabled]:pointer-events-none data-[disabled]:opacity-50
focus:bg-accent focus:text-accent-foreground",

      className,

    )}

    {...props}

  >

    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">

      <SelectPrimitive.ItemIndicator>

        <Check className="h-4 w-4" />

      </SelectPrimitive.ItemIndicator>

    </span>

    <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>

  </SelectPrimitive.Item>

));

SelectItem.displayName = SelectPrimitive.Item.displayName;

const SelectSeparator = React.forwardRef<

  React.ElementRef<typeof SelectPrimitive.Separator>,

  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>

>(({ className, ...props }, ref) => (

```



```
<SelectPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted",
className)} {...props} />
```

```
));
```

```
SelectSeparator.displayName = SelectPrimitive.Separator.displayName;
```

```
export {
```

```
  Select,
```

```
  SelectGroup,
```

```
  SelectValue,
```

```
  SelectTrigger,
```

```
  SelectContent,
```

```
  SelectLabel,
```

```
  SelectItem,
```

```
  SelectSeparator,
```

```
  SelectScrollUpButton,
```

```
  SelectScrollDownButton,
```

```
};
```

```
import * as React from "react";
```

```
import * as SeparatorPrimitive from "@radix-ui/react-separator";
```

```
import { cn } from "@lib/utils";
```

```
const Separator = React.forwardRef<
```

```
  React.ElementRef<typeof SeparatorPrimitive.Root>,
```

```
  React.ComponentPropsWithoutRef<typeof SeparatorPrimitive.Root>
```

```
>(({ className, orientation = "horizontal", decorative = true, ...props }, ref) => (
```

```
<SeparatorPrimitive.Root
  ref={ref}
  decorative={decorative}
  orientation={orientation}
  className={cn("shrink-0 bg-border", orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]", className)}
  {...props}
/>

));

Separator.displayName = SeparatorPrimitive.Root.displayName;

export { Separator };

import * as SheetPrimitive from "@radix-ui/react-dialog";
import { cva, type VariantProps } from "class-variance-authority";
import { X } from "lucide-react";
import * as React from "react";

import { cn } from "@lib/utils";

const Sheet = SheetPrimitive.Root;

const SheetTrigger = SheetPrimitive.Trigger;

const SheetClose = SheetPrimitive.Close;

const SheetPortal = SheetPrimitive.Portal;
```

```

const SheetOverlay = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
      className,
    )}
    {...props}
    ref={ref}
  />
));

SheetOverlay.displayName = SheetPrimitive.Overlay.displayName;

```

```

const sheetVariants = cva(
  "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:duration-300 data-[state=open]:duration-500",
  {
    variants: {
      side: {
        top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-[state=open]:slide-in-from-top",
        bottom:

```

```
"inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-[state=open]:slide-in-from-bottom",
```

```
left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-[state=open]:slide-in-from-left sm:max-w-sm",
```

```
right:
```

```
"inset-y-0 right-0 h-full w-3/4 border-l data-[state=closed]:slide-out-to-right data-[state=open]:slide-in-from-right sm:max-w-sm",
```

```
},
```

```
},
```

```
defaultVariants: {
```

```
  side: "right",
```

```
},
```

```
},
```

```
);
```

```
interface SheetContentProps
```

```
  extends React.ComponentPropsWithoutRef<typeof SheetPrimitive.Content>,
```

```
  VariantProps<typeof sheetVariants> {}
```

```
const SheetContent = React.forwardRef<React.ElementRef<typeof SheetPrimitive.Content>,  
SheetContentProps>(  
  ({ side = "right", className, children, ...props }, ref) => (  
    <SheetPortal>  
      <SheetOverlay />  
      <SheetPrimitive.Content ref={ref} className={cn(sheetVariants({ side }), className)}  
        {...props}>  
        {children}  
      </SheetPrimitive.Content>  
    </SheetPortal>  
  )  
)
```

```
<SheetPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-
offset-background transition-opacity data-[state=open]:bg-secondary hover:opacity-100
focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:pointer-events-
none">
```

```
<X className="h-4 w-4" />
```

```
<span className="sr-only">Close</span>
```

```
</SheetPrimitive.Close>
```

```
</SheetPrimitive.Content>
```

```
</SheetPortal>
```

```
),
```

```
);
```

```
SheetContent.displayName = SheetPrimitive.Content.displayName;
```

```
const SheetHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
```

```
<div className={cn("flex flex-col space-y-2 text-center sm:text-left", className)} {...props}
/>
```

```
);
```

```
SheetHeader.displayName = "SheetHeader";
```

```
const SheetFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
```

```
<div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
className)} {...props} />
```

```
);
```

```
SheetFooter.displayName = "SheetFooter";
```

```
const SheetTitle = React.forwardRef<
```

```
React.ElementRef<typeof SheetPrimitive.Title>,
```

```
React.ComponentPropsWithoutRef<typeof SheetPrimitive.Title>
```

```
>(({ className, ...props }, ref) => (
```

```
<SheetPrimitive.Title ref={ref} className={cn("text-lg font-semibold text-foreground",
className)} {...props} />
```

$$));$$

```
SheetTitle.displayName = SheetPrimitive.Title.displayName;
```

```
const SheetDescription = React.forwardRef<
```

React.ElementRef<typeof SheetPrimitive.Description>,

React.ComponentPropsWithoutRef<typeof SheetPrimitive.Description>

```
>(({ className, ...props }, ref) => (
```

```
<SheetPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground",
className)} {...props} />
```

$$));$$

```
SheetDescription.displayName = SheetPrimitive.Description.displayName;
```

```
export {
```

Sheet,

SheetClose,

SheetContent,

SheetDescription,

SheetFooter,

SheetHeader,

SheetOverlay,

SheetPortal,

SheetTitle,

SheetTrigger,

$$\};$$

```
import * as React from "react";

import { Slot } from "@radix-ui/react-slot";

import { VariantProps, cva } from "class-variance-authority";

import { PanelLeft } from "lucide-react";


import { useIsMobile } from "@/hooks/use-mobile";

import { cn } from "@/lib/utils";

import { Button } from "@components/ui/button";

import { Input } from "@components/ui/input";

import { Separator } from "@components/ui/separator";

import { Sheet, SheetContent } from "@components/ui/sheet";

import { Skeleton } from "@components/ui/skeleton";

import { Tooltip, TooltipContent, TooltipProvider, TooltipTrigger } from
"@components/ui/tooltip";


const SIDEBAR_COOKIE_NAME = "sidebar:state";

const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7;

const SIDEBAR_WIDTH = "16rem";

const SIDEBAR_WIDTH_MOBILE = "18rem";

const SIDEBAR_WIDTH_ICON = "3rem";

const SIDEBAR_KEYBOARD_SHORTCUT = "b";

type SidebarContext = {

  state: "expanded" | "collapsed";

  open: boolean;

  setOpen: (open: boolean) => void;
```

```
openMobile: boolean;

setOpenMobile: (open: boolean) => void;

isMobile: boolean;

toggleSidebar: () => void;

};

const SidebarContext = React.createContext<SidebarContext | null>(null);

function useSidebar() {

  const context = React.useContext(SidebarContext);

  if (!context) {

    throw new Error("useSidebar must be used within a SidebarProvider.");

  }

  return context;

}
```

```
const SidebarProvider = React.forwardRef<

  HTMLDivElement,

  React.ComponentProps<"div"> & {

    defaultOpen?: boolean;

    open?: boolean;

    onOpenChange?: (open: boolean) => void;

  }

>(({ defaultOpen = true, open: openProp, onOpenChange: setOpenProp, className, style,

children, ...props }, ref) => {
```



```

const isMobile = useIsMobile();

const [openMobile, setOpenMobile] = React.useState(false);

// This is the internal state of the sidebar.

// We use openProp and setOpenProp for control from outside the component.

const [_open, _setOpen] = React.useState(defaultOpen);

const open = openProp ?? _open;

const setOpen = React.useCallback(
  (value: boolean | ((value: boolean) => boolean)) => {
    const openState = typeof value === "function" ? value(open) : value;

    if (setOpenProp) {
      setOpenProp(openState);
    } else {
      _setOpen(openState);
    }
  }

  // This sets the cookie to keep the sidebar state.

  document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`;

  },

  [setOpenProp, open],

);

// Helper to toggle the sidebar.

const toggleSidebar = React.useCallback(() => {
  return isMobile ? setOpenMobile((open) => !open) : setOpen((open) => !open);

```

```
}, [isMobile, setOpen, setOpenMobile]);
```

```
// Adds a keyboard shortcut to toggle the sidebar.
```

```
React.useEffect(() => {
```

```
  const handleKeyDown = (event: KeyboardEvent) => {
```

```
    if (event.key === SIDEBAR_KEYBOARD_SHORTCUT && (event.metaKey || event.ctrlKey)) {
```

```
      event.preventDefault();
```

```
      toggleSidebar();
```

```
    }
```

```
  };
```

```
  window.addEventListener("keydown", handleKeyDown);
```

```
  return () => window.removeEventListener("keydown", handleKeyDown);
```

```
}, [toggleSidebar]);
```

```
// We add a state so that we can do data-state="expanded" or "collapsed".
```

```
// This makes it easier to style the sidebar with Tailwind classes.
```

```
const state = open ? "expanded" : "collapsed";
```

```
const contextValue = React.useMemo<SidebarContext>(  
  () => ({
```

```
    state,
```

```
    open,
```

```
    setOpen,
```

```
    isMobile,
```

```
    openMobile,
```

```
    setOpenMobile,  
    toggleSidebar,  
  }},  
  [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar],  
);
```

```
return (  
  <SidebarContext.Provider value={contextValue}>  
    <TooltipProvider delayDuration={0}>  
      <div  
        style={  
          {  
            "--sidebar-width": SIDEBAR_WIDTH,  
            "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,  
            ...style,  
          } as React.CSSProperties  
        }  
        className={cn("group/sidebar-wrapper flex min-h-svh w-full has-[[data-variant=inset]]:bg-sidebar", className)}  
        ref={ref}  
        {...props}  
      >  
        {children}  
      </div>  
    </TooltipProvider>  
  </SidebarContext.Provider>
```

```

);

});

SidebarProvider.displayName = "SidebarProvider";

const Sidebar = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<"div"> & {
    side?: "left" | "right";
    variant?: "sidebar" | "floating" | "inset";
    collapsible?: "offcanvas" | "icon" | "none";
  }
>(({ side = "left", variant = "sidebar", collapsible = "offcanvas", className, children, ...props },
ref) => {

  const { isMobile, state, openMobile, setOpenMobile } = useSidebar();

  if (collapsible === "none") {

    return (

      <div

        className={cn("flex h-full w-[--sidebar-width] flex-col bg-sidebar text-sidebar-
foreground", className)}

        ref={ref}

        {...props}

      >

        {children}

      </div>

    );

  }

```

```

if (isMobile) {

  return (

    <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>

      <SheetContent

        data-sidebar="sidebar"

        data-mobile="true"

        className="w-[--sidebar-width] bg-sidebar p-0 text-sidebar-foreground
[&>button]:hidden"

        style={

          {

            "--sidebar-width": SIDEBAR_WIDTH_MOBILE,

          } as React.CSSProperties

        }

        side={side}

      >

        <div className="flex h-full w-full flex-col">{children}</div>

      </SheetContent>

    </Sheet>

  );

}

```

```

return (

  <div

    ref={ref}

    className="group peer hidden text-sidebar-foreground md:block"

```

```

data-state={state}

data-collapsible={state === "collapsed" ? collapsible : ""}

data-variant={variant}

data-side={side}

>

{/* This is what handles the sidebar gap on desktop */}

<div

  className={cn(

    "relative h-svh w-[--sidebar-width] bg-transparent transition-[width] duration-200 ease-
linear",

    "group-data-[collapsible=offcanvas]:w-0",

    "group-data-[side=right]:rotate-180",

    variant === "floating" || variant === "inset"

    ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-
icon)_+_theme(spacing.4))]"

    : "group-data-[collapsible=icon]:w-[--sidebar-width-icon]",

  )}

/>

<div

  className={cn(

    "fixed inset-y-0 z-10 hidden h-svh w-[--sidebar-width] transition-[left,right,width]
duration-200 ease-linear md:flex",

    side === "left"

    ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"

    : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar width)*-1)]",

    // Adjust the padding for floating and inset variants.

    variant === "floating" || variant === "inset"

```

```
return (
```

```

<Button
  ref={ref}
  data-sidebar="trigger"
  variant="ghost"
  size="icon"
  className={cn("h-7 w-7", className)}
  onClick={(event) => {
    onClick?.(event);
    toggleSidebar();
  }}
  {...props}
>

  <PanelLeft />

  <span className="sr-only">Toggle Sidebar</span>

</Button>

);

},

);

SidebarTrigger.displayName = "SidebarTrigger";

const SidebarRail = React.forwardRef<HTMLButtonElement,
React.ComponentProps<"button">>(>
  ({ className, ...props }, ref) => {
    const { toggleSidebar } = useSidebar();

    return (

```



```

<button
  ref={ref}
  data-sidebar="rail"
  aria-label="Toggle Sidebar"
  tabIndex={-1}
  onClick={toggleSidebar}
  title="Toggle Sidebar"
  className={cn(
    "absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-linear
after:absolute after:inset-y-0 after:left-1/2 after:w-[2px] group-data-[side=left]:-right-4 group-
data-[side=right]:left-0 hover:after:bg-sidebar-border sm:flex",
    "[[data-side=left]_&]:cursor-w-resize [[data-side=right]_&]:cursor-e-resize",
    "[[data-side=left][data-state=collapsed]_&]:cursor-e-resize [[data-side=right][data-
state=collapsed]_&]:cursor-w-resize",
    "group-data-[collapsible=offcanvas]:translate-x-0 group-data-
[collapsible=offcanvas]:after:left-full group-data-[collapsible=offcanvas]:hover:bg-sidebar",
    "[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",
    "[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
    className,
  )}
  {...props}
/>

);

},

);

SidebarRail.displayName = "SidebarRail";

```

```

const SidebarInset = React.forwardRef<HTMLDivElement, React.ComponentProps<"main">>
(({ className, ...props }, ref) => {

  return (

    <main

      ref={ref}

      className={cn(

        "relative flex min-h-svh flex-1 flex-col bg-background",

        "peer-data-[variant=inset]:min-h-[calc(100svh-theme(spacing.4))] md:peer-data-
[variant=inset]:m-2 md:peer-data-[state=collapsed]:peer-data-[variant=inset]:ml-2 md:peer-
data-[variant=inset]:ml-0 md:peer-data-[variant=inset]:rounded-xl md:peer-data-
[variant=inset]:shadow",

        className,

      )}

      {...props}

    />

  );

});

SidebarInset.displayName = "SidebarInset";

```

```

const SidebarInput = React.forwardRef<React.ElementRef<typeof Input>,
React.ComponentProps<typeof Input>>(

  ({ className, ...props }, ref) => {

    return (

      <Input

        ref={ref}

        data-sidebar="input"

        className={cn(

```

```

    "h-8 w-full bg-background shadow-none focus-visible:ring-2 focus-visible:ring-sidebar-
ring",

    className,

  )}

  {...props}

/>

);

},

);

SidebarInput.displayName = "SidebarInput";

```

```

const SidebarHeader = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>
(({ className, ...props }, ref) => {

  return <div ref={ref} data-sidebar="header" className={cn("flex flex-col gap-2 p-2",
className)} {...props} />;

});

SidebarHeader.displayName = "SidebarHeader";

```

```

const SidebarFooter = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>
(({ className, ...props }, ref) => {

  return <div ref={ref} data-sidebar="footer" className={cn("flex flex-col gap-2 p-2",
className)} {...props} />;

});

SidebarFooter.displayName = "SidebarFooter";

```

```

const SidebarSeparator = React.forwardRef<React.ElementRef<typeof Separator>,
React.ComponentProps<typeof Separator>>(

  ({ className, ...props }, ref) => {

```

```

return (
  <Separator
    ref={ref}
    data-sidebar="separator"
    className={cn("mx-2 w-auto bg-sidebar-border", className)}
    {...props}
  />
);
},
);

SidebarSeparator.displayName = "SidebarSeparator";

const SidebarContent = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>
(({ className, ...props }, ref) => {
  return (
    <div
      ref={ref}
      data-sidebar="content"
      className={cn(
        "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-
hidden",
        className,
      )}
      {...props}
    />
  );
});

```

```
SidebarContent.displayName = "SidebarContent";
```

```
const SidebarGroup = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>
(({ className, ...props }, ref) => {
```

```
  return (
```

```
    <div
```

```
      ref={ref}
```

```
      data-sidebar="group"
```

```
      className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
```

```
      {...props}
```

```
    />
```

```
  );
```

```
});
```

```
SidebarGroup.displayName = "SidebarGroup";
```

```
const SidebarGroupLabel = React.forwardRef<HTMLDivElement,
React.ComponentProps<"div"> & { asChild?: boolean }>(  
  ({ className, asChild = false, ...props }, ref) => {
```

```
    const Comp = asChild ? Slot : "div";
```

```
    return (
```

```
      <Comp
```

```
        ref={ref}
```

```
        data-sidebar="group-label"
```

```
        className={cn(
```

```
          "flex h-8 shrink-0 items-center rounded-md px-2 text-xs font-medium text-sidebar-  
foreground/70 outline-none ring-sidebar-ring transition-[margin,opa] duration-200 ease-
```

```

linear focus-visible:ring-2 [&>svg]:size-4 [&>svg]:shrink-0",

    "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",

    className,

  )}

  {...props}

/>

);

},

);

```

```

SidebarGroupLabel.displayName = "SidebarGroupLabel";

```

```

const SidebarGroupAction = React.forwardRef<HTMLButtonElement,
React.ComponentProps<"button"> & { asChild?: boolean }>(

  ({ className, asChild = false, ...props }, ref) => {

    const Comp = asChild ? Slot : "button";

    return (

      <Comp

        ref={ref}

        data-sidebar="group-action"

        className={cn(

          "absolute right-3 top-3.5 flex aspect-square w-5 items-center justify-center rounded-md
p-0 text-sidebar-foreground outline-none ring-sidebar-ring transition-transform hover:bg-
sidebar-accent hover:text-sidebar-accent-foreground focus-visible:ring-2 [&>svg]:size-4
[&>svg]:shrink-0",

          // Increases the hit area of the button on mobile.

          "after:absolute after:-inset-2 after:md:hidden",

```

```

    "group-data-[collapsible=icon]:hidden",

    className,

  )}

  {...props}

/>

);

},

);

SidebarGroupAction.displayName = "SidebarGroupAction";

```

```

const SidebarGroupContent = React.forwardRef<HTMLDivElement,
React.ComponentProps<"div">>(

  ({ className, ...props }, ref) => (

    <div ref={ref} data-sidebar="group-content" className={cn("w-full text-sm", className)}
    {...props} />

  ),

);

SidebarGroupContent.displayName = "SidebarGroupContent";

```

```

const SidebarMenu = React.forwardRef<HTMLUListElement, React.ComponentProps<"ul">>
(({ className, ...props }, ref) => (

  <ul ref={ref} data-sidebar="menu" className={cn("flex w-full min-w-0 flex-col gap-1",
  className)} {...props} />

));

SidebarMenu.displayName = "SidebarMenu";

```

```

const SidebarMenuItem = React.forwardRef<HTMLLIElement, React.ComponentProps<"li">>
(({ className, ...props }, ref) => (

```

```
<li ref={ref} data-sidebar="menu-item" className={cn("group/menu-item relative",
className)} {...props} />
```

```
));
```

```
SidebarMenuItem.displayName = "SidebarMenuItem";
```

```
const sidebarMenuButtonVariants = cva(
```

```
  "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left
  text-sm outline-none ring-sidebar-ring transition-[width,height,padding] hover:bg-sidebar-
  accent hover:text-sidebar-accent-foreground focus-visible:ring-2 active:bg-sidebar-accent
  active:text-sidebar-accent-foreground disabled:pointer-events-none disabled:opacity-50
  group-has-[[data-sidebar=menu-action]]/menu-item:pr-8 aria-disabled:pointer-events-none
  aria-disabled:opacity-50 data-[active=true]:bg-sidebar-accent data-[active=true]:font-
  medium data-[active=true]:text-sidebar-accent-foreground data-[state=open]:hover:bg-
  sidebar-accent data-[state=open]:hover:text-sidebar-accent-foreground group-data-
  [collapsible=icon]:!size-8 group-data-[collapsible=icon]:!p-2 [&gt;span:last-child]:truncate
  [&gt;svg]:size-4 [&gt;svg]:shrink-0",
```

```
{
```

```
  variants: {
```

```
    variant: {
```

```
      default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
```

```
      outline:
```

```
        "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent
        hover:text-sidebar-accent-foreground hover:shadow-[0_0_0_1px_hsl(var(--sidebar-accent))]",
```

```
    },
```

```
    size: {
```

```
      default: "h-8 text-sm",
```

```
      sm: "h-7 text-xs",
```

```
      lg: "h-12 text-sm group-data-[collapsible=icon]:!p-0",
```

```
    },
```

```
  },
```



```

defaultVariants: {
  variant: "default",
  size: "default",
},
},
);

const SidebarMenuButton = React.forwardRef<
  HTMLButtonElement,
  React.ComponentProps<"button"> & {
    asChild?: boolean;
    isActive?: boolean;
    tooltip?: string | React.ComponentProps<typeof TooltipContent>;
  } & VariantProps<typeof sidebarMenuButtonVariants>
>(({ asChild = false, isActive = false, variant = "default", size = "default", tooltip, className,
...props }, ref) => {
  const Comp = asChild ? Slot : "button";
  const { isMobile, state } = useSidebar();

  const button = (
    <Comp
      ref={ref}
      data-sidebar="menu-button"
      data-size={size}
      data-active={isActive}
      className={cn(sidebarMenuButtonVariants({ variant, size }), className)}

```

```

    {...props}

  />

);

if (!tooltip) {
  return button;
}

if (typeof tooltip === "string") {
  tooltip = {
    children: tooltip,
  };
}

return (
  <Tooltip>
    <TooltipTrigger asChild>{button}</TooltipTrigger>
    <TooltipContent side="right" align="center" hidden={state !== "collapsed" || isMobile}
    {...tooltip} />
  </Tooltip>
);

});

SidebarMenuButton.displayName = "SidebarMenuButton";

const SidebarMenuAction = React.forwardRef<
  HTMLButtonElement,

```

```

React.ComponentProps<"button"> & {

  asChild?: boolean;

  showOnHover?: boolean;

}

>(({ className, asChild = false, showOnHover = false, ...props }, ref) => {

  const Comp = asChild ? Slot : "button";

  return (

    <Comp

      ref={ref}

      data-sidebar="menu-action"

      className={cn(

        "absolute right-1 top-1.5 flex aspect-square w-5 items-center justify-center rounded-md

p-0 text-sidebar-foreground outline-none ring-sidebar-ring transition-transform peer-

hover/menu-button:text-sidebar-accent-foreground hover:bg-sidebar-accent hover:text-

sidebar-accent-foreground focus-visible:ring-2 [>svg]:size-4 [>svg]:shrink-0",

        // Increases the hit area of the button on mobile.

        "after:absolute after:-inset-2 after:md:hidden",

        "peer-data-[size=sm]/menu-button:top-1",

        "peer-data-[size=default]/menu-button:top-1.5",

        "peer-data-[size=lg]/menu-button:top-2.5",

        "group-data-[collapsible=icon]:hidden",

        showOnHover &&

        "group-focus-within/menu-item:opacity-100 group-hover/menu-item:opacity-100 data-

[state=open]:opacity-100 peer-data-[active=true]/menu-button:text-sidebar-accent-

foreground md:opacity-0",

        className,

      )}

```

```

    {...props}

  />

);

});

SidebarMenuAction.displayName = "SidebarMenuAction";

const SidebarMenuBadge = React.forwardRef<HTMLDivElement,
React.ComponentProps<"div">>(>
  ({ className, ...props }, ref) => (
    <div
      ref={ref}
      data-sidebar="menu-badge"
      className={cn(
        "pointer-events-none absolute right-1 flex h-5 min-w-5 select-none items-center justify-
center rounded-md px-1 text-xs font-medium tabular-nums text-sidebar-foreground",
        "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-
button:text-sidebar-accent-foreground",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        className,
      )}
      {...props}
    />
  ),
);

```

```
SidebarMenuBadge.displayName = "SidebarMenuBadge";
```

```
const SidebarMenuSkeleton = React.forwardRef<
```

```
  HTMLDivElement,
```

```
  React.ComponentProps<"div"> & {
```

```
    showIcon?: boolean;
```

```
  }
```

```
>(({ className, showIcon = false, ...props }, ref) => {
```

```
  // Random width between 50 to 90%.
```

```
  const width = React.useMemo(() => {
```

```
    return `${Math.floor(Math.random() * 40) + 50}%`;
```

```
  }, []);
```

```
  return (
```

```
    <div
```

```
      ref={ref}
```

```
      data-sidebar="menu-skeleton"
```

```
      className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
```

```
      {...props}
```

```
    >
```

```
      {showIcon && <Skeleton className="size-4 rounded-md" data-sidebar="menu-skeleton-  
icon" />}
```

```
      <Skeleton
```

```
        className="h-4 max-w-[--skeleton-width] flex-1"
```

```
        data-sidebar="menu-skeleton-text"
```

```
        style={
```

```

    {
      "--skeleton-width": width,
    } as React.CSSProperties
  }

/>
</div>

);
});

```

```

SidebarMenuSkeleton.displayName = "SidebarMenuSkeleton";

```

```

const SidebarMenuSub = React.forwardRef<HTMLUListElement,
React.ComponentProps<"ul">>(
  ({ className, ...props }, ref) => (
    <ul
      ref={ref}
      data-sidebar="menu-sub"
      className={cn(
        "mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-l border-sidebar-border px-2.5
py-0.5",
        "group-data-[collapsible=icon]:hidden",
        className,
      )}
      {...props}
    />
  ),
);

SidebarMenuSub.displayName = "SidebarMenuSub";

```

```
const SidebarMenuSubItem = React.forwardRef<HTMLLIElement,  
React.ComponentProps<"li">>(({ ...props }, ref) => (
```

```
  <li ref={ref} {...props} />
```

```
));
```

```
SidebarMenuSubItem.displayName = "SidebarMenuSubItem";
```

```
const SidebarMenuSubButton = React.forwardRef<
```

```
  HTMLAnchorElement,
```

```
  React.ComponentProps<"a"> & {
```

```
    asChild?: boolean;
```

```
    size?: "sm" | "md";
```

```
    isActive?: boolean;
```

```
  }
```

```
>(({ asChild = false, size = "md", isActive, className, ...props }, ref) => {
```

```
  const Comp = asChild ? Slot : "a";
```

```
  return (
```

```
    <Comp
```

```
      ref={ref}
```

```
      data-sidebar="menu-sub-button"
```

```
      data-size={size}
```

```
      data-active={isActive}
```

```
      className={cn(
```

```
        "flex h-7 min-w-0 -translate-x-px items-center gap-2 overflow-hidden rounded-md px-2  
text-sidebar-foreground outline-none ring-sidebar-ring aria-disabled:pointer-events-none  
aria-disabled:opacity-50 hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
```

```
focus-visible:ring-2 active:bg-sidebar-accent active:text-sidebar-accent-foreground
disabled:pointer-events-none disabled:opacity-50 [&>span:last-child]:truncate [&>svg]:size-4
[&>svg]:shrink-0 [&>svg]:text-sidebar-accent-foreground",
```

```
  "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-foreground",
```

```
  size === "sm" && "text-xs",
```

```
  size === "md" && "text-sm",
```

```
  "group-data-[collapsible=icon]:hidden",
```

```
  className,
```

```
  )}
```

```
  {...props}
```

```
/>
```

```
);
```

```
});
```

```
SidebarMenuSubButton.displayName = "SidebarMenuSubButton";
```

```
export {
```

```
  Sidebar,
```

```
  SidebarContent,
```

```
  SidebarFooter,
```

```
  SidebarGroup,
```

```
  SidebarGroupAction,
```

```
  SidebarGroupContent,
```

```
  SidebarGroupLabel,
```

```
  SidebarHeader,
```

```
  SidebarInput,
```

```
  SidebarInset,
```



```
SidebarMenu,  
  
SidebarMenuAction,  
  
SidebarMenuBadge,  
  
SidebarMenuButton,  
  
SidebarMenuItem,  
  
SidebarMenuSkeleton,  
  
SidebarMenuSub,  
  
SidebarMenuSubButton,  
  
SidebarMenuSubItem,  
  
SidebarProvider,  
  
SidebarRail,  
  
SidebarSeparator,  
  
SidebarTrigger,  
  
useSidebar,  
  
};  
  
import { cn } from "@lib/utils";  
  
  
function Skeleton({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) {  
  return <div className={cn("animate-pulse rounded-md bg-muted", className)} {...props}  
/>;  
}  
  
  
export { Skeleton };  
  
import * as React from "react";  
  
import * as SliderPrimitive from "@radix-ui/react-slider";
```

```

import { cn } from "@/lib/utils";

const Slider = React.forwardRef<
  React.ElementRef<typeof SliderPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof SliderPrimitive.Root>
>(({ className, ...props }, ref) => (
  <SliderPrimitive.Root
    ref={ref}
    className={cn("relative flex w-full touch-none select-none items-center", className)}
    {...props}
  >
    <SliderPrimitive.Track className="relative h-2 w-full grow overflow-hidden rounded-full
bg-secondary">
      <SliderPrimitive.Range className="absolute h-full bg-primary" />
    </SliderPrimitive.Track>
    <SliderPrimitive.Thumb className="block h-5 w-5 rounded-full border-2 border-primary
bg-background ring-offset-background transition-colors focus-visible:outline-none focus-
visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none
disabled:opacity-50" />
  </SliderPrimitive.Root>
));

Slider.displayName = SliderPrimitive.Root.displayName;

export { Slider };

import { useTheme } from "next-themes";

import { Toaster as Sonner, toast } from "sonner";

```

```

type ToasterProps = React.ComponentProps<typeof Sonner>;

const Toaster = ({ ...props }: ToasterProps) => {

  const { theme = "system" } = useTheme();

  return (

    <Sonner

      theme={theme as ToasterProps["theme"]}

      className="toaster group"

      toastOptions={{

        classNames: {

          toast:

            "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-
            [.toaster]:border-border group-[.toaster]:shadow-lg",

          description: "group-[.toast]:text-muted-foreground",

          actionButton: "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",

          cancelButton: "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",

        },

      }}

      {...props}

    />

  );

};

export { Toaster, toast };

import * as React from "react";

```

```
import * as SwitchPrimitives from "@radix-ui/react-switch";
```

```
import { cn } from "@lib/utils";
```

```
const Switch = React.forwardRef<
```

```
  React.ElementRef<typeof SwitchPrimitives.Root>,
```

```
  React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
```

```
>(({ className, ...props }, ref) => (
```

```
  <SwitchPrimitives.Root
```

```
    className={cn(
```

```
      "peer inline-flex h-6 w-11 shrink-0 cursor-pointer items-center rounded-full border-2  
border-transparent transition-colors data-[state=checked]:bg-primary data-  
[state=unchecked]:bg-input focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-  
ring focus-visible:ring-offset-2 focus-visible:ring-offset-background disabled:cursor-not-  
allowed disabled:opacity-50",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
    ref={ref}
```

```
>
```

```
  <SwitchPrimitives.Thumb
```

```
    className={cn(
```

```
      "pointer-events-none block h-5 w-5 rounded-full bg-background shadow-lg ring-0  
transition-transform data-[state=checked]:translate-x-5 data-[state=unchecked]:translate-x-  
0",
```

```
    )}
```

```
  />
```

```
</SwitchPrimitives.Root>
```

```
));  
  
Switch.displayName = SwitchPrimitives.Root.displayName;
```

```
export { Switch };
```

```
import * as React from "react";
```

```
import { cn } from "@lib/utils";
```

```
const Table = React.forwardRef<HTMLTableElement,  
React.HTMLAttributes<HTMLTableElement>>(  
  
  ({ className, ...props }, ref) => (  
  
    <div className="relative w-full overflow-auto">  
  
      <table ref={ref} className={cn("w-full caption-bottom text-sm", className)} {...props} />  
  
    </div>  
  
  ),  
  
);
```

```
Table.displayName = "Table";
```

```
const TableHeader = React.forwardRef<HTMLTableSectionElement,  
React.HTMLAttributes<HTMLTableSectionElement>>(  
  
  ({ className, ...props }, ref) => <thead ref={ref} className={cn("&_tr:border-b", className)}  
  {...props} />,  
  
);
```

```
TableHeader.displayName = "TableHeader";
```

```
const TableBody = React.forwardRef<HTMLTableSectionElement,  
React.HTMLAttributes<HTMLTableSectionElement>>(  

```

```

({ className, ...props }, ref) => (
  <tbody ref={ref} className={cn("&_tr:last-child:border-0", className)} {...props} />
),
);

TableBody.displayName = "TableBody";

const TableFooter = React.forwardRef<HTMLTableSectionElement,
React.HTMLAttributes<HTMLTableSectionElement>>(
  ({ className, ...props }, ref) => (
    <tfoot ref={ref} className={cn("border-t bg-muted/50 font-medium [&>tr]:last:border-b-0", className)} {...props} />
  ),
);

TableFooter.displayName = "TableFooter";

const TableRow = React.forwardRef<HTMLTableRowElement,
React.HTMLAttributes<HTMLTableRowElement>>(
  ({ className, ...props }, ref) => (
    <tr
      ref={ref}
      className={cn("border-b transition-colors data-[state=selected]:bg-muted hover:bg-muted/50", className)}
      {...props}
    />
  ),
);

TableRow.displayName = "TableRow";

```

```

const TableHead = React.forwardRef<HTMLTableCellElement,
React.ThHTMLAttributes<HTMLTableCellElement>>(
  ({ className, ...props }, ref) => (
    <th
      ref={ref}
      className={cn(
        "h-12 px-4 text-left align-middle font-medium text-muted-foreground
[&:has([role=checkbox])]:pr-0",
        className,
      )}
      {...props}
    />
  ),
);

TableHead.displayName = "TableHead";

```

```

const TableCell = React.forwardRef<HTMLTableCellElement,
React.TdHTMLAttributes<HTMLTableCellElement>>(
  ({ className, ...props }, ref) => (
    <td ref={ref} className={cn("p-4 align-middle [&:has([role=checkbox])]:pr-0", className)}
      {...props} />
  ),
);

TableCell.displayName = "TableCell";

```

```

const TableCaption = React.forwardRef<HTMLTableCaptionElement,
React.HTMLAttributes<HTMLTableCaptionElement>>(

```

```

({ className, ...props }, ref) => (
  <caption ref={ref} className={cn("mt-4 text-sm text-muted-foreground", className)}
    {...props} />
),
);

TableCaption.displayName = "TableCaption";

export { Table, TableHeader, TableBody, TableFooter, TableHead, TableRow, TableCell,
  TableCaption };

import * as React from "react";

import * as TabsPrimitive from "@radix-ui/react-tabs";

import { cn } from "@lib/utils";

const Tabs = TabsPrimitive.Root;

const TabsList = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.List
    ref={ref}
    className={cn(
      "inline-flex h-10 items-center justify-center rounded-md bg-muted p-1 text-muted-foreground",
      className,
    )}
  >

```



```

    {...props}

  />

));

TabsList.displayName = TabsPrimitive.List.displayName;

const TabsTrigger = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Trigger
    ref={ref}
    className={cn(
      "inline-flex items-center justify-center whitespace-nowrap rounded-sm px-3 py-1.5 text-sm font-medium ring-offset-background transition-all data-[state=active]:bg-background data-[state=active]:text-foreground data-[state=active]:shadow-sm focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none disabled:opacity-50",
      className,
    )}
    {...props}
  />
));

TabsTrigger.displayName = TabsPrimitive.Trigger.displayName;

const TabsContent = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>

```

```
>(({ className, ...props }, ref) => (  
  
  <TabsPrimitive.Content  
  
    ref={ref}  
  
    className={cn(  
  
      "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-  
visible:ring-ring focus-visible:ring-offset-2",  
  
      className,  
  
    )}  
  
    {...props}  
  
  />  
  
));
```

```
TabsContent.displayName = TabsPrimitive.Content.displayName;
```

```
export { Tabs, TabsList, TabsTrigger, TabsContent };
```

```
import * as React from "react";
```

```
import { cn } from "@/lib/utils";
```

```
export interface TextareaProps extends  
React.TextareaHTMLAttributes<HTMLTextAreaElement> {}
```

```
const Textarea = React.forwardRef<HTMLTextAreaElement, TextareaProps>(({ className,  
...props }, ref) => {  
  
  return (  
  
    <textarea  
  
      className={cn(  

```

```
"flex min-h-[80px] w-full rounded-md border border-input bg-background px-3 py-2 text-sm ring-offset-background placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-not-allowed disabled:opacity-50",
```

```
  className,  
  
  )}  
  
  ref={ref}  
  
  {...props}  
  
/>  
  
);  
  
});  
  
Textarea.displayName = "Textarea";
```

```
export { Textarea };  
  
import * as React from "react";  
  
import * as ToastPrimitives from "@radix-ui/react-toast";  
  
import { cva, type VariantProps } from "class-variance-authority";  
  
import { X } from "lucide-react";
```

```
import { cn } from "@lib/utils";
```

```
const ToastProvider = ToastPrimitives.Provider;
```

```
const ToastViewport = React.forwardRef<  
  React.ElementRef<typeof ToastPrimitives.Viewport>,  
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>  
>(({ className, ...props }, ref) => (
```

```

<ToastPrimitives.Viewport
  ref={ref}

  className={cn(
    "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0
sm:top-auto sm:flex-col md:max-w-[420px]",
    className,
  )}
  {...props}
/>
));

ToastViewport.displayName = ToastPrimitives.Viewport.displayName;

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center justify-between space-x-4
overflow-hidden rounded-md border p-6 pr-8 shadow-lg transition-all data-
[swipe=cancel]:translate-x-0 data-[swipe=end]:translate-x-[var(--radix-toast-swipe-end-x)]
data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)] data-
[swipe=move]:transition-none data-[state=open]:animate-in data-[state=closed]:animate-out
data-[swipe=end]:animate-out data-[state=closed]:fade-out-80 data-[state=closed]:slide-out-
to-right-full data-[state=open]:slide-in-from-top-full data-[state=open]:sm:slide-in-from-
bottom-full",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive: "destructive group border-destructive bg-destructive text-destructive-
foreground",
      },
    },
  },
);

```

```

defaultVariants: {
  variant: "default",
},
},
);

const Toast = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> & VariantProps<typeof
toastVariants>
>(({ className, variant, ...props }, ref) => {
  return <ToastPrimitives.Root ref={ref} className={cn(toastVariants({ variant }), className)}
{...props} />;
});

Toast.displayName = ToastPrimitives.Root.displayName;

const ToastAction = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Action>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Action
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-
3 text-sm font-medium ring-offset-background transition-colors group-[.destructive]:border-
muted/40 hover:bg-secondary group-[.destructive]:hover:border-destructive/30 group-
[.destructive]:hover:bg-destructive group-[.destructive]:hover:text-destructive-foreground
focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 group-
[.destructive]:focus:ring-destructive disabled:pointer-events-none disabled:opacity-50",

```

```

    className,

  })

  {...props}

/>

));

ToastAction.displayName = ToastPrimitives.Action.displayName;

```

```

const ToastClose = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Close>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Close
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity
group-hover:opacity-100 group-[.destructive]:text-red-300 hover:text-foreground group-
[.destructive]:hover:text-red-50 focus:opacity-100 focus:outline-none focus:ring-2 group-
[.destructive]:focus:ring-red-400 group-[.destructive]:focus:ring-offset-red-600",
      className,
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </ToastPrimitives.Close>
));

ToastClose.displayName = ToastPrimitives.Close.displayName;

```

```
const ToastTitle = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Title>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Title ref={ref} className={cn("text-sm font-semibold", className)}
  {...props} />
));

ToastTitle.displayName = ToastPrimitives.Title.displayName;

const ToastDescription = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Description>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Description ref={ref} className={cn("text-sm opacity-90", className)}
  {...props} />
));

ToastDescription.displayName = ToastPrimitives.Description.displayName;

type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>;

type ToastActionElement = React.ReactElement<typeof ToastAction>;

export {
  type ToastProps,
  type ToastActionElement,
  ToastProvider,
```

```
ToastViewport,  
  
Toast,  
  
ToastTitle,  
  
ToastDescription,  
  
ToastClose,  
  
ToastAction,  
  
};  
  
import { useToast } from "@/hooks/use-toast";  
  
import { Toast, ToastClose, ToastDescription, ToastProvider, ToastTitle, ToastViewport } from  
"@/components/ui/toast";  
  
export function Toaster() {  
  
  const { toasts } = useToast();  
  
  return (  
  
    <ToastProvider>  
  
      {toasts.map(function ({ id, title, description, action, ...props }) {  
  
        return (  
  
          <Toast key={id} {...props}>  
  
            <div className="grid gap-1">  
  
              {title && <ToastTitle>{title}</ToastTitle>  
  
              {description && <ToastDescription>{description}</ToastDescription>  
  
            </div>  
  
            {action}  
  
            <ToastClose />  
  
          </Toast>  
  
        )  
  
      )}
```



```

    );

  }}}

  <ToastViewport />

</ToastProvider>

);

}

import * as React from "react";

import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group";

import { type VariantProps } from "class-variance-authority";

import { cn } from "@lib/utils";

import { toggleVariants } from "@components/ui/toggle";

const ToggleGroupContext = React.createContext<VariantProps<typeof toggleVariants>>({
  size: "default",
  variant: "default",
});

const ToggleGroup = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Root> &
  VariantProps<typeof toggleVariants>
>(({ className, variant, size, children, ...props }, ref) => (
  <ToggleGroupPrimitive.Root ref={ref} className={cn("flex items-center justify-center gap-1",
    className)} {...props}>

    <ToggleGroupContext.Provider value={{ variant, size }}>{children}</ToggleGroupContext.Provider>
  </ToggleGroupPrimitive.Root>

```

```
</ToggleGroupPrimitive.Root>
```

```
));
```

```
ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName;
```

```
const ToggleGroupItem = React.forwardRef<
```

```
  React.ElementRef<typeof ToggleGroupPrimitive.Item>,
```

```
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Item> &  
  VariantProps<typeof toggleVariants>
```

```
>(({ className, children, variant, size, ...props }, ref) => {
```

```
  const context = React.useContext(ToggleGroupContext);
```

```
  return (
```

```
    <ToggleGroupPrimitive.Item
```

```
      ref={ref}
```

```
      className={cn(
```

```
        toggleVariants({
```

```
          variant: context.variant || variant,
```

```
          size: context.size || size,
```

```
        }),
```

```
        className,
```

```
      )}
```

```
      {...props}
```

```
    {children}
```

```
  </ToggleGroupPrimitive.Item>
```

```
);
```

```
});
```

```
ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName;
```

```
export { ToggleGroup, ToggleGroupItem };
```

```
import * as React from "react";
```

```
import * as TogglePrimitive from "@radix-ui/react-toggle";
```

```
import { cva, type VariantProps } from "class-variance-authority";
```

```
import { cn } from "@lib/utils";
```

```
const toggleVariants = cva(
```

```
  "inline-flex items-center justify-center rounded-md text-sm font-medium ring-offset-  
background transition-colors hover:bg-muted hover:text-muted-foreground focus-  
visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2  
disabled:pointer-events-none disabled:opacity-50 data-[state=on]:bg-accent data-  
[state=on]:text-accent-foreground",
```

```
{
```

```
  variants: {
```

```
    variant: {
```

```
      default: "bg-transparent",
```

```
      outline: "border border-input bg-transparent hover:bg-accent hover:text-accent-  
foreground",
```

```
    },
```

```
    size: {
```

```
      default: "h-10 px-3",
```

```
      sm: "h-9 px-2.5",
```

```

    lg: "h-11 px-5",

  },

},

defaultVariants: {

  variant: "default",

  size: "default",

},

},

);

const Toggle = React.forwardRef<

  React.ElementRef<typeof TogglePrimitive.Root>,

  React.ComponentPropsWithoutRef<typeof TogglePrimitive.Root> & VariantProps<typeof
toggleVariants>

>(({ className, variant, size, ...props }, ref) => (

  <TogglePrimitive.Root ref={ref} className={cn(toggleVariants({ variant, size, className })
)} {...props} />

));

Toggle.displayName = TogglePrimitive.Root.displayName;

export { Toggle, toggleVariants };

import * as React from "react";

import * as TooltipPrimitive from "@radix-ui/react-tooltip";

import { cn } from "@lib/utils";

```

```
const TooltipProvider = TooltipPrimitive.Provider;
```

```
const Tooltip = TooltipPrimitive.Root;
```

```
const TooltipTrigger = TooltipPrimitive.Trigger;
```

```
const TooltipContent = React.forwardRef<
```

```
  React.ElementRef<typeof TooltipPrimitive.Content>,
```

```
  React.ComponentPropsWithoutRef<typeof TooltipPrimitive.Content>
```

```
>(({ className, sideOffset = 4, ...props }, ref) => (
```

```
  <TooltipPrimitive.Content
```

```
    ref={ref}
```

```
    sideOffset={sideOffset}
```

```
    className={cn(
```

```
      "z-50 overflow-hidden rounded-md border bg-popover px-3 py-1.5 text-sm text-popover-foreground shadow-md animate-in fade-in-0 zoom-in-95 data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=closed]:zoom-out-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
```

```
      className,
```

```
    )}
```

```
    {...props}
```

```
  />
```

```
));
```

```
TooltipContent.displayName = TooltipPrimitive.Content.displayName;
```

```
export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider };
```

```
import { useToast, toast } from "@hooks/use-toast";

export { useToast, toast };

import React, { useState, useRef } from 'react';

import { Dialog, DialogContent } from '@components/ui/dialog';

import { Button } from '@components/ui/button';

import { Camera, Upload, X, Loader2, Check, AlertTriangle, RotateCcw, Sparkles, ImageIcon } from 'lucide-react';

import { cn } from '@lib/Utils';

import { MealType } from '@types';

import { FoodAnalysis, FoodItem } from '@types/food';

interface AddFoodModalProps {

  isOpen: boolean;

  onClose: () => void;

  mealType: MealType;

  onAnalyze: (imageBase64: string) => Promise<FoodAnalysis>;

  onSave: (analysis: FoodAnalysis, imageUrl?: string) => void;

  isAnalyzing: boolean;

  isSaving: boolean;

}

function getFreshnessConfig(score: number) {

  if (score >= 0.7) return { label: 'Fresh', color: 'text-success', bg: 'bg-success/15' };

  if (score >= 0.4) return { label: 'Okay', color: 'text-warning', bg: 'bg-warning/15' };

  return { label: 'Check', color: 'text-destructive', bg: 'bg-destructive/15' };
```

```
}
```

```
function MacroBar({ label, value, color, icon }: { label: string; value: number; color: string; icon: string }) {
```

```
  return (
```

```
    <div className="flex items-center gap-3 py-2">
```

```
      <span className="text-lg">{icon}</span>
```

```
      <div className="flex-1">
```

```
        <div className="flex justify-between items-baseline mb-1">
```

```
          <span className="text-sm font-medium text-foreground">{label}</span>
```

```
          <span className="text-sm font-bold text-foreground">{Math.round(value)}g</span>
```

```
        </div>
```

```
      <div className="h-1.5 bg-secondary rounded-full overflow-hidden">
```

```
        <div
```

```
          className={cn("h-full rounded-full transition-all duration-500", color)}
```

```
          style={{ width: `${Math.min((value / 100) * 100, 100)}%` }}
```

```
        />
```

```
      </div>
```

```
    </div>
```

```
  </div>
```

```
);
```

```
}
```

```
function FoodItemCard({ food, index }: { food: FoodItem; index: number }) {
```

```
  const freshness = getFreshnessConfig(food.freshness_score);
```

```
return (
```

```
<div
```

```
  className="bg-secondary/50 rounded-2xl p-4 animate-slide-up"
```

```
  style={{ animationDelay: `${index * 100}ms` }}
```

```
>
```

```
<div className="flex justify-between items-start mb-3">
```

```
  <div className="flex-1">
```

```
    <h4 className="font-display font-bold text-foreground capitalize text-base">
```

```
      {food.name}
```

```
    </h4>
```

```
    <p className="text-sm text-muted-foreground">
```

```
      {food.portion_size} · ~{Math.round(food.estimated_weight_grams || 0)}g
```

```
    </p>
```

```
  </div>
```

```
<div className="text-right">
```

```
  <span className="text-xl font-display font-bold text-primary">
```

```
    {Math.round(food.estimated_calories)}
```

```
  </span>
```

```
  <span className="text-sm text-muted-foreground ml-1">kcal</span>
```

```
</div>
```

```
</div>
```

```
<div className="flex items-center justify-between">
```

```
  <div className={cn('flex items-center gap-1.5 px-2.5 py-1 rounded-full text-xs font-medium', freshness.bg, freshness.color)}>
```

```
    <span>{freshness.label}</span>
```



```

</div>

<div className="flex gap-4 text-xs text-muted-foreground">

  <span>🍞 {Math.round(food.macros.carbs_g)}g</span>

  <span>🥩 {Math.round(food.macros.protein_g)}g</span>

  <span>🧈 {Math.round(food.macros.fat_g)}g</span>

</div>

</div>

</div>

);
}

```

```

export const AddFoodModal: React.FC<AddFoodModalProps> = ({
  isOpen,
  onClose,
  mealType,
  onAnalyze,
  onSave,
  isAnalyzing,
  isSaving,
}) => {

  const [preview, setPreview] = useState<string | null>(null);

  const [analysis, setAnalysis] = useState<FoodAnalysis | null>(null);

  const [error, setError] = useState<string | null>(null);

  // Separate refs for camera capture and gallery upload

  const cameraInputRef = useRef<HTMLInputElement>(null);

```

```
const galleryInputRef = useRef<HTMLInputElement>(null);
```

```
const handleFileChange = (e: React.ChangeEvent<HTMLInputElement>) => {
```

```
  const file = e.target.files?.[0];
```

```
  if (!file) return;
```

```
  // Validate file type
```

```
  if (!file.type.startsWith('image/')) {
```

```
    setError('Please select an image file!');
```

```
    return;
```

```
  }
```

```
  // Validate file size (max 10MB)
```

```
  if (file.size > 10 * 1024 * 1024) {
```

```
    setError('Image is too large. Please select an image under 10MB!');
```

```
    return;
```

```
  }
```

```
  setError(null);
```

```
  const reader = new FileReader();
```

```
  reader.onload = (event) => {
```

```
    const dataUrl = event.target?.result as string;
```

```
    setPreview(dataUrl);
```

```
    handleAnalyze(dataUrl);
```

```
  };
```

```
  reader.onerror = () => {
```

```
      setError('Failed to read image file. Please try again.');
```

```
};
```

```
reader.readAsDataURL(file);
```



```
// Reset input so the same file can be selected again
```

```
e.target.value = '';
```

```
};
```



```
const handleTakePhoto = () => {
```

```
  setError(null);
```

```
  // Use the camera input - capture="environment" opens rear camera directly on mobile
```

```
  cameraInputRef.current?.click();
```

```
};
```



```
const handleUpload = () => {
```

```
  setError(null);
```

```
  // Use the gallery input - no capture attribute opens file picker / gallery
```

```
  galleryInputRef.current?.click();
```

```
};
```



```
const handleAnalyze = async (imageData: string) => {
```

```
  try {
```

```
    setError(null);
```

```
    const result = await onAnalyze(imageData);
```

```
    setAnalysis(result);
```

```
  } catch (err) {
```

```
    console.error('Analysis failed:', err);

    setError(err instanceof Error ? err.message : 'Failed to analyze image. Please try again.');
```

```
const handleSave = () => {
  if (analysis) {
    onSave(analysis, preview || undefined);
    handleClose();
  }
};
```

```
const handleClose = () => {
  setPreview(null);
  setAnalysis(null);
  setError(null);

  if (cameraInputRef.current) cameraInputRef.current.value = "";
  if (galleryInputRef.current) galleryInputRef.current.value = "";

  onClose();
};
```

```
const handleRetry = () => {
  setPreview(null);
  setAnalysis(null);
  setError(null);
};
```

```
// Calculate total macros
```

```
const totalMacros = analysis?.food_items.reduce(
```

```
(acc, item) => ({
```

```
  carbs: acc.carbs + item.macros.carbs_g,
```

```
  protein: acc.protein + item.macros.protein_g,
```

```
  fat: acc.fat + item.macros.fat_g,
```

```
}),
```

```
{ carbs: 0, protein: 0, fat: 0 }
```

```
) || { carbs: 0, protein: 0, fat: 0 };
```

```
return (
```

```
<Dialog open={isOpen} onOpenChange={handleClose}>
```

```
  <DialogContent className="max-w-md mx-auto max-h-[90vh] overflow-y-auto p-0 gap-0  
bg-background border-border">
```

```
    {/* Header */}
```

```
    <div className="sticky top-0 z-10 flex items-center justify-between p-4 bg-  
background/95 backdrop-blur-sm border-b border-border">
```

```
      <div>
```

```
        <h2 className="font-display font-bold text-lg text-foreground">Add {mealType}</h2>
```

```
        <p className="text-xs text-muted-foreground">Capture or upload your food</p>
```

```
      </div>
```

```
    <button
```

```
      onClick={handleClose}
```

```
      className="p-2 hover:bg-secondary rounded-full transition-colors touch-target"
```

```
>
```

```
    <X className="h-5 w-5 text-muted-foreground" />
```

```
</button>
```

```
</div>
```

```
<div className="p-4">
```

```
  { /* Hidden file inputs */ }
```

```
  { /* Camera input - uses capture="environment" for direct rear camera access on mobile */ }
```

```
  <input
```

```
    ref={cameraInputRef}
```

```
    type="file"
```

```
    accept="image/*"
```

```
    capture="environment"
```

```
    className="hidden"
```

```
    onChange={handleFileChange}
```

```
  />
```

```
  { /* Gallery input - no capture attribute opens file picker/gallery */ }
```

```
  <input
```

```
    ref={galleryInputRef}
```

```
    type="file"
```

```
    accept="image/*"
```

```
    className="hidden"
```

```
    onChange={handleFileChange}
```

```
  />
```

```
  { /* Initial State - Show capture options */ }
```

```
  { !preview && !isAnalyzing && (
```

```
<div className="space-y-5 animate-fade-in">
```

```
{/* Visual placeholder */}
```

```
<div className="aspect-[4/3] bg-gradient-to-br from-secondary/80 to-secondary/40 rounded-2xl flex flex-col items-center justify-center border-2 border-dashed border-border/60">
```

```
<div className="w-20 h-20 rounded-full bg-primary/10 flex items-center justify-center mb-4">
```

```
<Camera className="h-10 w-10 text-primary" />
```

```
</div>
```

```
<p className="text-foreground font-semibold text-lg mb-1">Snap your meal</p>
```

```
<p className="text-muted-foreground text-sm text-center px-6">
```

```
AI will detect foods and calculate calories instantly
```

```
</p>
```

```
</div>
```

```
{/* Action buttons */}
```

```
<div className="grid grid-cols-2 gap-3">
```

```
<Button
```

```
onClick={handleTakePhoto}
```

```
className="h-16 flex-col gap-1.5 rounded-2xl gradient-fresh text-primary-foreground shadow-glow-sm hover:opacity-90 transition-all touch-target"
```

```
>
```

```
<Camera className="h-6 w-6" />
```

```
<span className="text-sm font-bold">Take Photo</span>
```

```
</Button>
```

```
<Button
```

```
onClick={handleUpload}
```

```
variant="outline"
```

```
className="h-16 flex-col gap-1.5 rounded-2xl border-2 hover:border-primary  
hover:bg-primary/5 transition-all touch-target"
```

```
>
```

```
<ImageIcon className="h-6 w-6 text-primary" />
```

```
<span className="text-sm font-bold text-foreground">Gallery</span>
```

```
</Button>
```

```
</div>
```

```
{/* Error display */}
```

```
{error && (
```

```
<div className="p-4 bg-destructive/10 border border-destructive/20 rounded-xl  
animate-slide-up">
```

```
<div className="flex items-start gap-3">
```

```
<AlertTriangle className="h-5 w-5 text-destructive flex-shrink-0 mt-0.5" />
```

```
<div className="flex-1">
```

```
<p className="text-sm font-medium text-destructive">{error}</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
)}
```

```
{/* Helper text */}
```

```
<p className="text-xs text-center text-muted-foreground">
```

```
📷 Take Photo opens your camera directly<br/>
```

```
🖼️ Gallery lets you choose from photos
```

```
</p>
```



```
</div>
```

```
)}
```

```
{/* Analyzing State */}
```

```
{isAnalyzing && preview && (
```

```
<div className="space-y-6 animate-fade-in">
```

```
<div className="relative aspect-[4/3] rounded-2xl overflow-hidden">
```

```
<img src={preview} alt="Food" className="w-full h-full object-cover" />
```

```
<div className="absolute inset-0 bg-background/80 backdrop-blur-sm flex flex-col  
items-center justify-center">
```

```
<div className="relative">
```

```
<div className="w-16 h-16 rounded-full bg-primary/20 flex items-center justify-  
center animate-pulse">
```

```
<Sparkles className="h-8 w-8 text-primary animate-spin" style={{  
animationDuration: '2s' }} />
```

```
</div>
```

```
</div>
```

```
<p className="mt-4 font-display font-bold text-foreground">Analyzing your meal...  
</p>
```

```
<p className="text-sm text-muted-foreground">Detecting ingredients &  
nutrition</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
)}
```

```
{/* Preview with Error */}
```

```
{preview && error && !isAnalyzing && !analysis && (
```

```

<div className="space-y-4 animate-fade-in">

  <div className="relative aspect-[4/3] rounded-2xl overflow-hidden">

    <img src={preview} alt="Food" className="w-full h-full object-cover" />

  </div>

  <div className="p-4 bg-destructive/10 border border-destructive/20 rounded-xl">

    <div className="flex items-start gap-3">

      <AlertTriangle className="h-5 w-5 text-destructive flex-shrink-0 mt-0.5" />

      <div className="flex-1">

        <p className="text-sm font-medium text-destructive mb-3">{error}</p>

        <div className="flex gap-2">

          <Button size="sm" onClick={handleRetry} variant="outline" className="flex-1">

            <RotateCcw className="h-4 w-4 mr-1" />

            Try Again

          </Button>

        </div>

      </div>

    </div>

  </div>

</div>

)}

```

```

{/* Analysis Results */}

```

```

{analysis && !isAnalyzing && (

```

```

  <div className="space-y-5 animate-fade-in">

```

```

    {/* Image preview */}

```

```

    {preview && (

```

```
<div className="relative aspect-[4/3] rounded-2xl overflow-hidden shadow-lg">
```

```
<img src={preview} alt="Food" className="w-full h-full object-cover" />
```

```
<div className="absolute top-3 right-3 px-3 py-1.5 bg-background/90 backdrop-blur-sm rounded-full shadow-lg">
```

```
<span className="text-lg font-display font-bold text-primary">
```

```
{Math.round(analysis.total_calories)} kcal
```

```
</span>
```

```
</div>
```

```
</div>
```

```
)}
```

```
{/* Detected foods */}
```

```
<div className="space-y-3">
```

```
<div className="flex items-center gap-2">
```

```
<Check className="h-5 w-5 text-success" />
```

```
<h3 className="font-display font-bold text-foreground">
```

```
{analysis.food_items.length} item{analysis.food_items.length > 1 ? 's' : ''} detected
```

```
</h3>
```

```
</div>
```

```
{analysis.food_items.map((food, index) => (
```

```
<FoodItemCard key={index} food={food} index={index} />
```

```
))}
```

```
</div>
```

```
{/* Total macros */}
```

```

<div className="bg-secondary/30 rounded-2xl p-4 border border-border/50">

  <h4 className="font-display font-bold text-foreground mb-2">Total Nutrition</h4>

  <MacroBar label="Carbs" value={totalMacros.carbs} color="bg-amber-500" icon="🍞"
/>

  <MacroBar label="Protein" value={totalMacros.protein} color="bg-rose-500"
icon="🥩" />

  <MacroBar label="Fat" value={totalMacros.fat} color="bg-blue-500" icon="🧈" />

</div>


{/* Confidence */}

{analysis.confidence && (

  <div className="flex items-center justify-center gap-2 text-sm text-muted-
foreground">

    <Sparkles className="h-4 w-4 text-primary" />

    <span>AI Confidence: {Math.round(analysis.confidence * 100)}%</span>

  </div>

)}


{/* Actions */}

<div className="flex gap-3 pt-2">

  <Button

    onClick={handleRetry}

    variant="outline"

    className="flex-1 h-12 rounded-xl border-2"

    >

    <RotateCcw className="h-5 w-5 mr-2" />

    Retake

```

```
</Button>
```

```
<Button
```

```
  onClick={handleSave}
```

```
  disabled={isSaving}
```

```
  className="flex-1 h-12 rounded-xl gradient-fresh text-primary-foreground shadow-  
glow-sm"
```

```
>
```

```
  {isSaving ? (
```

```
    <>
```

```
      <Loader2 className="h-5 w-5 mr-2 animate-spin" />
```

```
      Saving...
```

```
    </>
```

```
  ) : (
```

```
    <>
```

```
      <Check className="h-5 w-5 mr-2" />
```

```
      Log Meal
```

```
    </>
```

```
  )}
```

```
</Button>
```

```
</div>
```

```
</div>
```

```
  )}
```

```
</div>
```

```
</DialogContent>
```

```
</Dialog>
```

```
);
```

```
};

import React from 'react';

import { Home, ClipboardList, BarChart3, User, Plus } from 'lucide-react';

import { cn } from '@lib/utls';

import { AppView } from '@types';

interface BottomNavProps {

  currentView: AppView;

  onNavigate: (view: AppView) => void;

  onScanPress: () => void;

  scansRemaining?: number;

}

const navItems: { id: AppView; icon: React.ElementType; label: string }[] = [

  { id: 'HOME', icon: Home, label: 'Home' },

  { id: 'LOG', icon: ClipboardList, label: 'Log' },

  { id: 'INSIGHTS', icon: BarChart3, label: 'Insights' },

  { id: 'PROFILE', icon: User, label: 'Profile' },

];

export const BottomNav: React.FC<BottomNavProps> = ({

  currentView,

  onNavigate,

  onScanPress,

  scansRemaining

}) => {
```

```

return (

  <nav className="fixed bottom-0 left-0 right-0 bg-card/95 backdrop-blur-lg border-t
border-border safe-bottom z-50">

    <div className="flex items-center justify-around px-2 py-2 max-w-md mx-auto relative">

      {/* Left side items */}

      {navItems.slice(0, 2).map((item) => {

        const Icon = item.icon;

        const isActive = currentView === item.id;

        return (

          <button

            key={item.id}

            onClick={() => onNavigate(item.id)}

            className={cn(

              'flex flex-col items-center justify-center py-2 px-4 rounded-xl transition-all touch-
target',

              isActive ? 'text-primary' : 'text-muted-foreground hover:text-foreground'

            )}

          >

            <Icon size={22} strokeWidth={isActive ? 2.5 : 2} />

            <span className={cn(

              'text-xs mt-1 font-medium',

              isActive && 'font-semibold'

            )}>

              {item.label}

            </span>

          </button>

        );

```

```
}}}
```

```
{/* Center Scan Button */}
```

```
<div className="relative -mt-8">
```

```
<button
```

```
  onClick={onScanPress}
```

```
  className="relative flex items-center justify-center"
```

```
>
```

```
  <div className="absolute inset-0 bg-primary/30 rounded-full blur-xl animate-pulse" />
```

```
    <div className="relative flex items-center gap-2 bg-primary hover:bg-primary/90 text-  
primary-foreground px-6 py-3.5 rounded-full shadow-glow transition-all hover:scale-105  
active:scale-95 touch-target">
```

```
      <Plus size={20} strokeWidth={2.5} />
```

```
      <span className="text-sm font-bold">Scan</span>
```

```
    </div>
```

```
</button>
```

```
{scansRemaining !== undefined && (
```

```
  <div className="absolute -bottom-5 left-1/2 -translate-x-1/2 px-2 py-0.5 bg-secondary  
rounded-full whitespace-nowrap">
```

```
    <span className="text-[10px] font-bold text-muted-foreground">
```

```
      {scansRemaining} left today
```

```
    </span>
```

```
  </div>
```

```
)}
```

```
</div>
```

```
{/* Right side items */}
```



```

{navItems.slice(2).map((item) => {

  const Icon = item.icon;

  const isActive = currentView === item.id;

  return (

    <button

      key={item.id}

      onClick={() => onNavigate(item.id)}

      className={cn(

        'flex flex-col items-center justify-center py-2 px-4 rounded-xl transition-all touch-
target',

        isActive ? 'text-primary' : 'text-muted-foreground hover:text-foreground'

      )}

    >

      <Icon size={22} strokeWidth={isActive ? 2.5 : 2} />

      <span className={cn(

        'text-xs mt-1 font-medium',

        isActive && 'font-semibold'

      )}>

        {item.label}

      </span>

    </button>

  );

}}

</div>

</nav>

);

```

```
};

export default BottomNav;

import React from 'react';

import { cn } from '@lib/utls';

interface CircularProgressProps {

  value: number;

  max: number;

  size?: 'sm' | 'md' | 'lg' | 'xl';

  strokeWidth?: number;

  color?: 'primary' | 'water' | 'steps' | 'calories';

  showValue?: boolean;

  label?: string;

  sublabel?: string;

  className?: string;

  children?: React.ReactNode;

}

const sizeConfig = {

  sm: { diameter: 80, fontSize: 'text-lg', labelSize: 'text-xs' },

  md: { diameter: 120, fontSize: 'text-2xl', labelSize: 'text-sm' },

  lg: { diameter: 160, fontSize: 'text-3xl', labelSize: 'text-base' },

  xl: { diameter: 200, fontSize: 'text-4xl', labelSize: 'text-lg' },

};
```

```
const colorConfig = {  
  primary: 'stroke-primary',  
  water: 'stroke-blue-500',  
  steps: 'stroke-orange-500',  
  calories: 'stroke-destructive',  
};
```

```
export const CircularProgress: React.FC<CircularProgressProps> = ({  
  value,  
  max,  
  size = 'md',  
  strokeWidth = 8,  
  color = 'primary',  
  showValue = true,  
  label,  
  sublabel,  
  className,  
  children,  
}) => {  
  const { diameter, fontSize, labelSize } = sizeConfig[size];  
  const radius = (diameter - strokeWidth) / 2;  
  const circumference = 2 * Math.PI * radius;  
  const progress = Math.min(value / max, 1);  
  const strokeDashoffset = circumference * (1 - progress);  
  
  return (  

```

```
<div className={cn('relative inline-flex items-center justify-center', className)}>
```

```
<svg
```

```
  width={diameter}
```

```
  height={diameter}
```

```
  className="transform -rotate-90"
```

```
>
```

```
  { /* Background circle */ }
```

```
<circle
```

```
  cx={diameter / 2}
```

```
  cy={diameter / 2}
```

```
  r={radius}
```

```
  fill="none"
```

```
  stroke="currentColor"
```

```
  strokeWidth={strokeWidth}
```

```
  className="text-secondary"
```

```
/>
```

```
  { /* Progress circle */ }
```

```
<circle
```

```
  cx={diameter / 2}
```

```
  cy={diameter / 2}
```

```
  r={radius}
```

```
  fill="none"
```

```
  strokeWidth={strokeWidth}
```

```
  strokeLinecap="round"
```

```
  strokeDasharray={circumference}
```

```
  strokeDashoffset={strokeDashoffset}
```

```
      className={cn('transition-all duration-500', colorConfig[color])}

    />

</svg>

{/* Center content */}

<div className="absolute inset-0 flex flex-col items-center justify-center">

  {children || (

    <>

      {showValue && (

        <span className={cn('font-display font-bold text-foreground', fontSize)}>

          {Math.round(value).toLocaleString()}

        </span>

      )}

      {label && (

        <span className={cn('text-muted-foreground', labelSize)}>

          {label}

        </span>

      )}

      {sublabel && (

        <span className={cn('text-muted-foreground', 'text-xs')}>

          {sublabel}

        </span>

      )}

    </>

  )}

</div>
```

```
</div>
```

```
);
```

```
};
```

```
export default CircularProgress;
```

```
import { Flame, Target } from 'lucide-react';
```

```
import { Card } from '@components/ui/card';
```

```
interface DailyStatsProps {
```

```
  todayCalories: number;
```

```
  targetCalories?: number;
```

```
}
```

```
export function DailyStats({ todayCalories, targetCalories = 2000 }: DailyStatsProps) {
```

```
  const progress = Math.min((todayCalories / targetCalories) * 100, 100);
```

```
  const remaining = Math.max(targetCalories - todayCalories, 0);
```

```
  return (
```

```
    <Card className="p-5 gradient-card shadow-soft overflow-hidden">
```

```
      <div className="flex items-center justify-between mb-4">
```

```
        <div>
```

```
          <h3 className="font-display font-bold text-lg text-foreground">Today's Progress</h3>
```

```
          <p className="text-sm text-muted-foreground">
```

```
            {remaining > 0 ? `${Math.round(remaining)} kcal remaining` : 'Goal reached!'}
```

```
          </p>
```

```
        </div>
```

```
<div className="h-12 w-12 rounded-full gradient-fresh flex items-center justify-center shadow-glow">

  <Flame className="h-6 w-6 text-primary-foreground" />

</div>

</div>

{/* Progress bar */}

<div className="relative h-3 bg-secondary rounded-full overflow-hidden mb-4">

  <div

    className="absolute inset-y-0 left-0 gradient-fresh rounded-full transition-all duration-500"

    style={{ width: `${progress}%` }}

  />

</div>

{/* Stats */}

<div className="grid grid-cols-2 gap-4">

  <div className="p-3 rounded-xl bg-secondary/50">

    <div className="flex items-center gap-2 mb-1">

      <Flame className="h-4 w-4 text-primary" />

      <span className="text-sm text-muted-foreground">Consumed</span>

    </div>

    <span className="text-2xl font-display font-bold text-foreground">

      {Math.round(todayCalories)}

    </span>

    <span className="text-sm text-muted-foreground ml-1">kcal</span>

  </div>

</div>
```

```

<div className="p-3 rounded-xl bg-secondary/50">

  <div className="flex items-center gap-2 mb-1">

    <Target className="h-4 w-4 text-accent" />

    <span className="text-sm text-muted-foreground">Target</span>

  </div>

  <span className="text-2xl font-display font-bold text-foreground">
    {targetCalories}
  </span>

  <span className="text-sm text-muted-foreground ml-1">kcal</span>

</div>

</div>

</Card>

);

}

import { FoodAnalysis, FoodItem } from '@types/food';

import { Card } from '@components/ui/card';

import { Button } from '@components/ui/button';

import {
  AlertTriangle,
  Check,
  Flame,
  Beef,
  Wheat,
  Droplets,
  Leaf,
  Save,

```


X

```
} from 'lucide-react';
```

```
import { cn } from '@lib/Utils';
```

```
interface FoodAnalysisResultProps {
```

```
  analysis: FoodAnalysis;
```

```
  onSave: () => void;
```

```
  onDiscard: () => void;
```

```
  isSaving: boolean;
```

```
}
```

```
function getFreshnessStatus(score: number): 'fresh' | 'acceptable' | 'spoiled' {
```

```
  if (score >= 0.7) return 'fresh';
```

```
  if (score >= 0.4) return 'acceptable';
```

```
  return 'spoiled';
```

```
}
```

```
function FreshnessIndicator({ score }: { score: number }) {
```

```
  const status = getFreshnessStatus(score);
```

```
  const getConfig = () => {
```

```
    switch (status) {
```

```
      case 'fresh':
```

```
        return {
```

```
          color: 'text-success',
```

```
          bg: 'bg-success/10',
```

```
    icon: Check,

    label: 'Fresh',

};

case 'acceptable':

    return {

        color: 'text-warning',

        bg: 'bg-warning/10',

        icon: AlertTriangle,

        label: 'Acceptable',

    };

case 'spoiled':

    return {

        color: 'text-destructive',

        bg: 'bg-destructive/10',

        icon: AlertTriangle,

        label: 'Spoiled',

    };

default:

    return {

        color: 'text-muted-foreground',

        bg: 'bg-muted',

        icon: Leaf,

        label: 'Unknown',

    };

}

};
```

```
const config = getConfig();

const Icon = config.icon;

return (
  <div className={cn('flex items-center gap-2 px-3 py-1.5 rounded-full', config.bg)}>
    <Icon className={cn('h-4 w-4', config.color)} />
    <span className={cn('text-sm font-medium', config.color)}>
      {config.label} ({Math.round(score * 100)}%)
    </span>
  </div>
);
}
```

```
function NutrientPill({
  icon: Icon,
  label,
  value,
  unit,
  colorClass,
}: {
  icon: React.ElementType;
  label: string;
  value: number;
  unit: string;
  colorClass: string;
```

```

    }) {

    return (

      <div className="flex flex-col items-center p-3 rounded-xl bg-secondary/50">

        <Icon className={cn('h-5 w-5 mb-1', colorClass)} />

        <span className="text-lg font-bold font-display">{Math.round(value)}{unit}</span>

        <span className="text-xs text-muted-foreground">{label}</span>

      </div>

    );
  }

```

```

function FoodItemCard({ food, index }: { food: FoodItem; index: number }) {

  return (

    <div className="p-4 bg-secondary/30 rounded-xl animate-scale-in" style={{
      animationDelay: `${index * 100}ms` }}>

      <div className="flex justify-between items-start mb-3">

        <div>

          <h4 className="font-display font-bold text-foreground capitalize">

            {food.name}

          </h4>

          <p className="text-sm text-muted-foreground">

            {food.portion_size || 'Estimated'} • ~{Math.round(food.estimated_weight_grams || 0)}g

          </p>

        </div>

        <div className="text-right">

          <span className="text-2xl font-display font-bold text-primary">

            {Math.round(food.estimated_calories)}


```


kcal

</div>

</div>

<div className="flex items-center justify-between mb-3">

<FreshnessIndicator score={food.freshness_score} />

</div>

<div className="grid grid-cols-3 gap-2">

<NutrientPill

icon={Beef}

label="Protein"

value={food.macros.protein_g}

unit="g"

colorClass="text-red-500"

/>

<NutrientPill

icon={Wheat}

label="Carbs"

value={food.macros.carbs_g}

unit="g"

colorClass="text-amber-500"

/>

<NutrientPill

icon={Droplets}

```

        label="Fat"

        value={food.macros.fat_g}

        unit="g"

        colorClass="text-blue-500"

    />

</div>

</div>

);

}

export function FoodAnalysisResult({
  analysis,
  onSave,
  onDiscard,
  isSaving,
}: FoodAnalysisResultProps) {
  return (
    <Card className="p-5 shadow-medium animate-scale-in overflow-hidden">
      {/* Header with total calories */}
      <div className="flex items-center justify-between mb-5">
        <div>
          <h3 className="font-display font-bold text-xl text-foreground">
            Analysis Complete
          </h3>
          <p className="text-muted-foreground text-sm">

```

```
Found {analysis.food_items.length} item{analysis.food_items.length !== 1 ? 's' : ''} •
{Math.round(analysis.confidence * 100)}% confident
```

```
</p>
```

```
</div>
```

```
<div className="flex items-center gap-2 px-4 py-2 rounded-full gradient-fresh">
```

```
<Flame className="h-5 w-5 text-primary-foreground" />
```

```
<span className="text-xl font-display font-bold text-primary-foreground">
```

```
{Math.round(analysis.total_calories)}
```

```
</span>
```

```
<span className="text-primary-foreground/80 text-sm">kcal</span>
```

```
</div>
```

```
</div>
```

```
{/* Freshness warning */}
```

```
{analysis.freshness_warning && (
```

```
<div className="mb-4 p-3 rounded-xl bg-destructive/10 border border-destructive/20
flex items-start gap-3">
```

```
<AlertTriangle className="h-5 w-5 text-destructive flex-shrink-0 mt-0.5" />
```

```
<p className="text-sm text-destructive">{analysis.freshness_warning}</p>
```

```
</div>
```

```
)}
```

```
{/* Food items */}
```

```
<div className="space-y-3 mb-5">
```

```
{analysis.food_items.map((food, index) => (
```

```
<FoodItemCard key={index} food={food} index={index} />
```

```
)))}
```

```
</div>
```

```
{/* Notes */}
```

```
{analysis.notes && (
```

```
  <p className="text-sm text-muted-foreground mb-5 italic">
```

```
     {analysis.notes}
```

```
  </p>
```

```
)}
```

```
{/* Action buttons */}
```

```
<div className="flex gap-3">
```

```
  <Button
```

```
    onClick={onDiscard}
```

```
    variant="outline"
```

```
    className="flex-1 h-12 rounded-xl font-display font-semibold"
```

```
  >
```

```
    <X className="h-4 w-4 mr-2" />
```

```
    Discard
```

```
  </Button>
```

```
  <Button
```

```
    onClick={onSave}
```

```
    disabled={isSaving}
```

```
    className="flex-1 h-12 rounded-xl font-display font-semibold gradient-fresh"
```

```
  >
```

```
    {isSaving ? (
```



```

        <div className="h-5 w-5 border-2 border-primary-foreground border-t-transparent
rounded-full animate-spin" />

        ) : (

            <>

                <Save className="h-4 w-4 mr-2" />

                Log Meal

            </>

        )}

    </Button>

</div>

</Card>

);

}

import { useAuth } from '@contexts/AuthContext';

import { Button } from '@components/ui/button';

import { Avatar, AvatarFallback, AvatarImage } from '@components/ui/avatar';

import {

    DropdownMenu,

    DropdownMenuContent,

    DropdownMenuItem,

    DropdownMenuTrigger,

} from '@components/ui/dropdown-menu';

import { LogOut, Leaf } from 'lucide-react';

export function Header() {

    const { user, signOut } = useAuth();

```

```
const initials = user?.email?.charAt(0).toUpperCase() || 'U';
```

```
const avatarUrl = user?.user_metadata?.avatar_url;
```

```
return (
```

```
  <header className="sticky top-0 z-50 bg-background/80 backdrop-blur-lg border-b  
border-border/50">
```

```
    <div className="container flex items-center justify-between h-16 px-4">
```

```
      <div className="flex items-center gap-2">
```

```
        <div className="h-10 w-10 rounded-xl gradient-fresh flex items-center justify-center  
shadow-glow">
```

```
          <Leaf className="h-5 w-5 text-primary-foreground" />
```

```
        </div>
```

```
      <div>
```

```
        <h1 className="font-display font-bold text-xl text-foreground">CalorieCam</h1>
```

```
      </div>
```

```
    </div>
```

```
  <DropdownMenu>
```

```
    <DropdownMenuTrigger asChild>
```

```
      <Button variant="ghost" size="icon" className="rounded-full h-10 w-10">
```

```
        <Avatar className="h-10 w-10 border-2 border-primary/20">
```

```
          <AvatarImage src={avatarUrl} />
```

```
          <AvatarFallback className="bg-secondary font-display font-bold">
```

```
            {initials}
```

```
          </AvatarFallback>
```

```
        </Avatar>
```

```

    </Button>

  </DropdownMenuTrigger>

  <DropdownMenuContent align="end" className="w-48">

    <DropdownMenuItem className="text-muted-foreground">

      {user?.email}

    </DropdownMenuItem>

    <DropdownMenuItem

      onClick={() => signOut()}

      className="text-destructive focus:text-destructive"

    >

      <Logout className="h-4 w-4 mr-2" />

      Sign Out

    </DropdownMenuItem>

  </DropdownMenuContent>

</DropdownMenu>

</div>

</header>

);

}

import { useRef, useState, useCallback } from 'react';

import { Camera, Upload, X, RotateCcw } from 'lucide-react';

import { Button } from '@components/ui/button';

import { cn } from '@lib/Utils';

interface ImageCaptureProps {

  onImageCapture: (imageBase64: string) => void;

```

```

    isAnalyzing: boolean;
  }

export function ImageCapture({ onImageCapture, isAnalyzing }: ImageCaptureProps) {
  const [preview, setPreview] = useState<string | null>(null);
  const [showCamera, setShowCamera] = useState(false);
  const [stream, setStream] = useState<MediaStream | null>(null);
  const videoRef = useRef<HTMLVideoElement>(null);
  const fileInputRef = useRef<HTMLInputElement>(null);
  const canvasRef = useRef<HTMLCanvasElement>(null);

  const startCamera = async () => {
    try {
      const mediaStream = await navigator.mediaDevices.getUserMedia({
        video: { facingMode: 'environment' },
      });
      setStream(mediaStream);
      setShowCamera(true);
      if (videoRef.current) {
        videoRef.current.srcObject = mediaStream;
      }
    } catch (error) {
      console.error('Error accessing camera:', error);
    }
  };

```

```
const stopCamera = useCallback(() => {  
  if (stream) {  
    stream.getTracks().forEach((track) => track.stop());  
    setStream(null);  
  }  
  setShowCamera(false);  
}, [stream]);
```

```
const capturePhoto = () => {  
  if (videoRef.current && canvasRef.current) {  
    const video = videoRef.current;  
    const canvas = canvasRef.current;  
    canvas.width = video.videoWidth;  
    canvas.height = video.videoHeight;  
    const ctx = canvas.getContext('2d');  
    if (ctx) {  
      ctx.drawImage(video, 0, 0);  
      const imageData = canvas.toDataURL('image/jpeg', 0.8);  
      setPreview(imageData);  
      stopCamera();  
    }  
  }  
};
```

```
const handleFileUpload = (e: React.ChangeEvent<HTMLInputElement>) => {  
  const file = e.target.files?.[0];
```

```
if (file) {

  const reader = new FileReader();

  reader.onload = (event) => {

    const result = event.target?.result as string;

    setPreview(result);

  };

  reader.readAsDataURL(file);

}

};

const handleAnalyze = () => {

  if (preview) {

    onImageCapture(preview);

  }

};

const clearPreview = () => {

  setPreview(null);

  if (fileInputRef.current) {

    fileInputRef.current.value = "";

  }

};

return (

  <div className="w-full space-y-4">

    <canvas ref={canvasRef} className="hidden" />
```

```
<input
  ref={fileInputRef}
  type="file"
  accept="image/*"
  onChange={handleFileUpload}
  className="hidden"
/>
```

```
{showCamera ? (
  <div className="relative rounded-2xl overflow-hidden shadow-medium animate-scale-in">
    <video
      ref={videoRef}
      autoPlay
      playsInline
      className="w-full aspect-[4/3] object-cover"
    />
    <div className="absolute bottom-4 left-0 right-0 flex justify-center gap-4">
      <Button
        onClick={stopCamera}
        variant="outline"
        size="icon"
        className="rounded-full h-12 w-12 bg-card/80 backdrop-blur-sm border-0"
      >
        <X className="h-5 w-5" />
      </Button>
```

```
<Button
  onClick={capturePhoto}
  size="icon"
  className="rounded-full h-16 w-16 gradient-fresh shadow-glow"
>

  <div className="h-12 w-12 rounded-full border-4 border-primary-foreground" />

</Button>

</div>

</div>

): preview ? (

  <div className="relative rounded-2xl overflow-hidden shadow-medium animate-scale-in">

    <img
      src={preview}
      alt="Food preview"
      className="w-full aspect-[4/3] object-cover"
    />

    <div className="absolute top-3 right-3 flex gap-2">

      <Button
        onClick={clearPreview}
        variant="outline"
        size="icon"
        className="rounded-full h-10 w-10 bg-card/80 backdrop-blur-sm border-0"
      >

        <RotateCcw className="h-4 w-4" />

      </Button>
```



```
</div>
```

```
<div className="absolute bottom-4 left-4 right-4">
```

```
<Button
```

```
  onClick={handleAnalyze}
```

```
  disabled={isAnalyzing}
```

```
  className="w-full h-14 rounded-xl text-lg font-display font-semibold gradient-fresh shadow-glow"
```

```
>
```

```
  {isAnalyzing ? (
```

```
    <span className="flex items-center gap-2">
```

```
      <div className="h-5 w-5 border-2 border-primary-foreground border-t-transparent rounded-full animate-spin" />
```

```
      Analyzing...
```

```
    </span>
```

```
  ) : (
```

```
    'Analyze Food'
```

```
  )}
```

```
</Button>
```

```
</div>
```

```
</div>
```

```
): (
```

```
<div className="space-y-3">
```

```
<div
```

```
  className={cn(
```

```
    'border-2 border-dashed rounded-2xl p-8 transition-all duration-300',
```

```
    'border-primary/30 bg-secondary/30 hover:border-primary/50 hover:bg-secondary/50'
```

```
}}
```

```
>
```

```
<div className="flex flex-col items-center text-center space-y-4">
```

```
  <div className="h-20 w-20 rounded-full gradient-fresh flex items-center justify-  
center shadow-glow animate-float">
```

```
    <Camera className="h-10 w-10 text-primary-foreground" />
```

```
  </div>
```

```
<div>
```

```
  <h3 className="font-display font-bold text-xl text-foreground">
```

```
    Capture Your Meal
```

```
  </h3>
```

```
  <p className="text-muted-foreground mt-1">
```

```
    Take a photo or upload an image
```

```
  </p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
<div className="grid grid-cols-2 gap-3">
```

```
  <Button
```

```
    onClick={startCamera}
```

```
    variant="outline"
```

```
    className="h-14 rounded-xl font-display font-semibold border-2 border-primary/20  
hover:border-primary/40 hover:bg-secondary"
```

```
  >
```

```
    <Camera className="h-5 w-5 mr-2" />
```

```
    Camera
```

```

    </Button>

    <Button
      onClick={() => fileInputRef.current?.click()}
      variant="outline"
      className="h-14 rounded-xl font-display font-semibold border-2 border-primary/20
        hover:border-primary/40 hover:bg-secondary"
    >

      <Upload className="h-5 w-5 mr-2" />

      Upload
    </Button>
  </div>
</div>

  )}

</div>

);

}

import React from 'react';

import { ScanEye } from 'lucide-react';

import { cn } from '@lib/utls';

interface LogoProps {
  size?: 'sm' | 'md' | 'lg' | 'xl';
  showText?: boolean;
  className?: string;
}

```

```
const sizeClasses = {  
  
  sm: 'w-8 h-8',  
  
  md: 'w-12 h-12',  
  
  lg: 'w-20 h-20',  
  
  xl: 'w-32 h-32',  
  
};
```

```
const iconSizes = {  
  
  sm: 16,  
  
  md: 24,  
  
  lg: 40,  
  
  xl: 64,  
  
};
```

```
const textSizes = {  
  
  sm: 'text-lg',  
  
  md: 'text-2xl',  
  
  lg: 'text-4xl',  
  
  xl: 'text-5xl',  
  
};
```

```
export const Logo: React.FC<LogoProps> = ({  
  
  size = 'md',  
  
  showText = false,  
  
  className  
  
}) => {
```

```

return (

  <div className={cn('flex items-center gap-2', className)}>

    <div className={cn(

      'gradient-brand rounded-2xl flex items-center justify-center shadow-brand',

      sizeClasses[size]

    )}>

      <ScanEye size={iconSizes[size]} className="text-primary-foreground" />

    </div>

    {showText && (

      <span className={cn(

        'font-display font-bold text-foreground',

        textSizes[size]

      )}>

        Lookai

      </span>

    )}

  </div>

);

};

export default Logo;

import { FoodLog } from '@types/food';

import { Card } from '@components/ui/card';

import { Button } from '@components/ui/button';

import { Trash2, Clock, Flame } from 'lucide-react';

import { format } from 'date-fns';

```

```
import { cn } from '@lib/utls';
```

```
interface MealHistoryProps {
```

```
  logs: FoodLog[];
```

```
  onDelete: (id: string) => void;
```

```
  isDeleting: boolean;
```

```
}
```

```
function MealCard({ log, onDelete, isDeleting }: { log: FoodLog; onDelete: () => void; isDeleting: boolean }) {
```

```
  const freshnessColors = {
```

```
    fresh: 'bg-success/10 text-success',
```

```
    acceptable: 'bg-warning/10 text-warning',
```

```
    spoiled: 'bg-destructive/10 text-destructive',
```

```
  };
```

```
  return (
```

```
    <Card className="p-4 shadow-soft hover:shadow-medium transition-shadow duration-300 animate-scale-in">
```

```
      <div className="flex gap-4">
```

```
        {log.image_url && (
```

```
          <img
```

```
            src={log.image_url}
```

```
            alt={log.food_name}
```

```
            className="w-20 h-20 rounded-xl object-cover flex-shrink-0"
```

```
          />
```

```
        )}
```

```
<div className="flex-1 min-w-0">
```

```
<div className="flex justify-between items-start">
```

```
<div>
```

```
<h4 className="font-display font-bold text-foreground truncate capitalize">
```

```
{log.food_name}
```

```
</h4>
```

```
<div className="flex items-center gap-2 text-sm text-muted-foreground mt-1">
```

```
<Clock className="h-3.5 w-3.5" />
```

```
{format(new Date(log.logged_at), 'MMM d, h:mm a')}
```

```
</div>
```

```
</div>
```

```
<Button
```

```
onClick={onDelete}
```

```
disabled={isDeleting}
```

```
variant="ghost"
```

```
size="icon"
```

```
className="h-8 w-8 text-muted-foreground hover:text-destructive"
```

```
>
```

```
<Trash2 className="h-4 w-4" />
```

```
</Button>
```

```
</div>
```

```
<div className="flex items-center gap-3 mt-3">
```

```
<div className="flex items-center gap-1.5 px-2.5 py-1 rounded-full bg-primary/10">
```

```
<Flame className="h-4 w-4 text-primary" />
```

```
<span className="text-sm font-semibold text-primary">
```

```
    {Math.round(log.calories)} kcal
```

```
</span>
```

```
</div>
```

```
{log.freshness_status && (
```

```
  <span className={cn(
```

```
    'px-2.5 py-1 rounded-full text-xs font-medium capitalize',
```

```
    freshnessColors[log.freshness_status]
```

```
  )}>
```

```
    {log.freshness_status}
```

```
</span>
```

```
)}
```

```
{log.confidence_score && (
```

```
  <span className="text-xs text-muted-foreground">
```

```
    {Math.round(log.confidence_score * 100)}% conf.
```

```
</span>
```

```
)}
```

```
</div>
```

```
{/* Macros */}
```

```
<div className="flex gap-4 mt-2 text-xs text-muted-foreground">
```

```
{log.protein_grams && (
```

```
  <span>P: {Math.round(log.protein_grams)}g</span>
```

```
)}
```

```
{log.carbs_grams && (
```



```

    <span>C: {Math.round(log.carbs_grams)}g</span>

  )}

  {log.fat_grams && (

    <span>F: {Math.round(log.fat_grams)}g</span>

  )}

</div>

</div>

</div>

</Card>

);

}

export function MealHistory({ logs, onDelete, isDeleting }: MealHistoryProps) {

  if (logs.length === 0) {

    return (

      <div className="text-center py-12">

        <div className="h-16 w-16 mx-auto rounded-full bg-secondary flex items-center justify-center mb-4">

          <Clock className="h-8 w-8 text-muted-foreground" />

        </div>

        <h3 className="font-display font-semibold text-foreground mb-1">

          No meals logged yet

        </h3>

        <p className="text-sm text-muted-foreground">

          Take a photo of your food to get started

        </p>

```

```
</div>
```

```
);
```

```
}
```

```
return (
```

```
<div className="space-y-3">
```

```
{logs.map((log) => (
```

```
<MealCard
```

```
key={log.id}
```

```
log={log}
```

```
onDelete={() => onDelete(log.id)}
```

```
isDeleting={isDeleting}
```

```
/>
```

```
))}
```

```
</div>
```

```
);
```

```
}
```

```
import React from 'react';
```

```
import { Dialog, DialogContent } from '@components/ui/dialog';
```

```
import { Button } from '@components/ui/button';
```

```
import { Crown, Check, X, Sparkles, BarChart3, Target, Infinity } from 'lucide-react';
```

```
import { cn } from '@lib/utils';
```

```
interface PremiumPaywallProps {
```

```
  isOpen: boolean;
```

```
  onClose: () => void;
```

```
onUpgrade: () => void;

isUpgrading?: boolean;

trigger?: 'scan_limit' | 'insights' | 'calorie_goal' | 'general';

}
```

```
const features = [

  { icon: Infinity, label: 'Unlimited scans', description: 'No daily limits' },

  { icon: BarChart3, label: 'Weekly insights', description: 'Charts & trends' },

  { icon: Target, label: 'Custom calorie goal', description: 'Set your own target' },

  { icon: Sparkles, label: 'Priority AI analysis', description: 'Faster & more accurate' },

];
```

```
const triggerMessages: Record<string, { title: string; subtitle: string }> = {

  scan_limit: {

    title: "You've hit your daily limit",

    subtitle: "Upgrade to keep scanning"

  },

  insights: {

    title: "Unlock Weekly Insights",

    subtitle: "See your progress over time"

  },

  calorie_goal: {

    title: "Set Custom Goals",

    subtitle: "Personalize your calorie target"

  },

  general: {
```

```

    title: "Get More with Premium",

    subtitle: "Unlock all features"

  },

};

export const PremiumPaywall: React.FC<PremiumPaywallProps> = ({

  isOpen,

  onClose,

  onUpgrade,

  isUpgrading = false,

  trigger = 'general',

}) => {

  const message = triggerMessages[trigger];

  return (

    <Dialog open={isOpen} onOpenChange={onClose}>

      <DialogContent className="max-w-sm mx-auto p-0 gap-0 bg-background border-border overflow-hidden">

        {/* Header with gradient */}

        <div className="gradient-brand p-6 text-center relative">

          <button

            onClick={onClose}

            className="absolute top-4 right-4 p-1.5 rounded-full bg-primary-foreground/20 hover:bg-primary-foreground/30 transition-colors"

          >

            <X className="h-4 w-4 text-primary-foreground" />

          </button>

```

```
<div className="w-16 h-16 mx-auto rounded-2xl bg-primary-foreground/20 flex items-center justify-center mb-4">
```

```
  <Crown className="h-8 w-8 text-primary-foreground" fill="currentColor" />
```

```
</div>
```

```
<h2 className="font-display font-bold text-xl text-primary-foreground mb-1">
```

```
  {message.title}
```

```
</h2>
```

```
<p className="text-sm text-primary-foreground/80">{message.subtitle}</p>
```

```
</div>
```

```
<div className="p-6 space-y-6">
```

```
  {/* Price */}
```

```
  <div className="text-center">
```

```
    <div className="flex items-baseline justify-center gap-1">
```

```
      <span className="text-4xl font-display font-bold text-foreground">₹49</span>
```

```
      <span className="text-muted-foreground">/month</span>
```

```
    </div>
```

```
    <p className="text-xs text-muted-foreground mt-1">Cancel anytime</p>
```

```
  </div>
```

```
  {/* Features */}
```

```
  <div className="space-y-3">
```

```
    {features.map((feature) => {
```

```
      const Icon = feature.icon;
```

```

return (

  <div key={feature.label} className="flex items-center gap-3">

    <div className="w-10 h-10 rounded-xl bg-primary/10 flex items-center justify-
center flex-shrink-0">

      <Icon className="h-5 w-5 text-primary" />

    </div>

    <div>

      <p className="font-medium text-foreground text-sm">{feature.label}</p>

      <p className="text-xs text-muted-foreground">{feature.description}</p>

    </div>

    <Check className="h-4 w-4 text-primary ml-auto" />

  </div>

);

)}}

</div>

{/* CTA Buttons */}

<div className="space-y-3">

  <Button

    onClick={onUpgrade}

    disabled={isUpgrading}

    className="w-full h-14 text-base font-bold gradient-brand text-primary-foreground
rounded-2xl shadow-brand hover:opacity-95 transition-opacity"

    >

    {isUpgrading ? 'Processing...' : 'Upgrade Now — ₹49/mo'}

  </Button>

```

```

    <Button
      onClick={onClose}
      variant="ghost"
      className="w-full text-muted-foreground hover:text-foreground"
    >
      Continue Free
    </Button>
  </div>

  <p className="text-xs text-center text-muted-foreground">
    Free plan includes 5 scans/day and basic tracking
  </p>
</div>
</DialogContent>
</Dialog>

);

};

```

```
export default PremiumPaywall;
```

contexts

```

import { createContext, useContext, useEffect, useState, ReactNode } from 'react';

import { User, Session } from '@supabase/supabase-js';

import { supabase } from '@integrations/supabase/client';

interface AuthContextType {

```

```
user: User | null;

session: Session | null;

loading: boolean;

signInWithGoogle: () => Promise<{ error: Error | null }>;

signInWithEmail: (email: string, password: string) => Promise<{ error: Error | null }>;

signUpWithEmail: (email: string, password: string) => Promise<{ error: Error | null }>;

signOut: () => Promise<void>;

}
```

```
const AuthContext = createContext<AuthContextType | undefined>(undefined);
```

```
export function AuthProvider({ children }: { children: ReactNode }) {
```

```
  const [user, setUser] = useState<User | null>(null);
```

```
  const [session, setSession] = useState<Session | null>(null);
```

```
  const [loading, setLoading] = useState(true);
```

```
  useEffect(() => {
```

```
    // Set up auth state listener FIRST
```

```
    const { data: { subscription } } = supabase.auth.onAuthStateChange(
```

```
      (event, session) => {
```

```
        setSession(session);
```

```
        setUser(session?.user ?? null);
```

```
        setLoading(false);
```

```
      }
```

```
    );
```



```
// THEN check for existing session
```

```
supabase.auth.getSession().then(({ data: { session } }) => {
```

```
  setSession(session);
```

```
  setUser(session?.user ?? null);
```

```
  setLoading(false);
```

```
});
```

```
return () => subscription.unsubscribe();
```

```
}, []);
```

```
const signInWithGoogle = async () => {
```

```
  const { error } = await supabase.auth.signInWithOAuth({
```

```
    provider: 'google',
```

```
    options: {
```

```
      redirectTo: `${window.location.origin}/`,
```

```
    },
```

```
  });
```

```
  return { error };
```

```
};
```

```
const signInWithEmail = async (email: string, password: string) => {
```

```
  const { error } = await supabase.auth.signInWithPassword({
```

```
    email,
```

```
    password,
```

```
  });
```

```
  return { error };
```

```
};
```

```
const signUpWithEmail = async (email: string, password: string) => {
```

```
  const { error } = await supabase.auth.signUp({
```

```
    email,
```

```
    password,
```

```
    options: {
```

```
      emailRedirectTo: `${window.location.origin}/`,
```

```
    },
```

```
  });
```

```
  return { error };
```

```
};
```

```
const signOut = async () => {
```

```
  await supabase.auth.signOut();
```

```
};
```

```
return (
```

```
  <AuthContext.Provider
```

```
    value={{
```

```
      user,
```

```
      session,
```

```
      loading,
```

```
      signInWithGoogle,
```

```
      signInWithEmail,
```

```
      signUpWithEmail,
```

```
    signOut,  
  }  
  >  
  {children}  
  </AuthContext.Provider>  
);  
}
```

```
export function useAuth() {  
  const context = useContext(AuthContext);  
  if (context === undefined) {  
    throw new Error('useAuth must be used within an AuthProvider');  
  }  
  return context;  
}
```

```
export const RAW_FOOD_DATA = `  
name,region,category,kcal_per_gram  
Rice (white cooked),india,staple,1.30  
Brown rice (cooked),india,staple,1.23  
Wheat flour (atta),india,grain,3.40  
Chapati (roti),india,bread,2.60  
Paratha (plain),india,bread,3.00  
Naan,india,bread,3.10  
Poha,india,breakfast,1.80  
Upma,india,breakfast,1.90  
Idli,india,breakfast,1.50`
```

Dosa (plain),india,breakfast,2.00

Dal (boiled),india,pulse,1.20

Moong dal,india,pulse,3.50

Toor dal,india,pulse,3.40

Chana dal,india,pulse,3.60

Rajma,india,pulse,3.30

Chickpeas (boiled),india,pulse,1.60

Black chana,india,pulse,3.60

Sambar,india,curry,0.90

Rasam,india,curry,0.40

Kadhi,india,curry,1.10

Potato (boiled),india,vegetable,0.87

Onion,india,vegetable,0.40

Tomato,india,vegetable,0.18

Carrot,india,vegetable,0.41

Cabbage,india,vegetable,0.25

Cauliflower,india,vegetable,0.25

Spinach,india,vegetable,0.23

Brinjal,india,vegetable,0.25

Lady finger (okra),india,vegetable,0.33

Green peas,india,vegetable,0.81

Apple,india,fruit,0.52

Banana,india,fruit,0.89

Mango,india,fruit,0.60

Orange,india,fruit,0.47

Papaya,india,fruit,0.43

Watermelon,india,fruit,0.30

Pineapple,india,fruit,0.50

Guava,india,fruit,0.68

Grapes,india,fruit,0.69

Pomegranate,india,fruit,0.83

Milk (full cream),india,dairy,0.64

Milk (toned),india,dairy,0.58

Curd (dahi),india,dairy,0.60

Paneer,india,dairy,2.65

Cheese,india,dairy,4.00

Butter,india,fat,7.20

Ghee,india,fat,9.00

Lassi (sweet),india,drink,0.90

Buttermilk,india,drink,0.40

Cream,india,dairy,3.40

Samosa,india,snack,3.20

Pakora,india,snack,3.10

Vada,india,snack,2.90

Pav bhaji,india,meal,2.10

Pani puri,india,snack,2.80

Bhel puri,india,snack,1.90

Sev,india,snack,5.50

Namkeen mixture,india,snack,5.00

Aloo chaat,india,snack,1.70

Kachori,india,snack,3.50

Gulab jamun,india,dessert,3.30

Rasgulla,india,dessert,1.90

Jalebi,india,dessert,4.50

Laddu (boondi),india,dessert,4.00

Barfi,india,dessert,4.20

Halwa (suji),india,dessert,3.60

Kheer,india,dessert,1.40

Payasam,india,dessert,1.50

Mysore pak,india,dessert,5.00

Ice cream,india,dessert,2.10

Egg (boiled),india,protein,1.55

Omelette,india,protein,1.90

Chicken curry,india,protein,2.40

Chicken breast (grilled),india,protein,1.65

Mutton curry,india,protein,3.00

Fish curry,india,protein,1.80

Fish fry,india,protein,2.80

Prawns,india,protein,1.00

Keema,india,protein,2.90

Tandoori chicken,india,protein,1.95

Cooking oil,india,fat,9.00

Groundnut,india,nuts,5.70

Almond,india,nuts,5.80

Cashew,india,nuts,5.50

Sugar,india,sweetener,4.00

Jaggery,india,sweetener,3.80

Veg biryani,india,meal,1.90

Chicken biryani,india,meal,2.20

Curd rice,india,meal,1.40

Khichdi,india,meal,1.30

Fried rice,india,meal,2.30

Masala dosa,india,meal,2.30

Chole bhature,india,meal,3.00

Thali (average),india,meal,2.10

White bread,usa,bread,2.65

Whole wheat bread,usa,bread,2.50

Bagel,usa,bread,2.75

Croissant,usa,bakery,4.10

Pancake,usa,breakfast,2.30

Waffle,usa,breakfast,2.90

Breakfast cereal (cornflakes),usa,breakfast,3.80

Oatmeal (cooked),usa,breakfast,0.70

Granola,usa,breakfast,4.70

Muffin,usa,bakery,3.50

Hamburger,usa,fastfood,2.60

Cheeseburger,usa,fastfood,2.90

Hot dog,usa,fastfood,2.90

French fries,usa,fastfood,3.10

Pizza (cheese),usa,fastfood,2.65

Pepperoni pizza,usa,fastfood,3.00

Fried chicken,usa,fastfood,2.90

Chicken nuggets,usa,fastfood,2.95

Onion rings,usa,fastfood,4.10

Tacos,usa,fastfood,2.40

Beef steak (grilled),usa,protein,2.50

Beef burger patty,usa,protein,2.80

Chicken breast (grilled),usa,protein,1.65

Chicken wings,usa,protein,2.90

Bacon,usa,protein,5.40

Sausage,usa,protein,3.20

Turkey (roasted),usa,protein,1.60

Ham,usa,protein,1.45

Meatballs,usa,protein,2.70

Pork chop,usa,protein,2.40

Salmon,usa,seafood,2.08

Tuna,usa,seafood,1.30

Shrimp,usa,seafood,1.00

Crab,usa,seafood,0.97

Fish sticks,usa,seafood,2.30

Lobster,usa,seafood,0.89

Fried fish,usa,seafood,2.50

Fish sandwich,usa,seafood,2.40

Sushi (average),usa,seafood,1.50

Clam chowder,usa,soup,0.95

Milk (whole),usa,dairy,0.64

Milk (skim),usa,dairy,0.34

Cheese (cheddar),usa,dairy,4.00

Mozzarella,usa,dairy,2.80

Butter,usa,fat,7.20

Cream cheese,usa,dairy,3.40

Yogurt (plain),usa,dairy,0.60

Ice cream,usa,dessert,2.10

Egg (boiled),usa,protein,1.55

Scrambled eggs,usa,protein,1.90

Potato (baked),usa,vegetable,0.93

Mashed potatoes,usa,vegetable,1.10

Sweet potato,usa,vegetable,0.86

Corn,usa,vegetable,0.96

Broccoli,usa,vegetable,0.34

Carrot,usa,vegetable,0.41

Lettuce,usa,vegetable,0.15

Tomato,usa,vegetable,0.18

Onion,usa,vegetable,0.40

Bell pepper,usa,vegetable,0.31

Apple,usa,fruit,0.52

Banana,usa,fruit,0.89

Orange,usa,fruit,0.47

Strawberry,usa,fruit,0.32

Blueberry,usa,fruit,0.57

Grapes,usa,fruit,0.69

Pineapple,usa,fruit,0.50

Watermelon,usa,fruit,0.30

Peach,usa,fruit,0.39

Avocado,usa,fruit,1.60

Chocolate bar,usa,dessert,5.30

Donut,usa,dessert,4.50

Cookie,usa,dessert,4.80

Brownie,usa,dessert,4.60

Cake (plain),usa,dessert,3.80

Cheesecake,usa,dessert,3.20

Apple pie,usa,dessert,2.60

Cupcake,usa,dessert,3.90

Marshmallow,usa,dessert,3.20

Pancake syrup,usa,sweetener,2.60

Soda,usa,drink,0.40

Orange juice,usa,drink,0.45

Milkshake,usa,drink,1.20

Coffee (black),usa,drink,0.02

Beer,usa,drink,0.43

Ketchup,usa,sauce,1.00

Mayonnaise,usa,sauce,6.80

Peanut butter,usa,spread,5.90

Jam,usa,spread,2.80

Honey,usa,sweetener,3.00

Mac and cheese,usa,meal,2.40

Spaghetti (with sauce),usa,meal,1.60

Lasagna,usa,meal,2.20

Grilled cheese sandwich,usa,meal,3.00

Chicken sandwich,usa,meal,2.40

Burrito,usa,meal,2.10

Nachos,usa,meal,3.40

Caesar salad,usa,meal,1.70

Steak dinner,usa,meal,2.50

American breakfast (average),usa,meal,2.60

Rice (white cooked),nepal,staple,1.30

Brown rice (cooked),nepal,staple,1.23

Beaten rice (chiura),nepal,grain,3.60

Wheat flour,nepal,grain,3.40

Roti,nepal,bread,2.60

Dhido (millet/maize),nepal,staple,1.10

Corn (boiled),nepal,staple,0.96

Sel roti,nepal,snack,3.80

Puffed rice (murra),nepal,grain,3.80

Bara (lentil pancake),nepal,snack,2.40

Dal (boiled),nepal,pulse,1.20

Masoor dal,nepal,pulse,3.50

Moong dal,nepal,pulse,3.50

Toor dal,nepal,pulse,3.40

Black lentils,nepal,pulse,3.40

Chana (boiled),nepal,pulse,1.60

Black chana,nepal,pulse,3.60

Kwati,nepal,pulse,1.40

Gahat dal (horse gram),nepal,pulse,3.20

Soybeans (boiled),nepal,pulse,1.70

Potato (boiled),nepal,vegetable,0.87

Spinach (saag),nepal,vegetable,0.23

Mustard greens,nepal,vegetable,0.27

Cauliflower,nepal,vegetable,0.25

Cabbage,nepal,vegetable,0.25

Pumpkin,nepal,vegetable,0.26

Bitter gourd,nepal,vegetable,0.17

Bottle gourd,nepal,vegetable,0.14

Radish,nepal,vegetable,0.16

Tomato,nepal,vegetable,0.18

Chicken curry,nepal,protein,2.40

Chicken (boiled),nepal,protein,1.65

Mutton curry,nepal,protein,3.00

Buffalo meat (fresh),nepal,protein,2.70

Sukuti (dried meat),nepal,protein,4.30

Pork curry,nepal,protein,3.50

Egg (boiled),nepal,protein,1.55

Omelette,nepal,protein,1.90

Fish curry,nepal,protein,1.80

Fried fish,nepal,protein,2.80

Milk (full cream),nepal,dairy,0.64

Curd (dahi),nepal,dairy,0.60

Ghee (gheu),nepal,fat,9.00

Butter,nepal,fat,7.20

Paneer,nepal,dairy,2.65

Cheese,nepal,dairy,4.00

Lassi,nepal,drink,0.90

Buttermilk,nepal,drink,0.40

Cream,nepal,dairy,3.40

Milk tea,nepal,drink,0.50

Momo (steamed),nepal,snack,1.80

Momo (fried),nepal,snack,2.60

Chowmein,nepal,meal,2.20

Thukpa,nepal,meal,1.10

Samosa,nepal,snack,3.20

Pakoda,nepal,snack,3.10

Aloo chop,nepal,snack,2.80

Chatamari,nepal,meal,2.00

Laphing,nepal,snack,1.50

Sekuwa,nepal,protein,2.70

Apple,nepal,fruit,0.52

Banana,nepal,fruit,0.89

Mango,nepal,fruit,0.60

Orange,nepal,fruit,0.47

Papaya,nepal,fruit,0.43

Guava,nepal,fruit,0.68

Pineapple,nepal,fruit,0.50

Watermelon,nepal,fruit,0.30

Pomegranate,nepal,fruit,0.83

Litchi,nepal,fruit,0.66

Achar (mixed),nepal,condiment,1.50

Tomato achar,nepal,condiment,0.90

Gundruk,nepal,vegetable,0.40

Sinkhi,nepal,vegetable,0.35

Tama (bamboo shoot),nepal,vegetable,0.27

Soy sauce,nepal,sauce,0.53

Chili paste,nepal,sauce,0.80

Sesame seeds,nepal,nuts,5.70

Peanuts,nepal,nuts,5.70

Cashew nuts,nepal,nuts,5.50

Kheer,nepal,dessert,1.40

Rice pudding,nepal,dessert,1.50

Sel roti (sweet),nepal,dessert,3.80

Laddu,nepal,dessert,4.00

Jalebi,nepal,dessert,4.50

Barfi,nepal,dessert,4.20

Halwa,nepal,dessert,3.60

Yogurt with sugar,nepal,dessert,0.80

Honey,nepal,sweetener,3.00

Jaggery (chaku),nepal,sweetener,3.80

Dal Bhat (average),nepal,meal,1.90

Dal Bhat Tarkari,nepal,meal,1.85

Veg thali,nepal,meal,1.70

Non-veg thali,nepal,meal,2.30

Khaja set,nepal,meal,2.20

Momo set,nepal,meal,2.00

Newari bhoj,nepal,meal,2.50

Rice + curry combo,nepal,meal,1.95

Festival feast (average),nepal,meal,2.60

Nepali home meal (average),nepal,meal,1.90

White rice (cooked),world,staple,1.30

Brown rice (cooked),world,staple,1.23

Wheat bread,world,bread,2.50

Pasta (cooked),world,grain,1.60

Noodles (cooked),world,grain,1.45

Couscous,world,grain,1.12

Quinoa (cooked),world,grain,1.20

Cornbread,world,bread,3.30

Tortilla (wheat),world,bread,2.80

Bagel,world,bread,2.75

Potato (boiled),world,vegetable,0.87

Sweet potato,world,vegetable,0.86

Tomato,world,vegetable,0.18

Carrot,world,vegetable,0.41

Broccoli,world,vegetable,0.34

Spinach,world,vegetable,0.23

Onion,world,vegetable,0.40

Bell pepper,world,vegetable,0.31

Zucchini,world,vegetable,0.17

Eggplant,world,vegetable,0.25

Apple,world,fruit,0.52

Banana,world,fruit,0.89

Mango,world,fruit,0.60

Orange,world,fruit,0.47

Grapes,world,fruit,0.69

Pineapple,world,fruit,0.50

Papaya,world,fruit,0.43

Watermelon,world,fruit,0.30

Strawberry,world,fruit,0.32

Avocado,world,fruit,1.60

Milk (whole),world,dairy,0.64

Skim milk,world,dairy,0.34

Yogurt (plain),world,dairy,0.60

Cheese (average),world,dairy,4.00

Butter,world,fat,7.20

Cream,world,dairy,3.40

Ice cream,world,dessert,2.10

Paneer,world,dairy,2.65

Egg (boiled),world,protein,1.55

Scrambled eggs,world,protein,1.90

Chicken breast (grilled),world,protein,1.65

Fried chicken,world,protein,2.90

Beef steak,world,protein,2.50

Pork chop,world,protein,2.40

Lamb curry,world,protein,3.00

Turkey,world,protein,1.60

Sausage,world,protein,3.20

Bacon,world,protein,5.40

Meatballs,world,protein,2.70

Tofu,world,protein,0.76

Salmon,world,seafood,2.08

Tuna,world,seafood,1.30

Shrimp,world,seafood,1.00

Crab,world,seafood,0.97

Lobster,world,seafood,0.89

Fish curry,world,seafood,1.80

Fried fish,world,seafood,2.50

Sushi (average),world,seafood,1.50

Fish fingers,world,seafood,2.30

Anchovies,world,seafood,2.10

Hamburger,world,fastfood,2.60

Cheeseburger,world,fastfood,2.90

Pizza (cheese),world,fastfood,2.65

French fries,world,fastfood,3.10

Hot dog,world,fastfood,2.90

Tacos,world,fastfood,2.40

Nachos,world,fastfood,3.40

Spring rolls,world,snack,2.80

Samosa,world,snack,3.20

Falafel,world,snack,3.30

Chocolate,world,dessert,5.30

Donut,world,dessert,4.50

Cookie,world,dessert,4.80

Cake (plain),world,dessert,3.80

Brownie,world,dessert,4.60

Ice cream sundae,world,dessert,2.40

Cheesecake,world,dessert,3.20

Apple pie,world,dessert,2.60

Pancake with syrup,world,dessert,2.80

Waffle,world,dessert,2.90

Almonds,world,nuts,5.80

Cashews,world,nuts,5.50

Peanuts,world,nuts,5.70

Peanut butter,world,spread,5.90

Olive oil,world,fat,9.00

Butter oil (ghee),world,fat,9.00

Mayonnaise,world,sauce,6.80

Sugar,world,sweetener,4.00

Honey,world,sweetener,3.00

Jam,world,spread,2.80

Biryani,world,meal,2.20

Pasta with sauce,world,meal,1.80

Fried rice,world,meal,2.30

Lasagna,world,meal,2.20

Ramen,world,meal,1.60

Paella,world,meal,2.00

Burrito,world,meal,2.10

Shawarma,world,meal,2.40

Bibimbap,world,meal,1.70

Mixed world meal (average),world,meal,2.10

roti,india,bread,2.60

chapati,india,bread,2.60

dal,india,pulse,1.20

dal bhat,nepal,meal,1.90

momo,nepal,snack,1.80

chowmein,nepal,meal,2.20

sel roti,nepal,snack,3.80

idli,india,breakfast,1.50

dosa,india,breakfast,2.00

sambar,india,curry,0.90

vada,india,snack,2.90

poha,india,breakfast,1.80

upma,india,breakfast,1.90

paneer curry,india,curry,2.65

rajma,india,pulse,3.30

chole,india,pulse,3.60

sabzi,india,vegetable,0.87

biryani,world,meal,2.20

chicken curry,india,protein,2.40

egg curry,india,protein,1.55

curd,india,dairy,0.60

pickle,nepal,condiment,1.50

achar,nepal,condiment,1.50

gundruk,nepal,vegetable,0.40`;

```
export const getFoodDatabasePrompt = () => {
```

```
  const lines = RAW_FOOD_DATA.trim().split('\n');
```

```
  // Skip header row
```

```
  const dataLines = lines.slice(1);
```

```
  // Format: "Item Name (Region): X kcal/g"
```

```
return dataLines.map(line => {

  const parts = line.split(',');

  if (parts.length < 4) return '';

  const name = parts[0];

  const region = parts[1];

  // const category = parts[2]; // not needed for prompt

  const kcal = parts[3];

  return `-${name} (${region}): ${kcal} kcal/g`;

}).join('\n');

};

import * as React from "react";

const MOBILE_BREAKPOINT = 768;

export function useIsMobile() {

  const [isMobile, setIsMobile] = React.useState<boolean | undefined>(undefined);

  React.useEffect(() => {

    const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`);

    const onChange = () => {

      setIsMobile(window.innerWidth < MOBILE_BREAKPOINT);

    };

    mql.addEventListener("change", onChange);

    setIsMobile(window.innerWidth < MOBILE_BREAKPOINT);

    return () => mql.removeEventListener("change", onChange);

  }, []);
```

```
return !!isMobile;
```

```
}
```

```
import * as React from "react";
```

```
import type { ToastActionElement, ToastProps } from "@components/ui/toast";
```

```
const TOAST_LIMIT = 1;
```

```
const TOAST_REMOVE_DELAY = 1000000;
```

```
type ToasterToast = ToastProps & {
```

```
  id: string;
```

```
  title?: React.ReactNode;
```

```
  description?: React.ReactNode;
```

```
  action?: ToastActionElement;
```

```
};
```

```
const actionTypes = {
```

```
  ADD_TOAST: "ADD_TOAST",
```

```
  UPDATE_TOAST: "UPDATE_TOAST",
```

```
  DISMISS_TOAST: "DISMISS_TOAST",
```

```
  REMOVE_TOAST: "REMOVE_TOAST",
```

```
} as const;
```

```
let count = 0;
```

```
function genId() {  
    count = (count + 1) % Number.MAX_SAFE_INTEGER;  
    return count.toString();  
}
```

```
type ActionType = typeof actionTypes;
```

```
type Action =
```

```
  | {  
    type: ActionType["ADD_TOAST"];  
    toast: ToasterToast;  
  }  
  | {  
    type: ActionType["UPDATE_TOAST"];  
    toast: Partial<ToasterToast>;  
  }  
  | {  
    type: ActionType["DISMISS_TOAST"];  
    toastId?: ToasterToast["id"];  
  }  
  | {  
    type: ActionType["REMOVE_TOAST"];  
    toastId?: ToasterToast["id"];  
  };  
};
```

```
interface State {
```

```
  toasts: ToasterToast[];
```

```
}
```

```
const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>();
```

```
const addToRemoveQueue = (toastId: string) => {
```

```
  if (toastTimeouts.has(toastId)) {
```

```
    return;
```

```
  }
```

```
  const timeout = setTimeout(() => {
```

```
    toastTimeouts.delete(toastId);
```

```
    dispatch({
```

```
      type: "REMOVE_TOAST",
```

```
      toastId: toastId,
```

```
    });
```

```
  }, TOAST_REMOVE_DELAY);
```

```
  toastTimeouts.set(toastId, timeout);
```

```
};
```

```
export const reducer = (state: State, action: Action): State => {
```

```
  switch (action.type) {
```

```
    case "ADD_TOAST":
```

```
      return {
```

```
        ...state,
```

```
toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
```

```
};
```

```
case "UPDATE_TOAST":
```

```
  return {
```

```
    ...state,
```

```
    toasts: state.toasts.map((t) => (t.id === action.toast.id ? { ...t, ...action.toast } : t)),
```

```
  };
```

```
case "DISMISS_TOAST": {
```

```
  const { toastId } = action;
```

```
  // ! Side effects ! - This could be extracted into a dismissToast() action,
```

```
  // but I'll keep it here for simplicity
```

```
  if (toastId) {
```

```
    addToRemoveQueue(toastId);
```

```
  } else {
```

```
    state.toasts.forEach((toast) => {
```

```
      addToRemoveQueue(toast.id);
```

```
    });
```

```
  }
```

```
  return {
```

```
    ...state,
```

```
    toasts: state.toasts.map((t) =>
```

```
      t.id === toastId || toastId === undefined
```



```
? {
```

```
...t,
```

```
open: false,
```

```
}
```

```
: t,
```

```
),
```

```
};
```

```
}
```

```
case "REMOVE_TOAST":
```

```
if (action.toastId === undefined) {
```

```
return {
```

```
...state,
```

```
toasts: [],
```

```
};
```

```
}
```

```
return {
```

```
...state,
```

```
toasts: state.toasts.filter((t) => t.id !== action.toastId),
```

```
};
```

```
}
```

```
};
```

```
const listeners: Array<(state: State) => void> = [];
```

```
let memoryState: State = { toasts: [] };
```

```
function dispatch(action: Action) {  
  memoryState = reducer(memoryState, action);  
  listeners.forEach((listener) => {  
    listener(memoryState);  
  });  
}
```

```
type Toast = Omit<ToasterToast, "id">;
```

```
function toast({ ...props }: Toast) {
```

```
  const id = genId();
```

```
  const update = (props: ToasterToast) =>
```

```
    dispatch({
```

```
      type: "UPDATE_TOAST",
```

```
      toast: { ...props, id },
```

```
    });
```

```
  const dismiss = () => dispatch({ type: "DISMISS_TOAST", toastId: id });
```

```
  dispatch({
```

```
    type: "ADD_TOAST",
```

```
    toast: {
```

```
      ...props,
```

```
      id,
```

```
      open: true,
```

```
      onOpenChange: (open) => {
```

```
    if (!open) dismiss();
```

```
  },
```

```
  },
```

```
});
```

```
return {
```

```
  id: id,
```

```
  dismiss,
```

```
  update,
```

```
};
```

```
}
```

```
function useToast() {
```

```
  const [state, setState] = React.useState<State>(memoryState);
```

```
  React.useEffect(() => {
```

```
    listeners.push(setState);
```

```
    return () => {
```

```
      const index = listeners.indexOf(setState);
```

```
      if (index > -1) {
```

```
        listeners.splice(index, 1);
```

```
      }
```

```
    };
```

```
  }, [state]);
```

```
  return {
```

```
...state,  
  
toast,  
  
dismiss: (toastId?: string) => dispatch({ type: "DISMISS_TOAST", toastId }),  
  
};  
  
}
```

```
export { useToast, toast };  
  
import { useState } from 'react';  
  
import { supabase } from '@integrations/supabase/client';  
  
import { FoodAnalysis } from '@types/food';  
  
import { toast } from 'sonner';
```

```
export function useAnalyzeFood() {  
  
  const [isAnalyzing, setIsAnalyzing] = useState(false);  
  
  
  const analyzeFood = async (imageBase64: string): Promise<FoodAnalysis> => {  
  
    setIsAnalyzing(true);  
  
  
    try {  
  
      const { data, error } = await supabase.functions.invoke('analyze-food', {  
  
        body: { image: imageBase64 },  
  
      });  
  
  
  
  
      if (error) {  
  
        console.error('Edge function error:', error);  
  
        throw new Error(error.message || 'Failed to analyze food');  
      }  
  
    }  
  
  }  
  
}
```

```
}
```

```
if (data?.error) {
```

```
  throw new Error(data.error);
```

```
}
```

```
// Validate the response has required fields
```

```
if (!data?.food_items || !Array.isArray(data.food_items)) {
```

```
  throw new Error('Invalid response from AI');
```

```
}
```

```
// Transform response to match our FoodAnalysis type
```

```
const analysis: FoodAnalysis = {
```

```
  food_items: data.food_items.map((item: any) => ({
```

```
    name: item.name || 'Unknown food',
```

```
    estimated_calories: item.estimated_calories || 0,
```

```
    macros: {
```

```
      protein_g: item.macros?.protein_g || 0,
```

```
      carbs_g: item.macros?.carbs_g || 0,
```

```
      fat_g: item.macros?.fat_g || 0,
```

```
    },
```

```
    freshness_score: item.freshness_score || 0.8,
```

```
    portion_size: item.portion_size || 'standard serving',
```

```
    estimated_weight_grams: item.estimated_weight_grams || 100,
```

```
  })),
```

```
  total_calories: data.total_calories || 0,
```

```
    confidence: data.confidence || 0.8,

    freshness_warning: data.freshness_warning || null,

    notes: data.notes || null,

  };

  return analysis;
} catch (err) {

  console.error('Analysis error:', err);

  const message = err instanceof Error ? err.message : 'Analysis failed';

  toast.error(message);

  throw err;

} finally {

  setIsAnalyzing(false);

}

};
```

```
  return { analyzeFood, isAnalyzing };
}
```

```
import { useQuery, useMutation, useQueryClient } from '@tanstack/react-query';

import { supabase } from '@integrations/supabase/client';

import { useAuth } from '@contexts/AuthContext';

import { FoodLog, FoodAnalysis } from '@types/food';

import { toast } from 'sonner';

import { Json } from '@integrations/supabase/types';
```

```
function getFreshnessStatus(score: number): 'fresh' | 'acceptable' | 'spoiled' {
```

```
if (score >= 0.7) return 'fresh';

if (score >= 0.4) return 'acceptable';

return 'spoiled';

}
```

```
export function useFoodLogs() {

  const { user } = useAuth();

  const queryClient = useQueryClient();

  const { data: logs = [], isLoading } = useQuery({

    queryKey: ['foodLogs', user?.id],

    queryFn: async () => {

      if (!user) return [];

      const { data, error } = await supabase

        .from('food_logs')

        .select('*')

        .eq('user_id', user.id)

        .order('logged_at', { ascending: false });

      if (error) throw error;

      // Transform the data to match our FoodLog type

      return (data || []).map((log) => ({

        ...log,

        ai_analysis: log.ai_analysis as unknown as FoodAnalysis | null,
```

```
    freshness_status: log.freshness_status as 'fresh' | 'acceptable' | 'spoiled' | null,  
  )) as FoodLog[];  
  
},  
  
enabled: !!user,  
  
});
```

```
const addLog = useMutation({  
  mutationFn: async ({  
    analysis,  
    imageUrl,  
  }: {  
    analysis: FoodAnalysis;  
    imageUrl?: string;  
  }) => {  
    if (!user) throw new Error('Not authenticated');
```

```
    // Create a log entry for each food item, or one combined entry  
  
    const primaryFood = analysis.food_items[0];  
  
    const foodNames = analysis.food_items.map(f => f.name).join(', ');
```

```
    // Calculate totals from all food items
```

```
    const totalWeight = analysis.food_items.reduce((sum, f) => sum +  
    (f.estimated_weight_grams || 0), 0);
```

```
    const totalProtein = analysis.food_items.reduce((sum, f) => sum + (f.macros?.protein_g || 0),  
    0);
```

```
    const totalCarbs = analysis.food_items.reduce((sum, f) => sum + (f.macros?.carbs_g || 0), 0);
```

```
    const totalFat = analysis.food_items.reduce((sum, f) => sum + (f.macros?.fat_g || 0), 0);
```



```
const { error } = await supabase.from('food_logs').insert([  
  user_id: user.id,  
  image_url: imageUrl || null,  
  food_name: foodNames,  
  portion_size: primaryFood?.portion_size || null,  
  estimated_weight_grams: totalWeight,  
  calories: analysis.total_calories,  
  protein_grams: totalProtein,  
  carbs_grams: totalCarbs,  
  fat_grams: totalFat,  
  freshness_score: primaryFood?.freshness_score || null,  
  freshness_status: primaryFood ? getFreshnessStatus(primaryFood.freshness_score) : null,  
  confidence_score: analysis.confidence || null,  
  ai_analysis: analysis as unknown as Json,  
]);
```

```
if (error) throw error;
```

```
},
```

```
onSuccess: () => {
```

```
  queryClient.invalidateQueries({ queryKey: ['foodLogs'] });
```

```
  toast.success('Meal logged successfully!');
```

```
},
```

```
onError: (error) => {
```

```
  console.error('Failed to log meal:', error);
```

```
  toast.error('Failed to log meal');
```

```
},
```

```
});
```

```
const deleteLog = useMutation({
```

```
  mutationFn: async (logId: string) => {
```

```
    if (!user) throw new Error('Not authenticated');
```

```
    const { error } = await supabase
```

```
      .from('food_logs')
```

```
      .delete()
```

```
      .eq('id', logId)
```

```
      .eq('user_id', user.id);
```

```
    if (error) throw error;
```

```
  },
```

```
  onSuccess: () => {
```

```
    queryClient.invalidateQueries({ queryKey: ['foodLogs'] });
```

```
    toast.success('Meal deleted');
```

```
  },
```

```
  onError: (error) => {
```

```
    console.error('Failed to delete meal:', error);
```

```
    toast.error('Failed to delete meal');
```

```
  },
```

```
});
```

```
const todayCalories = logs
```

```
.filter((log) => {  
  
  const logDate = new Date(log.logged_at).toDateString();  
  
  const today = new Date().toDateString();  
  
  return logDate === today;  
  
})  
  
.reduce((sum, log) => sum + (log.calories || 0), 0);  
  
  
return {  
  logs,  
  isLoading,  
  addLog,  
  deleteLog,  
  todayCalories,  
};  
}  
  
import { useQuery, useMutation, useQueryClient } from '@tanstack/react-query';  
  
import { supabase } from '@integrations/supabase/client';  
  
import { useAuth } from '@contexts/AuthContext';  
  
import { toast } from 'sonner';  
  
  
export interface UserSettings {  
  id: string;  
  
  user_id: string;  
  
  calorie_goal: number;  
  
  is_premium: boolean;  
  
  premium_expires_at: string | null;
```

```
  daily_scan_count: number;

  last_scan_date: string | null;
}
```

```
const FREE_SCAN_LIMIT = 5;
```

```
export const useUserSettings = () => {
```

```
  const { user } = useAuth();
```

```
  const queryClient = useQueryClient();
```

```
  const { data: settings, isLoading } = useQuery({
```

```
    queryKey: ['userSettings', user?.id],
```

```
    queryFn: async (): Promise<UserSettings | null> => {
```

```
      if (!user) return null;
```

```
      // First try to get existing settings
```

```
      const { data, error } = await supabase
```

```
        .from('user_settings')
```

```
        .select('*')
```

```
        .eq('user_id', user.id)
```

```
        .maybeSingle();
```

```
      if (error && error.code !== 'PGRST116') {
```

```
        console.error('Error fetching settings:', error);
```

```
        throw error;
```

```
      }
```

```
// If no settings exist, create default settings
```

```
if (!data) {
```

```
  const { data: newSettings, error: insertError } = await supabase
```

```
    .from('user_settings')
```

```
    .insert({ user_id: user.id })
```

```
    .select()
```

```
    .single();
```

```
  if (insertError) {
```

```
    console.error('Error creating settings:', insertError);
```

```
    throw insertError;
```

```
  }
```

```
  return newSettings as UserSettings;
```

```
}
```

```
  return data as UserSettings;
```

```
},
```

```
  enabled: !!user,
```

```
});
```

```
const updateCalorieGoal = useMutation({
```

```
  mutationFn: async (newGoal: number) => {
```

```
    if (!user || !settings) throw new Error('Not authenticated');
```

```
const { error } = await supabase
```

```
.from('user_settings')
```

```
.update({ calorie_goal: newGoal })
```

```
.eq('user_id', user.id);
```

```
if (error) throw error;
```

```
},
```

```
onSuccess: () => {
```

```
  queryClient.invalidateQueries({ queryKey: ['userSettings'] });
```

```
  toast.success('Calorie goal updated!');
```

```
},
```

```
onError: (error) => {
```

```
  console.error('Error updating calorie goal:', error);
```

```
  toast.error('Failed to update calorie goal');
```

```
},
```

```
});
```

```
const incrementScanCount = useMutation({
```

```
  mutationFn: async () => {
```

```
    if (!user || !settings) throw new Error('Not authenticated');
```

```
    const today = new Date().toISOString().split('T')[0];
```

```
    const isNewDay = settings.last_scan_date !== today;
```

```
    const newCount = isNewDay ? 1 : settings.daily_scan_count + 1;
```

```
const { error } = await supabase
```

```
.from('user_settings')
```

```
.update({
```

```
  daily_scan_count: newCount,
```

```
  last_scan_date: today
```

```
})
```

```
.eq('user_id', user.id);
```

```
if (error) throw error;
```

```
return newCount;
```

```
},
```

```
onSuccess: () => {
```

```
  queryClient.invalidateQueries({ queryKey: ['userSettings'] });
```

```
},
```

```
});
```

```
const upgradeToPremium = useMutation({
```

```
  mutationFn: async () => {
```

```
    if (!user) throw new Error('Not authenticated');
```

```
    // In a real app, this would process payment first
```

```
    // For MVP, we just set the flag
```

```
    const expiresAt = new Date();
```

```
    expiresAt.setMonth(expiresAt.getMonth() + 1);
```

```
const { error } = await supabase
```

```
.from('user_settings')
```

```
.update({
```

```
  is_premium: true,
```

```
  premium_expires_at: expiresAt.toISOString()
```

```
})
```

```
.eq('user_id', user.id);
```

```
  if (error) throw error;
```

```
},
```

```
  onSuccess: () => {
```

```
    queryClient.invalidateQueries({ queryKey: ['userSettings'] });
```

```
    toast.success('Welcome to LooKai Premium! 🎉');
```

```
},
```

```
  onError: (error) => {
```

```
    console.error('Error upgrading:', error);
```

```
    toast.error('Failed to upgrade. Please try again!');
```

```
},
```

```
});
```

```
// Check if today is a new day and reset count if needed
```

```
const today = new Date().toISOString().split('T')[0];
```

```
const isNewDay = settings?.last_scan_date !== today;
```

```
const currentScanCount = isNewDay ? 0 : (settings?.daily_scan_count || 0);
```

```
const isPremium = settings?.is_premium || false;
```

```
const canScan = isPremium || currentScanCount < FREE_SCAN_LIMIT;
```



```
const scansRemaining = isPremium ? Infinity : Math.max(0, FREE_SCAN_LIMIT - currentScanCount);
```

```
const calorieGoal = settings?.calorie_goal || 2000;
```

```
return {
```

```
  settings,
```

```
  isLoading,
```

```
  isPremium,
```

```
  canScan,
```

```
  scansRemaining,
```

```
  calorieGoal,
```

```
  updateCalorieGoal,
```

```
  incrementScanCount,
```

```
  upgradeToPremium,
```

```
};
```

```
};
```

```
// This file is automatically generated. Do not edit it directly.
```

```
import { createClient } from '@supabase/supabase-js';
```

```
import type { Database } from './types';
```

```
const SUPABASE_URL = import.meta.env.VITE_SUPABASE_URL;
```

```
const SUPABASE_PUBLISHABLE_KEY = import.meta.env.VITE_SUPABASE_PUBLISHABLE_KEY;
```

```
// Import the supabase client like this:
```

```
// import { supabase } from "@integrations/supabase/client";
```

```
export const supabase = createClient<Database>(SUPABASE_URL,
SUPABASE_PUBLISHABLE_KEY, {

  auth: {

    storage: localStorage,

    persistSession: true,

    autoRefreshToken: true,

  }

});export type Json =

  | string

  | number

  | boolean

  | null

  | { [key: string]: Json | undefined }

  | Json[]


export type Database = {

  // Allows to automatically instantiate createClient with right options
  // instead of createClient<Database, { PostgrestVersion: 'XX' }>(URL, KEY)

  __InternalSupabase: {

    PostgrestVersion: "14.1"

  }

  public: {

    Tables: {

      food_items: {

        Row: {

          calories_100g: number | null
```

calories_per_portion: number | null

carbs_g: number | null

category: string | null

created_at: string | null

fat_g: number | null

id: string

local_names: string[] | null

name: string

portion_unit: string | null

protein_g: number | null

region: string | null

}

Insert: {

calories_100g?: number | null

calories_per_portion?: number | null

carbs_g?: number | null

category?: string | null

created_at?: string | null

fat_g?: number | null

id?: string

local_names?: string[] | null

name: string

portion_unit?: string | null

protein_g?: number | null

region?: string | null

}

Update: {

calories_100g?: number | null

calories_per_portion?: number | null

carbs_g?: number | null

category?: string | null

created_at?: string | null

fat_g?: number | null

id?: string

local_names?: string[] | null

name?: string

portion_unit?: string | null

protein_g?: number | null

region?: string | null

}

Relationships: []

}

food_logs: {

Row: {

ai_analysis: Json | null

calories: number

carbs_grams: number | null

confidence_score: number | null

created_at: string

estimated_weight_grams: number | null

fat_grams: number | null

food_name: string

freshness_score: number | null

freshness_status: string | null

id: string

image_url: string | null

logged_at: string

portion_size: string | null

protein_grams: number | null

user_id: string

}

Insert: {

ai_analysis?: Json | null

calories: number

carbs_grams?: number | null

confidence_score?: number | null

created_at?: string

estimated_weight_grams?: number | null

fat_grams?: number | null

food_name: string

freshness_score?: number | null

freshness_status?: string | null

id?: string

image_url?: string | null

logged_at?: string

portion_size?: string | null

protein_grams?: number | null

user_id: string

```
}
```

```
Update: {
```

```
  ai_analysis?: Json | null
```

```
  calories?: number
```

```
  carbs_grams?: number | null
```

```
  confidence_score?: number | null
```

```
  created_at?: string
```

```
  estimated_weight_grams?: number | null
```

```
  fat_grams?: number | null
```

```
  food_name?: string
```

```
  freshness_score?: number | null
```

```
  freshness_status?: string | null
```

```
  id?: string
```

```
  image_url?: string | null
```

```
  logged_at?: string
```

```
  portion_size?: string | null
```

```
  protein_grams?: number | null
```

```
  user_id?: string
```

```
}
```

```
Relationships: []
```

```
}
```

```
profiles: {
```

```
  Row: {
```

```
    avatar_url: string | null
```

```
    created_at: string
```

```
    display_name: string | null
```

email: string | null

id: string

updated_at: string

user_id: string

}

Insert: {

avatar_url?: string | null

created_at?: string

display_name?: string | null

email?: string | null

id?: string

updated_at?: string

user_id: string

}

Update: {

avatar_url?: string | null

created_at?: string

display_name?: string | null

email?: string | null

id?: string

updated_at?: string

user_id?: string

}

Relationships: []

}

user_settings: {

Row: {

calorie_goal: number

created_at: string

daily_scan_count: number

id: string

is_premium: boolean

last_scan_date: string | null

premium_expires_at: string | null

updated_at: string

user_id: string

}

Insert: {

calorie_goal?: number

created_at?: string

daily_scan_count?: number

id?: string

is_premium?: boolean

last_scan_date?: string | null

premium_expires_at?: string | null

updated_at?: string

user_id: string

}

Update: {

calorie_goal?: number

created_at?: string

daily_scan_count?: number


```
    id?: string
    is_premium?: boolean
    last_scan_date?: string | null
    premium_expires_at?: string | null
    updated_at?: string
    user_id?: string
  }
```

```
  Relationships: []
```

```
}
```

```
}
```

```
Views: {
```

```
  [_ in never]: never
```

```
}
```

```
Functions: {
```

```
  [_ in never]: never
```

```
}
```

```
Enums: {
```

```
  [_ in never]: never
```

```
}
```

```
CompositeTypes: {
```

```
  [_ in never]: never
```

```
}
```

```
}
```

```
}
```

```
type DatabaseWithoutInternals = Omit<Database, "__InternalSupabase">
```

```
type DefaultSchema = DatabaseWithoutInternals[Extract<keyof Database, "public">]
```

```
export type Tables<
```

```
  DefaultSchemaTableNameOrOptions extends
```

```
    | keyof (DefaultSchema["Tables"] & DefaultSchema["Views"])
```

```
    | { schema: keyof DatabaseWithoutInternals },
```

```
  TableName extends DefaultSchemaTableNameOrOptions extends {
```

```
    schema: keyof DatabaseWithoutInternals
```

```
  }
```

```
    ? keyof (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]  
["Tables"] &
```

```
  DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])
```

```
    : never = never,
```

```
> = DefaultSchemaTableNameOrOptions extends {
```

```
  schema: keyof DatabaseWithoutInternals
```

```
}
```

```
  ? (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"] &
```

```
    DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])  
[TableName] extends {
```

```
  Row: infer R
```

```
}
```

```
  ? R
```

```
  : never
```

```
  : DefaultSchemaTableNameOrOptions extends keyof (DefaultSchema["Tables"] &
```

```
    DefaultSchema["Views"])
```

```
  ? (DefaultSchema["Tables"] &
```

```
DefaultSchema["Views"])[DefaultSchemaTableNameOrOptions] extends {
```

```
Row: infer R
```

```
}
```

```
? R
```

```
: never
```

```
: never
```

```
export type TablesInsert<
```

```
DefaultSchemaTableNameOrOptions extends
```

```
| keyof DefaultSchema["Tables"]
```

```
| { schema: keyof DatabaseWithoutInternals },
```

```
TableName extends DefaultSchemaTableNameOrOptions extends {
```

```
schema: keyof DatabaseWithoutInternals
```

```
}
```

```
? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]  
["Tables"]
```

```
: never = never,
```

```
> = DefaultSchemaTableNameOrOptions extends {
```

```
schema: keyof DatabaseWithoutInternals
```

```
}
```

```
? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]  
[TableName] extends {
```

```
Insert: infer I
```

```
}
```

```
? I
```

```
: never
```

```
: DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
```

```
? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
```

```
  Insert: infer I
```

```
}
```

```
? I
```

```
: never
```

```
: never
```

```
export type TablesUpdate<
```

```
  DefaultSchemaTableNameOrOptions extends
```

```
    | keyof DefaultSchema["Tables"]
```

```
    | { schema: keyof DatabaseWithoutInternals },
```

```
  TableName extends DefaultSchemaTableNameOrOptions extends {
```

```
    schema: keyof DatabaseWithoutInternals
```

```
  }
```

```
    ? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]  
    ["Tables"]
```

```
    : never = never,
```

```
  > = DefaultSchemaTableNameOrOptions extends {
```

```
    schema: keyof DatabaseWithoutInternals
```

```
  }
```

```
    ? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]  
    [TableName] extends {
```

```
      Update: infer U
```

```
    }
```

```
? U
```

```
: never
```

```
: DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
```

```
? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
```

```
  Update: infer U
```

```
}
```

```
? U
```

```
: never
```

```
: never
```

```
export type Enums<
```

```
  DefaultSchemaEnumNameOrOptions extends
```

```
    | keyof DefaultSchema["Enums"]
```

```
    | { schema: keyof DatabaseWithoutInternals },
```

```
  EnumName extends DefaultSchemaEnumNameOrOptions extends {
```

```
    schema: keyof DatabaseWithoutInternals
```

```
  }
```

```
  ? keyof DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]  
  ["Enums"]
```

```
  : never = never,
```

```
> = DefaultSchemaEnumNameOrOptions extends {
```

```
  schema: keyof DatabaseWithoutInternals
```

```
}
```

```
  ? DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]["Enums"]  
  [EnumName]
```

```
  : DefaultSchemaEnumNameOrOptions extends keyof DefaultSchema["Enums"]
```

```
    ? DefaultSchema["Enums"][DefaultSchemaEnumNameOrOptions]
```

```
    : never
```

```
export type CompositeTypes<
```

```

PublicCompositeTypeNameOrOptions extends
  | keyof DefaultSchema["CompositeTypes"]
  | { schema: keyof DatabaseWithoutInternals },

CompositeTypeName extends PublicCompositeTypeNameOrOptions extends {
  schema: keyof DatabaseWithoutInternals
}

? keyof DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]
["CompositeTypes"]

: never = never,

> = PublicCompositeTypeNameOrOptions extends {
  schema: keyof DatabaseWithoutInternals
}

? DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]
["CompositeTypes"][CompositeTypeName]

: PublicCompositeTypeNameOrOptions extends keyof DefaultSchema["CompositeTypes"]

? DefaultSchema["CompositeTypes"][PublicCompositeTypeNameOrOptions]

: never

```

```

export const Constants = {

  public: {

    Enums: {},

  },

} as const

import { clsx, type ClassValue } from "clsx";

import { twMerge } from "tailwind-merge";

export function cn(...inputs: ClassValue[]) {

```

```
    return twMerge(clsx(inputs));
}

import { useState, useEffect } from 'react';

import { useNavigate } from 'react-router-dom';

import { useAuth } from '@/contexts/AuthContext';

import { Button } from '@/components/ui/button';

import { Input } from '@/components/ui/input';

import { Label } from '@/components/ui/label';

import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';

import { Mail, Lock, Loader2, Eye, EyeOff, ArrowRight, Sparkles } from 'lucide-react';

import { toast } from 'sonner';

import { z } from 'zod';

import { Logo } from '@/components/Logo';

const emailSchema = z.string().email('Please enter a valid email');

const passwordSchema = z.string().min(6, 'Password must be at least 6 characters');

export default function Auth() {

  const navigate = useNavigate();

  const { user, signInWithGoogle, signInWithEmail, signUpWithEmail } = useAuth();

  const [email, setEmail] = useState('');

  const [password, setPassword] = useState('');

  const [showPassword, setShowPassword] = useState(false);

  const [loading, setLoading] = useState(false);

  const [errors, setErrors] = useState<{ email?: string; password?: string }>({});
```

```
useEffect(() => {  
  if (user) {  
    navigate('/', { replace: true });  
  }  
}, [user, navigate]);
```

```
const validateForm = () => {  
  const newErrors: { email?: string; password?: string } = {};  
  
  try {  
    emailSchema.parse(email);  
  } catch (e) {  
    if (e instanceof z.ZodError) {  
      newErrors.email = e.errors[0].message;  
    }  
  }  
}
```

```
try {  
  passwordSchema.parse(password);  
} catch (e) {  
  if (e instanceof z.ZodError) {  
    newErrors.password = e.errors[0].message;  
  }  
}
```

```
setErrors(newErrors);
```



```
return Object.keys(newErrors).length === 0;
```

```
};
```

```
const handleEmailSignIn = async (e: React.FormEvent) => {
```

```
  e.preventDefault();
```

```
  if (!validateForm()) return;
```

```
  setLoading(true);
```

```
  const { error } = await signInWithEmail(email, password);
```

```
  setLoading(false);
```

```
  if (error) {
```

```
    if (error.message.includes('Invalid login credentials')) {
```

```
      toast.error('Invalid email or password');
```

```
    } else {
```

```
      toast.error(error.message);
```

```
    }
```

```
  }
```

```
};
```

```
const handleEmailSignUp = async (e: React.FormEvent) => {
```

```
  e.preventDefault();
```

```
  if (!validateForm()) return;
```

```
  setLoading(true);
```

```
  const { error } = await signUpWithEmail(email, password);
```

```
setLoading(false);
```

```
if (error) {
```

```
  if (error.message.includes('already registered')) {
```

```
    toast.error('This email is already registered. Please sign in.');
```

```
  } else {
```

```
    toast.error(error.message);
```

```
  }
```

```
} else {
```

```
  toast.success('Account created! You can now sign in.');
```

```
}
```

```
};
```

```
const handleGoogleSignIn = async () => {
```

```
  setLoading(true);
```

```
  const { error } = await signInWithGoogle();
```

```
  setLoading(false);
```

```
if (error) {
```

```
  toast.error('Failed to sign in with Google');
```

```
}
```

```
};
```

```
return (
```

```
<div className="min-h-screen bg-background flex flex-col">
```

```
  { /* Hero Section */ }
```

```
<div className="flex-1 flex flex-col items-center justify-center px-6 py-12 safe-top">
```

```
<div className="w-full max-w-sm space-y-8 animate-scale-in">
```

```
{/* Logo & Branding */}
```

```
<div className="text-center space-y-4">
```

```
<div className="inline-flex">
```

```
<Logo size="lg" showText={false} />
```

```
</div>
```

```
<div>
```

```
<h1 className="font-display font-bold text-3xl text-foreground tracking-tight">
```

```
  LookKai
```

```
</h1>
```

```
<p className="text-muted-foreground mt-2 text-base">
```

```
  AI-powered calorie tracking
```

```
</p>
```

```
</div>
```

```
</div>
```

```
{/* Features pills */}
```

```
<div className="flex flex-wrap justify-center gap-2">
```

```
{['📷 Snap', '🔍 Analyze', '📊 Track'].map((feature) => (
```

```
<span
```

```
  key={feature}
```

```
  className="px-3 py-1.5 bg-secondary rounded-full text-sm text-muted-foreground"
```

```
>
```

```
    {feature}
```

```
</span>
```

```
    )}}
```

```
</div>
```

```
{/* Auth Card */}
```

```
<div className="bg-card rounded-3xl p-6 shadow-card border border-border">
```

```
  <Tabs defaultValue="signin" className="w-full">
```

```
    <TabsList className="grid w-full grid-cols-2 mb-6 h-12 p-1 bg-secondary rounded-xl">
```

```
      <TabsTrigger
```

```
        value="signin"
```

```
        className="font-medium rounded-lg data-[state=active]:bg-background data-[state=active]:shadow-sm transition-all"
```

```
      >
```

```
        Sign In
```

```
    </TabsTrigger>
```

```
    <TabsTrigger
```

```
      value="signup"
```

```
      className="font-medium rounded-lg data-[state=active]:bg-background data-[state=active]:shadow-sm transition-all"
```

```
    >
```

```
      Sign Up
```

```
    </TabsTrigger>
```

```
  </TabsList>
```

```
  <TabsContent value="signin" className="mt-0">
```

```
    <form onSubmit={handleEmailSignIn} className="space-y-4">
```

```
      <div className="space-y-2">
```

```
        <Label htmlFor="signin-email" className="text-sm font-medium">Email</Label>
```

```
<div className="relative">
```

```
  <Mail className="absolute left-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
```

```
  <Input
```

```
    id="signin-email"
```

```
    type="email"
```

```
    placeholder="you@example.com"
```

```
    value={email}
```

```
    onChange={(e) => setEmail(e.target.value)}
```

```
    className="pl-10 h-12 rounded-xl bg-secondary border-0 focus:ring-2 focus:ring-primary"
```

```
  />
```

```
</div>
```

```
{errors.email && (
```

```
  <p className="text-sm text-destructive">{errors.email}</p>
```

```
)}
```

```
</div>
```

```
<div className="space-y-2">
```

```
  <Label htmlFor="signin-password" className="text-sm font-medium">Password</Label>
```

```
  <div className="relative">
```

```
    <Lock className="absolute left-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
```

```
    <Input
```

```
      id="signin-password"
```

```
      type={showPassword ? 'text' : 'password'}
```

```
placeholder="....."
```

```
value={password}
```

```
onChange={(e) => setPassword(e.target.value)}
```

```
className="pl-10 pr-10 h-12 rounded-xl bg-secondary border-0 focus:ring-2  
focus:ring-primary"
```

```
/>
```

```
<button
```

```
type="button"
```

```
onClick={() => setShowPassword(!showPassword)}
```

```
className="absolute right-3.5 top-1/2 -translate-y-1/2 text-muted-foreground  
hover:text-foreground transition-colors"
```

```
>
```

```
{showPassword ? <EyeOff className="h-4 w-4" /> : <Eye className="h-4 w-4" />}
```

```
</button>
```

```
</div>
```

```
{errors.password && (
```

```
<p className="text-sm text-destructive">{errors.password}</p>
```

```
)}
```

```
</div>
```

```
<Button
```

```
type="submit"
```

```
disabled={loading}
```

```
className="w-full h-12 rounded-xl font-semibold gradient-fresh text-primary-  
foreground shadow-glow-sm transition-all hover:shadow-glow"
```

```
>
```

```
{loading ? (
```

```
<Loader2 className="h-5 w-5 animate-spin" />
```

```
) : (
```

```
<>
```

```
Sign In
```

```
<ArrowRight className="ml-2 h-4 w-4" />
```

```
</>
```

```
}}
```

```
</Button>
```

```
</form>
```

```
</TabsContent>
```

```
<TabsContent value="signup" className="mt-0">
```

```
<form onSubmit={handleEmailSignUp} className="space-y-4">
```

```
<div className="space-y-2">
```

```
<Label htmlFor="signup-email" className="text-sm font-medium">Email</Label>
```

```
<div className="relative">
```

```
<Mail className="absolute left-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
```

```
<Input
```

```
id="signup-email"
```

```
type="email"
```

```
placeholder="you@example.com"
```

```
value={email}
```

```
onChange={(e) => setEmail(e.target.value)}
```

```
className="pl-10 h-12 rounded-xl bg-secondary border-0 focus:ring-2 focus:ring-primary"
```

```
/>
```

```
</div>
```

```
{errors.email && (
```

```
<p className="text-sm text-destructive">{errors.email}</p>
```

```
)}
```

```
</div>
```

```
<div className="space-y-2">
```

```
<Label htmlFor="signup-password" className="text-sm font-medium">Password</Label>
```

```
<div className="relative">
```

```
<Lock className="absolute left-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
```

```
<Input
```

```
id="signup-password"
```

```
type={showPassword ? 'text' : 'password'}
```

```
placeholder="••••••••"
```

```
value={password}
```

```
onChange={(e) => setPassword(e.target.value)}
```

```
className="pl-10 pr-10 h-12 rounded-xl bg-secondary border-0 focus:ring-2 focus:ring-primary"
```

```
/>
```

```
<button
```

```
type="button"
```

```
onClick={() => setShowPassword(!showPassword)}
```

```
className="absolute right-3.5 top-1/2 -translate-y-1/2 text-muted-foreground hover:text-foreground transition-colors"
```

```
>
```



```
{showPassword ? <EyeOff className="h-4 w-4" /> : <Eye className="h-4 w-4" />}
```

```
</button>
```

```
</div>
```

```
{errors.password && (
```

```
<p className="text-sm text-destructive">{errors.password}</p>
```

```
)}
```

```
</div>
```

```
<Button
```

```
type="submit"
```

```
disabled={loading}
```

```
className="w-full h-12 rounded-xl font-semibold gradient-fresh text-primary-foreground shadow-glow-sm transition-all hover:shadow-glow"
```

```
>
```

```
{loading ? (
```

```
<Loader2 className="h-5 w-5 animate-spin" />
```

```
): (
```

```
<>
```

```
Create Account
```

```
<Sparkles className="ml-2 h-4 w-4" />
```

```
</>
```

```
)}
```

```
</Button>
```

```
</form>
```

```
</TabsContent>
```

```
</Tabs>
```

```
<div className="relative my-6">
```

```
  <div className="absolute inset-0 flex items-center">
```

```
    <div className="w-full border-t border-border" />
```

```
  </div>
```

```
  <div className="relative flex justify-center text-xs uppercase">
```

```
    <span className="bg-card px-3 text-muted-foreground">or</span>
```

```
  </div>
```

```
</div>
```

```
<Button
```

```
  onClick={handleGoogleSignIn}
```

```
  disabled={loading}
```

```
  variant="outline"
```

```
  className="w-full h-12 rounded-xl font-medium border-2 hover:bg-secondary  
  transition-all"
```

```
>
```

```
  <svg className="h-5 w-5 mr-2" viewBox="0 0 24 24">
```

```
    <path
```

```
      fill="#4285F4"
```

```
      d="M22.56 12.25c0-.78-.07-1.53-.2-2.25H12v4.26h5.92c-.26 1.37-1.04 2.53-2.21  
3.31v2.77h3.57c2.08-1.92 3.28-4.74 3.28-8.09z"
```

```
    />
```

```
    <path
```

```
      fill="#34A853"
```

```
      d="M12 23c2.97 0 5.46-.98 7.28-2.66l-3.57-2.77c-.98.66-2.23 1.06-3.71 1.06-2.86 0-  
5.29-1.93-6.16-4.53H2.18v2.84C3.99 20.53 7.7 23 12 23z"
```

```
/>
```

```
<path
```

```
fill="#FBBC05"
```

```
d="M5.84 14.09c-.22-.66-.35-1.36-.35-2.09s.13-1.43.35-2.09V7.07H2.18C1.43 8.55 1  
10.22 1 12s.43 3.45 1.18 4.93l2.85-2.22.81-.62z"
```

```
/>
```

```
<path
```

```
fill="#EA4335"
```

```
d="M12 5.38c1.62 0 3.06.56 4.21 1.64l3.15-3.15C17.45 2.09 14.97 1 12 1 7.7 1 3.99 3.47  
2.18 7.07l3.66 2.84c.87-2.6 3.3-4.53 6.16-4.53z"
```

```
/>
```

```
</svg>
```

```
Continue with Google
```

```
</Button>
```

```
</div>
```

```
<p className="text-center text-xs text-muted-foreground px-4">
```

```
By continuing, you agree to our Terms of Service and Privacy Policy.
```

```
</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
);
```

```
}
```

```
import { useState } from 'react';
```

```
import { Header } from '@components/Header';
```

```
import { ImageCapture } from '@components/ImageCapture';
```

```
import { FoodAnalysisResult } from '@components/FoodAnalysisResult';

import { DailyStats } from '@components/DailyStats';

import { MealHistory } from '@components/MealHistory';

import { useFoodLogs } from '@hooks/useFoodLogs';

import { FoodAnalysis } from '@types/food';

import { supabase } from '@integrations/supabase/client';

import { toast } from 'sonner';

import { Tabs, TabsContent, TabsList, TabsTrigger } from '@components/ui/tabs';

import { Camera, History } from 'lucide-react';

export default function Dashboard() {

  const [isAnalyzing, setIsAnalyzing] = useState(false);

  const [analysisResult, setAnalysisResult] = useState<FoodAnalysis | null>(null);

  const [currentImageBase64, setCurrentImageBase64] = useState<string | null>(null);

  const { logs, isLoading, addLog, deleteLog, todayCalories } = useFoodLogs();

  const handleImageCapture = async (imageBase64: string) => {

    setIsAnalyzing(true);

    setCurrentImageBase64(imageBase64);

    try {

      // Get current session to ensure user is authenticated

      const { data: sessionData } = await supabase.auth.getSession();

      if (!sessionData.session) {
```

```
throw new Error('You must be logged in to analyze food');
```

```
}
```

```
// Call edge function with explicit Authorization header
```

```
const response = await fetch(
```

```
`${import.meta.env.VITE_SUPABASE_URL}/functions/v1/analyze-food`,
```

```
{
```

```
  method: 'POST',
```

```
  headers: {
```

```
    'Content-Type': 'application/json',
```

```
    'Authorization': `Bearer ${sessionData.session.access_token}`,
```

```
  },
```

```
  body: JSON.stringify({ image: imageBase64 }),
```

```
}
```

```
);
```

```
if (!response.ok) {
```

```
  const errorData = await response.json().catch(() => ({}));
```

```
  throw new Error(errorData.error || `Analysis failed: ${response.status}`);
```

```
}
```

```
const data = await response.json();
```

```
if (data.error) {
```

```
  throw new Error(data.error);
```

```
}
```

```
    setAnalysisResult(data);

  } catch (error) {

    console.error('Analysis failed:', error);

    toast.error(

      error instanceof Error

        ? error.message

        : 'Failed to analyze image. Please try again.'

    );

    setAnalysisResult(null);

    setCurrentImageBase64(null);

  } finally {

    setIsAnalyzing(false);

  }

};
```

```
const handleSaveLog = async () => {

  if (!analysisResult) return;

  await addLog.mutateAsync({

    analysis: analysisResult,

    imageUrl: currentImageBase64 || undefined,

  });
```

```
  setAnalysisResult(null);

  setCurrentImageBase64(null);
```

```
};
```

```
const handleDiscardResult = () => {
```

```
  setAnalysisResult(null);
```

```
  setCurrentImageBase64(null);
```

```
};
```

```
return (
```

```
  <div className="min-h-screen bg-background">
```

```
    <Header />
```

```
    <main className="container px-4 py-6 max-w-lg mx-auto space-y-6">
```

```
      {/* Daily Stats */}
```

```
      <DailyStats todayCalories={todayCalories} />
```

```
      {/* Main Content Tabs */}
```

```
      <Tabs defaultValue="capture" className="w-full">
```

```
        <TabsList className="grid w-full grid-cols-2">
```

```
          <TabsTrigger value="capture" className="font-display font-semibold">
```

```
            <Camera className="h-4 w-4 mr-2" />
```

```
            Capture
```

```
          </TabsTrigger>
```

```
          <TabsTrigger value="history" className="font-display font-semibold">
```

```
            <History className="h-4 w-4 mr-2" />
```

```
            History
```

```
          </TabsTrigger>
```

```
</TabsList>
```

```
<TabsContent value="capture" className="mt-4 space-y-4">
```

```
{analysisResult ? (
```

```
<FoodAnalysisResult
```

```
  analysis={analysisResult}
```

```
  onSave={handleSaveLog}
```

```
  onDiscard={handleDiscardResult}
```

```
  isSaving={addLog.isPending}
```

```
/>
```

```
): (
```

```
<ImageCapture
```

```
  onImageCapture={handleImageCapture}
```

```
  isAnalyzing={isAnalyzing}
```

```
/>
```

```
)}  
</TabsContent>
```

```
<TabsContent value="history" className="mt-4">
```

```
{isLoading ? (
```

```
<div className="flex justify-center py-12">
```

```
  <div className="h-8 w-8 border-2 border-primary border-t-transparent rounded-full  
  animate-spin" />
```

```
</div>
```

```
): (
```

```
<MealHistory
```



```
logs={logs}
```

```
onDelete={(id) => deleteLog.mutate(id)}
```

```
isDeleting={deleteLog.isPending}
```

```
/>
```

```
}}
```

```
</TabsContent>
```

```
</Tabs>
```

```
</main>
```

```
</div>
```

```
);
```

```
}
```

```
import { useEffect } from 'react';
```

```
import { useNavigate } from 'react-router-dom';
```

```
import { useAuth } from '@/contexts/AuthContext';
```

```
import { LoadingSpinner } from '@/components/ui/LoadingSpinner';
```

```
import MainApp from '@/views/MainApp';
```

```
const Index = () => {
```

```
  const { user, loading } = useAuth();
```

```
  const navigate = useNavigate();
```

```
  useEffect(() => {
```

```
    if (!loading && !user) {
```

```
      navigate('/auth', { replace: true });
```

```
    }
```

```
  }, [user, loading, navigate]);
```

```
if (loading) {
```

```
  return (
```

```
    <div className="min-h-screen flex items-center justify-center bg-background">
```

```
      <div className="text-center">
```

```
        <LoadingSpinner size="lg" />
```

```
        <p className="text-muted-foreground mt-4 font-display">Loading...</p>
```

```
      </div>
```

```
    </div>
```

```
  );
```

```
}
```

```
if (!user) {
```

```
  return null;
```

```
}
```

```
return <MainApp />;
```

```
};
```

```
export default Index;
```

```
import { useLocation } from "react-router-dom";
```

```
import { useEffect } from "react";
```

```
const NotFound = () => {
```

```
  const location = useLocation();
```

```
useEffect(() => {

  console.error("404 Error: User attempted to access non-existent route:",
location.pathname);

}, [location.pathname]);


return (

  <div className="flex min-h-screen items-center justify-center bg-muted">

    <div className="text-center">

      <h1 className="mb-4 text-4xl font-bold">404</h1>

      <p className="mb-4 text-xl text-muted-foreground">Oops! Page not found</p>

      <a href="/" className="text-primary underline hover:text-primary/90">

        Return to Home

      </a>

    </div>

  </div>

);

};
```

```
export default NotFound;

export interface FoodItemMacros {

  carbs_g: number;

  protein_g: number;

  fat_g: number;

}
```

```
export interface FoodItem {
```

```
  name: string;

  portion_size?: string;

  estimated_weight_grams?: number;

  estimated_calories: number;

  macros: FoodItemMacros;

  freshness_score: number;
}
```

```
export interface FoodAnalysis {

  food_items: FoodItem[];

  total_calories: number;

  confidence: number;

  freshness_warning: string | null;

  notes?: string;
}
```

```
export interface FoodLog {

  id: string;

  user_id: string;

  image_url: string | null;

  food_name: string;

  portion_size: string | null;

  estimated_weight_grams: number | null;

  calories: number;

  protein_grams: number | null;

  carbs_grams: number | null;
}
```

```
fat_grams: number | null;

freshness_score: number | null;

freshness_status: 'fresh' | 'acceptable' | 'spoiled' | null;

confidence_score: number | null;

ai_analysis: FoodAnalysis | null;

logged_at: string;

created_at: string;

}

// Re-export food types

export * from './food';


// App Navigation Types

export type AppView =

  | 'HOME'

  | 'LOG'

  | 'INSIGHTS'

  | 'PROFILE';


export type MealType = 'Breakfast' | 'Lunch' | 'Dinner' | 'Snack';


export type FreshnessLevel = 'fresh' | 'acceptable' | 'spoiled';


// User Profile

export interface UserProfile {

  id: string;

  user_id: string;
```

```
display_name: string | null;  
  
email: string | null;  
  
avatar_url: string | null;  
  
}
```

```
// User Settings
```

```
export interface UserSettings {  
  
  id: string;  
  
  user_id: string;  
  
  calorie_goal: number;  
  
  is_premium: boolean;  
  
  premium_expires_at: string | null;  
  
  daily_scan_count: number;  
  
  last_scan_date: string | null;  
  
}
```

```
// Subscription Plan
```

```
export interface SubscriptionPlan {  
  
  id: string;  
  
  name: string;  
  
  price: number;  
  
  currency: string;  
  
  features: string[];  
  
}
```

```
// Analysis Result Types
```

```
export interface AnalysisItem {  
  
  name: string;  
  
  totalCalories: number;  
  
  estimatedWeightGrams: number;  
  
  caloriesPer100g: number;  
  
  confidence: number;  
  
  freshness: FreshnessLevel;  
  
  reasoning?: string;  
  
}
```

```
export interface AnalysisResult {  
  
  items: AnalysisItem[];  
  
  totalCalories: number;  
  
  summary: string;  
  
}
```

```
import React, { useState } from 'react';  
  
import { ChevronLeft, ChevronRight, Plus, Coffee, Sun, Moon, Cookie, Flame, Target } from  
'lucide-react';  
  
import { Logo } from '@components/Logo';  
  
import { CircularProgress } from '@components/CircularProgress';  
  
import { AddFoodModal } from '@components/AddFoodModal';  
  
import { cn } from '@lib/utils';  
  
import { MealType } from '@types';  
  
import { useFoodLogs } from '@hooks/useFoodLogs';  
  
import { useAnalyzeFood } from '@hooks/useAnalyzeFood';  
  
import { useUserSettings } from '@hooks/useUserSettings';
```

```
import { FoodAnalysis } from '@types/food';
```

```
import { format, addDays, subDays, isToday, isSameDay } from 'date-fns';
```

```
interface HomeViewProps {
```

```
  onAddFood?: (mealType: MealType) => void;
```

```
}
```

```
const mealConfig: Record<MealType, { icon: React.ElementType; targetPercent: number; gradient: string; time: string }> = {
```

```
  Breakfast: { icon: Coffee, targetPercent: 0.25, gradient: 'from-amber-500/20 to-orange-500/10', time: '6am - 11am' },
```

```
  Lunch: { icon: Sun, targetPercent: 0.35, gradient: 'from-yellow-500/20 to-amber-500/10', time: '11am - 3pm' },
```

```
  Dinner: { icon: Moon, targetPercent: 0.30, gradient: 'from-indigo-500/20 to-purple-500/10', time: '6pm - 9pm' },
```

```
  Snack: { icon: Cookie, targetPercent: 0.10, gradient: 'from-pink-500/20 to-rose-500/10', time: 'Anytime' },
```

```
};
```

```
export const HomeView: React.FC<HomeViewProps> = () => {
```

```
  const [currentDate, setCurrentDate] = useState(new Date());
```

```
  const [selectedMeal, setSelectedMeal] = useState<MealType | null>(null);
```

```
  const { logs, addLog } = useFoodLogs();
```

```
  const { analyzeFood, isAnalyzing } = useAnalyzeFood();
```

```
  const { calorieGoal } = useUserSettings();
```

```
  const dayLogs = logs.filter(log => isSameDay(new Date(log.logged_at), currentDate));
```



```
const dayCalories = dayLogs.reduce((sum, log) => sum + (log.calories || 0), 0);
```

```
const caloriesLeft = Math.max(0, calorieGoal - dayCalories);
```

```
const progress = Math.min((dayCalories / calorieGoal) * 100, 100);
```

```
const isOverGoal = dayCalories > calorieGoal;
```

```
const macros = dayLogs.reduce(
```

```
  (acc, log) => ({
```

```
    carbs: acc.carbs + (log.carbs_grams || 0),
```

```
    protein: acc.protein + (log.protein_grams || 0),
```

```
    fat: acc.fat + (log.fat_grams || 0),
```

```
  }),
```

```
  { carbs: 0, protein: 0, fat: 0 }
```

```
);
```

```
// Macro goals (example - could be user-configurable)
```

```
const macroGoals = { carbs: 250, protein: 120, fat: 70 };
```

```
const getMealType = (date: Date): MealType => {
```

```
  const hour = date.getHours();
```

```
  if (hour < 11) return 'Breakfast';
```

```
  if (hour < 15) return 'Lunch';
```

```
  if (hour < 20) return 'Dinner';
```

```
  return 'Snack';
```

```
};
```

```
const mealData = (['Breakfast', 'Lunch', 'Dinner', 'Snack'] as MealType[]).map(type => {
```

```
const config = mealConfig[type];
```

```
const mealLogs = dayLogs.filter(log => getMealType(new Date(log.logged_at)) === type);
```

```
const consumed = mealLogs.reduce((sum, log) => sum + (log.calories || 0), 0);
```

```
const target = Math.round(calorieGoal * config.targetPercent);
```

```
return { type, ...config, target, consumed, logs: mealLogs };
```

```
});
```

```
const handlePrevDay = () => setCurrentDate(prev => subDays(prev, 1));
```

```
const handleNextDay = () => setCurrentDate(prev => addDays(prev, 1));
```

```
const formatDateLabel = (date: Date) => {
```

```
  if (isToday(date)) return 'Today';
```

```
  return format(date, 'EEE, MMM d');
```

```
};
```

```
const handleAnalyze = async (imageBase64: string) => await analyzeFood(imageBase64);
```

```
const handleSave = (analysis: FoodAnalysis, imageUrl?: string) => addLog.mutate({ analysis, imageUrl });
```

```
// Motivational message based on progress
```

```
const getMotivationalMessage = () => {
```

```
  if (dayCalories === 0) return "Let's start tracking! 📸";
```

```
  if (progress < 50) return "Great start, keep going! 💪";
```

```
  if (progress < 80) return "You're doing amazing! 🔥";
```

```
  if (progress <= 100) return "Almost at your goal! 🎯";
```

```
  return "Goal reached - nice work! ⭐";
```

```
};
```

```
return (
```

```
<div className="min-h-screen bg-background pb-28">
```

```
  { /* Header */ }
```

```
  <header className="flex items-center justify-between px-5 pt-4 pb-2 safe-top">
```

```
    <Logo size="sm" showText />
```

```
    <div className="flex items-center gap-2 px-3 py-1.5 bg-primary/10 rounded-full">
```

```
      <Target size={14} className="text-primary" />
```

```
      <span className="text-xs font-semibold text-primary">{calorieGoal.toLocaleString()}  
kcal</span>
```

```
    </div>
```

```
  </header>
```

```
  { /* Date Navigation */ }
```

```
  <div className="flex items-center justify-center gap-3 py-3">
```

```
    <button onClick={handlePrevDay} className="p-2.5 hover:bg-secondary rounded-full  
touch-target transition-colors">
```

```
      <ChevronLeft size={20} className="text-muted-foreground" />
```

```
    </button>
```

```
    <div className="px-5 py-2 bg-secondary rounded-full min-w-[130px] text-center">
```

```
      <span className="text-sm font-bold text-foreground">{formatDateLabel(currentDate)}  
</span>
```

```
    </div>
```

```
    <button onClick={handleNextDay} className="p-2.5 hover:bg-secondary rounded-full  
touch-target transition-colors">
```

```
      <ChevronRight size={20} className="text-muted-foreground" />
```

```
</button>
```

```
</div>
```

```
{/* Hero Calorie Ring */}
```

```
<div className="flex flex-col items-center py-6 px-4">
```

```
<div className="relative">
```

```
<CircularProgress
```

```
value={dayCalories}
```

```
max={calorieGoal}
```

```
size="xl"
```

```
color={isOverGoal ? 'calories' : 'primary'}
```

```
strokeWidth={16}
```

```
>
```

```
<div className="text-center">
```

```
<span className={cn(
```

```
'text-4xl font-display font-bold',
```

```
isOverGoal ? 'text-destructive' : 'text-foreground'
```

```
))>
```

```
{caloriesLeft}
```

```
</span>
```

```
<p className="text-xs text-muted-foreground mt-1">kcal remaining</p>
```

```
</div>
```

```
</CircularProgress>
```

```
{/* Eaten badge */}
```

```
<div className="absolute -right-2 top-1/2 -translate-y-1/2 flex flex-col items-center bg-card p-3 rounded-2xl border border-border shadow-card">
```

```
<Flame className="h-5 w-5 text-primary mb-1" />
```

```
<span className="text-lg font-bold text-foreground">{Math.round(dayCalories)}</span>
```

```
<span className="text-[10px] text-muted-foreground uppercase tracking-wide">eaten</span>
```

```
</div>
```

```
</div>
```

```
{/* Motivational message */}
```

```
<p className="text-sm text-muted-foreground mt-4 font-medium">{getMotivationalMessage()}</p>
```

```
</div>
```

```
{/* Macros Grid */}
```

```
<div className="grid grid-cols-3 gap-3 px-5 py-2">
```

```
{[
```

```
{ label: 'Carbs', value: macros.carbs, goal: macroGoals.carbs, icon: '🍞', color: 'bg-carbs' },
```

```
{ label: 'Protein', value: macros.protein, goal: macroGoals.protein, icon: '🥩', color: 'bg-protein' },
```

```
{ label: 'Fat', value: macros.fat, goal: macroGoals.fat, icon: '👉', color: 'bg-fat' },
```

```
].map((macro) => {
```

```
  const percent = Math.min((macro.value / macro.goal) * 100, 100);
```

```
  return (
```

```
    <div key={macro.label} className="bg-card rounded-2xl p-4 text-center border border-border">
```

```
      <span className="text-xl mb-2 block">{macro.icon}</span>
```

```
<div className="flex items-baseline justify-center gap-0.5">
```

```
    <span className="text-xl font-bold text-foreground">{Math.round(macro.value)}</span>
```

```
    <span className="text-xs text-muted-foreground">/{macro.goal}g</span>
```

```
</div>
```

```
<p className="text-xs text-muted-foreground mt-1">{macro.label}</p>
```

```
{/* Mini progress bar */}
```

```
<div className="h-1 bg-secondary rounded-full mt-2 overflow-hidden">
```

```
  <div
```

```
    className={cn("h-full rounded-full transition-all duration-500", macro.color)}
```

```
    style={{ width: `${percent}%` }}
```

```
  />
```

```
</div>
```

```
</div>
```

```
);
```

```
}}}
```

```
</div>
```

```
{/* Meals Section */}
```

```
<div className="px-5 py-4 space-y-3">
```

```
  <div className="flex items-center justify-between">
```

```
    <h3 className="text-sm font-bold text-foreground uppercase tracking-wider">Meals</h3>
```

```
    {dayLogs.length > 0 && (
```

```
      <span className="text-xs text-muted-foreground">{dayLogs.length} logged</span>
```

```
    )}
```

```
</div>
```

```
{mealData.map((meal) => {
```

```
  const Icon = meal.icon;
```

```
  const hasFood = meal.consumed > 0;
```

```
  const percent = Math.min((meal.consumed / meal.target) * 100, 100);
```

```
  return (
```

```
    <div key={meal.type} className="space-y-2">
```

```
      <div className={cn(
```

```
        'bg-card rounded-2xl p-4 border border-border hover:border-primary/40 transition-all',
```

```
        hasFood && 'bg-gradient-to-r ' + meal.gradient
```

```
      )}>
```

```
      <div className="flex items-center justify-between">
```

```
        <div className="flex items-center gap-3">
```

```
          <div className={cn(
```

```
            'w-12 h-12 rounded-xl flex items-center justify-center transition-colors',
```

```
            hasFood ? 'bg-primary/15' : 'bg-secondary'
```

```
          )}>
```

```
            <Icon size={22} className={hasFood ? 'text-primary' : 'text-muted-foreground'} />
```

```
          </div>
```

```
        <div>
```

```
          <p className="font-bold text-foreground">{meal.type}</p>
```

```
          <p className="text-xs text-muted-foreground">{meal.time}</p>
```

```
        </div>
```

```
      </div>
```

```
<div className="flex items-center gap-3">
```

```
<div className="text-right">
```

```
<p className={cn(
```

```
'text-lg font-bold',
```

```
hasFood ? 'text-primary' : 'text-muted-foreground'
```

```
)}>
```

```
{Math.round(meal.consumed)}
```

```
</p>
```

```
<p className="text-xs text-muted-foreground">/ {meal.target} kcal</p>
```

```
</div>
```

```
<button
```

```
onClick={() => setSelectedMeal(meal.type)}
```

```
className={cn(
```

```
'p-3 rounded-xl transition-all touch-target',
```

```
hasFood
```

```
? 'bg-primary/20 hover:bg-primary/30'
```

```
: 'bg-primary hover:bg-primary/90'
```

```
)}>
```

```
>
```

```
<Plus size={18} className={hasFood ? 'text-primary' : 'text-primary-foreground'}
```

```
/>
```

```
</button>
```

```
</div>
```

```
</div>
```

```
{/* Progress bar for meal */}
```



```
{hasFood && (
```

```
<div className="h-1 bg-secondary/50 rounded-full mt-3 overflow-hidden">
```

```
<div
```

```
  className="h-full bg-primary rounded-full transition-all duration-500"
```

```
  style={{ width: `${percent}%` }}
```

```
</div>
```

```
)}
```

```
</div>
```

```
  {/* Logged items for this meal */}
```

```
{meal.logs.length > 0 && (
```

```
<div className="ml-4 space-y-2">
```

```
{meal.logs.map((log) => (
```

```
  <div key={log.id} className="bg-secondary/30 rounded-xl p-3 flex items-center justify-between animate-fade-in">
```

```
    <div className="flex items-center gap-3">
```

```
      {log.image_url && (
```

```
        <img src={log.image_url} alt="" className="w-10 h-10 rounded-lg object-cover"
```

```
      )}
```

```
    <div>
```

```
      <p className="text-sm font-medium capitalize text-foreground">{log.food_name}</p>
```

```
      <p className="text-xs text-muted-foreground">{format(new Date(log.logged_at), 'h:mm a')}</p>
```

```
    </div>
```

```
</div>
```

```
<div className="flex items-center gap-1.5 px-2.5 py-1 rounded-full bg-  
primary/10">
```

```
<Flame className="h-3 w-3 text-primary" />
```

```
<span className="text-sm font-bold text-primary">{Math.round(log.calories)}  
</span>
```

```
</div>
```

```
</div>
```

```
))}
```

```
</div>
```

```
)}  

```

```
</div>
```

```
);
```

```
}}}
```

```
</div>
```

```
<AddFoodModal
```

```
  isOpen={!selectedMeal}
```

```
  onClose={() => setSelectedMeal(null)}
```

```
  mealType={selectedMeal || 'Snack'}
```

```
  onAnalyze={handleAnalyze}
```

```
  onSave={handleSave}
```

```
  isAnalyzing={isAnalyzing}
```

```
  isSaving={addLog.isPending}
```

```
</div>
```

```
);
```

```
};
```

```
export default HomeView;
```

```
import React, { useState, useMemo } from 'react';
```

```
import { Lock, TrendingUp, Flame, Calendar, ChevronLeft, ChevronRight } from 'lucide-react';
```

```
import { Button } from '@components/ui/button';
```

```
import { useFoodLogs } from '@hooks/useFoodLogs';
```

```
import { useUserSettings } from '@hooks/useUserSettings';
```

```
import { PremiumPaywall } from '@components/PremiumPaywall';
```

```
import { format, startOfWeek, endOfWeek, eachDayOfInterval, isSameDay, subWeeks, addWeeks } from 'date-fns';
```

```
import { cn } from '@lib/utils';
```

```
export const InsightsView: React.FC = () => {
```

```
  const { logs } = useFoodLogs();
```

```
  const { isPremium, calorieGoal, upgradeToPremium } = useUserSettings();
```

```
  const [showPaywall, setShowPaywall] = useState(false);
```

```
  const [currentWeek, setCurrentWeek] = useState(new Date());
```

```
  const weekStart = startOfWeek(currentWeek, { weekStartsOn: 1 });
```

```
  const weekEnd = endOfWeek(currentWeek, { weekStartsOn: 1 });
```

```
  const weekDays = eachDayOfInterval({ start: weekStart, end: weekEnd });
```

```
  const weekData = useMemo(() => {
```

```
    return weekDays.map(day => {
```

```
      const dayLogs = logs.filter(log => isSameDay(new Date(log.logged_at), day));
```

```
const calories = dayLogs.reduce((sum, log) => sum + (log.calories || 0), 0);
```

```
const protein = dayLogs.reduce((sum, log) => sum + (log.protein_grams || 0), 0);
```

```
const carbs = dayLogs.reduce((sum, log) => sum + (log.carbs_grams || 0), 0);
```

```
const fat = dayLogs.reduce((sum, log) => sum + (log.fat_grams || 0), 0);
```

```
const meals = dayLogs.length;
```

```
return { day, calories, protein, carbs, fat, meals };
```

```
});
```

```
}, [logs, weekDays]);
```

```
const weekStats = useMemo(() => {
```

```
  const totalCalories = weekData.reduce((sum, d) => sum + d.calories, 0);
```

```
  const totalMeals = weekData.reduce((sum, d) => sum + d.meals, 0);
```

```
  const daysWithLogs = weekData.filter(d => d.meals > 0).length;
```

```
  const avgCalories = daysWithLogs > 0 ? Math.round(totalCalories / daysWithLogs) : 0;
```

```
  const daysOnTarget = weekData.filter(d => d.calories > 0 && d.calories <=
  calorieGoal).length;
```

```
  return { totalCalories, totalMeals, avgCalories, daysOnTarget, daysWithLogs };
```

```
}, [weekData, calorieGoal]);
```

```
const maxCalories = Math.max(...weekData.map(d => d.calories), calorieGoal);
```

```
const handlePrevWeek = () => setCurrentWeek(prev => subWeeks(prev, 1));
```

```
const handleNextWeek = () => setCurrentWeek(prev => addWeeks(prev, 1));
```

```
// If not premium, show locked state
```

```
if (!isPremium) {
```

```
return (
```

```
<div className="min-h-screen bg-background pb-28">
```

```
<header className="px-5 pt-6 pb-4 safe-top">
```

```
<h1 className="font-display font-bold text-xl text-foreground">Insights</h1>
```

```
</header>
```

```
<div className="px-5 py-12">
```

```
<div className="text-center space-y-6">
```

```
<div className="w-20 h-20 mx-auto rounded-full bg-secondary flex items-center justify-center">
```

```
<Lock className="h-10 w-10 text-muted-foreground" />
```

```
</div>
```

```
<div>
```

```
<h2 className="font-display font-bold text-xl text-foreground mb-2">
```

```
Weekly Insights
```

```
</h2>
```

```
<p className="text-muted-foreground text-sm max-w-[280px] mx-auto">
```

```
See your calorie trends, macro breakdowns, and progress charts with Premium
```

```
</p>
```

```
</div>
```

```
<Button
```

```
onClick={() => setShowPaywall(true)}
```

```
className="gradient-brand text-primary-foreground font-bold px-8 py-6 rounded-2xl shadow-brand"
```

```
>
```

```
Unlock Insights — ₹49/mo
```

```
</Button>
```

```
</div>
```

```
{/* Blurred preview */}
```

```
<div className="mt-8 relative">
```

```
  <div className="absolute inset-0 bg-background/60 backdrop-blur-md z-10 rounded-2xl" />
```

```
  <div className="bg-card rounded-2xl p-4 border border-border opacity-50">
```

```
    <div className="flex justify-between items-end h-32">
```

```
      {[40, 70, 55, 85, 60, 45, 75].map((h, i) => (
```

```
        <div key={i} className="w-8 bg-primary/30 rounded-t-lg" style={{ height: `${h}%` }} />
```

```
      )))
```

```
    </div>
```

```
  </div>
```

```
</div>
```

```
</div>
```

```
<PremiumPaywall
```

```
  isOpen={showPaywall}
```

```
  onClose={() => setShowPaywall(false)}
```

```
  onUpgrade={() => {
```

```
    upgradeToPremium.mutate();
```

```
    setShowPaywall(false);
```

```
  }}
```

```
  isUpgrading={upgradeToPremium.isPending}
```

```
  trigger="insights"
```

```
/>
```

```
</div>
```

```
);
```

```
}
```

```
return (
```

```
<div className="min-h-screen bg-background pb-28">
```

```
<header className="px-5 pt-6 pb-4 safe-top">
```

```
<h1 className="font-display font-bold text-xl text-foreground">Insights</h1>
```

```
</header>
```

```
<div className="px-5 space-y-4">
```

```
{/* Week Navigator */}
```

```
<div className="flex items-center justify-between">
```

```
<button onClick={handlePrevWeek} className="p-2 hover:bg-secondary rounded-full touch-target">
```

```
<ChevronLeft size={20} className="text-muted-foreground" />
```

```
</button>
```

```
<div className="flex items-center gap-2">
```

```
<Calendar size={16} className="text-primary" />
```

```
<span className="text-sm font-semibold text-foreground">
```

```
{format(weekStart, 'MMM d')} - {format(weekEnd, 'MMM d')}
```

```
</span>
```

```
</div>
```

```
<button onClick={handleNextWeek} className="p-2 hover:bg-secondary rounded-full touch-target">
```

```
<ChevronRight size={20} className="text-muted-foreground" />
```

```
</button>
```

```
</div>
```

```
{/* Stats Cards */}
```

```
<div className="grid grid-cols-2 gap-3">
```

```
  <div className="bg-card rounded-2xl p-4 border border-border">
```

```
    <div className="flex items-center gap-2 mb-2">
```

```
      <Flame className="h-4 w-4 text-primary" />
```

```
      <span className="text-xs text-muted-foreground">Avg/Day</span>
```

```
    </div>
```

```
    <p className="text-2xl font-bold text-foreground">{weekStats.avgCalories}</p>
```

```
    <p className="text-xs text-muted-foreground">kcal</p>
```

```
  </div>
```

```
<div className="bg-card rounded-2xl p-4 border border-border">
```

```
  <div className="flex items-center gap-2 mb-2">
```

```
    <TrendingUp className="h-4 w-4 text-primary" />
```

```
    <span className="text-xs text-muted-foreground">On Target</span>
```

```
  </div>
```

```
  <p className="text-2xl font-bold text-foreground">{weekStats.daysOnTarget}/7</p>
```

```
  <p className="text-xs text-muted-foreground">days</p>
```

```
</div>
```

```
</div>
```

```
{/* Weekly Chart */}
```

```
<div className="bg-card rounded-2xl p-5 border border-border">
```

```
  <h3 className="text-sm font-semibold text-foreground mb-4">Calorie Trend</h3>
```



```
{/* Goal line indicator */}
```

```
<div className="flex items-center gap-2 mb-3">
```

```
<div className="h-px flex-1 border-t border-dashed border-primary/40" />
```

```
<span className="text-xs text-primary font-medium">{calorieGoal} goal</span>
```

```
</div>
```

```
{/* Bar chart */}
```

```
<div className="flex items-end justify-between h-36 gap-2">
```

```
{weekData.map((data, i) => {
```

```
  const height = maxCalories > 0 ? (data.calories / maxCalories) * 100 : 0;
```

```
  const isOverGoal = data.calories > calorieGoal;
```

```
  const isToday = isSameDay(data.day, new Date());
```

```
  return (
```

```
    <div key={i} className="flex-1 flex flex-col items-center gap-2">
```

```
      <div className="w-full h-28 flex items-end justify-center">
```

```
        {data.calories > 0 ? (
```

```
          <div
```

```
            className={cn(
```

```
              "w-full max-w-8 rounded-t-lg transition-all duration-500",
```

```
              isOverGoal ? "bg-destructive/80" : "bg-primary/80"
```

```
            )}
```

```
            style={{ height: `${height}%` }}
```

```
          />
```

```
        ) : (
```

```
          <div className="w-full max-w-8 h-1 bg-secondary rounded-full" />
```

```
    )}
```

```
</div>
```

```
<span className={cn(
```

```
  "text-xs font-medium",
```

```
  isToday ? "text-primary" : "text-muted-foreground"
```

```
)}>
```

```
{format(data.day, 'EEE').slice(0, 2)}
```

```
</span>
```

```
</div>
```

```
);
```

```
  )}
```

```
</div>
```

```
</div>
```

```
{/* Macro Breakdown */}
```

```
<div className="bg-card rounded-2xl p-5 border border-border">
```

```
<h3 className="text-sm font-semibold text-foreground mb-4">Weekly Macros</h3>
```

```
<div className="grid grid-cols-3 gap-4 text-center">
```

```
<div>
```

```
<span className="text-2xl mb-1 block">🍞</span>
```

```
<p className="text-lg font-bold text-foreground">
```

```
{Math.round(weekData.reduce((sum, d) => sum + d.carbs, 0))}g
```

```
</p>
```

```
<p className="text-xs text-muted-foreground">Carbs</p>
```

```
</div>
```

```
<div>
```

```
<span className="text-2xl mb-1 block">🍖</span>
```

```
<p className="text-lg font-bold text-foreground">
```

```
{Math.round(weekData.reduce((sum, d) => sum + d.protein, 0))}g
```

```
</p>
```

```
<p className="text-xs text-muted-foreground">Protein</p>
```

```
</div>
```

```
<div>
```

```
<span className="text-2xl mb-1 block">🥑</span>
```

```
<p className="text-lg font-bold text-foreground">
```

```
{Math.round(weekData.reduce((sum, d) => sum + d.fat, 0))}g
```

```
</p>
```

```
<p className="text-xs text-muted-foreground">Fat</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
{/* Week Summary */}
```

```
<div className="bg-secondary/50 rounded-2xl p-4 text-center">
```

```
<p className="text-sm text-muted-foreground">
```

```
You logged <span className="font-bold text-foreground">{weekStats.totalMeals}  
meals</span> this week,
```

```
totaling <span className="font-bold text-primary">  
{weekStats.totalCalories.toLocaleString()} kcal</span>
```

```
</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
);
```

```
};
```

```
export default InsightsView;
```

```
import React, { useState, useMemo } from 'react';
```

```
import { ChevronLeft, ChevronRight, Clock, Flame, Calendar, Trash2, TrendingUp } from 'lucide-react';
```

```
import { Logo } from '@components/Logo';
```

```
import { Button } from '@components/ui/button';
```

```
import { useFoodLogs } from '@hooks/useFoodLogs';
```

```
import { format, startOfWeek, endOfWeek, eachDayOfInterval, isSameDay, subWeeks, addWeeks, isToday } from 'date-fns';
```

```
import { cn } from '@lib/utils';
```

```
export const LogView: React.FC = () => {
```

```
  const [currentWeek, setCurrentWeek] = useState(new Date());
```

```
  const [selectedDate, setSelectedDate] = useState(new Date());
```

```
  const { logs, deleteLog, isLoading } = useFoodLogs();
```

```
  const weekStart = startOfWeek(currentWeek, { weekStartsOn: 1 });
```

```
  const weekEnd = endOfWeek(currentWeek, { weekStartsOn: 1 });
```

```
  const weekDays = eachDayOfInterval({ start: weekStart, end: weekEnd });
```

```
  const selectedDayLogs = useMemo(() =>
```

```
    logs.filter(log => isSameDay(new Date(log.logged_at), selectedDate))
```

```
    .sort((a, b) => new Date(b.logged_at).getTime() - new Date(a.logged_at).getTime()),
```

```
[logs, selectedDate]
```

```
);
```

```
const weekStats = useMemo(() => {
```

```
  const weekLogs = logs.filter(log => {
```

```
    const logDate = new Date(log.logged_at);
```

```
    return logDate >= weekStart && logDate <= weekEnd;
```

```
  });
```

```
  const totalCalories = weekLogs.reduce((sum, log) => sum + (log.calories || 0), 0);
```

```
  const avgCalories = weekLogs.length > 0 ? Math.round(totalCalories / 7) : 0;
```

```
  return { totalMeals: weekLogs.length, totalCalories, avgCalories };
```

```
}, [logs, weekStart, weekEnd]);
```

```
const getDayCalories = (date: Date) => {
```

```
  return logs
```

```
    .filter(log => isSameDay(new Date(log.logged_at), date))
```

```
    .reduce((sum, log) => sum + (log.calories || 0), 0);
```

```
};
```

```
const handlePrevWeek = () => setCurrentWeek(prev => subWeeks(prev, 1));
```

```
const handleNextWeek = () => setCurrentWeek(prev => addWeeks(prev, 1));
```

```
const handleDeleteLog = (logId: string) => {
```

```
  deleteLog.mutate(logId);
```

```
};
```

```
return (
```

```
<div className="min-h-screen bg-background pb-28">
```

```
{/* Header */}
```

```
<header className="flex items-center justify-between px-5 pt-4 pb-3 safe-top">
```

```
<Logo size="sm" />
```

```
<h1 className="font-display font-bold text-lg text-foreground">Meal Log</h1>
```

```
<div className="w-8" />
```

```
</header>
```

```
{/* Week Navigator */}
```

```
<div className="px-5 py-3">
```

```
<div className="flex items-center justify-between mb-4">
```

```
<button
```

```
  onClick={handlePrevWeek}
```

```
  className="p-2 hover:bg-secondary rounded-full touch-target"
```

```
>
```

```
<ChevronLeft size={20} className="text-muted-foreground" />
```

```
</button>
```

```
<div className="flex items-center gap-2">
```

```
<Calendar size={16} className="text-primary" />
```

```
<span className="text-sm font-semibold text-foreground">
```

```
  {format(weekStart, 'MMM d')} - {format(weekEnd, 'MMM d, yyyy')}
```

```
</span>
```

```
</div>
```

```
<button
```

```
  onClick={handleNextWeek}
```

```
className="p-2 hover:bg-secondary rounded-full touch-target"
```

```
>
```

```
<ChevronRight size={20} className="text-muted-foreground" />
```

```
</button>
```

```
</div>
```

```
{/* Week Days */}
```

```
<div className="grid grid-cols-7 gap-1">
```

```
{weekDays.map((day) => {
```

```
  const isSelected = isSameDay(day, selectedDate);
```

```
  const isTodayDate = isToday(day);
```

```
  const dayCalories = getDayCalories(day);
```

```
  const hasLogs = dayCalories > 0;
```

```
  return (
```

```
    <button
```

```
      key={day.toISOString()}
```

```
      onClick={() => setSelectedDate(day)}
```

```
      className={cn(
```

```
        'flex flex-col items-center py-2 px-1 rounded-xl transition-all touch-target',
```

```
        isSelected
```

```
        ? 'bg-primary text-primary-foreground'
```

```
        : 'hover:bg-secondary',
```

```
        isTodayDate && !isSelected && 'ring-2 ring-primary/30'
```

```
      )}
```

```
>
```

```
<span className={cn(
```

```
'text-xs font-medium',
```

```
isSelected ? 'text-primary-foreground/80' : 'text-muted-foreground'
```

```
))>
```

```
{format(day, 'EEE').slice(0, 2)}
```

```
</span>
```

```
<span className={cn(
```

```
'text-lg font-bold',
```

```
isSelected ? 'text-primary-foreground' : 'text-foreground'
```

```
))>
```

```
{format(day, 'd')}
```

```
</span>
```

```
{hasLogs && (
```

```
<div className={cn(
```

```
'w-1.5 h-1.5 rounded-full mt-1',
```

```
isSelected ? 'bg-primary-foreground' : 'bg-primary'
```

```
)) />
```

```
}}
```

```
</button>
```

```
);
```

```
}}}
```

```
</div>
```

```
</div>
```

```
{/* Week Summary */}
```

```
<div className="px-5 py-3">
```



```
<div className="bg-card rounded-2xl p-4 border border-border">
```

```
<div className="flex items-center gap-2 mb-3">
```

```
<TrendingUp size={16} className="text-primary" />
```

```
<span className="text-sm font-semibold text-foreground">Week Summary</span>
```

```
</div>
```

```
<div className="grid grid-cols-3 gap-4">
```

```
<div>
```

```
<p className="text-2xl font-bold text-foreground">{weekStats.totalMeals}</p>
```

```
<p className="text-xs text-muted-foreground">meals logged</p>
```

```
</div>
```

```
<div>
```

```
<p className="text-2xl font-bold text-foreground">{weekStats.totalCalories.toLocaleString()}</p>
```

```
<p className="text-xs text-muted-foreground">total kcal</p>
```

```
</div>
```

```
<div>
```

```
<p className="text-2xl font-bold text-primary">{weekStats.avgCalories.toLocaleString()}</p>
```

```
<p className="text-xs text-muted-foreground">avg/day</p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
{/* Selected Day Header */}
```

```
<div className="px-5 py-2">
```

```
<div className="flex items-center justify-between">
```

```
<h2 className="font-semibold text-foreground">
```

```
{isToday(selectedDate) ? 'Today' : format(selectedDate, 'EEEE, MMM d')}
```

```
</h2>
```

```
<span className="text-sm text-primary font-medium">
```

```
{Math.round(getDayCalories(selectedDate))} kcal
```

```
</span>
```

```
</div>
```

```
</div>
```

```
{/* Meals List */}
```

```
<div className="px-5 py-2 space-y-3">
```

```
{isLoading ? (
```

```
<div className="text-center py-12">
```

```
<div className="animate-pulse">
```

```
<div className="h-20 bg-secondary rounded-2xl mb-3" />
```

```
<div className="h-20 bg-secondary rounded-2xl mb-3" />
```

```
<div className="h-20 bg-secondary rounded-2xl" />
```

```
</div>
```

```
</div>
```

```
) : selectedDayLogs.length === 0 ? (
```

```
<div className="text-center py-16">
```

```
<div className="w-16 h-16 mx-auto rounded-full bg-secondary flex items-center justify-center mb-4">
```

```
<Clock className="h-8 w-8 text-muted-foreground" />
```

```
</div>
```

```
<h3 className="font-display font-semibold text-foreground mb-2">No meals logged</h3>
```

```
<p className="text-sm text-muted-foreground mb-4">
```

```
Tap the + button to scan your first meal
```

```
</p>
```

```
</div>
```

```
): (
```

```
selectedDayLogs.map((log) => (
```

```
<div
```

```
key={log.id}
```

```
className="bg-card rounded-2xl p-4 border border-border hover:border-primary/30  
transition-colors animate-fade-in"
```

```
>
```

```
<div className="flex gap-4">
```

```
{log.image_url && (
```

```
<img
```

```
src={log.image_url}
```

```
alt={log.food_name}
```

```
className="w-16 h-16 rounded-xl object-cover flex-shrink-0"
```

```
/>
```

```
))}
```

```
<div className="flex-1 min-w-0">
```

```
<div className="flex justify-between items-start gap-2">
```

```
<div className="min-w-0">
```

```
<h4 className="font-semibold text-foreground truncate capitalize">
```

```
{log.food_name}
```

```
</h4>
```

```
<div className="flex items-center gap-2 text-xs text-muted-foreground mt-1">
```

```
<Clock className="h-3 w-3" />
```

```
{format(new Date(log.logged_at), 'h:mm a')}
```

```
{log.portion_size && (
```

```
<span className="text-muted-foreground"> {log.portion_size}</span>
```

```
)}
```

```
</div>
```

```
</div>
```

```
<Button
```

```
onClick={() => handleDeleteLog(log.id)}
```

```
disabled={deleteLog.isPending}
```

```
variant="ghost"
```

```
size="icon"
```

```
className="h-8 w-8 text-muted-foreground hover:text-destructive flex-shrink-0"
```

```
>
```

```
<Trash2 className="h-4 w-4" />
```

```
</Button>
```

```
</div>
```

```
<div className="flex items-center gap-3 mt-3">
```

```
<div className="flex items-center gap-1.5 px-2.5 py-1 rounded-full bg-primary/10">
```

```
<Flame className="h-3.5 w-3.5 text-primary" />
```

```
<span className="text-sm font-bold text-primary">
```

```
{Math.round(log.calories)} kcal
```

```
</span>
```

```
</div>
```

```
{log.freshness_status && (  
  <span className={cn(  
    'px-2 py-1 rounded-full text-xs font-medium capitalize',  
    log.freshness_status === 'fresh' && 'bg-success/10 text-success',  
    log.freshness_status === 'acceptable' && 'bg-warning/10 text-warning',  
    log.freshness_status === 'spoiled' && 'bg-destructive/10 text-destructive'  
  )}>  
    {log.freshness_status}  
  </span>  
)}  
</div>
```

```
{/* Macros */}
```

```
<div className="flex gap-4 mt-2 text-xs text-muted-foreground">
```

```
  {log.protein_grams != null && (  
    <span>🥩 {Math.round(log.protein_grams)}g</span>  
  )}
```

```
  {log.carbs_grams != null && (  
    <span>🍞 {Math.round(log.carbs_grams)}g</span>  
  )}
```

```
  {log.fat_grams != null && (  
    <span>🧈 {Math.round(log.fat_grams)}g</span>  
  )}
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
))
```

```
}}
```

```
</div>
```

```
</div>
```

```
);
```

```
};
```

```
export default LogView;
```

```
import React, { useState } from 'react';
```

```
import { BottomNav } from '@components/BottomNav';
```

```
import { HomeView } from '@views/HomeView';
```

```
import { LogView } from '@views/LogView';
```

```
import { InsightsView } from '@views/InsightsView';
```

```
import { ProfileView } from '@views/ProfileView';
```

```
import { AddFoodModal } from '@components/AddFoodModal';
```

```
import { AppView, MealType } from '@types';
```

```
import { useAuth } from '@contexts/AuthContext';
```

```
import { useFoodLogs } from '@hooks/useFoodLogs';
```

```
import { useAnalyzeFood } from '@hooks/useAnalyzeFood';
```

```
import { useUserSettings } from '@hooks/useUserSettings';
```

```
import { FoodAnalysis } from '@types/food';
```

```
import { PremiumPaywall } from '@components/PremiumPaywall';
```

```
export const MainApp: React.FC = () => {
```

```
  const { signOut } = useAuth();
```

```
const [currentView, setCurrentView] = useState<AppView>('HOME');
```

```
const [showScanModal, setShowScanModal] = useState(false);
```

```
const [showScanLimitPaywall, setShowScanLimitPaywall] = useState(false);
```

```
const { addLog } = useFoodLogs();
```

```
const { analyzeFood, isAnalyzing } = useAnalyzeFood();
```

```
const { canScan, scansRemaining, isPremium, incrementScanCount, upgradeToPremium } = useUserSettings();
```

```
// Determine meal type based on current time
```

```
const getCurrentMealType = (): MealType => {
```

```
  const hour = new Date().getHours();
```

```
  if (hour < 11) return 'Breakfast';
```

```
  if (hour < 15) return 'Lunch';
```

```
  if (hour < 20) return 'Dinner';
```

```
  return 'Snack';
```

```
};
```

```
const handleSignOut = async () => {
```

```
  await signOut();
```

```
};
```

```
const handleScanPress = () => {
```

```
  if (canScan) {
```

```
    setShowScanModal(true);
```

```
  } else {
```

```
setShowScanLimitPaywall(true);
```

```
}
```

```
};
```

```
const handleAnalyze = async (imageBase64: string) => {
```

```
  // Increment scan count before analyzing
```

```
  await incrementScanCount.mutateAsync();
```

```
  return await analyzeFood(imageBase64);
```

```
};
```

```
const handleSave = (analysis: FoodAnalysis, imageUrl?: string) => {
```

```
  addLog.mutate({ analysis, imageUrl });
```

```
};
```

```
const renderView = () => {
```

```
  switch (currentView) {
```

```
    case 'HOME':
```

```
      return <HomeView />;
```

```
    case 'LOG':
```

```
      return <LogView />;
```

```
    case 'INSIGHTS':
```

```
      return <InsightsView />;
```

```
    case 'PROFILE':
```

```
      return <ProfileView onSignOut={handleSignOut} />;
```

```
    default:
```

```
      return <HomeView />;
```



```
}
```

```
};
```

```
return (
```

```
<div className="min-h-screen bg-background">
```

```
{renderView()}
```

```
<BottomNav
```

```
currentView={currentView}
```

```
onNavigate={setCurrentView}
```

```
onScanPress={handleScanPress}
```

```
scansRemaining={isPremium ? undefined : scansRemaining}
```

```
/>
```

```
{/* Global Scan Modal */}
```

```
<AddFoodModal
```

```
isOpen={showScanModal}
```

```
onClose={() => setShowScanModal(false)}
```

```
mealType={getCurrentMealType()}
```

```
onAnalyze={handleAnalyze}
```

```
onSave={handleSave}
```

```
isAnalyzing={isAnalyzing}
```

```
isSaving={addLog.isPending}
```

```
/>
```

```
{/* Scan Limit Paywall */}
```

```
<PremiumPaywall
```

```
    isOpen={showScanLimitPaywall}

    onClose={() => setShowScanLimitPaywall(false)}

    onUpgrade={() => {

        upgradeToPremium.mutate();

        setShowScanLimitPaywall(false);

    }}

    isUpgrading={upgradeToPremium.isPending}

    trigger="scan_limit"

/>

</div>

);

};
```

```
export default MainApp;

import React, { useState } from 'react';

import { User, Crown, LogOut, Target, ChevronRight, Loader2 } from 'lucide-react';

import { Button } from '@components/ui/button';

import { Input } from '@components/ui/input';

import { Dialog, DialogContent, DialogHeader, DialogTitle } from '@components/ui/dialog';

import { useAuth } from '@contexts/AuthContext';

import { useUserSettings } from '@hooks/useUserSettings';

import { PremiumPaywall } from '@components/PremiumPaywall';

import { cn } from '@lib/utils';

interface ProfileViewProps {

    onSignOut: () => void;
```

```
}
```

```
export const ProfileView: React.FC<ProfileViewProps> = ({ onSignOut }) => {
```

```
  const { user } = useAuth();
```

```
  const {
```

```
    settings,
```

```
    isLoading,
```

```
    isPremium,
```

```
    calorieGoal,
```

```
    scansRemaining,
```

```
    updateCalorieGoal,
```

```
    upgradeToPremium
```

```
  } = useUserSettings();
```

```
  const [showPaywall, setShowPaywall] = useState(false);
```

```
  const [showGoalEditor, setShowGoalEditor] = useState(false);
```

```
  const [newGoal, setNewGoal] = useState(calorieGoal.toString());
```

```
  const displayName = user?.user_metadata?.full_name || user?.email?.split('@')[0] || 'User';
```

```
  const email = user?.email || '';
```

```
  const handleGoalSave = () => {
```

```
    const goal = parseInt(newGoal);
```

```
    if (goal >= 1000 && goal <= 5000) {
```

```
      updateCalorieGoal.mutate(goal);
```

```
      setShowGoalEditor(false);
```

```
}
```

```
};
```

```
const handleCalorieGoalClick = () => {
```

```
  if (isPremium) {
```

```
    setNewGoal(calorieGoal.toString());
```

```
    setShowGoalEditor(true);
```

```
  } else {
```

```
    setShowPaywall(true);
```

```
  }
```

```
};
```

```
if (isLoading) {
```

```
  return (
```

```
    <div className="min-h-screen bg-background flex items-center justify-center">
```

```
      <Loader2 className="h-8 w-8 animate-spin text-primary" />
```

```
    </div>
```

```
  );
```

```
}
```

```
return (
```

```
  <div className="min-h-screen bg-background pb-28">
```

```
    {/* Header */}
```

```
    <header className="px-5 pt-6 pb-4 safe-top">
```

```
      <h1 className="font-display font-bold text-xl text-foreground">Profile</h1>
```

```
    </header>
```

```
<div className="px-5 space-y-4">
```

```
  { /* Profile Card */ }
```

```
  <div className="bg-card rounded-2xl p-5 border border-border">
```

```
    <div className="flex items-center gap-4">
```

```
      <div className="w-16 h-16 rounded-full bg-primary/10 flex items-center justify-center">
```

```
        <User size={28} className="text-primary" />
```

```
      </div>
```

```
      <div className="flex-1 min-w-0">
```

```
        <h2 className="font-display font-bold text-lg text-foreground truncate">
```

```
          {displayName}
```

```
        </h2>
```

```
        <p className="text-sm text-muted-foreground truncate">{email}</p>
```

```
      </div>
```

```
    </div>
```

```
  </div>
```

```
  { /* Subscription Status */ }
```

```
  <div
```

```
    className={cn(
```

```
      "rounded-2xl p-5 border transition-all",
```

```
      isPremium
```

```
        ? "bg-gradient-to-r from-primary/10 to-primary/5 border-primary/30"
```

```
        : "bg-card border-border"
```

```
    )}
```

>

```
<div className="flex items-center justify-between">
```

```
<div className="flex items-center gap-3">
```

```
<div className={cn(
```

```
"w-12 h-12 rounded-xl flex items-center justify-center",
```

```
isPremium ? "bg-primary/20" : "bg-secondary"
```

```
))>
```

```
<Crown
```

```
size={24}
```

```
className={isPremium ? "text-primary" : "text-muted-foreground"}
```

```
fill={isPremium ? "currentColor" : "none"}
```

```
/>
```

```
</div>
```

```
<div>
```

```
<p className="font-semibold text-foreground">
```

```
{isPremium ? 'LooKai Premium' : 'Free Plan'}
```

```
</p>
```

```
<p className="text-sm text-muted-foreground">
```

```
{isPremium
```

```
? 'Unlimited scans & insights'
```

```
: `${scansRemaining} scans remaining today`
```

```
}
```

```
</p>
```

```
</div>
```

```
</div>
```

```
{!isPremium && (
```

```
<Button
```

```
  onClick={() => setShowPaywall(true)}
```

```
  size="sm"
```

```
  className="gradient-brand text-primary-foreground font-semibold rounded-xl"
```

```
>
```

```
  Upgrade
```

```
</Button>
```

```
  )}
```

```
</div>
```

```
</div>
```

```
{/* Calorie Goal */}
```

```
<button
```

```
  onClick={handleCalorieGoalClick}
```

```
  className="w-full bg-card rounded-2xl p-5 border border-border hover:border-  
primary/30 transition-colors text-left"
```

```
>
```

```
  <div className="flex items-center justify-between">
```

```
    <div className="flex items-center gap-3">
```

```
      <div className="w-12 h-12 rounded-xl bg-primary/10 flex items-center justify-  
center">
```

```
        <Target size={24} className="text-primary" />
```

```
      </div>
```

```
    <div>
```

```
      <p className="font-semibold text-foreground">Daily Calorie Goal</p>
```

```
      <p className="text-sm text-muted-foreground">
```

```
        {isPremium ? 'Tap to edit' : 'Premium feature'}
```

```
</p>
```

```
</div>
```

```
</div>
```

```
<div className="flex items-center gap-2">
```

```
<span className="text-lg font-bold text-primary">{calorieGoal}</span>
```

```
<span className="text-sm text-muted-foreground">kcal</span>
```

```
<ChevronRight className="h-5 w-5 text-muted-foreground" />
```

```
</div>
```

```
</div>
```

```
</button>
```

```
{/* Logout */}
```

```
<Button
```

```
  onClick={onSignOut}
```

```
  variant="ghost"
```

```
  className="w-full h-14 justify-start gap-3 text-destructive hover:text-destructive
  hover:bg-destructive/10 rounded-2xl"
```

```
>
```

```
<LogOut className="h-5 w-5" />
```

```
<span className="font-medium">Sign Out</span>
```

```
</Button>
```

```
</div>
```

```
{/* Premium Paywall */}
```

```
<PremiumPaywall
```

```
  isOpen={showPaywall}
```



```
onClose={() => setShowPaywall(false)}
```

```
onUpgrade={() => {
```

```
  upgradeToPremium.mutate();
```

```
  setShowPaywall(false);
```

```
}}
```

```
isUpgrading={upgradeToPremium.isPending}
```

```
trigger="general"
```

```
/>
```

```
{/* Calorie Goal Editor */}
```

```
<Dialog open={showGoalEditor} onOpenChange={setShowGoalEditor}>
```

```
  <DialogContent className="max-w-sm">
```

```
    <DialogHeader>
```

```
      <DialogTitle>Set Calorie Goal</DialogTitle>
```

```
    </DialogHeader>
```

```
    <div className="space-y-4 py-4">
```

```
      <div className="space-y-2">
```

```
        <label className="text-sm text-muted-foreground">
```

```
          Daily calorie target (1000-5000)
```

```
        </label>
```

```
        <Input
```

```
          type="number"
```

```
          value={newGoal}
```

```
          onChange={(e) => setNewGoal(e.target.value)}
```

```
          min={1000}
```

```
          max={5000}
```

```
className="text-center text-xl font-bold h-14"
```

```
/>
```

```
</div>
```

```
<div className="flex gap-3">
```

```
<Button
```

```
variant="outline"
```

```
className="flex-1"
```

```
onClick={() => setShowGoalEditor(false)}
```

```
>
```

```
Cancel
```

```
</Button>
```

```
<Button
```

```
className="flex-1 gradient-brand text-primary-foreground"
```

```
onClick={handleGoalSave}
```

```
disabled={updateCalorieGoal.isPending}
```

```
>
```

```
{updateCalorieGoal.isPending ? 'Saving...' : 'Save'}
```

```
</Button>
```

```
</div>
```

```
</div>
```

```
</DialogContent>
```

```
</Dialog>
```

```
</div>
```

```
);
```

```
};
```

```
export default ProfileView;
```

```
#root {
```

```
  max-width: 1280px;
```

```
  margin: 0 auto;
```

```
  padding: 2rem;
```

```
  text-align: center;
```

```
}
```

```
.logo {
```

```
  height: 6em;
```

```
  padding: 1.5em;
```

```
  will-change: filter;
```

```
  transition: filter 300ms;
```

```
}
```

```
.logo:hover {
```

```
  filter: drop-shadow(0 0 2em #646cffaa);
```

```
}
```

```
.logo.react:hover {
```

```
  filter: drop-shadow(0 0 2em #61dafbaa);
```

```
}
```

```
@keyframes logo-spin {
```

```
  from {
```

```
    transform: rotate(0deg);
```

```
  }
```

```
  to {
```

```
transform: rotate(360deg);  
  
}  
  
}
```

```
@media (prefers-reduced-motion: no-preference) {  
  
  a:nth-of-type(2) .logo {  
  
    animation: logo-spin infinite 20s linear;  
  
  }  
  
}
```

```
.card {  
  
  padding: 2em;  
  
}
```

```
.read-the-docs {  
  
  color: #888;  
  
}
```

```
import { Toaster } from "@components/ui/toaster";  
  
import { Toaster as Sonner } from "@components/ui/sonner";  
  
import { TooltipProvider } from "@components/ui/tooltip";  
  
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";  
  
import { BrowserRouter, Routes, Route } from "react-router-dom";  
  
import { AuthProvider } from "@contexts/AuthContext";  
  
import Index from "./pages/Index";  
  
import Auth from "./pages/Auth";  
  
import NotFound from "./pages/NotFound";
```

```
const queryClient = new QueryClient();
```

```
const App = () => (
```

```
  <QueryClientProvider client={queryClient}>
```

```
    <AuthProvider>
```

```
      <TooltipProvider>
```

```
        <Toaster />
```

```
        <Sonner />
```

```
        <BrowserRouter>
```

```
          <Routes>
```

```
            <Route path="/" element={<Index />} />
```

```
            <Route path="/auth" element={<Auth />} />
```

```
            { /* ADD ALL CUSTOM ROUTES ABOVE THE CATCH-ALL "*" ROUTE */ }
```

```
            <Route path="*" element={<NotFound />} />
```

```
          </Routes>
```

```
        </BrowserRouter>
```

```
      </TooltipProvider>
```

```
    </AuthProvider>
```

```
  </QueryClientProvider>
```

```
);
```

```
export default App;
```

```
@tailwind base;
```

```
@tailwind components;
```

```
@tailwind utilities;
```

```
@import url('https://fonts.googleapis.com/css2?
family=Plus+Jakarta+Sans:wght@400;500;600;700;800&family=Inter:wght@400;500;600&
display=swap');
```

```
/* Lookai - Modern Health & Wellness Design System */
```

```
@layer base {
```

```
:root {
```

```
  /* Light mode */
```

```
  --background: 0 0% 98%;
```

```
  --foreground: 222 47% 11%;
```

```
  --card: 0 0% 100%;
```

```
  --card-foreground: 222 47% 11%;
```

```
  --popover: 0 0% 100%;
```

```
  --popover-foreground: 222 47% 11%;
```

```
  /* Brand lime/green accent */
```

```
  --primary: 83 78% 55%;
```

```
  --primary-foreground: 222 47% 11%;
```

```
  --secondary: 220 14% 96%;
```

```
  --secondary-foreground: 222 47% 11%;
```

```
  --muted: 220 14% 96%;
```

--muted-foreground: 220 9% 46%;

--accent: 83 78% 55%;

--accent-foreground: 222 47% 11%;

--destructive: 0 84% 60%;

--destructive-foreground: 0 0% 100%;

--success: 142 71% 45%;

--success-foreground: 0 0% 100%;

--warning: 38 92% 50%;

--warning-foreground: 38 92% 15%;

--border: 220 13% 91%;

--input: 220 13% 91%;

--ring: 83 78% 55%;

--radius: 0.75rem;

/* Brand colors */

--brand: 83 78% 55%;

--brand-foreground: 222 47% 11%;

/* Macro colors */

--carbs: 38 92% 50%;

```
--protein: 142 71% 45%;
```

```
--fat: 217 91% 60%;
```

```
/* Chart colors */
```

```
--chart-calories: 0 84% 60%;
```

```
--chart-protein: 142 71% 45%;
```

```
--chart-carbs: 38 92% 50%;
```

```
--chart-fat: 217 91% 60%;
```

```
--chart-water: 199 89% 48%;
```

```
--chart-steps: 25 95% 53%;
```

```
--sidebar-background: 0 0% 98%;
```

```
--sidebar-foreground: 222 47% 11%;
```

```
--sidebar-primary: 83 78% 55%;
```

```
--sidebar-primary-foreground: 222 47% 11%;
```

```
--sidebar-accent: 220 14% 96%;
```

```
--sidebar-accent-foreground: 222 47% 11%;
```

```
--sidebar-border: 220 13% 91%;
```

```
--sidebar-ring: 83 78% 55%;
```

```
}
```

```
.dark {
```

```
/* Dark theme - premium dark health app */
```

```
--background: 224 71% 4%;
```

```
--foreground: 210 20% 98%;
```


--card: 224 71% 7%;

--card-foreground: 210 20% 98%;

--popover: 224 71% 7%;

--popover-foreground: 210 20% 98%;

/* Vibrant lime accent */

--primary: 83 78% 55%;

--primary-foreground: 224 71% 4%;

--secondary: 215 28% 17%;

--secondary-foreground: 210 20% 98%;

--muted: 215 28% 17%;

--muted-foreground: 217 10% 64%;

--accent: 83 78% 55%;

--accent-foreground: 224 71% 4%;

--destructive: 0 84% 60%;

--destructive-foreground: 0 0% 100%;

--success: 142 71% 45%;

--success-foreground: 0 0% 100%;

--warning: 38 92% 50%;

--warning-foreground: 38 92% 15%;

--border: 215 28% 17%;

--input: 215 28% 17%;

--ring: 83 78% 55%;

--brand: 83 78% 55%;

--brand-foreground: 224 71% 4%;

/* Macro colors - dark mode */

--carbs: 38 92% 55%;

--protein: 142 71% 50%;

--fat: 217 91% 65%;

/* Chart colors for dark mode */

--chart-calories: 0 84% 60%;

--chart-protein: 142 71% 50%;

--chart-carbs: 38 92% 55%;

--chart-fat: 217 91% 65%;

--chart-water: 199 89% 53%;

--chart-steps: 25 95% 58%;

--sidebar-background: 224 71% 6%;

--sidebar-foreground: 210 20% 98%;

--sidebar-primary: 83 78% 55%;

--sidebar-primary-foreground: 224 71% 4%;

```
--sidebar-accent: 215 28% 17%;
```

```
--sidebar-accent-foreground: 210 20% 98%;
```

```
--sidebar-border: 215 28% 17%;
```

```
--sidebar-ring: 83 78% 55%;
```

```
}
```

```
}
```

```
@layer base {
```

```
* {
```

```
  @apply border-border;
```

```
}
```

```
html {
```

```
  @apply dark;
```

```
}
```

```
body {
```

```
  @apply bg-background text-foreground font-sans antialiased;
```

```
  font-family: 'Inter', system-ui, sans-serif;
```

```
  -webkit-font-smoothing: antialiased;
```

```
  -moz-osx-font-smoothing: grayscale;
```

```
}
```

```
h1, h2, h3, h4, h5, h6 {
```

```
  font-family: 'Plus Jakarta Sans', system-ui, sans-serif;
```

```
  font-weight: 700;
```

```
}
```

```
}
```

```
@layer utilities {
```

```
  /* Gradients */
```

```
  .gradient-brand {
```

```
    background: linear-gradient(135deg, hsl(83 78% 55%) 0%, hsl(142 71% 45%) 100%);
```

```
  }
```

```
  .gradient-fresh {
```

```
    background: linear-gradient(135deg, hsl(83 78% 55%) 0%, hsl(100 70% 45%) 100%);
```

```
  }
```

```
  .gradient-sunrise {
```

```
    background: linear-gradient(135deg, hsl(38 92% 50%) 0%, hsl(25 95% 53%) 100%);
```

```
  }
```

```
  .gradient-card {
```

```
    background: linear-gradient(180deg, hsl(224 71% 8%) 0%, hsl(224 71% 5%) 100%);
```

```
  }
```

```
  .gradient-hero {
```

```
    background: linear-gradient(180deg, hsl(224 71% 6%) 0%, hsl(224 71% 4%) 100%);
```

```
  }
```

```
  .gradient-water {
```

```
background: linear-gradient(180deg, hsl(199 89% 53%) 0%, hsl(210 100% 45%) 100%);  
}
```

```
.gradient-steps {
```

```
background: linear-gradient(180deg, hsl(25 95% 53%) 0%, hsl(15 90% 45%) 100%);  
}
```

```
.gradient-dark-card {
```

```
background: linear-gradient(145deg, hsl(215 28% 12%) 0%, hsl(215 28% 8%) 100%);  
}
```

```
/* Shadows */
```

```
.shadow-soft {
```

```
box-shadow: 0 4px 20px -4px hsl(0 0% 0% / 0.25);  
}
```

```
.shadow-medium {
```

```
box-shadow: 0 8px 30px -6px hsl(0 0% 0% / 0.35);  
}
```

```
.shadow-glow {
```

```
box-shadow: 0 0 40px -10px hsl(83 78% 55% / 0.4);  
}
```

```
.shadow-brand {
```

```
box-shadow: 0 4px 24px hsl(83 78% 55% / 0.3);
```

```
}
```

```
.shadow-card {
```

```
  box-shadow: 0 2px 8px -2px hsl(0 0% 0% / 0.1), 0 4px 16px -4px hsl(0 0% 0% / 0.15);
```

```
}
```

```
/* Text utilities */
```

```
.text-balance {
```

```
  text-wrap: balance;
```

```
}
```

```
/* Glass effect */
```

```
.glass {
```

```
  background: hsl(224 71% 7% / 0.8);
```

```
  backdrop-filter: blur(20px);
```

```
  -webkit-backdrop-filter: blur(20px);
```

```
}
```

```
.glass-light {
```

```
  background: hsl(0 0% 100% / 0.1);
```

```
  backdrop-filter: blur(12px);
```

```
  -webkit-backdrop-filter: blur(12px);
```

```
}
```

```
/* Animations */
```

```
.animate-float {
```

```
animation: float 3s ease-in-out infinite;
```

```
}
```

```
@keyframes float {
```

```
0%, 100% { transform: translateY(0px); }
```

```
50% { transform: translateY(-8px); }
```

```
}
```

```
.animate-pulse-soft {
```

```
animation: pulse-soft 2s ease-in-out infinite;
```

```
}
```

```
@keyframes pulse-soft {
```

```
0%, 100% { opacity: 1; }
```

```
50% { opacity: 0.7; }
```

```
}
```

```
.animate-scale-in {
```

```
animation: scale-in 0.3s ease-out forwards;
```

```
}
```

```
@keyframes scale-in {
```

```
from {
```

```
opacity: 0;
```

```
transform: scale(0.95);
```

```
}
```

```
to {
```

```
  opacity: 1;
```

```
  transform: scale(1);
```

```
}
```

```
}
```

```
.animate-slide-up {
```

```
  animation: slide-up 0.4s ease-out forwards;
```

```
}
```

```
@keyframes slide-up {
```

```
  from {
```

```
    opacity: 0;
```

```
    transform: translateY(16px);
```

```
}
```

```
  to {
```

```
    opacity: 1;
```

```
    transform: translateY(0);
```

```
}
```

```
}
```

```
.animate-fade-in {
```

```
  animation: fade-in 0.3s ease-out forwards;
```

```
}
```

```
@keyframes fade-in {
```



```
from { opacity: 0; }  
  
to { opacity: 1; }  
  
}
```

```
/* Custom scrollbar for dark theme */
```

```
::-webkit-scrollbar {  
  
width: 6px;  
  
height: 6px;  
  
}
```

```
::-webkit-scrollbar-track {  
  
background: transparent;  
  
}
```

```
::-webkit-scrollbar-thumb {  
  
background: hsl(215 28% 25%);  
  
border-radius: 3px;  
  
}
```

```
::-webkit-scrollbar-thumb:hover {  
  
background: hsl(215 28% 35%);  
  
}
```

```
/* Safe area insets for mobile */
```

```
.safe-bottom {  
  
padding-bottom: max(env(safe-area-inset-bottom), 16px);  
  
}
```

```
}
```

```
.safe-top {
```

```
padding-top: max(env(safe-area-inset-top), 16px);
```

```
}
```

```
/* Focus states */
```

```
.focus-ring {
```

```
@apply focus:outline-none focus:ring-2 focus:ring-primary focus:ring-offset-2 focus:ring-  
offset-background;
```

```
}
```

```
/* Touch targets - minimum 44px */
```

```
.touch-target {
```

```
min-height: 44px;
```

```
min-width: 44px;
```

```
}
```

```
}
```

```
import { createRoot } from "react-dom/client";
```

```
import App from "./App.tsx";
```

```
import "./index.css";
```

```
createRoot(document.getElementById("root")).render(<App />);
```

```
/// <reference types="vite/client" />
```

```
VITE_SUPABASE_PROJECT_ID="yihuydaplbxkkewskvvg"
```

```
VITE_SUPABASE_PUBLISHABLE_KEY="eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6ImhpaHV5ZGFwbGJ4a2tld3NrdnZnliwicm9sZSI6ImFub24iLCJpYXQiOiE3
```

Njc0MjA4MjgsImV4cCI6MjA4Mjk5NjgyOH0.tszALfDAHuEeT0eNHLU1CC5QpX-vO3G2SJzv0Bq_AMI"

VITE_SUPABASE_URL="https://yihuydaplbxkkewskvvg.supabase.co"

Logs

logs

*.log

npm-debug.log*

yarn-debug.log*

yarn-error.log*

pnpm-debug.log*

lerna-debug.log*

node_modules

dist

dist-ssr

*.local

Editor directories and files

.vscode/*

!.vscode/extensions.json

.idea

.DS_Store

*.suo

.ntvs

*.njsproj

*.sln

*.sw?

```
{  
  "$schema": "https://ui.shadcn.com/schema.json",  
  "style": "default",  
  "rsc": false,  
  "tsx": true,  
  "tailwind": {  
    "config": "tailwind.config.ts",  
    "css": "src/index.css",  
    "baseColor": "slate",  
    "cssVariables": true,  
    "prefix": ""  
  },  
  "aliases": {  
    "components": "@components",  
    "utils": "@lib/Utils",  
    "ui": "@components/ui",  
    "lib": "@lib",  
    "hooks": "@hooks"  
  }  
}  
  
import js from "@eslint/js";  
import globals from "globals";  
import reactHooks from "eslint-plugin-react-hooks";  
import reactRefresh from "eslint-plugin-react-refresh";  
import tseslint from "typescript-eslint";
```

```
export default tseslint.config(  
  { ignores: ["dist"] },  
  {  
    extends: [js.configs.recommended, ...tseslint.configs.recommended],  
    files: ["**/*.ts,tsx"],  
    languageOptions: {  
      ecmaVersion: 2020,  
      globals: globals.browser,  
    },  
    plugins: {  
      "react-hooks": reactHooks,  
      "react-refresh": reactRefresh,  
    },  
    rules: {  
      ...reactHooks.configs.recommended.rules,  
      "react-refresh/only-export-components": ["warn", { allowConstantExport: true }],  
      "@typescript-eslint/no-unused-vars": "off",  
    },  
  },  
);  
  
<!DOCTYPE html>  
  
<html lang="en">  
  
<head>  
  
  <meta charset="UTF-8" />
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0, maximum-scale=1.0, user-scalable=no" />
```

```
<meta name="theme-color" content="#22c55e" />
```

```
<title>LooKai - AI Food Calorie Tracker</title>
```

```
<meta name="description" content="LooKai - Look at your food, AI does the rest. Track calories instantly with AI-powered food recognition.">
```

```
<meta name="author" content="LooKai" />
```

```
<!-- PWA Meta Tags -->
```

```
<meta name="apple-mobile-web-app-capable" content="yes" />
```

```
<meta name="apple-mobile-web-app-status-bar-style" content="default" />
```

```
<meta name="apple-mobile-web-app-title" content="LooKai" />
```

```
<!-- Open Graph -->
```

```
<meta property="og:type" content="website" />
```

```
<meta property="og:image" content="https://storage.googleapis.com/gpt-engineer-file-uploads/XEQCQKLzTzgyFEZSFtirNDj5qJ42/social-images/social-1768071847806-ChatGPT Image Jan 3, 2026, 03_40_59 PM (1).png">
```

```
<meta name="twitter:card" content="summary_large_image" />
```

```
<meta name="twitter:site" content="@LooKaiApp" />
```

```
<meta name="twitter:image" content="https://storage.googleapis.com/gpt-engineer-file-uploads/XEQCQKLzTzgyFEZSFtirNDj5qJ42/social-images/social-1768071847806-ChatGPT Image Jan 3, 2026, 03_40_59 PM (1).png">
```

```
<link rel="icon" type="image/png" href="https://storage.googleapis.com/gpt-engineer-file-uploads/XEQCQKLzTzgyFEZSFtirNDj5qJ42/uploads/1768071826742-ChatGPT Image Jan 3, 2026, 03_40_59 PM (1).png">
```

```
<meta property="og:title" content="Lookai - AI Food Calorie Tracker">
```

```
<meta name="twitter:title" content="Lookai - AI Food Calorie Tracker">
```

```
<meta property="og:description" content="Lookai - Look at your food, AI does the rest. Track calories instantly with AI-powered food recognition.">
```

```
<meta name="twitter:description" content="Lookai - Look at your food, AI does the rest. Track calories instantly with AI-powered food recognition.">
```

```
</head>
```

```
<body>
```

```
<div id="root"></div>
```

```
<script type="module" src="/src/main.tsx"></script>
```

```
</body>
```

```
</html>
```

```
{
```

```
"name": "vite-react-shadcn-ts",
```

```
"private": true,
```

```
"version": "0.0.0",
```

```
"type": "module",
```

```
"scripts": {
```

```
"dev": "vite",
```

```
"build": "vite build",
```

```
"build:dev": "vite build --mode development",
```

```
"lint": "eslint .",
```

```
"preview": "vite preview"
```

```
},
```

```
"dependencies": {
```

```
"@hookform/resolvers": "^3.10.0",
```

```
"@radix-ui/react-accordion": "^1.2.11",
```

```
"@radix-ui/react-alert-dialog": "^1.1.14",
```

```
"@radix-ui/react-aspect-ratio": "^1.1.7",
```

```
"@radix-ui/react-avatar": "^1.1.10",
```

```
"@radix-ui/react-checkbox": "^1.3.2",
```

```
"@radix-ui/react-collapsible": "^1.1.11",
```

```
"@radix-ui/react-context-menu": "^2.2.15",
```

```
"@radix-ui/react-dialog": "^1.1.14",
```

```
"@radix-ui/react-dropdown-menu": "^2.1.15",
```

```
"@radix-ui/react-hover-card": "^1.1.14",
```

```
"@radix-ui/react-label": "^2.1.7",
```

```
"@radix-ui/react-menubar": "^1.1.15",
```

```
"@radix-ui/react-navigation-menu": "^1.2.13",
```

```
"@radix-ui/react-popover": "^1.1.14",
```

```
"@radix-ui/react-progress": "^1.1.7",
```

```
"@radix-ui/react-radio-group": "^1.3.7",
```

```
"@radix-ui/react-scroll-area": "^1.2.9",
```

```
"@radix-ui/react-select": "^2.2.5",
```

```
"@radix-ui/react-separator": "^1.1.7",
```

```
"@radix-ui/react-slider": "^1.3.5",
```

```
"@radix-ui/react-slot": "^1.2.3",
```

```
"@radix-ui/react-switch": "^1.2.5",
```

```
"@radix-ui/react-tabs": "^1.1.12",
```


"@radix-ui/react-toast": "^1.2.14",
"@radix-ui/react-toggle": "^1.1.9",
"@radix-ui/react-toggle-group": "^1.1.10",
"@radix-ui/react-tooltip": "^1.2.7",
"@supabase/supabase-js": "^2.89.0",
"@tanstack/react-query": "^5.83.0",
"class-variance-authority": "^0.7.1",
"clsx": "^2.1.1",
"cmdk": "^1.1.1",
"date-fns": "^3.6.0",
"embla-carousel-react": "^8.6.0",
"input-otp": "^1.4.2",
"lucide-react": "^0.462.0",
"next-themes": "^0.3.0",
"react": "^18.3.1",
"react-day-picker": "^8.10.1",
"react-dom": "^18.3.1",
"react-hook-form": "^7.61.1",
"react-resizable-panels": "^2.1.9",
"react-router-dom": "^6.30.1",
"recharts": "^2.15.4",
"sonner": "^1.7.4",
"tailwind-merge": "^2.6.0",
"tailwindcss-animate": "^1.0.7",
"vaul": "^0.9.9",
"zod": "^3.25.76"

```
  },  
  
  "devDependencies": {  
  
    "@eslint/js": "^9.32.0",  
  
    "@tailwindcss/typography": "^0.5.16",  
  
    "@types/node": "^22.16.5",  
  
    "@types/react": "^18.3.23",  
  
    "@types/react-dom": "^18.3.7",  
  
    "@vitejs/plugin-react-swc": "^3.11.0",  
  
    "autoprefixer": "^10.4.21",  
  
    "eslint": "^9.32.0",  
  
    "eslint-plugin-react-hooks": "^5.2.0",  
  
    "eslint-plugin-react-refresh": "^0.4.20",  
  
    "globals": "^15.15.0",  
  
    "lovable-tagger": "^1.1.13",  
  
    "postcss": "^8.5.6",  
  
    "tailwindcss": "^3.4.17",  
  
    "typescript": "^5.8.3",  
  
    "typescript-eslint": "^8.38.0",  
  
    "vite": "^5.4.19"  
  
  }  
  
}  
  
export default {  
  
  plugins: {  
  
    tailwindcss: {},  
  
    autoprefixer: {},  
  
  },  
  
},
```

```
};
```

```
import type { Config } from "tailwindcss";
```

```
export default {
```

```
  darkMode: ["class"],
```

```
  content: ["/pages/**/*.{ts,tsx}", "/components/**/*.{ts,tsx}", "/app/**/*.{ts,tsx}", "/src/**/*.{ts,tsx}"],
```

```
  prefix: "",
```

```
  theme: {
```

```
    container: {
```

```
      center: true,
```

```
      padding: "1rem",
```

```
      screens: {
```

```
        "2xl": "1400px",
```

```
      },
```

```
    },
```

```
    extend: {
```

```
      fontFamily: {
```

```
        sans: ['Inter', 'system-ui', 'sans-serif'],
```

```
        display: ['Plus Jakarta Sans', 'system-ui', 'sans-serif'],
```

```
      },
```

```
      fontSize: {
```

```
        'xs': ['0.75rem', { lineHeight: '1rem' }],
```

```
        'sm': ['0.875rem', { lineHeight: '1.25rem' }],
```

```
        'base': ['1rem', { lineHeight: '1.5rem' }],
```

```
        'lg': ['1.125rem', { lineHeight: '1.75rem' }],
```

```
'xl': ['1.25rem', { lineHeight: '1.75rem' }],
```

```
'2xl': ['1.5rem', { lineHeight: '2rem' }],
```

```
'3xl': ['1.875rem', { lineHeight: '2.25rem' }],
```

```
'4xl': ['2.25rem', { lineHeight: '2.5rem' }],
```

```
'5xl': ['3rem', { lineHeight: '1' }],
```

```
},
```

```
spacing: {
```

```
'18': '4.5rem',
```

```
'22': '5.5rem',
```

```
'26': '6.5rem',
```

```
'30': '7.5rem',
```

```
},
```

```
colors: {
```

```
border: "hsl(var(--border))",
```

```
input: "hsl(var(--input))",
```

```
ring: "hsl(var(--ring))",
```

```
background: "hsl(var(--background))",
```

```
foreground: "hsl(var(--foreground))",
```

```
primary: {
```

```
  DEFAULT: "hsl(var(--primary))",
```

```
  foreground: "hsl(var(--primary-foreground))",
```

```
},
```

```
secondary: {
```

```
  DEFAULT: "hsl(var(--secondary))",
```

```
  foreground: "hsl(var(--secondary-foreground))",
```

```
},
```

```
destructive: {  
  DEFAULT: "hsl(var(--destructive))",  
  foreground: "hsl(var(--destructive-foreground))",  
},  
  
success: {  
  DEFAULT: "hsl(var(--success))",  
  foreground: "hsl(var(--success-foreground))",  
},  
  
warning: {  
  DEFAULT: "hsl(var(--warning))",  
  foreground: "hsl(var(--warning-foreground))",  
},  
  
muted: {  
  DEFAULT: "hsl(var(--muted))",  
  foreground: "hsl(var(--muted-foreground))",  
},  
  
accent: {  
  DEFAULT: "hsl(var(--accent))",  
  foreground: "hsl(var(--accent-foreground))",  
},  
  
popover: {  
  DEFAULT: "hsl(var(--popover))",  
  foreground: "hsl(var(--popover-foreground))",  
},  
  
card: {  
  DEFAULT: "hsl(var(--card))",
```

```
    foreground: "hsl(var(--card-foreground))",
  },

  sidebar: {
    DEFAULT: "hsl(var(--sidebar-background))",
    foreground: "hsl(var(--sidebar-foreground))",
    primary: "hsl(var(--sidebar-primary))",
    "primary-foreground": "hsl(var(--sidebar-primary-foreground))",
    accent: "hsl(var(--sidebar-accent))",
    "accent-foreground": "hsl(var(--sidebar-accent-foreground))",
    border: "hsl(var(--sidebar-border))",
    ring: "hsl(var(--sidebar-ring))",
  },

  // Macro nutrient colors
  carbs: "hsl(var(--carbs))",
  protein: "hsl(var(--protein))",
  fat: "hsl(var(--fat))",
},

borderRadius: {
  lg: "var(--radius)",
  md: "calc(var(--radius) - 2px)",
  sm: "calc(var(--radius) - 4px)",
  '2xl': '1rem',
  '3xl': '1.5rem',
  '4xl': '2rem',
},

boxShadow: {
```

```
'glow': '0 0 40px -10px hsl(83 78% 55% / 0.4)',
```

```
'glow-sm': '0 0 20px -5px hsl(83 78% 55% / 0.3)',
```

```
'card': '0 2px 8px -2px hsl(0 0% 0% / 0.1), 0 4px 16px -4px hsl(0 0% 0% / 0.15)',
```

```
'elevated': '0 8px 32px -8px hsl(0 0% 0% / 0.3)',
```

```
},
```

```
keyframes: {
```

```
  "accordion-down": {
```

```
    from: { height: "0" },
```

```
    to: { height: "var(--radix-accordion-content-height)" },
```

```
  },
```

```
  "accordion-up": {
```

```
    from: { height: "var(--radix-accordion-content-height)" },
```

```
    to: { height: "0" },
```

```
  },
```

```
  "shimmer": {
```

```
    "0%": { transform: "translateX(-100%)" },
```

```
    "100%": { transform: "translateX(100%)" },
```

```
  },
```

```
  "pulse-ring": {
```

```
    "0%": { transform: "scale(0.95)", opacity: "1" },
```

```
    "100%": { transform: "scale(1.3)", opacity: "0" },
```

```
  },
```

```
},
```

```
animation: {
```

```
  "accordion-down": "accordion-down 0.2s ease-out",
```

```
  "accordion-up": "accordion-up 0.2s ease-out",
```

```
    "shimmer": "shimmer 2s infinite",

    "pulse-ring": "pulse-ring 1.5s cubic-bezier(0.4, 0, 0.6, 1) infinite",

  },

},

},

plugins: [require("tailwindcss-animate")],
} satisfies Config;

{

  "compilerOptions": {

    "target": "ES2020",

    "useDefineForClassFields": true,

    "lib": ["ES2020", "DOM", "DOM.Iterable"],

    "module": "ESNext",

    "skipLibCheck": true,


    /* Bundler mode */

    "moduleResolution": "bundler",

    "allowImportingTsExtensions": true,

    "isolatedModules": true,

    "moduleDetection": "force",

    "noEmit": true,

    "jsx": "react-jsx",


    /* Linting */

    "strict": false,

    "noUnusedLocals": false,
```



```
"noUnusedParameters": false,

"noImplicitAny": false,

"noFallthroughCasesInSwitch": false,


"baseUrl": "",

"paths": {

  "@/*": ["/src/*"]

},

},

"include": ["src"]

}

{

  "files": [],

  "references": [{ "path": "./tsconfig.app.json" }, { "path": "./tsconfig.node.json" }],

  "compilerOptions": {

    "baseUrl": "",

    "paths": {

      "@/*": ["/src/*"]

    },

    "noImplicitAny": false,

    "noUnusedParameters": false,

    "skipLibCheck": true,

    "allowJs": true,

    "noUnusedLocals": false,

    "strictNullChecks": false

  }

}
```

```
}
```

```
{
```

```
  "compilerOptions": {
```

```
    "target": "ES2022",
```

```
    "lib": ["ES2023"],
```

```
    "module": "ESNext",
```

```
    "skipLibCheck": true,
```

```
    /* Bundler mode */
```

```
    "moduleResolution": "bundler",
```

```
    "allowImportingTsExtensions": true,
```

```
    "isolatedModules": true,
```

```
    "moduleDetection": "force",
```

```
    "noEmit": true,
```

```
    /* Linting */
```

```
    "strict": true,
```

```
    "noUnusedLocals": false,
```

```
    "noUnusedParameters": false,
```

```
    "noFallthroughCasesInSwitch": true
```

```
  },
```

```
  "include": ["vite.config.ts"]
```

```
}
```

```
import { defineConfig } from "vite";
```

```
import react from "@vitejs/plugin-react-swc";
```

```
import path from "path";
```

```
import { componentTagger } from "lovable-tagger";
```

```
// https://vitejs.dev/config/
```

```
export default defineConfig(({ mode }) => ({
```

```
  server: {
```

```
    host: "::",
```

```
    port: 8080,
```

```
  },
```

```
  plugins: [react(), mode === "development" && componentTagger()].filter(Boolean),
```

```
  resolve: {
```

```
    alias: {
```

```
      "@": path.resolve(__dirname, "./src"),
```

```
    },
```

```
  },
```

```
}));
```