

HTML BASIC

Feroza Naznin
Lecturer, GUB

What is HTML?

- HTML stands for Hyper Text Markup Language. It is a language of World Wide Web. It is a standard text formatting language which is used to create and display pages on the Web. It makes the text more interactive and dynamic. It can turn text into images, tables, links.

What are Tags?

- HTML tags are composed of three things: an opening tag, content and ending tag.
 - Some tags are unclosed tags.
- ❑ HTML documents contain two things:
 - content, and
 - tags

When a web browser reads an HTML document, the browser reads it from top to bottom and left to right. HTML tags are used to create HTML documents and render their properties. Each HTML tags have different properties.

Syntax

- ❑ `<tag> content </tag>`

Content is placed between tags to display data on the web page.

Do all HTML tags have an end tag?

No.

There are some HTML tags that don't need a closing tag.
For example:

- `<image>` tag
- `<br>` tag.

`<br>` Tag: br stands for break line, it breaks the line of the code.

`<hr>` Tag: hr stands for Horizontal Rule. This tag is used to put a line across the webpage.

What is formatting in HTML?

The HTML formatting is a process of format the text for a better look and feel. It uses different tags to make text bold, italicized, underlined.

- Physical tag: These tags are used to provide the visual appearance to the text.
- Logical tag: These tags are used to add some logical or semantic value to the text.

`<b>` This is a physical tag, which is used to bold the text written between it.

`<strong>` This is a logical tag, which tells the browser that the text is important.

How many types of heading does an HTML contain?

The HTML contains six types of headings which are defined with the `<h1>` to `<h6>` tags.

Each type of heading tag displays different text size from another. So

- `<h1>` is the largest heading tag and
- `<h6>` is the smallest one.

How to create a hyperlink in HTML?

The HTML provides an anchor tag to create a hyperlink that links one page to another page. These tags can appear in any of the following ways:

- Unvisited link - It is displayed, underlined and blue.
- Visited link - It is displayed, underlined and purple.
- Active link - It is displayed, underlined and red.

HTML Anchor

The HTML anchor tag defines a hyperlink that links one page to another page. It can create hyperlink to other web page as well as files, location, or any URL. The "href" attribute is the most important attribute of the HTML a tag. and which links to destination page or URL.

href attribute of HTML anchor tag:

The href attribute is used to define the address of the file to be linked. In other words, it points out the destination page.

The syntax of HTML anchor tag is given below.

** Link Text **

Let's see an example of HTML anchor tag.

Click for Second Page

What is the difference between HTML elements and tags?

HTML elements communicate to the browser to render text. When the elements are enclosed by brackets `<>`, they form HTML tags.

Most of the time, tags come in a pair and surround content.

- A text header, denoted using the `<h1>`, `<h2>`, `<h3>`, `<h4>`, `<h5>`, `<h6>` tags.
- A paragraph, denoted using the `<p>` tag.

What are some common lists that are used when designing a page?

There are many common lists which are used to design a page. You can choose any or a combination of the following list types:

- Ordered list - The ordered list displays elements in numbered format. It is represented by `<ol>` tag.
- Unordered list - The unordered list displays elements in bulleted format. It is represented by `<ul>` tag.
- Definition list - The definition list displays elements in definition form like in dictionary.

The `<dl>`, `<dt>` and `<dd>` tags are used to define description list.

HTML List Tags

HTML List Tags

Tag	Description
<u></u>	Defines an unordered list
<u></u>	Defines an ordered list
<u></u>	Defines a list item
<u><dl></u>	Defines a description list
<u><dt></u>	Defines a term in a description list
<u><dd></u>	Describes the term in a description list

What is semantic HTML?

Semantic HTML is a coding style. It is the use of HTML markup to reinforce the semantics or meaning of the content.

For example:

- In semantic HTML `<b>` `</b>` tag is not used for bold statement as well as `<i>` `</i>` tag is used for italic.
- Instead of these we use ```</strong>` and `<em>``` tags.

Which HTML tag is used to display the data in the tabular form?

Tag	Description
<code><table></code>	It defines a table.
<code><tr></code>	It defines a row in a table.
<code><th></code>	It defines a header cell in a table.
<code><td></code>	It defines a cell in a table.
<code><caption></code>	It defines the table caption.
<code><colgroup></code>	It specifies a group of one or more columns in a table for formatting.
<code><col></code>	It is used with <code><colgroup></code> element to specify column properties for each column.
<code><tbody></code>	It is used to group the body content in a table.
<code><thead></code>	It is used to group the header content in a table.
<code><tfooter></code>	It is used to group the footer content in a table.

What is an image map?

Image map facilitates you to link many different web pages using a single image.

- ❑ It is represented by `<map>` tag.

You can define shapes in images that you want to make part of an image mapping.

How to insert a copyright symbol on a browser page?

You can insert a copyright symbol by using

□ `©` or `©` in an HTML file.

Example:

Source code:

□ `<footer>© Copyright 2020 HTML.am</footer>`

Result:

□ © Copyright 2020 HTML.am

How to create a nested webpage in HTML?

The HTML iframe tag is used to display a nested webpage. In other words, it represents a webpage within a webpage.

The HTML <iframe> tag defines an inline frame.

For example:

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>HTML Iframes example</h2>
```

```
<p>Use the height and width attributes to specify the size of the iframe:</p>
```

```
<iframe src="https://www.javatpoint.com/" height="300" width="400"></iframe>
```

```
</body>
```

```
</html>
```


How do you keep list elements straight in an HTML file?

You can keep the list elements straight by using indents.

HTML Block <div> Elements

- The *<div> tag* defines a division or a section in an *HTML* document.
- The *<div> tag* is used as a container for *HTML* elements
- which is then styled with CSS or manipulated with JavaScript.
- The *<div> tag* is easily styled by using the class or id attribute.

```
<html>
<head>
<style>
.myDiv {
  border: 5px outset red;
  background-color: lightblue;
  text-align: center;
}
</style>
</head>
<body>

<div class="myDiv">
  <h2>This is a heading in a div element</h2>
  <p>This is some text in a div element.</p>
</div>

</body>
</html>
```

Block-level Elements

<address>	<article>	<aside>	<blockquote>	<canvas>	<dd>
<div>	<dl>	<dt>	<fieldset>	<figcaption>	<figure>
<footer>	<form>	<h1>-<h6>	<header>	<hr>	
<main>	<nav>	<noscript>		<p>	<pre>
<section>	<table>	<tfoot>		<video>	

HTML Inline Elements

Definition :

The * tag* is an inline container used to mark up a part of a text, or a part of a document.

Usage:

Browser Support *Element* .

Global Attributes.

More Inline Elements

<a>	<abbr>	<acronym>		<bdo>	<big>
 	<button>	<cite>	<code>	<dfn>	
<i>		<input>	<kbd>	<label>	<map>
<object>	<output>	<q>	<samp>	<script>	<select>
<small>			<sub>	<sup>	<textarea>
<time>	<tt>	<var>			