

HUMBOLDT-UNIVERSITÄT ZU BERLIN
MATHEMATISCH-NATURWISSENSCHAFTLICHE FAKULTÄT
INSTITUT FÜR INFORMATIK

Automated Security Vulnerability Detection in Source Code Using Deep Learning On Github Data

Masterarbeit

zur Erlangung des akademischen Grades
Master of Science (M. Sc.)

eingereicht von: Laura Wartschinski

geboren am: 11.05.1994

geboren in: Eisenach

Gutachter/innen: Prof. Dr. Lars Grunske
Dr. Thomas Vogel

eingereicht am:

verteidigt am:

Inhaltsverzeichnis

Summary	6
1. Motivation	7
1.1. The challenge of detecting vulnerabilities	7
1.2. Problem statement and proposed approach	9
2. Background	10
2.1. Discovering vulnerabilities	10
2.2. 'Traditional' approaches	10
2.2.1. Static analysis	10
2.2.2. Dynamic and hybrid analysis	11
2.3. Machine learning	12
2.3.1. Deep learning and neural networks	13
2.3.2. Recurrent neural networks	14
2.3.3. Vanishing and exploding gradients	16
2.3.4. Long short term memory networks	16
2.4. Representing code	18
2.4.1. Abstract syntax trees	18
2.4.2. Code as natural text	19
2.4.3. Bag of words	19
2.4.4. N-gram models	19
2.5. Embedding code in a numerical vector	20
2.5.1. One-hot embedding	20
2.5.2. Word2Vec embedding	20
2.6. Mining Software Repositories	22
2.6.1. Approaches for mining software repositories	22
2.6.2. Tools for mining software repositories	22
2.6.3. Mining Github	23
2.7. Python vulnerabilities	23
2.7.1. Injection attacks	23
2.7.2. Various types of session hijacking	25
2.7.3. Cross-site scripting	26
2.7.4. Cross-Site request forgery	27
2.7.5. Directory traversal / path disclosure	27
2.7.6. Open redirect vulnerabilities	28
2.7.7. Other terms in relation to vulnerabilities	28
3. Related Work	29
3.1. Vulnerability prediction based on software metrics	29
3.2. Anomaly detection approaches for finding vulnerabilities	30
3.3. Vulnerable code pattern analysis and similarity analysis	31
3.3.1. Deep learning for vulnerability prediction	33

3.3.2. Long short term memory networks	35
3.4. Contributions	35
4. Methodology	38
4.1. Architecture	38
4.2. Choosing a programming language	38
4.3. Data source	39
4.4. Choosing vulnerabilites	39
4.5. Labeling	39
4.6. Representation of source code	40
4.6.1. Choosing a representation	40
4.6.2. Choosing granularity	40
4.6.3. Preprocessing the code	41
4.6.4. Choosing the vector embedding	41
4.7. Selecting the machine learning model	42
4.8. Choosing the optimizer	43
4.9. Evaluation	44
5. Implementation	46
5.1. Collecting the data	46
5.1.1. Scraping Github	46
5.1.2. Filtering the results	47
5.1.3. First misguided attempt: Using only diffs	48
5.1.4. Downloading the dataset	49
5.1.5. Flaws in the data	50
5.1.6. Filtering data	51
5.1.7. Second misguided attempt: subtle errors in creating the dataset	52
5.2. Processing the data	53
5.3. Word2Vec embedding	54
5.4. Preparing the data for classification	57
5.5. Training the LSTM	57
5.5.1. Architecture of the model	57
5.5.2. Choosing hyperparameters for the LSTM	58
5.5.3. Practical considerations	59
5.6. Application on code	60
6. Evaluation	62
6.1. The data	62
6.2. The baseline model	62
6.3. Hyperparameters of the word2vec embedding	63
6.3.1. Vector dimensionality	64
6.3.2. String replacement	64
6.3.3. Minimum count	65
6.3.4. Iterations	65

6.4.	Parameters in creating the the dataset	66
6.5.	Hyperparameters and performance of the LSTM model	67
6.5.1.	Number of neurons	68
6.5.2.	Batch size	69
6.5.3.	Dropout	69
6.5.4.	Optimizer	69
6.5.5.	Number of training epochs	70
6.5.6.	Optimal configuration	71
6.6.	Performance for subsets of vulnerabilities	72
6.6.1.	SQL injection	73
6.6.2.	Cross-site scripting	74
6.6.3.	Command injection	75
6.6.4.	Cross-site request forgery	75
6.6.5.	Path disclosure	76
6.6.6.	Remote code execution	78
6.6.7.	Open redirect	79
7.	Discussion	80
7.1.	Answers to research questions	80
7.1.1.	Research question 1	80
7.1.2.	Research question 2	80
7.1.3.	Research question 3	81
7.1.4.	Research question 4	81
7.2.	Comparison with other works	82
7.3.	Limitations and threats to validity	84
7.4.	Future work	87
	Conclusion	89
	Bibliography	90
	Appendices	100
A.	SQL injection	100
B.	Cross-site scripting	103
C.	Command injection	104
D.	Cross-site request forgery	106
E.	Path disclosure	109
F.	Open redirect	110
G.	Remote Code Execution	114

Summary

Computer Software is indispensable for modern human life. Security vulnerabilities are prevalent in software systems and can lead to various severe consequences such as information loss, disclosure of secret information, manipulation, or system failure. Although tools exist to detect vulnerable code, their accuracy and effectiveness remain a challenging research question. To define features that identify vulnerabilities, many existing solutions require extensive work from human experts.

This work presents VUDENC (Vulnerability Detection with Deep Learning on a Natural Codebase), a deep learning-based vulnerability detection system that automatically learns features from a large collection of real-life code. The dataset is collected from Github and contains Python code with a variety of vulnerabilities, which is embedded in a vector space using a new word2vec model that was trained specifically for this work on a large Python corpus. The data samples are created from the source code of the vulnerable files by taking individual code tokens and their context, allowing for a fine-grained analysis. The samples are then separated into datasets for each vulnerability, and a Long-Short-Term-Memory network is trained to recognize features of vulnerable code and applied to detect vulnerabilities in source code. This approach enables VUDENC to recognize seven different security vulnerabilities with high precision ($> 94\%$) and recall ($> 70\%$) and being able to highlight the specific parts in the code that are suspected to be vulnerable.

This work starts with describing the challenge of vulnerabilities in Section 1, explaining the technical background in Section 2 and presenting related work in Section 3. Design choices and methodological considerations for VUDENC are laid out in Section 4, followed by the description of the practical implementation including all its challenges in Section 5. The work concludes with the evaluation of the model in Section 6, the discussion of results in Section 7, and finally the conclusion.

The following research questions are investigated. RQ1: Can a dataset of suitable Python source code be mined from Github for common vulnerability types? RQ2: Is the word2vec model effective as an embedding, and how do its hyperparameters influence the overall results? RQ3: Which types of vulnerabilities can be detected? RQ4: How effective is VUDENC in detecting vulnerabilities as measured with accuracy, precision, and recall?

1. Motivation

Modern life would not work the way it does without computer programs. Software has become a necessity for several aspects of society, including healthcare, energy, transportation, public safety, education, entertainment and many more. However, creating safe, reliable and secure software is by no means a trivial task. Oversights and errors made by software architects and engineers can easily cause software vulnerabilities - and the consequences are severe. An exploit like the ransomware WannaCry will, for example, shut down hospitals and transportation systems and cause hundreds of millions of dollars in damage [Dan17]. Just a small flaw in the code, sometimes spanning a few or even just one line, can be enough to cause a severe vulnerability and make the system an easy target for attacks [YLR12]. The famous Heartbleed bug, a severe vulnerability in the OpenSSL cryptographic library that affected billions of internet users, could have been prevented with two more lines of code [DLK⁺14]. Cyberattacks are an increasing threat to governments, businesses, and consumers [DTP⁺17], costing an estimated 400 billion dollars a year [Los14]. At the same time, the number of entries in the Common Vulnerabilities and Exposures (CVE) database was approximately over 125000 in October 2019 [CVE19], and although there are guidelines for developing secure applications, many developers do not adhere to them or make mistakes introducing vulnerabilities regardless of such guidelines [GGS14], not to speak of out-of-data software that is an easy target for exploits.

1.1. The challenge of detecting vulnerabilities

Code inspection is a key process for detecting vulnerabilities, and a necessary prerequisite to fixing them [YTWM19]. Even code that is secure at some point in time often does not stay like that for very long. Any code change in a project can possibly alter the attack surface or introduce a security vulnerability [MHMW15]. Therefore, constant scrupulous code reviews are necessary to catch any such flaw. But inspecting code manually is a tedious, time-consuming process that requires substantial knowledge in the area of security [YLR11], mostly because modern software systems are becoming increasingly complex and interconnected, and problems can lie in very innocuous-looking segments of code [PXN15, LZX⁺18]. Vulnerabilities often result from violating unspoken, implicit programming rules that can be hard to keep track of [LZ05]. Software testers attempting to detect vulnerabilities need to know not only the language and architecture of the software in question, but also malicious strategies and mindsets, being able to reason like an attacker [PXN15].

To make matters worse, many security vulnerabilities do not affect the typical functionalities of a system and can therefore stay undetected for a long time. Those 'hidden vulnerabilities' can have disastrous effects, since they are usually only discovered long after the bug has been introduced, giving attackers ample time to exploit the vulnerability [WMWM12, MTL⁺17, RKH⁺18]. Due to the prevalence of open-source software,

code re-use (for instance, Github forks) etc., vulnerable code can propagate quickly from one project to the next. And even if a nearly unlimited time is spent searching for more vulnerabilities, defenders can never be sure they have caught everything, while at the same time, an attacker only needs to find one single useful vulnerability to be able to cause harm and, for instance, cause a program to crash or expose sensitive information. It is hard for developers to stay ahead of the game

Because there is no systematic way that covers all possible flaws, coming up with identifying features that define vulnerabilities is largely an art, depending strongly on individual expertise [RSG⁺18, LZX⁺18]. Since the quality of defined features (and therefore the power of a vulnerability detection system) varies strongly with the individual creating them, the outcome for such a process must be improved by asking multiple experts and combining their results, which would require even more manpower [LZX⁺18]. Instead, it is desirable to reduce the need for human labor as much as possible.

Some tools are already used to support developers, for example by helping with prioritization and testing and reducing the time spent on the task [DTP⁺17]. The dominant approach so far has been a formal one, which aims to model programming languages with mathematical structures and prove certain properties [ABDS18], for example, about code coverage and data flows. With symbolic execution, input data is replaced with symbolic values and analyzed as it changes over the control flow of the program. Static analysis tools analyze source code without executing it, following a rule-based approach. Some examples for widely used tools include FindBugs [HP04, Hov05] for Java, Splint [Eva02] and Flawfinder [Whe06] for C, and PyT [MT16] (Python taint) for Python. They play an important role, but they are not sufficient to solve the prevalence of vulnerabilities. Many tools used today that rely on static analysis and suffer from a high false positive rate, which hinders their adoption [LKB⁺18] and leads to various problems described below, in addition to the fact that their criteria still have to be defined by experts and can therefore lag behind recent developments.

A new approach is emerging with methods based on data analysis and machine learning. It is driven by the goal to design a vulnerability detection system without relying on subjective expert opinions and without suffering from high rates of false negatives or false positives [LZX⁺18]. The core idea is to derive patterns from large amounts of data, using a machine learning algorithm to discover vulnerability features, and to classify code accordingly. This means that vulnerability detection can be automated, and possibly also applied very early in the software lifecycle, which can significantly reduce the costs of finding and fixing errors [DTP⁺17, GGS14]. Machine learning models can be retrained with new data any time a previously unknown type of vulnerability or exploit emerges. The approach also reduces the reliance on subjective personal experience and offers a more objective and general approach to defining features. Ultimately, it has the potential to scale a lot better. Unfortunately, automatic vulnerability discovery is not yet widespread. A study funded by IBM measured the adoption rate and the effect of automation (mostly referring to machine learning and artificial intelligence) in detecting cyber attacks [IBM]. They came to the conclusion that various automation techniques help significantly with preventing exploits, but that around 77% of organizations use automation only moderately, insignificantly or not at all, pointing to a strong potential

of further improvement.

1.2. Problem statement and proposed approach

Ideally, the process of finding vulnerabilities should be automated in a way that is both precise and significantly faster than manual code inspection. It would not require subjective features that are manually defined, but learn features from real-life code and automatically adapt to new challenges. A tool like that would support human experts by reducing or eliminating the need for the most time-consuming and error-prone tasks in detecting vulnerabilities. With a low rate in false positives *and* false negatives, such a tool would provide great benefit to developers, if it could highlight possible vulnerabilities at their locations in the source code.

In reality, machine learning techniques are not yet widely used, compared to static analysis and other traditional approaches. Research has been done on machine learning for vulnerability feature detection, however, many studies work on synthetic code examples, use a very small code base as a dataset, or are only applicable to a small set of projects (see Section 3). Several widespread programming languages have so far not received any attention. And many proposed approaches only classify whole files, which is easier to achieve, but less useful for developers. Different techniques have been applied so far for representing code and for creating a model, but some of them (like the bag of words models and simple classification algorithms) are not able to capture the sequential nature and semantic structure of sourcecode.

In consequence, there is still a lot of work to be done. This work aims to contribute to the field by proposing VUDENC, a tool that leverages a deep neural network to learn vulnerability features from a large codebase mined from Github. VUDENC focuses on code in the programming language Python and learns only from natural code, in order to actually be applicable to real-life projects. It works directly on the sourcecode itself, leveraging word2vec to represent code in a numerical vector representation. VUDENC uses a fine-grained approach that looks at individual code tokens to be able to classify specific parts in the code. To model vulnerabilities, a long short term memory network is used, which has the ability to use an internal 'memory' to capture the semantic context of code tokens. VUDENC is a proof of concept that shows a promising approach for a vulnerability detection tool based on deep learning. Its applicability on code is demonstrated by various examples.

2. Background

2.1. Discovering vulnerabilities

The NIST defines a vulnerability as *weakness in an information system, system security procedures, internal controls, or implementation that could be exploited or triggered by a threat source* [NIS]; similarly, they are described as *...specific flaws or oversights in a piece of software that allow attackers to do something malicious: expose or alter sensitive information, disrupt or destroy a system, or take control of a computer system or program* in a standard handbook on software security assessment [DMS06]. Vulnerabilities can be viewed as a subset of defects [MHMW15], although they occur much less frequently. For example, Shin et al. [SW13] report that roughly 21% of files in Mozilla Firefox have defects, but only 3% have some kind of security vulnerability. How does one recognize code that contains a flaw relevant to security? One of the key issues in discovering vulnerabilities is the challenge of identifying **features** that correctly describe vulnerable code and distinguish it from clean code. There is a wide variety of different approaches [GS17], for example vulnerability prediction models based on software metrics, in which more high-level features, like code complexity, are used; anomaly detection models that aim to describe all possible *correct* behavior and spot deviations from that; and vulnerable code pattern recognition, in which features of the code itself are created that are typical for vulnerabilities, for example not checking user input before executing it. This last approach is widely applied in practice and will also be a core focus of this work.

Furthermore, methods can be divided in static analysis, which processes code without executing it, dynamic analysis, in which code behavior is analyzed at runtime, and hybrid approaches. Those three methods are described in the following sections, before the core concepts of Machine Learning approaches are introduced.

2.2. 'Traditional' approaches

2.2.1. Static analysis

In static code analysis, the form, structure, content or documentation [LSCL12] of a program is analyzed without executing it, using generalization and abstract rules [GS17]. Therefore, static approaches are able to name the precise cause for a vulnerability that was detected [GGS14]. They can discover threats stemming from issues with access control, information flow and (in)correct usage of APIs (e.g., cryptographic libraries) with a wide range of different algorithms [PCFY07]. Static analysis can identify good programming practices and potential defects, for instance, misused APIs, performance issues, deadlocks, and others [VG14]. Several different categories can be distinguished, including rule matching, pointer analysis, taint analysis, slicing, model checking, theorem provers, data-flow and control-flow analysis and dependency analysis [GGS14, LSCL12]. For an overview, also refer to the works of Chess et al. [CM04]. Static code analysis tools are frequently used to identify potential issues, and a wide

range of commercial and open-source tools are available. Without any doubt, those tools have a strong positive effect on code quality [LKB⁺18], and they allow developers to fix mistakes even before the program is run for the first time [GGS14].

The success of static analysis tools depends fundamentally on the quality of the underlying patterns, abstractions or rules that are used to identify problems, and the more complex software becomes and the more creative potential attackers are, the harder it is to define patterns of secure software. Although new rules can always be added to a static tool, if one hasn't been written about a particular vulnerability yet, the tool will be blind for this problem and never recognize it [CM04]. To create those patterns *automatically* appears to be nearly impossible [RSG⁺18, YLR12], and creating them manually is tedious and time-consuming, especially since technology and computer systems advance quickly, and therefore keeping track of all possible kinds of vulnerabilities is hard [MTL⁺17].

The accuracy of static analysis tools is measured by calculating the rate of false positives (reported problems that are in fact not an issue) and false negatives (missed problems). In an ideal, theoretical case, a static analysis tool could be *sound* (never reporting a false positive). However, following Rice's theorem, any nontrivial question about the features of a program can be reduced to the halting problem, and therefore it is fundamentally undecidable whether there are security vulnerabilities in a given piece of code [CM04], which means that there might always be false negatives (missed vulnerabilities) and the tool can never be sound and *complete* (discovering all vulnerabilities) at the same time. In practice, static analysis is limited by computational restrictions and the false positive rate. Especially the high false positive rate in many tools is a big obstacle [LKB⁺18], as those misclassifications cause developers to spend a large amount of time checking each one, which makes it harder to spot the actual problems. They might even get used to ignoring the warnings in those tools, causing actual bugs and vulnerabilities to be overlooked. As Li et al. [LZ05] phrase it, high false negative rates prevent a vulnerability detection system from being *useful*, and high false positive rates make it not *usable*.

2.2.2. Dynamic and hybrid analysis

Another option is dynamic program analysis, in which programs are executed and monitored at runtime and execution traces are systematically analyzed [STB13a]. Of course, not all possible inputs and execution paths can always be covered, so dynamic analysis can very well miss a lot of problems. A big practical problem is that dynamic analysis requires much more computational time and resources and is simply not possible in many circumstances, especially when analyzing larger software or software collections. Dynamic approaches are limited in their applicability by the large number of test cases that need to be run [AJ06].

In hybrid analysis, a dynamic approach is complemented with a static analysis to identify false negatives, or vice versa, combining the advantages and disadvantages of both approaches. For example, Balzarotti et al. check code for sanitization issues and

use a dynamic approach in which they first analyze the static properties of a program, and if this seems likely to be imprecise, they simulate the behavior with various test input strings [BCF⁺08].

2.3. Machine learning

As it has been pointed out, traditional approaches rely on features defined by human experts to detect vulnerable code, however, it is desirable to reduce the human workload and find more general, scalable and objective methods. This is where Data Mining and Machine Learning come in to play. Data Mining, sometimes also called knowledge discovery [Mit99], is simply the process of extracting knowledge from large sources of data. The process of data mining also includes building and maintaining the database, formatting, filtering and cleaning of the data and all tasks related to it [Mit99].

In this case, the data of interest is of course all information relating to code, bugs or vulnerabilities. Several official bug databases, such as the Bugzilla bug database or the Common Vulnerabilities and Exposures (CVE) database [CVE19], have been used in projects involving some form of information extraction from those sources [WMWM12]. But source code itself also contains much valuable information. Fortunately, due to the emergence of large online repositories and open-source software, it is comparatively easy to gain access to large amounts of code that can then be analyzed in some way. More about the process of extracting the data from software repositories can be found in Section 2.6.

Machine Learning describes computational algorithms that allow computer systems to solve problems without explicit programming. It allows them to learn from experience and form concepts from examples by extracting patterns from the raw data [GBC16]. Approaches are distinguished as supervised learning techniques, which use labeled data to allow a learning system to gain insight and create a model, unsupervised learning, in which the system finds patterns and structures in the dataset without guidance, and reinforcement learning, in which the system is provided with rewards and penalties after each step to train it dynamically [M⁺97].

The data presented to a machine learning algorithm has to be structured in a certain way, more specifically, a suitable representation has to be found. Each piece of information that is encoded in this representation can become part of a feature, depending on how the model is structured [GBC16]. Machine Learning provides the benefit of being independent of human judgment and expertise in generating features. Those approaches can analyze large repositories without requiring the source to be compiled, similarly to static analysis. However, they do not suffer from the false positive problem as much, as they allow for a finetuning of precision and recall, giving them an at least promising advantage over both static and dynamic approaches [RKH⁺18].

Machine Learning and Data Mining techniques have been used successfully in the area of security, for example, in defining firewalls, by analyzing potentially malicious code with anomaly-based detection methods. Elovici et al. [ESM⁺07] use decision trees, neural networks and bayesian networks to detect malicious code in network traffic, and

Schultz et al. [SEZS00] use, amongst others, a multi-naive bayes model on binary files to detect malicious executables passing through a mail filter, doubling the detection rate of purely signature-based methods.

The following sections describe a more sophisticated machine learning approaches that can be applied in vulnerability detection: deep learning with different types of neural networks.

2.3.1. Deep learning and neural networks




Fig. 1: Example illustration of a neural network

In many cases and for more complex problems, the representation of data (and the features) are not trivially determined, especially when the features are likely to be high-level and abstract. Deep learning is an approach that allows computer systems to learn more complicated concepts by defining them through their relation to simpler concepts, creating a hierarchy with many layers [GBC16]. In order to accomplish this, neural networks are created.

An (artificial) neural network is a system that consists of many simple parts, called neurons, in analogy to the neurons in the human brain. '*Deep Learning*' is simply the term applied to learning with neural networks that have a high number of layers of neurons [Nie15]. The neurons in a neural network are organized in layers and can either be activated or not activated. The first layer of neurons is called the input layer, the following layers are hidden layers, and the last is called output layer, however a neural network can also consist of just one single layer. In Figure 1, the network has six layers, including four hidden layers. The neurons of each layer are connected with neurons from the precedent and subsequent layer, and in case of input neurons, also with input variables from the neural network's environment, or if they are output neurons, with output variables. Following their own set of rules, the neurons react to the other neuron's activation patterns (and, if applicable, the inputs) by activating or

de-activating themselves, and consequently cause changes in the next layer of neurons, until the activation pattern of the final layer of neurons provides the output of the neural network. The point of learning in a neural network, or training it, is to find the right internal rules and triggers that make the network as a whole exhibit a desired behavior. Since the internal rules are described in terms of mathematical functions, this comes down to discovering the correct values for weights associated with different variables.

The number of neurons can vary between layers. If the output is only a single value, as it is the case in some classification problems, the last layer might only have one neuron. A fully connected or 'dense' layer is a layer in which every neuron of the layer before is connected with every neuron of the dense layer. In the illustration, layer 4 is a dense layer, all others are not dense, also called 'sparse'.

A dropout layer is a layer in which some randomly chosen neurons are simply ignored by setting their output to zero, so that they can't affect the next layer. In Figure 1, this is shown in layer 5. The percentage of neurons to ignore is set by a dropout parameter. This concept was introduced by Srivastava et. al. [SHK⁺14] in 2014 and helps to prevent overfitting, which might occur if the network relies too heavily on some nodes. By randomly 'turning off' a share of nodes, the cost function has to take the neighboring nodes more into account.

Deep neural networks have won numerous pattern recognition competitions, achieving superhuman abilities in some domains [Sch15]. Deep Learning has also been proven to be applicable to various software engineering tasks, including feature learning for defect prediction [WLT16], learning code suggestions [BRBR16], detecting malicious code in network traffic [ESM⁺07], detecting malicious executables [SEZS00], detecting malicious URLs and file paths with CNNs [SB17], or learning features for detecting bugs and faults [HLZ16, GPKS17a]. Several approaches have been able to capture structural patterns in code [DTP16] and have been successfully used to locate bugs [HLZ16, RKH⁺18].

2.3.2. Recurrent neural networks

Neural networks in which nodes on a layer only receive inputs from the precedent layer are called *feedforward* neural networks. Those networks take data as input, process it through the network ('from left to right'), and transform it into an output. The data never passes a given node of the network twice. Every time the input is fed to the network, it is mapped to the output in a deterministic way. Therefore, the whole network's output is only dependent on the input, and not on what it might have processed earlier. In practical terms, this means that the network can not take the context of the information they are processing into account. They see each input as completely independent from the next one.

But neural networks can also be constructed with an information flow from subsequent neurons to previous ones, essentially forming a circle in the network. Such networks are called *recurrent neural networks* (RNNs), and they use an internal state. This state




Fig. 2: Recurrent neural network. Left showing neurons with example connections, right simplified visuals for sequential data

can be saved over a longer time period, it can be modified and accessed by neurons in any layer. It essentially works as a memory. RNNs use this feedback loop to take previous outputs into account for the current operation, which allows them to model dependencies in the data. The consequences are huge, as the internal memory essentially enables RNNs to recognize patterns in data beyond a single sample, and thus greatly expands their capabilities. They can 'understand' time series data, semantic context in written natural text or in sensor readings, musical notes, health data or genome sequences. As Schmidhuber [Sch15] puts it, RNNs can be called the 'deepest of all NNs', and they are in principle able to create and process memories of any input pattern to recall it later. Figure 2 depicts a sample architecture of an RNN. Note that a single state layer of three neurons, and a subset of all possible connections is depicted. Of course, RNNs can also be constructed with more internal state layers influencing each other.

How can RNNs now be leveraged to classify source code and to find vulnerabilities? It is probably not a controversial assertion to state that a single code token, taken by itself, can hardly be classified as 'safe' or 'vulnerable', be it a variable, a built-in object of the language, or an operator. Only in the *context* of the tokens that came before and after, a judgment about the qualities of the code snippet becomes feasible. Source code tokens form a sequence that is connected by strong semantic ties: previous declarations and operations absolutely do have an influence on their successors. Just changing the initial value of a single variable can drastically alter the behavior of a complete program. Therefore, a type of recurrent neural network which has a 'memory', lends itself to modeling this type of data.

As a result of their memory capabilities, RNNs can also learn a much richer notion of similarity, for example, they are able to learn that two for loops with different counting variables and different end conditions are nevertheless similar constructs [ABDS18]. Those assumptions are supported by practical evidence. The works by White et al., [WVLVP15] and Dam et al. [DTGG16, DTP16] demonstrated that recurrent

neural networks can be effectively used to model source code, and in a later work, White et al. successfully model code clones with RNNs [WTVP16].

Unfortunately, RNNs have limits. Specifically, they are not able to model dependencies over a very long distance. Hochreiter [Hoc91] and Bengio et al. [BSF⁺94] show that recurrent networks with gradient descent of an error criterion become increasingly inefficient when the span between the place where a piece of information occurs first and the place where it becomes relevant later grows. This is mostly because of the problem of vanishing or exploding gradients.

2.3.3. Vanishing and exploding gradients

To give a short summary of a quite complex problem: The gradients of loss in a neural network are frequently calculated using backpropagation, coming from the deeper layers to the initial one. The gradients have to go through a number of layers using certain activation functions like, for example, the sigmoid activation function, which maps the weights to the range between -1 and 1, or the hyperbolic tangent function. When training an RNN, the gradients coming from deeper layers have to pass through continuous operations of this type, since the backpropagation algorithm uses the chain rule to compute the gradients. The further they are apart from the earlier layers, the more multiplications with small numbers occur, making the gradient decrease exponentially. This means that the information is lost and the model can not learn from it anymore.

If the output values of the activation functions are larger than 1, the opposite problem occurs: the gradients get larger and eventually 'explode'. In such a case, the trained weights in the network are changed drastically and might even become so large that they cause an overflow error and become NaN, causing the whole network to break down.

There are several different solutions to this problem, including gradient clipping, using different activation functions like the rectified linear activation function [GBB11], and a whole new kind of RNNs has been developed to model long term dependencies, called long short term memory networks (LSTMs).

2.3.4. Long short term memory networks

Sepp Hochreiter and Jürgen Schmidhuber presented the idea of LSTMs in 1997 [HS97]. They offer a solution to the vanishing gradient problem with their network architecture, which they achieve by using a gradient-based algorithm that enforces constant error flow through the internal states, preventing both exploding and vanishing. Refer to Figure 3 for an illustration of an LSTM.

LSTMs utilize a memory cell that stores accumulated context information. The memory content can be modified by sigmoid neural net layers called 'gates': an input gate, a forget gate, and an output gate, each of which can return a value between 0 and 1. A

value of 0 lets no information pass, a value of 1 means that all information is passed through. All those gates are trained as well, and influence the content of the memory cell and thereby the final output. This is how LSTMs can avoid vanishing or exploding gradients by learning which information should be kept or forgotten.

The forget gate is a sigmoid layer that has the purpose to filter out some information that shall no longer affect the cell state. For each component C_{t-1} of the memory cell's state, it generates a value between 0 and 1 that determines how much of it should be kept according to $f_t = \sigma(W_f * [h_{t-1}, x_t] + b_f)$, where h_{t-1} corresponds to the output of the previous step, x_t is the current input, and W_f and b_f are weights. This gate is supposed to allow information that is no longer relevant to be forgotten, so that it does not linger around and distorts the results of further steps.

The input gate is a multiplicative gate which is used to shield the memory contents from irrelevant inputs. Its purpose is to decide which information needs to be updated. It consists of two parts, both taking the resulting state of the previous step, the current input, and weights into account. One part uses a tanh gate to compute the new values: $C_t = \tanh(W_c * [h_{t-1}, x_t] + b_c)$ between -1 and 1, the other one is a sigmoid gate that decides which values are even put in the memory cell: $\sigma(W_i * [h_{t-1}, x_t] + b_i)$. Those are multiplied and then the result is added to the memory cell.

Finally, there's the output gate, which consists of a sigmoid layer which computes $o_t = \sigma(W_o * [h_{t-1}, x_t] + b_o)$ to filter which values are output, that is then multiplied to the values of the memory cells after they have been modified by a tanh function to scale them between -1 and 1. The result $h_t = o_t * \tanh(C_t)$ is now used as an actual part of the output of the LSTM and also fed back into the feedback loop, becoming the new h_{t-1} for the next step.




Fig. 3: LSTM network

The above description defines one typical architecture for an LSTM, however, a lot of different variations have been introduced. The forget gate was not included in the

very first draft of the LSTM, but developed later [GSC99]. Other variants of LSTMs include so-called 'peephole connections', which allow even the gate layers to take the current cell memory state into account [GS00], and gated recurrent units [CvG⁺14], which merge some gates and simplify and change the design of the LSTM.

long short term memory networks have shown some impressive capabilities, starting in the areas of image recognition and speech tagging. LSTMs have been shown to be able to learn how to automatically tie knots in minimally invasive open-heart surgery [MGW⁺08], to compose polyphonic music with intricate melodies and chords [KR19], and to analyze biological sequences to predict to which subcellular compartment a protein belongs [SSNW15]. The Open project AI also trained an LSTM to learn to give inputs to a robot hand to manipulate objects [Ope18] with impressive dexterity. They developed a bot based on LSTMs that can beat human players in Dota 2 [Rod18], and Deep Mind's Alpha Star was able to beat professional players in Starcraft II [Sta19]. Both games are complex and strategic real-time strategy games popular in esports. Those feats were called a 'huge milestone in advancing artificial intelligence' by Bill Gates [Lou]. In conclusion, the impressive capabilities of LSTMs provide a lot of potential for future applications, especially in modeling sequential data.

2.4. Representing code

When working with machine learning techniques on source code, many different paths can be taken to preprocess the code and represent it in a suitable format. Some approaches that are frequently used in research, and that will therefore be mentioned again later, are described in this section. However, this is by no means an exhaustive list of all possible methods.

2.4.1. Abstract syntax trees

Abstract syntax trees (ASTs) provide a hierarchical representation of either the code or the changes applied to the code [LKB⁺18], and can be used in different styles, omitting more or less tokens to simplify the tree. Yamaguchi et al. [YLR12] lay out several different approaches: only API nodes and function names can be used as nodes in the tree, cutting off everything else; subtrees of depth n with API nodes and placeholders can be used; or subtrees including API nodes, placeholders and syntax nodes. In most cases, however, many parts of the code are not represented in the AST.

Several researchers have gone to great lengths to create intricate ASTs from their code and operate on them [MTL⁺17, YLR12]. As a motivation, it has been stated that it is too challenging to mine patterns from plain text code [LKB⁺18] and the AST notation is therefore necessary. Note that there are counterexamples, showing that working on the plain text can also be a very effective approach [RKH⁺18, HSJW12].

2.4.2. Code as natural text

Code can also be viewed just as a sequence of words or tokens, with the added characteristic of resembling natural language. In the recent past, more and more research has applied Natural Language Processing (NLP) techniques to software code, treating it as natural text (see Section 2.4.2). Thus, code features can be extracted automatically, which opens up a wide range of applications [DTP⁺17].

The so-called 'natural hypothesis' of code holds that coding is a form of communication, and large code corpora manifest patterns similar to those in natural language. The first evidence for this assumption has been brought forward by Hindle et al [HBS⁺12]. Source code shares some characteristics with natural language text: repetitiveness of certain structures and common patterns, localness (repetitions occur in a local context), and long-term dependencies (think of `try` requiring an `except` later in Python, like the natural language statements *on the one hand* and *on the other hand*) [DTP16]. Because code is usually written by humans who tend to prefer conventional, familiar and typical code [ABDS18], patterns and typical structures inevitably emerge. Following this line of reasoning, machine learning models that are successfully used in natural language modeling can be applied to code as well, since the core strength of machine learning lies precisely in the ability to uncover and generalize patterns and handle noise. Furthermore, insecure code often contains several vulnerabilities of a similar flawed pattern, for instance, a missing check before a function call. Those vulnerabilities can be found easily if their similarity is recognized [YLR12]. Another important feature of code is its 'localness' [TSD14], meaning that there are certain (relatively short) patterns that occur very often in a local context.

Code, however, is different from natural language in so far that it is 'semantically brittle' [ABDS18], because small changes to code can already alter the functionality completely. It also contains highly complex structural information, for example, in nested loops and similar constructs. Despite those differences, NLP-inspired models have been applied successfully to software code.

2.4.3. Bag of words

A very simple representation that just takes code as text is the bag of words model. A data sample (such as a sentence) is represented by a collection of the singular tokens (or words) and the number of times they appeared. The order of tokens is not taken into account. To give an example for code: The code snippet `if (a > b or b > c):` would be represented with `{'a': 1, 'b':2, 'c': 1, 'if': 1, 'or': 1, '>': 2, ':':1, '(': 1, ')': 1}`.

2.4.4. N-gram models

One of the most popular language models is the n-gram model, and it has also been applied to model source code (see for example [PXN15]). In n-gram models, the last n tokens are taken into account and collected as an element. For example, for

$n = 2$, (a bigram model), the code snippet from above would be transformed into the representation $\{ '(a', 'a >', '> b', 'b \text{ or}', 'or b', \dots \}$, always looking at the last two tokens. For bigger n , this approach is able to capture some of the semantic context that lies in the order of tokens. N-grams are useful for discovering sequential patterns in code. However, they suffer from problems in their performance when dealing with high dimensionality, and therefore the context is mostly only very few code tokens [DTP16].

2.5. Embedding code in a numerical vector

In the end, if a neural network is to be trained on the data, the samples also have to be transformed in a numerical representation. As above, only a very short overview is given here.

For ASTs, there exist mainly handcrafted methods by researchers to transform the tree structure into a numerical vector.

2.5.1. One-hot embedding

In one-hot embedding, a vector of dimensionality n is used to represent each token. The value n is at the same time the total number of unique tokens that can be encoded. Each token is encoded by a vector consisting only of zeros and one singular '1' at the position that refers to this token. As a result, those vectors are extremely high in dimensionality and sparse. For example, in the code snippet used as an example in the previous section, a vector with 9 dimensions would be necessary, and 'a' could be encoded as $\{1,0,0,0,0,0,0,0\}$, 'b' as $\{0,1,0,0,0,0,0,0\}$, and so on.

2.5.2. Word2Vec embedding




Fig. 4: word2vec embedding

The word2vec embedding was developed in 2013 [MSC⁺13]. It also yields a unique vector representation for each unique token, however, it takes semantics into account

by giving similar tokens similar representations. Word2vec is a two-layer network and has to be trained on its own by providing it with a corpus of training data from which the semantics can be learned. Word2vec uses the ways tokens appear in combination and relation to each other to assign vectors with high cosine similarity to semantically similar tokens. If two words have nothing in common and no relation to each other at all, their vectors would have a 90-degree angle, and complete similarity or equivalence is expressed as a 0-degree-angle. For code tokens, it would be expected that, for instance, the vectors for `true` and `false` have higher similarity than the vectors for `return` and `while`, for that matter.

All vectors in the same embedding have the same dimensionality or number of cells. The encoding uses cells to represent certain semantic features. For example, in a word2vec model operating with the English language, the 3rd cell might indicate that a word represents some kind of object, and have a high value in the embeddings of words such as *apple* or *book*, but not in the embeddings of *such* or *leave*. However, what exactly the cells represent can only be guessed afterwards, as the representation is learned automatically by the word2vec model and not specified manually by any human. For most applications, it will be impossible to reverse engineer the function of each cell in a given word2vec model. Note also that there are many equivalent embedding models who work just as well on the same data.

Figure 4 shows a simplified illustration of a word2vec model. Python code tokens like `true` or `count` are transformed in a vector representation of dimensionality eleven, represented by the eleven colored cells for each token. The different numerical values that make up a vector are represented with colors to highlight the differences and similarities between the vectors visually. In this example, the vector representations of `true` and `false` share similarities in the first to fourth cell. Furthermore, one might, for example, guess that the 8th, 9th and 11th cell might encode some of the semantic of logical operations, as they have similar values in the token representation of `if` and `and`. However, it is not possible to define a specific, unequivocal meaning for each cell. To the very right of the figure, a simplified two-dimensional vectorspace is shown, containing the encoding for the words which are just symbolically represented as two-dimensional vectors. Tokens with related semantics have high cosine similarity, or a very small angle between them. Of course, in an actual word2vec implementation, the vectorspace can easily have more than 100 dimensions.

Interestingly, the numerical representation created by word2vec allows for meaningful arithmetics on the vectors. A famous example goes as following: a word2vec model is trained on an English corpus of words, for instance, many Wikipedia articles, or newspaper articles. The resulting embedding yields, among many others, numerical vectors for the words king, man and woman. If one takes the vector for 'king', subtracts the vector for 'man', adds the vector for 'woman', the resulting vector is closest to the vector representing - 'queen'. Although those results are fascinating, the work presented here does not need any kind of mathematical operation on the word vectors. However, for more information and illustrated examples, refer to [Jay19].

2.6. Mining Software Repositories

The performance of machine learning techniques depends greatly on the quality and characteristics of the training data [PXN15]. Therefore, acquiring a large collection of high-quality samples is the first and mandatory step of all machine learning on source code.

For many software systems, bugs and code changes are tracked with the help of version control and source code management systems [ZS17]. They also help share code between developers as well as giving access to the general public in the case of open-source projects. With the growth in size, number and popularity in openly accessible projects hosted on such platforms, it has become possible to gather large amounts of code and utilize data-driven approaches to discover vulnerabilities [RKH⁺18]. In contrast to works focusing on just a handful of projects to train and validate their models, potentially hundreds and thousands of repositories can be used to draw much more general conclusions. Furthermore, the repositories are generally real-life projects of actual applications, which makes them more relevant than vulnerability datasets with artificially constructed examples. Of course, this also means that a lot of low-quality code will be present. Besides mining the actual code, software repositories can also be investigated to gain insights about dependencies, commit messages, patterns of changes and various other metrics [LKB⁺18].

2.6.1. Approaches for mining software repositories

According to Kagdi et al. [KCM05], approaches can be divided in mining via annotations, via heuristics, via differencing, and via data mining. The first approach focuses on commit messages and metadata and analyzes, for instance, which classes change how often, which classes change together, how often changes occur in a particular subsystem and so on. The second approach focuses on heuristics about developers or code layout. In mining via differencing, the differences between two versions of source code are analyzed, for example, by determining how many functions or function calls are inserted or deleted, how many conditions are changed or how an abstract graph representation changes. Finally, with data mining, cross-connections between changes and associations are found. Zimmer et al. [ZZWD05] looked at combinations of functions that were often changed together and derived suggestions from there, preventing developers from making errors due to incomplete changes and predicting changes that are likely. Many of those approaches take high-level information into account, for example, classes, functions and metadata, while differencing and Data Mining can in principle be applied at a very fine level, down to single code statements.

2.6.2. Tools for mining software repositories

Mining software repositories is a task not suitable for manual work, therefore tools are used to assist with it. The main purposes of those tools are data extraction, data

filtering, pattern finding and prediction tools. Chaturverdi et al. [CSS13] provide an overview of pre-existing tools and datasets used in mining software repositories and find that data retrieval and preprocessing are frequently the most time-consuming task in the whole process. Their findings also suggest that many researchers decide to develop their tools and scripts themselves, while only some rely on already developed solutions.

2.6.3. Mining Github

Github is a provider of hosting services based on the version control and source code management system Git. The scale of the available data that can be found on the platform is enormous - in summer 2018, Github reached 57 million repositories (roughly half of them public open-source projects) with over 28 million users [Git]. At the time of this writing, a search for public Python repositories returns close to 2 million results. This is what Allamanis et al. [ABDS18] refer to as 'Big Code', and those massive amounts of data can be used for gaining insight into code features that occur in vulnerable code.

Data from Github has frequently been used in current research to train machine learning algorithms to detect bugs and vulnerabilities, see [ZS17], [RKH⁺18] and [LKB⁺18]. Of course, the base rate of commits that are relevant for security is relatively low, which is why efforts to gain a large dataset of vulnerable and fixed code must tailor their mining technique accordingly, for example, by using search terms relevant to security [ZS17].

2.7. Python vulnerabilities

Typical vulnerabilities in source code are sometimes shared between languages and application domains, while others only occur in some. For example, buffer overflows are typical in the C family of languages, and cross-site request forgery is only of interest in the context of web applications. The VUDENC approach described in this work is aimed at code written in Python. The following section will introduce and describe some typical vulnerabilities that are mentioned later. Note that all examples given are extremely simple and are just presented to illustrate the general idea, and exploits are often much more complex in practice.

2.7.1. Injection attacks

An injection attack is based on user input that causes unintended or dangerous behavior when interpreted or executed. Exploiting an injection vulnerability usually allows the user to make the interpreter (for example, the server or the operating system) execute arbitrary commands, and sometimes to access or alter data without authorisation [MT16]. Injection attacks can be prevented by checking all user input and applying so-called 'sanitization' techniques that convert harmful into harmless inputs, for instance, by filtering out special characters.

2.7.1.1. SQL injection

According to the OWASP foundation, SQL injections (also called SQLI) are among the top security vulnerabilities [OWA], belonging to the most common and serious vulnerabilities that are affecting web applications.

The Common Weakness Enumeration defines an SQL injection as following: *The software constructs all or part of an SQL command using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended SQL command when it is sent to a downstream component* [Com19d]. When user-controllable input contains SQL syntax that is not removed, it can be interpreted as an SQL statement instead of user data, and executed. This can be exploited to alter queries, for instance, to access files that should not be accessible or to add additional statements changing or destroying databases. Any kind of database-driven website is potentially in danger of becoming the target of such an exploit if their sanitization is not thorough.

The following snippet illustrates such a vulnerability.

```
(...)  
cur = db.cursor()  
name = raw_input('Enter name: ')  
cur.execute("SELECT * FROM users WHERE username = '" + name + "  
            ';"")  
(...)
```

If the user enters a legitimate request, like Tom, then all goes well and the query has no negative effects. However, if the user inserts a string containing SQL code, like Tom'; DROP TABLE users;;, the semicolon is interpreted as the end of the query and everything afterward is executed as a new command, deleting the entire database table. If the code is changed like this:

```
(...)  
cur = db.cursor()  
name = raw_input('Enter name: ')  
cur.execute("SELECT * FROM users WHERE username = %s;", (name,)  
            )  
(...)
```

The parameter passed after the comma is escaped, not directly substituted, in the place of the placeholder %s. Any SQL code tokens are removed, and the request can be executed safely. This is of course only one option to fix the problem, but it illustrates the general need for filtering and sanitizing the user-provided input.

2.7.1.2. Command injection

Quoting again the Common Weakness Enumeration: *The software constructs all or part of a command using externally-influenced input from an upstream component,*

but it does not neutralize or incorrectly neutralizes special elements that could modify the intended command when it is sent to a downstream component [Com19e]. This is another case where untrusted data is executed, but this time, it is not targeted at an SQL database, but instead a command that is executed by the machine that is attacked, for example, the server shell. This can give an attacker the capability to read, change or destroy files they should not be able to access.

The following minimal example for a command injection in Python 3 demonstrates the vulnerability:

```
import subprocess
filename = input('Please provide the path for the file: ')
command = 'cat {path}'.format(path=filename)
subprocess.call(command, shell=True)
```

If a user enters `file.txt`, the file is displayed with the `cat` command, but by adding a semicolon, the user can append other commands which are then executed as well without question. For example, entering `file.txt; ls` would cause the shell to print the current directory, and `file.txt; rm -rf /` would cause a considerable amount of damage. This vulnerability could have been prevented by a) not calling `subprocess` with `shell=True`, and b) sanitizing or filtering the input.

2.7.1.3. Remote code execution

The term 'Remote Code Execution' describes a similar situation to command injection, the difference being mainly that actual programming code is executed on the target system, while in command injection, it is an OS system command that is executed. Sometimes, it is also used to describe a hacking goal rather than a vulnerability, in the sense that exploiting a vulnerability grants the attacker the capability to execute arbitrary commands on a system.

2.7.2. Various types of session hijacking

The core idea of **session hijacking** is for an attacker to insert themselves into the connection between the server and the client, mostly by stealing or guessing a valid session token to pretend to be an authorized client [OWA14].

Session fixation works by tricking a user to start a connection with a client using a session ID that is set by a malicious third party, for example, by making the user click a link with the session ID as a parameter. Since the malicious third party then knows the session token, the active session can be accessed. The attacker might even be able to access a logged-in account [OWA14].

Cross-site scripting (see below) can also be used to steal a session token, enabling the attacker to hijack the client's and server's shared session.

Man-in-the-middle attacks also belong in the session hijacking category. An attacker tries to intercept a communication between two systems, perhaps a client and a server,

posing towards both sides as their connection partner. The attacker effectively acts as a proxy and can therefore access the content of the communication and sometimes even modify it [OWA15]. The use of proper encryption and certificates prevents man-in-the-middle attacks.

The term **replay attack** describes an attack in which a valid part of communication between two parties (like client and server) is recorded and later sent again by the attacker, who is posing as the original sender of the transmission. If no proper protection mechanisms are in place (mainly secret one-time session IDs), the attacker can gain access to functionality and information that was only intended to be accessible for the original sender.

2.7.3. Cross-site scripting

Cross-site scripting, often abbreviated as XSS, is one of the most important vulnerabilities in web applications. It appears frequently in the OWASP top ten vulnerabilities [OWA].

In cross-site scripting, unsanitized data is also the root of the problem. This time, custom code inserted by a user is added to a website or a URL that is then delivered to other users, who will receive the code as part of the website and execute it in their browser. The CWE defines Cross-site Scripting as following: *The software does not neutralize or incorrectly neutralizes user-controllable input before it is placed in output that is used as a web page that is served to other users* [Com19a].

A classic example (in this case stored cross-site scripting) is a guest book in which arbitrary input is allowed. A guest can leave plain text, or a piece of Javascript that is then permanently stored on the site and delivered to other visitors, who will receive and execute the Javascript code. Of course, many variations of this are possible, for instance, using different kinds of input options and creating executable code with Flash and other languages. Another example is an email with a link to another website that contains malicious Javascript within the URL, which will then be executed upon following the link. To prevent XSS attacks, user-generated content has to be sanitized, using functions such as `html_escape` and others.

An example taken from the works of Micheelsen et al. [MT16] shows a vulnerable snippet of Python code using the web framework Flask. The input 'param' is taken from the user and inserted in the result page via the `html.replace` function.

```
@app.route('/ XSS_param', methods = ['GET'])
def XSS1():
    param = request.args.get('param', 'not set')
    html = open('templates / XSS_param.html').read()
    resp = make_response(html.replace('{{param}}', param ))
    return resp
```

2.7.4. Cross-Site request forgery

The CWE defines Cross-site request forgery as follows: *The web application does not, or can not, sufficiently verify whether a well-formed, valid, consistent request was intentionally provided by the user who submitted the request* [Com19c] and further explains: *When a webserver is designed to receive a request from a client without any mechanism for verifying that it was intentionally sent, then it might be possible for an attacker to trick a client into making an unintentional request to the webserver which will be treated as an authentic request. This (...) can result in exposure of data or unintended code execution.* To illustrate this with an example: A badly protected website might receive a POST request from a user which contains parameters to change the password. This request could have been generated by the user intentionally clicking on a html form that generates the request - or because a malicious person tricked the user into clicking a link with the same parameters that triggers the same POST request. The password is changed either way, and the user might be locked out of their account while the attacker has access. This kind of attack can be prevented by using tokens that are exchanged between client and server that are secret and unique for each request. The following example shows how a token could be used to prevent XSRF attacks.

```
from oauth2client import xsrfutil
(...)
def CheckToken(self, *args, **kwargs):
    user = users.get_current_user()
    token = str(self.request.get('xsrf_token'))
    if not user or not xsrfutil.validate_token(_GetSecretKey(),
        token, user.user_id()):
        self.abort(403)
```

2.7.5. Directory traversal / path disclosure

A path traversal or directory traversal vulnerability occurs when the user is able to manipulate input in a way that paths of a file system are exposed that were not meant to be accessed. As defined by the CWE: *The software uses external input to construct a pathname that is intended to identify a file or directory that is located underneath a restricted parent directory, but the software does not properly neutralize special elements within the pathname that can cause the pathname to resolve to a location that is outside of the restricted directory* [Com19b]. A typical case of this vulnerability is a website that displays a file for which the path is specified in a URL parameter. By changing this parameter to contain some `'../..'`, the attacker can navigate the file system and possibly display files that were not meant to be accessed.

Assuming that `filepath` is a variable provided by the user, the following example shows a vulnerable code segment.

```
import os.path
(...)
```

```
prefix = '/home/user/files/'
full_path = os.path.join(prefix, filepath)
read(full_path, 'rb')
```

A possible way to fix this would be to use methods like `os.path.commonprefix` or `os.path.abspath` on to check whether the prefixes are still the same.

2.7.6. Open redirect vulnerabilities

As the name suggests, open redirect vulnerabilities occur when a website that is supposed to redirect a user gets the target of the redirect from a parameter value. When this URL paramter is manipulated, the redirect sends the user to the wrong page, for instance, a malicious page crafted by an attacker. The Python web framework django contains a check called `is_safe_url` (later renamed to `url_has_allowed_host_and_scheme`) which can be used to perform a check to prevent open redirect vulnerabilities as shown in the following examples.

```
next_url = request.GET["next"]
return next_url
```

```
from django.utils.http import is_safe_url
(...)
if is_safe_url(request.GET["next"]):
    next_url = request.GET["next"]
    return next_url
```

2.7.7. Other terms in relation to vulnerabilities

There are more terms relating to cyber security and vulnerabilities that can be used to find relevant commits on Github.

Tampering refers to the act of modifying data without having the right to do so. The term covers destruction and manipulation of data in transit and at rest, essentially referring to all unauthorized data modifications. It is frequently used in the context of data transmissions.

The term **sanitization** has come up before. It refers to the process of cleaning and modifying input data to remove possible dangers. It is mostly done by checking for certain patterns and characters that could lead to undesired behavior, for example, javascript code included in an online guestbook entry, or SQL queries in a search bar.

3. Related Work

So far, the basic concepts necessary for this work have been described. The next section describes previous work in finding vulnerabilities and also attempts a classification, although there are many different criteria under which approaches can be compared. The advantages and disadvantages of the previous approaches are described, and VUDENC is categorized among them.

3.1. Vulnerability prediction based on software metrics

What are the features to use when predicting whether code is vulnerable or not? For a long time, the most commonly used features were found outside the source code itself, in the form of software and developer metric. Those include size of the code (LOC), cyclomatic complexity, code churn, developer activity, coupling, number of dependencies or legacy metrics [MHMW15]. Such metrics have been universally used as features for building fault prediction models [HBB⁺11] and are highly relevant in the field of software quality and reliability assurance. To give just one example, Nagappan et al. [NMB08] use organizational metrics to predict faults in software. It seems plausible that those metrics could also be used in vulnerability prediction - however, there are some problems with that.

First, it is possible that two pieces of code have the same metrics (for instance, complexity) but a totally different behavior, leading to a different likelihood to be vulnerable. In addition to that, they also tend to not generalize well from one software project to the next. The strongest criticism is that such metrics do not capture the semantics of the code [SW08], and this approach does not take the actual source code, the program behavior, or the data flow into account. The approach is effectively applying a foregone conclusion that certain meta features will be related to security flaws, which is not necessarily true [HSJW12]. For example, many vulnerabilities can also arise in very simple programs. In fact, often the trivial or direct solution to an algorithmic problem does not contain the safeguards and precautions that are required for preventing exploits, which is precisely the reason why software developers who are under time constraints or lack experience with security considerations run into problems. Code complexity is not an ideal predictor for security flaws, and similar arguments and counterexamples can be found for the other metrics as well. However, it must be acknowledged that at least *some* insights can be gained from software metrics. This is illustrated with the following works that use machine learning approaches utilizing code metrics to predict the occurrence of security-related flaws in software.

Shin et al. [SW08] use nine complexity metrics to predict vulnerabilities in Javascript projects, achieving a low false positive rate, but a relatively high false negative rate. In a later work [SMWO10], the authors leveraged code complexity, code churn and developer metrics to predict vulnerabilities, achieving 80% recall and 25% false positives with linear discriminant analysis and bayesian networks.

Using complexity, coupling and cohesion metrics (commonly abbreviated as CCC), Chowdhury et al. [CZ11] try to predict software vulnerabilities using approaches that have been applied to fault detection before. They conduct a study on releases of Mozilla Firefox and use decision trees, random forest, logistic regression, and naive bayes models to predict vulnerabilities, achieving around 70% precision and recall, respectively. Zimmerman et al. added even more metrics to the list: they investigated code churn, code complexity, code coverage, organizational measures and actual dependencies [ZNW10]. They found a weak, but statistically significant correlation between the investigated metrics and used logistic regression to predict vulnerabilities based on them, focusing on the proprietary code of Windows Vista. The metrics were able to predict vulnerabilities with a median precision of 60%, but with a relatively disappointing recall of 40%. Neuhaus et al. [NZHZ07] looked at import statements in the Mozilla project, reporting an average precision of 70% and recall of 40% when predicting vulnerabilities by import statements with support vector machines. Yu et al. [YTW19] take many different possible features into account, including software metrics such as number of subclasses, or number of methods in a file, as well as crash features and code tokens with their tf-idf scores. Their approach is therefore a mix of many different angles. They predict vulnerabilities on the level of whole files and achieve very satisfying results in narrowing down the volume of code that has to be inspected by human experts to find a vulnerability. Other researchers have been able to make predictions just with commit messages. Zhou et al. [ZS17] leverage a K-fold stacking algorithm to analyze commit messages to predict whether a commit contains vulnerabilities, reportedly with great success. In contrast, Russel et al. [RKH⁺18] found that both humans and Machine Learning algorithms performed poorly at predicting build failures or bugs just from commit messages. The proposed approach, VUDENC, does not take external code metrics into account, but learns features directly from the source code itself.

3.2. Anomaly detection approaches for finding vulnerabilities

Anomaly Detection refers to the problem of describing normal and expected behavior and detecting deviations from it. The assumption is that code not conforming to the implied rules can often be the cause of a defect. Data mining techniques have been used to analyze source code and extract normal coding patterns. To name one example, Li et al. [LZ05] developed a tool called PR-Miner that can find code patterns in any programming language and that has been proven to be quite useful. Their approach, which relies mostly on associating programming patterns that are used together with each other, is independent of any chosen language and violations reported by their tool have been confirmed as bugs in Linux, PostgreSQL and Apache. A fundamental problem is, however, that bugs that are *themselves* typical patterns (and therefore occur frequently in the code) are systematically overlooked, resulting in common flaws not being detected [YLR12]. At the same time, rare programming




Fig. 5: One way to structure different approaches for vulnerability detection

patterns or API usages can be flagged as false positive simply because they do not occur often.

Several of the anomaly detection approaches have quite high false-positive rates [GS17]. Specifically for finding security vulnerabilities (and not mere bugs that do not have any implication for security), anomaly detection in code is not a straightforward approach, since it is hard to tell when a violation of common code patterns has an implication for security and when it does not.

The approach in this work differs from typical anomaly detection insofar as explicit labels are used to train a model on vulnerable and (mostly) secure code, thereby avoiding the questionable assumption that 'typical' equals 'correct'. It belongs in the next category: vulnerable code pattern analysis.

3.3. Vulnerable code pattern analysis and similarity analysis

Since the goal is to find vulnerabilities, in comparison to learning about abstract metrics or the definition of correct code, it seems almost like the most natural choice to just try to answer the question: What does vulnerable code typically look like? There are two slightly different strategies to answer that question: vulnerable code pattern analysis

and similarity analysis.

Similarity analysis does exactly what the name suggest. Given a vulnerable code snippet, the goal is to find the most similar code fragments, assuming that they are at risk to share the vulnerability. This approach works best for identical or nearly identical code clones in which the inherent structure of the compared code fragments is very similar [LZX⁺18], a situation that occurs quite often, especially through code sharing in the open-source community.

In vulnerable code pattern analysis, vulnerable code segments are analyzed with data-mining and machine-learning techniques to extract their typical features. Those features represent patterns, that can then be applied on new code segments to find vulnerabilities. Most of the works in this area gather a large dataset, processes it to extract feature vectors, and then uses machine-learning algorithms on it, as described by Ghaffarian et al. [GS17].

Both approaches are typically applied to source code without executing it, as a static analysis, although some researchers also combine their approach with a dynamic analysis. The crux of the matter is that in contrast to 'traditional' static analysis, the features are created automatically or semi-automatically, eliminating the need for subjective human experts. By learning directly from a dataset of code what vulnerable code entails, an unbiased model can be built.

In many cases, those approaches also rely on a very rough granularity, classifying whole programs [GGU⁺16], files [SMWO10], components [NZHZ07] or functions [YLR11], which makes it impossible to pin down the exact location of a vulnerability. Some, like Li et al. [LZX⁺18] and Russell et al. [RKH⁺18], use a more fine-grained representation of the code. Furthermore, the approaches differ in many aspects:

- **Language:** what language is subject of the classification efforts
- **Data basis:** does the data stem from real-life projects or from synthetic databases (for instance, benchmark data sets).
- **Labels:** how are the labels for the training data originally generated
- **Granularity:** is the code evaluated on a rough granularity (whole classes or files) or a fine granularity (lines or tokens)
- **Machine Learning Approach:** what class of neural network or machine learning approach is used (CNN, RNN, LSTM, etc.)
- **Vulnerability types:** which kinds of vulnerabilities are detected
- **Size of data set:** how many functions, projects, classes etc. make up the dataset
- **Scope and applicability:** Has the model been trained on a single project and can it only classify files within that application, or is it generally applicable to any code from a large variety of sources

First, some basic approaches using various machine learning techniques will be described. Afterwards, approaches that leverage deep learning are examined in more detail.

Morrison et al. [MHMW15] examine security vulnerabilities in Windows 7 and Windows 8 with various machine learning techniques including logistic regression, naive bayes, support vector machines and random forest classifiers, with relatively disappointing results, achieving very low precision and recall values.

In a very straightforward approach, Pang et al. [PXN15] take labels from an online database and use a mix of feature selection and n-gram analysis to classify whole java classes as vulnerable or not vulnerable. Working on a relatively small dataset of four Java android applications, they apply a simple n-gram model (see Section 2.4.4) in combination with feature selection (or better: ranking) methods to combine related features and reduce the number of irrelevant features taken into account. Afterwards, they pick support vector machines as learning algorithm, achieving around 92% accuracy, 96% precision and 87% recall within the *same* project, and values around 65% in cross-project prediction (training on one project and trying to classify vulnerable files in another one).

Shar et al. [ST13] apply machine learning to reduce false positives in spotting XSS and SQLI vulnerabilities in PHP code. They first pick some code attributes manually and then train a multi-layer perceptron to complement static analysis tools. Compared to a static analysis tool, they detected less vulnerabilities, but also achieved lower false positive rates in an overall satisfying result. In their later work [STB13b], they use a hybrid approach including dynamic analysis, improving their previous results notably, as tested on six big PHP projects. They also experiment with unsupervised predictors, which are less accurate, but still a promising area of research.

Hovsepyan et al. [HSJW12] analyze raw source code as text. As their example, they picked an Android email client written in Java and mostly focused on analyzing the source code like a natural language, processing files as a whole. After filtering out comments, they transform files in feature vectors made up from Java tokens with their respective counts in the file (in a bag-of-words-style approach). Those feature vectors are classified in a binary scheme as vulnerable or clean. Finally, the classifier (a support vector machine) is trained to predict if a file is vulnerable. The accuracy achieved by this classifier is 87%, with 85% precision and 88% recall. Their success shows that much insight can be gained without elaborate models of code representation by just taking the source code as natural text and analyzing it as-is. Unfortunately, their work is limited by the application on a single software repository. In a later work, they used decision trees, k-nearest-neighbour, naive bayes, random forest and support vector machines for a similar task [SWHJ14].

3.3.1. Deep learning for vulnerability prediction

As it has been stated in sections 2.3.1 and 2.3.2, a number of works have successfully leveraged deep learning models to automatically learn features for fault prediction [IEE15, IEE16, WLT16]. How this approach can be applied to vulnerability detection is demonstrated by the following works.

Recurrent neural networks and convolutional neural networks are used by Russell et al. [RKH⁺18], who scrape a big codebase of C projects from Github, the Debian Linux distribution, and 'synthetic' examples from the SATE IV Juliet test suite, collecting a database of over 12 million functions in total. They use three different static tools to generate the binary labels 'vulnerable' and 'not vulnerable' for the functions and a randomly initialized one-hot embedding for lexing. For the core part of their work, convolutional neural networks and recurrent neural networks are explored for feature extraction, followed by a random forest classifier (as the neural networks did not perform well on classification on their own). The convolutional neural networks performed best, allowing for finetuning of precision and recall against each other. With their work, Russell et al are not only among the first researchers to use deep representation learning directly on source code from a *large* codebase, but they are also able to use a convolutional feature activation map to highlight the suspicious parts in the code, instead of just classifying a whole function as vulnerable.

Liu et al. [LKB⁺18] base their work on the assumption that violations that are routinely fixed are actually true positives, while those that are ignored are likely to be either not important, or false positives. They investigate changes from 730 Java projects, apply the static bug detection tool Findbugs to find changes that are fixing a violation reported by that tool, and track the violations throughout the different versions to find whether they are fixed or ignored. Using this data, they can analyze which violations reported by the tool are routinely ignored over many revisions, and which others are fixed almost immediately. They collect the code patterns corresponding to violations based on representation with an abstract syntax tree. Instead of training a binary classifier on 'vulnerable' or 'not vulnerable', Liu et. al use an unsupervised learning approach to extract features of code, focusing specifically on patches to learn fix patterns. Their approach could therefore be classified as a type of similarity analysis. The found code patterns are encoded into a vector space using word2vec, the discriminating features are learned with a convolutional neural network, and an X-means clustering algorithm is used to cluster violations with learned features. They find that while security-related violations are relatively rare (0.5% of violation occurrences), they are widespread across 30% of the projects. Also, the works show that only a small fraction of violations is fixed. Looking into the code patterns of fixed violations, Liu et. al find that for 90% of the violations, a chunk of just 10 lines of code or less is sufficient to capture the relevant context. The CNN yields patterns that are largely consistent with the tool's violation description, and that are used to generate fix patterns. Roughly one third of a test set of violations can be fixed with one of the top five presented fix patterns. Liu et. al also chose 10 open-source Java projects to make suggestions to based on fixes proposed from their tool, and of the 116 suggestions, 67 have been immediately merged. Of course, their tool can only suggest patches that correspond to fix patterns previously found in the database.

3.3.2. Long short term memory networks

Although Gupta et al. [GPKS17a] and Dam et al. [DTGG16] have already shown that long short term memory Networks are highly suitable for modeling source code and fixing errors in C Code, the latter were probably the first to leverage LSTMs networks to automatically learn features for predicting *security vulnerabilities* [DTP⁺17]. They take a publicly available dataset consisting of 18 Java applications and extract the code of all methods within the source file, using Java Abstract Syntax Tree and replacing some tokens with generic versions. They then use LSTMs for training syntactic and semantic features and a random forest classifier. They achieved around 91% precision for within-project prediction of vulnerabilities, and on average, after training a model on one project, it achieved more than 80% precision and recall in at least 4 of the other 17 projects.

The tool VulDeePecker is a deep-learning based vulnerability detection system [LZX⁺18]. The authors present the first dataset of vulnerabilities intended for deep learning approaches, which is not a database of natural code, but stems from popular C and C++ open-source products, derived from the National Vulnerability Database and the Software Assurance Reference Dataset maintained by the NIST. Li et. al strive to create a tool that does not rely on humans to define features and still provides a satisfyingly low rate of both false negatives and false positives. They split files into so-called code-gadgets, semantically related lines of code that are grouped together, focusing on key points of library and function API calls in a relatively complex mechanism. They only evaluate two different kinds of vulnerability: buffer errors and resource management errors (which both have a lot of subtypes). Li et al decided on bidirectional long short term memory networks on different subsets of their data, achieving a precision of around 87%, with improved results if the network is trained on manually selected function calls. They also managed to detect four previously unknown vulnerabilities in software projects.

Harer et al. [HOL⁺18] trained LSTM networks to detect and fix vulnerabilities in the synthetic SATE IV code base of C vulnerabilities. They were able to leverage a sequence-to-sequence approach to produce fixes for found vulnerabilities, although it is hard to measure and compare their success. Similarly, Gupta et al. [GPKS17b] use RNNs in a sequence-to-sequence setup to fix buggy C code, although they are not focusing on security vulnerabilities, fixing 27% of their programs and 19% partially.

3.4. Contributions

VUDENC expands the work in the area of vulnerable code pattern analysis. A large dataset of source code written in Python is collected from Github, filtered, preprocessed, and labeled based on the information from commits. Several different types of vulnerabilities are taken into consideration, and source code from many different projects is collected. The resulting dataset of natural code containing vulnerabilities is made available for further research. Samples are generated by dividing the code in overlapping snippets that capture the immediate context of some tokens. The samples are embedded

in numerical vectors using word2vec. A long short term memory network is trained to extract features, and then applied to classify code that was not used in training, highlighting the exact locations within the code that are potentially vulnerable. The approach in VUDENC is in some way distinct from all other works that have been carried out so far.

In contrast to the approaches by Li et al. [LZX⁺18], Pang et al. [PXN15], Hovsepyan et al. [HSJW12] and Dam et al. [DTP⁺17], VUDENC uses a wide code base and not only a select number of projects. The predictions are not only applicable within the same file or the same project, but generalize to any other source code.

In further contrast to those four works, a fine granularity is chosen. The mentioned works all classify whole files, or in the case of Li et al. [LZX⁺18], only take API and function calls into account. VUDENC is more comparable to the work of Russell et al. [RKH⁺18] and Ma et al. [MTL⁺17], as vulnerabilities are not just detected on the file level, but in specific positions within the code, which is presumably more useful for developers. In VUDENC, different tokens can even be highlighted in different colors depending on the confidence level of the classification.

Similarly to the research by Hovsepyan et al. [HSJW12], and in contrast to works by Ma et al. [MTL⁺17], Yamaguchi et al. [YLR12] and Liu et al. [LKB⁺18] this work does not transform source code into a structure like an abstract syntax tree, but takes it as plain text. It follows the natural hypothesis and aims to use as little assumptions as possible, leaving the extraction of features from the source code entirely to the trained model.

The labels for the dataset are generated not by using a static analysis tool, as it is the case in the works of Russell et al. [RKH⁺18], Dam et al. [DTP⁺17] and Hovsepyan et al. [HSJW12]. The whole idea of VUDENC is to be independent of manually designed features that are the main limitation of the static analysis tools of the past. The goal is not to model an existing static tool, but to learn features without initial assumptions. Therefore, VUDENC relies on a similar assumption as Liu et al. [LKB⁺18], namely that code that was patched or fixed has a high chance of having been vulnerable before the fix. The labeling is based purely on the Github commits, which (at least theoretically) allows the discovery of vulnerability patterns that have not yet been manually included in static analysis tools.

The dataset used as a basis for training is made out of natural code from real-life software projects, and not from synthetic databases designed to provide clear examples for vulnerabilities. This makes the whole task harder, as real-life code is a lot messier and less clean than the synthetic code. In this aspect, VUDENC differs from the approaches chosen by Russell et al. [RKH⁺18] and Li et al. [LZX⁺18]. However, it also makes VUDENC agnostic towards specific projects with their own characteristics, and therefore to an extent robust against the threats to validity that would result from a more narrow approach.

The machine learning model used is a long short term memory network, the same kind as used by Li et al. [LZX⁺18] and Dam et al. [DTP⁺17]. In comparison to the latter, the architecture and preprocessing of data is much simpler in VUDENC. Many other

approaches use either different deep learning models (CNNs and RNNs in the works of Russell et al. [RKH⁺18]), or entirely different machine learning approaches (support vector machines in the case of the contribution by Pang et al. [PXN15]).

To conclude the list of contributions, the focus lies on code written in Python, in contrast to most other research projects that are mostly concerned with Java, C, C++ or PHP. No other approach was found that uses remotely similar techniques and works with Python. Of course, the proposed approach of VUDENC could also be applied to other languages. The word2vec model trained for Python is another contribution of the work.

It can be concluded that VUDENC is distinct from previous research in many ways, although it also shares some characteristics with other works. The specific approach chosen for this work is the result of the design decisions that are justified in the following section, in which the methodology is described in detail.

4. Methodology

In this section, the preliminary guiding principles for the approach taken in this work will be discussed, including the scope, sources of data, choices of data representation and selection of neural networks for the task.

4.1. Architecture

To give a brief overview: The VUDENC approach works on code tokens and their surrounding tokens to understand the context in which a token appears. The code is embedded in numerical vectors using a word2vec model. Afterwards, an LSTM network is used to recognize features of vulnerable code, and (with a final dense layer with a single output neuron), to classify code as vulnerable or not vulnerable.




Fig. 6: Architecture of the model

4.2. Choosing a programming language

Some of the previous works have trained their models on very small corpora, as pointed out by Bhoopchand et al. [BRBR16]. Those who worked on a large dataset have usually been focusing on statically-typed languages like Java, C and C++ [BKA⁺07, RKH⁺18, LKB⁺18, DTP⁺17, RSG⁺18]. Several groups of researchers were kind enough to present their databases as publicly available training sets. However, the programming language Python has not received such attention. According to several online rankings, Python is one of the most important and popular programming languages [Aye19, Vid19], and it is the third most used language on Github [Git19b], after Javascript and Java. Although Python is known for its usefulness in data science and statistics, this is not its only area of application. With popular web frameworks such as Django and Flask, Python is used to create dynamic websites and web apps, and is subject to the wide range of security problems concerning this domain.

4.3. Data source

In previous works, the researchers were able to get better results in predicting vulnerabilities if they were applying their model to code from the same project that it had been trained on [PXN15, DTP⁺17]. Trying to use a model trained on one project to find vulnerabilities in a different project (cross-project prediction) resulted in a sharp decrease in precision and recall. It can also be stated that in works by Russel et al. [RKH⁺18] and Li et al. [LZX⁺18], the best results were achieved when working on a (partially) synthetic data set, as opposed to code from 'real' projects.

Nevertheless, VUDENC aims to make use of a large dataset of real-life sourcecode and train a model that can be applied to any code, not restricted to a single project, because such a vulnerability detection tool appears to be the most desirable and end result.

The full dataset is gathered from projects publicly available on Github, for several reasons: First, Github is the largest host of source code in the world, so it is unlikely that the amount of available useful data will be too little for this application. Second, in contrast to synthetic code bases, nearly all projects on Github contain 'natural' source code in the sense that they are actual projects used in practice. And third, the data is public, making it easier to re-examine and replicate the work, which is not as easy in works that focus, for instance, on proprietary code.

Since Github is mainly also a version control system, it is centered around commits, and as Zhou et al. [ZS17] suggests, it is practicable to look at commits to detect vulnerabilities. Commits that fix a bug or vulnerabilities can be described as patch, consisting of a pair of versions, one buggy and one updated and (hopefully) correct. By analyzing the differences between the old and the new version, vulnerable code patterns can be learned.

4.4. Choosing vulnerabilities

To cover common vulnerabilities, the CVE [CVE19] and lists of typical security issues like the OWASP Top 10 [OWA] are taken into account. Furthermore, related works [ZS17, MNC14, YLR12] are studied to get an overview of the typical vulnerabilities that should be covered. The goal is first to find vulnerabilities that are relevant enough to be frequently fixed on Github (otherwise there would be not much of a dataset to gather), and second also to assure that the work is comparable with other related approaches.

4.5. Labeling

Similarly to Li et al. [LZX⁺18], the data is labeled according to information from the commit context. Since the data consists of security-related fixes, the sections of code that were changed or deleted in such a commit can be labeled as vulnerable, and the version after the fix, as well as all the data surrounding the changed part, is labeled as (possibly) not vulnerable. Of course, there are cases in which a fix does not

actually solve a problem, or there are several vulnerabilities at the same time, or even a new vulnerability is introduced. All those are disregarded by this approach, as the main focus here is easy automation without the need for human expert oversight. (In contrast to the approach taken by Li et al., this work does not include a manual check afterwards, as it would be impractical for the size of the dataset). Furthermore, it needs to be stressed that everything labeled as 'not-vulnerable' is supposed to be interpreted as 'at least not proven to be vulnerable'.

4.6. Representation of source code

4.6.1. Choosing a representation

Simple approaches like bag of words representations have yielded mediocre results in the past, and are by design not able to capture the semantic context of code (see Section 2.4.3). They can be rejected immediately.

Liu et al. [LKB⁺18] argued that an AST representation is necessary to mine patterns from code, while others like Russel et al. [RKH⁺18] and Hovsepyan et al. [HSJW12] demonstrate that this is not necessarily the case, as code can also be modeled with textual representations. Furthermore, Dam et al. [DTP16] argues that, alongside with human-engineered features and software metrics, ASTs might not be able to capture the semantics hidden deeply in source code.

As described in Section 2.4.2, code is sequential data similar to natural text, and long short term memory networks are designed precisely for the task of modeling such types of data, with outstanding results (see Section 2.3.4).

Taking all this into account, VUDENC is designed to work directly on source code as text. Since snippets of code are taken as samples, the approach could be called a version of an n-gram approach, although the length of the snippets is much longer than usually in n-grams (covering not only a handful of tokens, but several lines of code). To account for the localness property of code [TSD14], emphasis will be placed on the context around each code token for learning features.

4.6.2. Choosing granularity

As Morrison et al. [MHMW15] describe, binary-level predictions and analysis on the level of whole files provide little insight, as developers often already know which files might be sensitive to security vulnerabilities, and developers strongly prefer a much finer approach, if possible at the level of lines or instructions.

Dam et al. [DTP⁺17] provide some convincing examples at the beginning of their work, arguing that there exist files with similar metrics, similar structure and even nearly the same tokens, of which one might be clean and another might be vulnerable, despite the similar metrics. A top-down perspective, looking at whole files, can therefore not be as promising as an approach that 'zooms in' to analyze small snippets of code individually. VUDENC implements an approach of fine granularity, looking at each token in the

code as well as its context. Only this makes it possible to pin down the exact location of the vulnerability.

4.6.3. Preprocessing the code

In languages such as Python, source-code level tokens consist of identifiers, keywords, separators, operators, literals, and comments. While some researchers exclude separators and operators [PXN15], others strip out a lot of tokens and keep only API nodes or function calls [YLR12]. This work strips out comments, as they do not influence the behavior of the program. Even if they might contain some predictive value for the vulnerability status, it is not the kind of information that should be learned by the model, which is intended to detect vulnerable code itself. Otherwise, the source code is kept exactly as it is. Hovsepyan et al use a similar approach [HSJW12]. No variables or literals are replaced by generic names, but everything is taken exactly the way it is represented in the code.

4.6.4. Choosing the vector embedding




Fig. 7: transforming code in vectors

Neural networks work on numerical vectors with an uniform size, and therefore it is necessary to represent code tokens as vectors that retain the semantic and syntactic information that was present in the code. In addition, the variables of the vector have to be chosen in such a way that the vectors are manageable in size.

While Li et al. [LZX⁺18] use carefully crafted code gadgets, Hovsepyan et al. [HSJW12] employ a simple bag-of-words approach, Russel et al. [RKH⁺18] train a randomly initialized one-hot-embedding, and Liu et al. [LKB⁺18] leverage word2vec. As already described in Section 2.5.1, a naive one-hot encoding is a possible way to approach this, however, it is completely blind for the semantic meaning of tokens. In contrast, a word2vec embedding represents semantically similar code tokens with vectors of high

cosine similarity, as explained in Section 2.5.2.

In VUDENC, a code snippet is transformed in a list of representations of its separate tokens. Those can be language keywords, identifiers like function names and variables, numbers, operators and even whitespaces, brackets and indentations. Each of those tokens has to be embedded, in other words, represented by a numeric vector. A full section of code is therefore transformed into a vector of vectors of numbers.

Word2vec has been successfully used for similar projects before [LKB⁺18]. In addition to the conceptual advantages over a one-hot encoding, it also requires much smaller vector sizes, which makes it less computationally expensive. It is chosen as the appropriate embedding method for VUDENC.

Since there is currently no pre-trained language model for Python code available, the word2model first has to be trained. For this purpose, a corpus of high-quality python code is acquired, once again from Github. On this corpus, the word2vec model is trained to prepare it for the task to encode Python code tokens as vectors.

4.7. Selecting the machine learning model

There are many machine learning models and approaches, and some of them, including SVMs, decision trees, random forest and naive bayes models, have been applied to vulnerability detection, with mixed results (see Section 3). However, not all of those models have the desired capabilities.

The goal for VUDENC is to create a model that can learn vulnerability features from sequences of code tokens. Sourcecode is, by its very nature, sequential data, as every statement's effect depends greatly on other instructions around it. To detect a vulnerability, it is not enough to learn that a single token is 'bad', as this will lead to many false positives. Rather, the goal is to learn that a token is 'bad' *when used in a specific way*, in a specific combination with tokens that came before.

Deep learning-based, especially RNNs, are especially well-suited to represent the localness of code, while at the same time being able to capture much longer context than n-grams [DTP16]. The advantages of deep neural networks, especially recurrent neural networks and long short term memory networks, have been described in Section 2.3.1. To reiterate, those networks are able to model sequential data, using an internal state as a 'memory' to keep track of previous inputs and put information into context. RNNs, however, suffer from the problem of vanishing or exploding gradients, which makes it difficult to train them on longer sequences, as the long distance between the occurrence of a piece of information and the point it becomes relevant exceeds the RNNs capabilities. However, LSTMs have been designed to deal with this sort of problem, as they are able to learn how long information should be stored. They are designed for exactly the kind of task required in VUDENC (see Section 2.3.4) and have been successfully used in modeling code (see Section 3.3.1 and especially the research by Dam et al. [DTP16], who found LSTMs to perform consistently better than RNNs when modeling longer code sequences). Therefore, an LSTM is chosen as the model for this work.

4.8. Choosing the optimizer

The goal for VUDENC is to achieve high precision and high recall at the same time, which is why the F1 score has been chosen as a metric for the model's performance. A loss function based on the F1 score will be used to measure how 'wrong' the predictions are at a certain point. The loss function needs to be minimized, and to do so, the optimizer needs to update the model parameters until the global minimum is found. The loss function tells the optimizer whether the new parameters are better or worse than the previous ones, or in other words, whether the optimization is going in the right direction. The most basic optimizer is stochastic gradient descent (SGD), which essentially calculates what a small change of the weights in all possible directions would mean for the end result, then picks the best one, which has the steepest descent. It then updates the model, and repeats this process until it cannot improve anymore. However, SGD can get stuck in a local minimum if the loss function is not convex or there are ill-conditioned regions. This can be amended by using a smaller learning rate. However, a learning rate that is too small means that the network won't learn quickly enough. How should the learning rate be chosen?

Fortunately, the learning rate does not have to be fixed to a specific value, but can be adapted dynamically. The adam optimizer (named after the technique of 'adaptive moment estimation') chooses a learning rate dynamically. It was published in 2014 [KB14] and is designed specifically for deep neural networks, where it achieves good results fast and is often taken as a go-to optimization algorithm for many problems. It updates network weights not only based on the gradient, but takes into account the previous updates and the first and second momentum of the gradient, which are defined as the expected value of that variable to the power of one or two, respectively - those are the mean and the centered variance of the gradient. According to the authors, it combines the advantages of the Adaptive Gradient Algorithm (Adagrad) [DHS11] and Root Mean Square Propagation (RMSprop) [TH12].

Adagrad adapts the learning rate differently for different features, and works really well on sparse datasets with a lot of missing samples. Its drawback is a learning rate that tends to become very small. RMSprop, a special version of Adagrad, adapts learning rates based on recent magnitudes of the gradients for the weight and performs well on on-line and non-stationary problems. It only looks at gradients in a fixed window when calculating the momentum. There are more optimizers, including adadelta, nadam, adamax, NAG, and so forth, that will not be described in detail here.

Since the chosen loss function, the F1 score, is not convex, SGD will probably not converge towards the optimal solution. According to research by IBM [IBM19], under some conditions, the optimizers from the adam family (which includes RMSprop, Adagrad, and so forth) should converge.

Looking at other works in the field, Li et al. [LZX⁺18] use adamax, Russell et al. [RKH⁺18] leverage the standard adam optimizer and Dam et al. [DTP⁺17] use RMSprop, although the applicability depends strongly on the specifics of the dataset. For VUDENC, the adam optimizer will be used as a starting point, can be compared empirically to other optimizers to review which yields the best results in practice.

4.9. Evaluation

For the purpose of prediction and classification, four key concepts are usually the basis for evaluation: true positives, true negatives, false positive and false negatives. They have been mentioned before but shall be defined properly here. Positive and negative refer to the prediction, meaning that (without loss of generality) in this work a prediction of 'vulnerable' would be a positive and a prediction of 'not vulnerable' would be a negative. The terms true and false refer to whether the prediction corresponds to the actual value or external judgment. Hence, a false positive is a clean code incorrectly labeled as vulnerable by the classifier, a true positive is a vulnerability that was correctly spotted, a false negative is an actual vulnerability that was not classified as such, and a true negative is a piece of code that was classified as 'not vulnerable' and is indeed harmless.

Two metrics are directly derived from those four values: precision and recall. The **precision** is the rate of true positives within all positives. It measures how precise the model is in terms of how many of the predicted positives are actual positives, or phrased differently, how much trust can be placed in the classification of a positive and how many false alarms are produced. The **recall**, also called sensitivity, is a measurement for the rate of positives that were correctly identified in comparison to the total number of actual positives. One could take it as a measurement for how vigilantly the classifier spots all positives - or how much gets overlooked.

$$precision = \frac{true\ positives}{true\ positives + false\ positives}$$

$$recall = \frac{true\ positives}{true\ positives + false\ negatives}$$

The **accuracy** is the fraction of correct predictions compared to all predictions. For binary classification, it is defined as following:

$$accuracy = \frac{true\ positives + true\ negatives}{true\ positives + true\ negatives + false\ positives + false\ negatives}$$

However, accuracy does not provide much insight when there is a class imbalanced data set, meaning that there are many more positives than negatives or vice versa. In the case of vulnerability detection, it is indeed the case that most code fragments will be clean and vulnerabilities are relatively rare. For example, Morrison et al. [MHMW15] found that their dataset of Windows code contained only 0.003% vulnerable files, and Shin et al. [SMWO10] report that 3% of their files in Mozilla Firefox had vulnerabilities. In a case where true positives are rare and true negatives are very common, a classifier can achieve high accuracy scores even though it misses most of the positives, as the many true negatives make it seem like the overall outcome was quite accurate. Therefore, the accuracy alone is not a suitable measurement for this application.

The **F1 score** is a balanced score (harmonic mean) that takes precision and recall into account. The F1 score is not as easily influenced by a large number of true negatives and is better suited for class-imbalanced data sets. The F1 score is defined as following:

$$F1 = 2 \cdot \frac{precision \cdot recall}{precision + recall}$$

In an ideal, perfect case, the model would achieve a near 0% rate for false positives and false negatives, meaning that precision and recall both are close to 1, as well as accuracy and F1 score. In this work, the accuracy, precision, recall, and the F1 score will be used to evaluate the model, even though many other works on similar topics only take the first three of those four values into account.

According to some researchers [MHMW15, SW13, NZHZ07], precision and recall values of 70% are reasonable for prediction models, but modern approaches have shown some more impressive results, as has been described in Section 3. A precision and recall of above 65% seems like a desirable goal for this work.

5. Implementation

In the following section, the technical aspects, challenges, and obstacles of this work are described in detail.

5.1. Collecting the data

5.1.1. Scraping Github

The very first step in constructing VUDENC is to find the dataset, more precisely, to find a large amount of Python commits that fix a problem related to security. Since the goal is to cover a range of different vulnerabilities, many examples for each of those vulnerability types are required. By the very design of this work, commits are the main focus of interest, since the act of patching a flaw indicates the presence of the flaw in the first place and forms the basis for labeling the data later.

Due to the restrictions of the Github search API, only certain kinds of requests can be made, and for every request, the number of results is limited to 1000 [Git19a]. In contrast to the regular search available for users [Git19c], filters can not be applied in the search API, so it is not possible to filter for just the programming language Python. Therefore, this filtering has to be done manually by further narrowing down the results after receiving them and finding the few relevant and useful ones among them. The approach chosen here is consequently to write a script that uses the Github API to search for commits with various security-related search terms, and then filter out everything that is not relevant, for instance, code in a different programming language, or config files. The script uses an API token for authentication and can be found in the repository as `scrapingGithub.py`.

At first, a relatively long list of keywords was used that are relevant to security. Those keywords are in part inspired by similar research [ZS17], and also stem from the CVE database [CVE19] and the OWASP foundation's list of security threats [OWA]. A Python script using the requests library was created to collect the data, accessing the Github API. The original list of keywords was as follows:

```
["buffer overflow", "denial of service", "dos", "XXE", "vuln", "CVE", "XSS", "NVD", "malicious", "cross site", "exploit", "directory traversal", "rce", "remote code execution", "XSRF", "cross site request forgery", "click jack", "clickjack", "session fixation", "cross origin", "infinite loop", "brute force", "buffer overflow", "cache overflow", "command injection", "cross frame scripting", "csv injection", "eval injection", "execution after redirect", "format string", "path disclosure", "function injection", "replay attack", "session hijacking", "smurf", "sql injection", "flooding", "tampering", "sanitize", "sanitise", "unauthorized", "unauthorised"]
```

This set was combined with a second set of keywords related to improvements, fixes or changes, in such a manner that every possible combination of an element of the first and an element of the second set is taken into account. Since the second set contains keywords that indicate a problem or a fix, the combinations should be helpful

(although not sufficient) to distinguish actual security fixes from many other mentions of vulnerabilities, such as demonstrations for illustrative purposes in showcase projects.

```
["prevent", "fix", "attack", "protect", "issue", "correct", "update", "improve", "change", "check", "malicious", "insecure", "vulnerable", "vulnerability"]
```

However, it became quickly apparent that only a few of those keyword combinations were actually well-suited for the intended purpose. Some, like 'vuln', 'XXE', 'malicious' or 'CVE', were too general and yielded a wide range of different results, others, like 'dos' (as abbreviation for denial of service) generated flat-out unrelated results because of overlap of meanings (in this case, 'dos' referring to old windows operating system, and, even more often, the very common Portuguese word for 'of' that occurs in many commit messages.)

Therefore, the combinations were narrowed down significantly. The remaining primary keywords were:

```
["buffer overflow", "denial of service", "XSS", "cross site", "directory traversal", "remote code execution", "XSRF", "cross site request forgery", "click jack", "clickjack", "session fixation", "cross origin", "brute force", "buffer overflow", "cache overflow", "command injection", "cross frame scripting", "csv injection", "eval injection", "execution after redirect", "format string", "path disclosure", "function injection", "replay attack", "session hijacking", "smurf", "sql injection", "flooding", "tampering", "sanitize", "sanitise", "unauthorized", "unauthorised"]
```

After combining every keyword from the revised first set with every keyword from the second set, for each of the combinations, a search request is sent to Github. Note that this only means that the names (and therefore URLs) of commits and repositories are collected - no actual source code or even diff file is downloaded yet.

5.1.2. Filtering the results

The next concern was to filter projects that are showcases for security vulnerabilities, demonstrate exploits, are tools attacking or teaching how to prevent exploits. While those works in many cases contain good examples for vulnerabilities, they usually do not have commits fixing them, but rather commits that introduce them in the codebase, since they are included on purpose. Furthermore, they are not in line with the methodological assumptions of this work, as the goal is to learn features of vulnerable code as it occurs in real-life projects of developers making genuine mistakes. Therefore, an attempt is made to filter out those kinds of projects.

The script `filterShowcases.py` contains a list of keywords indicating such undesired projects. The repository names were checked to see if they contain the following keywords:

```
"offensive", "pentest", "vulnerab", "security", "hack", "exploit", "ctf ", " ctf", "capture the flag", "attack"
```

Then, the README files for the remaining projects are downloaded from Github and also checked for occurrences of the following terms:

"offensive security", "pentest", "exploits", "vulnerability research", "hacking", "security framework", "vulnerability database", "simulated attack", "security research"

In the next step, the diff files are downloaded (`getDiffs.py`). In the GNU diff representation and similar representations also used by Github, a diff is simply a text file representing the changes made in a commit. It contains some meta information (such as the filename and the line number of the changes), and the changed lines plus three lines of code before and after. A '+' at the start of a line indicates the new and fixed line, while a '-' indicates the line was removed in favor of the fix [LKB⁺18]. On Github, a commit can include changes to several different files at once.

Downloading the diff for a commit URL can be done with a single simple HTTP request. This is a much easier approach than to clone the full repository and selectively pick the whole files from a certain point in the history of a project, which, at this point, seems not feasible due to the size of the dataset and computational and time constraints.

The result of the previous step is a big collection of code diffs which can be used to reconstruct the relevant lines of code in the state before and after the patch. For every changed file, the diff from Github provides the changed lines as well as three lines before the first change and three lines after the last, so there is not much context for the change. But it is very well possible that the large number of changes that can be mined with this strategy makes up for the relatively narrow context provided for each change.

Executing all those queries took roughly 80 hours and resulted in 25040 commits from 14686 repositories containing python code, after filtering out roughly 3000 repositories that are showcases, attacks or for demonstration purposes, and roughly 70000 commits that did not change any python file.

5.1.3. First misguided attempt: Using only diffs

At first, I was under the impression that downloading the source code for each commit would require far too much computational effort and therefore time for the scope of this work. So I took the path of downloading only the diff files and creating the dataset as follows: I took the whole commit and recreated the 'previous version' and the 'after version', each containing the changed lines and three lines above and below those. Then, I intended to use the previous version with a label of 'vulnerable' and the second one with a label of 'not vulnerable'. I went through all the next steps, including the training of the long short term memory network, and actually received quite satisfying results. The classifier who had learned with the training set was able to correctly sort the examples in my test set and decide whether they belonged to the 'previous/vulnerable' or 'after/fixed' category.

However, the problem became clear when I tried to apply the classifier on a file with



Fig. 8: Retrieving the snippet in the state before and after the commit from a git diff, old vulnerable version in red, new version in green

source code, going through many parts of it and trying to classifying them. A staggering amount of false positives was the result of that attempt. The reason is, of course, that my dataset contained the exact same number of (true) positives and negatives, while in real life, vulnerable code is relatively rare in between many lines of 'clean' code. The dataset did not reflect the class-imbalanced nature of the actual data the classifier should be applied to.

Of course, I had known about this from the start, but I was under the impression that collecting the diffs was simply the best I could manage due to the aforementioned limits on time and computational power. However, I realized that I had more options.

5.1.4. Downloading the dataset

As it turned out, downloading the source code was actually feasible in acceptable time if all the filtering was done beforehand in a clever way to minimize the downloaded repositories to the absolute minimum. The script for downloading all data for a given vulnerability can be found under `getData.py`.

At first, it is checked whether the commit contains keywords relevant to the given vulnerability. Then, the diff file is checked to see if any files with the ending '.py' are affected. If this is not the case, the commit can be ignored, since only commits changing Python source code files are of interested. Next, the commit is compared with the commits already downloaded. By the nature of open-source repositories, many are

forks or clones of each other or contain the commit history of other projects. Those duplicates are excluded. Next, the diff is analyzed in more detail.

Each change in the commit is affecting a certain file. For each change, the filename is checked to see whether it contains keywords that hint to it being a showcase project - a file called 'sql exploit' will probably not be a subject to a patch in which an accidental vulnerability is fixed, but rather be a part of a project demonstrating exploits. Then, the body of the diff file is processed. If html tags or the keywords 'sage' are included, the diff is not taken into account anymore. HTML code is sometimes embedded in Python files, but the vulnerabilities in those files are usually not in the Python code itself. Sage is the name of an open-source mathematics system, and some commits contain a lot of parameters and variables relevant to it that are also not interesting for our purposes. Finally, it is checked whether the change actually deletes or replaces any lines of codes. If there are only additions, the algorithm cannot learn very well which lines are vulnerable if they are present. Finally, after all those filtering steps, it is determined which commits are actually worthwhile to download.

It is only now that the tool Pydriller [SAB18] is used to download the repositories containing interesting commits, and traverse their commits to find all the matches with the commits that are remaining in the collection of interesting ones. For each commit, some checks are applied again. If the previous file is empty, the commit is skipped. If the previous file is more than 30.000 characters long, the commit is skipped as well. The commit message is checked for suspicious keywords similarly to the filename before. And finally, the source code itself is downloaded and saved in the dataset.

5.1.5. Flaws in the data

For the vulnerabilities related to the keywords `cross origin`, `buffer overflow`, `function injection`, `clickjack`, `eval injection`, `cache overflow`, `smurf` and `denial of service`, there were less than 50 distinct commits found, so it was decided that those do not provide a large enough dataset to learn generalized features.

Looking at the data more closely, it became clear that the method of collecting vulnerability samples based on commit messages in and on itself is far from perfect. There were still some (albeit few) commits containing not fixes, but implementations of exploits, such as setups for capture the flag, attack demonstrations or cybersecurity tools like Burp Suite.

In some commits, the commit messages read, for instance, 'fix remote code execution', and indeed such a vulnerability is fixed *somewhere*, but the same commit contains not only this patch, but, for example, eight other files with small and large changes that may or may not be related to the issue described in the commit message. Without human supervision or predefined knowledge, it is not easy to determine which of the changes actually relates to the purpose stated in the commit message.

For some keywords, the results were just very unspecific. For the term `brute force`, there were a lot of results in which a brute force approach was used to solve a problem, not in which a defense against a brute force attack was applied. Therefore, the results

were not very relevant. With the term **tampering**, a similar problem occurred, as it was used quite rarely and for many different reasons (including DNS tampering, but also modification of game data for cheating purposes). The keyword **hijacking** was used a lot in a figurative way, for instance, for a person or application that put in content somewhere that was undesirable, but authorized, or for data fields or entries that were used by the developers themselves for other purposes as intended. The keyword **directory traversal** resulted in many fixes and commits that related to developers traversing their own file structures, not an attacker trying to do so.

Sometimes, changes were simply very complicated and spanned multiple files, sometimes including files that were not written in python. The more complicated those changes were and the more lines are edited, the harder it is to model and learn from the sample. Another problem is that many vulnerabilities are basically defined by the *absence* of certain protection mechanisms, like xsrf tokens, or nonces / counters that prevent replay attacks. Fixing those vulnerabilities sometimes does not edit or remove a snippet of code that is vulnerable, leading to insights about what vulnerable code looks like, but only introduces some additional lines. In some cases, those lines can be placed in many different positions, with many different variations of how to produce the desired functionality. It is definitely harder to learn to recognize the absence of something vague that is needed, than to recognize a very specific wrong snippet of code that is present.

Commits relating to **replay attacks** frequently had both of the problems that were just described: They are spread out over a lot of files, and they do not edit an existing flawed code segment, but mostly introduce new lines. Therefore, this type of vulnerability had to be excluded.

For **man-in-the-middle** attacks, there were only few results that were actually trying to harden an application against them instead of executing them. And the defense mechanisms were so specific that not much useful data came out of it. For the term **unauthorized**, most of the commits were also not related to fixes of vulnerable code segments, but called methods or handled errors that were not specifically connected to a vulnerability. For **sanitization**, there was a great number of results regarding prevention of error messages that were not directly related to security, and for the term **formatstring**, there were simply too many applications outside the realm of security and vulnerabilities that were just concerned with pretty formatting of outputs and not with preventing vulnerabilities exploiting formatstrings.

Fortunately, there were other types of vulnerabilities, such as SQL injection attacks and cross-site scripting, which did produce very favorable samples to learn from.

5.1.6. Filtering data

To enhance the quality of the dataset, some restrictions were placed on individual samples. Only files that were no longer than 10000 characters long were taken into account. This has several positive effects: The very long files usually have a lot of content that is not relevant, such as long segments of comments, docstrings, manually

defined variables etc. Furthermore, they act as a kind of 'long tail' in computational expenses, requiring a lot of time to be processed for little gains. And finally, according to some samples that were examined manually, they do not seem to contain the highest quality code.

To improve the quality of the dataset further, commits that removed or edited a file in more than 10 different places were taken out of the sample. Such bulk edits are likely going to change a lot of different issues at once, and not just fixing one problem.

Those steps reduced the number of samples, of course. For example, in the case of sql injections, the dataset was trimmed from 335 repositories and 403 commits changing 654 files of 82913 lines of code in total; down to 223 repositories, 251 commits, 409 files and 30711 lines of code. For command injection, the count went from 85 repositories, 106 commits, 197 files and 36031 lines of code down to 52 repositories, 63 commits, 81 files and 10051 lines of code. While there is a reduction of more than half, the quality of the data did not suffer, as a test of the final model (see later sections) with the non-trimmed dataset did not provide any better results.

5.1.7. Second misguided attempt: subtle errors in creating the dataset

At this point, I made a grave mistake in constructing the dataset that I only realized very late in the process. I had determined from the diff which changes were made to the file and could identify the parts that were removed or changed as probably vulnerable. I removed them from the source code and labeled those code parts as 'vulnerable'. Then I took the rest of the source code and split it into even blocks that had roughly the length of the average length of the vulnerable code snippets. Those blocks were labeled as 'not vulnerable' and added to the dataset as well. The process is visualized in figure 9.




Fig. 9: Process of splitting the whole code with vulnerable (red) and non vulnerable (green) parts in snippets for the dataset. Notice that the splitting happens first, and then vulnerable and not vulnerable are separated.

The problem with this approach was that I treated the vulnerable areas of code dif-

ferently than the not vulnerable ones. The process of creating a code block was not the same: for the vulnerable code, I just took the relevant part out, for the clean code, I used the block-splitting algorithm. This resulted in the vulnerable blocks having some distinct features that were easily recognizable by the trained classifier. I suspect that some vulnerable sections were very long (whole functions deleted etc.) and most were very short (one or two lines changed), leading to an average of medium length, so I cut the clean code in medium length blocks, which resulted in the length of the blocks doubling as a proxy for their vulnerability status. The result were unrealistically high values for precision and recall, and disappointing performance when the classifier was applied to a new source code file cut into even blocks and should determine which were vulnerable.

5.2. Processing the data

To correctly process the data, vulnerable and not vulnerable parts had to be treated alike the whole way up to the labeling step. The data was split into equal blocks, and then the blocks were labeled as vulnerable if they had an overlap with one of the vulnerable code segments, otherwise they were labeled as clean, see figure 10.




Fig. 10: Process of splitting the whole code with vulnerable (red) and non vulnerable (green) parts in snippets for the dataset

So far, the process for splitting the source code into blocks has been presented in a simplified way. The actual procedure works as follows (see figure 11). Similarly to the works by Hovsepyan et al. [HSJW12] and many others, comments are filtered out from the code, as they are unlikely to influence the vulnerability of a file. A small focus window traverses through the whole source code in steps of length n . Some positions of the focus window are depicted in blue in the figure. The focus window always starts and stops at a character that marks the end of a token in Python, for instance, a colon, a bracket or a whitespace to prevent cutting tokens in half. For this focus window, the surrounding context of roughly length m , also starting and stopping at the border of code tokens, is determined, with $m > n$. If the focus window is close to the beginning of the file, the context will mostly lie behind it (see Block A), and if it is located in the middle with plenty of code before and after, the surrounding context will be spanning

a snippet that lies equally before and after the focus area. This results in a number of overlapping blocks. If the whole block contains partially vulnerable code (as example blocks B and C), it is labeled as vulnerable, otherwise it is labeled as clean. This ensures that code snippets containing a vulnerability in them are marked as such. The parameters n and m are subject to optimization, their ideal values will be determined experimentally. Liu et al. [LKB⁺18] stated that most of the time, a chunk of just 10 lines of code is sufficient to capture the relevant context for a vulnerability.




Fig. 11: Process of splitting the whole code with vulnerable (red) and non vulnerable (green) parts in snippets for the dataset

The next step is to transform those code blocks, which are nothing more than lists of Python tokens, into lists of numerical vectors. For this, we need the word2vec embedding.

5.3. Word2Vec embedding

To encode the code tokens in a word2vec vector, a fitting word2vec model is needed that has been trained on Python source code. To train this model, a large training base of code is required, ideally made up of clean, working Python code.

Similarly to the approaches taken by Bhoopchand et al. [BRBR16] and Allamanis et al. [AS13], I follow the heuristic that popular code projects are of good quality. Note that those repositories are likely to contain few security vulnerabilities, as well as bugs in general. Github offers two metrics to assess the popularity of a repository: stars (highlights similar to bookmarks set by users) and forks (copies for further development and experimentation in a personal project). Choosing Python repositories with a high number of stars and forks, the following selection of example repositories is gathered:

- <https://github.com/numpy/numpy>
- <https://github.com/django/django>
- <https://github.com/scikit-learn/scikit-learn>
- <https://github.com/tensorflow/tensorflow>
- <https://github.com/keras-team/keras>
- <https://github.com/ansible/ansible>
- <https://github.com/TheAlgorithms/Python>
- <https://github.com/pallets/flask>
- <https://github.com/ytdl-org/youtube-dl>

- <https://github.com/pandas-dev/pandas>
- <https://github.com/scrapy/scrapy>
- <https://github.com/kennethreitz/requests>
- <https://github.com/home-assistant/home-assistant>
- https://github.com/ageitgey/face_recognition
- <https://github.com/emesik/mamona>
- <https://github.com/progrium/notify-io>
- <https://github.com/phoenix2/phoenix>
- <https://github.com/odoo/odoo>
- https://github.com/ageitgey/face_recognition
- <https://github.com/psf/requests>
- <https://github.com/deepfakes/faceswap>
- <https://github.com/XX-net/XX-Net>
- <https://github.com/tornadoweb/tornado>
- <https://github.com/saltstack/salt>
- <https://github.com/matplotlib/matplotlib>
- <https://github.com/celery/celery>
- <https://github.com/binux/pyspider>
- <https://github.com/miguelgrinberg/flasky>
- <https://github.com/sqlmapproject/sqlmap>
- <https://github.com/zulip/zulip>
- <https://github.com/scipy/scipy>
- <https://github.com/bokeh/bokeh>
- <https://github.com/docker/compose>
- <https://github.com/getsentry/sentry>
- <https://github.com/timgrossmann/InstaPy>
- <https://github.com/divio/django-cms>
- <https://github.com/boto/boto>

With the tool Pydriller [SAB18], the Python files in those repositories can be downloaded (see script `w2v_pythoncorpus.py`). The resulting source code is simply concatenated to form one huge Python code file. Then, another script (`w2v_cleancorpus.py`) is used to remove problems within this file, such as indentation errors. Now, the built-in Python tokenizer is used to split the code into Python tokens (`w2v_tokenize.py`). Comments are removed from the file, and new lines, indentations, and tabs are normalized. At this point, there are two different ways to go ahead: string tokens could be kept as they are, or they could be replaced with a generic string token. Both versions are tested. Finally, the results are concatenated in one big Python file (`w2v_mergecorpus.py`). Using the Gensim implementation for Python, the word2vec model is then trained on the corpus (`w2v_trainmodel.py`). Hyperparameters of the word2vec model include the dimensionality of the resulting vectors, the minimum number of times a token has to appear in the corpus to include it in the model, and the training iterations. Several different hyperparameter settings are tested and evaluated. To see whether a trained embedding is useful, there are basically two options: One can simply look at some tokens and their most similar tokens according to the model, and think about whether they seem to make sense, which is, of course, a subjective approach. And the model can be evaluated by looking at the final performance of the LSTM, which can only work reasonably well if the way the training data is embedded is sensible. By judging from the final performance of the full model, the embedding hyperparameters can be

evaluated.

The following table shows the embedding of a word2vec model that does not replace strings, has a minimum count of 1000, a vector size of 200 and 100 iterations. Displayed are some words in the vocabulary and their respective most similar other tokens, as determined by the cosine similarity. A cosine similarity of '1' would mean that the two tokens are identical or complete synonyms.

word	most similar	second most similar	third most similar	forth most similar
import	from (0.42)	collections (0.34)	print_function (0.32)	importerror (0.31)
true	false (0.90)	module (0.35)	boolean (0.35)	none (0.34)
while	break (0.54)	-= (0.39)	found (0.38)	continue (0.37)
if	elif (0.78)	and (0.75)	or (0.72)	assert (0.59)
try	else (0.50)	attributeerror (0.46)	keyerror (0.40)	pass (0.36)
in	is (0.48)	hasattr (0.46)	isinstance (0.40)	== (0.36)
+	+= (0.66)	% (0.48)	- (0.43)	* (0.43)
x	y (0.73)	z (0.40)	condition (0.32)	alpha (0.28)
[](0.49)	1 (0.46)	0 (0.43)	" (0.40)
str	bool (0.48)	tuple (0.48)	list (0.45)	repr (0.45)
count	total (0.53)	len (0.50)	max (0.44)	counter (0.42)
len	count (0.50)	split (0.39)	max (0.39)	num (0.38)
where	select (0.41)	find (0.38)	sum (0.35)	mask (0.34)
join	write (0.55)	append (0.55)	extend (0.52)	dirname (0.45)
split	parts (0.50)	strip (0.46)	rstrip (0.49)	append (0.43)
==	! (0.71)	> (0.56)	< (0.56)	hasattr (0.43)

Note that, for instance, the operator '==', used to test for equality, is most similar to other comparison operators that result in a boolean outcome. In general, the similarities seem plausible and suggest that the word2vec model was able to learn something about the role of different Python tokens, for instance, that true and false have very similar functionality in code.

The hyperparameters of the word2vec model are:

- leaving strings; or replacing strings
- training iterations: between just one and more than hundred
- minimum count: between 10 and 5000
- vector dimensionality: between 5 and 300

Judging from other applications and default values, it is likely that a vector dimensionality below 30 will not be able to capture the semantics of Python code tokens and will result in poor overall model performance. Also, 100 training iterations will probably not make much of a difference compared to 50. All of those hyperparameters are tried out to find a configuration that works well for this application. In order to better judge the effectiveness of the word2vec model, an earlier idea was to compare it to a naive one-hot embedding. For the dataset of SQL injections, the number of unique code tokens was 22724, so for a complete one-hot embedding, every single token would have to be encoded in a vector of this dimensionality. After trying to reduce that number by just taking into account tokens that appear at least 10 or 100 times, and using the some more efficient sparse vector representation from the Scipy library,

the problem was still far too computationally expensive to be handled in any way, causing the machines to abort the process every time. It can therefore be concluded that word2vec is at least superior to one-hot embeddings in terms of plain feasibility.

5.4. Preparing the data for classification

The collected data is still in the format of vulnerable and not vulnerable code snippets. The snippets are converted into a list of tokens (such as 'if', 'init', '2.3' or '+') and each of the token is replaced with its vector representation according to the word2vec model that was chosen. Each list of vectors is associated with their binary label, '0' meaning vulnerable and '1' meaning not vulnerable or unknown status.

The data is partitioned into mutually exclusive training, validation and test sets. 70% of the data is randomly selected as a training set, 15% is taken as a test set for validation, and 15% is put aside for a final evaluation at the very end of the experiments. This is well in line with general practice in training neural networks as well as other works on similar tasks, for example, Dam et al. [DTP16] chose the same ratios, Russel et al. [RKH⁺18] split their dataset in 80% training, 10% validation and 10% final test set, and Li et al. [LZX⁺18] used a split of 80-20 in train and test set. Note that the validation set is not used to learn any parameters, it is only used to evaluate the model performance after it learned its parameters on the training set. This evaluation is taken into account when modifying the model's hyperparameters, until in the end, all results are presented using the final test set that the model has never seen before.

The lists of vectors (each representing one code snippet), are truncated and padded to achieve an equal length of vectors per sample.

5.5. Training the LSTM

5.5.1. Architecture of the model

The dataset is ready to be used in training (see the source file (`makemodel.py`)). Using the Keras library, a sequential model is created. The most important part comes first: The LSTM layer, which has been described in its functionality in detail in Section 2.3.4. The purpose of this layer is to learn features which are associated with the vulnerability status of a code snippet. The LSTM layer is subject to several hyperparameters (see next section), including dropout and recurrent dropout, so there is no need for a separate dropout layer.

Since the data is inherently class-imbalanced (there are many more clean code blocks in the training data than vulnerable ones), the classes should be weighed accordingly. This assures that even though there are a lot more examples for clean code, the examples for vulnerable code are taken just as seriously in training. The **class weights** are calculated automatically using the `class_weight` function from the scikit-learn library. After the LSTM layer, there is just the activation layer, a dense output layer with a single neuron. The activation function used here is a sigmoid activation function because

the goal is to make a prediction between 0 and 1 for the two classes of vulnerable or not vulnerable code.

Refer also to figure 6 for an overview of the architecture.

5.5.2. Choosing hyperparameters for the LSTM

A lot of decisions have to be made regarding the LSTM hyperparameters. After estimating some plausible starting values based on other research and common sense, the hyperparameters are varied and tested empirically to find the optimal configurations. **Metric and loss function** are technically hyperparameters. Since a good balance between false positives and false negatives is desirable for VUDENC and the classes are already weighed, the F1 metric seems especially well suited to evaluate the overall performance (see Section 4.9). Therefore, the F1 score is chosen as the optimization criterium for the LSTM model. The F1 metric and the corresponding loss function are custom defined in the scripts.

A core hyperparameter defining the model is, naturally, the number of **neurons** (or units). It affects the learning capacity. More neurons allow the model to learn a more complex structure, but also require a longer time to train the model. The number of neurons also defines the dimensionality of the output space (the feature vector, which is fed as input into the dense layer).

The **batch size** describes how many samples are shown to the network to be processed before the weights are updated again. Therefore, the model should not be trained with a batch size smaller than the number of samples used at a time when making a prediction later. A variety of different batch sizes are tried out to compare the results. The most extreme values would be a batch size of one single sample (as used in on-line learning or stochastic gradient descent approaches), or a batch size of a full training set (batch forecasting). In the middle between the two, batch sizes of 32, 64 and 128 samples are typically used.

Like many models, LSTMs can be trained to the point of overfitting training data, which reduces their predictive performance. **Dropout** is a regularization method where input and recurrent connections to LSTM units are sometimes randomly excluded from the next step of the training, so they can't be taken into account when the network updates its weights. This reduces the chance that the network overfits by relying on a few inputs too heavily. In LSTMs, there are two kinds of dropout: the standard dropout describes the fraction of units to drop from the inputs. The recurrent dropout describes the fraction of units to drop from the recurrent state (the memory of the previous steps of the model). A typical dropout is chosen between 10% and 50%. The ideal dropout will be determined by experimentation.

Finally, the **number of epochs**, in other words, the number of times that the learning algorithm will work through the whole training data set, has to be adjusted. Typical numbers for epochs in the literature include 10, 100, 500 or even 1000 epochs.

As described in Section 4.8, a variety of optimizers in the adam family will be tested to see which yields the best results.

After all those hyperparameters have been adjusted, a model with optimal configurations can be calculated. Refer to Fig. 12 for an overview of all (hyper)parameters that come into play for the full model.




Fig. 12: steps of creating the model and order in which the hyperparameters come into play

5.5.3. Practical considerations

Training the models and comparing different hyperparameter settings took a long time. All work was done remotely on the gruenau3-8 machines of the institute of computer science of Humboldt University. Ideally, many combinations of different hyperparameters should be tried, however, training one specific configuration could easily already take one to ten hours to be completed. This was especially problematic with the hyperparameters for the word2vec model.

The whole process of training the VUDENC system can be split into two parts: first, a word2vec model is training with its own parameters, such as min_count or iterations. Only then, the code blocks can be encoded in their vector representations. In the second step, the LSTM model is trained, with its respective hyperparameters such as the number of neurons or dropout. In order to save time, I originally saved the results of the first step (the encoded dataset in vector representation) for many different word2vec hyperparameter combinations. I could then use them for many different LSTM models, without having to redo the whole first step over and over again. However, those encoded datasets occupied more than 5 GB each - and this for every word2vec hyperparameter combination. Soon, I vastly exceeded the amount of space intended for a single student, occupying around 550 GB of space with the various datasets and models. As a result, my account was blocked until I hastily apologized and deleted the models. Afterwards, I had to revert back to do both the first and the second step as one, each time I trained an LSTM model, which increased the time needed by around 40 minutes each time. Even after committing to a fixed set of word2vec hyperparameters, the data limit still had to be taken into account, since a new dataset had to be created for each vulnerability type as well, and saving them all would again exceed the space assigned

to me. Going forward, I had to stick with this approach. This is why datasets are not saved in an embedded format, but the embedding is calculated anew each time the LSTM model is trained.

Another obstacle was that for some calculations (among others, word2vec models with too many iterations, LSTM models with too many or too large samples, or with too many neurons), the process was killed on the gruenau machines. Even after contacting the computer operations services, it was not possible to resolve this problem.

Computational load and disk space both pose a strict limitation on the complexity of possible models. Also, the work is restricted by time constraints: even if the machines are able to calculate a model, it is not possible for me to go through all combinations that I would like because this would take more weeks and months than are available for the completion of this thesis (and the scripts have been running all day and all night for months already). Therefore, the number of combinations of hyperparameters that has been tried out is more limited than I would like. It is very well possible that the end result is not the absolut optimum of what could be achieved with the data because the best hyperparameters were not hit. However, I believe that the end result is at least in the approximate area of the optimum, as there are diminishinig returns for most hyperparameters, such as neurons and training epochs. See Section 6 for the specific results.

5.6. Application on code

standard resolution			'fine' resolution		
prediction 0.9 .. 1.0			prediction 0.9999 .. 1.0000		
prediction 0.8 .. 0.9			prediction 0.9990 .. 0.9999		
prediction 0.7 .. 0.8			prediction 0.9900 .. 0.9990		
prediction 0.6 .. 0.7			prediction 0.9000 .. 0.9900		
prediction 0.5 .. 0.6			prediction 0.5000 .. 0.9000		
prediction 0.4 .. 0.5			prediction 0.1000 .. 0.5000		
prediction 0.3 .. 0.4			prediction 0.0100 .. 0.1000		
prediction 0.2 .. 0.3			prediction 0.0010 .. 0.0100		
prediction 0.1 .. 0.2			prediction 0.0001 .. 0.0010		
prediction 0.0 .. 0.1			prediction 0.0000 .. 0.0001		
	positive (vulnerable)			positive (vulnerable)	
	negative (clean)			negative (clean)	

Fig. 13: colors and confidence levels

Finally, the usability of the trained classifier is tested on the source code. The code is split into blocks in exactly the same way as before (using a small focus area and a sliding context window as described in Section 5.2). The focus area traverses through the code, and for each new step the surrounding context is taken, the model makes a prediction based on that context as input, and the prediction is used as the vulnerability classification for the focus area. Colors are used to highlight the different convidence levels of the classification (see figures 13 and 14).

If the labels are available (possibly because the code comes from the labeled dataset), true positives, false positives, true negatives and false negatives can be marked visually. In this case, the colors for code that was labeled as not vulnerable stay the same. This means that orange and red mark false positives, and shades of green are true positives.

```

# set the appropriate inheritance whether modification is allowed
if modify:
    inherit = ModifyMixin, handler
else:
    inherit = handler,

# create a file handler for routes
class GenFileHandler(*inherit):
    def respond(self):
        norm_request = normpath(self.groups['path'])
        if self.groups['path'] != norm_request:
            self.response.headers.set('Location', self.remote + norm_request)

            return 307, ''

        self.filename = self.local + urllib.parse.unquote(self.groups['path'])

        return handler.respond(self)

GenFileHandler.local = local
GenFileHandler.remote = remote
GenFileHandler.dir_index = dir_index

return {remote + '(<path>|/[^\#]*)(<query>[?#].*)?': GenFileHandler}

if __name__ == '__main__':
    import signal

    from argparse import ArgumentParser

```

Fig. 14: Code with a path disclosure vulnerability with colored classifications (fine resolution)

Vulnerable code that was recognized as such (true positive) is blue, and vulnerable code that was not recognized is a bright purple (false negative). See figure 16 for another code fragment with a vulnerability, colored using the labels. It is evident by the blue color that the vulnerabilities were recognized, and most other parts are dark green because they are not vulnerable and also not interpreted as such. Just around the borders of the vulnerable part, there is some discrepancy (magenta and red). The important part is, however, that the core of the vulnerable code fragment was correctly recognized as such.

A large number of examples are presented in the appendix of this work, as well as online in the Github repository, with instructions on how to recreate those results.

standard resolution		'fine' resolution	
Label 0 (not vulnerable)		Label 0 (not vulnerable)	
prediction 0.9 .. 1.0	false positive	prediction 0.9999 .. 1.0000	false positive
prediction 0.8 .. 0.9		prediction 0.9990 .. 0.9999	
prediction 0.7 .. 0.8		prediction 0.9900 .. 0.9990	
prediction 0.6 .. 0.7		prediction 0.9000 .. 0.9900	
prediction 0.5 .. 0.6		prediction 0.5000 .. 0.9000	
prediction 0.4 .. 0.5	true negative	prediction 0.1000 .. 0.5000	true negative
prediction 0.3 .. 0.4		prediction 0.0100 .. 0.1000	
prediction 0.2 .. 0.3		prediction 0.0010 .. 0.0100	
prediction 0.1 .. 0.2		prediction 0.0001 .. 0.0010	
prediction 0.0 .. 0.1		prediction 0.0000 .. 0.0001	
Label 1 (vulnerable)		Label 1 (vulnerable)	
prediction 0.5 .. 1.0	true positive	prediction 0.5 .. 1.0	true positive
prediction 0.0 .. 0.5	false negative	prediction 0.0 .. 0.5	false negative

Fig. 15: Colors and confidence levels taking labels into account

```

original_names = {}
for index in source.indexes:
    # make sure the name is < 63 chars with the suffix
    name = hashlib.sha256(temp + index.name.encode('utf-8') + suffix).hexdigest()[0:60]
    original_names[name] = index.name
    columns = []
    for column in index.columns:
        columns.append(next(x for x in destination.columns if x.name == column.name))
    new = sqlalchemy.Index(name, *columns)
    new.unique = index.unique
    new.table = destination
    new.create(bind=self._connection)
    self.insert(destination.name, dataframe, batch_size=batch_size)
    self.execute("BEGIN; SET LOCAL statement_timeout = '1min'; ANALYZE %s; COMMIT;" % table)

with self as transaction:
    backup = sqlalchemy.Table(table + '_b', self.metadata)
    backup.drop(bind=self._connection, checkfirst=True)
    source.rename(name=source.name + '_b', connection=self._connection)
    destination.rename(name=table, connection=self._connection)
    for index in source.indexes:
        index.rename(index.name[0:-2] + '_b', connection=self._connection)
    for index in destination.indexes:
        index.rename(original_names[index.name], connection=self._connection)

for func in after_replace_callbacks:
    func(destination, source)

```

Fig. 16: Code with sql vulnerability with colored classifications using labels (fine resolution)

6. Evaluation

6.1. The data

To answer research question 1 (*Can a dataset of suitable Python source code be mined from Github for common vulnerability types?*), a large number of vulnerability-fixing commits was collected. After gathering all the data and filtering it, a separate dataset was required for each vulnerability. The basic information about them is summarized in the table below, which presents the number of repositories and commits that are part of the dataset are given, the number of changed files with vulnerabilities, their lines of code, the number of separate functions within, and the total number of characters. That this dataset is *suitable* will be demonstrated in the next sections, by utilizing it in training the model.

Vulnerability	rep.	commits	files	functions	LOC	chars
sql injection	336	406	657	5388	83558	3960074
xss	39	69	81	783	14916	736567
command injection	85	106	197	2161	36031	1740339
xsrif	88	141	296	4418	56198	2682206
remote code execution	50	54	131	2592	30591	1455087
path disclosure	133	140	232	2968	42303	2014413
open redirect	81	93	182	1762	26521	1295748

6.2. The baseline model

To show the effects of various hyperparameter changes and tweaks, a baseline model was created. Its hyperparameters are not optimal, but it can be used to demonstrate how other hyperparameters cause better or worse results, since some configuration has to be taken as a starting point. After going through all hyperparameters and pointing out how they affect the final performance, the optimal combination of all parameters

can be determined. The baseline model has a focus area step size n of 5, a context length m of 200, and works on the dataset for SQL injections. It has 30 neurons and is trained for 10 epochs with a dropout and recurrent dropout of 20%, with a batch size of 200, using the adam optimizer. Although more epochs would almost certainly lead to better outcomes, this was not feasible, since many combinations have to be tested and training one model takes more than one hour already, so due to time constraints, only the resulting 'best' model is trained for more epochs. To compare results, the F1 score of the classification performance of the resulting LSTM model is used, which provides a balanced score that takes precision and recall into account.

6.3. Hyperparameters of the word2vec embedding

Research question 2 has been stated to be: *Is the word2vec model effective as an embedding, and how do its hyperparameters influence the overall results?* The following experiments investigate this.




Fig. 17: Vector length and string replacement for the word2vec model

The training corpus taken from various Python repositories contains 69517343 (close to 70 million) individual token. The hyperparameters vector length, min_count, and training iterations are tried out in various settings. The outcome of replacing strings with generic string tokens versus keeping them as they are is also evaluated.

As already stated, the baseline model (see Section 6.2) is used, so all hyperparameters are chosen according to this default configuration unless specified otherwise. The approach is, in general terms, to train a word2vec model, than use it to embed the data and train a LSTM model on it. The performance of the LSTM model is used to judge the quality of the underlying word2vec embedding, since the embedding itself can not be evaluated by a number of any kind. Its effectiveness is determined by the fact that it can be used in the context it is intended for. A bad embedding will results in a bad LSTM model that can not make sense of the data it is presented with. On the other hand, a working LSTM model proves that the word2vec embedding was suitable.

6.3.1. Vector dimensionality

When using word2vec, the code tokens are converted into numerical vectors of a certain length or dimensionality. The longer those vectors are, the more different 'axes' there are for putting words in relation to each other, allowing the word2vec model to capture more complex relationships. A vector size of less than 100 is unlikely to represent the semantics of Python code well, judging from similar tasks with natural language, where vector sizes of 200 are typical.

To compare different vector lengths, the minimum count of a token to appear in the vocabulary is set to 1000 and training iterations of the word2vec model are set to 100. The model that replaces strings with a generic string token was used. Using those hyperparameters, the vector dimensionality was varied between 5 and 300, with the following results:

Dimensionality:	5	10	15	30	50	75	100	150	200	300
F1 score:	29%	40%	54%	61%	60%	68%	67%	73%	78%	76%

As is evident from the table and figure 17, a reasonable vector size seems to be around 200.

6.3.2. String replacement

Strings occurring in the Python training file could be replaced with a generic 'string' token, as some other researchers have done, or they could be kept as they are. Replacing them might reduce the level of detail of the model, but keeping them might put too much focus on the specific content of string tokens - it is hard to say beforehand what works better. To compare the two approaches, the length of the embedding vectors is fixed to 200. The training iterations are varied between 1 and 300, and a min_count of 10, 100 and 5000 is compared.

In the table, the value before the '/' marks the F1 score for the word2vec encoding that keeps strings, the one after the '/' is the F1 score for the model that replaces strings with a generic string token.

min_count	1 Iter.	10 Iter.	100 Iter.	300 Iter.
10	64% / 48%	68% / 62%	72% / 62%	74% / 64%
100	48% / 39%	65% / 56%	63% / 59%	72% / 64%
5000	40% / 39%	57% / 54%	65% / 63%	66% / 63%

Those results show that the version without string replacement yields consistently better results. In figure 17, in the graph to the right, the models without string replacement are marked with green lines, while the models that replace the strings with a generic string token are shown with lines in blue. It seems that keeping the strings as they are yields the best results.

Looking at the data, it can also already be suspected that more iterations, and a lower min_count, are beneficial for the overall performance. Those hyperparameters will be evaluated in the next sections.

6.3.3. Minimum count

The minimum count defines how often a token has to appear in the training corpus in order to actually get assigned a vector representation. Tokens that appear less often are simply ignored and will not be encoded (and instead skipped over later when whole lists of tokens are converted to lists of vectors). This is mostly to ignore rare variable names, strings or other identifiers that are not really relevant. The word2vec model is trained with strings kept as they are, for 100 iterations, and with a vector size of 200. The `min_count` is chosen between 10 and 5000, with the following results:

<code>min_count</code>	100 iterations
10	71%
30	70%
50	69%
100	68%
300	67%
5000	67%

See figure 18 for a graphical representation. Although it might have seemed reasonable to assume that ignoring rare tokens would improve the performance, this was indeed not the case. The model performs better when nearly no tokens are ignored.




Fig. 18: Iterations and minimum count in the word2vec model

6.3.4. Iterations

The number of iterations defines the number of repetitions in training the word2vec model. It is to be expected that after a certain number of iterations, there will be no added benefit in further training. As before, the model is trained on a corpus with original strings included, with a dimensionality of 200, and a `min_count` of 10.

	iterations						
min_count	1	5	10	30	50	100	300
10	65%	65%	64%	71%	72%	72%	74%
5000	46%	48%	55%	61%	61%	67%	66%

It appears that up until 50 or 100 iterations, more iterations lead to a better performance of the model. Increasing the iterations to 300 does not improve the model performance significantly, and since it results in much longer time needed for training, there is no need to do so. Note that we can again confirm that a lower min_count generally results in better performance.

It is evident from the tables above that the word2vec hyperparameters do result in significantly different performances of the LSTM model that relies on the word2vec embedding, spanning a difference of roughly 25 percentage points for the LSTM's F1 score between the best and worst word2vec parameters. It can therefore be concluded that careful consideration of the hyperparameter values was not a waste of time, and the quality of the embedding has an influence on how well the final model is able to learn features.

The final word2vec model will encode code tokens in numerical vectors of 200 dimensions, not replace any strings, require a min_count of just 10 for tokens to be included, and will be trained for 100 iterations.

6.4. Parameters in creating the the dataset




Fig. 19: Parameters in creating the dataset

The dataset consists of samples, each of them representing a small snippet of code centered around a single token. As described in Section 5.2, when moving the focus

point through the source code, different step sizes n can be chosen. A smaller step size means more samples in total, and more overlap for the samples. The size of the context window around the token in focus is the second parameter, the full length of a code sample m . Both are measured in characters. All hyperparameters of the LSTM model are the default values described before in Section 6.2, and the ideal word2vec model determined before is used.

	n=5	n=10	n=15	n=20	n=25	n=30
m = 30	39%					27%
m = 50	44%	45%	41%	41 %	40%	38%
m = 100	60%	55%	49%	49%	47%	43%
m = 125	58%					46%
m = 150	60%					50%
m = 175	63%					52%
m = 200	66%					55%

A larger n consistently leads to worse results. This is most likely a result of the fact that if the gaps between one focus point and the next are large, there is not much overlap between their surrounding context, the moving window that makes up the code snippets. If the focus moves in very small steps, the code snippets have a lot of overlap, and consequently, a single token will appear several times: for instance, at the end of one snippet, at the center of the next, and at the start of the one after that. This means that for every vulnerability, there are samples that show the relevant code with more of the context before and after it, possibly making it easier for the model to learn which part is actually the source of the vulnerability.

The model performs better with a larger full length m of the code snippet making up one sample. A larger m again leads to more overlap. The disadvantage here is that the prediction might get a little less accurate, as a large snippet around some token might be classified as vulnerable because somewhere else in the snippet of length m is a vulnerable part. On the other hand, a larger m also has the advantage that more context can be taken into account for a token, which is precisely why the LSTM was chosen in the first place. For a full length of more than 200, the samples that were already quite numerous got also relatively large in size, exceeding the computational capabilities of the machines.

Going forward, a step length of $n=5$ and a full context window length of $m = 200$ were fixed as the parameters for creating the training set.

6.5. Hyperparameters and performance of the LSTM model

In order to answer research question 4 (*How effective is VUDENC in detecting vulnerabilities as measured with accuracy, precision, and recall?*), suitable hyperparameters for the LSTM model have to be determined. The next section is all about finding the best configuration for the LSTM model.

When evaluating different settings of one hyperparameter of the LSTM, the baseline

model is still used for all other hyperparameters (see Section 6.2): $n=5$, $m=200$, 30 neurons, 10 epochs, dropout 20% and adam optimizer. The word2vec model with the ideal configuration determined before is used for embedding the code samples.

6.5.1. Number of neurons

A higher number of neurons allows the model to capture more complex structures, but also increases the time needed for training.

Neurons	Accuracy	Precision	Recall	F1 Score
1	86%	38%	55%	45%
5	90%	51%	52%	52%
10	92%	66%	54%	59%
25	95%	80%	60%	70%
30	95%	86%	59%	69%
50	95%	88%	61%	72%
60	95%	86%	64%	73%
75	95%	89%	66%	76%
100	95%	88%	66%	75%
150	95%	87%	66%	75%
250	96%	90%	67%	77%




Fig. 20: Hyperparameters for the LSTM model

More neurons lead to a better performing model in general, with diminishing returns after around 50-70 neurons (see figure 20). Everything else being equal, the training time roughly doubles going from 1 neuron to 100 neurons, and doubles again from 100 to 250 neurons. For more epochs and larger datasets, the machines the models are trained on reached the limit of their capabilities, sometimes aborting the process. Therefore, 100 neurons are chosen as the best configuration.

6.5.2. Batch size

Using the baseline model, typical batch sizes (32, 64 and 128) and some batch sizes much smaller and much larger were tried, with the following results:

Batch Size:	32	64	128	200	250	500	1000	3000	5000
F1 score:	71%	71%	72%	68%	68%	68%	66%	60%	59%

The batch size does not seem to have a very strong influence on the overall performance of the model. Only a relatively huge batch size of more than 1000 reduces the performance (see figure 20). On the other hand, the batch size influenced the time needed for training the model significantly. While training with a batch size of 5000 took 45s per epoch, a batch size of 200 took 130s, for a batch size of 64 it were 270s, and for a batch size of 32 around 370s, the smallest that was feasible to complete. At a batch size of 10, it took nearly twenty minutes to train the model for just one epoch, so the training was aborted. It can be concluded for batch sizes smaller than 64, there is no improvement in accuracy and recall that would justify putting in the extra time needed for training with such small chunks of samples. Henceforth, a batch size of 128 will be considered optimal.

6.5.3. Dropout

Dropout and recurrent dropout are chosen together. The baseline model is trained again, but this time for 30 epochs. There are still some variations in the result that can account for a variance of around 2 percent points. The following results were obtained:

Dropout:	0%	5%	10%	15%	20%	25%	30%	35%	40%	45%	50%
F1 score:	70%	72%	71%	72%	69%	71%	65%	62%	60%	59%	56%

The model performs well up until a dropout of 25%. More random loss of neurons causes the overall performance to slowly decrease. Therefore, it seems like a justifiable choice to set the default dropout to 20%, preventing overfitting while still allowing for sufficient model performance (see figure 21).

6.5.4. Optimizer

The Keras model offers the standard adam optimizer and some related optimizers, such as RMSprop and adagrad as well as nadam and adamax. They are all tried out to evaluate their performance. As it has been described in Section 4.8, the stochastic gradient descent (SGD) optimizer is unlikely to yield good results, as the loss function F1 is not necessarily convex. Just out of curiosity, it is compared to the adam family optimizers.

Optimizer	Accuracy	Precision	Recall	F1
Adam	95%	87%	63%	72%
Adagrad	94%	78%	56%	65%
Adamax	94%	78%	56%	65%
Nadam	95%	86%	61%	71%
RMSProp	95%	86%	63%	73%
SGD	15%	10%	97%	19%

It seems that adam, nadam, and RMSprop perform slightly better than adagrad and adamax, possibly because they are well suited for on-line problems. The performance of the SGD is even worse than expected. The three best optimizers are compared again, this time with 50 epochs, which takes around three hours to train per optimizer.

Optimizer	Accuracy	Precision	Recall	F1
Adam	96%	90%	70%	79%
RMSProp	96%	91%	70%	80%
Nadam	96%	90%	67%	77%

As this is a very close call, adam is chosen as preferred standard optimizer. All else being equal, this optimizer is most likely to be used in other research, and therefore allows for easier comparison.

6.5.5. Number of training epochs




Fig. 21: Hyperparameters for the LSTM model

Training the model for more epochs increases the performance, but doing so too much can lead to overfitting, which is why the performance on the validation set (that was not used in training) has to be watched. The model was trained with 100 neurons. Note that the accuracy, precision, recall and F1 score are calculated from the performance on the validation set. Also, the model includes a dropout of 20%, which should work

to prevent overfitting. Obviously, more epochs also mean that it takes longer to train the whole model.

Epochs	Accuracy	Precision	Recall	F1
1	91%	57%	40%	45%
2	93%	68%	52%	59%
3	92%	69%	54%	61%
4	93%	72%	62%	66%
5	94%	83%	55%	66%
10	95%	89%	64%	74%
20	96%	91%	67%	77%
30	96%	88%	74%	80%
40	97%	91%	72%	81%
50	97%	89%	76%	82%
60	97%	92%	76%	83%
70	97%	90%	78%	83%
80	97%	91%	78%	84%
90	97%	90%	80%	84%
100	97%	92%	80%	85%
150	97%	91%	81%	85%
200	97%	91%	82%	86%

Apparently, there are significant improvements from longer training times (see figure 21). However, there is not much to be gained after 100 epochs, and 100 epochs are chosen for the model.

6.5.6. Optimal configuration

The hyperparameter settings deemed optimal given the dataset and the restrictions in computational power and disk space are:

- 100 neurons
- training for 100 epochs
- dropout and recurrent dropout of 20%
- batch size 128
- optimizing with the adam optimizer

With those hyperparameters, the model can now be trained on all vulnerabilities to achieve the best possible results.

6.6. Performance for subsets of vulnerabilities

To answer research question 3 - *Which types of vulnerabilities can be detected?* - the vulnerabilities are examined one by one. Out of all vulnerabilities that were considered in the beginning, several had to be excluded. The keywords `cross origin`, `buffer overflow`, `function injection`, `clickjack`, `eval injection`, `cache overflow`, `smurf` and `denial of service` only yielded very few results, and no dataset of reasonable size could be created.

The keywords `brute force`, `tampering`, `directory traversal`, `hijacking`, `replay attack`, `man-in-the-middle`, `fromatstring`, `unauthorized` and `sanitize` resulted in many commits that were not related to security issues. A manual inspection of some randomly picked samples showed that those commits were mostly fixing other issues that had nothing to do with preventing an exploit. Therefore, no quality dataset could be created for those vulnerabilities.

This leaves seven vulnerabilities for which a dataset could be created. Using the determined ideal hyperparameters, the LSTM model is trained on them with the goal of maximizing the F1 score. The results are presented in the following table.

Vulnerability	Accuracy	Precision	Recall	F1
SQL injection	96.5%	91.3%	74.7%	82.2%
XSS	98.9%	98.0%	90.1%	93.9%
Command injection	99.0%	95.6%	80.3%	87.3%
XSRF	98.6%	95.4%	80.6%	87.4%
Remote code execution.	89.3%	96.4%	69.1%	80.5%
Path disclosure	97.9%	94.5%	75.6%	84.0%
Open redirect	98.0%	94.3%	74.5%	83.2%

It appears that while the optimizer tries to minimize the F1 score, this is done more easily by improving the precision, while the recall is a little lower.

To illustrate what the model actually does when performing predictions on code, in the appendix there are three examples given for each vulnerability, with their commit changes and the results of analyzing them with VUDENC.




Fig. 22: Commit for vulnerability (SQL injection)

<https://github.com/uktrade/export-wins-data/commit/307587cc00d2290a433bf74bd305aecffcb05a2>

```

sql_str = "SELECT id FROM wins_completed_wins_fy"
if self.end_date:
    sql_str = f"{sql_str} where created <= '{self.end_date.strftime('%m-%d-%Y')}'"

with connection.cursor() as cursor:
    cursor.execute(sql_str)
    ids = cursor.fetchall()

wins = Win.objects.filter(id__in=[id[0] for id in ids]).values()

for win in wins:
    yield self._get_win_data(win)

def get(self, request, format=None):
    end_str = request.GET.get("end", None)
    if end_str:
        try:
            self.end_date = models.DateField().to_python(end_str)
        except ValidationError:
            self.end_date = None

```

Fig. 23: Detection of vulnerability (SQL injection)

6.6.1. SQL injection

The data for the sql injection vulnerability was split in training set and test set, resulting in 96041 samples for training and 20581 for testing. Roughly 10.9% of those code snippets contained some vulnerable code. After training the LSTM model for 100 epochs on the training set, with hyperparameters as specified above, it achieved an accuracy of 96.5%, a precision of 91.3%, a recall of 74.7% and therefore an F1 score of 82.2% as measured on the test set.

A relatively small example of an sql injection fix on Github and the vulnerable code part being detected by the model can be seen in Figures 22 and 23. In the vulnerable code snippet, the command `cursor.execute` is used to execute an SQL query stored in the variable `sql_str`, which is created by directly putting other variables together in a string. More examples can be found in the appendix.

6.6.2. Cross-site scripting

Splitting and processing the data for cross-site scripting resulted in 17010 trainings samples and 3645 test samples with a rate of 8.9% vulnerable samples. After the training on the training set, the model performed on the test set with an accuracy of 89.9%, a precision of 98.0%, a recall of 90.1% and an F1 score of 93.9%, the highest of all trained vulnerabilities. This is possibly due to a relatively narrow set of commits from Github that are almost all relevant to the actual problem, with little 'contamination' by other fixes and patches.

See Figures 24 and 25 for an example of how the model detects an XSS vulnerability. A piece of html content for a comment section is created dynamically using the variable `self.content`, which should be escaped to ensure that no scripting can be injected there.




Fig. 24: Commit for vulnerability (XSS)

<https://github.com/dongweiming/lyanna/commit/fcefac79e4b7601e81a3b3fe0ad26ab18ee95d7d>

```
async def save(self, *args, **kwargs):
    content = kwargs.pop('content', None)
    if content is not None:
        await self.set_content(content)
    return await super().save(*args, **kwargs)

@property
async def content(self):
    rv = await self.get_props_by_key('content')
    if rv:
        return rv.decode('utf-8')

@property
async def html_content(self):
    content = await self.content
    if not content:
        return ''
    return markdown(content)

async def clear_mc(self):
    for key in (MC_KEY_N_COMMENTS, MC_KEY_COMMENT_LIST):
        await clear_mc(key % self.post_id)

@property
async def user(self):
    return await GithubUser.get(gid=self.github_id)

@property
async def n_likes(self):
    return (await self.stats).love_count
```

Fig. 25: Detection of vulnerability (XSS)

6.6.3. Command injection

The command injection model performed on the test set with an accuracy of 99.0%, a precision of 95.6%, a recall of 80.3% and an F1 score of 87.3%. From the dataset, 51763 training samples and 11073 test samples were created, with a rate of 4.6% samples containing a vulnerability. Refer to Figures 26 and 27 for one example, or the appendix for more. The example presented here shows a piece of code that executes a command with `subprocess.call` to execute the Java compiler. Since the command is handed over as a string and with the parameter '`shell=True`', additional items can be treated as additional arguments to the shell, allowing for an injection of other commands.



Fig. 26: Commit for vulnerability (Command injection)

<https://github.com/Atticuss/ajar/commit/5ed8aba271ad20e6168f2e3bd6c25ba89b84484f>

```
with open("tmp/%s" % backdoor, 'w') as f:
    for l in bd.split("\n"):
        if "main(" in l:
            inmain=True
            f.write(l)
        elif "}" in l and level<2 and inmain:
            f.write("%s.main(args);}" % oldmain)
            inmain=False
        elif "}" in l and level>1 and inmain:
            level-=1
            f.write(l)
        elif "{" in l and inmain:
            level+=1
            f.write(l)
        else:
            f.write(l)
print("[*] Provided backdoor successfully modified")

print("[*] Compiling modified backdoor...")
if subprocess.call("javac -cp tmp/ tmp/%s" % backdoor, shell=True) != 0:
    print("[!] Error compiling %s" % backdoor)
print("[*] Compiled modified backdoor")

if (len(oldmain)<1):
    print("[!] Main-Class manifest attribute not found")
else:
    print("[*] Repackaging target jar file...")
    createZip("tmp", outfile)
    print("[*] Target jar successfully repackaged")
shutil.rmtree('tmp/')
```

Fig. 27: Detection of vulnerability (Command Injection)

6.6.4. Cross-site request forgery

The data was processed in 68434 training samples, 14665 test samples, and roughly 5.9% of all samples contained vulnerable code. With an accuracy of 98.6%, a precision of 95.4%, a recall of 80.6% and a resulting F1 score of 87.4%, the model was able to

perform very well on the test data set for XSRF. A small example illustrates a XSRF vulnerability (Figure 28) and how the model detects it (Figure 29). In this case, a check for correct XSRF cookies that prevent XSRF attacks was simply missing.




Fig. 28: Commit for vulnerability (XSRF)

<https://github.com/deepnote/notebook/commit/d7becafd593c2958d8a241928412ddf4ba801a42>

```
@property
def content_security_policy(self):
    # In case we're serving HTML/SVG, confine any Javascript to a unique
    # origin so it can't interact with the notebook server.
    return super(FilesHandler, self).content_security_policy + \
        "; sandbox allow-scripts"

@web.authenticated
def head(self, path):
    self.get(path, include_body=False)

@web.authenticated
def get(self, path, include_body=True):
    cm = self.contents_manager

    if cm.is_hidden(path) and not cm.allow_hidden:
        self.log.info("Refusing to serve hidden file, via 404 Error")
        raise web.HTTPError(404)

    path = path.strip('/')
    if '/' in path:
        _, name = path.rsplit('/', 1)
    else:
        name = path

    model = yield maybe_future(cm.get(path, type='file', content=include_body))

    if self.get_argument("download", False):
        self.set_attachment_header(name)
```

Fig. 29: Detection of vulnerability (XSRF)

6.6.5. Path disclosure

The number of training samples for this vulnerability was 55072, with 11802 test samples, and a rate of 7.13% vulnerable samples. The model performed on the test set with an accuracy 97.9%, a precision 94.5%, a recall of 75.6% and a total F1 score of 84.0%. Refer to Figures 30 and 31 for an example, or see the appendix. In the example, a path disclosure was fixed by using the `commonprefix` function to check if the requested path is within the web root directory. The example also illustrates how the model finds flaws in different parts of the sourcecode.




Fig. 30: Commit for vulnerability (Path disclosure)

<https://github.com/zcutlip/pyweb/commit/76918b12c408529eaf04f75917f128f56e250111>

```

def _sanity_check_path(self, src, dst, www_root):
    logger = self.logger
    if not os.path.isdir(src):
        msg = "Source path: %s does not exist or is not a directory." % src
        logger.critical(msg)
        raise ContentInstallerException(msg)

    if not os.path.isdir(www_root):
        msg = "Web root %s does not exist or is not a directory." % src
        logger.critical(msg)
        raise ContentInstallerException(msg)

    www_root_abs = os.path.abspath(www_root)

    rel_dst = dst
    if os.path.isabs(dst):
        _root = os.path.commonprefix([www_root_abs, dst])
        if _root is not www_root_abs:
            msg = "Destination path is absolute and is not a subdirectory of web root. {}".format([www_root, dst])
            logger.critical(msg)
            raise ContentInstallerException(msg)
        rel_dst = os.path.realpath(www_root_abs, dst)
    else:
        _dst = os.path.join(www_root_abs, dst)
        _dst = os.path.realpath(_dst)
        _root = os.path.commonprefix([www_root_abs, _dst])
        if _root is not www_root_abs:
            msg = "Destination is a relative path that resolves outside of web root. {}".format([www_root_abs, dst])
            logger.critical(msg)
            raise ContentInstallerException(msg)
        rel_dst = os.path.realpath(www_root_abs, _dst)

    abs_dst = os.path.join(www_root_abs, rel_dst)
    if os.path.exists(abs_dst):
        msg = "Destination directory already exists: {}".format(abs_dst)
        logger.critical(msg)
        raise ContentInstallerException(msg)

    return (src, rel_dst, www_root_abs)

def install(self):
    logger = self.logger
    src_path = self.src_path
    dst_path = os.path.join(self.www_root, self.dst_path)
    logger.info("Copying %s to %s" % (src_path, dst_path))
    try:
        shutil.copytree(src_path, dst_path, symlinks=True)
    except Exception as e:
        logger.critical("Exception: {}".format(e))
        raise

```

Fig. 31: Detection of vulnerability (Path disclosure)

6.6.6. Remote code execution

The data for remote code execution was processed resulting in a total of 45723 training samples and 9797 test samples. Roughly 5.3% of the samples were vulnerable, the rest was considered clean. After being trained on the training set, the model performed on the test set with relatively low accuracy compared to the other vulnerabilities: 'just' 89.3%. The recall was also a little lower than what was achieved for the other vulnerabilities, with just 69.1%. In total, an F1 score of 80.5% was achieved. As with the other vulnerabilities, there is an example presented here (Figures 32 and 33), and two more in the appendix. The example shows a case in which a call to `os.system` is used to execute a command that is constructed via concatenation of strings. Passing the command as a sequence instead is preferred, because then only the first element in the sequence will be interpreted as a program to execute (for a more thorough explanation, see the python docs on 'subprocess').




Fig. 32: Commit for vulnerability (Remote Code Execution)

<https://github.com/ntc-chip-revived/ChippyRuxpin/commit/0cd7d78e4d806852fd75fee03c24cce322f76014>

```
def talk(myText):
    if( myText.find( "twitter" ) >= 0 ):
        myText += "0"
        myText = myText[7:-1]
        try:
            myText = twitter.getTweet( myText )
        except:
            print( "!!!ERROR: INVALID TWITTER CREDENTIALS. Please read README.md for instructions." )
            return

    os.system( "espeak \"...\" 2>/dev/null" ) # Sometimes the beginning of audio can get cut off. Insert silence.
    time.sleep( 0.5 )
    os.system( "espeak -w speech.wav \"\" + myText + "\" -s 130" )
    audio.play("speech.wav")
    return myText

mouthThread = Thread(target=updateMouth)
mouthThread.start()
eyesThread = Thread(target=updateEyes)
eyesThread.start()
audio = AudioPlayer()

if( consumerKey.find( 'TWITTER' ) >= 0 ):
    print( "WARNING: INVALID TWITTER CREDENTIALS. Please read README.md for instructions." )
else:
    twitter = ChippyTwitter(consumerKey,consumerSecret,accessTokenKey,accessTokenSecret)

web = WebFramework(talk)
isRunning = False
io.cleanup()
sys.exit(1)
```

Fig. 33: Detection of vulnerability (Remote Code Execution)

6.6.7. Open redirect

After processing the data, there were 38189 training samples and 8184 test samples. Around 6.4% of all samples contained a vulnerability. For this last vulnerability, an accuracy of 98.0%, a precision of 94.3%, a recall of 74.5% and an F1 score of 83.2% was reached. Figures 34 and 35 demonstrate how the model detects a typical and small example, in which the next url for the session is requested without sanitization, allowing untrusted url strings to contain redirect parameters that send the user to a different page than was intended. Two more examples can be found in the appendix.




Fig. 34: Commit for vulnerability (Open redirect)

<https://github.com/karambir/mozilla-django-oidc/commit/22b6ecb953bbf40f0394a8bfd41d71a3f16e3465>

```
params = {
    'response_type': 'code',
    'scope': 'openid',
    'client_id': self.OIDC_OP_CLIENT_ID,
    'redirect_uri': absolutify(
        request,
        reverse('oidc_authentication_callback')
    ),
    'state': state,
}

if import_from_settings('OIDC_USE_NONCE', True):
    nonce = get_random_string(import_from_settings('OIDC_NONCE_SIZE', 32))
    params.update({
        'nonce': nonce
    })
    request.session['oidc_nonce'] = nonce

request.session['oidc_state'] = state
request.session['oidc_login_next'] = request.GET.get(redirect_field_name)

query = urlencode(params)
redirect_url = '{url}?{query}'.format(url=self.OIDC_OP_AUTH_ENDPOINT, query=query)
return HttpResponseRedirect(redirect_url)

class OIDCLogoutView(View):
    """Logout helper view"""
```

Fig. 35: Detection of vulnerability (Open redirect)

7. Discussion

The following section is dedicated to discussing the results and comparing them to other works in the field.

7.1. Answers to research questions

7.1.1. Research question 1

Can a dataset of suitable Python source code be mined from Github for common vulnerability types?

With respect to RQ1, it can be reported that despite some technical challenges, a satisfyingly large dataset could be acquired.

The full dataset (before filtering) consists of 25040 commits in 14686 different repositories. From this, specialized datasets are created for each vulnerability. Only files that are python source code are part of the datasets. Excessive duplicates are excluded as well as projects that are showcases for vulnerabilities or demonstrate hacking techniques, and low-quality data is filtered out according to some heuristics. The final datasets contain the source code and some information about the commit as well as the vulnerable and the clean segments within the code. In total, 7 different types of vulnerabilities are part of the data set: SQL injection, cross-site scripting, command injection, cross-site request forgery, open redirect, path disclosure and remote code execution vulnerabilities.

Each vulnerability datasets stems from at least 39, some from several hundred different repositories or projects. Each vulnerability dataset contains source code between 14.000 and 83.000 lines of code in total, spread out to 80-650 files with between 700 and 5.000 functions.

7.1.2. Research question 2

Is the word2vec model effective as an embedding, and how do its hyperparameters influence the overall results?

In short: the word2vec model is suitable as an effective embedding.

The performance of the LSTM model depends on the quality of the word2vec embedding. Choosing hyperparameters for the word2vec model that are not suitable can easily result in a significant drop in performance for the classification capabilities of the LSTM model, as measured by a difference of about 25 percentage points in the F1 score. Vice versa, correctly chosen hyperparameters for the embedding result in an LSTM that can learn features well enough to achieve a very good precision and recall, and thus F1 score. Therefore, the word2vec model can definitely be described as a suitable and effective embedding mechanism.

It was determined that a higher dimensionality for the embedding vectors leads to better results, up to a dimensionality of around 200. Encoding the source code exactly as it is, and not replacing strings with a general string token, proved to be the better

alternative. It was found that the results were better when the minimum number of occurrences in the corpus that was required (so that a token would be assigned a numerical representation) was very low, meaning that even very rare tokens, that appeared just ten times or more in the training corpus, were included. The ideal number of iterations was somewhat restricted by the computational restrictions, as more than - at most - 300 iterations were not feasible on the machines. However, after 100 iterations, the gains did not continue to grow very much, therefore 300 iterations can be determined as a very generous choice for ideal results. Overall, the use of a word2vec embedding can definitely be recommended as a feasible approach for future, similar research.

7.1.3. Research question 3

Which types of vulnerabilities can be detected?

After disregarding keywords that resulted in very low-quality results (see Section 5.1.5), or were not represented in enough samples to form a dataset of reasonable size. The LSTM model was trained on the remaining types of vulnerabilities. Features could be learned and successfully applied to discover the same patterns in new code. For each vulnerability, a separate model was trained. The vulnerabilities are:

- SQL injection
- Cross-site scripting (XSS)
- Command injection
- Cross-site request forgery (XSRF)
- Path disclosure
- Remote Code Execution
- Open Redirect

All those are vulnerabilities that are widespread and in many cases dangerous to applications and systems (refer to the OWASP guide sheets or the CVE database).

7.1.4. Research question 4

How effective is VUDENC in detecting vulnerabilities as measured with accuracy, precision, and recall?

The models were trained with the goal of optimizing the F1 score. The accuracy of the predictions (the share of correct predictions compared to all predictions) ranged from 89% to 98%. The precision (the fraction of true positives in all positive predictions) ranged from 94% to 98%, suggesting a very low false positive rate. The recall is a little lower, between 75% and 90%, which means that no more than one fourth of the

samples labeled as 'vulnerable' was missed. Finally, the overall F1 score, the harmonic mean of precision and recall, ranges from 82%-93%, which is a very satisfying result.

7.2. Comparison with other works

The following section contains comparisons with similar works in the field to provide a reference frame for the evaluation of this work. Of course, there are fundamental differences in each approach, and no direct comparison can be drawn.

Approaches are compared under the following aspects:

- **Language:** what language is subject of the classification efforts
- **Data basis:** does the data stem from real-life projects or from synthetic databases (such as benchmark data sets).
- **Labels:** how are the labels for the training data originally generated
- **Granularity:** is the code evaluated on a rough granularity (whole classes or files) or a fine granularity (lines or tokens)
- **Machine Learning Approach:** what class of neural network or machine learning approach is used (CNN, RNN, LSTM)
- **Vulnerability types:** which kinds of vulnerabilities are detected
- **Size of data set:** how many functions, projects, classes etc. make up the dataset
- **Scope and applicability:** Has the model been trained on a single project and can it only classify files within that application, or is it generally applicable to any code from a large variety of sources

Russel et al. [RKH⁺18] worked directly on lexed source code and use a similar approach to VUDENC. They take C and C++ code from real software packages including Github and the Debian Linux distribution as well as from benchmark datasets to find vulnerabilities. Their dataset is large, including 9 million functions from Github. In contrast to VUDENC, they do not use LSTMs, but the verysimilar CNN and RNN networks. The main difference is that they use static parsers to generate the labels, while VUDENC relies only on commit contexts to create labels. They identify five different types of vulnerabilities, including buffer overflows and null pointers, which of course are quite different from the vulnerabilities found in Python code. Russel et al. use a random forest classifier for the final classification step. On natural data sets, they achieve an F1 score of 0.566.

Pang et al. [PXN15] use a hybrid n-gram and feature selection analysis on a dataset consisting of four Java android applications. They downloaded the labels from an online benchmark that was already prepared. They conduct their analysis on the level of whole classes (rough granularity) and try to predict whether the class contains a vulnerability or not by training a support vector machine. While they achieve good results for

prediction within the same project (accuracy, precision, and recall around 90 percent), the cross-project results are less strong with an F1 score of around 65%. The two main differences here are that VUDENC uses a much larger and more diverse dataset, and that it can point out very specific locations in the code where a vulnerability might be, possibly being more useful to the developer in practice.

The tool VuRLE [MTL⁺17] was trained on 40 applications in Java collected from Github. The commits are analyzed manually to find vulnerabilities of five different types. Abstract syntax trees are the basis for the approach in which 'edit groups' are created to classify vulnerabilities, using 10-fold cross-validation. Five different kinds of vulnerabilities are detected, including SQL injections. Although their main goal is to create repair templates, they first have to detect vulnerabilities, which they manage with an F1 score of around 65%.

Li et al. [LZX⁺18] developed the tool VulDeePecker to detect buffer error vulnerabilities and resource management error vulnerabilities in C/C++ programs. They work on a 'code gadget database' made from a large number of popular open-source projects, including the Linux kernel and Firefox. The vulnerabilities are found by using the NVD and SARD dataset, which contain synthetic and real-life / production code, flaws, and vulnerabilities. In selecting their data from those sources, Li et al work on very high-quality code. Just like VUDENC, they use code changes / patches to find vulnerabilities and create their labels, but include a second step of human supervision to double-check every positive label manually (in contrast, the approach taken for VUDENC is completely automatic). They train a bidirectional LSTM and achieve an impressive F1 score of around 85-95%. VUDENC can not achieve quite the same high score since it uses data from all kinds of Github projects, which are not as clearly categorized and perfectly categorized as the high-profile projects which are used to train VulDeePecker. Furthermore, the VUDENC database only consists of real-life code and no synthetic code.

The authors of VulDeePecker compare their tool to other approaches and find an F1 score of 27% for the tool Flawfinder, 47% for Checkmarx, 18.2% for VulPecker, and 9.3% for VUDDY. The latter two, however, are optimized to have close to zero false positives.

The authors of [DTP⁺17] train an LSTM on 18 android applications. In an approach that is very similar to VUDENC, they look at code tokens and represent them with multi-dimensional vectors, however, their feature extraction algorithm is focused on the specific project, learning relevant syntactic and semantic information that is specific for this one application. They only classify whole files, working on a very rough granularity. In their best configuration, they achieve a precision, recall and F1 measure of around 91% - however, only for predictions within the *same single* project on which the classifier was trained. For inter-project predictions, they do not present those metrics, but rather state the *number* of other projects (out of 17) that a model trained on one project can classify with precision and recall of more than 80%. On average, their models are able to classify the vulnerabilities in 4 out of 17 other projects.

Hovsepyan et al. [HSJW12] focus their efforts on one single Java application and try to predict whether a whole file is vulnerable or not. To this end, they split the file in

tokens and use a static tool to create the labels for their files, and use a radial base function and a grid search algorithm to learn their features for the classification. They achieve an accuracy, precision, and recall of over 80%. It is unclear how useful those results are, given that they work only on this one single project, and they can not locate vulnerabilities, but only classify whole files.

characteristics of approach							resulting metrics			
Name	Language	Data	Labels	Scope	Granularity	Method	Acc.	Pre.	Rec.	F1
Russel et al.	C/C++	real & synth.	static tool	general	token level (fine)	CNN, RNN				57%
Pang et al.	Java	real	pre-existing	4 apps	whole classes	SVM	63%	67%	63%	65%
VuRLE	Java	real	manually identified	general	edits (fine)	10-fold CV		65%	66%	65%
VulDeePecker	C/C++	real & synth.	patches & manual	general	API/function calls	BLSTM				85%-95%
Dam et al.	Java	real	static tool	18 apps	whole file	LSTM	4 / 17 (see above)			
Hovsepyan et al.	Java	real	static tool	1 project	whole file	grid search	87%	85%	88%	85%
VUDENC	Python	real	patches	general	token level	LSTM	89-99%	94-98%	75-90%	82-93%

In conclusion, we see that higher metrics in precision, recall and F1 are much easier to achieve if the approach focuses on predictions within a single project, as Hovsepyan et al. [HSJW12] and Dam et al. [DTP⁺17] do when they train a classifier to predict vulnerabilities within the very same application. Training a classifier that is applicable for general detection of vulnerabilities is much harder - but also leads to a much more useful end result. Note that the same two approaches, as well as the one taken by Pang et al. [PXN15], are also only trying to predict whether a whole file is vulnerable or not without being able to point out the exact location of the vulnerability. Since VUDENC aims to develop a general vulnerability detector that can be used at the fine granularity of code tokens, it has a much more complicated task to fulfill.

Furthermore, the quality of a model depends a lot on the quality of the underlying data. Classification and prediction on synthetic data sets, or data sets that are curated and selected manually, will therefore be easier than training a model on possibly messy real-life code from sources such as Github. With essentially the same approach, Russel et al. achieved 56% on natural code from Github, but 84% on the SATE test suite due to its clean and consistent style and structure. The VUDENC approach arguably performs quite well given that it works purely on natural real-life code.

7.3. Limitations and threats to validity

7.3.0.1. Labeling based on the commit context

A major threat to the external validity of this work is the reliance on commit contexts for classifying code snippets into vulnerable or (probably) not vulnerable. It is assumed that in general, there was an actual vulnerability, and the fixed version is in some way better than the previous versions. Of course, there are many situations in which

those assumptions do not hold true. There is no other method of double-checking the vulnerability status applied in this work. The typical way to do this would be to choose a static analysis tool or bug checker, however, this work aims to work out the insights that can be gained without *any* prior knowledge or pre-made assumptions about vulnerabilities, just using the code database as a source of information for the neural network. There might be a lot of undetected vulnerabilities in the files labeled as 'possibly not vulnerable' just because no developer ever fixed them, and our network can therefore also not learn to spot them. Furthermore, some fixes could be wrong. The answer to this problem is purely the size of the dataset, in which such restrictions might not play a big role compared to many legitimate fixes that share characteristics.

7.3.0.2. Systematic oversights due to developer decisions

The dataset does only contain fixes that were actually applied by developers, and vulnerabilities that are either never detected or that developers chose to ignore remain invisible for the algorithm. This leads inevitably to blind spots in the classifier which restrict its ability to spot vulnerabilities. Note that Liu et al. [LKB⁺18] use exactly this restriction in their work *on purpose*, as they are trying to learn which violations are actually fixed by developers and are therefore with some certainty not false positives. The situation is therefore ambivalent: false positives as they would result from using tools that report assumed violations are avoided better by only taking problems into account that were actually fixed. On the other hand, false negatives could be introduced for vulnerabilities that developers do not notice, understand or care about.

7.3.0.3. Limitations in types of vulnerabilities

Although a variety of different types of vulnerabilities were taken into account than in many other works, the list is of course not complete and the work focuses only on the most important and typical vulnerabilities. Therefore, rare and atypical kinds of vulnerabilities are not caught by the vulnerability detection.

7.3.0.4. Issues regarding the underlying data

The data collected from Github might not be entirely representative of Python source code in general. All data stems from projects that are publicly available on the platform, therefore the findings might not be applicable to industry and closed-source projects that might have different approaches regarding code quality and spotting vulnerabilities. Furthermore, although we excluded projects that were marked as a fork on Github, it is very well possible that several projects in our database are very similar to each other. By the nature of open-source and code sharing practices, some parts of the code in different repositories might even come close to being duplicates, meaning that the dataset is more limited than it first seems. Threats to internal validity include the fact that only Python files were taken into account and XML files were ignored, although they might include security-relevant information. Regarding the applicability of the examples to the vulnerabilities, there were many samples that contained a mixture of

different patches, or fixes that did not relate to the vulnerability at all (see Section 5.1.5). Of course, any vulnerability might also occur in ways that was simply not represented in our dataset and can therefore not be learned and recognized by the model. While those issues are partially resolved by only taking vulnerabilities for which good datasets could be gathered, and collecting large numbers of samples overall to even out those complications, it remains an issue and cleaner data would definitely be favoured.

7.3.0.5. Unknown vulnerabilities

The predictions are evaluated against known vulnerabilities in the past. A prerequisite for the model is the existence of vulnerabilities to learn from, and in cases where no known examples for code with vulnerabilities are available, this method cannot be applied. As pointed out by Yamaguchi et al. [YLR12], such situations are rare in practice, as the main concern for large software repositories is not to discover a single vulnerability, but to make sure that the same type of error does not spread across the project, which is what this method is useful for. Future vulnerabilities that are not yet known, or that developers are not aware of yet, can of course not be taken into account.

7.3.0.6. Not capturing the full context of a vulnerability

The diff around a change provides that changed lines and three lines before and after them, respectively. There are certainly many situations in which a vulnerability stems from the interaction of lines of code that are spread out over a large file (or several files) and are interacting despite their distance from each other. However, the examples for vulnerabilities used to train the model only focus on the surroundings of the fixed lines, and therefore, the model cannot learn the implications of very far-reaching dependencies.

7.3.0.7. Conclusion validity

By using standard performance measures for the classifier that have been applied in other works regarding vulnerability prediction, threats to conclusion validity are minimized. To evaluate the performance of the predictions, accuracy, precision, and recall were used. However, in practice, there may be other metrics and representation demonstrating how well a classifier performs.

7.3.0.8. Chosen method, model and hyperparameters

Threats to internal validity also include limitations in the chosen method. The basic prediction model used in this work is an LSTM, and as described at length in Section 3, other models are used as well, such as CNNs, naive bayes, and more. The results obtained from different models may vary. The data has been embedded using a word2vec model that was custom made for this application, and shortcomings in the word2vec model could affect the overall performance of the LSTM. Furthermore, some design decisions

were made, such as excluding occurrences of more than three separators in a row, which might affect the overall end result.

7.3.0.9. Relying on source code

The present design of this work is limited to dealing with vulnerabilities in source code, for which such source code must be available. The detection of vulnerabilities in binary files or executables is a different problem that is not tackled here.

7.3.0.10. Limitation in programming language

The present version of the word2vec encoding used, the collection of files for training and testing the work, and the whole concept only looks at Python code. While there is no specific reason why Python should be more or less suitable for vulnerability detection than other languages that researchers in the field focus on (mainly C, C++, Java, PHP and Javascript), this is undoubtedly a strong restriction of the model.

7.4. Future work

Open problems for future research are abundant. First, the approach itself could probably be tweaked and improved, for instance, by optimizing the labeling process or collecting more data.

The data could be curated and filtered more thoroughly, leading to much more representative samples. By double-checking the collected samples either manually or with a static tool (or some other approach), it could be ensured that a larger percentage of the samples actually contains relevant examples. Consequently, even vulnerabilities that could not be taken into account in this work due to low quality data (such as the replay attack) could receive the attention they deserve. Given that several types of vulnerabilities had to be excluded because the approach did not yield enough examples, or too many unrelated results, improving the process of gathering data is highly promising. It seems plausible that an underlying dataset of higher quality would be the main contributor to a better end result.

Experiments on code in **other programming languages** are of interest. The proposed approach could be extended to other programming languages such as PHP, C++ or Java. A first step would be to check if the word2vec encoding for those programming languages can be created with the same success. Then, the LSTM could be trained on vulnerability datasets in those other languages and compared to the works of other researchers.

The proposed approach could also be applied to specific other **types of applications** including a specific focus on web applications, mobile applications or software in specific domains that come with their own typical security risks.

Of course, it is also of interest to take more different **types of vulnerabilities** into account. Note that some vulnerabilities like buffer overflows or memory management

issues are responsible for many dangerous exploits, but are only relevant in other programming languages such as C or C++. Extending the scope of the language therefore also comes with other vulnerabilities that are to be taken into account.

The approach could also be extended to predicting **defects and bugs** of other kinds in code. There is a whole research area dealing with this problem, and the application of long short term memory networks trained on natural code can surely offer valuable insights.

Conceptionally, there are alternatives in creating the **feature vector** that could be investigated. Various other works that have been mentioned before could provide inspiration for different approaches. Just to name a few possibilities: The feature vectors could be learned based on abstract syntax trees instead of code as text. They could be created with an underlying dataset that combines source code with code metrics such as complexity or quality metrics. Several different ways of preprocessing the code (for instance, only keeping built-in functions, removing strings, removing unique variable names, only using API calls, and so on) could be evaluated and compared. The possibilities are vast and a lot of work is still to be done in this area.

A very worthwhile continuation of this work could be the creation of automatic **fix patterns**. Since the original data from Github that was mined already focuses on commits and therefore each sample in the dataset is a fix, the data lends itself to this kind of application. Automated program repair is the logical next step that could just not be included in this work because of time and scope constraints.

Finally, a future extension could involve building a fully functional **vulnerability detection system** with high usability that takes code as input and predicts vulnerabilities. While a simple prototype has already been constructed in this work, it has not been optimized for usability in daily programming. One option would be to create a plugin for an IDE or a highly customizable command line tool.

Conclusion

In this work, VUDENC has been presented, a system for vulnerability detection based on deep learning on a natural code base. VUDENC's purpose is to relieve human experts from the time-consuming and subjective work of manually defining features for vulnerability detection. This work demonstrates the potential of using machine learning directly on source code in order to learn such vulnerability features by leveraging LSTM models. VUDENC works on Python source code and can predict 8 different types of vulnerabilities.

Firstly, the background was examined and described, including the theory of machine learning concepts and approaches for mining software repositories, and a brief overview for several security vulnerabilities was given. Then, related work has been described, categorized and compared to this work.

To create the basis for VUDENC, a large dataset of commits was mined from Github and labeled according to the commit context. The data stems from several hundred real-world repositories containing natural source code and covers 7 different types of vulnerabilities, including SQL injections, cross-site scripting and command injections. The dataset has been made publicly available and can be used to replicate this work and conduct further research. A word2vec model has been trained on a large corpus of Python code to be able to perform embeddings of code tokens that preserve semantics, and has been made available as well.

The raw sourcecode was preprocessed and the datasets for each vulnerability were built by taking every single code token with its context (the tokens before and after it) as one sample and embedding it using the word2vec model. The LSTM network was trained to detect vulnerable code on the level of individual tokens.

Systematic experiments show that VUDENC achieves a accuracy of 87%-98%, a recall of 68%-90%, a precision of 87-98% and an F1 score of 78-93%. These results are very promising and encourage further research in this area. VUDENC is able to highlight the specific areas in code that are likely to contain vulnerabilities and provide confidence levels for its predictions. It can be adjusted in ordner to focus on minimizing the rate of false positives or false negatives.

Future work should focus on improving the approach for labeling the data, combining VUDENC with other approaches for enhanced results, and leveraging the commit context to create actionable fix recommendations. The work could also be extended to other programming languages or types of vulnerabilities.

The code for VUDENC has been made available as a public github repository at <https://github.com/LauraWartschinski/VulnerabilityDetection/> alongside with datasets, trained models, and examples.

Bibliography

Literatur

- [ABDS18] Miltiadis Allamanis, Earl T. Barr, Premkumar Devanbu, and Charles Sutton. A survey of machine learning for big code and naturalness. *ACM Computing Surveys (CSUR)*, 51(4):81, 2018.
- [AJ06] Ashish Aggarwal and Pankaj Jalote. Integrating static and dynamic analysis for detecting vulnerabilities. In *30th Annual International Computer Software and Applications Conference (COMPSAC'06)*, volume 1, pages 343–350, 2006.
- [AS13] Miltiadis Allamanis and Charles Sutton. Mining source code repositories at massive scale using language modeling. In *Proceedings of the 10th Working Conference on Mining Software Repositories*, pages 207–216, 2013.
- [Aye19] Ayesha Cuthbert. 8 top programming languages & frameworks of 2019, 15. 4. 2019. URL: <https://hackernoon.com/8-top-programming-languages-frameworks-of-2019-2f08d2d21a1> [cited 3. 10. 2019].
- [BCF⁺08] Davide Balzarotti, Marco Cova, Vika Felmetsger, Nenad Jovanovic, Engin Kirda, Christopher Kruegel, and Giovanni Vigna. Saner: Composing static and dynamic analysis to validate sanitization in web applications. In *2008 IEEE Symposium on Security and Privacy (sp 2008)*, pages 387–401, 2008.
- [BKA⁺07] Stefan Bellon, Rainer Koschke, Giulio Antoniol, Jens Krinke, and Ettore Merlo. Comparison and evaluation of clone detection tools. *IEEE Transactions on Software Engineering*, 33(9):577–591, 2007.
- [BRBR16] Avishkar Bhoopchand, Tim Rocktäschel, Earl Barr, and Sebastian Riedel. Learning python code suggestion with a sparse pointer network. *arXiv preprint arXiv:1611.08307*, 2016.
- [BSF⁺94] Yoshua Bengio, Patrice Simard, Paolo Frasconi, et al. Learning long-term dependencies with gradient descent is difficult. *IEEE transactions on neural networks*, 5(2):157–166, 1994.
- [CM04] Brian Chess and Gary McGraw. Static analysis for security. *IEEE security & privacy*, 2(6):76–79, 2004.
- [Com19a] Common Weakness Enumeration. Cwe-79: Improper neutralization of input during web page generation ('cross-site scripting'), 19. 09. 2019. URL: <https://cwe.mitre.org/data/definitions/79.html> [cited 3. 10. 2019].

- [Com19b] Common Weakness Enumeration. Cwe-22: Improper limitation of a pathname to a restricted directory ('path traversal'), 19. 9. 2019. URL: <https://cwe.mitre.org/data/definitions/22.html> [cited 3. 10. 2019].
- [Com19c] Common Weakness Enumeration. Cwe-352: Cross-site request forgery (csrf), 19. 9. 2019. URL: <https://cwe.mitre.org/data/definitions/352.html> [cited 3. 10. 2019].
- [Com19d] Common Weakness Enumeration. Cwe-89: Improper neutralization of special elements used in an sql command ('sql injection'), 19. 9. 2019. URL: <https://cwe.mitre.org/data/definitions/89.html> [cited 3. 10. 2019].
- [Com19e] Common Weakness Enumeration. Cwe-77: Improper neutralization of special elements used in a command ('command injection'), 23. 9. 2019. URL: <https://cwe.mitre.org/data/definitions/77.html> [cited 3. 10. 2019].
- [CSS13] Krishna Kumar Chaturvedi, V. B. Sing, and Prashast Singh. Tools in mining software repositories. In *2013 13th International Conference on Computational Science and Its Applications*, pages 89–98, 2013.
- [CVE19] CVE. Cve, 2019. URL: <http://cve.mitre.org/> [cited 02.09.2019].
- [CvG⁺14] Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.
- [CZ11] Istehad Chowdhury and Mohammad Zulkernine. Using complexity, coupling, and cohesion metrics as early indicators of vulnerabilities. *Journal of Systems Architecture*, 57(3):294–313, 2011.
- [Dan17] Dan Goodin. An nsa-derived ransomware worm is shutting down computers worldwide, 2017. URL: <https://arstechnica.com/information-technology/2017/05/an-nsa-derived-ransomware-worm-is-shutting-down-computers-worldwide/> [cited 02.09.2019].
- [DHS11] John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 12(Jul):2121–2159, 2011.
- [DLK⁺14] Zakir Durumeric, Frank Li, James Kasten, Johanna Amann, Jethro Beekman, Mathias Payer, Nicolas Weaver, David Adrian, Vern Paxson, Michael Bailey, et al. The matter of heartbleed. In *Proceedings of the 2014 conference on internet measurement conference*, pages 475–488, 2014.

- [DMS06] Mark Dowd, John McDonald, and Justin Schuh. *The art of software security assessment: Identifying and preventing software vulnerabilities*. Pearson Education, 2006.
- [DTGG16] Hoa Khanh Dam, Truyen Tran, John Grundy, and Aditya Ghose. Deepsoft: A vision for a deep model of software. In *Proceedings of the 2016 24th ACM SIGSOFT International Symposium on Foundations of Software Engineering*, pages 944–947, 2016.
- [DTP16] Hoa Khanh Dam, Truyen Tran, and Trang Pham. A deep language model for software code. *arXiv preprint arXiv:1608.02715*, 2016.
- [DTP⁺17] Hoa Khanh Dam, Truyen Tran, Trang Pham, Shien Wee Ng, John Grundy, and Aditya Ghose. Automatic feature learning for vulnerability prediction. *arXiv preprint arXiv:1708.02368*, 2017.
- [ESM⁺07] Yuval Elovici, Asaf Shabtai, Robert Moskovitch, Gil Tahan, and Chanan Glezer. Applying machine learning techniques for detection of malicious code in network traffic. In *Annual Conference on Artificial Intelligence*, pages 44–50, 2007.
- [Eva02] David Evans. Splint-secure programming lint. *Technical report, Technical report*, 2002.
- [GBB11] Xavier Glorot, Antoine Bordes, and Yoshua Bengio. Deep sparse rectifier neural networks. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 315–323, 2011.
- [GBC16] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT Press, 2016.
- [GGS14] Mukesh Kumar Gupta, M. C. Govil, and Girdhari Singh. Static analysis approaches to detect sql injection and cross site scripting vulnerabilities in web applications: A survey. In *International Conference on Recent Advances and Innovations in Engineering (ICRAIE-2014)*, pages 1–5, 2014.
- [GGU⁺16] Gustavo Grieco, Guillermo Luis Grinblat, Lucas Uzal, Sanjay Rawat, Josselin Feist, and Laurent Mounier. Toward large-scale vulnerability discovery using machine learning. In *Proceedings of the Sixth ACM Conference on Data and Application Security and Privacy*, pages 85–96, 2016.
- [Git] Github.com. Celebrating nine years of github with an anniversary sale. <https://github.com/blog/2345-celebrating-nine-years-of-github-with-an-anniversary-sale>. Abgerufen am 25. 4. 2019.
- [Git19a] Github.com. About the search api, 2019. URL: <https://developer.github.com/v3/search/#about-the-search-api> [cited 2. 9. 2019].

- [Git19b] Github.com. Github - the state of the octoverse 2018, 2019. URL: <https://octoverse.github.com/projects> [cited 3. 10. 2019].
- [Git19c] Github.com. Searching commits, 2019. URL: <https://help.github.com/en/articles/searching-commits> [cited 1.9.2019].
- [GPKS17a] Rahul Gupta, Soham Pal, Aditya Kanade, and Shirish Shevade. Deepfix: Fixing common c language errors by deep learning. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.
- [GPKS17b] Rahul Gupta, Soham Pal, Aditya Kanade, and Shirish Shevade. Deepfix: Fixing common c language errors by deep learning. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.
- [GS00] Felix A. Gers and Jürgen Schmidhuber. Recurrent nets that time and count. In *Proceedings of the IEEE-INNS-ENNS International Joint Conference on Neural Networks. IJCNN 2000. Neural Computing: New Challenges and Perspectives for the New Millennium*, volume 3, pages 189–194, 2000.
- [GS17] Seyed Mohammad Ghaffarian and Hamid Reza Shahriari. Software vulnerability analysis and discovery using machine-learning and data-mining techniques: A survey. *ACM Computing Surveys (CSUR)*, 50(4):56, 2017.
- [GSC99] Felix A. Gers, Jürgen Schmidhuber, and Fred Cummins. Learning to forget: Continual prediction with lstm. 1999.
- [HBB⁺11] Tracy Hall, Sarah Beecham, David Bowes, David Gray, and Steve Counsell. A systematic literature review on fault prediction performance in software engineering. *IEEE Transactions on Software Engineering*, 38(6):1276–1304, 2011.
- [HBS⁺12] Abram Hindle, Earl T. Barr, Zhendong Su, Mark Gabel, and Premkumar Devanbu. On the naturalness of software. In *2012 34th International Conference on Software Engineering (ICSE)*, pages 837–847, 2012.
- [HLZ16] Xuan Huo, Ming Li, and Zhi-Hua Zhou. Learning unified features from natural and programming languages for locating buggy source code. In *IJCAI*, pages 1606–1612, 2016.
- [Hoc91] Sepp Hochreiter. Untersuchungen zu dynamischen neuronalen netzen. *Diploma, Technische Universität München*, 91(1), 1991.
- [HOL⁺18] Jacob Harer, Onur Ozdemir, Tomo Lazovich, Christopher Reale, Rebecca Russell, Louis Kim, et al. Learning to repair software vulnerabilities with generative adversarial networks. In *Advances in Neural Information Processing Systems*, pages 7933–7943, 2018.

- [Hov05] David Hovemeyer. *Simple and effective static analysis to find bugs*. PhD thesis, 01.01.2005.
- [HP04] David Hovemeyer and William Pugh. Finding bugs is easy. *Acm sigplan notices*, 39(12):92–106, 2004.
- [HS97] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.
- [HSJW12] Aram Hovsepyan, Riccardo Scandariato, Wouter Joosen, and James Walden. Software vulnerability prediction using text analysis techniques. In *Proceedings of the 4th international workshop on Security measurements and metrics*, pages 7–10, 2012.
- [IBM] IBM News Room. Ibm study: More than half of organizations with cybersecurity incident response plans fail to test them: Yet use of automation improved detection and containment of cyberattacks by nearly 25%. URL: <https://newsroom.ibm.com/2019-04-11-IBM-Study-More-Than-Half-of-Organizations-with-Cybersecurity> [cited 27.9.2019].
- [IBM19] IBM Research Editorial Staff. Will adam algorithms work for me?, 6. 5. 2019. URL: <https://www.ibm.com/blogs/research/2019/05/adam-algorithms/> [cited 21. 9. 2019].
- [IEE15] *2015 IEEE International Conference on Software Quality, Reliability and Security*, 2015.
- [IEE16] *2016 IEEE/ACM 38th International Conference on Software Engineering (ICSE)*, 2016.
- [Jay19] Jay Alammar. The illustrated word2vec, 27. 03. 2019. URL: <https://jalamar.github.io/illustrated-word2vec/> [cited 1. 11. 2019].
- [KB14] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.
- [KCM05] Huzefa Kagdi, Michael L. Collard, and Jonathan I. Maletic. Towards a taxonomy of approaches for mining of source code repositories. In *ACM SIGSOFT Software Engineering Notes*, volume 30, pages 1–5, 2005.
- [KR19] Harish Kumar and Balaraman Ravindran. Polyphonic music composition with lstm neural networks and reinforcement learning. *arXiv preprint arXiv:1902.01973*, 2019.
- [LKB⁺18] Kui Liu, Dongsun Kim, Tegawendé F. Bissyandé, Shin Yoo, and Yves Le Traon. Mining fix patterns for findbugs violations. *IEEE Transactions on Software Engineering*, 2018.

- [Los14] Net Losses. Estimating the global cost of cybercrime. *McAfee, Centre for Strategic & International Studies*, 2014.
- [Lou] Loukia Papadopoulos. Bill gates praises elon musk-founded openai’s latest dota 2 win as “huge milestone” in field: The billionaire founder of microsoft took to twitter to congratulate the ai research firm on its latest video game win. URL: <https://interestingengineering.com/bill-gates-praises-elon-musk-founded-openais-latest-dota-2-win-as-huge-milestone> [cited 27. 9. 2019].
- [LSCL12] Bingchang Liu, Liang Shi, Zhuhua Cai, and Min Li. Software vulnerability discovery techniques: A survey. In *2012 fourth international conference on multimedia information networking and security*, pages 152–156, 2012.
- [LZ05] Zhenmin Li and Yuanyuan Zhou. Pr-miner: automatically extracting implicit programming rules and detecting violations in large software code. In *ACM SIGSOFT Software Engineering Notes*, volume 30, pages 306–315, 2005.
- [LZX⁺18] Zhen Li, Deqing Zou, Shouhuai Xu, Xinyu Ou, Hai Jin, Sujuan Wang, Zhijun Deng, and Yuyi Zhong. Vuldeepecker: A deep learning-based system for vulnerability detection. *arXiv preprint arXiv:1801.01681*, 2018.
- [M⁺97] Tom M. Mitchell et al. Machine learning. 1997. *Burr Ridge, IL: McGraw Hill*, 45(37):870–877, 1997.
- [MGW⁺08] Hermann Mayer, Faustino Gomez, Daan Wierstra, Istvan Nagy, Alois Knoll, and Jürgen Schmidhuber. A system for robotic heart surgery that learns to tie knots using recurrent neural networks. *Advanced Robotics*, 22(13-14):1521–1537, 2008.
- [MHMW15] Patrick Morrison, Kim Herzig, Brendan Murphy, and Laurie Williams. Challenges with applying vulnerability prediction models. In *Proceedings of the 2015 Symposium and Bootcamp on the Science of Security*, page 4, 2015.
- [Mit99] Tom M. Mitchell. Machine learning and data mining. *Communications of the ACM*, 42(11), 1999.
- [MNC14] Ibéria Medeiros, Nuno F. Neves, and Miguel Correia. Automatic detection and correction of web application vulnerabilities using data mining to predict false positives. In *Proceedings of the 23rd international conference on World wide web*, pages 63–74, 2014.
- [MSC⁺13] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S. Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pages 3111–3119, 2013.

- [MT16] Stefan Micheelsen and Bruno Thalmann. A static analysis tool for detecting security vulnerabilities in python web applications, 2016.
- [MTL⁺17] Siqi Ma, Ferdian Thung, David Lo, Cong Sun, and Robert H. Deng. Vurle: Automatic vulnerability detection and repair by learning from examples. In *European Symposium on Research in Computer Security*, pages 229–246, 2017.
- [Nie15] Michael A. Nielsen. *Neural networks and deep learning*, volume 25. Determination press San Francisco, CA, USA, 2015.
- [NIS] NIST Computer Security Ressource Center. URL: <https://csrc.nist.gov/glossary/term/vulnerability> [cited 25. 9. 2019].
- [NMB08] Nachiappan Nagappan, Brendan Murphy, and Victor Basili. The influence of organizational structure on software quality. In *2008 ACM/IEEE 30th International Conference on Software Engineering*, pages 521–530, 2008.
- [NZHZ07] Stephan Neuhaus, Thomas Zimmermann, Christian Holler, and Andreas Zeller. Predicting vulnerable software components. In *ACM Conference on computer and communications security*, pages 529–540, 2007.
- [Ope18] Learning dexterity, 2018. URL: <https://openai.com/blog/learning-dexterity/> [cited 1. 10. 2019].
- [OWA] OWASP Foundation. URL: <https://www.owasp.org> [cited 1. 10. 2019].
- [OWA14] OWASP Foundation. Session fixation, 2014. URL: https://www.owasp.org/index.php/Session_fixation [cited 3. 10. 2019].
- [OWA15] OWASP Foundation. Man-in-the-middle attack, 31. 8. 2015. URL: https://www.owasp.org/index.php/Man-in-the-middle_attack [cited 3. 10. 2019].
- [PCFY07] Marco Pistoia, Satish Chandra, Stephen J. Fink, and Eran Yahav. A survey of static analysis methods for identifying security vulnerabilities in software systems. *IBM Systems Journal*, 46(2):265–288, 2007.
- [PXN15] Yulei Pang, Xiaozhen Xue, and Akbar Siami Namin. Predicting vulnerable software components through n-gram analysis and statistical feature selection. In *2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA)*, pages 543–548, 2015.
- [RKH⁺18] Rebecca Russell, Louis Kim, Lei Hamilton, Tomo Lazovich, Jacob Harer, Onur Ozdemir, Paul Ellingwood, and Marc McConley. Automated vulnerability detection in source code using deep representation learning. In *2018 17th IEEE International Conference on Machine Learning and Applications (ICMLA)*, pages 757–762, 2018.

- [Rod18] Jesus Rodriguez. The science behind openai five that just produced one of the greatest breakthrough in the history of ai. *Towards Data Science*, 2018. URL: <https://towardsdatascience.com/the-science-behind-openai-five-that-just-produced-one-of-the-greatest-breakthrough-in-the-history-of-ai/>
- [RSG⁺18] Reudismam Rolim, Gustavo Soares, Rohit Gheyi, Titus Barik, and Loris D’Antoni. Learning quick fixes from code repositories. *arXiv preprint arXiv:1803.03806*, 2018.
- [SAB18] Davide Spadini, Maurício Aniche, and Alberto Bacchelli. Pydriller: Python framework for mining software repositories. In *The 26th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE)*. 2018. doi:10.1145/3236024.3264598.
- [SB17] Joshua Saxe and Konstantin Berlin. expose: A character-level convolutional neural network with embeddings for detecting malicious urls, file paths and registry keys. *arXiv preprint arXiv:1702.08568*, 2017.
- [Sch15] Jürgen Schmidhuber. Deep learning in neural networks: An overview. *Neural networks*, 61:85–117, 2015.
- [SEZS00] Matthew G. Schultz, Eleazar Eskin, F. Zadok, and Salvatore J. Stolfo. Data mining methods for detection of new malicious executables. In *Proceedings 2001 IEEE Symposium on Security and Privacy. S&P 2001*, pages 38–49, 2000.
- [SHK⁺14] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.
- [SMWO10] Yonghee Shin, Andrew Meneely, Laurie Williams, and Jason A. Osborne. Evaluating complexity, code churn, and developer activity metrics as indicators of software vulnerabilities. *IEEE Transactions on Software Engineering*, 37(6):772–787, 2010.
- [SSNW15] Søren Kaae Sønderby, Casper Kaae Sønderby, Henrik Nielsen, and Ole Winther. Convolutional lstm networks for subcellular localization of proteins. In *International Conference on Algorithms for Computational Biology*, pages 68–80, 2015.
- [ST13] Lwin Khin Shar and Hee Beng Kuan Tan. Predicting sql injection and cross site scripting vulnerabilities through mining input sanitization patterns. *Information and Software Technology*, 55(10):1767–1780, 2013.
- [Sta19] Stacy Stanford. Deepmind’s ai, alphastar showcases significant progress towards agi. *Medium ML Me-*

moirs, 2019. URL: <https://medium.com/mlmemoirs/deepminds-ai-alphastar-showcases-significant-progress-towards-agi-938>

- [STB13a] Lwin Khin Shar, Hee Beng Kuan Tan, and Lionel C. Briand. Mining sql injection and cross site scripting vulnerabilities using hybrid program analysis. In *Proceedings of the 2013 International Conference on Software Engineering*, pages 642–651, 2013.
- [STB13b] Lwin Khin Shar, Hee Beng Kuan Tan, and Lionel C. Briand. Mining sql injection and cross site scripting vulnerabilities using hybrid program analysis. In *Proceedings of the 2013 International Conference on Software Engineering*, pages 642–651, 2013.
- [SW08] Yonghee Shin and Laurie Williams. An empirical model to predict security vulnerabilities using code complexity metrics. In *Proceedings of the Second ACM-IEEE international symposium on Empirical software engineering and measurement*, pages 315–317, 2008.
- [SW13] Yonghee Shin and Laurie Williams. Can traditional fault prediction models be used for vulnerability prediction? *Empirical Software Engineering*, 18(1):25–59, 2013.
- [SWHJ14] Riccardo Scandariato, James Walden, Aram Hovsepyan, and Wouter Joosen. Predicting vulnerable software components via text mining. *IEEE Transactions on Software Engineering*, 40(10):993–1006, 2014.
- [TH12] Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5-rmsprop, coursera: Neural networks for machine learning. *University of Toronto, Technical Report*, 2012.
- [TSD14] Zhaopeng Tu, Zhendong Su, and Premkumar Devanbu. On the localness of software. In *Proceedings of the 22nd ACM SIGSOFT International Symposium on Foundations of Software Engineering*, pages 269–280, 2014.
- [VG14] Radhika D. Venkatasubramanyam and Shrinath Gupta. An automated approach to detect violations with high confidence in incremental code using a learning system. In *Companion Proceedings of the 36th International Conference on Software Engineering*, pages 472–475, 2014.
- [Vid19] Vidushi Dwivedi. Top 10 programming languages of the world, 2019. URL: <https://www.geeksforgeeks.org/top-10-programming-languages-of-the-world-2019-to-begin-with/> [cited 3. 10. 2019].
- [Whe06] David Wheeler. Flawfinder home page, 2006. URL: <http://www.dwheeler.com/flawfinder> [cited 27. 9. 2019].
- [WLT16] Song Wang, Taiyue Liu, and Lin Tan. Automatically learning semantic

- features for defect prediction. In *2016 IEEE/ACM 38th International Conference on Software Engineering (ICSE)*, pages 297–308, 2016.
- [WMWM12] Dumidu Wijayasekara, Milos Manic, Jason L. Wright, and Miles McQueen. Mining bug databases for unidentified software vulnerabilities. In *2012 5th International Conference on Human System Interactions*, pages 89–96, 2012.
- [WTVP16] Martin White, Michele Tufano, Christopher Vendome, and Denys Poshyvanyk. Deep learning code fragments for code clone detection. In *Proceedings of the 31st IEEE/ACM International Conference on Automated Software Engineering*, pages 87–98, 2016.
- [WVLVP15] Martin White, Christopher Vendome, Mario Linares-Vásquez, and Denys Poshyvanyk. Toward deep learning software repositories. In *Proceedings of the 12th Working Conference on Mining Software Repositories*, pages 334–345, 2015.
- [YLR11] Fabian Yamaguchi, Felix Lindner, and Konrad Rieck. Vulnerability extrapolation: assisted discovery of vulnerabilities using machine learning. In *Proceedings of the 5th USENIX conference on Offensive technologies*, page 13, 2011.
- [YLR12] Fabian Yamaguchi, Markus Lottmann, and Konrad Rieck. Generalized vulnerability extrapolation using abstract syntax trees. In *Proceedings of the 28th Annual Computer Security Applications Conference*, pages 359–368, 2012.
- [YTWM19] Zhe Yu, Christopher Theisen, Laurie Williams, and Tim Menzies. Improving vulnerability inspection efficiency using active learning. *IEEE Transactions on Software Engineering*, 2019.
- [ZNW10] Thomas Zimmermann, Nachiappan Nagappan, and Laurie Williams. Searching for a needle in a haystack: Predicting security vulnerabilities for windows vista. In *2010 Third International Conference on Software Testing, Verification and Validation*, pages 421–428, 2010.
- [ZS17] Yaqin Zhou and Asankhaya Sharma. Automated identification of security issues from commit messages and bug reports. In *Proceedings of the 2017 11th Joint Meeting on Foundations of Software Engineering*, pages 914–919, 2017.
- [ZZWD05] Thomas Zimmermann, Andreas Zeller, Peter Weissgerber, and Stephan Diehl. Mining version histories to guide software changes. *IEEE Transactions on Software Engineering*, 31(6):429–445, 2005.

Appendix: Examples

A. SQL injection



Fig. 36: Commit for vulnerability (SQL injection 2)

<https://github.com/instacart/lore/commit/a0a5fd945a8bf128d4b9fb6a3ebc6306f82fa4d0>

```
original_names = {}
for index in source.indexes:
    # make sure the name is < 63 chars with the suffix
    name = hashlib.sha256(temp + index.name.encode('utf-8') + suffix).hexdigest()[0:60]
    original_names[name] = index.name
    columns = []
    for column in index.columns:
        columns.append(next(x for x in destination.columns if x.name == column.name))
    new = sqlalchemy.Index(name, *columns)
    new.unique = index.unique
    new.table = destination
    new.create(bind=self._connection)
self.insert(destination.name, dataframe, batch_size=batch_size)
self.execute("BEGIN; SET LOCAL statement_timeout = '1min'; ANALYZE %s; COMMIT;" % table)

with self as transaction:
    backup = sqlalchemy.Table(table + '_b', self.metadata)
    backup.drop(bind=self._connection, checkfirst=True)
    source.rename(name=source.name + '_b', connection=self._connection)
    destination.rename(name=table, connection=self._connection)
    for index in source.indexes:
        index.rename(index.name[0:-2] + '_b', connection=self._connection)
    for index in destination.indexes:
        index.rename(original_names[index.name], connection=self._connection)

for func in _after_replace_callbacks:
    func(destination, source)
```

Fig. 37: Detection of vulnerability (SQL injection 2)

```

- prevent sql injection attack
master
kyojuceles committed on 28 Nov 2018
1 parent e5ae414 commit 47f5aa6aa2e82de7ce2a440aea870958edf0ae77
Showing 1 changed file with 7 additions and 5 deletions.
Unified Split

```

12

db/db_processor_mysql.py

...

...

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

Fig. 38: Commit for vulnerability (SQL injection 3)
<https://github.com/kyojuceles/mud/commit/47f5aa6aa2e82de7ce2a440aea870958edf0ae77>

```

async def create_account(name: str, password: str):
    """
    global _pool
    uid = -1
    async with await _pool.Connection() as conn:
        try:
            async with conn.cursor() as cursor:
                await cursor.execute(\
                    "INSERT INTO player (name, password, lv, xp, hp) values ('%s', '%s', 1, 0, 150)"\
                    % (name, password))
                uid = conn.insert_id()
            except Exception as ex:
                await conn.rollback()
                _error_report(ex)
                return False, -1
            await conn.commit()

        return True, uid

async def get_player_info(name: str) -> tuple:
    """
    global _pool
    async with await _pool.Connection() as conn:
        try:
            async with conn.cursor() as cursor:
                await cursor.execute("SELECT uid, name, password, lv, xp, hp FROM player where name = '%s'" % name)
                data = cursor.fetchone()
            except Exception as ex:
                _error_report(ex)
                return tuple()

        if data is None:
            return tuple()

        return data

async def update_level_and_xp(name: str, lv: int, xp: int):
    """level"""
    global _pool
    async with await _pool.Connection() as conn:
        try:
            async with conn.cursor() as cursor:
                await cursor.execute("UPDATE player SET lv=%d, xp=%d where name = '%s'" % (lv, xp, name))
            except Exception as ex:
                _error_report(ex)
                return False
            await conn.commit()

        return True

    ( . . . )

def close():
    """
    global _pool
    if _pool is not None:
        _pool.close()
        _pool = None

def _error_report(err_msg):
    """
    global _handler
    if _handler:
        _handler(err_msg)

if __name__ == '__main__':
    def error_handler(msg):
        print(msg)

    loop = asyncio.get_event_loop()
    set_log_handler(error_handler)
    result = connect_db_server('127.0.0.1', 'root', 'mysql12345', 'mud_db', loop)
    print('db connect result is ' + str(result))
    loop.run_until_complete(create_item(37, 0))
    close()

```

Fig. 39: Detection of vulnerability (SQL injection 3)

B. Cross-site scripting




Fig. 40: Commit for vulnerability (XSS2)

<https://github.com/inveniosoftware/invenio-records/commit/361def20617cde5a1897c2e81b70bfadaabae608>

```
column_details_list = ('id', 'version_id', 'updated', 'created', 'json')
column_labels = dict(
    id=_('UUID'),
    version_id=_('Revision'),
    json=_('JSON'),
)
column_formatters = dict(
    version_id=lambda v, c, m, p: m.version_id-1,
    json=lambda v, c, m, p: Markup("<pre>{0}</pre>".format(
        json.dumps(m.json, indent=2, sort_keys=True)))
)
column_filters = ('created', 'updated', )
column_default_sort = ('updated', True)
page_size = 25

def delete_model(self, model):
    """Delete a record. """
    try:
        if model.json is None:
            return True
        record = Record(model.json, model=model)
        record.delete()
        db.session.commit()
```

Fig. 41: Detection of vulnerability (XSS 2)




Fig. 42: Commit for vulnerability (XSS 3)

<https://github.com/onefork/pontoon-sr/commit/fc07ed9c68e08d41f74c078b4e7727f1a0888be8>

```

@login_required(redirect_field_name='', login_url='/403')
@require_POST
@require AJAX
@transaction.atomic
def batch_edit_translations(request):
    """Perform an action on a list of translations.

    Available actions are defined in 'ACTIONS_FN_MAP'. Arguments to this view
    are defined in 'models.BatchActionsForm'."""

    form = forms.BatchActionsForm(request.POST)
    if not form.is_valid():
        return HttpResponseBadRequest(form.errors.as_json())

    locale = get_object_or_404(Locale, code=form.cleaned_data['locale'])
    entities = Entity.objects.filter(pk__in=form.cleaned_data['entities'])

    if not entities.exists():
        return JsonResponse({'count': 0})

```

Fig. 43: Detection of vulnerability (XSS 3)

C. Command injection

```

Fix command injection vulnerability in disk.usage
master (#7774) v2019.8 v2014.1
techhat committed on 12 Oct 2013
1 parent b89fa91 commit ebdef37b7e5d2b95a01d34b211c61c61da67e46a

Showing 1 changed file with 8 additions and 1 deletion.
Unified Split

salt/modules/disk.py
31 @@ -31,14 +31,21 @@ def usage(args=None):
32     salt '*' disk.usage
33     ...
34
35 + flags = ''
36 + allowed = ('a', 'B', 'h', 'H', 'i', 'k', 'l', 'P', 't', 'T', 'x', 'v')
37 + for flag in args:
38 +     if flag in allowed:
39 +         flags += flag
40 +     else:
41 +         break
42
43 if __grains__['kernel'] == 'Linux':
44     cmd = 'df -p'
45 elif __grains__['kernel'] == 'OpenBSD':
46     cmd = 'df -kp'
47 else:
48     cmd = 'df'
49 if args:
50     cmd = cmd + ' ' + args
51
52 ret = {}
53 out = __salt__['cmd.run'](cmd).splitlines()
54 for line in out:
55
56     salt '*' disk.usage
57     ...
58
59 if __grains__['kernel'] == 'Linux':
60     cmd = 'df -p'
61 elif __grains__['kernel'] == 'OpenBSD':
62     cmd = 'df -kp'
63 else:
64     cmd = 'df'
65 if args:
66     cmd = cmd + ' {}'.format(flags)
67
68 ret = {}
69 out = __salt__['cmd.run'](cmd).splitlines()
70 for line in out:

```

Fig. 44: Commit for vulnerability (Command injection 2)

<https://github.com/saltstack/salt/commit/ebdef37b7e5d2b95a01d34b211c61c61da67e46a>


```
def usage(args=None):
    """
    Return usage information for volumes mounted on this minion

    CLI Example:

    .. code-block:: bash

        salt '*' disk.usage
    """
    if __grains__['kernel'] == 'Linux':
        cmd = 'df -P'
    elif __grains__['kernel'] == 'OpenBSD':
        cmd = 'df -kp'
    else:
        cmd = 'df'
    if args:
        cmd = cmd + ' -' + args
    ret = {}
    out = __salt__['cmd.run'](cmd).splitlines()
    for line in out:
        if not line:
            continue
        if line.startswith('Filesystem'):
            continue
        comps = line.split()
        while not comps[1].isdigit():
            comps[0] = '{0} {1}'.format(comps[0], comps[1])
            comps.pop(1)
        try:
            if __grains__['kernel'] == 'Darwin':
                ret[comps[0]] = {
                    'filesystem': comps[0],
                    '512-blocks': comps[1],
                    'used': comps[2],
                    'available': comps[3],
                    'capacity': comps[4],
                    'iused': comps[5],
                    'ifree': comps[6],
                    '%iused': comps[7],
                }
            else:
                ret[comps[0]] = {
                    'filesystem': comps[0],
                    '512-blocks': comps[1],
                    'used': comps[2],
                    'available': comps[3],
                    'capacity': comps[4],
                    'iused': comps[5],
                    'ifree': comps[6],
                    '%iused': comps[7],
                }
        except:
            pass
```

Fig. 45: Detection of vulnerability (Command Injection 2)




Fig. 46: Commit for vulnerability (Command injection 3)

<https://github.com/yasong/netzob/commit/557abf64867d715497979b029efedbd2777b912e>

```

def initHeader(self):
    """Initialize the IP header according to the IP format definition.

    """

    # Ethernet header

    # Retrieve remote MAC address
    dstMacAddr = arpreq.arpreq(self.remoteIP)
    if dstMacAddr is not None:
        dstMacAddr = dstMacAddr.replace(':', '')
        dstMacAddr = binascii.unhexlify(dstMacAddr)
    else:
        # Force ARP resolution
        p = subprocess.Popen("ping -c1 {}".format(self.remoteIP), shell=True)
        p.wait()
        time.sleep(0.1)

        dstMacAddr = arpreq.arpreq(self.remoteIP)
        if dstMacAddr is not None:
            dstMacAddr = dstMacAddr.replace(':', '')
            dstMacAddr = binascii.unhexlify(dstMacAddr)
        else:
            raise Exception("Cannot resolve IP address to a MAC address for IP: {}".format(self.remoteIP))

    # Retrieve local MAC address
    srcMacAddr = self.get_interface_addr(bytes(self.interface, 'utf-8'))[1]

    eth_dst = Field(name='eth.dst', domain=Raw(dstMacAddr))
    eth_src = Field(name='eth.sre', domain=Raw(srcMacAddr))
    eth_type = Field(name='eth.type', domain=Raw(b"\x08\x00"))

    # IP header

```

Fig. 47: Detection of vulnerability (Command Injection 3)

D. Cross-site request forgery




Fig. 48: Commit for vulnerability (XSRF 2)

<https://github.com/wbrxcorp/forgetthespiltmilk/commit/51bed3f7f01079d91864ddc386a73eb3e1ca634b>

```

if "user" in auth_status and auth_status["user"]:
    data["login_user"] = auth_status["user"]

response = None

if "template" in data:
    response = flask.Response(flask.render_template(data["template"], **data))
else:
    response = flask.jsonify(data)

for k, v in response_headers.iteritems():
    response.headers[k] = v

if flask.session.get("XSRF-TOKEN") is None:
    xsrf_token = "%030x" % random.randrange(16**30)
    flask.session["XSRF-TOKEN"] = xsrf_token
    response.set_cookie("XSRF-TOKEN", xsrf_token)

return response

@app.template_filter("markdown")
def __markdown(md):
    return markdown.markdown(md, extensions=['gfm'])

```

Fig. 49: Detection of vulnerability (XSRF 2)

Implement proper modhash checking to stop xsrf

master deployed-production-20170328232541 deployed-production-20140513025824

David Powell committed on 10 Aug 2011 1 parent ecd3437 commit ef303fe078c60d964e3f9e87d3da1a67fed2c2b

Showing 3 changed files with 17 additions and 9 deletions

Unified Split

> 8 r2/r2/controllers/validator/validator.py

> 8 r2/r2/lib/utils/utils.py

▼ 18 r2/r2/models/account.py

<pre> 24 from r2.lib.db.operators import lower 25 from r2.lib.db.userrel import UserRel 26 from r2.lib.memoize import memoize, clear_memo 27 - from r2.lib.utils import modhash, valid_hash, randstr 28 from r2.lib.strings import strings, plurals 29 30 from pylons import g 31 from pylons.i18n import _ 32 33 @@ -206,11 +207,12 @@ def make_cookie(self, timestr = None, admin = False): 206 def needs_captcha(self): 207 return self.safe_karma < 1 208 209 - def modhash(self, rand=None, test=False): 210 - return modhash(self, rand = rand, test = test) 211 212 def valid_hash(self, hash): 213 - return valid_hash(self, hash) 214 215 @classmethod </pre>	<pre> 24 from r2.lib.db.operators import lower 25 from r2.lib.db.userrel import UserRel 26 from r2.lib.memoize import memoize, clear_memo 27 + from r2.lib.utils import randstr 28 from r2.lib.strings import strings, plurals 29 + from r2.lib.base import current_login_cookie 30 31 from pylons import g 32 from pylons.i18n import _ 33 34 @@ -207,12 +208,13 @@ def needs_captcha(self): 207 def needs_captcha(self): 208 return self.safe_karma < 1 209 210 + def modhash(self): 211 + to_hash = '%'.join([current_login_cookie(), g.SECRET]) 212 + return hashlib.sha1(to_hash).hexdigest() 213 214 def valid_hash(self, hash): 215 + return hash == self.modhash() 216 217 @classmethod </pre>
---	---

Fig. 50: Commit for vulnerability (XSRF 3)

<https://github.com/tricycle/lesswrong/commit/ef303fe078c60d964e3f9e87d3da1a67fed2c2b>

```

from pylons import c
from r2.lib.db.thing import Thing, Relation, NotFound
from r2.lib.db.operators import lower
from r2.lib.db.userrel import UserRel
from r2.lib.memoize import memoize, clear_memo
from r2.lib.utils import modhash, valid_hash, randstr
from r2.lib.strings import strings, plurals

from pylons import g
from pylons.i18n import _
import time, hashlib
from copy import copy

class AccountExists(Exception): pass
class NotEnoughKarma(Exception): pass

class Account(Thing):
    _data_int_props = Thing._data_int_props + ('link_karma', 'comment_karma',
                                                'report_made', 'report_correct',
                                                'report_ignored', 'spammer',
                                                'reported')

    _int_prop_suffix = ' karma'
    _defaults = dict(pref_numsites = 10,
                     pref_frame = False,
                     pref_newwindow = False,
                     pref_public_votes = False,
                     pref_kibitz = False,
                     pref_hide_ups = False,
                     pref_hide_downs = True,
                     pref_min_link_score = -2,
                     pref_min_comment_score = -2,
                     pref_num_comments = g.num_comments,
                     pref_lang = 'en',
                     pref_content_langs = ('en',),
                     pref_over_18 = False,
                     pref_compress = False,
                     pref_organic = True,
                     pref_show_stylesheets = True,
                     pref_url = '',
                     pref_location = '',
                     reported = 0,
                     report_made = 0,
                     report_correct = 0,
                     report_ignored = 0,
                     spammer = 0,
                     sort_options = {},
                     has_subscribed = False,
                     pref_media = 'subreddit',
                     share = {},

    (...))

    def make_cookie(self, timestr = None, admin = False):
        if not self._loaded:
            self._load()
        timestr = timestr or time.strftime('%Y-%m-%dT%H:%M:%S')
        id_time = str(self._id) + ',' + timestr
        to_hash = ','.join((id_time, self.password, g.SECRET))
        if admin:
            to_hash += 'admin'
        return id_time + ',' + hashlib.sh1(to_hash).hexdigest()

    def needs_captcha(self):
        return self.safe_karma < 1

    def modhash(self, rand=None, test=False):
        return modhash(self, rand = rand, test = test)

    def valid_hash(self, hash):
        return valid_hash(self, hash)

    @classmethod
    @memoize('account._by_name')
    def _by_name_cache(cls, name, allow_deleted = False):
        #lower name here, just in case
        deleted = (True, False) if allow_deleted else False
        q = cls._query(lower(Account.c.name) == name.lower(),
                       Account.c._spam == (True, False),
                       Account.c._deleted == deleted)

        q._limit = 1
        l = list(q)
        if l:
            return l[0]._id

```

Fig. 51: Detection of vulnerability (XSRF 3)

E. Path disclosure




Fig. 52: Commit for vulnerability (Path disclosure 2)

<https://github.com/fkmclane/python-fooster-web/commit/80202a6d3788ad1212a162d19785c600025e6aa4>

```
# set the appropriate inheritance whether modification is allowed
if modify:
    inherit = ModifyMixin, handler
else:
    inherit = handler,

# create a file handler for routes
class GenFileHandler(*inherit):
    def respond(self):
        norm_request = normpath(self.groups['path'])
        if self.groups['path'] != norm_request:
            self.response.headers.set('Location', self.remote + norm_request)

            return 307, ''

        self.filename = self.local + urllib.parse.unquote(self.groups['path'])

        return handler.respond(self)

GenFileHandler.local = local
GenFileHandler.remote = remote
GenFileHandler.dir_index = dir_index

return {remote + '({P<path>|/{^?#}*)(?P<query>[?#].*)?': GenFileHandler}

if __name__ == '__main__':
    import signal
    from argparse import ArgumentParser
```

Fig. 53: Detection of vulnerability (Path disclosure 2)




Fig. 54: Commit for vulnerability (Path disclosure 3)

<https://github.com/zms-publishing/zms4/commit/3f28620d475220dfdb06f79787158ac50727c61a>

```

# manage_system
if request.form.has_key('zmi-manage-system'):
    request.SESSION.set('zmi-manage-system',int(request.get('zmi-manage-system')))
# avoid declarative urls
physical_path = self.getPhysicalPath()
path_to_handle = request['URL0'][:len(request['BASE0']):].split('/')
path = path_to_handle[:-1]
if len(filter(lambda x: x.find('.')>0 or x.startswith('manage_'),path))==0:
    for i in range(len(path)):
        if path[:-(i+1)] != physical_path[:-(i+1)]:
            path[:-(i+1)] = physical_path[:-(i+1)]
    new_path = path+[path_to_handle[-1]]
    if path_to_handle != new_path:
        request.RESPONSE.redirect('/'.join(new_path))

def f_standard_html_request(self, *args, **kwargs):
    request = self.REQUEST
    self.zmi_page_request()
    if not request.get('lang'):
        request.set('lang',self.getLanguage(request))
    if not request.get('manage_lang') in self.getLocale().get_manage_langs():
        request.set('manage_lang',self.get_manage_lang())

```

Fig. 55: Detection of vulnerability (Path disclosure 3)

F. Open redirect

The screenshot shows a GitHub commit titled "Fix open redirect (#519)" by user TheAMM, committed on 16 Sep 2018. The commit message states: "The funny thing is that we don't even use this anywhere, and the referrer is useless on forms. But hey, maybe someday." The diff shows changes to the file `nyaa/views/account.py`. The original code (left) had a simple redirect logic: if the URL is not the home URL, it redirects to the home URL. The updated code (right) implements a more robust open redirect fix by checking the referrer and ensuring the target URL is either a local path or starts with the current host's domain. The diff highlights the changes with a green background for the new code and a red background for the removed code.

```

211 @@ -211,14 +211,22 @@ def profile():
212
213
214 -     home_url = flask.url_for('main.home')
215 -
216 -     url = flask.request.args.get('next') or \
217 -         flask.request.referrer or \
218 -         home_url
219 -     if url == flask.request.url:
220 -         return home_url
221 -     return url
222
223
224 def send_verification_email(user):
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

Fig. 56: Commit for vulnerability (Open redirect 2)

<https://github.com/nyaa-devs/nyaa/commit/b2ddba994ca5e78fa5dcabc0e00d6171a44b0b338>

```

        db.session.add(user)
        db.session.commit()

        flask.g.user = user
        return flask.redirect('/profile')

    return flask.render_template('profile.html', form=form)

def redirect_url():
    home_url = flask.url_for('main.home')

    url = flask.request.args.get('next') or \
        flask.request.referrer or \
        home_url
    if url == flask.request.url:
        return home_url
    return url

def send_verification_email(user):
    activation_link = get_activation_link(user)

    tpl_context = {
        'activation_link': activation_link,
        'user': user
    }

    email_msg = email.EmailHolder(
        subject='Verify your {} account'.format(app.config['GLOBAL_SITE_NAME']),
        recipient=user,
        text=flask.render_template('email/verify.txt', **tpl_context),
        html=flask.render_template('email/verify.html', **tpl_context),
    )

    email.send_email(email_msg)

def send_password_reset_email(user):
    ''' Alert user that their password has been successfully reset '''

```

Fig. 57: Detection of vulnerability (Open redirect 2)

Fix open redirect issue

Solves the problem for fully-qualified and scheme-relative URLs

Explicitly allows cross-domain redirects or not where appropriate

master

3.10.0

3.5.1

davidfischer

committed on 5 Jun

Verified

1 parent

d0f6dad

commit e3bccfc582beb57800c33e4f0afe01351733f2a5

Showing 3 changed files with 122 additions and 3 deletions.

Unified

Split

readthedocs/redirects/models.py

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

def get_from_url_display(self):

return ''

def get_full_path(self, filename, language=None, version_slug=None):

Return a full path for a given filename.

This will include version and language information. No protocol/domain is returned.

Handle explicit http redirects

if re.match("https?://", filename):

return filename

return resolve_path(

def redirect_page(self, path, language=None, version_slug=None):

filename=self.to_url.lstrip('/')

language=language,

version_slug=version_slug,

return to

def redirect_exact(self, path, language=None, version_slug=None):

full_path = path

if language and version_slug:

reconstruct the full path for an exact redirect

full_path = self.get_full_path(path, language, version_slug)

if full_path == self.from_url:

log.debug('Redirecting %s', self)

return self.to_url

def redirect_sphinx_html(self, path, language=None, version_slug=None):

filename=to,

language=language,

version_slug=version_slug,

return to

def redirect_sphinx_htmlid(self, path, language=None, version_slug=None):

def redirect_sphinx_htmlid(self, path, language=None, version_slug=None):

filename=to,

language=language,

version_slug=version_slug,

allow_crossdomain=False,

return to

Fig. 58: Commit for vulnerability (Open redirect 3)

<https://github.com/readthedocs/readthedocs.org/commit/e3bccfc582beb57800c33e4f0afe01351733f2a5>

112


```

    )

def get_from_to_url_display(self):
    if self.redirect_type in ['prefix', 'page', 'exact']:
        from_url = self.from_url
        to_url = self.to_url
        if self.redirect_type == 'prefix':
            to_url = '{lang}/{version}'.format(
                lang=self.project.language,
                version=self.project.default_version,
            )
        return '{from_url} -> {to_url}'.format(
            from_url=from_url,
            to_url=to_url,
        )
    return ''

def get_full_path(self, filename, language=None, version_slug=None):
    """
    Return a full path for a given filename.

    This will include version and language information. No protocol/domain
    is returned.
    """
    # Handle explicit http redirects
    if re.match('^https?://', filename):
        return filename

    return resolve_path(
        project=self.project,
        language=language,
        version_slug=version_slug,
        filename=filename,
    )

def get_redirect_path(self, path, language=None, version_slug=None):
    method = getattr(
        self,
        'redirect_{type}'.format(
            type=self.redirect_type,
        ),
    )
    return method(path, language=language, version_slug=version_slug)

def redirect_prefix(self, path, language=None, version_slug=None):
    if path.startswith(self.from_url):
        log.debug('Redirecting %s', self)
        cut_path = re.sub('^%s' % self.from_url, '', path)
        to = self.get_full_path(
            filename=cut_path,
            language=language,
            version_slug=version_slug,
        )
    return to

def redirect_page(self, path, language=None, version_slug=None):
    if path == self.from_url:
        log.debug('Redirecting %s', self)
        to = self.get_full_path(
            filename=self.to_url.lstrip('/'),
            language=language,
            version_slug=version_slug,
        )
    return to

def redirect_exact(self, path, language=None, version_slug=None):
    full_path = path
    if language and version_slug:
        # reconstruct the full path for an exact redirect
        full_path = self.get_full_path(path, language, version_slug)
    if full_path == self.from_url:
        log.debug('Redirecting %s', self)
        return self.to_url
    # Handle full sub-level redirects
    if '$rest' in self.from_url:
        match = self.from_url.split('$rest')[0]
        if full_path.startswith(match):
            cut_path = re.sub('^%s' % match, self.to_url, full_path)
            return cut_path

def redirect_sphinx_html(self, path, language=None, version_slug=None):
    for ending in ['/', '/index.html']:
        if path.endswith(ending):
            log.debug('Redirecting %s', self)
            path = path[1:] # Strip leading slash.
            to = re.sub(ending + '$', '.html', path)
            return self.get_full_path(
                filename=to,
                language=language,
                version_slug=version_slug,
            )

```

Fig. 59: Detection of vulnerability (Open redirect 3)

G. Remote Code Execution



Fig. 60: Commit for vulnerability (Remote Code Execution 2)

<https://github.com/Scout24/monitoring-config-generator/commit/2191fe6c5a850ddcf7a78f7913881cef1677500d>

```
def read_config_from_host(url):
    try:
        response = requests.get(url)
    except socket.error as e:
        msg = "Could not open socket for '%s', error: %s" % (url, e)
        raise HostUnreachableException(msg)
    except ConnectionError as e:
        msg = "Could not establish connection for '%s', error: %s" % (url, e)
        raise HostUnreachableException(msg)
    except Timeout as e:
        msg = "Connect timed out for '%s', error: %s" % (url, e)
        raise HostUnreachableException(msg)
    except RequestException as e:
        msg = "Could not get monitoring yaml from '%s', error: %s" % (url, e)
        raise MonitoringConfigGeneratorException(msg)

    def get_from_header(field):
        return response.headers[field] if field in response.headers else None

    if response.status_code == 200:
        yaml_config = yaml.load(response.content)
        etag = get_from_header('etag')
        mtime = get_from_header('last-modified')
        mtime = datetime.datetime.strptime(mtime, '%a, %d %b %Y %H:%M:%S %Z').strftime('%s') if mtime else int(time())
    else:
        msg = "Request %s returned with status %s. I don't know how to handle that." % (url, response.status_code)
        raise MonitoringConfigGeneratorException(msg)

    return yaml_config, Header(etag=etag, mtime=mtime)
```

Fig. 61: Detection of vulnerability (Remote Code Execution 2)

Fix remote code execution.

Reddit controls the contents of "link" in:

```
os.system("mpv %s %s (%s)" % ("link": link, "args": mpv))
```

so arbitrary remote code can be executed under the user running "reddytt.sh". Example:

```
<a href="https://youtu.be/VuCa0g392Co; touch $HOME/puned" />a
```

Fixes issue: #5

master (v4.8) 1.4.2

arkonten committed on 16 Jan 2018

parent 382b2f8 commit b037e8526d75ea27596d41fafb0deaec656395c

Showing 1 changed file with 5 additions and 4 deletions.

Unlified Split

9 reddytt.py

10 import urllib3

11 import certifi

12 import re

13 import sys

14 import argparse as ap

15 #from argparse import ArgumentParser, REMINDER

16 def getytlinks(link):

17 subreddit = args.subreddit

18 depth = args.depth

19 mpv = " ".join(args.mpv)

20 subreddit_link = "https://reddit.com/r/" + subreddit

21 def getytlinks(link):

22 if link in seen_links:

23 print("ReddYtt: Link seen. Skipping.")

24 else:

25 x = os.system("mpv %s (%s)" % ("link": link, "args": mpv))

26 print("ReddYtt: That was: %s" % link)

27 if x == 0:

28 # The video finished or you hit 'q' (or whatever your binding is), this is a good exit.

29 # Store the video in seen_links.

30 seen_links.append(link)

31 save_links.remove(link)

32 elif x == 1024:

33 # You made a hard exit, and want to stop. (Ctrl+C)

34 # Store the links and exit the program.

35 print("ReddYtt: Forced exit detected. Saving and exiting.")

36 elif x == 1024:

37 # You made a hard exit, and want to stop. (Ctrl+C)

38 # Store the links and exit the program.

39 print("ReddYtt: Forced exit detected. Saving and exiting.")

10 import urllib3

11 import certifi

12 import re

13 + import subprocess

14 import sys

15 import argparse as ap

16 #from argparse import ArgumentParser, REMINDER

17 def getytlinks(link):

18 subreddit = args.subreddit

19 depth = args.depth

20 mpv = " ".join(args.mpv)

21 subreddit_link = "https://reddit.com/r/" + subreddit

22 def getytlinks(link):

23 if link in seen_links:

24 print("ReddYtt: Link seen. Skipping.")

25 else:

26 p = subprocess.Popen(["mpv", link] + args.mpv, shell=False)

27 p.communicate()

28 print("ReddYtt: That was: %s" % link)

29 if p.returncode == 0:

30 # The video finished or you hit 'q' (or whatever your binding is), this is a good exit.

31 # Store the video in seen_links.

32 seen_links.append(link)

33 save_links.remove(link)

34 + elif p.returncode == 4:

35 # You made a hard exit, and want to stop. (Ctrl+C)

36 # Store the links and exit the program.

37 print("ReddYtt: Forced exit detected. Saving and exiting.")

Fig. 62: Commit for vulnerability (Remote Code Execution 3)

<https://github.com/johanbluecreek/reddytt/commit/bd037e882d675ea27b96d41faf0deeac6563695c>

```

if __name__ == '__main__':
    parser = ap.ArgumentParser(usage='% (prog)s [options] <subreddit> [-- [mpv-arguments]]', description='Play the youtube links from your favourite subreddit.')
    parser.add_argument('--depth', metavar='d', type=int, default=0, help='How many pages into the subreddit you want to go.')
    parser.add_argument('subreddit', type=str, help='The subreddit you want to play.')
    parser.add_argument('mpv', nargs=ap.REMAINDER, help='Arguments to pass to mpv.')

    args = parser.parse_args()

    subreddit = args.subreddit
    depth = args.depth
    mpv = " ".join(args.mpv)

    subreddit_link = "https://reddit.com/r/" + subreddit

    # Setup working directory
    work_dir = os.environ['HOME'] + "/.reddytt"
    sr_dir = work_dir + "/" + subreddit
    seen_file = sr_dir + "/seen"
    seen_links = []
    unseen_file = sr_dir + "/unseen"
    unseen_links = []
    print("Reddytt: Checking for reddytt working directory (%s)." % work_dir)

    if not os.path.isdir(work_dir):
        print("Reddytt: Working directory not found. Creating %s, and files." % work_dir)
        os.mkdir(work_dir)
        os.mkdir(sr_dir)
        os.system("touch %s" % seen_file)
        with open(seen_file, 'wb') as f:
            pickle.dump(seen_links, f)
        os.system("touch %s" % unseen_file)
        with open(unseen_file, 'wb') as f:
            pickle.dump(unseen_links, f)
    elif not os.path.isdir(sr_dir):
        print("Reddytt: Working directory found, but no subreddit directory. Creating %s, and files." % sr_dir)
        os.mkdir(sr_dir)
        os.system("touch %s" % seen_file)
        with open(seen_file, 'wb') as f:
            pickle.dump(seen_links, f)
        os.system("touch %s" % unseen_file)
        with open(unseen_file, 'wb') as f:
            pickle.dump(unseen_links, f)
    else:
        print("Reddytt: Working directory found. Loading variables.")
        with open(seen_file, 'rb') as f:
            seen_links = pickle.load(f)
        with open(unseen_file, 'rb') as f:
            unseen_links = pickle.load(f)

    new_links, links = getytlinks(subreddit_link)

    # So deeper
    if depth > 0:
        for d in range(depth):
            link = ""
            for l in links:
                if re.search("after=", l):
                    link = l
            if link == "":
                print("Reddytt: Could not identify 'after'-variable to progress deeper.")
            else:
                newer_links, links = getytlinks(link)
                new_links += newer_links
                new_links = list(set(new_links))

    # we also want to watch the stored ones
    new_links += unseen_links
    new_links = list(set(new_links))

    # Start watching
    save_links = new_links
    for link in new_links:
        if link in seen_links:
            print("Reddytt: Link seen. Skipping.")
        else:
            x = os.system("mpv %s %s" % (link)s % ("link": link, "args": mpv))
            print("Reddytt: That was: %s" % link)
            if x == 0:
                # The video finished or you hit 'q' (or whatever your binding is), this is a good exit.
                # Store the video in seen_links.
                seen_links.append(link)
                save_links.remove(link)
            elif x == 1024:
                # You made a hard exit, and want to stop. (Ctrl+C)
                # Store the links and exit the program.
                print("Reddytt: Forced exit detected. Saving and exiting.")
                with open(seen_file, 'wb') as f:
                    pickle.dump(seen_links, f)
                with open(unseen_file, 'wb') as f:
                    pickle.dump(save_links, f)
                # Exit program.
                sys.exit()

```

Fig. 63: Detection of vulnerability (Remote Code Execution 3)

Selbständigkeitserklärung

Ich erkläre hiermit, dass ich die vorliegende Arbeit selbständig verfasst und noch nicht für andere Prüfungen eingereicht habe. Sämtliche Quellen einschließlich Internetquellen, die unverändert oder abgewandelt wiedergegeben werden, insbesondere Quellen für Texte, Grafiken, Tabellen und Bilder, sind als solche kenntlich gemacht. Mir ist bekannt, dass bei Verstößen gegen diese Grundsätze ein Verfahren wegen Täuschungsversuchs bzw. Täuschung eingeleitet wird.