

Question 1:

Write a method that overrides the getID method for Doctor_ty type. The overridden method should return the registration number (regNo).

ANSWER:

SQL:

```
ALTER TYPE Doctor_ty ADD OVERRIDING MEMBER FUNCTION getID RETURN CHAR CASCADE;  
  
CREATE OR REPLACE TYPE BODY Doctor_ty AS OVERRIDING MEMBER FUNCTION getID RETURN  
CHAR IS BEGIN RETURN regNo; END; END; /
```

Question 2:

Use the method declared above (i.e. getID) and print the ids of all doctors.

ANSWER:

SQL:

```
SELECT TREAT(VALUE(d) AS Doctor_ty).getID() FROM People d WHERE VALUE(d) IS OF (ONLY  
Doctor_ty);
```

Brief Explanation (for your notes):

Part 1 (Overriding getID): - ALTER TYPE ... ADD OVERRIDING → Adds a new version of getID that replaces the one from the parent type. - CREATE OR REPLACE TYPE BODY → Contains the actual logic: simply returns the doctor's regNo.

Part 2 (Query to display Doctor IDs): - TREAT(VALUE(d) AS Doctor_ty) → Treats the object as a Doctor so we can call the Doctor-specific getID() method. - WHERE VALUE(d) IS OF (ONLY Doctor_ty) → Shows only Doctor rows (filters out Patients).