

Introduction to Colour Science

NPGR025

Unit 8: WB, CAT, CAM



Computer
Graphics
Charles
University

Sources



Computer
Graphics
Charles
University

Overview

- White Balance
- Colour Transforms
- CIECAM

2



Computer
Graphics
Charles
University

White Balance Colour Appearance Transforms (CAT)

3

Terminology

- **Colour Constancy (CC)**
 - The name for the phenomenon
- **Chromatic Adaptation (CA)**
 - What your brain and eyes do to compensate ambient illumination colour casts
 - The name of the process behind CC
- **White Balance (WB)**
 - "What you do to images to make them look right"
 - Effectively simulation of CC/CA under different viewing conditions


4

Colour Transforms

- Colour values are dependent on the illuminant they are measured under
 - Reflected light = illumination x reflectance
- If only a colour value is known for an object, it is impossible to predict exactly what it will look like under a different illuminant
 - However, reasonable approximations of varying quality are possible
 - Von Kries, Bradford transform
 - These are referred to as "chromatic adaptation transforms" (CAT)

5

Colour - A Visual Sensation



6



Chromatic Adaptation: Example



7



Colour Correction

- Alternative name: white balance
- Attempts to replicate the illuminant hue compensation of the human visual system
- Overall goal: *evoke identical viewer response to captured or synthetic scenes, and reality*
- Problem: different viewing surrounds, different adaptation states of observer
 - Real scene: immersion
 - Captured scene (image): displayed on monitor
- Solution: *Colour Appearance Models*

8



CAM Overview





Figure from Kim, Weyrich, Kautz: Modeling Human Color Perception under Extended Luminance Levels, SIGGRAPH 2009

9

Colour Correction Workflow

- Colour Correction is a two-step process:
 - Determining the illuminant colour
 - Applying a transform that compensates for the illuminant
- *Step 1 is the tricky one if you only have image data at your disposal!*



10

State of the Art - Step 1

- Still a challenging task - many algorithms exist
 - Gray world, White patch, Retinex
 - Gamut constraint, Neural networks
- Large research area in computer vision
 - Goals are sometimes subtly different from computer graphics needs
- Almost all current algorithms are image based
 - Exception: Ward et al.
- Very sophisticated methods available
 - However, none are entirely robust!

11

Step 2 - Colour Appearance Transforms

- Colour values are dependent on the illuminant they are measured under
 - Reflected light = illumination x reflectance
- If only a colour value is known for an object, it is impossible to predict exactly what it will look like under a different illuminant
 - However, reasonable approximations of varying quality are possible
 - Von Kries, Bradford transform
 - These are referred to as "chromatic adaptation transforms" (CAT)

12

Linear Transform Chromatic Adaptation

- All colours are transformed within CIE XYZ space by a 3x3 matrix M

$$\begin{bmatrix} X_D & Y_D & Z_D \end{bmatrix} = \begin{bmatrix} X_S & Y_S & Z_S \end{bmatrix} \cdot \begin{bmatrix} M \end{bmatrix}$$

(D - destination, S - source)

- The matrix M is dependent on the source and destination reference whites, which are also specified in CIE XYZ coordinates

13

Matrix Adaptation

- Transform the CIE XYZ value you want to adapt to a cone response domain (ρ, γ, β)
- Scale the (ρ, γ, β) components in this domain, based on the (ρ, γ, β) components of the two white points
- Transform the (ρ, γ, β) coordinates back to CIE XYZ with the inverse transform
- Executive Summary: you use source and destination white as input, and you get a 3x3 transformation matrix

14

Matrix Notation

$$\begin{bmatrix} X_D & Y_D & Z_D \end{bmatrix} = \begin{bmatrix} X_S & Y_S & Z_S \end{bmatrix} \cdot \begin{bmatrix} M \end{bmatrix}$$

$$\begin{bmatrix} M \end{bmatrix} = \begin{bmatrix} M_A \end{bmatrix} \begin{bmatrix} \rho_D / \rho_S & 0 & 0 \\ 0 & \gamma_D / \gamma_S & 0 \\ 0 & 0 & \beta_D / \beta_S \end{bmatrix} \begin{bmatrix} M_A \end{bmatrix}^{-1}$$

$$\begin{bmatrix} \rho_S & \gamma_S & \beta_S \end{bmatrix} = \begin{bmatrix} X_{WS} & Y_{WS} & Z_{WS} \end{bmatrix} \cdot \begin{bmatrix} M_A \end{bmatrix}$$

$$\begin{bmatrix} \rho_D & \gamma_D & \beta_D \end{bmatrix} = \begin{bmatrix} X_{WD} & Y_{WD} & Z_{WD} \end{bmatrix} \cdot \begin{bmatrix} M_A \end{bmatrix}$$

15

- Von Kries - older approach


$$[M_A] = \begin{bmatrix} 0.40024 & -0.22630 & 0.00000 \\ 0.70760 & 1.16532 & 0.00000 \\ -0.08081 & 0.04570 & 0.91822 \end{bmatrix}$$

- Bradford - newer, used within Photoshop

$$[M_A] = \begin{bmatrix} 0.8951 & -0.7502 & 0.0389 \\ 0.2664 & 1.7135 & -0.0685 \\ -0.1614 & 0.0367 & 1.0296 \end{bmatrix}$$

16

- Illuminant and red Macbeth patch CIE (x,y) coordinates:




17

A Technique for Determining Relevant Illumination in Renderings

18


Algorithm Overview

- Two additional images are computed during rendering
 - All directly viewed surfaces set to neutral
 - All lights set to neutral on directly viewed surfaces
- Cheap to compute as by-product of rendering
- Sub-sampling possible
- Images processed to get actual illumination estimate



19



Illumination Estimator - Overview



20

NWCI Image

NWCI stands for **N**eutral **W**orld, **C**oloured **I**lluminants




21

NWCI stands for Coloured World, Neutral Illuminants



22

1 - Chroma Image



23

1 - Chroma Image

- CWNI image is converted to LCH space
- Compute min, max chroma and luminance values for entire image


$$g = \left(\left(1 - \frac{C_{pixel} - C_{min}}{C_{max} - C_{min}} \right) \cdot \frac{L_{pixel}}{L_{max}} \right)^w$$

- Parameter **w** allows control of how much emphasis is placed on reference white objects


24



NWCImul Image



1-Chroma Image



NWCImul Image

25




Results

26




White vs. Orange World



colour corrected image

white box, orange light




colour corrected image

orange box, white light

27

3D Mondrian, Yellow Illuminant




no white object present




one white block in scene

28

Green-Blue 3D Mondrian, Blue Light



no white object present



one white block in scene

29

Adaptation for Reference White Objects



30

Influence of Parameter w

$w = 4$

1 - Chroma image




NWCimul image



31

Additional Examples



32

Realistic Scene, Various Illuminants

daylight, tinted window



colour corrected image

33

Conclusion

- Technique to reliably extract relevant illuminant colour from renderings
- Cheap to compute
- Caters for influence of larger influence of white objects on illuminant colour perception
- How this information is then used is up to the tone reproduction / CAM used
 - Bradford transform appears to be sufficient

14

Chromatic Adaptation Models (CAM)

15

CIELab & CIELuv Appearance Prediction

- CIE Lab & CIE Luv are limited in their applicability
 - Theoretically only valid for small viewing angles
 - Surround and observer status are not included in the model
- For prediction of object appearance under varying conditions, CATs have to be used
 - Inherently inaccurate
- Integrated models are needed!


16

Colour Appearance Models - CIECAM

- A **Colour Appearance Model** is a model of colour vision, which is capable of predicting colour appearance under different viewing conditions
- A CAM must
 - Account for chromatic adaptation
 - Have correlates for at least lightness, chroma and hue (CIE TC 1-34, 1992)


CIECAM 97 and 02

- First CIE CAM published in 1997, revised in 2002 (CIECAM 02 replaces 97)
- **Complex model with many input parameters:**
 - Illuminant colour / reference white
 - Surround luminance
 - Background luminance
 - Colour value
 - Context parameters



CIECAM I/O

- Transforms XYZ data to a perceptual space



CAM Overview





Figure from Kim, Weyrich, Kautz: Modeling Human Color Perception under Extended Luminance Levels, SIGGRAPH 2009

40

CAT vs. CAMs in Image Reproduction



41