

```
#!/usr/bin/env python
# -*- coding: utf-8 -*-

__author__ = "Konstantinos Kitsios"
__version__ = "1.0.1"
__maintainer__ = "Konstantinos Kitsios"
__email__ = "kitsiosk@ece.auth.gr"

"""
Simple Neural Network with 1 hidden layer with the number
of hidden units as a hyperparameter to calculate the XOR function
"""

import numpy as np

def sigmoid(z):
    return 1 / (1 + np.exp(-z))

def initialize_parameters(n_x, n_h, n_y):
    W1 = np.random.randn(n_h, n_x)
    b1 = np.zeros((n_h, 1))
    W2 = np.random.randn(n_y, n_h)
    b2 = np.zeros((n_y, 1))

    parameters = {
        "W1": W1,
        "b1": b1,
        "W2": W2,
        "b2": b2
    }
    return parameters

def forward_prop(X, parameters):
    W1 = parameters["W1"]
    b1 = parameters["b1"]
    W2 = parameters["W2"]
    b2 = parameters["b2"]

    Z1 = np.dot(W1, X) + b1
    A1 = np.tanh(Z1)
    Z2 = np.dot(W2, A1) + b2
    A2 = sigmoid(Z2)

    cache = {
        "A1": A1,
        "A2": A2
    }
    return A2, cache

def calculate_cost(A2, Y):

def backward_prop(X, Y, cache, parameters):
    A1 = cache["A1"]
    A2 = cache["A2"]

    W2 = parameters["W2"]

    dZ2 = A2 - Y
    dW2 = np.dot(dZ2, A1.T) / m
    db2 = np.sum(dZ2, axis=1, keepdims=True) / m
    dZ1 = np.multiply(np.dot(W2.T, dZ2), 1 - np.power(A1, 2))
    dW1 = np.dot(dZ1, X.T) / m
    db1 = np.sum(dZ1, axis=1, keepdims=True) / m

    grads = {
        "dW1": dW1,
        "db1": db1,
        "dW2": dW2,
        "db2": db2
    }

    return grads

def update_parameters(parameters, grads, learning_rate):
    W1 = parameters["W1"]
    b1 = parameters["b1"]
    W2 = parameters["W2"]
    b2 = parameters["b2"]

    dW1 = grads["dW1"]
    db1 = grads["db1"]
    dW2 = grads["dW2"]
    db2 = grads["db2"]

    W1 = W1 - learning_rate * dW1
    b1 = b1 - learning_rate * db1
    W2 = W2 - learning_rate * dW2
    b2 = b2 - learning_rate * db2

    new_parameters = {
        "W1": W1,
        "W2": W2,
        "b1": b1,
        "b2": b2
    }

    return new_parameters

def model(X, Y, n_x, n_h, n_y, num_of_iters, learning_rate):
    parameters = initialize_parameters(n_x, n_h, n_y)

    for i in range(0, num_of_iters + 1):
        a2, cache = forward_prop(X, parameters)

        cost = calculate_cost(a2, Y)

        grads = backward_prop(X, Y, cache, parameters)

        parameters = update_parameters(parameters, grads, learning_rate)

        if (i % 100 == 0):
            print('Cost after iteration# {}: {}'.format(i, cost))

    return parameters

def predict(X, parameters):
    a2, cache = forward_prop(X, parameters)
    yhat = a2
    yhat = np.squeeze(yhat)
    if (yhat >= 0.5):
        y_predict = 1
    else:
        y_predict = 0

    return y_predict

np.random.seed(2)

# The 4 training examples by columns
X = np.array([[0, 0, 1, 1], [0, 1, 0, 1]])

# The outputs of the XOR for every example in X
Y = np.array([[1, 0, 0, 1]])

# No. of training examples
m = X.shape[1]

# Set the hyperparameters
n_x = 2 # No. of neurons in first layer
n_h = 2 # No. of neurons in hidden layer
n_y = 1 # No. of neurons in output layer
num_of_iters = 1000
learning_rate = 0.3

trained_parameters = model(X, Y, n_x, n_h, n_y, num_of_iters, learning_rate)

# Test 2X1 vector to calculate the XOR of its elements.
# Try (0, 0), (0, 1), (1, 0), (1, 1)
X_test = np.array([[1], [1]])

cost = -np.sum(np.multiply(Y, np.log(A2)) + np.multiply(1 - Y, np.log(1 - A2))) / m
cost = np.squeeze(cost)

return cost

def backward_prop(X, Y, cache, parameters):
    A1 = cache["A1"]
    A2 = cache["A2"]

    W2 = parameters["W2"]

    dZ2 = A2 - Y
    dW2 = np.dot(dZ2, A1.T) / m
    db2 = np.sum(dZ2, axis=1, keepdims=True) / m
    dZ1 = np.multiply(np.dot(W2.T, dZ2), 1 - np.power(A1, 2))
    dW1 = np.dot(dZ1, X.T) / m
    db1 = np.sum(dZ1, axis=1, keepdims=True) / m

    grads = {
        "dW1": dW1,
        "db1": db1,
        "dW2": dW2,
        "db2": db2
    }

    return grads

def update_parameters(parameters, grads, learning_rate):
    W1 = parameters["W1"]
    b1 = parameters["b1"]
    W2 = parameters["W2"]
    b2 = parameters["b2"]

    dW1 = grads["dW1"]
    db1 = grads["db1"]
    dW2 = grads["dW2"]
    db2 = grads["db2"]

    W1 = W1 - learning_rate * dW1
    b1 = b1 - learning_rate * db1
    W2 = W2 - learning_rate * dW2
    b2 = b2 - learning_rate * db2

    new_parameters = {
        "W1": W1,
        "W2": W2,
        "b1": b1,
        "b2": b2
    }

    return new_parameters

y_predict = predict(X_test, trained_parameters)

print('Neural Network prediction for example ({:d}, {:d}) is {:d}'.format(
    X_test[0][0], X_test[1][0], y_predict))
```