Accenture Technical Mock Test — Set 10

45 Questions • Computer Science • Networking • Pseudo Code

Pattern aligned to the supplied Accenture mock materials. Questions are uniquely authored across the 10 sets.

Section 1 — Computer Science

Q1. Which deployment strategy gradually shifts traffic to a new application version?

A. Big-bang deployment
B. Cold backup
C. Canary deployment
D. Static linking

Q2. Which JavaScript method removes the last array element?

A. slice()
B. shift()
C. push()
D. pop()

Q3. Which HTTP method is intended to retrieve a representation without modifying server state?

A. PUT
B. DELETE
C. POST
D. GET

Q4. Which SQL join includes unmatched rows from both `Students` and `Enrollments`?

A. SELF JOIN
B. INNER JOIN
C. LEFT JOIN
D. CROSS JOIN

Q5. What is the result of Java expression `"A".repeat(3).length()`?

A. 4
B. Compilation error
C. 6
D. 3

Q6. Which SQL statement changes existing rows?

A. UPDATE
B. ALTER
C. INSERT
D. CREATE

Q7. Which HTTP method is generally used to partially update a resource?

A. TRACE
B. GET
C. HEAD
D. PATCH

Q8. A `Square` class gives its own implementation of `draw()` inherited from `Shape`. What is this called?

A. Aggregation
B. Constructor chaining
C. Method overriding
D. Method overloading

Q9. Which graph algorithm finds a minimum spanning tree by repeatedly choosing the smallest safe edge?

A. Kruskal's algorithm
B. Dijkstra's algorithm
C. Floyd-Warshall
D. BFS

Q10. What is the result of Java expression `"A".repeat(11).length()`?

A. Compilation error
B. 11
C. 12
D. 22

Q11. Which SQL clause filters groups after aggregation?

A. WHERE
B. DISTINCT
C. ORDER BY
D. HAVING

Q12. Which SQL aggregate function returns the average value of `amount`?

A. MAX()
B. COUNT()
C. AVG()
D. SUM()

Q13. When a subclass supplies a replacement implementation for an inherited method, which OOP feature is used?

A. Constructor chaining
B. Method overloading
C. Method overriding
D. Aggregation

Q14. Which keyword declares that a method may pass an exception to its caller?

A. throws
B. throw
C. catch
D. finally

Section 2 — Fundamentals of Networking

Q15. What is the subnet mask for /24?

A. 255.0.0.0
B. 255.255.255.128
C. 255.255.0.0
D. 255.255.255.0

Q16. Which firewall type filters packets without maintaining connection state?

A. WAF only
B. Proxy ARP
C. Stateful firewall
D. Stateless firewall

Q17. What does NAT primarily do?

A. Assigns MAC addresses
B. Translates private and public IP addresses
C. Encrypts every packet
D. Resolves DNS names

Q18. Which address represents all IPv4 hosts on the local network?

A. 127.0.0.1
B. 224.0.0.1
C. 0.0.0.0
D. 255.255.255.255

Q19. Which EAP method commonly creates a TLS tunnel using a server certificate and then carries inner credentials?

A. PEAP
B. RIP
C. ARP
D. EAP-TLS

Q20. Which cloud service connects on-premises networks to cloud networks using a dedicated private circuit?

A. WAF
B. DNS resolver
C. Direct Connect/ExpressRoute
D. NAT gateway only

Q21. Which application is most sensitive to jitter?

A. Database dump
B. Bulk file archive
C. Real-time voice
D. Email backup

Q22. Which routing protocol is a link-state interior gateway protocol?

A. RIP
B. OSPF
C. BGP
D. ARP

Q23. Which routing metric counts the number of hops?

A. Delay only
B. Bandwidth
C. Hop count
D. CPU load

Q24. Which device separates broadcast domains by default?

A. Router
B. Hub
C. Patch panel
D. Layer-2 repeater

Q25. Which device separates collision domains on each switch port?

A. Passive splitter
B. Repeater
C. Hub
D. Switch

Q26. Which protocol securely transfers files using TLS?

A. FTP plain
B. ARP
C. FTPS
D. TFTP

Q27. How many usable IPv4 host addresses are normally available in a /26 subnet?

A. 62
B. 64

C. 32

D. 60

Q28. Which port is commonly used by RDP?

A. 8080

B. 3389

C. 161

D. 3306

Section 3 — Pseudo Code

Q29. Using bitwise XOR, what is printed?

```
x ← 11
y ← 7
PRINT x ^ y
```

A. 12

B. 18

C. 77

D. 4

Q30. What is printed by the recursive function for n = 7?

```
FUNCTION F(n)
IF n <= 1
RETURN n
RETURN F(n-1) + F(n-2)
END FUNCTION
PRINT F(7)
```

A. 14

B. 13

C. 7

D. 12

Q31. How many times is the inner statement executed?

```
count ← 0
FOR i ← 1 TO 4
FOR j ← 1 TO 3
count ← count + 1
END FOR
END FOR
PRINT count
```

A. 7

B. 11

C. 4

D. 12

Q32. How many vowels are counted in `PYTHON`?

```
s ← "PYTHON"
count ← 0
FOR each ch IN s
IF ch is a vowel
count ← count + 1
END IF
END FOR
PRINT count
```

A. 0

B. 1

C. 2

D. 6

Q33. What value is printed?

```
a ← 4
b ← 7
```

```
IF a > b
PRINT a
ELSE
PRINT b
END IF
```

A. 7

B. 11

C. 3

D. 4

Q34. What value is printed?

```
count ← 0
FOR i ← 1 TO 30
IF i MOD 2 = 0
count ← count + 1
END IF
END FOR
PRINT count
```

A. 16

B. 15

C. 30

D. 14

Q35. What is the output?

```
A ← [3, 8, 2, 9]
sum ← 0
FOR i ← 0 TO 3
sum ← sum + A[i]
END FOR
PRINT sum
```

A. 4

B. 9

C. 2

D. 22

Q36. What is the output?

```
A ← [11, 3, 6]
sum ← 0
FOR i ← 0 TO 2
sum ← sum + A[i]
END FOR
PRINT sum
```

A. 11

B. 20

C. 3

D. 3

Q37. What position is printed for the target?

```
A ← [11, 5, 2, 9]
target ← 2
FOR i ← 0 TO 3
IF A[i] = target
PRINT i + 1
BREAK
END IF
END FOR
```

A. 3

B. 4

C. 0

D. 2

Q38. What is the final printed value?

```
n ← 2507
sum ← 0
```

```
WHILE n > 0
digit ← n MOD 10
sum ← sum + digit
n ← n DIV 10
END WHILE
PRINT sum
```

A. 15

B. 14

C. 4

D. 7

Q39. What is printed by the pseudocode?

```
x ← 18
sum ← 0
FOR i ← 1 TO x
sum ← sum + i
END FOR
PRINT sum
```

A. 324

B. 172

C. 171

D. 170

Q40. How many vowels are counted in `PROGRAM`?

```
s ← "PROGRAM"
count ← 0
FOR each ch IN s
IF ch is a vowel
count ← count + 1
END IF
END FOR
PRINT count
```

A. 2

B. 3

C. 7

D. 0

Q41. What is printed?

```
x ← 88
PRINT x MOD 13
```

A. 10

B. 13

C. 11

D. 6

Q42. What is printed?

```
n ← 10
fact ← 1
FOR i ← 1 TO n
fact ← fact * i
END FOR
PRINT fact
```

A. 3628801

B. 100

C. 3628800

D. 3628790

Q43. What is the final value of sum?

```
sum ← 0
FOR i ← 2 TO 10 STEP 2
sum ← sum + i
END FOR
PRINT sum
```

A. 32

B. 30

C. 8

D. 5

Q44. What is the final printed value?

```
n ← 4312
sum ← 0
WHILE n > 0
digit ← n MOD 10
sum ← sum + digit
n ← n DIV 10
END WHILE
PRINT sum
```

A. 11

B. 10

C. 4

D. 12

Q45. What is printed after the assignments?

```
x ← 2
y ← 5
x ← y
y ← 3
PRINT x + y
```

A. 8

B. 7

C. 5

D. 2