Accenture Technical Mock Test — Set 2

45 Questions • Computer Science • Networking • Pseudo Code

Pattern aligned to the supplied Accenture mock materials. Questions are uniquely authored across the 10 sets.

Section 1 — Computer Science

Q1. Which CSS selector targets an element with id `main`?

A. main
B. .main
C. #.main
D. #main

Q2. In Java, `print(int)` and `print(String)` have the same method name but different parameters. What feature is this?

A. Method overriding
B. Encapsulation
C. Method overloading
D. Composition

Q3. Which HTML element creates a hyperlink?

A. <a>
B. <url>
C. <link>
D. <href>

Q4. Which Java exception is unchecked?

A. ClassNotFoundException
B. NullPointerException
C. SQLException
D. IOException

Q5. Which SQL aggregate function returns the average value of `age`?

A. SUM()
B. COUNT()
C. AVG()
D. MAX()

Q6. Which SQL join returns all rows from both `Customers` and `Orders`, including unmatched rows?

A. LEFT JOIN
B. FULL OUTER JOIN
C. CROSS JOIN
D. INNER JOIN

Q7. Which algorithm uses a divide-and-conquer strategy to sort an array around a pivot?

A. Linear search
B. Bubble sort
C. Counting sort
D. Quick sort

Q8. What is the result of Java expression `"A".repeat(8).length()`?

A. Compilation error
B. 8
C. 16
D. 9

Q9. What software layer creates virtual machines on a physical host?

A. Hypervisor
B. Firewall
C. Proxy
D. Compiler

Q10. Which object stores a saved query that can be queried like a table?

A. Trigger
B. Index
C. Sequence
D. View

Q11. Which mechanism automatically executes logic when INSERT/UPDATE/DELETE occurs?

A. Trigger
B. View
C. Schema
D. Index

Q12. Which cloud model delivers complete ready-to-use software over the web?

A. SaaS
B. IaaS
C. PaaS
D. FaaS

Q13. A class declares `area(int)` and `area(double)` methods. Which compile-time polymorphism feature is used?

A. Composition
B. Method overriding
C. Encapsulation
D. Method overloading

Q14. Which interface is used to define an ordering external to a class?

A. Comparator
B. Callable
C. Iterable
D. AutoCloseable

Section 2 — Fundamentals of Networking

Q15. Which 802.1X component actually requests network access authentication?

A. Authenticator
B. Supplicant
C. DNS resolver
D. RADIUS server

Q16. Which load-balancing strategy sends a request to the server with the fewest active connections?

A. Flooding
B. Round robin
C. Least connections
D. Random DNS

Q17. Which protocol is used to send email between mail servers?

A. POP3
B. SMTP
C. IMAP
D. DNS

Q18. Which device forwards packets between different IP networks?

A. Repeater
B. Hub
C. Router
D. Bridge only

Q19. Which IPv4 range is private?

A. 1.1.1.0/24
B. 192.168.0.0/16
C. 172.40.0.0/16
D. 8.8.8.0/24

Q20. Which protocol bundles multiple physical links into one logical link for higher bandwidth/redundancy?

A. LACP
B. ARP
C. DNS
D. ICMP

Q21. Which NAT type maps many private hosts to one public address using different ports?

A. DNS
B. Static NAT
C. Proxy ARP
D. PAT

Q22. Which attack overwhelms a service with traffic from many distributed sources?

A. Port mirroring
B. ARP spoofing
C. DDoS
D. DNS caching

Q23. Which IPv4 prefix represents the default route?

A. 127.0.0.0/8
B. 255.255.255.255/32
C. 0.0.0.0/0
D. 10.0.0.0/8

Q24. Which wireless standard uses 5 GHz and can provide higher throughput than older 802.11a/b/g deployments?

A. 802.11ac
B. 802.11b
C. 802.11g
D. 802.11a only

Q25. What is the subnet mask for /28?

A. 255.255.255.248
B. 255.255.255.240
C. 255.255.0.0
D. 255.255.255.224

Q26. What is the subnet mask for /27?

A. 255.255.255.240
B. 255.255.255.192
C. 255.255.255.224
D. 255.255.255.128

Q27. A /24 IPv4 subnet contains how many total addresses?

A. 256
B. 254

C. 128

D. 512

Q28. Which IPv4 class is historically reserved for multicast?

A. Class B

B. Class C

C. Class A

D. Class D

Section 3 — Pseudo Code

Q29. What is printed after the assignments?

```
x ← 3
y ← 11
x ← y
y ← 6
PRINT x + y
```

A. 5

B. 9

C. 14

D. 17

Q30. What position is printed for the target?

```
A ← [2, 9, 5, 8]
target ← 8
FOR i ← 0 TO 3
IF A[i] = target
PRINT i + 1
BREAK
END IF
END FOR
```

A. 0

B. 5

C. 4

D. 3

Q31. What value is printed?

```
count ← 0
FOR i ← 1 TO 17
IF i MOD 2 = 0
count ← count + 1
END IF
END FOR
PRINT count
```

A. 8

B. 9

C. 17

D. 7

Q32. What is the final value of sum?

```
sum ← 0
FOR i ← 5 TO 20 STEP 5
sum ← sum + i
END FOR
PRINT sum
```

A. 55

B. 15

C. 50

D. 4

Q33. What value is printed?

```
a ← 5
b ← 3
IF a > b
PRINT a
ELSE
PRINT b
END IF
```

A. 5

B. 8

C. 2

D. 3

Q34. What is the final printed value?

```
n ← 3405
sum ← 0
WHILE n > 0
digit ← n MOD 10
sum ← sum + digit
n ← n DIV 10
END WHILE
PRINT sum
```

A. 13

B. 4

C. 12

D. 5

Q35. What is printed?

```
x ← 65
PRINT x MOD 11
```

A. 10

B. 11

C. 11

D. 5

Q36. What is printed for the string `NOON`?

```
s ← "NOON"
r ← reverse(s)
IF s = r
PRINT "YES"
ELSE
PRINT "NO"
END IF
```

A. EMPTY

B. YES

C. ERROR

D. NO

Q37. What is printed by the recursive function for n = 4?

```
FUNCTION F(n)
IF n <= 1
RETURN n
RETURN F(n-1) + F(n-2)
END FUNCTION
PRINT F(4)
```

A. 4

B. 4

C. 2

D. 3

Q38. Using bitwise AND, what is printed?

```
x ← 13
y ← 9
PRINT x & y
```

A. 22

B. 4

C. 117

D. 9

Q39. What is the output?

```
A ← [4, 6, 10, 2]
sum ← 0
FOR i ← 0 TO 3
sum ← sum + A[i]
END FOR
PRINT sum
```

A. 10

B. 22

C. 2

D. 4

Q40. What value is printed?

```
A ← [6, 1, 11, 4]
mx ← A[0]
FOR i ← 1 TO 3
IF A[i] > mx
mx ← A[i]
END IF
END FOR
PRINT mx
```

A. 22

B. 1

C. 11

D. 4

Q41. How many times is the inner statement executed?

```
count ← 0
FOR i ← 1 TO 3
FOR j ← 1 TO 4
count ← count + 1
END FOR
END FOR
PRINT count
```

A. 12

B. 7

C. 11

D. 4

Q42. What is printed by the pseudocode?

```
x ← 15
sum ← 0
FOR i ← 1 TO x
sum ← sum + i
END FOR
PRINT sum
```

A. 225

B. 119

C. 121

D. 120

Q43. What value is printed?

```
n ← 613
rev ← 0
WHILE n > 0
d ← n MOD 10
rev ← rev * 10 + d
n ← n DIV 10
END WHILE
PRINT rev
```

A. 613

B. 316

C. 317

D. 3

Q44. What is printed?

```
n ← 3
fact ← 1
FOR i ← 1 TO n
fact ← fact * i
END FOR
PRINT fact
```

A. 3

B. 7

C. 9

D. 6

Q45. What is printed for the string `ACCENTURE`?

```
s ← "ACCENTURE"
r ← reverse(s)
IF s = r
PRINT "YES"
ELSE
PRINT "NO"
END IF
```

A. YES

B. NO

C. EMPTY

D. ERROR