# Accenture Technical Mock Test — Set 7

45 Questions • Computer Science • Networking • Pseudo Code

Pattern aligned to the supplied Accenture mock materials. Questions are uniquely authored across the 10 sets.

## Section 1 — Computer Science

**Q1.** Which JavaScript method adds an element to the end of an array?

**A.** shift()
**B.** pop()
**C.** unshift()
**D.** push()

**Q2.** Which clause sorts query results?

**A.** SORT
**B.** HAVING
**C.** GROUP BY
**D.** ORDER BY

**Q3.** What is the result of Java expression `"A".repeat(10).length()`?

**A.** 11
**B.** 10
**C.** 20
**D.** Compilation error

**Q4.** Which Java keyword prevents a class from being inherited?

**A.** private
**B.** static
**C.** final
**D.** sealed

**Q5.** Which Linux permission allows a file to be executed?

**A.** r
**B.** w
**C.** s
**D.** x

**Q6.** A class has `max(int,int)` and `max(double,double)` methods. Which feature is used?

**A.** Composition
**B.** Encapsulation
**C.** Method overloading
**D.** Method overriding

**Q7.** Which version-control command creates a local copy of a remote Git repository?

**A.** git reset
**B.** git merge
**C.** git stash
**D.** git clone

**Q8.** `login(String)` and `login(String,String)` are declared in one class. Which Java capability is illustrated?

**A.** Method overloading
**B.** Method overriding
**C.** Composition
**D.** Encapsulation

**Q9.** Which HTTP method is commonly used to create a resource?

**A.** GET
**B.** OPTIONS
**C.** HEAD
**D.** POST

**Q10.** Which SQL command undoes uncommitted changes?

**A.** ROLLBACK
**B.** COMMIT
**C.** MERGE
**D.** TRUNCATE

**Q11.** What is the default value of an instance `int` field in Java?

**A.** 1
**B.** 0
**C.** undefined
**D.** null

**Q12.** Which join returns only records where the join condition succeeds in both tables?

**A.** INNER JOIN
**B.** CROSS JOIN
**C.** RIGHT JOIN
**D.** LEFT JOIN

**Q13.** Which data structure is typically used by DFS iteratively?

**A.** Queue
**B.** Priority queue
**C.** Stack
**D.** Array only

**Q14.** Which join keeps all rows from the first table and fills NULLs when no second-table match exists?

**A.** LEFT JOIN
**B.** CROSS JOIN
**C.** RIGHT JOIN
**D.** INNER JOIN

## Section 2 — Fundamentals of Networking

**Q15.** Which DNS record maps an IPv4 address back to a hostname?

**A.** PTR record
**B.** A record
**C.** MX record
**D.** NS only

**Q16.** Which TCP flag is commonly used to gracefully close a connection?

**A.** ACK
**B.** FIN
**C.** SYN
**D.** ECE

**Q17.** Which default port is associated with SSH?

**A.** 22
**B.** 53
**C.** 21
**D.** 23

**Q18.** Which technique marks packets so routers can prioritize certain traffic classes?

**A.** DNS recursion
**B.** QoS marking
**C.** NAT
**D.** ARP

**Q19.** Which protocol uses Dijkstra's shortest-path-first algorithm?

**A.** OSPF
**B.** DHCP
**C.** RIP
**D.** BGP

**Q20.** Which technology protects DNS responses against tampering using cryptographic signatures?

**A.** DHCP
**B.** SNMP
**C.** DNSSEC
**D.** FTP

**Q21.** Which IPv6 address type is used for loopback?

**A.** FE80::/10
**B.** ::1
**C.** ::
**D.** FF00::/8

**Q22.** Which default port is associated with HTTPS?

**A.** 22
**B.** 80
**C.** 443
**D.** 25

**Q23.** Which protocol can securely authenticate network devices using centralized AAA?

**A.** ICMP
**B.** ARP
**C.** TFTP
**D.** RADIUS

**Q24.** A /29 IPv4 subnet contains how many total addresses?

**A.** 4
**B.** 8
**C.** 6
**D.** 16

**Q25.** What is the network address of 10.0.0.77/26?

**A.** 10.0.0.128
**B.** 10.0.0.0
**C.** 10.0.0.64
**D.** 10.0.0.76

**Q26.** Which DNS technique can distribute clients across multiple IP addresses?

**A.** STP
**B.** DHCP relay
**C.** Round-robin DNS
**D.** ARP inspection

**Q27.** Which IPv6 mechanism replaces broadcast with multicast?

**A.** Multicast
**B.** Unicast flooding

**C.** NAT

**D.** ARP

**Q28.** What is the main purpose of network segmentation?

**A.** Eliminate routing

**B.** Replace DNS

**C.** Increase CPU clock speed

**D.** Limit the spread of unauthorized traffic

## Section 3 — Pseudo Code

**Q29.** What value is printed?

```
A ← [16, 3, 12, 8]
mx ← A[0]
FOR i ← 1 TO 3
IF A[i] > mx
mx ← A[i]
END IF
END FOR
PRINT mx
```

**A.** 16

**B.** 3

**C.** 4

**D.** 39

**Q30.** What is printed after the assignments?

```
x ← 15
y ← 6
x ← y
y ← 3
PRINT x + y
```

**A.** 9

**B.** 21

**C.** 18

**D.** 3

**Q31.** Using bitwise AND, what is printed?

```
x ← 12
y ← 10
PRINT x & y
```

**A.** 22

**B.** 2

**C.** 120

**D.** 8

**Q32.** What value is printed?

```
count ← 0
FOR i ← 1 TO 26
IF i MOD 2 = 0
count ← count + 1
END IF
END FOR
PRINT count
```

**A.** 14

**B.** 13

**C.** 26

**D.** 12

**Q33.** What is printed?

```
x ← 73
PRINT x MOD 10
```

**A.** 7

**B.** 4

**C.** 10

**D.** 3

**Q34.** How many vowels are counted in `COMPUTER`?

```
s ← "COMPUTER"
count ← 0
FOR each ch IN s
IF ch is a vowel
count ← count + 1
END IF
END FOR
PRINT count
```

**A.** 8

**B.** 4

**C.** 0

**D.** 3

**Q35.** What position is printed for the target?

```
A ← [4, 7, 9, 2]
target ← 9
FOR i ← 0 TO 3
IF A[i] = target
PRINT i + 1
BREAK
END IF
END FOR
```

**A.** 0

**B.** 4

**C.** 3

**D.** 2

**Q36.** What is the final printed value?

```
n ← 8046
sum ← 0
WHILE n > 0
digit ← n MOD 10
sum ← sum + digit
n ← n DIV 10
END WHILE
PRINT sum
```

**A.** 19

**B.** 18

**C.** 4

**D.** 46

**Q37.** What value is printed?

```
n ← 390
rev ← 0
WHILE n > 0
d ← n MOD 10
rev ← rev * 10 + d
n ← n DIV 10
END WHILE
PRINT rev
```

**A.** 93

**B.** 390

**C.** 94

**D.** 0

**Q38.** What is printed?

```
n ← 7
fact ← 1
FOR i ← 1 TO n
```

```
fact ← fact * i
END FOR
PRINT fact
```

**A.** 5041

**B.** 49

**C.** 5040

**D.** 5033

**Q39.** What is printed by the recursive function for n = 2?

```
FUNCTION F(n)
IF n <= 1
RETURN n
RETURN F(n-1) + F(n-2)
END FUNCTION
PRINT F(2)
```

**A.** 2

**B.** 2

**C.** 1

**D.** 0

**Q40.** What is the final value of sum?

```
sum ← 0
FOR i ← 2 TO 14 STEP 4
sum ← sum + i
END FOR
PRINT sum
```

**A.** 32

**B.** 4

**C.** 36

**D.** 12

**Q41.** What is printed for the string `RADAR`?

```
s ← "RADAR"
r ← reverse(s)
IF s = r
PRINT "YES"
ELSE
PRINT "NO"
END IF
```

**A.** EMPTY

**B.** YES

**C.** NO

**D.** ERROR

**Q42.** What value is printed?

```
a ← 6
b ← 6
IF a > b
PRINT a
ELSE
PRINT b
END IF
```

**A.** 0

**B.** 12

**C.** 6

**D.** 6

**Q43.** What is printed by the pseudocode?

```
x ← 5
sum ← 0
FOR i ← 1 TO x
sum ← sum + i
END FOR
PRINT sum
```

**A.** 25

**B.** 15

**C.** 16

**D.** 14

**Q44.** How many times is the inner statement executed?

```
count ← 0
FOR i ← 1 TO 2
FOR j ← 1 TO 3
count ← count + 1
END FOR
END FOR
PRINT count
```

**A.** 6

**B.** 5

**C.** 5

**D.** 3

**Q45.** What value is printed?

```
A ← [5, 17, 6, 14]
mx ← A[0]
FOR i ← 1 TO 3
IF A[i] > mx
mx ← A[i]
END IF
END FOR
PRINT mx
```

**A.** 5

**B.** 17

**C.** 4

**D.** 42