# Accenture Technical Mock Test — Set 8

45 Questions • Computer Science • Networking • Pseudo Code

Pattern aligned to the supplied Accenture mock materials. Questions are uniquely authored across the 10 sets.

## Section 1 — Computer Science

**Q1.** Which Linux command displays the current working directory?

**A.** pwd
**B.** cd
**C.** ls
**D.** whoami

**Q2.** Which SQL aggregate function returns the average value of `price`?

**A.** MAX()
**B.** AVG()
**C.** COUNT()
**D.** SUM()

**Q3.** Which traversal visits a binary tree in left-root-right order?

**A.** Postorder
**B.** Level-order
**C.** Preorder
**D.** Inorder

**Q4.** Which keyword explicitly raises an exception?

**A.** throws
**B.** throw
**C.** finally
**D.** catch

**Q5.** Which keyword is used to explicitly invoke a superclass constructor?

**A.** super
**B.** this
**C.** base
**D.** parent

**Q6.** Which HTTP header commonly carries a bearer access token?

**A.** Host
**B.** Accept-Language
**C.** Authorization
**D.** Referer

**Q7.** Which status code indicates a client-side malformed request?

**A.** 404
**B.** 500
**C.** 301
**D.** 400

**Q8.** Which constraint ensures each value in a column is unique?

**A.** NOT NULL
**B.** UNIQUE
**C.** INDEX
**D.** DEFAULT

**Q9.** A subclass overrides an accessible superclass method so the subclass version runs through a parent reference. Which concept is this?

**A.** Method overloading
**B.** Constructor chaining
**C.** Method overriding
**D.** Aggregation

**Q10.** Which SQL command permanently saves the current transaction?

**A.** ROLLBACK
**B.** SAVEPOINT
**C.** GRANT
**D.** COMMIT

**Q11.** Which SQL aggregate function returns the average value of `rating`?

**A.** AVG()
**B.** SUM()
**C.** COUNT()
**D.** MAX()

**Q12.** Which HTTP method is idempotent and commonly replaces a resource?

**A.** CONNECT
**B.** POST
**C.** PATCH
**D.** PUT

**Q13.** What is the result of Java expression `"A".repeat(6).length()`?

**A.** 12
**B.** Compilation error
**C.** 6
**D.** 7

**Q14.** `SavingsAccount` defines its own `withdraw()` implementation inherited from `Account`. What OOP feature is involved?

**A.** Method overriding
**B.** Method overloading
**C.** Aggregation
**D.** Constructor chaining

## Section 2 — Fundamentals of Networking

**Q15.** Which TCP flag abruptly resets a connection?

**A.** FIN
**B.** SYN
**C.** RST
**D.** ACK

**Q16.** What is the broadcast address of 192.168.1.64/26?

**A.** 192.168.1.63
**B.** 192.168.1.255
**C.** 192.168.1.127
**D.** 192.168.1.128

**Q17.** Which technique falsely associates an attacker's MAC address with another host's IP address?

**A.** DNSSEC
**B.** VLAN tagging
**C.** NAT

**D.** ARP spoofing

**Q18.** Which protocol secures Wi-Fi using modern WPA3-Personal authentication?

**A.** SAE
**B.** TKIP
**C.** WEP
**D.** FTP

**Q19.** Which protocol dynamically assigns IP configuration to hosts?

**A.** SNMP
**B.** DHCP
**C.** DNS
**D.** ARP

**Q20.** Which SNMP operation retrieves a managed object's value?

**A.** DISCOVER
**B.** SET only
**C.** GET
**D.** TRAP only

**Q21.** Which DNS record provides an alias from one hostname to another canonical hostname?

**A.** CNAME
**B.** PTR
**C.** MX
**D.** SOA

**Q22.** What is the network address of 192.168.1.130/25?

**A.** 192.168.1.255
**B.** 192.168.1.129
**C.** 192.168.1.0
**D.** 192.168.1.128

**Q23.** Which feature copies traffic from selected switch ports to a monitoring interface?

**A.** NAT
**B.** Link aggregation
**C.** VLAN pruning
**D.** Port mirroring

**Q24.** Which protocol is commonly used to test reachability with echo request/reply?

**A.** ICMP
**B.** ARP
**C.** FTP
**D.** TCP

**Q25.** Which IPv4 address class traditionally includes 10.0.0.0/8 private addresses?

**A.** Class A range
**B.** Class D range
**C.** Class C range
**D.** Class B range

**Q26.** Which transport protocol is connectionless and has lower overhead?

**A.** UDP
**B.** SCTP only
**C.** TCP
**D.** ARP

**Q27.** Which component translates private subnet traffic to the Internet while keeping private hosts unaddressable from outside?

**A.** Public load balancer

**B.** RADIUS

**C.** NAT gateway

**D.** DNS server

**Q28.** Which switch security feature validates ARP packets against trusted bindings?

**A.** Dynamic ARP Inspection

**B.** DHCP relay

**C.** Port forwarding

**D.** NAT

## Section 3 — Pseudo Code

**Q29.** What position is printed for the target?

```
A ← [13, 7, 4, 11]
target ← 11
FOR i ← 0 TO 3
IF A[i] = target
PRINT i + 1
BREAK
END IF
END FOR
```

**A.** 5

**B.** 4

**C.** 0

**D.** 3

**Q30.** How many times is the inner statement executed?

```
count ← 0
FOR i ← 1 TO 5
FOR j ← 1 TO 3
count ← count + 1
END FOR
END FOR
PRINT count
```

**A.** 5

**B.** 15

**C.** 8

**D.** 14

**Q31.** What is the output?

```
A ← [12, 5, 2, 6]
sum ← 0
FOR i ← 0 TO 3
sum ← sum + A[i]
END FOR
PRINT sum
```

**A.** 4

**B.** 12

**C.** 2

**D.** 25

**Q32.** What is the final value of sum?

```
sum ← 0
FOR i ← 3 TO 21 STEP 6
sum ← sum + i
END FOR
PRINT sum
```

**A.** 54

**B.** 48

**C.** 18

**D.** 4

**Q33.** What value is printed?

```
n ← 1205
rev ← 0
WHILE n > 0
d ← n MOD 10
rev ← rev * 10 + d
n ← n DIV 10
END WHILE
PRINT rev
```

**A.** 1205

**B.** 5021

**C.** 5022

**D.** 5

**Q34.** What is printed for the string `JAVA`?

```
s ← "JAVA"
r ← reverse(s)
IF s = r
PRINT "YES"
ELSE
PRINT "NO"
END IF
```

**A.** EMPTY

**B.** YES

**C.** ERROR

**D.** NO

**Q35.** What is printed?

```
n ← 8
fact ← 1
FOR i ← 1 TO n
fact ← fact * i
END FOR
PRINT fact
```

**A.** 40320

**B.** 64

**C.** 40321

**D.** 40312

**Q36.** What value is printed?

```
a ← 13
b ← 18
IF a > b
PRINT a
ELSE
PRINT b
END IF
```

**A.** 18

**B.** 31

**C.** 5

**D.** 13

**Q37.** What is the output?

```
A ← [9, 2, 4, 1]
sum ← 0
FOR i ← 0 TO 3
sum ← sum + A[i]
END FOR
PRINT sum
```

**A.** 4

**B.** 9

**C.** 1

**D.** 16

**Q38.** What is printed for the string `PYTHON`?

```
s ← "PYTHON"
r ← reverse(s)
IF s = r
PRINT "YES"
ELSE
PRINT "NO"
END IF
```

**A.** YES

**B.** EMPTY

**C.** NO

**D.** ERROR

**Q39.** What value is printed?

```
count ← 0
FOR i ← 1 TO 23
IF i MOD 2 = 0
count ← count + 1
END IF
END FOR
PRINT count
```

**A.** 12

**B.** 11

**C.** 23

**D.** 10

**Q40.** What is printed by the pseudocode?

```
x ← 11
sum ← 0
FOR i ← 1 TO x
sum ← sum + i
END FOR
PRINT sum
```

**A.** 121

**B.** 66

**C.** 67

**D.** 65

**Q41.** What is printed?

```
x ← 52
PRINT x MOD 8
```

**A.** 5

**B.** 4

**C.** 8

**D.** 6

**Q42.** What is printed after the assignments?

```
x ← 12
y ← 5
x ← y
y ← 2
PRINT x + y
```

**A.** 3

**B.** 17

**C.** 7

**D.** 14

**Q43.** What is printed by the recursive function for n = 3?

```
FUNCTION F(n)
IF n <= 1
RETURN n
RETURN F(n-1) + F(n-2)
END FUNCTION
PRINT F(3)
```

**A.** 1

**B.** 3

**C.** 2

**D.** 3

**Q44.** Using bitwise AND, what is printed?

```
x ← 14
y ← 3
PRINT x & y
```

**A.** 42

**B.** 17

**C.** 2

**D.** 11

**Q45.** What value is printed?

```
n ← 4567
rev ← 0
WHILE n > 0
d ← n MOD 10
rev ← rev * 10 + d
n ← n DIV 10
END WHILE
PRINT rev
```

**A.** 7655

**B.** 4567

**C.** 7

**D.** 7654