

Day 5: Form

Code Screenshot:

```
ODE > <> Day 5.html > html > body > form > label
 2  <html lang="en">
 8  <body>
 9    <form action="">
17      <input type="text" id="fullName" name="fullName" minlength="3" required p
18      <br>
19      <label for="gender">Gender
20      <input type="radio" id="gender" name="gender" value="M"> male
21      <input type="radio" id="gender" name="gender" value="F"> female
22      <input type="radio" id="gender" name="gender" value="O"> others
23      </label>
24      <br>
25      <label for="gmail">Gmail:</label>|
26      <input type="email" id="gmail" name="email" placeholder="Enter your Email
27      <br>
28      <label for="tel"> Phone :</label>
29      <input type="tel" pattern="[0-9]{4}-[0-9]{3}-[0-9]{3}">
30      <br>
31      <label for="">Position Applied</label>
32      <select name="" id="">
33        <!-- value is used to store the value in backend -->
34        <option value="">--select--</option>
35        <option value="FD">ForntEnd Developer</option>
36        <option value="BD">Backend Developer</option>
37        <option value="SD">Software Developer</option>
38        <option value="UIUX">UI/Ux Developer</option>
39      </select>
40      <br>
41      <input type="text" readonly placeholder="Avoid Fake Information">
42      <br>
43      <label for="date">date:</label>
44      <input type="date" id="date">
45      <br>
46      <label for="cv">Cv :</label>
47      <input type="file" name="cv" id="cv">
48      <br>
49      <button>Submit</button>
```

Output:


Login Page


Full Name:

Gender ☐ male ☐ female ☐ others

Gmail:

Phone :

Position Applied --select-- 

date: 

Cv : No file chosen

Notes:

form:

forms

8)nbsp ; → create one single space

type → attribute (additional element of the element)

Types of input types:

- 1) text 2) password 3) Number 4) Submit 10) name
5) button 6) tel 7) radio 8) email 9) file
(value = button value)

value:

* Value attribute is used to specify the value of an <input> element. The value attribute is used differently for different input types.

* For elements, the value attribute sets the value of list item (for ordered lists).

Form and its attributes:

- An HTML form is used to collect user input.
- The user input is most often sent to a server for processing.
- The <form> element is a container for a types of input elements, such as: text, checkboxes, radio buttons, Submit buttons.