

PROJECT DOCUMENTATION

6. PROJECT DOCUMENTATION PHASE

6.1 PROJECT OVERVIEW

The project “Script-Controlled ACL – Restrict Record Access Based on Field Value” demonstrates how Access Control Lists (ACLs) can be used in ServiceNow to control access to records based on user roles and field values.

In this project, EEE branch users are allowed to access EEE branch records according to the configured ACL, while administrators retain full access.

6.2 USER AND ROLE DETAILS

The following user and roles are created:

User: EEE User

Role: bb1

Role: bb2

Role: bb3

Role: bb4

The roles are used for controlling different record operations.

6.3 TABLE DETAILS

The project uses the following custom table:

Table Label: Institution Details

Table Name: u_institution_details

The table contains:

Student Roll Number

Student Name

Faculty Name

Branch

Email

Phone Number

Description

6.4 ACL DETAILS

The following ACLs are implemented:

ACL	Role	Purpose
-----	------	---------

Read	bb1	Control record viewing
------	-----	------------------------

Create	bb2	Control record creation
--------	-----	-------------------------

Write	bb3	Control record modification
-------	-----	-----------------------------

Delete	bb4	Control record deletion
--------	-----	-------------------------

The Read ACL includes the Branch is EEE data condition.

6.5 ACL SCRIPT

The Read ACL uses a script to check the user's role and provide or deny access.

```
(function () {  
    if (gs.hasRole('admin')) {  
        return true;  
    }  
    if (gs.hasRole('bb1')){  
        return true;  
    }  
    return false;  
})();
```

6.6 VERIFICATION

The ACL implementation is verified using different users and roles.

The verification includes:

A user with bb1 role can view the required EEE branch records.

A user without the required role cannot view the records.

An administrator can view all records.

Users with the required roles can perform the configured Create, Write, and Delete operations.

6.7 PROJECT OUTCOME

The project demonstrates how script-controlled READ, CREATE, WRITE, and DELETE ACLs can be used to enforce record-level security in ServiceNow.

It also demonstrates how user roles and record field values can be evaluated to control access to 1records.

6.8 DOCUMENTATION REFERENCES

The project documentation contains:

Project overview

Requirements

System design

Development steps

ACL configurations

ACL script

Verification results

Warning: A role, security attribute, data condition, script or ACL control via reference fields is required to properly secure access with this ACL.

* Type: record

* Operation: write

Decision Type: Allow If

Admin overrides: ☒

Protection policy: None

* Name: Institution Details [u_institution_details]

Description: View results in new tab

Applies To: No. of records matching the condition: 3 @

Add Filter Condition Add OR Clause

-- choose field -- -- oper -- -- value --

Conditions

Access Control Rules have two decision types, and these types will behave differently depending on conditions.

1. Allow Access: Allows access to a resource if all conditions are met. Additional ACLs may grant access to records where this ACL has not granted access.

2. Deny Access: Denies access to a resource unless all conditions are met. Additional ACLs may not grant access to records where this ACL has denied access.

Warning: A role, security attribute, data condition, script or ACL control via reference fields is required to properly secure access with this ACL.

* Type: record

* Operation: delete

Decision Type: execute

Admin overrides: conditional_table_query_range

Protection policy: query_range

* Name: read

Description: write

Applies To: (empty)

Conditions

Access Control Rules have two decision types, and these types will behave differently depending on conditions.

1. Allow Access: Allows access to a resource if all conditions are met. Additional ACLs may grant access to records where this ACL has not granted access.

2. Deny Access: Denies access to a resource unless all conditions are met. Additional ACLs may not grant access to records where this ACL has denied access.

(15) WhatsAppSkillWalletServiceNow DevelopersNew Record | Access Control |Ask Gemini

dev230428.service-now.com/now/nav/ui/classic/params/target/sys_security_acl.do%3Fsys_id%3D1%26sys_is_list%3Dtrue%26sys_target%3Dsys_security_acl%26sysparm_checked_items%3D%2...

servicenowAllFavoritesHistoryWorkspacesAccess Control - New RecordSearch

Access ControlNew recordSubmit

Warning: A role, security attribute, data condition, script or ACL control via reference fields is required to properly secure access with this ACL.

* Type: record ⓘ

* Operation: read ⓘ

Decision Type: Allow If

Application: Global ⓘ

Active: ☒

Advanced: ☐

Admin overrides: ☒

Protection policy: -- None --

* Name: * -- None --

Description:

Applies To: Not a valid table name ⓘ
Add Filter ConditionAdd OR Clause

Conditions

Access Control Rules have two decision types, and these types will behave differently depending on conditions.
1. Allow Access: Allows access to a resource if all conditions are met. Additional ACLs may grant access to records where this ACL has not granted access.
2. Deny Access: Denies access to a resource unless all conditions are met. Additional ACLs may not grant access to records where this ACL has denied access.
[More Info](#)

31°C Mostly cloudy

Search

ENG US

14:18 24-09-2026