

```
R2>en
R2#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R2(config)#ip access-list standard R2NAT
R2(config-std-nacl)#permit 192.168.10.0 0.0.0.255
R2(config-std-nacl)#permit 192.168.10.0 0.0.0.255
R2(config-std-nacl)#
R2(config-std-nacl)#
R2(config-std-nacl)#permit 192.168.20.0 0.0.0.255
R2(config-std-nacl)#permit 192.168.30.0 0.0.0.255
R2(config-std-nacl)#exit
R2(config)#ip nat pool R2POOL 209.165.202.129 209.165.202.129 netmask 255.255.255.252
R2(config)#ip nat inside source list R2NAT pool R2POOL overload
R2(config)#int s0/1/0
R2(config-if)#ip nat outside
R2(config-if)#exit
R2(config)#int fa0/0
R2(config-if)#ip nat inside
R2(config-if)#exit
R2(config)#int se0/0/0
R2(config-if)#ip nat inside
R2(config-if)#exit
R2(config)#int se0/0/1
R2(config-if)#ip nat inside
R2(config-if)#exit
R2(config)#ip nat inside source static 192.168.20.254 209.165.202.130
R2(config)#exit
R2#
%SYS-5-CONFIG_I: Configured from console by console
```