

Program:

```
#define N 4
#include <stdbool.h>
#include <stdio.h>

void printSolution(int board[N][N])
{
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++)
            printf(" %d ", board[i][j]);
        printf("\n");
    }
}

bool isSafe(int board[N][N], int row, int col)
{
    int i, j;
    for (i = 0; i < col; i++)
        if (board[row][i])
            return false;
    for (i = row, j = col; i >= 0 && j >= 0; i--, j--)
        if (board[i][j])
            return false;
    for (i = row, j = col; j >= 0 && i < N; i++, j--)
        if (board[i][j])
            return false;

    return true;
}
```

```

}
bool solveNQUtil(int board[N][N], int col)
{
    if (col >= N)
        return true;
    for (int i = 0; i < N; i++) {

        if (isSafe(board, i, col)) {
            board[i][col] = 1;
            if (solveNQUtil(board, col + 1))
                return true;
            board[i][col] = 0; // BACKTRACK
        }
    }
    return false;
}

bool solveNQ()
{
    int board[N][N] = { { 0, 0, 0, 0 },
                        { 0, 0, 0, 0 },
                        { 0, 0, 0, 0 },
                        { 0, 0, 0, 0 } };

    if (solveNQUtil(board, 0) == false) {
        printf("Solution does not exist");
        return false;
    }

    printSolution(board);
    return true;
}

int main()

```

```
{  
    solveNQ();  
    return 0;  
}
```

Output:

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL JUPYTER

PS D:\5th-Sem-Practicals\DAA\Pract 5> gcc prog.c

PS D:\5th-Sem-Practicals\DAA\Pract 5> ./a.exe

0 0 1 0

1 0 0 0

0 0 0 1

0 1 0 0

PS D:\5th-Sem-Practicals\DAA\Pract 5> □