TECHNICAL SERVICE GUIDE

NxtGen Security Services Catalog

Cloud and endpoint protection for modern enterprise operations

A practical guide to what each service does, where it fits, and how to select it.

CONNECT | PROTECT | RUN | GOVERN

This guide translates the supplied August 2026 catalog into technical language for discovery, architecture, and solution-design conversations.

Prepared from the supplied NxtGen Security Services Catalog. Exact coverage, capacity, integrations, response times, retention, prerequisites, and commercials remain solution-specific.

01 | READ THE CATALOG CORRECTLY

Security is a system of controls, not one product

The catalog divides protection into two zones: cloud security for NxtGen-hosted customers and endpoint security for users, devices, remote servers, email, and data. Use the zones to locate the control, then validate the operating boundary.

Two protection zones

Zone	Primary question	Service families
Cloud security	How do we protect hosted workloads from the network edge through applications, data, recovery, and monitoring?	Connect, Protect, Run, Govern
Endpoint security	How do we protect users, remote servers, business data, email, and the human attack surface?	Protect, Run, Govern

The operating journey

- Connect establishes protected reachability and traffic distribution.
- Protect applies access, network, application, identity, data, and detection controls.
- Run keeps workloads recoverable through backup and disaster-recovery services.
- Govern centralizes telemetry, automates approved actions, detects integrity changes, and validates readiness.

Source boundary: the catalog is a service menu. It names the service intent, but the final proposal should confirm supported assets, coverage, capacity, retention, integration, response expectations, responsibilities, and commercials.

02 | CLOUD SECURITY

Connect: protect the cloud edge and distribute demand

Internet-facing workloads usually need two different controls: one to reduce the impact of volumetric disruption and another to distribute legitimate application traffic across available resources.

01 DDoS-Protected Internet Port
What it does: Provides internet connectivity with protection designed to mitigate distributed-denial-of-service traffic before it disrupts hosted services.
Example: A public customer portal is targeted by a traffic flood. The protected edge absorbs or filters disruptive traffic so legitimate requests can continue to reach the service.
Confirm: Internet-port capacity, traffic profile, mitigation behavior, escalation path, protected IPs, and service-level expectations.

02 Load Balancer 1G
What it does: Distributes incoming application traffic across available resources, with a 1G service capacity stated in the catalog.
Example: Two web servers run behind a virtual service address. New connections are distributed between them so one server is not the single point of traffic concentration.
Confirm: Application protocol, TLS termination, health checks, persistence, maximum throughput, backend topology, and failover behavior.

Do not conflate the controls

- DDoS protection focuses on availability against hostile or abnormal volume at the internet edge.
- Load balancing focuses on distributing legitimate traffic and detecting unhealthy backends.
- A public application may need both, plus WAF and firewall controls for deeper inspection.

Selection example: for a customer-facing API, begin with protected internet ingress, add load balancing when there are multiple application instances, then validate whether WAF, firewall policy, and monitoring are also required.

03 | CLOUD SECURITY

Protect: control access, networks, and web requests

The catalog separates remote access, network traffic policy, and application-layer filtering. They are complementary controls at different layers of the path.

03 VPN + MFA + MAC Binding
What it does: Combines encrypted VPN connectivity, multi-factor authentication, and device MAC binding for remote access.
Example: An administrator connects from an approved laptop, completes MFA, and reaches a management subnet through an encrypted tunnel.
Confirm: Identity provider, device-binding behavior, supported clients, split tunneling, user groups, and break-glass access.

04 Firewall
What it does: Applies policy-based inspection and control to traffic entering, leaving, or moving across the hosted environment.
Example: Only HTTPS from approved networks can reach an application tier; database ports are allowed only from the application subnet.
Confirm: Zones, rules, NAT, logging, change workflow, rule ownership, and east-west versus north-south coverage.

05 Web Application Firewall (WAF)
What it does: Filters application-layer requests and helps protect web applications from malicious requests and common web attacks.
Example: A WAF inspects a login or API request and blocks a pattern that violates the approved application security policy.
Confirm: Protected domains, TLS handling, rule mode, tuning process, API coverage, false-positive handling, and logging destination.

Layered-control example

A remote engineer first authenticates through VPN plus MFA, the firewall permits only the intended network path, and the WAF evaluates requests once they reach the web application. Each control has a different failure mode and evidence source.

Useful metrics

- VPN: successful versus failed MFA, device-binding exceptions, session duration, and privileged access review.
- Firewall: rule hit counts, denied traffic, stale rules, and time to approve or remove a rule.
- WAF: blocked requests, false-positive rate, top attack patterns, and protected application coverage.

04 | CLOUD SECURITY

Protect keys, databases, and privileged actions

These services reduce risk around cryptographic material, sensitive data stores, and high-impact administrative sessions. They should be designed together with identity, application ownership, and audit requirements.

Service	Technical role	Example and selection focus
06 KMS + HSM Partition	Centralized key management supported by a logically separated HSM partition for cryptographic operations.	Use for encryption-key lifecycle and controlled cryptographic operations. Confirm key ownership, rotation, backup, access roles, and application integration.
07 Dedicated HSM	A dedicated hardware security module for customers requiring isolated cryptographic processing and key protection.	Use when the isolation boundary or throughput requirement cannot be met by a shared logical partition. Confirm tenancy, operational ownership, performance, and HA design.
08 Database Activity Monitoring (DAM)	Monitors database access and activity to surface policy exceptions, suspicious behavior, and sensitive operations.	Use to investigate unusual reads or privileged queries. Confirm database engines, agents or connectors, query visibility, retention, and alert workflow.
09 Privileged Access Management (PAM)	Controls and monitors elevated access to critical systems and high-risk administrative sessions.	Use for break-glass or administrator access to a production database. Confirm vaulting, approval, session recording, credential rotation, and emergency access.

Logical partition versus dedicated HSM

- A KMS plus HSM partition provides centralized management with logical separation inside an HSM service.
- A dedicated HSM is a stronger physical or tenancy-isolation choice for customers with specific cryptographic or assurance requirements.
- Neither service replaces access governance: define who can use keys, which applications may call them, and how operations are audited.

Design example: encrypt a database with customer-controlled keys, restrict key administration through PAM, monitor database activity with DAM, and send relevant events to SIEM for investigation.

05 | CLOUD SECURITY

XDR: connect signals into an investigation workflow

SpeedCloud Protect - XDR is presented as a way to bring detection context together across protected assets. It is a workflow for understanding and responding to signals, not a substitute for every underlying control.

Step	What happens	Example evidence
Collect	Bring relevant security signals into a common detection context.	Endpoint alert, firewall deny, identity event, or suspicious process telemetry.
Correlate	Connect related observations so investigators are not forced to review isolated alerts.	A new admin login, unusual endpoint process, and outbound connection linked to one incident.
Investigate	Use consolidated context to understand scope, priority, and likely impact.	Determine affected user, device, workload, timeline, and whether privileged access was involved.
Respond	Support coordinated action according to the approved operating model.	Isolate an endpoint, disable a session, block an indicator, or escalate for human approval.

How to use XDR in architecture

- Define which data sources are in scope and how quickly signals become available.
- Define who investigates, who approves disruptive action, and which actions may be automated.
- Measure time to triage, time to contain, investigation completeness, and recurring false positives.
- Keep the evidence trail: incident ID, affected assets, decisions, actions, and recovery outcome.

Example: an administrator's credentials are used from an unusual device. XDR correlates the identity event with endpoint behavior and firewall activity, giving the responder one incident context instead of three separate alerts.

06 | CLOUD SECURITY

Run: make workloads recoverable

Backup and disaster recovery address different failure outcomes. Backup preserves recoverable data; disaster recovery provides a planned way to restore application service and dependencies.

11 Managed Backup
What it does: Provides policy-driven backup operations for selected NxtGen-hosted workloads within the agreed protection scope.
Example: A database is backed up daily with a retention policy and a tested restore procedure.
Confirm: Workload coverage, frequency, retention, encryption, storage location, restore permissions, and restore-test cadence.

12 Managed Disaster Recovery
What it does: Provides a managed recovery capability for selected applications and workloads around an agreed recovery architecture.
Example: After a site or infrastructure failure, application servers, data services, network dependencies, and access paths are recovered in a defined order.
Confirm: RPO, RTO, dependencies, recovery sequence, failover and failback, target capacity, testing, and customer responsibilities.

Backup versus DR

Question	Backup	Disaster recovery
Primary purpose	Recover data or a workload state.	Restore a usable service and its dependencies.
Typical decision	How much data can we lose and how far back can we restore?	How quickly must the service return, and where does it run during recovery?
Evidence	Successful backup jobs and restore tests.	Exercise results, achieved RPO/RTO, runbook quality, and dependency readiness.

Design example: a revenue application may use frequent managed backups for data recovery and a DR design for a full service outage. A backup that has never been restored is an assumption; a DR plan that has never been exercised is an unvalidated dependency chain.

07 | CLOUD SECURITY

Govern: monitor, automate, and detect integrity changes

The catalog presents SIEM as the core monitoring capability, with SOAR and FIM as add-ons. The architecture should make the relationship explicit: collect and analyze, then automate approved actions or watch critical changes.

Service	What it adds	Example use
13 SIEM	Centralizes relevant logs and security events to support monitoring, investigation, and reporting.	Search firewall, identity, workload, and security events together during an incident or audit.
14 SOAR Add-on	Orchestrates security tools and automates approved response workflows.	When a high-confidence indicator appears, create a case, enrich it, request approval, and execute a defined containment action.
15 FIM Add-on	Detects changes to selected critical files and configurations.	Alert when a production configuration, system binary, or security policy file changes outside the approved change window.

A practical control loop

- SIEM answers: what happened across the environment, and what evidence supports the conclusion?
- SOAR answers: which approved steps can be coordinated or automated after the signal is trusted?
- FIM answers: did a critical file or configuration change, and was the change expected?

Example: FIM detects an unexpected change to a web-server configuration, SIEM correlates the change with a privileged login and outbound connection, and SOAR opens the incident workflow with enrichment and an approval gate before containment.

08 | CLOUD SECURITY

Assurance: test exposure and recovery readiness

Assurance services validate different things. Vulnerability assessment and penetration testing examine security weaknesses, application testing focuses on web and mobile behavior, and a DR drill exercises recovery coordination.

Service	What it tests	When to use it
16 VA/PT - External & Internal	Agreed external and internal assets within an approved vulnerability-assessment and penetration-testing scope.	Before major release, after architecture change, or as a recurring control for exposed and internal infrastructure.
17 AppSec Testing - Comprehensive	Comprehensive web- and mobile-application penetration testing, described as WAPT/MAPT in the catalog.	Before production launch or after material application, API, authentication, or mobile-client changes.
18 DR Drill	A planned exercise of agreed recovery procedures, coordination, and readiness.	Validate runbooks, dependencies, people, access, communications, and achieved recovery objectives.

Pre-test authorization checklist

- Written authorization, asset ownership, target scope, test windows, rate limits, exclusions, and emergency contacts.
- Application accounts, test data handling, production-versus-nonproduction boundaries, and reporting format.
- For DR drills: success criteria, failover sequence, communication plan, observer roles, and rollback or failback steps.

Example: run external and internal VA/PT for infrastructure, comprehensive AppSec testing for the customer portal and mobile app, then use a DR drill to prove that the application can be recovered with its data and dependencies.

09 | ENDPOINT SECURITY

Protect critical users and remote servers

Endpoint offers extend protection beyond hosted infrastructure. The catalog distinguishes a combined critical-user offer from remote-server protection and separates additional protection storage from the base service.

01 Critical User Protection (CUP)
What it does: Combines XDR and endpoint backup for critical users; backup storage is charged separately.
Example: Protect a finance approver's laptop with endpoint detection and response context plus recoverable endpoint data.
Confirm: Which users are critical, endpoint operating systems, XDR telemetry, backup data scope, retention, and storage sizing.

02 Remote Server Protection
What it does: Provides security and recovery coverage for selected remote-server workloads within the agreed protection scope.
Example: Protect a branch or remote-site server that is outside the primary hosted environment but still supports a business process.
Confirm: Server inventory, agents, operating systems, network reachability, application dependencies, recovery expectations, and support ownership.

Add-on Additional Protection Storage
What it does: Provides additional capacity only with Remote Server Protection; quantity and commercial unit are confirmed in the proposal.
Example: A remote server accumulates more protected data than the base entitlement. Add storage capacity instead of weakening retention or coverage without approval.
Confirm: Capacity, growth rate, retention, backup frequency, tiering, restore demand, and unit of measure.

Selection rule

- Use CUP when the object of protection is a critical human user and the service must combine endpoint detection with backup.
- Use Remote Server Protection when the object is a remote server or workload with its own recovery boundary.
- Treat additional storage as a capacity decision; it does not replace security policy, monitoring, or restore testing.

10 | ENDPOINT SECURITY

Run: extend data resilience beyond hosted workloads

Archive, Microsoft 365 backup, and endpoint backup protect different data sources. Define the source, ownership, retention, restore path, and expected recovery experience for each one.

Service	Data source and role	Example planning question
03 Backup Archive Storage	Archive capacity for backup data that must be retained according to the protection design.	Which backup sets move to archive, how long are they retained, and how quickly must they be retrieved?
04 Microsoft 365 Backup	Independent backup for supported Microsoft 365 data within the selected service scope.	Which mailboxes, SharePoint, OneDrive, Teams, or other supported data must be recoverable independently?
05 Endpoint Backup	Backup protection for selected user-endpoint data according to device and data coverage.	Which folders or data classes are protected, how is a device replaced, and how is a user restored?

Minimum protection-design fields

- Data source and owner: hosted workload, SaaS tenant, endpoint, or archive tier.
- Capacity and growth: current size, daily change rate, and expected retention horizon.
- Recovery: restore granularity, target location, access approval, expected time, and evidence of testing.
- Compliance: retention lock, legal hold, residency, encryption, and deletion requirements where applicable.

Example: a user may need Microsoft 365 backup for mailbox and collaboration data, endpoint backup for local working files, and archive storage for long-retained backup sets. One service should not be assumed to cover the others.

11 | ENDPOINT SECURITY

Govern the human attack surface

Email Security, DLP, Dark Web Monitoring, and Phishing Simulation address different parts of the threat path. Combine them when the risk is a user receiving, handling, or exposing sensitive information.

Service	Technical role	Example use
06 Email Security	Inspects email traffic and helps block malicious or unwanted messages according to policy and scope.	Filter a suspicious attachment or message before it reaches a user's mailbox.
07 Data Leak Prevention (DLP)	Monitors selected data movement and applies policies designed to reduce unauthorized disclosure.	Alert or block a user from sending a sensitive document to an unapproved external destination.
08 Dark Web Monitoring (DWM)	Monitors agreed dark-web sources for organization-linked risk indicators.	Identify an exposed corporate credential or brand-linked indicator so the organization can investigate and rotate access.
09 Phishing Simulation	Runs controlled phishing simulations to assess user behavior and support targeted awareness improvement.	Measure reporting behavior, identify teams needing coaching, and repeat the exercise to track improvement.

Important distinction

- Email Security is an operational protection service applied to real email traffic.
- Phishing Simulation is a controlled assessment activity; it should be authorized, communicated appropriately, and measured without exposing real credentials.
- DLP requires precise data classification and policy tuning to balance protection with business usability.
- DWM creates external-risk visibility; it does not by itself remediate an exposed credential or indicator.

Example: protect inbound mail with Email Security, reduce unauthorized outbound disclosure with DLP, use DWM to find exposed organization-linked indicators, and run phishing simulations to test whether users report suspicious messages.

12 | ARCHITECTURE PATTERNS

Choose a combination by asset, threat, and outcome

The fastest way to select services is to start with what must be protected, how it can fail, and what evidence or recovery outcome the business expects.

Scenario	Recommended starting combination	Why
Public web application	DDoS-Protected Internet Port + Load Balancer 1G + Firewall + WAF + SIEM	Protect edge availability, distribute traffic, enforce network policy, filter application requests, and retain investigation evidence.
Privileged admin access	VPN + MFA + MAC Binding + PAM + SIEM	Authenticate and bind the device, govern elevated sessions, and centralize evidence.
Sensitive database	KMS + HSM Partition or Dedicated HSM + DAM + PAM + Backup	Protect keys, monitor database activity, control administration, and preserve recoverability.
Critical application outage	Managed Backup + Managed Disaster Recovery + DR Drill + SIEM	Recover data, restore service architecture, exercise the runbook, and monitor the operational picture.
Human-layer risk	Email Security + DLP + Phishing Simulation + DWM + Endpoint Backup	Reduce malicious email exposure, control data movement, measure behavior, monitor external exposure, and recover endpoint data.

Use the patterns as starting points, not automatic bundles. The right combination depends on architecture, threat model, user population, data classification, recovery objectives, and the operating model.

13 | SOLUTION DESIGN

Assess, design, confirm, activate

The catalog closes with a four-step motion. Use it as a working checklist in discovery and proposal reviews.

Step	Technical work	Evidence to capture
01 Assess	Identify assets, exposure, users, data, recovery needs, and operating constraints.	Asset inventory, data flows, internet exposure, identity sources, dependencies, RPO/RTO, and regulatory constraints.
02 Design	Select relevant Connect, Protect, Run, and Govern services and define the control boundaries.	Architecture diagram, control map, data-source list, responsibility matrix, and target metrics.
03 Confirm	Agree scope, prerequisites, capacity, integrations, testing, service responsibilities, and commercials.	Approved proposal, assumptions, exclusions, acceptance criteria, and implementation plan.
04 Activate	Onboard services, configure policies, integrate telemetry, test recovery, and hand over operating procedures.	Configuration baseline, test results, runbooks, escalation contacts, and ongoing review cadence.

Questions to take into a technical workshop

- What assets, users, applications, and data are in scope, and which are explicitly out of scope?
- What is the threat or failure scenario, and what outcome must the control deliver?
- What must be automated, what requires approval, and who owns the response?
- What is the required availability, RPO, RTO, retention, and evidence of successful testing?
- What integrations, agents, credentials, network paths, quotas, or change windows are prerequisites?
- What is measured after go-live: coverage, alert quality, time to detect, time to contain, restore success, or user behavior?

Final takeaway: select security services as a coherent operating system for the workload. Connect the environment, protect the access and data paths, keep it recoverable, and govern the evidence and response loop.

Source note: this guide is an explanatory interpretation of the supplied NxtGen Security Services Catalog (August 2026). Product names, service descriptions, capacity references, and company statements remain subject to the source document and final confirmation with NxtGen.