

Problem statement

predicting the house price in USA.To create a model to help him estimate of what the house would sell for.

```
In [1]: import numpy as np  
import pandas as pd  
import matplotlib.pyplot as plt  
import seaborn as sns
```

```
In [2]: df=pd.read_csv("uber")
```

To display top 10 rows

```
In [3]: df.head(10)
```

```
Out[3]:
```

	Unnamed: 0	key	fare_amount	pickup_datetime	pickup_longitude	pickup_latitude	dropoff_longitude	dropoff_latitude	p
0	24238194	2015-05-07 19:52:06.0000003	7.5	2015-05-07 19:52:06 UTC	-73.999817	40.738354	-73.999512	40.723217	
1	27835199	2009-07-17 20:04:56.0000002	7.7	2009-07-17 20:04:56 UTC	-73.994355	40.728225	-73.994710	40.750325	
2	44984355	2009-08-24 21:45:00.00000061	12.9	2009-08-24 21:45:00 UTC	-74.005043	40.740770	-73.962565	40.772647	
3	25894730	2009-06-26 08:22:21.0000001	5.3	2009-06-26 08:22:21 UTC	-73.976124	40.790844	-73.965316	40.803349	
4	17610152	2014-08-28 17:47:00.000000188	16.0	2014-08-28 17:47:00 UTC	-73.925023	40.744085	-73.973082	40.761247	
5	44470845	2011-02-12 02:27:09.0000006	4.9	2011-02-12 02:27:09 UTC	-73.969019	40.755910	-73.969019	40.755910	
6	48725865	2014-10-12 07:04:00.0000002	24.5	2014-10-12 07:04:00 UTC	-73.961447	40.693965	-73.871195	40.774297	
7	44195482	2012-12-11 13:52:00.00000029	2.5	2012-12-11 13:52:00 UTC	0.000000	0.000000	0.000000	0.000000	
8	15822268	2012-02-17 09:32:00.00000043	9.7	2012-02-17 09:32:00 UTC	-73.975187	40.745767	-74.002720	40.743537	
9	50611056	2012-03-29 19:06:00.000000273	12.5	2012-03-29 19:06:00 UTC	-74.001065	40.741787	-73.963040	40.775012	

Data Cleaning And Pre-Processing

```
In [4]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200000 entries, 0 to 199999
Data columns (total 9 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Unnamed: 0            200000 non-null  int64
1   key                   200000 non-null  object
2   fare_amount           200000 non-null  float64
3   pickup_datetime      200000 non-null  object
4   pickup_longitude      200000 non-null  float64
5   pickup_latitude       200000 non-null  float64
6   dropoff_longitude     199999 non-null  float64
7   dropoff_latitude      199999 non-null  float64
8   passenger_count       200000 non-null  int64
dtypes: float64(5), int64(2), object(2)
memory usage: 13.7+ MB
```

```
In [5]: # Display the statistical summary
df.describe()
```

Out[5]:

	Unnamed: 0	fare_amount	pickup_longitude	pickup_latitude	dropoff_longitude	dropoff_latitude	passenger_count
count	2.000000e+05	200000.000000	200000.000000	200000.000000	199999.000000	199999.000000	200000.000000
mean	2.771250e+07	11.359955	-72.527638	39.935885	-72.525292	39.923890	1.684535
std	1.601382e+07	9.901776	11.437787	7.720539	13.117408	6.794829	1.385997
min	1.000000e+00	-52.000000	-1340.648410	-74.015515	-3356.666300	-881.985513	0.000000
25%	1.382535e+07	6.000000	-73.992065	40.734796	-73.991407	40.733823	1.000000
50%	2.774550e+07	8.500000	-73.981823	40.752592	-73.980093	40.753042	1.000000
75%	4.155530e+07	12.500000	-73.967154	40.767158	-73.963658	40.768001	2.000000
max	5.542357e+07	499.000000	57.418457	1644.421482	1153.572603	872.697628	208.000000

```
In [6]: # To display the col headings
df.columns
```

```
Out[6]: Index(['Unnamed: 0', 'key', 'fare_amount', 'pickup_datetime',
              'pickup_longitude', 'pickup_latitude', 'dropoff_longitude',
              'dropoff_latitude', 'passenger_count'],
              dtype='object')
```

```
In [7]: cols=df.dropna()
cols
```

```
Out[7]:
```

	Unnamed: 0	key	fare_amount	pickup_datetime	pickup_longitude	pickup_latitude	dropoff_longitude	dropoff_latitu
0	24238194	2015-05-07 19:52:06.0000003	7.5	2015-05-07 19:52:06 UTC	-73.999817	40.738354	-73.999512	40.7232
1	27835199	2009-07-17 20:04:56.0000002	7.7	2009-07-17 20:04:56 UTC	-73.994355	40.728225	-73.994710	40.7503
2	44984355	2009-08-24 21:45:00.00000061	12.9	2009-08-24 21:45:00 UTC	-74.005043	40.740770	-73.962565	40.7726
3	25894730	2009-06-26 08:22:21.0000001	5.3	2009-06-26 08:22:21 UTC	-73.976124	40.790844	-73.965316	40.8033
4	17610152	2014-08-28 17:47:00.000000188	16.0	2014-08-28 17:47:00 UTC	-73.925023	40.744085	-73.973082	40.7612
...
199995	42598914	2012-10-28 10:49:00.00000053	3.0	2012-10-28 10:49:00 UTC	-73.987042	40.739367	-73.986525	40.7402
199996	16382965	2014-03-14 01:09:00.0000008	7.5	2014-03-14 01:09:00 UTC	-73.984722	40.736837	-74.006672	40.7396
199997	27804658	2009-06-29 00:42:00.00000078	30.9	2009-06-29 00:42:00 UTC	-73.986017	40.756487	-73.858957	40.6925
199998	20259894	2015-05-20 14:56:25.0000004	14.5	2015-05-20 14:56:25 UTC	-73.997124	40.725452	-73.983215	40.6954
199999	11951496	2010-05-15 04:08:00.00000076	14.1	2010-05-15 04:08:00 UTC	-73.984395	40.720077	-73.985508	40.7687

199999 rows × 9 columns




```
In [8]: cols.columns  
cols1=cols[['pickup_longitude', 'pickup_latitude', 'dropoff_longitude']]
```


EDA and Visualization

```
In [9]: d=df.head(200)
```

```
In [10]: sns.pairplot(d)
```

```
Out[10]: <seaborn.axisgrid.PairGrid at 0x25e51234b50>
```







```
In [11]: # We use displot in older version we get distplot use displot
sns.distplot(d['pickup_longitude'])
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).
warnings.warn(msg, FutureWarning)

```
Out[11]: <AxesSubplot:xlabel='pickup_longitude', ylabel='Density'>
```



```
In [12]: df1=df[['pickup_longitude', 'pickup_latitude', 'passenger_count']]
df1
```


Out[12]:

	pickup_longitude	pickup_latitude	passenger_count
0	-73.999817	40.738354	1
1	-73.994355	40.728225	1
2	-74.005043	40.740770	1
3	-73.976124	40.790844	3
4	-73.925023	40.744085	5
...
199995	-73.987042	40.739367	1
199996	-73.984722	40.736837	1
199997	-73.986017	40.756487	2
199998	-73.997124	40.725452	1
199999	-73.984395	40.720077	1

200000 rows × 3 columns

```
In [13]: sns.heatmap(df1.corr())
```

```
Out[13]: <AxesSubplot:>
```



To train the model - MODEL BUILD

Going to train linear regression model; We split our data into 2 variables x and y where x is independent var(input) and y is dependent on x(output), we could ignore address col as it is not required for our model

```
In [14]: x=df1[['pickup_longitude', 'pickup_latitude', 'passenger_count']]  
y=df1[['pickup_latitude']]
```

To split the dataset into test data

```
In [15]: # importing lib for splitting test data  
from sklearn.model_selection import train_test_split
```

```
In [16]: x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.3)
```

```
In [17]: from sklearn.linear_model import LinearRegression
```

```
lr=LinearRegression()  
lr.fit(x_train,y_train)
```

```
Out[17]: LinearRegression()
```

```
In [18]: print(lr.intercept_)
```

```
[-2.13162821e-14]
```

```
In [19]: print(lr.score(x_test,y_test))
```

```
1.0
```


```
In [20]: coeff=pd.DataFrame(lr.coef_)  
coeff
```

```
Out[20]:
```

	0	1	2
0	-4.012190e-15	1.0	1.959285e-17

```
In [21]: pred = lr.predict(x_test)  
plt.scatter(y_test,pred)
```

```
Out[21]: <matplotlib.collections.PathCollection at 0x25e6a479670>
```



In []: