

Challenge 7

Pre/Post Increment and Decrement



<pre>#include <stdio.h> int main() { int a = 5; printf("%d\n", a++); printf("%d\n", a); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 5; printf("%d\n", ++a); printf("%d\n", a); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 10; printf("%d\n", a--); printf("%d\n", a); return 0; }</pre>
<pre>#include <stdio.h> int main() { int a = 5; int b = a++ + ++a; //Undefined behaviour printf("a=%d\n", a); printf("b=%d\n", b); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 5; int b = ++a + ++a; //Undefined behaviour printf("a=%d\n", a); printf("b=%d\n", b); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 5; printf("a=%d\n", ++a + ++a); //Undefined behaviour return 0; }</pre>
<pre>#include <stdio.h> int main() { int a = 5; int b=7; b = ++a + b++; //Undefined behaviour printf("a=%d\n", a); printf("a=%d\n", b); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 5; int b = 10; int c = a++ + ++b; printf("a= %d\n",a); printf("b= %d\n",b); printf("c=%d\n", c); return 0; }</pre>	<pre>#include <stdio.h> int main() { int a = 5; int b = ++a + 10; printf("a=%d\n", a); printf("b=%d\n", b); return 0; }</pre>
<pre>#include <stdio.h> int main() {</pre>	<pre>#include <stdio.h> int main() {</pre>	<pre>#include <stdio.h> int main() {</pre>

<pre> int a = 5; int b = a++ * 2; printf("a = %d\n", a); printf("b = %d\n", b); return 0; } </pre>	<pre> int a = 5; int b = ++a * 2; printf("a = %d\n", a); printf("b = %d\n", b); return 0; } </pre>	<pre> int a = 5; a++; ++a; a--; printf("%d", a); return 0; } </pre>
<pre> #include <stdio.h> int main() { int a = 5; int b = a++; b++; printf("a = %d\n", a); printf("b = %d\n", b); return 0; } </pre>	<pre> #include <stdio.h> int main() { int a = 5; printf("%d ", a++); printf("%d ", ++a); printf("%d ", a--); printf("%d", --a); return 0; } </pre>	<pre> #include <stdio.h> int main() { int a = 10; int b = a++ - --a; printf("a = %d\n", a); printf("b = %d\n", b); return 0; } </pre>

GATE Questions



<pre> #include <stdio.h> int main() { int m = 10; int n, n1; n = ++m; n1 = m++; } </pre>	<pre> #include <stdio.h> int main() { int a = 2; int b, c; b = 2 * (a++); c = 2 * (++a); } </pre>	<pre> #include <stdio.h> int main() { int i = 0, count = 0; for (int j = -3; j <= 3; j++) { } </pre>
--	---	---

<pre> n--; --n1; n -= n1; printf("%d", n); return 0; } </pre>	<pre> printf("b = %d\n", b); printf("c = %d\n", c); return 0; } </pre>	<pre> if ((j >= 0) && (i++)) count += j; } count += i; printf("%d", count); return 0; } </pre>
--	---	--

More Questions



<pre> #include <stdio.h> int main() { int i = 0; if (1 i++) printf("A"); printf(" %d", i); return 0; } </pre>	<pre> #include <stdio.h> int main() { int i = 0; if (0 i++) printf("A"); printf(" %d", i); return 0; } </pre>	<pre> #include <stdio.h> int main() { int i = 0; if (1 && ++i) printf("A"); printf(" %d", i); return 0; } </pre>
--	--	--



```
#include <stdio.h>
```

```
int main()
{
    int i = 0;

    if (0 && ++i)
        printf("A");

    printf(" %d", i);

    return 0;
}
```

```
#include <stdio.h>
```

```
int main()
{
    int i = 0;
    int count = 0;

    for (int j = 0; j < 5; j++)
    {
        if (j % 2 == 0 && i++)
            count++;
    }

    printf("%d %d", i, count);

    return 0;
}
```

```
#include <stdio.h>
```

```
int main()
{
    int i = 0;
    int count = 0;

    for (int j = 0; j < 5; j++)
    {
        if (j % 2 != 0 || i++)
            count++;
    }
}
```

```
printf("%d %d", i, count);

return 0;
}
```

```
#include <stdio.h>

int main()
{
    int i = 0;
    int sum = 0;

    for (int j = 1; j <= 5; j++)
    {
        if (j < 3 && ++i)
            sum += j;
    }

    printf("%d %d", i, sum);

    return 0;
}
```

```
#include <stdio.h>

int main()
{
    int i = 0;
    int count = 0;

    for (int j = 1; j <= 5; j++)
    {
        if ((j < 3) || (i++))
            count++;
    }

    printf("%d %d", i, count);

    return 0;
}
```

```
#include <stdio.h>

int main()
{
    int a = 5;
    int b = 0;

    if (a++ > 5)
```

```
        b++;

        if (++a > 6)
            b++;

        printf("%d %d", a, b);

        return 0;
}
```

```
#include <stdio.h>

int main()
{
    int a = 5;
    int b = 0;

    if (a++ == 5 || ++a == 7)
        b++;

    printf("%d %d", a, b);

    return 0;
}
```



```
#include <stdio.h>

int main()
{
    int i = 0;
    int count = 0;

    for (int j = 0; j < 5; j++)
    {
```

```
        if ((j % 2 == 0 && i++) || (++i > 3))
            count++;
    }

    printf("%d %d", i, count);

    return 0;
}
```

```
#include <stdio.h>

int main()
{
    int i = 0;
    int count = 0;

    for (int j = 1; j <= 6; j++)
    {
        if ((j % 2 && i++) || (j % 3 == 0 && ++i))
            count++;
    }
    printf("%d %d", i, count);
    return 0;
}
```

```
#include <stdio.h>
int main()
{
    int i = 0;
    int count = 0;
    for (int j = 0; j < 5; j++)
    {
        if ((j % 2 == 0 && i++) && (++i > 3))
            count++;
    }
    printf("%d %d", i, count);
    return 0;
}
```