

Integration Manual

for S32K3 MEM_EEP Driver

Document Number: IM34MEM_EEP ASRR21-11 Rev0000R3.0.0 Rev. 1.0

1 Revision History	2
2 Introduction	3
2.1 Supported Derivatives	3
2.2 Overview	4
2.3 About This Manual	5
2.4 Acronyms and Definitions	6
2.5 Reference List	6
3 Building the driver	7
3.1 Build Options	7
3.1.1 GCC Compiler/Assembler/Linker Options	8
3.1.2 DIAB Compiler/Assembler/Linker Options	10
3.1.3 GHS Compiler/Assembler/Linker Options	12
3.1.4 IAR Compiler/Assembler/Linker Options	14
3.2 Files required for compilation	16
3.2.1 Other includes files:	17
3.3 Setting up the plugins	18
4 Function calls to module	20
4.1 Function Calls during Start-up	20
4.2 Function Calls during Shut-down	20
4.3 Function Calls during Wake-up	20
5 Module requirements	21
5.1 Exclusive areas to be defined in BSW scheduler	21
5.1.1 Critical Region Exclusive Matrix	23
5.2 Exclusive areas not available on this platform	23
5.3 Peripheral Hardware Requirements	23
5.4 ISR to configure within AutosarOS - dependencies	23
5.5 ISR Macro	23
5.5.1 Without an Operating System	23
5.5.2 With an Operating System	24
5.6 Other AUTOSAR modules - dependencies	24
5.7 Data Cache Restrictions	25
5.8 User Mode support	25
5.8.1 User Mode support in module	25
5.8.2 User Mode configuration in AutosarOS	25
5.9 Multicore support	26
6 Main API Requirements	27
6.1 Main function calls within BSW scheduler	27

6.2 API Requirements	27
6.3 Calls to Notification Functions, Callbacks, Callouts	27
7 Memory allocation	28
7.1 Sections to be defined in Mem_43_Eep_MemMap.h	28
7.2 Linker command file	29
8 Integration Steps	30
9 External assumptions for driver	31



Chapter 1

Revision History

Revision	Date	Author	Description
1.0	31.03.2023	NXP RTD Team	S32K3 Real-Time Drivers AUTOSAR 4.4 & R21-11 Version 3.0.0

Chapter 2

Introduction

- [Supported Derivatives](#)
- [Overview](#)
- [About This Manual](#)
- [Acronyms and Definitions](#)
- [Reference List](#)

This integration manual describes the integration requirements for Mem_43_Eep Driver for S32K3 microcontrollers.

2.1 Supported Derivatives

The software described in this document is intended to be used with the following microcontroller devices of NXP Semiconductors:

- s32k310_mqfp100
- s32k310_lqfp48
- s32k311_mqfp100 / MWCT2015S_mqfp100
- s32k311_lqfp48
- s32k312_mqfp100 / MWCT2016S_mqfp100
- s32k312_mqfp172 / MWCT2016S_mqfp172
- s32k314_mqfp172
- s32k314_mapbga257
- s32k322_mqfp100 / MWCT2D16S_mqfp100
- s32k322_mqfp172 / MWCT2D16S_mqfp172
- s32k324_mqfp172 / MWCT2D17S_mqfp172
- s32k324_mapbga257

- s32k341_mqfp100
- s32k341_mqfp172
- s32k342_mqfp100
- s32k342_mqfp172
- s32k344_mqfp172
- s32k344_mapbga257
- s32k394_mapbga289
- s32k396_mapbga289
- s32k358_mqfp172
- s32k358_mapbga289
- s32k328_mqfp172
- s32k328_mapbga289
- s32k338_mqfp172
- s32k338_mapbga289
- s32k348_mqfp172
- s32k348_mapbga289
- s32m274_lqfp64
- s32m276_lqfp64

All of the above microcontroller devices are collectively named as S32K3.

Note: MWCT part numbers contain NXP confidential IP for Qi Wireless Power.

2.2 Overview

AUTOSAR (AUTomotive Open System ARchitecture) is an industry partnership working to establish standards for software interfaces and software modules for automobile electronic control systems.

AUTOSAR:

- paves the way for innovative electronic systems that further improve performance, safety and environmental friendliness.
- is a strong global partnership that creates one common standard: "Cooperate on standards, compete on implementation".
- is a key enabling technology to manage the growing electrics/electronics complexity. It aims to be prepared for the upcoming technologies and to improve cost-efficiency without making any compromise with respect to quality.
- facilitates the exchange and update of software and hardware over the service life of the vehicle.

2.3 About This Manual

This Technical Reference employs the following typographical conventions:

- **Boldface** style: Used for important terms, notes and warnings.
- *Italic* style: Used for code snippets in the text. Note that C language modifiers such "const" or "volatile" are sometimes omitted to improve readability of the presented code.

Notes and warnings are shown as below:

Note

This is a note.

Warning

This is a warning

2.4 Acronyms and Definitions

Term	Definition
API	Application Programming Interface
AUTOSAR	Automotive Open System Architecture
DET	Default Error Tracer
DEM	Diagnostic Event Manager
ECC	Error Correcting Code
VLE	Variable Length Encoding
N/A	Not Available
MCU	Microcontroller Unit
ECU	Electronic Control Unit
EEPROM	Electrically Erasable Programmable Read-Only Memory
EA	MEM_43_EEPROM Abstraction
USDHC	Ultra Secured Digital Host Controller
EMMC	Enhanced Multi Media Card
MEM_43_EEP	Memory EEPROM driver
XML	Extensible Markup Language

2.5 Reference List

#	Title	Version
1	Specification of MEM Driver	AUTOSAR Release R21-11
2	Reference Manual	S32K3xx Reference Manual, Rev.6, Draft B, 01/2023
		S32K39 and S32K37 Reference Manual, Rev. 2 Draft A, 11/2022
3	Datasheet	S32K3xx Data Sheet, Rev. 6, 11/2022
		S32K396 Data Sheet, Rev. 1.1 — 08/2022
4	Errata	S32K358_0P14E Mask Set Errata — Rev. 28, 9/2022
		S32K396_0P40E Mask Set Errata, Rev. DEC2022, 12/2022
		S32K311_0P98C Mask Set Errata, Rev. 6/March/2023, 3/2023
		S32K312: Mask Set Errata for Mask 0P09C, Rev. 25/April/2022
		S32K342: Mask Set Errata for Mask 0P97C, Rev. 10, 11/2022
		S32K3x4: Mask Set Errata for Mask 0P55A/1P55A, Rev. 14/Oct/2022

Chapter 3

Building the driver

- [Build Options](#)
- [Files required for compilation](#)
- [Setting up the plugins](#)

This section describes the source files and various compilers, linker options used for building the driver. It also explains the EB Tresos Studio plugin setup procedure.

3.1 Build Options

- [GCC Compiler/Assembler/Linker Options](#)
- [DIAB Compiler/Assembler/Linker Options](#)
- [GHS Compiler/Assembler/Linker Options](#)
- [IAR Compiler/Assembler/Linker Options](#)

The RTD driver files are compiled using:

- NXP GCC 10.2.0 20200723 (Build 1728 Revision g5963bc8)
- Wind River Diab Compiler 7.0.4
- Compiler Versions: Green Hills Multi 7.1.6d / Compiler 2021.1.4
- Compiler Versions: IAR ANSI C/C++ Compiler V8.50.10 (safety version)

The compiler, assembler, and linker flags used for building the driver are explained below.

The TS_T40D34M30I0R0 part of the plugin name is composed as follows:

- T = Target_Id (e.g. T40 identifies Cortex-M architecture)
- D = Derivative_Id (e.g. D34 identifies S32K3 platform)
- M = SW_Version_Major and SW_Version_Minor
- I = SW_Version_Patch
- R = Reserved

3.1.1.1 GCC Compiler/Assembler/Linker Options

3.1.1.1.1 GCC Compiler Options

Compiler Option	Description
-mcpu=cortex-m7	Targeted ARM processor for which GCC should tune the performance of the code
-mthumb	Generates code that executes in Thumb state
-mlittle-endian	Generate code for a processor running in little-endian mode
-mfpv=fpv5-sp-d16	Specifies the floating-point hardware available on the target
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions
-std=c99	Specifies the ISO C99 base standard
-Os	Optimize for size. Enables all -O2 optimizations except those that often increase code size
-ggdb3	Produce debugging information for use by GDB using the most expressive format available, including GDB extensions if at all possible. Level 3 includes extra information, such as all the macro definitions present in the program
-Wall	Enables all the warnings about constructions that some users consider questionable, and that are easy to avoid (or modify to prevent the warning), even in conjunction with macros
-Wextra	This enables some extra warning flags that are not enabled by -Wall
-pedantic	Issue all the warnings demanded by strict ISO C. Reject all programs that use forbidden extensions. Follows the version of the ISO C standard specified by the aforementioned -std option
-Wstrict-prototypes	Warn if a function is declared or defined without specifying the argument types
-Wundef	Warn if an undefined identifier is evaluated in an #if directive. Such identifiers are replaced with zero
-Wunused	Warn whenever a function, variable, label, value, macro is unused
-Werror=implicit-function-declaration	Make the specified warning into an error. This option throws an error when a function is used before being declared
-Wsign-compare	Warn when a comparison between signed and unsigned values could produce an incorrect result when the signed value is converted to unsigned.
-Wdouble-promotion	Give a warning when a value of type float is implicitly promoted to double
-fno-short-enums	Specifies that the size of an enumeration type is at least 32 bits regardless of the size of the enumerator values.
-funsigned-char	Let the type char be unsigned by default, when the declaration does not use either signed or unsigned
-funsigned-bitfields	Let a bit-field be unsigned by default, when the declaration does not use either signed or unsigned

Compiler Option	Description
-fno-common	Makes the compiler place uninitialized global variables in the BSS section of the object file. This inhibits the merging of tentative definitions by the linker so you get a multiple-definition error if the same variable is accidentally defined in more than one compilation unit
-fstack-usage	This option is only used to build test for generation Ram/↔ Stack size report. Makes the compiler output stack usage information for the program, on a per-function basis
-fdump-ipa-all	This option is only used to build test for generation Ram/↔ Stack size report. Enables all inter-procedural analysis dumps
-c	Stop after assembly and produce an object file for each source file
-DS32K3XX	Predefine S32K3XX as a macro, with definition 1
-D \$ (DERIVATIVE)	Predefine S32K3's derivative as a macro, with definition 1. For example: Predefine for S32K344 will be -DS32K344.
-DGCC	Predefine GCC as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode
-DD_CACHE_ENABLE	Predefine D_CACHE_ENABLE as a macro, with definition 1. Enables data cache initialization in source file system.↔ c under the Platform driver
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode.
-sysroot=	Specifies the path to the sysroot, for Cortex-M7 it is /arm-none-eabi/newlib
-specs=nano.specs	Use Newlib nano specs
-specs=nosys.specs	Do not use printf/scanf

3.1.1.2 GCC Assembler Options

Assembler Option	Description
-Xassembler-with-cpp	Specifies the language for the following input files (rather than letting the compiler choose a default based on the file name suffix)
-mcpu=cortexm7	Targeted ARM processor for which GCC should tune the performance of the code
-mfpu=fpv5-sp-d16	Specifies the floating-point hardware available on the target
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions
-mthumb	Generates code that executes in Thumb state
-c	Stop after assembly and produce an object file for each source file

3.1.1.3 GCC Linker Options

Linker Option	Description
-Wl,-Map,filename	Produces a map file
-T linkerfile	Use linkerfile as the linker script. This script replaces the default linker script (rather than adding to it)
-entry=Reset_Handler	Specifies that the program entry point is Reset_Handler
-nostartfiles	Do not use the standard system startup files when linking
-mcpu=cortexm7	Targeted ARM processor for which GCC should tune the performance of the code
-mthumb	Generates code that executes in Thumb state
-mfpu=fpv5-sp-d16	Specifies the floating-point hardware available on the target
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions
-mlittle-endian	Generate code for a processor running in little-endian mode
-ggdb3	Produce debugging information for use by GDB using the most expressive format available, including GDB extensions if at all possible. Level 3 includes extra information, such as all the macro definitions present in the program
-lc	Link with the C library
-lm	Link with the Math library
-lgcc	Link with the GCC library
-specs=nano.specs	Use Newlib nano specs
-specs=nosys.specs	Do not use printf/scanf

3.1.2 DIAB Compiler/Assembler/Linker Options

3.1.2.1 DIAB Compiler Options

Compiler Option	Description
-tARMCORTEXM7MG:simple	Selects target processor (hardware single-precision, software double-precision floating-point)
-mthumb	Selects generating code that executes in Thumb state
-std=c99	Follows the C99 standard for C
-Oz	Like -O2 with further optimizations to reduce code size
-g	Generates DWARF 4.0 debug information
-fstandalone-debug	Emits full debug info for all types used by the program
-Wstrict-prototypes	Warn if a function is declared or defined without specifying the argument types
-Wsign-compare	Produce warnings when comparing signed type with unsigned type
-Wdouble-promotion	Give a warning when a value of type float is implicitly promoted to double
-Wunknown-pragmas	Issues a warning for unknown pragmas
-Wundef	Warns if an undefined identifier is evaluated in an #if directive. Such identifiers are replaced with zero

Compiler Option	Description
-Wextra	Enables some extra warning flags that are not enabled by '-Wall'
-Wall	Enables all of the most useful warnings (for historical reasons this option does not literally enable all warnings)
-pedantic	Emits a warning whenever the standard specified by the -std option requires a diagnostic
-Werror=implicit-function-declaration	Generates an error whenever a function is used before being declared
-fno-common	Compile common globals like normal definitions
-fno-signed-char	Char is unsigned
-fno-trigraphs	Do not process trigraph sequences
-V	Displays the current version number of the tool suite
-c	Stop after assembly and produce an object file for each source file
-DS32K3XX	Predefine S32K3XX as a macro, with definition 1
-D \$ (DERIVATIVE)	Predefine S32K3's derivative as a macro, with definition 1
-DDIAB	Predefine DIAB as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode
-DD_CACHE_ENABLE	Predefine D_CACHE_ENABLE as a macro, with definition 1. Enables data cache initialization in source file system.c under the Platform driver
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode

3.1.2.2 DIAB Assembler Options

Assembler Option	Description
-mthumb	Selects generating code that executes in Thumb state
-Xpreprocess-assembly	Invokes C preprocessor on assembly files before running the assembler
-Xassembly-listing	Produces an .lst assembly listing file
-c	Stop after assembly and produce an object file for each source file
-tARMCORTEXM7MG:simple	Selects target processor (hardware single-precision, software double-precision floating-point)

3.1.2.3 DIAB Linker Options

Linker Option	Description
-e Reset_Handler	Make the symbol Reset_Handler be treated as a root symbol and the start label of the application
linker_script_file.dld	Use linker_script_file.dld as the linker script. This script replaces the default linker script (rather than adding to it)
-m30	m2 + m4 + m8 + m16
-Xstack-usage	Gathers and display stack usage at link time
-Xpreprocess-lecl	Perform pre-processing on linker scripts
-Llibrary_path	Points to the libraries location for ARMV7EMMG to be used for linking
-lc	Links with the standard C library
-lm	Links with the math library
-tARMCORTEXM7MG:simple	Selects target processor (hardware single-precision, software double-precision floating-point)

3.1.3 GHS Compiler/Assembler/Linker Options

3.1.3.1 GHS Compiler Options

Compiler Option	Description
-cpu=cortexm7	Selects target processor: Arm Cortex M7
-thumb	Selects generating code that executes in Thumb state
-fpu=vfpv5_d16	Specifies hardware floating-point using the v5 version of the VFP instruction set, with 16 double-precision floating-point registers
-fsingle	Use hardware single-precision, software double-precision FP instructions
-C99	Use (strict ISO) C99 standard (without extensions)
-ghstd=last	Use the most recent version of Green Hills Standard mode (which enables warnings and errors that enforce a stricter coding standard than regular C and C++)
-Osize	Optimize for size
-gnu_asm	Enables GNU extended asm syntax support
-dual_debug	Generate DWARF 2.0 debug information
-G	Generate debug information
-keeptempfiles	Prevents the deletion of temporary files after they are used. If an assembly language file is created by the compiler, this option will place it in the current directory instead of the temporary directory
-Wimplicit-int	Produce warnings if functions are assumed to return int
-Wshadow	Produce warnings if variables are shadowed
-Wtrigraphs	Produce warnings if trigraphs are detected
-Wundef	Produce a warning if undefined identifiers are used in #if preprocessor statements
-unsigned_chars	Let the type char be unsigned, like unsigned char
-unsigned_fields	Bitfields declared with an integer type are unsigned

Compiler Option	Description
-no_commons	Allocates uninitialized global variables to a section and initializes them to zero at program startup
-no_exceptions	Disables C++ support for exception handling
-no_slash_comment	C++ style // comments are not accepted and generate errors
-prototype_errors	Controls the treatment of functions referenced or called when no prototype has been provided
-incorrect_pragma_warnings	Controls the treatment of valid #pragma directives that use the wrong syntax
-c	Stop after assembly and produce an object file for each source file
-DS32K3XX	Predefine S32K3XX as a macro, with definition 1
-D \$ (DERIVATIVE)	Predefine S32K3's derivative as a macro, with definition 1. For example: Predefine for S32K344 will be -DS32K344.
-DGHS	Predefine GHS as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode
-DD_CACHE_ENABLE	Predefine D_CACHE_ENABLE as a macro, with definition 1. Enables data cache initialization in source file system.c under the Platform driver
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode

3.1.3.2 GHS Assembler Options

Assembler Option	Description
-cpu=cortexm7	Selects target processor: Arm Cortex M7
-fpu=vfpv5_d16	Specifies hardware floating-point using the v5 version of the VFP instruction set, with 16 double-precision floating-point registers
-fsingle	Use hardware single-precision, software double-precision FP instructions
-preprocess_assembly_files	Controls whether assembly files with standard extensions such as .s and .asm are preprocessed
-list	Creates a listing by using the name and directory of the object file with the .lst extension
-c	Stop after assembly and produce an object file for each source file

3.1.3.3 GHS Linker Options

Linker Option	Description
-e Reset_Handler	Make the symbol Reset_Handler be treated as a root symbol and the start label of the application
-T linker_script_file.ld	Use linker_script_file.ld as the linker script. This script replaces the default linker script (rather than adding to it)
-map	Produce a map file
-keepmap	Controls the retention of the map file in the event of a link error
-Mn	Generates a listing of symbols sorted alphabetically/numerically by address
-delete	Instructs the linker to remove functions that are not referenced in the final executable. The linker iterates to find functions that do not have relocations pointing to them and eliminates them
-ignore_debug_references	Ignores relocations from DWARF debug sections when using -delete. DWARF debug information will contain references to deleted functions that may break some third-party debuggers
-Llibrary_path	Points to library_path (the libraries location) for thumb2 to be used for linking
-larch	Link architecture specific library
-lstartup	Link run-time environment startup routines. The source code for themodules in this library is provided in the src/libstartup directory
-lind_sd	Link language-independent library, containing support routines for features such as software floating point, run-time error checking, C99 complex numbers, and some general purpose routines of the ANSI C library
-v	Prints verbose information about the activities of the linker, including the libraries it searches to resolve undefined symbols
-keep=C40_Ip_AccessCode	Avoid linker remove function C40_Ip_AccessCode from Fls module because it is not referenced explicitly
-nostartfiles	Controls the start files to be linked into the executable

3.1.4 IAR Compiler/Assembler/Linker Options

3.1.4.1 IAR Compiler Options

Compiler Option	Description
-cpu Cortex-M7	Targeted ARM processor for which IAR should tune the performance of the code
-cpu_mode thumb	Generates code that executes in Thumb state
-endian little	Generate code for a processor running in little-endian mode
-fpu VFPv5-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant.
-e	Enables all IAR C language extensions
-Osz	Optimize for size. the compiler will emit AEABI attributes indicating the requested optimization goal. This information can be used by the linker to select smaller or faster variants of DLIB library functions
-debug	Makes the compiler include debugging information in the object modules. Including debug information will make the object files larger

Compiler Option	Description
-no_clustering	Disables static clustering optimizations. Static and global variables defined within the same module will not be arranged so that variables that are accessed in the same function are close to each other
-no_mem_idioms	Makes the compiler not optimize certain memory access patterns
-do_explicit_zero_opt_in_named_sections	Disable the exception for variables in user-named sections, and thus treat explicit initializations to zero as zero initializations, not copy initializations
-require_prototypes	Force the compiler to verify that all functions have proper prototypes. Generates an error otherwise
-no_wrap_diagnostics	Does not wrap long lines in diagnostic messages
-diag_suppress Pa050	Suppresses diagnostic message Pa050
-DS32K3XX	Predefine S32K3XX as a macro, with definition 1
-D \$ (DERIVATIVE)	Predefine S32K3's derivative as a macro, with definition 1. For example: Predefine for S32K344 will be -DS32K344.
-DIAR	Predefine IAR as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode.
-DD_CACHE_ENABLE	Predefine D_CACHE_ENABLE as a macro, with definition 1. Enables data cache initialization in source file system.c under the Platform driver
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode.

3.1.4.2 IAR Assembler Options

Assembler Option	Description
-cpu Cortex-M7	Targeted ARM processor for which IAR should generate the instruction set
-fpu VFPv5-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant.
-cpu_mode thumb	Selects the thumb mode for the assembler directive CODE
-g	Disables the automatic search for system include files
-r	Generates debug information

3.1.4.3 IAR Linker Options

Linker Option	Description
-map filename	Produces a map file
-config linkerfile	Use linkerfile as the linker script. This script replaces the default linker script (rather than adding to it)
-cpu=Cortex-M7	Selects the ARM processor variant to link the application for
-fpu VFPv5-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant.
-entry _start	Treats _start as a root symbol and start label
-enable_stack_usage	Enables stack usage analysis. If a linker map file is produced, a stack usage chapter is included in the map file
-skip_dynamic_initialization	Dynamic initialization (typically initialization of C++ objects with static storage duration) will not be performed automatically during application startup
-no_wrap_diagnostics	Does not wrap long lines in diagnostic messages

3.2 Files required for compilation

This section describes the include files required to compile, assemble (if assembler code) and link the Mem_43_Eep driver for S32K3XX microcontrollers. To avoid integration of incompatible files, all the include files from other modules shall have the same AR_MAJOR_VERSION and AR_MINOR_VERSION, i.e. only files with the same AUTOSAR major and minor versions can be compiled.

#Mem_43_Eep files:

- Mem_43_Eep_TS_T40D34M30I0R0\include\Mem_43_Eep.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Mem_43_Eep_InternalTypes.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Mem_43_Eep_IPW.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Mem_43_Eep_Types.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Sd_Emmc_Ip.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Sd_Emmc_Ip_Types.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Usdhc_Ip.h
- Mem_43_Eep_TS_T40D34M30I0R0\include\Usdhc_Ip_Types.h
- Mem_43_Eep_TS_T40D34M30I0R0\src\Mem_43_Eep.c
- Mem_43_Eep_TS_T40D34M30I0R0\src\Mem_43_Eep_IPW.c
- Mem_43_Eep_TS_T40D34M30I0R0\src\Sd_Emmc_Ip.c
- Mem_43_Eep_TS_T40D34M30I0R0\src\Usdhc_Ip.c

Note

- Mem_43_Eep_Cfg.h - this file should be generated by the user using a configuration/generation tool
- Mem_43_Eep_Cfg.c - this file should be generated by the user using a configuration/generation tool
- Sd_Emmc_Ip_Cfg.c - this file should be generated by the user using a configuration/generation tool
- Sd_Emmc_Ip_Cfg.h - this file should be generated by the user using a configuration/generation tool
- Usdhc_Ip_Cfg.c - this file should be generated by the user using a configuration/generation tool
- Usdhc_Ip_Cfg.h - this file should be generated by the user using a configuration/generation tool
- Usdhc_Ip_DeviceRegisters.h - this file should be generated by the user using a configuration/generation tool

3.2.1 Other includes files:

3.2.1.1 Files from MemAcc folder:

- MemAcc_TS_T40D34M30I0R0\include\MemAcc_Types.h

3.2.1.2 Files from BaseNXP common folder:

- BaseNXP_TS_T40D34M30I0R0\include\Compiler.h
- BaseNXP_TS_T40D34M30I0R0\include\Compiler_Cfg.h
- BaseNXP_TS_T40D34M30I0R0\include\ComStack_Types.h
- BaseNXP_TS_T40D34M30I0R0\include\Fls_MemMap.h
- BaseNXP_TS_T40D34M30I0R0\include\Mcal.h
- BaseNXP_TS_T40D34M30I0R0\include\OsIf.h
- BaseNXP_TS_T40D34M30I0R0\include\Platform_Types.h
- BaseNXP_TS_T40D34M30I0R0\include\Std_Types.h
- BaseNXP_TS_T40D34M30I0R0\include\Reg_eSys.h
- BaseNXP_TS_T40D34M30I0R0\include\Soc_Ips.h
- BaseNXP_TS_T40D34M30I0R0\include\Reg_Macros.h
- BaseNXP_TS_T40D34M30I0R0\include\SilRegMacros.h
- BaseNXP_TS_T40D34M30I0R0\header\S32K358.h

3.2.1.3 Files from Det folder:

- Det_TS_T40D34M30I0R0\include\Det.h

3.2.1.4 Files from Dem folder:

- Dem_TS_T40D34M30I0R0\include\Dem.h

3.2.1.5 Files from Platform folder:

- Platform_TS_T40D34M30I0R0\include\Platform.h

3.2.1.6 Files from Rte folder:

- Rte_TS_T40D34M30I0R0\include\SchM_Mem_43_Eep.h

3.2.1.7 Files from Os folder:

- Os_TS_T40D34M30I0R0\include\Os.h

3.2.1.8 Files from Rm folder:

- Rm_TS_T40D34M30I0R0\include\CDD_Rm.h
- Rm_TS_T40D34M30I0R0\include\Sema42_Ip.h
- Rm_TS_T40D34M30I0R0\include\Xrdc_Ip.h

3.3 Setting up the plugins

The Mem_43_Eep Driver was designed to be configured by using the EB Tresos Studio (version 27.1.0 or later)

3.3.0.0.1 Steps to generate the configuration:

1. Copy the module folders:

- BaseNXP_TS_T40D34M30I0R0
- Det_TS_T40D34M30I0R0
- Dem_TS_T40D34M30I0R0
- EcuC_TS_T40D34M30I0R0
- Mem_43_Eep_TS_T40D34M30I0R0
- Rm_TS_T40D34M30I0R0
- MemAcc_TS_T40D34M30I0R0
- Os_TS_T40D34M30I0R0
- Platform_TS_T40D34M30I0R0
- Resource_TS_T40D34M30I0R0
- Rte_TS_T40D34M30I0R0 into the Tresos plugins folder.

2. Set the desired Tresos Output location folder for the generated sources and header files.

3. Use the EB tresos Studio GUI to modify ECU configuration parameters values.

4. Generate the configuration files.

3.3.0.0.2 Location of various files inside the MEM_43_EEP module folder:

- VSMD (Vendor Specific Module Definition) file in EB Tresos Studio XDM format:
 - Mem_43_Eep_TS_T40D34M30I0R0\config\Mem_43_Eep.xdm
- VSMD (Vendor Specific Module Definition) file(s) in AUTOSAR compliant EPD format:
 - Mem_43_Eep_TS_T40D34M30I0R0\autosar\Mem_43_Eep_<subderivative_name>.epd
- Code Generation Templates for variant aware parameters:
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\src\Sd_Emmc_Ip_Cfg.c
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\src\Usdhc_Ip_Cfg.c
- Code Generation Templates for parameters without variation points:
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\include\Mem_43_Eep_Cfg.h
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\include\Sd_Emmc_Ip_Cfg.h
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\include\Usdhc_Ip_Cfg.h
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\include\Usdhc_Ip_Features.h
 - Mem_43_Eep_TS_T40D34M30I0R0\generate_PC\src\Mem_43_Eep_Cfg.c

Chapter 4

Function calls to module

- [Function Calls during Start-up](#)
- [Function Calls during Shut-down](#)
- [Function Calls during Wake-up](#)

4.1 Function Calls during Start-up

MEM_43_EEP shall be initialized during STARTUP phase of EcuM initialization. The API to be called for this is Mem_43_Eep_Init(). The MCU module should be initialized before the MEM_43_EEP is initialized.

4.2 Function Calls during Shut-down

MEM_43_EEP shall be initialized during STARTUP phase of EcuM deinitialization. The API to be called for this is Mem_43_Eep_DeInit().

4.3 Function Calls during Wake-up

None.

Chapter 5

Module requirements

- Exclusive areas to be defined in BSW scheduler
- Exclusive areas not available on this platform
- Peripheral Hardware Requirements
- ISR to configure within AutosarOS - dependencies
- ISR Macro
- Other AUTOSAR modules - dependencies
- Data Cache Restrictions
- User Mode support
- Multicore support

5.1 Exclusive areas to be defined in BSW scheduler

- In the current implementation, MEM_43_EEP is using the services of Run-Time Environment (RTE) for entering and exiting the critical regions.
- RTE implementation is done by the integrators of the RTD using OS or non-OS services.
- For testing the MEM_43_EEP, stubs are used for RTE.
- MEM_43_EEP driver has five exclusive areas.
- The purpose of these exclusive areas is to make the functions Mem_43_Eep_Erase, Mem_43_Eep_Write and Mem_43_Eep_Read thread safe and thus protect MEM_43_EEP internal job variables.

MEM_43_EEP_EXCLUSIVE_AREA_01 is used in function Mem_43_Eep_Erase. It protects the variables:

- Mem_43_Eep_u32EepromAddrIt
- Mem_43_Eep_u32RemainingLength

Module requirements

- Mem_43_Eep_eJob
- Mem_43_Eep_eJobResult

MEM_43_EEP_EXCLUSIVE_AREA_02 is used in function Mem_43_Eep_Write. It protects the variables:

- Mem_43_Eep_u32EepromAddrIt
- Mem_43_Eep_pJobSrcAddrPtr
- Mem_43_Eep_u32RemainingLength
- Mem_43_Eep_eJob
- Mem_43_Eep_eJobResult

MEM_43_EEP_EXCLUSIVE_AREA_03 is used in function Mem_43_Eep_Read. It protects the variables:

- Mem_43_Eep_u32EepromAddrIt
- Mem_43_Eep_pJobSrcAddrPtr
- Mem_43_Eep_u32RemainingLength
- Mem_43_Eep_eJob
- Mem_43_Eep_eJobResult

MEM_43_EEP_EXCLUSIVE_AREA_04 is used in function Mem_43_Eep_Erase. It protects the variables:

- Mem_43_Eep_u32EepromAddrIt
- Mem_43_Eep_u32RemainingLength
- Mem_43_Eep_eJob
- Mem_43_Eep_eJobResult

MEM_43_EEP_EXCLUSIVE_AREA_05 is used in function Mem_43_Eep_Compare. It protects the variables:

- Mem_43_Eep_u32EepromAddrIt
- Mem_43_Eep_pJobSrcAddrPtr
- Mem_43_Eep_u32RemainingLength
- Mem_43_Eep_eJob
- Mem_43_Eep_eJobResult

5.1.1 Critical Region Exclusive Matrix

- Below is the table depicting the exclusivity between different critical region IDs from the MEM_43_EEP driver.
- If there is an “X” in a table, it means that those 2 critical regions cannot interrupt each other.

Exclusive Area ID	DRIVER_EXCLUSIVE_AREA_01 (Eep_Erase)	DRIVER_EXCLUSIVE_AREA_02 (Eep_Write)	DRIVER_EXCLUSIVE_AREA_03 (Eep_Read)	DRIVER_EXCLUSIVE_AREA_04 (Eep_Compare)
DRIVER_EXCLUSIVE_AREA_01 (Eep_Erase)		x	x	x
DRIVER_EXCLUSIVE_AREA_02 (Eep_Write)	x		x	x
DRIVER_EXCLUSIVE_AREA_03 (Eep_Read)	x	x		x
DRIVER_EXCLUSIVE_AREA_04 (Eep_Compare)	x	x	x	

5.2 Exclusive areas not available on this platform

None.

5.3 Peripheral Hardware Requirements

The MEM_43_EEP driver uses/controls the "USDHC" MCU peripheral. For more details about peripheral and its structure refers to MCU reference manual.

5.4 ISR to configure within AutosarOS - dependencies

ISR Name	GIC InterruptID	NVIC Interrupt ID	Observations
uSDHC0_Isr	177	44	None

5.5 ISR Macro

RTD drivers use the ISR macro to define the functions that will process hardware interrupts. Depending on whether the OS is used or not, this macro can have different definitions.

5.5.1 Without an Operating System

The macro `_USING_OS_AUTOSAROS_` must not be defined.

5.5.1.1 Using Software Vector Mode

The macro `_USE_SW_VECTOR_MODE_` must be defined and the ISR macro is defined as:

```
#define ISR(IsrName) void IsrName(void)
```

In this case, the drivers' interrupt handlers are normal C functions and their prologue/epilogue will handle the context save and restore.

5.5.1.2 Using Hardware Vector Mode

The macro `_USE_SW_VECTOR_MODE_` must not be defined and the ISR macro is defined as:

```
#define ISR(IsrName) INTERRUPT_FUNC void IsrName(void)
```

In this case, the drivers' interrupt handlers must also handle the context save and restore.

5.5.2 With an Operating System Please refer to your OS documentation for description of the ISR macro.

5.6 Other AUTOSAR modules - dependencies

- **BaseNXP**: This module provides basic data types and auxiliary macros or functions commonly used by other AUTOSAR modules.
- **Dem**: This module is necessary for enabling reporting of production relevant error status. The API function used is `Dem_ReportErrorStatus()`.
- **Det**: This module is necessary for enabling Development error detection. The API function used is `Det_ReportError()`. The activation/deactivation of Development error detection is configurable using 'Mem_43←_EepDevErrorDetect' configuration parameter.
- **EcuC**: (only for ASR 4.2) The ECUC module is used for ECU configuration. RTD modules need ECUC to retrieve the variant information.
- **Rte**: Exclusive areas implementations.
- **MemAcc**: Memory Interface.
- **Mcl**: Clean/invalidate cache In the DMA transfer modes.
- **Rm**: Provide Semaphore which is needed in multicore.

5.7 Data Cache Restrictions

In the DMA transfer mode, DMA transfers may issue cache coherency problems. To avoid possible coherency issues when D-CACHE is enabled, the user shall ensure that the buffers used as TCD source and destination are allocated in the NON-CACHEABLE area (by means of `Mem_43_Eep_Memmap`) or enable the feature **Mem_43_Eep_SynchronizeCache** to clean/invalidate data cache before transferring.

Note

- In case the user's buffer address or length are not aligned with the cache line size (32-byte), driver will decrease the start address and increase the length to compensate, to ensure both of them are aligned
- It is highly recommended to define the DMA buffers aligned to the cache line size boundary, and the buffer length is a multiple of the cache line size to avoid unexpected behavior

5.8 User Mode support

- [User Mode support in module](#)
- [User Mode configuration in AutosarOS](#)

5.8.1 User Mode support in module

No special measures need to be taken to run `Mem_43_Eep` module from user mode. The `Mem_43_Eep` driver code can be executed at any time from both supervisor and user mode.

5.8.2 User Mode configuration in AutosarOS

When User mode is enabled, the driver may have the functions that need to be called as trusted functions in AutosarOS context. Those functions are already defined in driver and declared in the header `<IpName>_IpTrustedFunctions.h`. This header also included all headers files that contains all types definition used by parameters or return types of those functions. Refer the chapter [User Mode support in module](#) for more detail about those functions and the name of header files they are declared inside. Those functions will be called indirectly with the naming convention below in order to AutosarOS can call them as trusted functions.

```
Call_<Function_Name>_TRUSTED(parameter1,parameter2,...)
```

That is the result of macro expansion `OsIf_Trusted_Call` in driver code:

```
#define OsIf_Trusted_Call[1-6params](name,param1,...,param6) Call_##name##_TRUSTED(param1,...,param6)
```

So, the following steps need to be done in AutosarOS:

- Ensure `MCAL_ENABLE_USER_MODE_SUPPORT` macro is defined in the build system or somewhere global.
- Define and declare all functions that need to call as trusted functions follow the naming convention above in Integration/User code. They need to be visible in `Os.h` for the driver to call them. They will do the marshalling of the parameters and call `CallTrustedFunction()` in OS specific manner.
- `CallTrustedFunction()` will switch to privileged mode and call `TRUSTED_<Function_Name>()`.

Module requirements

- `TRUSTED_<Function_Name>()` function is also defined and declared in Integration/User code. It will un-marshalling of the parameters to call `<Function_Name>()` of driver. The `<Function_Name>()` functions are already defined in driver and declared in `<IpName>_Ip_TrustedFunctions.h`. This header should be included in OS for OS call and indexing these functions.

See the sequence chart below for an example calling `Linflexd_Uart_Ip_Init_Privileged()` as a trusted function.




Figure 5.1 Example sequence chart for calling `Linflexd_Uart_Ip_Init_Privileged` as trusted function

5.9 Multicore support

The Multicore support is not yet implemented.

Chapter 6

Main API Requirements

- [Main function calls within BSW scheduler](#)
- [API Requirements](#)
- [Calls to Notification Functions, Callbacks, Callouts](#)

6.1 Main function calls within BSW scheduler

Mem_43_Eep_MainFunction (call rate depends on target application, i.e. how fast the data needs to be read/written/erased into SD/EMMC memory)

6.2 API Requirements

None.

6.3 Calls to Notification Functions, Callbacks, Callouts

The MEM_43_EEP driver does not provides any notification function.

Chapter 7

Memory allocation

- [Sections to be defined in Mem_43_Eep_MemMap.h](#)
- [Linker command file](#)

7.1 Sections to be defined in Mem_43_Eep_MemMap.h

Section name	Type of section	Description
MEM_43_EEP_START_SEC_↔ CONFIG_DATA_32	Configuration Data	Used for 32 bit Configuration
MEM_43_EEP_STOP_SEC_↔ CONFIG_DATA_32	Configuration Data	End of above section
MEM_43_EEP_START_SEC_↔ CONFIG_DATA_UNSPECIFIED	Configuration Data	Used for Configuration when the SIZE (alignment) does not fit the criteria of 8,16 or 32 bit
MEM_43_EEP_STOP_SEC_↔ CONFIG_DATA_UNSPECIFIED	Configuration Data	End of above section
MEM_43_EEP_START_SEC_CODE	Code	Start of memory Section for Code
MEM_43_EEP_STOP_SEC_CODE	Code	End of above section
MEM_43_EEP_START_SEC_↔ CONST_UNSPECIFIED	Constant Data	The parameters that are not variant aware shall be stored in memory section for constants.
MEM_43_EEP_STOP_SEC_↔ CONST_UNSPECIFIED	Constant Data	End of above section
MEM_43_EEP_START_SEC_VAR_↔ _INIT_BOOLEAN	Variables	Used for boolean variables, structures, arrays. These are initialized with values after every reset.
MEM_43_EEP_STOP_SEC_VAR_↔ INIT_BOOLEAN	Variables	End of above section
MEM_43_EEP_START_SEC_VAR_↔ _INIT_32	Variables	Used for 32 bit variables, structures, arrays. These are initialized with values after every reset.
MEM_43_EEP_STOP_SEC_VAR_↔ INIT_32	Variables	End of above section

Section name	Type of section	Description
MEM_43_EEP_START_SEC_VAR↔ _INIT_UNSPECIFIED	Variables	Used for variables, structures, arrays, when the SIZE (alignment) does not fit the criterion of 8,16 or 32 bit. These variables are initialized with values after every reset.
MEM_43_EEP_STOP_SEC_VAR↔ INIT_UNSPECIFIED	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_BOOLEAN	Variables	Used for boolean variables, structures, arrays. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR↔ CLEARED_BOOLEAN	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_8	Variables	Used for variables, structures, arrays when the SIZE (alignment) fit the criteria of 8 bit. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR↔ CLEARED_8	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_8_NO_CACHEABLE	Variables	Used for variables, structures, arrays when the SIZE (alignment) fit the criteria of 8 bit. These variables are cleared to zero by start-up code.(no cacheable)
MEM_43_EEP_STOP_SEC_VAR↔ CLEARED_8_NO_CACHEABLE	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_16	Variables	Used for variables, structures, arrays when the SIZE (alignment) fit the criteria of 16 bit. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR↔ CLEARED_16	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_32	Variables	Used for variables, structures, arrays when the SIZE (alignment) fit the criteria of 32 bit. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR↔ CLEARED_32	Variables	End of above section
MEM_43_EEP_START_SEC_VAR↔ _CLEARED_UNSPECIFIED_NO↔ CACHEABLE	Non-Cacheable Variables	Used for variables, structures, arrays when the SIZE (alignment) does not fit the criteria of 8,16 or 32 bit, and that have to be stored in a non-cacheable memory section. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR↔ _CLEARED_UNSPECIFIED_NO↔ CACHEABLE	Non-Cacheable Variables	End of above section

7.2 Linker command file

Memory shall be allocated for every section defined in the driver's "<Module>"_MemMap.h.

Chapter 8

Integration Steps

This section gives a brief overview of the steps needed for integrating this module:

1. Generate the required module configuration(s). For more details refer to section [Files Required for Compilation](#)
2. Allocate the proper memory sections in the driver's memory map header file ("`<Module>_MemMap.h`") and linker command file. For more details refer to section [Sections to be defined in `<Module>_MemMap.h`](#)
3. Compile & build the module with all the dependent modules. For more details refer to section [Building the Driver](#)

Chapter 9

External assumptions for driver

The section presents requirements that must be complied with when integrating the MEM_43_EEP driver into the application.

External Assumption Req ID	External Assumption Text
EA_RTD_00071	If interrupts are locked, a centralized function pair to lock and unlock interrupts shall be used.
EA_RTD_00082	When caches are enabled and data buffers are allocated in cacheable memory regions the buffers involved in DMA transfer shall be aligned with both start and end to cache line size. Note: Rationale: This ensures that no other buffers/variables compete for the same cache lines.
EA_RTD_00106	Standalone IP configuration and HL configuration of the same driver shall be done in the same project
EA_RTD_00107	The integrator shall use the IP interface only for hardware resources that were configured for standalone IP usage. Note:♦ The integrator shall not directly use the IP interface for hardware resources that were allocated to be used in HL context.
EA_RTD_00108	The integrator shall use the IP interface to build a CDD, therefore the BSWMD will not contain reference to the IP interface

How to Reach Us:

Home Page:

nxp.com

Web Support:

nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, I2C BUS, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC, MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, Altivec, C-5, CodeTEST, CodeWarrior, ColdFire, ColdFire+, C-Ware, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorIQ, QorIQ Qonverge, Ready Play, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platform in a Package, QUICC Engine, SMARTMOS, Tower, TurboLink, and UMEMS are trademarks of NXP B.V. All other product or service names are the property of their respective owners. ARM, AMBA, ARM Powered, Artisan, Cortex, Jazelle, Keil, SecurCore, Thumb, TrustZone, and Vision are registered trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. ARM7, ARM9, ARM11, big.LITTLE, CoreLink, CoreSight, DesignStart, Mali, mbed, NEON, POP, Sensinode, Socrates, ULINK and Versatile are trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© 2023 NXP B.V.

