

Assignment Solution

1. What do you mean by Multithreading? Why is it important?

Ans: Multithreading means multiple threads and is considered one of the most important features of Java. As the name suggests, it is the ability of a CPU to execute multiple threads independently at the same time but share the process resources simultaneously. Its main purpose is to provide simultaneous execution of multiple threads to utilize the CPU time as much as possible. It is a Java feature where one can subdivide the specific program into two or more threads to make the execution of the program fast and easy.

2. What are the benefits of using Multithreading?

Ans: There are various benefits of multithreading as given below: Allow the program to run continuously even if a part of it is blocked.

- Improve performance as compared to traditional parallel programs that use multiple processes.
- Allows to write effective programs that utilize maximum CPU time
- Improves the responsiveness of complex applications or programs.
- Increase use of CPU resources and reduce costs of maintenance.
- Saves time and parallelism tasks.

3. What is Thread in Java?

Ans: Threads are basically the lightweight and smallest unit of processing that can be managed independently by a scheduler. Threads are referred to as parts of a process that simply let a program execute efficiently with other parts or threads of the process at the same time. Using threads, one can perform complicated tasks in the easiest way. It is considered the simplest way to take advantage of multiple CPUs available in a machine. They share the common address space and are independent of each other.

4. What are the two ways of implementing thread in Java?

Ans: There are basically two ways of implementing thread in java as given below. Extending the Thread class

Example:1.

```
class Multithread extends Thread{

public void run(){

System.out.println("My thread is in running state.");

}

public static void main(String args[]){

    Multithread obj=new Multithread();
    obj.start();

}
}
// Output: My thread is in running state.
```

Example 2.

```
//Implementing Runnable Interface In Java

class MultithreadingDemo implements Runnable{
public void run(){
```

```

System.out.println("My thread is in running state.");
}
public static void main(String args[]){

Multithread obj=new Multithread();
Thread Obj =new Thread(obj);
obj.start();
}
}

// Output: My thread is in running state.

```

5. What's the difference between thread and process?

Ans: Thread it simply refers to the smallest units of the particular process. It has the ability to execute different parts (referred to as thread) of the program at the same time. Process it simply refers to a program that is in execution ie, an active program. A process can be handled using PCB (Process Control Block).

6.How can we create daemon threads?

Ans: We can create daemon threads in java using the thread class setDaemon(true) it is used to mark the current thread as doemon thread or user thread isDaemon() method is generally used to check whether the current thread is daemon or not. if the thread is a doemon, it will return true otherwise it returns faise

Example:

```

//Program to illustrate the use of setDaemon() and
isDaemon () method.

public class Daemon Thread extends Thread{
public DaemonThread(String name)
{

```

```
        super (name);
    }
    public void run(){

        // Checking whether the thread is Daemon or not

        if (Thread.currentThread().isDaemon())

            System.out.println(getName()+" is Daemon thread");

        }

        else

            System.out.println(getName()+" is User thread");

    public static void main(String[] args)
    {
        {
            Daemon Thread t1 = new Daemon Thread("t1");
            DaemonThread t2 = new Daemon Thread("t2");
            DaemonThread t3 = new DaemonThread("t3");
            // Setting user thread t1 to Daemon
            t1.setDaemon (true); // starting first 2 threads
            t1.start(); t2.start();
            // Setting user thread t3 to Daemon
            t3.setDaemon (true); t3.start();
        }
    }
}

// Output:
// t1 is Daemon thread
// t3 is Daemon thread
```

```
// t2 is User thread
```

7. What are the wait() and sleep() methods?

Ans: wait(): As the name suggests, it is a non-static method that causes the current thread to wait and go to sleep until some other threads call the notify() or notifyAll() method for the object's monitor (lock). It simply releases the lock and is mostly used for inter-thread communication. It is defined in the object class, and should only be called from a synchronized context.

Example:

```
synchronized (monitor)
{
monitor.wait(); Here Lock Is Released by Current Thread
}
```

sleep(): As the name suggests, it is a static method that pauses or stops the execution of the current thread for some specified period. It doesn't release the lock while waiting and is mostly used to introduce pause on execution. It is defined in thread class, and no need to call from a synchronized context.

Example:

```
synchronized (monitor)
Thread.sleep(1088); //Here Lock Is Held by The Current
Thread

// after 1888 milliseconds, the current
// thread will wake up, or after we call
// that is interrupt() method
```