1. Books

```
id
title
author
description
price
pdf_url
category_id
total_pages
  rating real
publish_year
tags
created_at
updated_at
created_by
pdf_hosted_path
Is_restricted
constraint books_pkey primary key (id),
  constraint books_created_by_fkey foreign KEY (created_by) references
users (id)
```

```
create table public.books (
  id serial not null,
  title text not null,
  author text not null,
  description text null,
  price real not null default 0,
  cover_url text not null,
  pdf_url text null,
  preview_pdf_url text null,
  category_id integer null,
  is_featured boolean not null default false,
  preview_pages integer not null default 3,
  total_pages integer not null default 0,
  rating real null,
  language text not null default 'Bengali'::text,
  publish_year integer null,
  tags text[] not null default '{}'::text[],
  status text not null default 'published'::text,
  created_at timestamp with time zone not null default now(),
```

```
  updated_at timestamp with time zone not null default now(),
  created_by integer null,
  pdf_hosted_path text null,
  is_uap_only boolean not null default true,
  constraint books_pkey primary key (id),
  constraint books_created_by_fkey foreign KEY (created_by) references
users (id)
) TABLESPACE pg_default;
```

2. Users

```
create table public.users (
  id serial not null,
  name text not null,
  email text not null,
  password_hash text not null,
  role text not null default 'user'::text,
  balance integer not null default 0,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  status text not null default 'active'::text,
  phone text null,
  username text null,
  avatar_color text not null default 'blue'::text,
  pending_username text null,
  last_seen_at timestamp with time zone null,
  avatar_url text null,
  semester text null,
  clerk_user_id text null,
  blood_group text null,
  email_verified boolean not null default true,
  constraint users_pkey primary key (id),
  constraint users_email_unique unique (email)
) TABLESPACE pg_default;

create unique INDEX IF not exists users_username_unique on public.users using
btree (username) TABLESPACE pg_default
where
  (username is not null);
```

```
create unique INDEX IF not exists users_clerk_user_id_idx on public.users using
btree (clerk_user_id) TABLESPACE pg_default
where
  (clerk_user_id is not null);
```

`12

3. Videos

```
create table public.videos (
  id serial not null,
  title text not null,
  description text null,
  type text not null default 'movie'::text,
  category_id integer null,
  subcategory_id integer null,
  thumbnail_url text not null,
  banner_url text null,
  tags text[] not null default '{}'::text[],
  source_type text not null default 'youtube'::text,
  source_ref text not null,
  source_resource_key text null,
  series_id integer null,
  season_number integer null,
  episode_number integer null,
  status text not null default 'draft'::text,
  access_level text not null default 'free'::text,
  is_featured boolean not null default false,
  view_count integer not null default 0,
  release_date date null,
  created_by integer null,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  is_demo boolean not null default false,
  constraint videos_pkey primary key (id)
) TABLESPACE pg_default;

create unique INDEX IF not exists videos_source_type_ref_unique on
public.videos using btree (source_type, source_ref) TABLESPACE pg_default;

create unique INDEX IF not exists videos_source_type_source_ref_idx on
public.videos using btree (source_type, source_ref) TABLESPACE pg_default;
```

4.Watch history

```
create table public.watch_history (
  id serial not null,
  user_id integer not null,
  video_id integer not null,
  progress_seconds integer not null default 0,
  updated_at timestamp with time zone not null default now(),
  constraint watch_history_pkey primary key (id),
  constraint watch_history_user_video_unique unique (user_id, video_id)
) TABLESPACE pg_default;
```

5. user_custom_roles

```
create table public.user_custom_roles (
  user_id integer not null,
  custom_role_id integer not null,
  assigned_at timestamp with time zone not null default now(),
  constraint user_custom_roles_pkey primary key (user_id, custom_role_id),
  constraint user_custom_roles_custom_role_id_fkey foreign KEY (custom_role_id)
references custom_roles (id) on delete CASCADE,
  constraint user_custom_roles_user_id_fkey foreign KEY (user_id) references
users (id) on delete CASCADE
) TABLESPACE pg_default;
```

6. search_history

```
create table public.search_history (
  id serial not null,
  user_id integer not null,
  query character varying(200) not null,
  content_type character varying(20) not null default 'video'::character
varying,
  created_at timestamp with time zone not null default now(),
  constraint search_history_pkey primary key (id)
) TABLESPACE pg_default;
```

7. pyq_papers

```
create table public.pyq_papers (
  id serial not null,
  semester text not null,
  subject_name text not null,
  course_code text not null,
  exam_type text not null,
```

```
  batch_info text null,
  file_urls text[] not null default '{}'::text[],
  file_type text not null default 'image'::text,
  description text null,
  status text not null default 'published'::text,
  is_uap_only boolean not null default true,
  sort_order integer not null default 0,
  created_by integer null,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  file_hosted_paths text[] not null default '{}'::text[],
  constraint pyq_papers_pkey primary key (id)
) TABLESPACE pg_default;
```

8. playlists

```
create table public.playlists (
  id serial not null,
  title text not null,
  description text null,
  thumbnail_url text null,
  created_by integer not null,
  is_public boolean not null default true,
  source_type text not null default 'custom'::text,
  source_url text null,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  max_videos integer null,
  category_id integer null,
  constraint playlists_pkey primary key (id),
  constraint playlists_category_id_fkey foreign KEY (category_id) references
categories (id) on delete set null
) TABLESPACE pg_default;
```

9. playlist_items

```
create table public.playlist_items (
  id serial not null,
  playlist_id integer not null,
  video_id integer not null,
  position integer not null default 0,
  created_at timestamp with time zone not null default now(),
  constraint playlist_items_pkey primary key (id)
```

```
) TABLESPACE pg_default;
```

10. favorites

```
create table public.favorites (
  id serial not null,
  user_id integer not null,
  content_type text not null,
  content_id integer not null,
  created_at timestamp with time zone not null default now(),
  constraint favorites_pkey primary key (id),
  constraint favorites_user_content_unique unique (user_id, content_type,
content_id)
) TABLESPACE pg_default;
```

11. categories

```
create table public.categories (
  id serial not null,
  name text not null,
  slug text not null,
  description text null,
  kind text not null default 'video'::text,
  parent_id integer null,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  constraint categories_pkey primary key (id),
  constraint categories_slug_unique unique (slug)
) TABLESPACE pg_default;
```

12. book_playlists

```
create table public.book_playlists (
  id serial not null,
  title text not null,
  description text null,
  thumbnail_url text null,
  created_by integer not null,
  is_public boolean not null default true,
  created_at timestamp with time zone not null default now(),
  updated_at timestamp with time zone not null default now(),
  category_id integer null,
  constraint book_playlists_pkey primary key (id),
```

```
  constraint book_playlists_category_id_fkey foreign KEY (category_id)
references categories (id) on delete set null
) TABLESPACE pg_default;
```

13. book_playlist_items

```
create table public.book_playlist_items (
  id serial not null,
  playlist_id integer not null,
  book_id integer not null,
  position integer not null default 0,
  created_at timestamp with time zone not null default now(),
  constraint book_playlist_items_pkey primary key (id)
) TABLESPACE pg_default;
```

14. book_history

```
create table public.book_history (
  id serial not null,
  user_id integer not null,
  book_id integer not null,
  updated_at timestamp with time zone not null default now(),
  constraint book_history_pkey primary key (id),
  constraint book_history_user_book_unique unique (user_id, book_id)
) TABLESPACE pg_default;
```

15. attachments

```
create table public.attachments (
  id serial not null,
  message_id integer null,
  uploader_id integer not null,
  original_filename text not null,
  stored_filename text not null,
  mime_type text not null,
  size integer not null,
  width integer null,
  height integer null,
  created_at timestamp with time zone not null default now(),
  duration integer null,
  filename text null,
  storage_key text null,
  constraint attachments_pkey primary key (id),
```

```
  constraint attachments_message_id_fkey foreign KEY (message_id) references
messages (id) on delete CASCADE,
  constraint attachments_uploader_id_fkey foreign KEY (uploader_id) references
users (id) on delete CASCADE
) TABLESPACE pg_default;

create index IF not exists idx_attachments_message on public.attachments using
btree (message_id) TABLESPACE pg_default;

create index IF not exists idx_attachments_uploader on public.attachments using
btree (uploader_id) TABLESPACE pg_default;
```