lib/app.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L004 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L005 | import 'package:instproject/features/auth/data/firebase_authrepo.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/data/firebase_authrepo.dart';

```
L006 | import 'package:instproject/features/auth/data/fire_profile_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/data/fire_profile_repo.dart';

```
L007 | import 'package:instproject/features/auth/domain/repos/auth_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/repos/auth_repo.dart';

```
L008 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L009 | import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';

```
L010 | import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';

```
L011 | import 'package:instproject/features/auth/presentation/pages/auth_page.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/pages/auth_page.dart';

```
L012 | import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';

```
L013 | import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';

```
L014 | import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';

```
L015 | import 'package:instproject/features/chatgroup/data/fire_group_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/data/fire_group_repo.dart';

```
L016 | import 'package:instproject/features/chatgroup/pages/create_group_page.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/pages/create_group_page.dart';

```
L017 | import 'package:instproject/features/posts/data/fire_post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/fire_post_repo.dart';

```
L018 | import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';

```
L019 | import 'package:instproject/features/posts/domain/post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/domain/post_repo.dart';

```
L020 | import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';

```
L021 | import 'package:instproject/features/posts/presentation/pages/saved_posts_page.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/pages/saved_posts_page.dart';

```
L022 | import 'package:instproject/features/posts/presentation/pages/search_posts.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/pages/search_posts.dart';

```
L023 | import 'package:instproject/features/storage/domain/storage_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/storage/domain/storage_repo.dart';

```
L024 | import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';

```
L025 | import 'package:instproject/main_shell.dart';
```
-> Imports module or package: import 'package:instproject/main_shell.dart';

```
L026 | import 'package:instproject/splash_screen.dart';
```
-> Imports module or package: import 'package:instproject/splash_screen.dart';

```
L027 | import 'package:instproject/themes/theme.dart';
```
-> Imports module or package: import 'package:instproject/themes/theme.dart';

```
L028 | import 'package:instproject/themes/theme_cubit.dart';
```
-> Imports module or package: import 'package:instproject/themes/theme_cubit.dart';

```
L029 |
```
-> Blank line

```
L030 | class MyApp extends StatelessWidget {
```
-> Class declaration: class MyApp extends StatelessWidget {

```
L031 |   final firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final firestore = FirebaseFirestore.instance;

```
L032 |   final authRepo = FirebaseAuthRepo();
```
-> Variable declaration: final authRepo = FirebaseAuthRepo();

```
L033 |   final profileRepo = FireProfileRepo();
```
-> Variable declaration: final profileRepo = FireProfileRepo();

```
L034 |   final storageRepo = AppwriteStorageRepo();
```
-> Variable declaration: final storageRepo = AppwriteStorageRepo();

```
L035 |   final postRepo = FirePostRepo();
```
-> Variable declaration: final postRepo = FirePostRepo();

```
L036 |   final postStorageRepo = AppwritePostStorageRepo();
```
-> Variable declaration: final postStorageRepo = AppwritePostStorageRepo();

```
L037 |   final groupRepo = FireGroupRepo();
```
-> Variable declaration: final groupRepo = FireGroupRepo();

```
L038 |   final chatRepo = FireChatRepo();
```
-> Variable declaration: final chatRepo = FireChatRepo();

```
L039 |
```
-> Blank line

```
L040 |   MyApp({super.key});
```
-> Code: MyApp({super.key});

```
L041 |
```
-> Blank line

```
L042 |   @override
```
-> Annotation/Decorator: @override

```
L043 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L044 |     return MultiRepositoryProvider(
```
-> Return statement: return MultiRepositoryProvider(

```
L045 |       providers: [
```
-> Code: providers: [

```
L046 |         RepositoryProvider.value(value: firestore),
```
-> Code: RepositoryProvider.value(value: firestore),

```
L047 |         RepositoryProvider<AuthRepo>.value(value: authRepo),
```
-> Code: RepositoryProvider<AuthRepo>.value(value: authRepo),

```
L048 |         RepositoryProvider<FireProfileRepo>.value(value: profileRepo),
```
-> Code: RepositoryProvider<FireProfileRepo>.value(value: profileRepo),

```
L049 |         RepositoryProvider<StorageRepo>.value(value: storageRepo),
```
-> Code: RepositoryProvider<StorageRepo>.value(value: storageRepo),

```
L050 |         RepositoryProvider<AppwriteStorageRepo>.value(value: storageRepo),
```
-> Code: RepositoryProvider<AppwriteStorageRepo>.value(value: storageRepo),

```
L051 |         RepositoryProvider<PostRepo>.value(value: postRepo),
```
-> Code: RepositoryProvider<PostRepo>.value(value: postRepo),

```
L052 |         RepositoryProvider<AppwritePostStorageRepo>.value(
```
-> Code: RepositoryProvider<AppwritePostStorageRepo>.value(

```
L053 |           value: postStorageRepo,
```
-> Code: value: postStorageRepo,

```
L054 |         ),
```
-> Code:),

```
L055 |         RepositoryProvider.value(value: groupRepo),
```
-> Code: RepositoryProvider.value(value: groupRepo),

```
L056 |         RepositoryProvider.value(value: chatRepo),
```
-> Code: RepositoryProvider.value(value: chatRepo),

```
L057 |       ],
```
-> Code:],

```
L058 |       child: MultiBlocProvider(
```
-> Code: child: MultiBlocProvider(

```
L059 |         providers: [
```
-> Code: providers: [

```
L060 |           BlocProvider(
```
-> Code: BlocProvider(

```
L061 |             create: (_) => AuthCubit(authRepo: authRepo)..checkAuth(),
```
-> Code: create: (_) => AuthCubit(authRepo: authRepo)..checkAuth(),

```
L062 |           ),
```
-> Code:),

```
L063 |           BlocProvider(
```
-> Code: BlocProvider(

```
L064 |             create: (_) => ProfileCubit(
```
-> Code: create: (_) => ProfileCubit(

```
L065 |               profileRepo: profileRepo,
```
-> Code: profileRepo: profileRepo,

```
L066 |               storageRepo: storageRepo,
```
-> Code: storageRepo: storageRepo,

```
L067 |             ),
```
-> Code:),

```
L068 |           ),
```
-> Code:),

```
L069 |           BlocProvider(
```
-> Code: BlocProvider(

```
L070 |             create: (_) =>
```
-> Code: create: (_) =>

```
L071 |                 PostCubit(postRepo: postRepo, storageRepo: postStorageRepo),
  -> Code: PostCubit(postRepo: postRepo, storageRepo: postStorageRepo),
L072 |           ),
  -> Code: ),
L073 |
  -> Blank line
L074 |           BlocProvider(create: (_) => GroupCubit(groupRepo)..loadGroups()),
  -> Code: BlocProvider(create: (_) => GroupCubit(groupRepo)..loadGroups()),
L075 |           BlocProvider(
  -> Code: BlocProvider(
L076 |             create: (_) => ChatCubit(repo: chatRepo, groupId: ''),
  -> Code: create: (_) => ChatCubit(repo: chatRepo, groupId: ''),
L077 |           ),
  -> Code: ),
L078 |           BlocProvider(create: (_) => ThemeCubit()),
  -> Code: BlocProvider(create: (_) => ThemeCubit()),
L079 |         ],
  -> Code: ],
L080 |         child: BlocBuilder<ThemeCubit, ThemeMode>(
  -> Code: child: BlocBuilder<ThemeCubit, ThemeMode>(
L081 |           builder: (context, themeMode) {
  -> Code: builder: (context, themeMode) {
L082 |             return MaterialApp(
  -> Return statement: return MaterialApp(
L083 |               debugShowCheckedModeBanner: false,
  -> Code: debugShowCheckedModeBanner: false,
L084 |               theme: lightMode,
  -> Code: theme: lightMode,
L085 |               darkTheme: darkMode,
  -> Code: darkTheme: darkMode,
L086 |               themeMode: themeMode,
  -> Code: themeMode: themeMode,
L087 |               routes: {
  -> Code: routes: {
L088 |                 '/auth': (context) => const AuthPage(),
  -> Code: '/auth': (context) => const AuthPage(),
L089 |                 '/main': (context) => const MainShell(),
  -> Code: '/main': (context) => const MainShell(),
L090 |                 '/splash': (context) => const SplashScreen(),
  -> Code: '/splash': (context) => const SplashScreen(),
L091 |                 '/search': (context) => const SearchPostsPage(),
  -> Code: '/search': (context) => const SearchPostsPage(),
L092 |                 '/create_group': (context) => const CreateGroupPage(),
  -> Code: '/create_group': (context) => const CreateGroupPage(),
L093 |                 '/save': (context) {
  -> Code: '/save': (context) {
L094 |                   final currentUser = FirebaseAuth.instance.currentUser;
  -> Variable declaration: final currentUser = FirebaseAuth.instance.currentUser;
L095 |                   return SavedPostsPage(userId: currentUser!.uid);
  -> Return statement: return SavedPostsPage(userId: currentUser!.uid);
L096 |                 },
  -> Code: },
L097 |               },
  -> Code: },
L098 |               home: BlocListener<AuthCubit, AuthState>(
  -> Code: home: BlocListener<AuthCubit, AuthState>(
L099 |                 listener: (context, state) {
  -> Code: listener: (context, state) {
L100 |                   if (state is Unauthenticated) {
  -> Control flow statement: if (state is Unauthenticated) {
L101 |                     Future.microtask(() {
  -> Function/method declaration or async return type: Future.microtask(() {
L102 |                       Navigator.of(
  -> Code: Navigator.of(
L103 |                         context,
  -> Code: context,
L104 |                       ).pushNamedAndRemoveUntil('/auth', (route) => false);
  -> Short arrow function/expression: ).pushNamedAndRemoveUntil('/auth', (route) => false);
L105 |                     });
  -> Code: });
L106 |                   } else if (state is Authenticated) {
  -> Code: } else if (state is Authenticated) {
```

```
L107 |                       Future.microtask(() {
```
-> Function/method declaration or async return type: Future.microtask(() {

```
L108 |                         Navigator.of(
```
-> Code: Navigator.of(

```
L109 |                           context,
```
-> Code: context,

```
L110 |                         ).pushNamedAndRemoveUntil('/main', (route) => false);
```
-> Short arrow function/expression:).pushNamedAndRemoveUntil('/main', (route) => false);

```
L111 |                       });
```
-> Code: });

```
L112 |                     }
```
-> Code: }

```
L113 |                   },
```
-> Code: },

```
L114 |                   child: const SplashScreen(),
```
-> Code: child: const SplashScreen(),

```
L115 |                 ),
```
-> Code:),

```
L116 |               );
```
-> Code:);

```
L117 |             },
```
-> Code: },

```
L118 |           ),
```
-> Code:),

```
L119 |         ),
```
-> Code:),

```
L120 |       );
```
-> Code:);

```
L121 |     }
```
-> Code: }

```
L122 | }
```
-> Code: }

lib/core/appconfig.dart

```
L001 | const String appwriteEndpoint = 'https://nyc.cloud.appwrite.io/v1';
```
-> Variable declaration: const String appwriteEndpoint = 'https://nyc.cloud.appwrite.io/v1';

```
L002 | const String projectId1 = '68f2d630001e0e7d0bcd';
```
-> Variable declaration: const String projectId1 = '68f2d630001e0e7d0bcd';

```
L003 | const String bucketId1 = '68f3d11d00112560d57f';
```
-> Variable declaration: const String bucketId1 = '68f3d11d00112560d57f';

```
L004 | const String apiKey =
'standard_eb27f226fa1c2f9330b33259965a46ac661b89be2328daa3328edb864c3e1a7b2a000e00ded76ad168ca6beb21c13e32b9fd5c6dd3
6fd2884eeaac019563f50b705d991051eb94fb5eb3cc461dccf40f4f85f4157726ce935871e0a68a3c17ac0d23112886cb9506cfe04c15e572d7
1a8d3d35e126b72d9a36906fb6c4c05849';
```
-> Variable declaration: const String apiKey =
'standard_eb27f226fa1c2f9330b33259965a46ac661b89be2328daa3328edb864c3e1a7b2a000e00ded76ad168ca6beb21c13e32b9fd5c6dd36fd2884eeaac01
9563f50b705d991051eb94fb5eb3cc461dccf40f4f85f4157726ce935871e0a68a3c17ac0d23112886cb9506cfe04c15e572d71a8d3d35e126b72d9a36906fb6c4
c05849';

```
L005 |
```
-> Blank line

```
L006 |
```
-> Blank line

```
L007 |
```
-> Blank line

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'dart:convert';
```
-> Imports module or package: import 'dart:convert';

```
L003 | import 'package:http/http.dart' as http;
```
-> Imports module or package: import 'package:http/http.dart' as http;

```
L004 | import 'package:instproject/core/appconfig.dart';
```
-> Imports module or package: import 'package:instproject/core/appconfig.dart';

```
L005 |
```
-> Blank line

```
L006 |
```
-> Blank line

```
L007 | class AppwriteStorageAPI {
```
-> Class declaration: class AppwriteStorageAPI {

```
L008 |
```
-> Blank line

```
L009 |   static Future<String?> uploadImage(File file, String fileName) async {
```
-> Code: static Future<String?> uploadImage(File file, String fileName) async {

```
L010 |     try {
```
-> Code: try {

```
L011 |       final url = Uri.parse(
```
-> Variable declaration: final url = Uri.parse(

```
L012 |         '$appwriteEndpoint/storage/buckets/$bucketId1/files',
```
-> Code: '$appwriteEndpoint/storage/buckets/$bucketId1/files',

```
L013 |       );
```
-> Code:);

```
L014 |
```
-> Blank line

```
L015 |       final request = http.MultipartRequest('POST', url)
```
-> Variable declaration: final request = http.MultipartRequest('POST', url)

```
L016 |         ..headers['X-Appwrite-Project'] = projectId1
```
-> Code: ..headers['X-Appwrite-Project'] = projectId1

```
L017 |         ..headers['X-Appwrite-Key'] = apiKey
```
-> Code: ..headers['X-Appwrite-Key'] = apiKey

```
L018 |         ..fields['fileId'] = 'unique()'
```
-> Code: ..fields['fileId'] = 'unique()'

```
L019 |         ..files.add(
```
-> Code: ..files.add(

```
L020 |           await http.MultipartFile.fromPath(
```
-> Code: await http.MultipartFile.fromPath(

```
L021 |             'file',
```
-> Code: 'file',

```
L022 |             file.path,
```
-> Code: file.path,

```
L023 |             filename: fileName,
```
-> Code: filename: fileName,

```
L024 |           ),
```
-> Code:),

```
L025 |         );
```
-> Code:);

```
L026 |
```
-> Blank line

```
L027 |       final response = await request.send();
```
-> Variable declaration: final response = await request.send();

```
L028 |       final resBody = await response.stream.bytesToString();
```
-> Variable declaration: final resBody = await response.stream.bytesToString();

```
L029 |
```
-> Blank line

```
L030 |       if (response.statusCode == 201) {
```
-> Control flow statement: if (response.statusCode == 201) {

```
L031 |         final data = jsonDecode(resBody);
```
-> Variable declaration: final data = jsonDecode(resBody);

```
L032 |         final fileId = data['\$id'];
```
-> Variable declaration: final fileId = data['\$id'];

```
L033 |         print('Uploaded file ID: $fileId');
```
-> Code: print('Uploaded file ID: $fileId');

```
L034 |         return getFileUrl(fileId);
```
-> Return statement: return getFileUrl(fileId);

```
L035 |       } else {
  -> Code: } else {
L036 |         print(' Upload failed: ${response.statusCode} - $resBody');
  -> Code: print(' Upload failed: ${response.statusCode} - $resBody');
L037 |         return null;
  -> Return statement: return null;
L038 |       }
  -> Code: }
L039 |     } catch (e) {
  -> Code: } catch (e) {
L040 |       print('Exception during upload: $e');
  -> Code: print('Exception during upload: $e');
L041 |       return null;
  -> Return statement: return null;
L042 |     }
  -> Code: }
L043 |   }
  -> Code: }
L044 |
  -> Blank line
L045 |
  -> Blank line
L046 |   static Future<void> deleteFileByUrl(String fileUrl) async {
  -> Code: static Future<void> deleteFileByUrl(String fileUrl) async {
L047 |     try {
  -> Code: try {
L048 |       final fileId = extractFileIdFromUrl(fileUrl);
  -> Variable declaration: final fileId = extractFileIdFromUrl(fileUrl);
L049 |
  -> Blank line
L050 |       final url = Uri.parse(
  -> Variable declaration: final url = Uri.parse(
L051 |         '$appwriteEndpoint/storage/buckets/$bucketId1/files/$fileId',
  -> Code: '$appwriteEndpoint/storage/buckets/$bucketId1/files/$fileId',
L052 |       );
  -> Code: );
L053 |
  -> Blank line
L054 |       final response = await http.delete(
  -> Variable declaration: final response = await http.delete(
L055 |         url,
  -> Code: url,
L056 |         headers: {'X-Appwrite-Project': projectId1, 'X-Appwrite-Key': apiKey},
  -> Code: headers: {'X-Appwrite-Project': projectId1, 'X-Appwrite-Key': apiKey},
L057 |       );
  -> Code: );
L058 |
  -> Blank line
L059 |       if (response.statusCode == 204) {
  -> Control flow statement: if (response.statusCode == 204) {
L060 |         print(' File deleted successfully.');
  -> Code: print(' File deleted successfully.');
L061 |       } else {
  -> Code: } else {
L062 |         print(
  -> Code: print(
L063 |           ' Failed to delete file: ${response.statusCode} - ${response.body}',
  -> Code: ' Failed to delete file: ${response.statusCode} - ${response.body}',
L064 |         );
  -> Code: );
L065 |       }
  -> Code: }
L066 |     } catch (e) {
  -> Code: } catch (e) {
L067 |       print(' Exception during delete: $e');
  -> Code: print(' Exception during delete: $e');
L068 |     }
  -> Code: }
L069 |   }
  -> Code: }
L070 |
  -> Blank line
```

```
L071 |
```
-> Blank line

```
L072 |   static String getFileUrl(String fileId) {
```
-> Code: static String getFileUrl(String fileId) {

```
L073 |     return '$appwriteEndpoint/storage/buckets/$bucketId1/files/$fileId/view?project=$projectId1';
```
-> Return statement: return '$appwriteEndpoint/storage/buckets/$bucketId1/files/$fileId/view?project=$projectId1';

```
L074 |   }
```
-> Code: }

```
L075 |
```
-> Blank line

```
L076 |
```
-> Blank line

```
L077 |   static String extractFileIdFromUrl(String url) {
```
-> Code: static String extractFileIdFromUrl(String url) {

```
L078 |     try {
```
-> Code: try {

```
L079 |       final parts = url.split('/');
```
-> Variable declaration: final parts = url.split('/');

```
L080 |       final fileIdIndex = parts.indexOf('files') + 1;
```
-> Variable declaration: final fileIdIndex = parts.indexOf('files') + 1;

```
L081 |       if (fileIdIndex > 0 && fileIdIndex < parts.length) {
```
-> Control flow statement: if (fileIdIndex > 0 && fileIdIndex < parts.length) {

```
L082 |         return parts[fileIdIndex];
```
-> Return statement: return parts[fileIdIndex];

```
L083 |       }
```
-> Code: }

```
L084 |       throw Exception('Invalid Appwrite file URL');
```
-> Code: throw Exception('Invalid Appwrite file URL');

```
L085 |     } catch (e) {
```
-> Code: } catch (e) {

```
L086 |       throw Exception('Failed to extract file ID: $e');
```
-> Code: throw Exception('Failed to extract file ID: $e');

```
L087 |     }
```
-> Code: }

```
L088 |   }
```
-> Code: }

```
L089 | }
```
-> Code: }

lib/features/aistudy/ai_study_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:google_generative_ai/google_generative_ai.dart';
```
-> Imports module or package: import 'package:google_generative_ai/google_generative_ai.dart';

```
L003 | import 'package:shared_preferences/shared_preferences.dart';
```
-> Imports module or package: import 'package:shared_preferences/shared_preferences.dart';

```
L004 |
```
-> Blank line

```
L005 |
```
-> Blank line

```
L006 | class AiStudy extends StatefulWidget {
```
-> Class declaration: class AiStudy extends StatefulWidget {

```
L007 |   const AiStudy({super.key});
```
-> Variable declaration: const AiStudy({super.key});

```
L008 |
```
-> Blank line

```
L009 |   @override
```
-> Annotation/Decorator: @override

```
L010 |   State<AiStudy> createState() => _AiStudyState();
```
-> Short arrow function/expression: State<AiStudy> createState() => _AiStudyState();

```
L011 | }
```
-> Code: }

```
L012 |
```
-> Blank line

```
L013 | class _AiStudyState extends State<AiStudy> {
```
-> Class declaration: class _AiStudyState extends State<AiStudy> {

```
L014 |   late final GenerativeModel chatModel;
```
-> Code: late final GenerativeModel chatModel;

```
L015 |   late final ChatSession chatSession;
```
-> Code: late final ChatSession chatSession;

```
L016 |   TextEditingController chatInput = TextEditingController();
```
-> Code: TextEditingController chatInput = TextEditingController();

```
L017 |   List<String> messages = [];
```
-> Code: List<String> messages = [];

```
L018 |
```
-> Blank line

```
L019 |   @override
```
-> Annotation/Decorator: @override

```
L020 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L021 |     super.initState();
```
-> Code: super.initState();

```
L022 |     _loadMessages();
```
-> Code: _loadMessages();

```
L023 |     chatModel = GenerativeModel(
```
-> Code: chatModel = GenerativeModel(

```
L024 |       model: 'gemini-2.5-flash',
```
-> Code: model: 'gemini-2.5-flash',

```
L025 |       apiKey: 'AIzaSyD4NaXwHsB6CcYL3ZGosk8QTSJAlJtNT2E',
```
-> Code: apiKey: 'AIzaSyD4NaXwHsB6CcYL3ZGosk8QTSJAlJtNT2E',

```
L026 |       systemInstruction: Content('system', [
```
-> Code: systemInstruction: Content('system', [

```
L027 |         TextPart(
```
-> Code: TextPart(

```
L028 |           'Answer all questions related to education in Aden, and also general academic subjects like math,
science, and language. '
```
-> Code: 'Answer all questions related to education in Aden, and also general academic subjects like math, science, and language. '

```
L029 |           'Also answer all questions related to sports in Aden. '
```
-> Code: 'Also answer all questions related to sports in Aden. '

```
L030 |           'If you are asked about anything else, always reply: "I am not programmed for this."',
```
-> Code: 'If you are asked about anything else, always reply: "I am not programmed for this."',

```
L031 |         ),
```
-> Code:),

```
L032 |       ]),
```
-> Code:]),

```
L033 |     );
```
-> Code:);

```
L034 |     chatSession = chatModel.startChat();
```
-> Code: chatSession = chatModel.startChat();

```
L035 |   }
```
-> Code: }

```
L036 |
```
-> Blank line

```
L037 |
```
-> Blank line

```
L038 |   Future<void> _saveMessages() async {
```
-> Function/method declaration or async return type: Future<void> _saveMessages() async {

```
L039 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L040 |     await prefs.setStringList('ai_study_messages', messages);
```
-> Code: await prefs.setStringList('ai_study_messages', messages);

```
L041 |   }
```
-> Code: }

```
L042 |
```
-> Blank line

```
L043 |
```
-> Blank line

```
L044 |   Future<void> _loadMessages() async {
```
-> Function/method declaration or async return type: Future<void> _loadMessages() async {

```
L045 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L046 |     final savedMessages = prefs.getStringList('ai_study_messages');
```
-> Variable declaration: final savedMessages = prefs.getStringList('ai_study_messages');

```
L047 |     if (savedMessages != null) {
```
-> Control flow statement: if (savedMessages != null) {

```
L048 |       setState(() {
```
-> Code: setState(() {

```
L049 |         messages = savedMessages;
```
-> Code: messages = savedMessages;

```
L050 |       });
```
-> Code: });

```
L051 |     }
```
-> Code: }

```
L052 |   }
```
-> Code: }

```
L053 |
```
-> Blank line

```
L054 |
```
-> Blank line

```
L055 |   Future<void> generateChatOutput(String msg) async {
```
-> Function/method declaration or async return type: Future<void> generateChatOutput(String msg) async {

```
L056 |     if (msg.trim().isEmpty) return;
```
-> Control flow statement: if (msg.trim().isEmpty) return;

```
L057 |     setState(() {
```
-> Code: setState(() {

```
L058 |       messages.add('ME: $msg');
```
-> Code: messages.add('ME: $msg');

```
L059 |     });
```
-> Code: });

```
L060 |     await _saveMessages();
```
-> Code: await _saveMessages();

```
L061 |
```
-> Blank line

```
L062 |     chatInput.clear();
```
-> Code: chatInput.clear();

```
L063 |     final message = Content('user', [TextPart(msg)]);
```
-> Variable declaration: final message = Content('user', [TextPart(msg)]);

```
L064 |     final response = await chatSession.sendMessage(message);
```
-> Variable declaration: final response = await chatSession.sendMessage(message);

```
L065 |
```
-> Blank line

```
L066 |     final reply = response.text ?? '...';
```
-> Variable declaration: final reply = response.text ?? '...';

```
L067 |     setState(() {
```
-> Code: setState(() {

```
L068 |       messages.add('AI: $reply');
```
-> Code: messages.add('AI: $reply');

```
L069 |     });
```
-> Code: });

```
L070 |     await _saveMessages();
```
-> Code: await _saveMessages();

```
L071 |   }
```
-> Code: }

```
L072 |
```
-> Blank line

```
L073 |   @override
```
-> Annotation/Decorator: @override

```
L074 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L075 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L076 |       backgroundColor: Colors.black,
```
-> Code: backgroundColor: Colors.black,

```
L077 |       appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L078 |         backgroundColor: Colors.black,
```
-> Code: backgroundColor: Colors.black,

```
L079 |         title: ClipOval(
```
-> Code: title: ClipOval(

```
L080 |           child: Image.asset(
```
-> Code: child: Image.asset(

```
L081 |             'images/sai.png',
```
-> Code: 'images/sai.png',

```
L082 |             height: 50,
```
-> Code: height: 50,

```
L083 |             width: 50,
```
-> Code: width: 50,

```
L084 |             fit: BoxFit.contain,
```
-> Code: fit: BoxFit.contain,

```
L085 |           ),
```
-> Code:),

```
L086 |         ),
```
-> Code:),

```
L087 |       ),
```
-> Code:),

```
L088 |       body: Padding(
```
-> Code: body: Padding(

```
L089 |         padding: const EdgeInsets.all(8.0),
```
-> Code: padding: const EdgeInsets.all(8.0),

```
L090 |         child: ListView.builder(
```
-> Flutter UI widget usage: child: ListView.builder(

```
L091 |           itemCount: messages.length,
```
-> Code: itemCount: messages.length,

```
L092 |           itemBuilder: (context, index) {
```
-> Code: itemBuilder: (context, index) {

```
L093 |             bool isUser = messages[index].startsWith('ME:');
```
-> Code: bool isUser = messages[index].startsWith('ME:');

```
L094 |             return Align(
```
-> Return statement: return Align(

```
L095 |               alignment: isUser ? Alignment.centerRight : Alignment.centerLeft,
```
-> Code: alignment: isUser ? Alignment.centerRight : Alignment.centerLeft,

```
L096 |               child: Container(
```
-> Code: child: Container(

```
L097 |                 padding: const EdgeInsets.all(10),
```
-> Code: padding: const EdgeInsets.all(10),

```
L098 |                 margin: const EdgeInsets.symmetric(vertical: 6),
```
-> Code: margin: const EdgeInsets.symmetric(vertical: 6),

```
L099 |                 decoration: BoxDecoration(
```
-> Code: decoration: BoxDecoration(

```
L100 |                   color: isUser ? Colors.brown: Colors.blueAccent,
```
-> Code: color: isUser ? Colors.brown: Colors.blueAccent,

```
L101 |                   borderRadius: BorderRadius.circular(15),
```
-> Code: borderRadius: BorderRadius.circular(15),

```
L102 |                 ),
```
-> Code:),

```
L103 |                 child: Text(
```
-> Code: child: Text(

```
L104 |                   messages[index],
```
-> Code: messages[index],

```
L105 |                   style: const TextStyle(color: Colors.white),
```
-> Code: style: const TextStyle(color: Colors.white),

```
L106 |                 ),
```
-> Code:),

```
L107 |               ),
  -> Code: ),
L108 |             );
  -> Code: );
L109 |           },
  -> Code: },
L110 |         ),
  -> Code: ),
L111 |       ),
  -> Code: ),
L112 |       bottomNavigationBar: Padding(
  -> Code: bottomNavigationBar: Padding(
L113 |         padding: const EdgeInsets.all(10),
  -> Code: padding: const EdgeInsets.all(10),
L114 |         child: TextFormField(
  -> Code: child: TextFormField(
L115 |           style: const TextStyle(color: Colors.white),
  -> Code: style: const TextStyle(color: Colors.white),
L116 |           controller: chatInput,
  -> Code: controller: chatInput,
L117 |           decoration: InputDecoration(
  -> Code: decoration: InputDecoration(
L118 |             hintStyle: const TextStyle(color: Colors.white70),
  -> Code: hintStyle: const TextStyle(color: Colors.white70),
L119 |             hintText: 'Ask Me',
  -> Code: hintText: 'Ask Me',
L120 |             enabledBorder: OutlineInputBorder(
  -> Code: enabledBorder: OutlineInputBorder(
L121 |               borderSide: const BorderSide(color: Colors.brown),
  -> Code: borderSide: const BorderSide(color: Colors.brown),
L122 |               borderRadius: BorderRadius.circular(20),
  -> Code: borderRadius: BorderRadius.circular(20),
L123 |             ),
  -> Code: ),
L124 |             focusedBorder: OutlineInputBorder(
  -> Code: focusedBorder: OutlineInputBorder(
L125 |               borderSide: const BorderSide(color: Colors.white),
  -> Code: borderSide: const BorderSide(color: Colors.white),
L126 |               borderRadius: BorderRadius.circular(20),
  -> Code: borderRadius: BorderRadius.circular(20),
L127 |             ),
  -> Code: ),
L128 |             suffixIcon: IconButton(
  -> Code: suffixIcon: IconButton(
L129 |               onPressed: () {
  -> Code: onPressed: () {
L130 |                 generateChatOutput(chatInput.text);
  -> Code: generateChatOutput(chatInput.text);
L131 |               },
  -> Code: },
L132 |               icon: const Icon(Icons.send, color: Colors.white),
  -> Code: icon: const Icon(Icons.send, color: Colors.white),
L133 |             ),
  -> Code: ),
L134 |           ),
  -> Code: ),
L135 |         ),
  -> Code: ),
L136 |       ),
  -> Code: ),
L137 |     );
  -> Code: );
L138 |   }
  -> Code: }
L139 | }
  -> Code: }
```

lib/features/auth/data/fire_profile_repo.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L002 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L003 | import 'package:instproject/features/auth/domain/repos/profile_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/repos/profile_repo.dart';

```
L004 |
```
-> Blank line

```
L005 |
```
-> Blank line

```
L006 | class FireProfileRepo implements ProfileRepo {
```
-> Class declaration: class FireProfileRepo implements ProfileRepo {

```
L007 |   final _firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final _firestore = FirebaseFirestore.instance;

```
L008 |
```
-> Blank line

```
L009 |   @override
```
-> Annotation/Decorator: @override

```
L010 |   Future<AppUser?> fetchUserProfile(String uid) async {
```
-> Function/method declaration or async return type: Future<AppUser?> fetchUserProfile(String uid) async {

```
L011 |     final doc = await _firestore.collection('users').doc(uid).get();
```
-> Variable declaration: final doc = await _firestore.collection('users').doc(uid).get();

```
L012 |     if (!doc.exists) return null;
```
-> Control flow statement: if (!doc.exists) return null;

```
L013 |     return AppUser.fromMap(doc.data()!);
```
-> Return statement: return AppUser.fromMap(doc.data()!);

```
L014 |   }
```
-> Code: }

```
L015 |
```
-> Blank line

```
L016 |   @override
```
-> Annotation/Decorator: @override

```
L017 |   Future<void> updateProfile(AppUser user) async {
```
-> Function/method declaration or async return type: Future<void> updateProfile(AppUser user) async {

```
L018 |     await _firestore.collection('users').doc(user.uid).update(user.toMap());
```
-> Code: await _firestore.collection('users').doc(user.uid).update(user.toMap());

```
L019 |   }
```
-> Code: }

```
L020 | }
```
-> Code: }

lib/features/auth/data/firebase_authrepo.dart

```
L001 | import 'package:firebase_auth/firebase_auth.dart';
  -> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';
L002 | import 'package:cloud_firestore/cloud_firestore.dart';
  -> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';
L003 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
  -> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';
L004 | import 'package:instproject/features/auth/domain/repos/auth_repo.dart';
  -> Imports module or package: import 'package:instproject/features/auth/domain/repos/auth_repo.dart';
L005 |
  -> Blank line
L006 | class FirebaseAuthRepo implements AuthRepo {
  -> Class declaration: class FirebaseAuthRepo implements AuthRepo {
L007 |   final FirebaseAuth _auth = FirebaseAuth.instance;
  -> Variable declaration: final FirebaseAuth _auth = FirebaseAuth.instance;
L008 |   final FirebaseFirestore _firestore = FirebaseFirestore.instance;
  -> Variable declaration: final FirebaseFirestore _firestore = FirebaseFirestore.instance;
L009 |
  -> Blank line
L010 |   @override
  -> Annotation/Decorator: @override
L011 |   Future<AppUser?> RegisterWithEmailAndPassword(
  -> Function/method declaration or async return type: Future<AppUser?> RegisterWithEmailAndPassword(
L012 |     String username,
  -> Code: String username,
L013 |     String email,
  -> Code: String email,
L014 |     String password,
  -> Code: String password,
L015 |   ) async {
  -> Code: ) async {
L016 |     try {
  -> Code: try {
L017 |       final userCredential = await _auth.createUserWithEmailAndPassword(
  -> Variable declaration: final userCredential = await _auth.createUserWithEmailAndPassword(
L018 |         email: email,
  -> Code: email: email,
L019 |         password: password,
  -> Code: password: password,
L020 |       );
  -> Code: );
L021 |
  -> Blank line
L022 |       final user = userCredential.user;
  -> Variable declaration: final user = userCredential.user;
L023 |       if (user == null) return null;
  -> Control flow statement: if (user == null) return null;
L024 |
  -> Blank line
L025 |       await user.updateDisplayName(username);
  -> Code: await user.updateDisplayName(username);
L026 |
  -> Blank line
L027 |
  -> Blank line
L028 |       final appUser = AppUser(
  -> Variable declaration: final appUser = AppUser(
L029 |         uid: user.uid,
  -> Code: uid: user.uid,
L030 |         name: username,
  -> Code: name: username,
L031 |         email: email,
  -> Code: email: email,
L032 |         bio: "Hey there! I'm using InstProject ",
  -> Code: bio: "Hey there! I'm using InstProject ",
L033 |         profileImg:
  -> Code: profileImg:
L034 |             "https://cdn-icons-png.flaticon.com/512/3135/3135715.png",
  -> Code: "https://cdn-icons-png.flaticon.com/512/3135/3135715.png",
```

```
L035 |       );
```
-> Code:);

```
L036 |
```
-> Blank line

```
L037 |       await _firestore.collection('users').doc(user.uid).set(appUser.toMap());
```
-> Code: await _firestore.collection('users').doc(user.uid).set(appUser.toMap());

```
L038 |
```
-> Blank line

```
L039 |       return appUser;
```
-> Return statement: return appUser;

```
L040 |     } catch (e) {
```
-> Code: } catch (e) {

```
L041 |       print(" Registration Error: $e");
```
-> Code: print(" Registration Error: $e");

```
L042 |       rethrow;
```
-> Code: rethrow;

```
L043 |     }
```
-> Code: }

```
L044 |   }
```
-> Code: }

```
L045 |
```
-> Blank line

```
L046 |   @override
```
-> Annotation/Decorator: @override

```
L047 |   Future<AppUser?> LoginWithEmailAndPassword(
```
-> Function/method declaration or async return type: Future<AppUser?> LoginWithEmailAndPassword(

```
L048 |     String email,
```
-> Code: String email,

```
L049 |     String password,
```
-> Code: String password,

```
L050 |   ) async {
```
-> Code:) async {

```
L051 |     try {
```
-> Code: try {

```
L052 |       final userCredential = await _auth.signInWithEmailAndPassword(
```
-> Variable declaration: final userCredential = await _auth.signInWithEmailAndPassword(

```
L053 |         email: email,
```
-> Code: email: email,

```
L054 |         password: password,
```
-> Code: password: password,

```
L055 |       );
```
-> Code:);

```
L056 |       final user = userCredential.user;
```
-> Variable declaration: final user = userCredential.user;

```
L057 |       if (user == null) return null;
```
-> Control flow statement: if (user == null) return null;

```
L058 |
```
-> Blank line

```
L059 |       final doc = await _firestore.collection('users').doc(user.uid).get();
```
-> Variable declaration: final doc = await _firestore.collection('users').doc(user.uid).get();

```
L060 |
```
-> Blank line

```
L061 |       if (!doc.exists) return null;
```
-> Control flow statement: if (!doc.exists) return null;

```
L062 |
```
-> Blank line

```
L063 |       return AppUser.fromMap(doc.data()!);
```
-> Return statement: return AppUser.fromMap(doc.data()!);

```
L064 |     } catch (e) {
```
-> Code: } catch (e) {

```
L065 |       print(" Login Error: $e");
```
-> Code: print(" Login Error: $e");

```
L066 |       rethrow;
```
-> Code: rethrow;

```
L067 |     }
```
-> Code: }

```
L068 |   }
```
-> Code: }

```
L069 |
```
-> Blank line

```
L070 |   @override
```
-> Annotation/Decorator: @override

```
L071 |   Future<void> Logout() async {
```
-> Function/method declaration or async return type: Future<void> Logout() async {

```
L072 |     await _auth.signOut();
```
-> Code: await _auth.signOut();

```
L073 |   }
```
-> Code: }

```
L074 |
```
-> Blank line

```
L075 |   @override
```
-> Annotation/Decorator: @override

```
L076 |   Future<AppUser?> getCurrentUser() async {
```
-> Function/method declaration or async return type: Future<AppUser?> getCurrentUser() async {

```
L077 |     final user = _auth.currentUser;
```
-> Variable declaration: final user = _auth.currentUser;

```
L078 |     if (user == null) return null;
```
-> Control flow statement: if (user == null) return null;

```
L079 |
```
-> Blank line

```
L080 |     final doc = await _firestore.collection('users').doc(user.uid).get();
```
-> Variable declaration: final doc = await _firestore.collection('users').doc(user.uid).get();

```
L081 |
```
-> Blank line

```
L082 |     if (!doc.exists) return null;
```
-> Control flow statement: if (!doc.exists) return null;

```
L083 |
```
-> Blank line

```
L084 |     return AppUser.fromMap(doc.data()!);
```
-> Return statement: return AppUser.fromMap(doc.data()!);

```
L085 |   }
```
-> Code: }

```
L086 | }
```
-> Code: }

lib/features/auth/domain/entities/app_user.dart

```
L001 | class AppUser {
  -> Class declaration: class AppUser {
L002 |   final String uid;
  -> Variable declaration: final String uid;
L003 |   final String name;
  -> Variable declaration: final String name;
L004 |   final String email;
  -> Variable declaration: final String email;
L005 |   final String bio;
  -> Variable declaration: final String bio;
L006 |   final String profileImg;
  -> Variable declaration: final String profileImg;
L007 |
  -> Blank line
L008 |   AppUser({
  -> Code: AppUser({
L009 |     required this.uid,
  -> Code: required this.uid,
L010 |     required this.name,
  -> Code: required this.name,
L011 |     required this.email,
  -> Code: required this.email,
L012 |     required this.bio,
  -> Code: required this.bio,
L013 |     required this.profileImg,
  -> Code: required this.profileImg,
L014 |   });
  -> Code: });
L015 |
  -> Blank line
L016 |   AppUser copyWith({
  -> Code: AppUser copyWith({
L017 |     String? name,
  -> Code: String? name,
L018 |     String? email,
  -> Code: String? email,
L019 |     String? bio,
  -> Code: String? bio,
L020 |     String? profileImg,
  -> Code: String? profileImg,
L021 |   }) {
  -> Code: }) {
L022 |     return AppUser(
  -> Return statement: return AppUser(
L023 |       uid: uid,
  -> Code: uid: uid,
L024 |       name: name ?? this.name,
  -> Code: name: name ?? this.name,
L025 |       email: email ?? this.email,
  -> Code: email: email ?? this.email,
L026 |       bio: bio ?? this.bio,
  -> Code: bio: bio ?? this.bio,
L027 |       profileImg: profileImg ?? this.profileImg,
  -> Code: profileImg: profileImg ?? this.profileImg,
L028 |     );
  -> Code: );
L029 |   }
  -> Code: }
L030 |
  -> Blank line
L031 |   Map<String, dynamic> toMap() {
  -> Code: Map<String, dynamic> toMap() {
L032 |     return {
  -> Return statement: return {
L033 |       'uid': uid,
  -> Code: 'uid': uid,
L034 |       'name': name,
  -> Code: 'name': name,
```

```
L035 |       'email': email,
```
-> Code: 'email': email,

```
L036 |       'bio': bio,
```
-> Code: 'bio': bio,

```
L037 |       'profileImg': profileImg,
```
-> Code: 'profileImg': profileImg,

```
L038 |     };
```
-> Code: };

```
L039 |   }
```
-> Code: }

```
L040 |
```
-> Blank line

```
L041 |   factory AppUser.fromMap(Map<String, dynamic> map) {
```
-> Code: factory AppUser.fromMap(Map<String, dynamic> map) {

```
L042 |     return AppUser(
```
-> Return statement: return AppUser(

```
L043 |       uid: map['uid'] ?? '',
```
-> Code: uid: map['uid'] ?? '',

```
L044 |       name: map['name'] ?? '',
```
-> Code: name: map['name'] ?? '',

```
L045 |       email: map['email'] ?? '',
```
-> Code: email: map['email'] ?? '',

```
L046 |       bio: map['bio'] ?? '',
```
-> Code: bio: map['bio'] ?? '',

```
L047 |       profileImg: map['profileImg'] ?? '',
```
-> Code: profileImg: map['profileImg'] ?? '',

```
L048 |     );
```
-> Code:);

```
L049 |   }
```
-> Code: }

```
L050 | }
```
-> Code: }

lib/features/auth/domain/entities/profile_define.dart

```
L001 | class ProfileDefine {
  -> Class declaration: class ProfileDefine {
L002 |   final String name;
  -> Variable declaration: final String name;
L003 |   final String email;
  -> Variable declaration: final String email;
L004 |   final String bio;
  -> Variable declaration: final String bio;
L005 |
  -> Blank line
L006 |   ProfileDefine({required this.name, required this.email, required this.bio});
  -> Code: ProfileDefine({required this.name, required this.email, required this.bio});
L007 |
  -> Blank line
L008 |   Map<String, dynamic> toJson() => {'name': name, 'email': email, 'bio': bio};
  -> Short arrow function/expression: Map<String, dynamic> toJson() => {'name': name, 'email': email, 'bio': bio};
L009 |
  -> Blank line
L010 |   factory ProfileDefine.fromJson(Map<String, dynamic> json) =>
  -> Code: factory ProfileDefine.fromJson(Map<String, dynamic> json) =>
L011 |       ProfileDefine(
  -> Code: ProfileDefine(
L012 |         name: json['name'] ?? "",
  -> Code: name: json['name'] ?? "",
L013 |          email: json['email'] ?? "",
  -> Code: email: json['email'] ?? "",
L014 |           bio: json['bio'] ?? "");
  -> Code: bio: json['bio'] ?? "");
L015 | }
  -> Code: }
```

```
L001 | // import 'package:instproject/features/auth/domain/entities/app_user.dart';
  -> Comment:  import 'package:instproject/features/auth/domain/entities/app_user.dart';
L002 |
  -> Blank line
L003 | // class ProfileUser extends AppUser {
  -> Comment:  class ProfileUser extends AppUser {
L004 | //   final String bio;
  -> Comment:   final String bio;
L005 | //   final String profileImg;
  -> Comment:   final String profileImg;
L006 |
  -> Blank line
L007 | //   ProfileUser({
  -> Comment:   ProfileUser({
L008 | //     required super.uid,
  -> Comment:    required super.uid,
L009 | //     required super.name,
  -> Comment:    required super.name,
L010 | //     required super.email,
  -> Comment:    required super.email,
L011 | //     required this.bio,
  -> Comment:    required this.bio,
L012 | //     required this.profileImg,
  -> Comment:    required this.profileImg,
L013 | //   });
  -> Comment:   });
L014 |
  -> Blank line
L015 | //   ProfileUser copyWith({String? newBio, String? newProfileImg, required String bio, required String
profileImg}) {
  -> Comment:   ProfileUser copyWith({String? newBio, String? newProfileImg, required String bio, required String profileImg}) {
L016 | //     return ProfileUser(
  -> Comment:    return ProfileUser(
L017 | //       uid: uid,
  -> Comment:     uid: uid,
L018 | //       name: name,
  -> Comment:     name: name,
L019 | //       email: email,
  -> Comment:     email: email,
L020 | //       bio: newBio ?? bio,
  -> Comment:     bio: newBio ?? bio,
L021 | //       profileImg: newProfileImg ?? profileImg,
  -> Comment:     profileImg: newProfileImg ?? profileImg,
L022 | //     );
  -> Comment:    );
L023 | //   }
  -> Comment:   }
L024 |
  -> Blank line
L025 | //   Map<String, dynamic> toJson() => {
  -> Comment:   Map<String, dynamic> toJson() => {
L026 | //     'uid': uid,
  -> Comment:    'uid': uid,
L027 | //     'name': name,
  -> Comment:    'name': name,
L028 | //     'email': email,
  -> Comment:    'email': email,
L029 | //     'bio': bio,
  -> Comment:    'bio': bio,
L030 | //     'profileImg': profileImg,
  -> Comment:    'profileImg': profileImg,
L031 | //   };
  -> Comment:   };
L032 |
  -> Blank line
L033 | //   factory ProfileUser.fromJson(Map<String, dynamic> json) => ProfileUser(
  -> Comment:   factory ProfileUser.fromJson(Map<String, dynamic> json) => ProfileUser(
L034 | //     uid: json['uid'],
  -> Comment:    uid: json['uid'],
```

```
L035 | //      name: json['name'] ,
```
-> Comment: name: json['name'] ,

```
L036 | //      email: json['email'],
```
-> Comment: email: json['email'],

```
L037 | //      bio: json['bio'] ?? '',
```
-> Comment: bio: json['bio'] ?? '',

```
L038 | //      profileImg: json['profileImg'] ?? '',
```
-> Comment: profileImg: json['profileImg'] ?? '',

```
L039 | //    );
```
-> Comment:);

```
L040 |
```
-> Blank line

```
L041 |
```
-> Blank line

```
L042 | // }
```
-> Comment: }

lib/features/auth/domain/repos/auth_repo.dart

```
L001 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L002 |
```
-> Blank line

```
L003 | abstract class AuthRepo {
```
-> Class declaration (complex): abstract class AuthRepo {

```
L004 |   Future<AppUser?> LoginWithEmailAndPassword(String email, String password);
```
-> Function/method declaration or async return type: Future<AppUser?> LoginWithEmailAndPassword(String email, String password);

```
L005 |   Future<AppUser?> RegisterWithEmailAndPassword(
```
-> Function/method declaration or async return type: Future<AppUser?> RegisterWithEmailAndPassword(

```
L006 |     String username,
```
-> Code: String username,

```
L007 |     String email,
```
-> Code: String email,

```
L008 |     String password,
```
-> Code: String password,

```
L009 |   );
```
-> Code:);

```
L010 |
```
-> Blank line

```
L011 |   Future<void> Logout();
```
-> Function/method declaration or async return type: Future<void> Logout();

```
L012 |
```
-> Blank line

```
L013 |   Future<AppUser?> getCurrentUser();
```
-> Function/method declaration or async return type: Future<AppUser?> getCurrentUser();

```
L014 | }
```
-> Code: }

lib/features/auth/domain/repos/profile_repo.dart

```
L001 |
```
-> Blank line

```
L002 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L003 |
```
-> Blank line

```
L004 |
```
-> Blank line

```
L005 | abstract class ProfileRepo {
```
-> Class declaration (complex): abstract class ProfileRepo {

```
L006 |   Future<AppUser?> fetchUserProfile(String uid);
```
-> Function/method declaration or async return type: Future<AppUser?> fetchUserProfile(String uid);

```
L007 |    Future<void> updateProfile(AppUser updateProfile);
```
-> Function/method declaration or async return type: Future<void> updateProfile(AppUser updateProfile);

```
L008 |
```
-> Blank line

```
L009 |
```
-> Blank line

```
L010 | }
```
-> Code: }

```
L011 |
```
-> Blank line

```
L012 |
```
-> Blank line

lib/features/auth/presentation/bloc/auth_cubit.dart

```
L001 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L002 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L003 | import 'package:instproject/features/auth/domain/repos/auth_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/repos/auth_repo.dart';

```
L004 | import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';

```
L005 |
```
-> Blank line

```
L006 | class AuthCubit extends Cubit<AuthState> {
```
-> Class declaration: class AuthCubit extends Cubit<AuthState> {

```
L007 |   final AuthRepo authRepo;
```
-> Variable declaration: final AuthRepo authRepo;

```
L008 |   AppUser? _currentUser;
```
-> Code: AppUser? _currentUser;

```
L009 |
```
-> Blank line

```
L010 |   AuthCubit({required this.authRepo}) : super(AuthInitial());
```
-> Code: AuthCubit({required this.authRepo}) : super(AuthInitial());

```
L011 |
```
-> Blank line

```
L012 |   AppUser? get currentUser => _currentUser;
```
-> Short arrow function/expression: AppUser? get currentUser => _currentUser;

```
L013 |
```
-> Blank line

```
L014 |
```
-> Blank line

```
L015 |   Future<void> checkAuth() async {
```
-> Function/method declaration or async return type: Future<void> checkAuth() async {

```
L016 |     try {
```
-> Code: try {

```
L017 |       emit(AuthLoading());
```
-> Code: emit(AuthLoading());

```
L018 |       final user = await authRepo.getCurrentUser();
```
-> Variable declaration: final user = await authRepo.getCurrentUser();

```
L019 |       if (user != null) {
```
-> Control flow statement: if (user != null) {

```
L020 |         _currentUser = user;
```
-> Code: _currentUser = user;

```
L021 |         emit(Authenticated(user));
```
-> Code: emit(Authenticated(user));

```
L022 |       } else {
```
-> Code: } else {

```
L023 |         emit(Unauthenticated());
```
-> Code: emit(Unauthenticated());

```
L024 |       }
```
-> Code: }

```
L025 |     } catch (e) {
```
-> Code: } catch (e) {

```
L026 |       emit(AuthErorr('Failed to check auth: $e'));
```
-> Code: emit(AuthErorr('Failed to check auth: $e'));

```
L027 |     }
```
-> Code: }

```
L028 |   }
```
-> Code: }

```
L029 |
```
-> Blank line

```
L030 |
```
-> Blank line

```
L031 |   Future<void> register(String name, String email, String pass) async {
```
-> Function/method declaration or async return type: Future<void> register(String name, String email, String pass) async {

```
L032 |     try {
```
-> Code: try {

```
L033 |       emit(AuthLoading());
```
-> Code: emit(AuthLoading());

```
L034 |       final user = await authRepo.RegisterWithEmailAndPassword(
```
-> Variable declaration: final user = await authRepo.RegisterWithEmailAndPassword(

```
L035 |         name,
```
-> Code: name,

```
L036 |         email,
```
-> Code: email,

```
L037 |         pass,
```
-> Code: pass,

```
L038 |       );
```
-> Code:);

```
L039 |       if (user != null) {
```
-> Control flow statement: if (user != null) {

```
L040 |         _currentUser = user;
```
-> Code: _currentUser = user;

```
L041 |         emit(Authenticated(user));
```
-> Code: emit(Authenticated(user));

```
L042 |       } else {
```
-> Code: } else {

```
L043 |         emit(Unauthenticated());
```
-> Code: emit(Unauthenticated());

```
L044 |       }
```
-> Code: }

```
L045 |     } catch (e) {
```
-> Code: } catch (e) {

```
L046 |       emit(AuthErorr('Registration failed: $e'));
```
-> Code: emit(AuthErorr('Registration failed: $e'));

```
L047 |     }
```
-> Code: }

```
L048 |   }
```
-> Code: }

```
L049 |
```
-> Blank line

```
L050 |
```
-> Blank line

```
L051 |   Future<void> login(String email, String pass) async {
```
-> Function/method declaration or async return type: Future<void> login(String email, String pass) async {

```
L052 |     try {
```
-> Code: try {

```
L053 |       emit(AuthLoading());
```
-> Code: emit(AuthLoading());

```
L054 |       final user = await authRepo.LoginWithEmailAndPassword(email, pass);
```
-> Variable declaration: final user = await authRepo.LoginWithEmailAndPassword(email, pass);

```
L055 |       if (user != null) {
```
-> Control flow statement: if (user != null) {

```
L056 |         _currentUser = user;
```
-> Code: _currentUser = user;

```
L057 |         emit(Authenticated(user));
```
-> Code: emit(Authenticated(user));

```
L058 |       } else {
```
-> Code: } else {

```
L059 |         emit(Unauthenticated());
```
-> Code: emit(Unauthenticated());

```
L060 |       }
```
-> Code: }

```
L061 |     } catch (e) {
```
-> Code: } catch (e) {

```
L062 |       emit(AuthErorr('Login failed: $e'));
```
-> Code: emit(AuthErorr('Login failed: $e'));

```
L063 |     }
```
-> Code: }

```
L064 |   }
```
-> Code: }

```
L065 |
```
-> Blank line

```
L066 |   Future<void> logout() async {
```
-> Function/method declaration or async return type: Future<void> logout() async {

```
L067 |     try {
```
-> Code: try {

```
L068 |       await authRepo.Logout();
```
-> Code: await authRepo.Logout();

```
L069 |       _currentUser = null;
```
-> Code: _currentUser = null;

```
L070 |       emit(Unauthenticated());
```
-> Code: emit(Unauthenticated());

```
L071 |     } catch (e) {
```
-> Code: } catch (e) {

```
L072 |       emit(AuthErorr('Failed to log out: $e'));
```
-> Code: emit(AuthErorr('Failed to log out: $e'));

```
L073 |     }
```
-> Code: }

```
L074 |   }
```
-> Code: }

```
L075 | }
```
-> Code: }

lib/features/auth/presentation/bloc/auth_states.dart

```
L001 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L002 |
```
-> Blank line

```
L003 | abstract class AuthState {}
```
-> Code: abstract class AuthState {}

```
L004 |
```
-> Blank line

```
L005 | class AuthInitial extends AuthState {}
```
-> Class declaration: class AuthInitial extends AuthState {}

```
L006 |
```
-> Blank line

```
L007 | class AuthLoading extends AuthState {}
```
-> Class declaration: class AuthLoading extends AuthState {}

```
L008 |
```
-> Blank line

```
L009 | class Authenticated extends AuthState {
```
-> Class declaration: class Authenticated extends AuthState {

```
L010 |   final AppUser user;
```
-> Variable declaration: final AppUser user;

```
L011 |   Authenticated(this.user);
```
-> Code: Authenticated(this.user);

```
L012 | }
```
-> Code: }

```
L013 |
```
-> Blank line

```
L014 | class Unauthenticated extends AuthState {}
```
-> Class declaration: class Unauthenticated extends AuthState {}

```
L015 |
```
-> Blank line

```
L016 | class AuthErorr extends AuthState {
```
-> Class declaration: class AuthErorr extends AuthState {

```
L017 |   final String message;
```
-> Variable declaration: final String message;

```
L018 |   AuthErorr(this.message);
```
-> Code: AuthErorr(this.message);

```
L019 | }
```
-> Code: }

```
L001 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L002 | import 'package:instproject/features/storage/domain/storage_repo.dart';
  -> Imports module or package: import 'package:instproject/features/storage/domain/storage_repo.dart';
L003 | import '../../domain/repos/profile_repo.dart';
  -> Imports module or package: import '../../domain/repos/profile_repo.dart';
L004 |
  -> Blank line
L005 | import 'profile_states.dart';
  -> Imports module or package: import 'profile_states.dart';
L006 |
  -> Blank line
L007 | class ProfileCubit extends Cubit<ProfileStates> {
  -> Class declaration: class ProfileCubit extends Cubit<ProfileStates> {
L008 |   final ProfileRepo profileRepo;
  -> Variable declaration: final ProfileRepo profileRepo;
L009 |   final StorageRepo storageRepo;
  -> Variable declaration: final StorageRepo storageRepo;
L010 |
  -> Blank line
L011 |   ProfileCubit({required this.profileRepo, required this.storageRepo})
  -> Code: ProfileCubit({required this.profileRepo, required this.storageRepo})
L012 |     : super(ProfileInitial());
  -> Code: : super(ProfileInitial());
L013 |
  -> Blank line
L014 |   Future<void> fetchUserProfile(String uid) async {
  -> Function/method declaration or async return type: Future<void> fetchUserProfile(String uid) async {
L015 |     try {
  -> Code: try {
L016 |       emit(ProfileLoading());
  -> Code: emit(ProfileLoading());
L017 |       final user = await profileRepo.fetchUserProfile(uid);
  -> Variable declaration: final user = await profileRepo.fetchUserProfile(uid);
L018 |
  -> Blank line
L019 |       if (user != null) {
  -> Control flow statement: if (user != null) {
L020 |         emit(ProfileLoaded(user));
  -> Code: emit(ProfileLoaded(user));
L021 |       } else {
  -> Code: } else {
L022 |         emit(ProfileError('Profile not found in Firestore'));
  -> Code: emit(ProfileError('Profile not found in Firestore'));
L023 |       }
  -> Code: }
L024 |     } catch (e) {
  -> Code: } catch (e) {
L025 |       emit(ProfileError('Error fetching profile: $e'));
  -> Code: emit(ProfileError('Error fetching profile: $e'));
L026 |     }
  -> Code: }
L027 |   }
  -> Code: }
L028 |
  -> Blank line
L029 |   Future<void> updateProfile({
  -> Function/method declaration or async return type: Future<void> updateProfile({
L030 |     required String uid,
  -> Code: required String uid,
L031 |     String? newBio,
  -> Code: String? newBio,
L032 |     String? imageMobilePath,
  -> Code: String? imageMobilePath,
L033 |   }) async {
  -> Code: }) async {
L034 |     emit(ProfileLoading());
  -> Code: emit(ProfileLoading());
```

```
L035 |
```
-> Blank line

```
L036 |     try {
```
-> Code: try {

```
L037 |       final currentUser = await profileRepo.fetchUserProfile(uid);
```
-> Variable declaration: final currentUser = await profileRepo.fetchUserProfile(uid);

```
L038 |       if (currentUser == null) {
```
-> Control flow statement: if (currentUser == null) {

```
L039 |         emit(ProfileError('User profile not found'));
```
-> Code: emit(ProfileError('User profile not found'));

```
L040 |         return;
```
-> Code: return;

```
L041 |       }
```
-> Code: }

```
L042 |
```
-> Blank line

```
L043 |       String? imageDownloadUrl;
```
-> Code: String? imageDownloadUrl;

```
L044 |
```
-> Blank line

```
L045 |
```
-> Blank line

```
L046 |       if (imageMobilePath != null && imageMobilePath.isNotEmpty) {
```
-> Control flow statement: if (imageMobilePath != null && imageMobilePath.isNotEmpty) {

```
L047 |         imageDownloadUrl = await storageRepo.uploadProfileImageMobile(
```
-> Code: imageDownloadUrl = await storageRepo.uploadProfileImageMobile(

```
L048 |           imageMobilePath,
```
-> Code: imageMobilePath,

```
L049 |           uid,
```
-> Code: uid,

```
L050 |         );
```
-> Code:);

```
L051 |
```
-> Blank line

```
L052 |         if (imageDownloadUrl == null) {
```
-> Control flow statement: if (imageDownloadUrl == null) {

```
L053 |           emit(ProfileError('Failed to upload image'));
```
-> Code: emit(ProfileError('Failed to upload image'));

```
L054 |           return;
```
-> Code: return;

```
L055 |         }
```
-> Code: }

```
L056 |       }
```
-> Code: }

```
L057 |
```
-> Blank line

```
L058 |
```
-> Blank line

```
L059 |       final updatedUser = currentUser.copyWith(
```
-> Variable declaration: final updatedUser = currentUser.copyWith(

```
L060 |         bio: newBio ?? currentUser.bio,
```
-> Code: bio: newBio ?? currentUser.bio,

```
L061 |         profileImg: imageDownloadUrl ?? currentUser.profileImg,
```
-> Code: profileImg: imageDownloadUrl ?? currentUser.profileImg,

```
L062 |       );
```
-> Code:);

```
L063 |
```
-> Blank line

```
L064 |
```
-> Blank line

```
L065 |       await profileRepo.updateProfile(updatedUser);
```
-> Code: await profileRepo.updateProfile(updatedUser);

```
L066 |
```
-> Blank line

```
L067 |
```
-> Blank line

```
L068 |       await fetchUserProfile(uid);
```
-> Code: await fetchUserProfile(uid);

```
L069 |     } catch (e) {
```
-> Code: } catch (e) {

```
L070 |       emit(ProfileError('Error updating profile: $e'));
```
-> Code: emit(ProfileError('Error updating profile: $e'));

```
L071 |      }
```
-> Code: }

```
L072 |    }
```
-> Code: }

```
L073 | }
```
-> Code: }

lib/features/auth/presentation/bloc/profile_states.dart

```
L001 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L002 |
```
-> Blank line

```
L003 |
```
-> Blank line

```
L004 | abstract class ProfileStates {}
```
-> Code: abstract class ProfileStates {}

```
L005 |
```
-> Blank line

```
L006 | class ProfileInitial extends ProfileStates {}
```
-> Class declaration: class ProfileInitial extends ProfileStates {}

```
L007 |
```
-> Blank line

```
L008 | class ProfileLoading extends ProfileStates {}
```
-> Class declaration: class ProfileLoading extends ProfileStates {}

```
L009 |
```
-> Blank line

```
L010 | class ProfileLoaded extends ProfileStates {
```
-> Class declaration: class ProfileLoaded extends ProfileStates {

```
L011 |   final AppUser appUser;
```
-> Variable declaration: final AppUser appUser;

```
L012 |   ProfileLoaded(this.appUser);
```
-> Code: ProfileLoaded(this.appUser);

```
L013 | }
```
-> Code: }

```
L014 |
```
-> Blank line

```
L015 | class ProfileError extends ProfileStates {
```
-> Class declaration: class ProfileError extends ProfileStates {

```
L016 |   final String message;
```
-> Variable declaration: final String message;

```
L017 |   ProfileError(this.message);
```
-> Code: ProfileError(this.message);

```
L018 | }
```
-> Code: }

lib/features/auth/presentation/components/bio_box.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class MyBioBox extends StatelessWidget {
  -> Class declaration: class MyBioBox extends StatelessWidget {
L004 |   final String text;
  -> Variable declaration: final String text;
L005 |   const MyBioBox({super.key, required this.text});
  -> Variable declaration: const MyBioBox({super.key, required this.text});
L006 |
  -> Blank line
L007 |   @override
  -> Annotation/Decorator: @override
L008 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L009 |     return Container(
  -> Return statement: return Container(
L010 |       padding: const EdgeInsets.all(25),
  -> Code: padding: const EdgeInsets.all(25),
L011 |
  -> Blank line
L012 |       decoration: BoxDecoration(
  -> Code: decoration: BoxDecoration(
L013 |         color: Theme.of(context).colorScheme.inversePrimary
  -> Code: color: Theme.of(context).colorScheme.inversePrimary
L014 |       ),
  -> Code: ),
L015 |
  -> Blank line
L016 |       width: double.infinity,
  -> Code: width: double.infinity,
L017 |
  -> Blank line
L018 |       child: Text(text.isNotEmpty ? text : 'Empty Bio'),
  -> Code: child: Text(text.isNotEmpty ? text : 'Empty Bio'),
L019 |     );
  -> Code: );
L020 |   }
  -> Code: }
L021 | }
  -> Code: }
```

lib/features/auth/presentation/components/my_button.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class MyButton extends StatelessWidget {
  -> Class declaration: class MyButton extends StatelessWidget {
L004 |    final VoidCallback? function;
  -> Variable declaration: final VoidCallback? function;
L005 |   final String text;
  -> Variable declaration: final String text;
L006 |   final Size minimumSize;
  -> Variable declaration: final Size minimumSize;
L007 |   const MyButton({
  -> Variable declaration: const MyButton({
L008 |     super.key,
  -> Code: super.key,
L009 |     required this.function,
  -> Code: required this.function,
L010 |     required this.text,
  -> Code: required this.text,
L011 |     required this.minimumSize,
  -> Code: required this.minimumSize,
L012 |   });
  -> Code: });
L013 |
  -> Blank line
L014 |   @override
  -> Annotation/Decorator: @override
L015 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L016 |     return ElevatedButton(
  -> Return statement: return ElevatedButton(
L017 |       style: ElevatedButton.styleFrom(
  -> Code: style: ElevatedButton.styleFrom(
L018 |         backgroundColor: Colors.brown,
  -> Code: backgroundColor: Colors.brown,
L019 |         foregroundColor: Colors.white,
  -> Code: foregroundColor: Colors.white,
L020 |         minimumSize: Size(120, 40),
  -> Code: minimumSize: Size(120, 40),
L021 |
  -> Blank line
L022 |         shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(20)),
  -> Code: shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(20)),
L023 |       ),
  -> Code: ),
L024 |
  -> Blank line
L025 |       onPressed: function,
  -> Code: onPressed: function,
L026 |       child: Text(text, style: TextStyle(fontSize: 18)),
  -> Code: child: Text(text, style: TextStyle(fontSize: 18)),
L027 |     );
  -> Code: );
L028 |   }
  -> Code: }
L029 | }
  -> Code: }
```

lib/features/auth/presentation/components/my_drawer.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L004 | import 'package:instproject/features/auth/presentation/components/mydrawer_tail.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/mydrawer_tail.dart';

```
L005 | import 'package:instproject/themes/theme_mode_switcher.dart';
```
-> Imports module or package: import 'package:instproject/themes/theme_mode_switcher.dart';

```
L006 |
```
-> Blank line

```
L007 | class MyDrawer extends StatelessWidget {
```
-> Class declaration: class MyDrawer extends StatelessWidget {

```
L008 |   const MyDrawer({super.key});
```
-> Variable declaration: const MyDrawer({super.key});

```
L009 |
```
-> Blank line

```
L010 |   @override
```
-> Annotation/Decorator: @override

```
L011 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L012 |     return Drawer(
```
-> Return statement: return Drawer(

```
L013 |       backgroundColor: Theme.of(context).colorScheme.surface,
```
-> Code: backgroundColor: Theme.of(context).colorScheme.surface,

```
L014 |       child: SafeArea(
```
-> Code: child: SafeArea(

```
L015 |         child: Padding(
```
-> Code: child: Padding(

```
L016 |           padding: const EdgeInsets.symmetric(horizontal: 25.0),
```
-> Code: padding: const EdgeInsets.symmetric(horizontal: 25.0),

```
L017 |           child: ListView(
```
-> Flutter UI widget usage: child: ListView(

```
L018 |             children: [
```
-> Code: children: [

```
L019 |
```
-> Blank line

```
L020 |               const SizedBox(height: 50),
```
-> Variable declaration: const SizedBox(height: 50),

```
L021 |
```
-> Blank line

```
L022 |               Padding(
```
-> Code: Padding(

```
L023 |                 padding: const EdgeInsets.symmetric(vertical: 50.0),
```
-> Code: padding: const EdgeInsets.symmetric(vertical: 50.0),

```
L024 |                 child: Icon(
```
-> Code: child: Icon(

```
L025 |                   Icons.person,
```
-> Code: Icons.person,

```
L026 |                   size: 80,
```
-> Code: size: 80,

```
L027 |                   color: Theme.of(context).colorScheme.primary,
```
-> Code: color: Theme.of(context).colorScheme.primary,

```
L028 |                 ),
```
-> Code:),

```
L029 |               ),
```
-> Code:),

```
L030 |
```
-> Blank line

```
L031 |               Divider(color: Theme.of(context).colorScheme.secondary),
```
-> Code: Divider(color: Theme.of(context).colorScheme.secondary),

```
L032 |
```
-> Blank line

```
L033 |               MydrawerTail(
```
-> Code: MydrawerTail(

```
L034 |                 title: 'Favorites',
```
-> Code: title: 'Favorites',

```
L035 |                   icon: Icons.bookmark,
```
-> Code: icon: Icons.bookmark,

```
L036 |                   onTap: () => Navigator.pushNamed(context, '/save'),
```
-> Code: onTap: () => Navigator.pushNamed(context, '/save'),

```
L037 |                 ),
```
-> Code:),

```
L038 |
```
-> Blank line

```
L039 |                 const ThemeSwitcherTile(),
```
-> Variable declaration: const ThemeSwitcherTile(),

```
L040 |
```
-> Blank line

```
L041 |                 MydrawerTail(
```
-> Code: MydrawerTail(

```
L042 |                   title: 'LogOut',
```
-> Code: title: 'LogOut',

```
L043 |                   icon: Icons.logout,
```
-> Code: icon: Icons.logout,

```
L044 |                   onTap: () => context.read<AuthCubit>().logout(),
```
-> Code: onTap: () => context.read<AuthCubit>().logout(),

```
L045 |                 ),
```
-> Code:),

```
L046 |               ],
```
-> Code:],

```
L047 |             ),
```
-> Code:),

```
L048 |           ),
```
-> Code:),

```
L049 |         ),
```
-> Code:),

```
L050 |       );
```
-> Code:);

```
L051 |     }
```
-> Code: }

```
L052 | }
```
-> Code: }

lib/features/auth/presentation/components/my_textfiled.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class MyTextfiled extends StatelessWidget {
  -> Class declaration: class MyTextfiled extends StatelessWidget {
L004 |   final String hint;
  -> Variable declaration: final String hint;
L005 |   final bool? obsecure;
  -> Variable declaration: final bool? obsecure;
L006 |   final String? Function(String?)? validator;
  -> Variable declaration: final String? Function(String?)? validator;
L007 |   final TextEditingController? controller;
  -> Variable declaration: final TextEditingController? controller;
L008 |   const MyTextfiled({
  -> Variable declaration: const MyTextfiled({
L009 |     super.key,
  -> Code: super.key,
L010 |     required this.hint,
  -> Code: required this.hint,
L011 |     required this.obsecure,
  -> Code: required this.obsecure,
L012 |     this.validator,
  -> Code: this.validator,
L013 |     this.controller,
  -> Code: this.controller,
L014 |   });
  -> Code: });
L015 |
  -> Blank line
L016 |   @override
  -> Annotation/Decorator: @override
L017 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L018 |     return TextFormField(
  -> Return statement: return TextFormField(
L019 |       controller: controller,
  -> Code: controller: controller,
L020 |       style: TextStyle(color: Colors.white),
  -> Code: style: TextStyle(color: Colors.white),
L021 |       obscureText: obsecure!,
  -> Code: obscureText: obsecure!,
L022 |       decoration: InputDecoration(
  -> Code: decoration: InputDecoration(
L023 |         hintText: hint,
  -> Code: hintText: hint,
L024 |         hintStyle: TextStyle(color: Colors.white),
  -> Code: hintStyle: TextStyle(color: Colors.white),
L025 |         enabledBorder: OutlineInputBorder(
  -> Code: enabledBorder: OutlineInputBorder(
L026 |           borderSide: BorderSide(color: Colors.brown),
  -> Code: borderSide: BorderSide(color: Colors.brown),
L027 |           borderRadius: BorderRadius.circular(20),
  -> Code: borderRadius: BorderRadius.circular(20),
L028 |         ),
  -> Code: ),
L029 |         focusedBorder: OutlineInputBorder(
  -> Code: focusedBorder: OutlineInputBorder(
L030 |           borderSide: BorderSide(color: Colors.brown),
  -> Code: borderSide: BorderSide(color: Colors.brown),
L031 |           borderRadius: BorderRadius.circular(20),
  -> Code: borderRadius: BorderRadius.circular(20),
L032 |         ),
  -> Code: ),
L033 |       ),
  -> Code: ),
L034 |       validator: validator,
  -> Code: validator: validator,
```

```
L035 |       autovalidateMode: AutovalidateMode.onUserInteraction,
```
-> Code: autovalidateMode: AutovalidateMode.onUserInteraction,

```
L036 |     );
```
-> Code:);

```
L037 |   }
```
-> Code: }

```
L038 | }
```
-> Code: }

lib/features/auth/presentation/components/mydrawer_tail.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class MydrawerTail extends StatelessWidget {
  -> Class declaration: class MydrawerTail extends StatelessWidget {
L004 |   final String title;
  -> Variable declaration: final String title;
L005 |   final IconData icon;
  -> Variable declaration: final IconData icon;
L006 |   final void Function()? onTap;
  -> Variable declaration: final void Function()? onTap;
L007 |   const MydrawerTail({super.key, required this.title, required this.icon,
  -> Variable declaration: const MydrawerTail({super.key, required this.title, required this.icon,
L008 |     required this.onTap});
  -> Code: required this.onTap});
L009 |
  -> Blank line
L010 |   @override
  -> Annotation/Decorator: @override
L011 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L012 |     return ListTile(
  -> Return statement: return ListTile(
L013 |       title: Text(title),
  -> Code: title: Text(title),
L014 |       leading: Icon(icon),
  -> Code: leading: Icon(icon),
L015 |       onTap: onTap ,
  -> Code: onTap: onTap ,
L016 |     );
  -> Code: );
L017 |   }
  -> Code: }
L018 | }
  -> Code: }
```

lib/features/auth/presentation/pages/auth_page.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 | import 'login_page.dart';
  -> Imports module or package: import 'login_page.dart';
L003 | import 'register_page.dart';
  -> Imports module or package: import 'register_page.dart';
L004 |
  -> Blank line
L005 | class AuthPage extends StatefulWidget {
  -> Class declaration: class AuthPage extends StatefulWidget {
L006 |   const AuthPage({super.key});
  -> Variable declaration: const AuthPage({super.key});
L007 |
  -> Blank line
L008 |   @override
  -> Annotation/Decorator: @override
L009 |   State<AuthPage> createState() => _AuthPageState();
  -> Short arrow function/expression: State<AuthPage> createState() => _AuthPageState();
L010 | }
  -> Code: }
L011 |
  -> Blank line
L012 | class _AuthPageState extends State<AuthPage> {
  -> Class declaration: class _AuthPageState extends State<AuthPage> {
L013 |   bool showLoginPage = true;
  -> Code: bool showLoginPage = true;
L014 |
  -> Blank line
L015 |   void togglePages() {
  -> Function/method declaration or async return type: void togglePages() {
L016 |     setState(() {
  -> Code: setState(() {
L017 |       showLoginPage = !showLoginPage;
  -> Code: showLoginPage = !showLoginPage;
L018 |     });
  -> Code: });
L019 |   }
  -> Code: }
L020 |
  -> Blank line
L021 |   @override
  -> Annotation/Decorator: @override
L022 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L023 |     return showLoginPage
  -> Return statement: return showLoginPage
L024 |         ? LoginPage(togglePages: togglePages)
  -> Code: ? LoginPage(togglePages: togglePages)
L025 |         : RegisterPage(togglePages: togglePages);
  -> Code: : RegisterPage(togglePages: togglePages);
L026 |   }
  -> Code: }
L027 | }
  -> Code: }
```

lib/features/auth/presentation/pages/edit_profile_page.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:image_picker/image_picker.dart';
```
-> Imports module or package: import 'package:image_picker/image_picker.dart';

```
L005 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L006 | import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';

```
L007 | import 'package:instproject/features/auth/presentation/bloc/profile_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/profile_states.dart';

```
L008 | import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';

```
L009 |
```
-> Blank line

```
L010 | class EditProfilePage extends StatefulWidget {
```
-> Class declaration: class EditProfilePage extends StatefulWidget {

```
L011 |   final AppUser user;
```
-> Variable declaration: final AppUser user;

```
L012 |   const EditProfilePage({super.key, required this.user});
```
-> Variable declaration: const EditProfilePage({super.key, required this.user});

```
L013 |
```
-> Blank line

```
L014 |   @override
```
-> Annotation/Decorator: @override

```
L015 |   State<EditProfilePage> createState() => _EditProfilePageState();
```
-> Short arrow function/expression: State<EditProfilePage> createState() => _EditProfilePageState();

```
L016 | }
```
-> Code: }

```
L017 |
```
-> Blank line

```
L018 | class _EditProfilePageState extends State<EditProfilePage> {
```
-> Class declaration: class _EditProfilePageState extends State<EditProfilePage> {

```
L019 |   final bioController = TextEditingController();
```
-> Variable declaration: final bioController = TextEditingController();

```
L020 |   String? _imagePath;
```
-> Code: String? _imagePath;

```
L021 |
```
-> Blank line

```
L022 |   @override
```
-> Annotation/Decorator: @override

```
L023 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L024 |     super.initState();
```
-> Code: super.initState();

```
L025 |     bioController.text = widget.user.bio;
```
-> Code: bioController.text = widget.user.bio;

```
L026 |   }
```
-> Code: }

```
L027 |
```
-> Blank line

```
L028 |
```
-> Blank line

```
L029 |   Future<void> pickImage() async {
```
-> Function/method declaration or async return type: Future<void> pickImage() async {

```
L030 |     final picker = ImagePicker();
```
-> Variable declaration: final picker = ImagePicker();

```
L031 |     final picked = await picker.pickImage(source: ImageSource.gallery);
```
-> Variable declaration: final picked = await picker.pickImage(source: ImageSource.gallery);

```
L032 |     if (picked != null) {
```
-> Control flow statement: if (picked != null) {

```
L033 |       setState(() => _imagePath = picked.path);
```
-> Short arrow function/expression: setState(() => _imagePath = picked.path);

```
L034 |     }
```
-> Code: }

```
L035 |   }
```
-> Code: }

```
L036 |
```
-> Blank line

```
L037 |
```
-> Blank line

```
L038 |   void updateProfile() async {
```
-> Function/method declaration or async return type: void updateProfile() async {

```
L039 |     final profileCubit = context.read<ProfileCubit>();
```
-> Variable declaration: final profileCubit = context.read<ProfileCubit>();

```
L040 |     await profileCubit.updateProfile(
```
-> Code: await profileCubit.updateProfile(

```
L041 |       uid: widget.user.uid,
```
-> Code: uid: widget.user.uid,

```
L042 |       newBio: bioController.text,
```
-> Code: newBio: bioController.text,

```
L043 |       imageMobilePath: _imagePath,
```
-> Code: imageMobilePath: _imagePath,

```
L044 |     );
```
-> Code:);

```
L045 |   }
```
-> Code: }

```
L046 |
```
-> Blank line

```
L047 |   @override
```
-> Annotation/Decorator: @override

```
L048 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L049 |     return BlocConsumer<ProfileCubit, ProfileStates>(
```
-> Return statement: return BlocConsumer<ProfileCubit, ProfileStates>(

```
L050 |       listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L051 |         if (state is ProfileLoaded) {
```
-> Control flow statement: if (state is ProfileLoaded) {

```
L052 |           Navigator.pop(context, true);
```
-> Code: Navigator.pop(context, true);

```
L053 |         }
```
-> Code: }

```
L054 |       },
```
-> Code: },

```
L055 |       builder: (context, state) {
```
-> Code: builder: (context, state) {

```
L056 |         if (state is ProfileLoading) {
```
-> Control flow statement: if (state is ProfileLoading) {

```
L057 |           return const Scaffold(
```
-> Return statement: return const Scaffold(

```
L058 |             body: Center(
```
-> Code: body: Center(

```
L059 |               child: Column(
```
-> Code: child: Column(

```
L060 |                 mainAxisAlignment: MainAxisAlignment.center,
```
-> Code: mainAxisAlignment: MainAxisAlignment.center,

```
L061 |                 children: [
```
-> Code: children: [

```
L062 |                   CircularProgressIndicator(),
```
-> Code: CircularProgressIndicator(),

```
L063 |                   SizedBox(height: 10),
```
-> Code: SizedBox(height: 10),

```
L064 |                   Text('Saving changes...'),
```
-> Code: Text('Saving changes...'),

```
L065 |                 ],
```
-> Code:],

```
L066 |               ),
```
-> Code:),

```
L067 |             ),
```
-> Code:),

```
L068 |           );
```
-> Code:);

```
L069 |         }
```
-> Code: }

```
L070 |
```
-> Blank line

```
L071 |          return Scaffold(
  -> Return statement: return Scaffold(
L072 |            appBar: AppBar(
  -> Flutter UI widget usage: appBar: AppBar(
L073 |              title: const Text('Edit Profile'),
  -> Code: title: const Text('Edit Profile'),
L074 |              actions: [
  -> Code: actions: [
L075 |                IconButton(
  -> Code: IconButton(
L076 |                  onPressed: updateProfile,
  -> Code: onPressed: updateProfile,
L077 |                  icon: const Icon(Icons.upload),
  -> Code: icon: const Icon(Icons.upload),
L078 |                ),
  -> Code: ),
L079 |              ],
  -> Code: ],
L080 |            ),
  -> Code: ),
L081 |            body: Padding(
  -> Code: body: Padding(
L082 |              padding: const EdgeInsets.all(20),
  -> Code: padding: const EdgeInsets.all(20),
L083 |              child: Column(
  -> Code: child: Column(
L084 |                children: [
  -> Code: children: [
L085 |                  GestureDetector(
  -> Code: GestureDetector(
L086 |                    onTap: pickImage,
  -> Code: onTap: pickImage,
L087 |                    child: Stack(
  -> Code: child: Stack(
L088 |                      children: [
  -> Code: children: [
L089 |                        CircleAvatar(
  -> Code: CircleAvatar(
L090 |                          radius: 80,
  -> Code: radius: 80,
L091 |                          backgroundColor: Theme.of(
  -> Code: backgroundColor: Theme.of(
L092 |                            context,
  -> Code: context,
L093 |                          ).colorScheme.inversePrimary,
  -> Code: ).colorScheme.inversePrimary,
L094 |                          backgroundImage: _buildProfileImage(),
  -> Code: backgroundImage: _buildProfileImage(),
L095 |                        ),
  -> Code: ),
L096 |                        Positioned(
  -> Code: Positioned(
L097 |                          bottom: 0,
  -> Code: bottom: 0,
L098 |                          right: 10,
  -> Code: right: 10,
L099 |                          child: CircleAvatar(
  -> Code: child: CircleAvatar(
L100 |                            backgroundColor: Colors.blue,
  -> Code: backgroundColor: Colors.blue,
L101 |                            radius: 20,
  -> Code: radius: 20,
L102 |                            child: const Icon(Icons.edit, color: Colors.white),
  -> Code: child: const Icon(Icons.edit, color: Colors.white),
L103 |                          ),
  -> Code: ),
L104 |                        ),
  -> Code: ),
L105 |                      ],
  -> Code: ],
L106 |                    ),
  -> Code: ),
```

```
L107 |                 ),
```
-> Code:),

```
L108 |                 const SizedBox(height: 30),
```
-> Variable declaration: const SizedBox(height: 30),

```
L109 |                 const Text('Bio', style: TextStyle(fontSize: 16)),
```
-> Variable declaration: const Text('Bio', style: TextStyle(fontSize: 16)),

```
L110 |                 const SizedBox(height: 10),
```
-> Variable declaration: const SizedBox(height: 10),

```
L111 |                 MyTextfiled(
```
-> Code: MyTextfiled(

```
L112 |                   controller: bioController,
```
-> Code: controller: bioController,

```
L113 |                   hint: 'Enter your bio...',
```
-> Code: hint: 'Enter your bio...',

```
L114 |                   obsecure: false,
```
-> Code: obsecure: false,

```
L115 |                 ),
```
-> Code:),

```
L116 |               ],
```
-> Code:],

```
L117 |             ),
```
-> Code:),

```
L118 |           ),
```
-> Code:),

```
L119 |         );
```
-> Code:);

```
L120 |       },
```
-> Code: },

```
L121 |     );
```
-> Code:);

```
L122 |   }
```
-> Code: }

```
L123 |
```
-> Blank line

```
L124 |   ImageProvider _buildProfileImage() {
```
-> Code: ImageProvider _buildProfileImage() {

```
L125 |     if (_imagePath != null && File(_imagePath!).existsSync()) {
```
-> Control flow statement: if (_imagePath != null && File(_imagePath!).existsSync()) {

```
L126 |       return FileImage(File(_imagePath!));
```
-> Return statement: return FileImage(File(_imagePath!));

```
L127 |     } else if (widget.user.profileImg.isNotEmpty) {
```
-> Code: } else if (widget.user.profileImg.isNotEmpty) {

```
L128 |       return NetworkImage(widget.user.profileImg);
```
-> Return statement: return NetworkImage(widget.user.profileImg);

```
L129 |     } else {
```
-> Code: } else {

```
L130 |       return const AssetImage('images/defaultImage.jpeg');
```
-> Return statement: return const AssetImage('images/defaultImage.jpeg');

```
L131 |     }
```
-> Code: }

```
L132 |   }
```
-> Code: }

```
L133 | }
```
-> Code: }

lib/features/auth/presentation/pages/home_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:instproject/features/auth/presentation/components/my_drawer.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_drawer.dart';

```
L003 |
```
-> Blank line

```
L004 | class HomePage extends StatefulWidget {
```
-> Class declaration: class HomePage extends StatefulWidget {

```
L005 |   const HomePage({super.key});
```
-> Variable declaration: const HomePage({super.key});

```
L006 |
```
-> Blank line

```
L007 |   @override
```
-> Annotation/Decorator: @override

```
L008 |   State<HomePage> createState() => _HomePageState();
```
-> Short arrow function/expression: State<HomePage> createState() => _HomePageState();

```
L009 | }
```
-> Code: }

```
L010 |
```
-> Blank line

```
L011 | class _HomePageState extends State<HomePage> {
```
-> Class declaration: class _HomePageState extends State<HomePage> {

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L014 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L015 |       appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L016 |         title: Align(
```
-> Code: title: Align(

```
L017 |           alignment: Alignment.centerLeft,
```
-> Code: alignment: Alignment.centerLeft,

```
L018 |           child: Text('Study Group')),
```
-> Code: child: Text('Study Group')),

```
L019 |
```
-> Blank line

```
L020 |         // actions: [
```
-> Comment: actions: [

```
L021 |         //   IconButton(
```
-> Comment: IconButton(

```
L022 |         //     onPressed: () {
```
-> Comment: onPressed: () {

```
L023 |         //       context.read<AuthCubit>().logout();
```
-> Comment: context.read<AuthCubit>().logout();

```
L024 |         //     },
```
-> Comment: },

```
L025 |         //     icon: Icon(Icons.logout),
```
-> Comment: icon: Icon(Icons.logout),

```
L026 |         //   ),
```
-> Comment:),

```
L027 |         // ],
```
-> Comment:],

```
L028 |       ),
```
-> Code:),

```
L029 |       drawer: MyDrawer(),
```
-> Code: drawer: MyDrawer(),

```
L030 |     );
```
-> Code:);

```
L031 |   }
```
-> Code: }

```
L032 | }
```
-> Code: }

lib/features/auth/presentation/pages/login_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L004 | import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';

```
L005 | import 'package:instproject/features/auth/presentation/components/my_button.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_button.dart';

```
L006 | import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';

```
L007 |
```
-> Blank line

```
L008 | class LoginPage extends StatefulWidget {
```
-> Class declaration: class LoginPage extends StatefulWidget {

```
L009 |   final void Function()? togglePages;
```
-> Variable declaration: final void Function()? togglePages;

```
L010 |   const LoginPage({super.key, this.togglePages});
```
-> Variable declaration: const LoginPage({super.key, this.togglePages});

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   State<LoginPage> createState() => _LoginPageState();
```
-> Short arrow function/expression: State<LoginPage> createState() => _LoginPageState();

```
L014 | }
```
-> Code: }

```
L015 |
```
-> Blank line

```
L016 | class _LoginPageState extends State<LoginPage> {
```
-> Class declaration: class _LoginPageState extends State<LoginPage> {

```
L017 |   final _formKey = GlobalKey<FormState>();
```
-> Variable declaration: final _formKey = GlobalKey<FormState>();

```
L018 |   final TextEditingController _emailController = TextEditingController();
```
-> Variable declaration: final TextEditingController _emailController = TextEditingController();

```
L019 |   final TextEditingController _passController = TextEditingController();
```
-> Variable declaration: final TextEditingController _passController = TextEditingController();

```
L020 |
```
-> Blank line

```
L021 |   @override
```
-> Annotation/Decorator: @override

```
L022 |   void dispose() {
```
-> Function/method declaration or async return type: void dispose() {

```
L023 |     _emailController.dispose();
```
-> Code: _emailController.dispose();

```
L024 |     _passController.dispose();
```
-> Code: _passController.dispose();

```
L025 |     super.dispose();
```
-> Code: super.dispose();

```
L026 |   }
```
-> Code: }

```
L027 |
```
-> Blank line

```
L028 |   void _login() {
```
-> Function/method declaration or async return type: void _login() {

```
L029 |     if (_formKey.currentState!.validate()) {
```
-> Control flow statement: if (_formKey.currentState!.validate()) {

```
L030 |       final email = _emailController.text.trim();
```
-> Variable declaration: final email = _emailController.text.trim();

```
L031 |       final pass = _passController.text.trim();
```
-> Variable declaration: final pass = _passController.text.trim();

```
L032 |       context.read<AuthCubit>().login(email, pass);
```
-> Code: context.read<AuthCubit>().login(email, pass);

```
L033 |     }
```
-> Code: }

```
L034 |   }
```
-> Code: }

```
L035 |
```
-> Blank line

```
L036 |   @override
```
-> Annotation/Decorator: @override

```
L037 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L038 |     return BlocConsumer<AuthCubit, AuthState>(
```
-> Return statement: return BlocConsumer<AuthCubit, AuthState>(

```
L039 |       listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L040 |         if (state is AuthErorr) {
```
-> Control flow statement: if (state is AuthErorr) {

```
L041 |           ScaffoldMessenger.of(
```
-> Code: ScaffoldMessenger.of(

```
L042 |             context,
```
-> Code: context,

```
L043 |           ).showSnackBar(SnackBar(content: Text(state.message)));
```
-> Code:).showSnackBar(SnackBar(content: Text(state.message)));

```
L044 |         }
```
-> Code: }

```
L045 |       },
```
-> Code: },

```
L046 |       builder: (context, state) {
```
-> Code: builder: (context, state) {

```
L047 |         final isLoading = state is AuthLoading;
```
-> Variable declaration: final isLoading = state is AuthLoading;

```
L048 |
```
-> Blank line

```
L049 |         return Scaffold(
```
-> Return statement: return Scaffold(

```
L050 |           resizeToAvoidBottomInset: true,
```
-> Code: resizeToAvoidBottomInset: true,

```
L051 |           body: SafeArea(
```
-> Code: body: SafeArea(

```
L052 |             child: SingleChildScrollView(
```
-> Code: child: SingleChildScrollView(

```
L053 |               padding: const EdgeInsets.all(16.0),
```
-> Code: padding: const EdgeInsets.all(16.0),

```
L054 |               child: Form(
```
-> Code: child: Form(

```
L055 |                 key: _formKey,
```
-> Code: key: _formKey,

```
L056 |                 child: Column(
```
-> Code: child: Column(

```
L057 |                   mainAxisAlignment: MainAxisAlignment.center,
```
-> Code: mainAxisAlignment: MainAxisAlignment.center,

```
L058 |                   children: [
```
-> Code: children: [

```
L059 |                     const SizedBox(height: 40),
```
-> Variable declaration: const SizedBox(height: 40),

```
L060 |
```
-> Blank line

```
L061 |
```
-> Blank line

```
L062 |                     ClipRRect(
```
-> Code: ClipRRect(

```
L063 |                       borderRadius: BorderRadius.circular(12),
```
-> Code: borderRadius: BorderRadius.circular(12),

```
L064 |                       child: Image.asset(
```
-> Code: child: Image.asset(

```
L065 |                         'images/sg.png',
```
-> Code: 'images/sg.png',

```
L066 |                         width: 100,
```
-> Code: width: 100,

```
L067 |                         height: 100,
```
-> Code: height: 100,

```
L068 |                       ),
```
-> Code:),

```
L069 |                     ),
```
-> Code:),

```
L070 |
```
-> Blank line

```
L071 |                       const SizedBox(height: 40),
  -> Variable declaration: const SizedBox(height: 40),
L072 |                       const Text(
  -> Variable declaration: const Text(
L073 |                         'Login',
  -> Code: 'Login',
L074 |                         style: TextStyle(
  -> Code: style: TextStyle(
L075 |                           fontSize: 26,
  -> Code: fontSize: 26,
L076 |                           fontWeight: FontWeight.bold,
  -> Code: fontWeight: FontWeight.bold,
L077 |                           fontStyle: FontStyle.italic
  -> Code: fontStyle: FontStyle.italic
L078 |                         ),
  -> Code: ),
L079 |                       ),
  -> Code: ),
L080 |                       const SizedBox(height: 5),
  -> Variable declaration: const SizedBox(height: 5),
L081 |
  -> Blank line
L082 |
  -> Blank line
L083 |                       const SizedBox(height: 30),
  -> Variable declaration: const SizedBox(height: 30),
L084 |
  -> Blank line
L085 |
  -> Blank line
L086 |                       MyTextfiled(
  -> Code: MyTextfiled(
L087 |                         validator: (value) {
  -> Code: validator: (value) {
L088 |                           if (value == null || value.isEmpty) {
  -> Control flow statement: if (value == null || value.isEmpty) {
L089 |                             return 'Please enter your email';
  -> Return statement: return 'Please enter your email';
L090 |                           }
  -> Code: }
L091 |                           if (!RegExp(r'^[^@]+@[^@]+\.[^@]+').hasMatch(value)) {
  -> Control flow statement: if (!RegExp(r'^[^@]+@[^@]+\.[^@]+').hasMatch(value)) {
L092 |                             return 'Enter a valid email';
  -> Return statement: return 'Enter a valid email';
L093 |                           }
  -> Code: }
L094 |                           return null;
  -> Return statement: return null;
L095 |                       },
  -> Code: },
L096 |                       controller: _emailController,
  -> Code: controller: _emailController,
L097 |                       hint: 'Enter your Email',
  -> Code: hint: 'Enter your Email',
L098 |                       obsecure: false,
  -> Code: obsecure: false,
L099 |                       ),
  -> Code: ),
L100 |
  -> Blank line
L101 |                       const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L102 |
  -> Blank line
L103 |
  -> Blank line
L104 |                       MyTextfiled(
  -> Code: MyTextfiled(
L105 |                         validator: (value) {
  -> Code: validator: (value) {
L106 |                           if (value == null || value.isEmpty) {
  -> Control flow statement: if (value == null || value.isEmpty) {
```

```
L107 |                             return 'Please enter your password';
  -> Return statement: return 'Please enter your password';
L108 |                           }
  -> Code: }
L109 |                           if (value.length < 6) {
  -> Control flow statement: if (value.length < 6) {
L110 |                             return 'Password must be at least 6 characters';
  -> Return statement: return 'Password must be at least 6 characters';
L111 |                           }
  -> Code: }
L112 |                           return null;
  -> Return statement: return null;
L113 |                         },
  -> Code: },
L114 |                         controller: _passController,
  -> Code: controller: _passController,
L115 |                         hint: 'Enter your Password',
  -> Code: hint: 'Enter your Password',
L116 |                         obsecure: true,
  -> Code: obsecure: true,
L117 |                       ),
  -> Code: ),
L118 |
  -> Blank line
L119 |                       // Align(
  -> Comment:  Align(
L120 |                       //   alignment: Alignment.centerRight,
  -> Comment:    alignment: Alignment.centerRight,
L121 |                       //   child: TextButton(
  -> Comment:    child: TextButton(
L122 |                       //     onPressed: () {},
  -> Comment:     onPressed: () {},
L123 |                       //     child: const Text('Forgot Password?'),
  -> Comment:     child: const Text('Forgot Password?'),
L124 |                       //   ),
  -> Comment:    ),
L125 |                       // ),
  -> Comment:  ),
L126 |
  -> Blank line
L127 |                       const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L128 |
  -> Blank line
L129 |
  -> Blank line
L130 |                       SizedBox(
  -> Code: SizedBox(
L131 |                         width: 200,
  -> Code: width: 200,
L132 |                         child: MyButton(
  -> Code: child: MyButton(
L133 |                           function: isLoading ? null : _login,
  -> Code: function: isLoading ? null : _login,
L134 |                           text: isLoading ? 'Loading...' : 'Login',
  -> Code: text: isLoading ? 'Loading...' : 'Login',
L135 |                           minimumSize: const Size(140, 40),
  -> Code: minimumSize: const Size(140, 40),
L136 |                         ),
  -> Code: ),
L137 |                       ),
  -> Code: ),
L138 |
  -> Blank line
L139 |                       const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L140 |
  -> Blank line
L141 |
  -> Blank line
L142 |                       Row(
  -> Code: Row(
```

```
L143 |                       mainAxisAlignment: MainAxisAlignment.center,
  -> Code: mainAxisAlignment: MainAxisAlignment.center,
L144 |                       children: [
  -> Code: children: [
L145 |                         const Text('Don't have an account?'),
  -> Variable declaration: const Text('Don't have an account?'),
L146 |                         TextButton(
  -> Code: TextButton(
L147 |                           onPressed: widget.togglePages,
  -> Code: onPressed: widget.togglePages,
L148 |                           child: const Text(
  -> Code: child: const Text(
L149 |                             'Register',
  -> Code: 'Register',
L150 |                             style: TextStyle(color: Colors.brown),
  -> Code: style: TextStyle(color: Colors.brown),
L151 |                           ),
  -> Code: ),
L152 |                         ),
  -> Code: ),
L153 |                       ],
  -> Code: ],
L154 |                     ),
  -> Code: ),
L155 |                   ],
  -> Code: ],
L156 |                 ),
  -> Code: ),
L157 |               ),
  -> Code: ),
L158 |             ),
  -> Code: ),
L159 |           ),
  -> Code: ),
L160 |         );
  -> Code: );
L161 |       },
  -> Code: },
L162 |     );
  -> Code: );
L163 |   }
  -> Code: }
L164 | }
  -> Code: }
```

lib/features/auth/presentation/pages/profile_page.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:shared_preferences/shared_preferences.dart';
```
-> Imports module or package: import 'package:shared_preferences/shared_preferences.dart';

```
L005 | import 'package:instproject/features/auth/domain/entities/app_user.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/domain/entities/app_user.dart';

```
L006 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L007 | import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/profile_cubit.dart';

```
L008 | import 'package:instproject/features/auth/presentation/bloc/profile_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/profile_states.dart';

```
L009 | import 'package:instproject/features/auth/presentation/components/bio_box.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/bio_box.dart';

```
L010 | import 'package:instproject/features/auth/presentation/pages/edit_profile_page.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/pages/edit_profile_page.dart';

```
L011 | import 'package:instproject/features/posts/data/post_model.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/post_model.dart';

```
L012 | import 'package:instproject/features/posts/domain/post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/domain/post_repo.dart';

```
L013 | import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';

```
L014 | import 'package:instproject/features/posts/presentation/bloc/post_states.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/bloc/post_states.dart';

```
L015 | import 'package:instproject/features/posts/presentation/pages/post_detail_page.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/pages/post_detail_page.dart';

```
L016 |
```
-> Blank line

```
L017 | class ProfilePage extends StatefulWidget {
```
-> Class declaration: class ProfilePage extends StatefulWidget {

```
L018 |   final String uid;
```
-> Variable declaration: final String uid;

```
L019 |   const ProfilePage({super.key, required this.uid});
```
-> Variable declaration: const ProfilePage({super.key, required this.uid});

```
L020 |
```
-> Blank line

```
L021 |   @override
```
-> Annotation/Decorator: @override

```
L022 |   State<ProfilePage> createState() => _ProfilePageState();
```
-> Short arrow function/expression: State<ProfilePage> createState() => _ProfilePageState();

```
L023 | }
```
-> Code: }

```
L024 |
```
-> Blank line

```
L025 | class _ProfilePageState extends State<ProfilePage> {
```
-> Class declaration: class _ProfilePageState extends State<ProfilePage> {

```
L026 |   late final AuthCubit authCubit;
```
-> Code: late final AuthCubit authCubit;

```
L027 |   late final ProfileCubit profileCubit;
```
-> Code: late final ProfileCubit profileCubit;

```
L028 |   late final PostCubit postCubit;
```
-> Code: late final PostCubit postCubit;

```
L029 |
```
-> Blank line

```
L030 |   AppUser? currentUser;
```
-> Code: AppUser? currentUser;

```
L031 |   String? _localImagePath;
```
-> Code: String? _localImagePath;

```
L032 |   String? _localBio;
```
-> Code: String? _localBio;

```
L033 |
```
-> Blank line

```
L034 |   @override
```
-> Annotation/Decorator: @override

```
L035 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L036 |     super.initState();
```
-> Code: super.initState();

```
L037 |     authCubit = context.read<AuthCubit>();
```
-> Code: authCubit = context.read<AuthCubit>();

```
L038 |     profileCubit = context.read<ProfileCubit>();
```
-> Code: profileCubit = context.read<ProfileCubit>();

```
L039 |     postCubit = context.read<PostCubit>();
```
-> Code: postCubit = context.read<PostCubit>();

```
L040 |
```
-> Blank line

```
L041 |     currentUser = authCubit.currentUser;
```
-> Code: currentUser = authCubit.currentUser;

```
L042 |
```
-> Blank line

```
L043 |     profileCubit.fetchUserProfile(widget.uid);
```
-> Code: profileCubit.fetchUserProfile(widget.uid);

```
L044 |     postCubit.fetchPostsByUserId(widget.uid);
```
-> Code: postCubit.fetchPostsByUserId(widget.uid);

```
L045 |
```
-> Blank line

```
L046 |     _loadLocalData();
```
-> Code: _loadLocalData();

```
L047 |   }
```
-> Code: }

```
L048 |
```
-> Blank line

```
L049 |
```
-> Blank line

```
L050 |   Future<void> _saveBioLocally(String bio) async {
```
-> Function/method declaration or async return type: Future<void> _saveBioLocally(String bio) async {

```
L051 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L052 |     await prefs.setString('user_bio_${widget.uid}', bio);
```
-> Code: await prefs.setString('user_bio_${widget.uid}', bio);

```
L053 |   }
```
-> Code: }

```
L054 |
```
-> Blank line

```
L055 |   Future<void> _saveProfileImagePath(String path) async {
```
-> Function/method declaration or async return type: Future<void> _saveProfileImagePath(String path) async {

```
L056 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L057 |     await prefs.setString('profile_image_${widget.uid}', path);
```
-> Code: await prefs.setString('profile_image_${widget.uid}', path);

```
L058 |   }
```
-> Code: }

```
L059 |
```
-> Blank line

```
L060 |   Future<void> _loadLocalData() async {
```
-> Function/method declaration or async return type: Future<void> _loadLocalData() async {

```
L061 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L062 |     setState(() {
```
-> Code: setState(() {

```
L063 |       _localImagePath = prefs.getString('profile_image_${widget.uid}');
```
-> Code: _localImagePath = prefs.getString('profile_image_${widget.uid}');

```
L064 |       _localBio = prefs.getString('user_bio_${widget.uid}');
```
-> Code: _localBio = prefs.getString('user_bio_${widget.uid}');

```
L065 |     });
```
-> Code: });

```
L066 |   }
```
-> Code: }

```
L067 |
```
-> Blank line

```
L068 |
```
-> Blank line

```
L069 |
```
-> Blank line

```
L070 |   @override
```
-> Annotation/Decorator: @override

```
L071 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L072 |     return BlocBuilder<ProfileCubit, ProfileStates>(
```
-> Return statement: return BlocBuilder<ProfileCubit, ProfileStates>(

```
L073 |       builder: (context, state) {
```
-> Code: builder: (context, state) {

```
L074 |         if (state is ProfileLoading) {
```
-> Control flow statement: if (state is ProfileLoading) {

```
L075 |           return const Scaffold(
```
-> Return statement: return const Scaffold(

```
L076 |             body: Center(child: CircularProgressIndicator()),
```
-> Code: body: Center(child: CircularProgressIndicator()),

```
L077 |           );
```
-> Code:);

```
L078 |         }
```
-> Code: }

```
L079 |
```
-> Blank line

```
L080 |         if (state is ProfileError) {
```
-> Control flow statement: if (state is ProfileError) {

```
L081 |           return Scaffold(body: Center(child: Text(state.message)));
```
-> Return statement: return Scaffold(body: Center(child: Text(state.message)));

```
L082 |         }
```
-> Code: }

```
L083 |
```
-> Blank line

```
L084 |         if (state is ProfileLoaded) {
```
-> Control flow statement: if (state is ProfileLoaded) {

```
L085 |           final user = state.appUser;
```
-> Variable declaration: final user = state.appUser;

```
L086 |
```
-> Blank line

```
L087 |
```
-> Blank line

```
L088 |           final displayedBio = _localBio ?? user.bio;
```
-> Variable declaration: final displayedBio = _localBio ?? user.bio;

```
L089 |
```
-> Blank line

```
L090 |           return Scaffold(
```
-> Return statement: return Scaffold(

```
L091 |             appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L092 |               title: Text(user.name),
```
-> Code: title: Text(user.name),

```
L093 |               actions: [
```
-> Code: actions: [

```
L094 |                 if (currentUser != null && currentUser!.uid == user.uid)
```
-> Control flow statement: if (currentUser != null && currentUser!.uid == user.uid)

```
L095 |                   IconButton(
```
-> Code: IconButton(

```
L096 |                     icon: const Icon(Icons.edit),
```
-> Code: icon: const Icon(Icons.edit),

```
L097 |                     onPressed: () async {
```
-> Code: onPressed: () async {

```
L098 |                       final result = await Navigator.push(
```
-> Variable declaration: final result = await Navigator.push(

```
L099 |                         context,
```
-> Code: context,

```
L100 |                         MaterialPageRoute(
```
-> Code: MaterialPageRoute(

```
L101 |                           builder: (_) => EditProfilePage(user: user),
```
-> Code: builder: (_) => EditProfilePage(user: user),

```
L102 |                         ),
```
-> Code:),

```
L103 |                       );
```
-> Code:);

```
L104 |
```
-> Blank line

```
L105 |                       if (result is Map<String, dynamic>) {
```
-> Control flow statement: if (result is Map<String, dynamic>) {

```
L106 |
```
-> Blank line

```
L107 |                           final updatedBio = result['bio'] as String?;
  -> Variable declaration: final updatedBio = result['bio'] as String?;
L108 |                           final updatedImage = result['imagePath'] as String?;
  -> Variable declaration: final updatedImage = result['imagePath'] as String?;
L109 |
  -> Blank line
L110 |                           if (updatedBio != null) {
  -> Control flow statement: if (updatedBio != null) {
L111 |                             _saveBioLocally(updatedBio);
  -> Code: _saveBioLocally(updatedBio);
L112 |                             setState(() {
  -> Code: setState(() {
L113 |                               _localBio = updatedBio;
  -> Code: _localBio = updatedBio;
L114 |                             });
  -> Code: });
L115 |                           }
  -> Code: }
L116 |
  -> Blank line
L117 |                           if (updatedImage != null) {
  -> Control flow statement: if (updatedImage != null) {
L118 |                             _saveProfileImagePath(updatedImage);
  -> Code: _saveProfileImagePath(updatedImage);
L119 |                             setState(() {
  -> Code: setState(() {
L120 |                               _localImagePath = updatedImage;
  -> Code: _localImagePath = updatedImage;
L121 |                             });
  -> Code: });
L122 |                           }
  -> Code: }
L123 |
  -> Blank line
L124 |
  -> Blank line
L125 |                           profileCubit.fetchUserProfile(widget.uid);
  -> Code: profileCubit.fetchUserProfile(widget.uid);
L126 |                           postCubit.fetchPostsByUserId(widget.uid);
  -> Code: postCubit.fetchPostsByUserId(widget.uid);
L127 |                         }
  -> Code: }
L128 |                       },
  -> Code: },
L129 |                     ),
  -> Code: ),
L130 |                 ],
  -> Code: ],
L131 |               ),
  -> Code: ),
L132 |               body: SingleChildScrollView(
  -> Code: body: SingleChildScrollView(
L133 |                 padding: const EdgeInsets.all(20),
  -> Code: padding: const EdgeInsets.all(20),
L134 |                 child: Column(
  -> Code: child: Column(
L135 |                   crossAxisAlignment: CrossAxisAlignment.center,
  -> Code: crossAxisAlignment: CrossAxisAlignment.center,
L136 |                   children: [
  -> Code: children: [
L137 |                     CircleAvatar(
  -> Code: CircleAvatar(
L138 |                       radius: 70,
  -> Code: radius: 70,
L139 |                       backgroundColor: Theme.of(
  -> Code: backgroundColor: Theme.of(
L140 |                         context,
  -> Code: context,
L141 |                       ).colorScheme.inversePrimary,
  -> Code: ).colorScheme.inversePrimary,
L142 |                       backgroundImage: _buildProfileImage(user),
  -> Code: backgroundImage: _buildProfileImage(user),
```

```
L143 |                     ),
  -> Code: ),
L144 |                     const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L145 |                     Text(
  -> Code: Text(
L146 |                       user.email,
  -> Code: user.email,
L147 |                       style: TextStyle(
  -> Code: style: TextStyle(
L148 |                         fontSize: 16,
  -> Code: fontSize: 16,
L149 |                         color: Theme.of(context).colorScheme.inversePrimary,
  -> Code: color: Theme.of(context).colorScheme.inversePrimary,
L150 |                       ),
  -> Code: ),
L151 |                     ),
  -> Code: ),
L152 |                     const SizedBox(height: 25),
  -> Variable declaration: const SizedBox(height: 25),
L153 |                     MyBioBox(
  -> Code: MyBioBox(
L154 |                       text: displayedBio.isNotEmpty ? displayedBio : "No bio yet",
  -> Code: text: displayedBio.isNotEmpty ? displayedBio : "No bio yet",
L155 |                     ),
  -> Code: ),
L156 |                     const SizedBox(height: 40),
  -> Variable declaration: const SizedBox(height: 40),
L157 |                     BlocBuilder<PostCubit, PostStates>(
  -> Code: BlocBuilder<PostCubit, PostStates>(
L158 |                       builder: (context, pState) {
  -> Code: builder: (context, pState) {
L159 |                         if (pState is PostLoading) {
  -> Control flow statement: if (pState is PostLoading) {
L160 |                           return const Center(child: CircularProgressIndicator());
  -> Return statement: return const Center(child: CircularProgressIndicator());
L161 |                         }
  -> Code: }
L162 |
  -> Blank line
L163 |                         if (pState is PostError) {
  -> Control flow statement: if (pState is PostError) {
L164 |                           return Text(pState.message);
  -> Return statement: return Text(pState.message);
L165 |                         }
  -> Code: }
L166 |
  -> Blank line
L167 |                         if (pState is PostLoaded) {
  -> Control flow statement: if (pState is PostLoaded) {
L168 |                           final posts = pState.posts
  -> Variable declaration: final posts = pState.posts
L169 |                               .where((p) => p.userId == widget.uid)
  -> Code: .where((p) => p.userId == widget.uid)
L170 |                               .toList();
  -> Code: .toList();
L171 |
  -> Blank line
L172 |                         if (posts.isEmpty) {
  -> Control flow statement: if (posts.isEmpty) {
L173 |                           return const Text('No posts yet');
  -> Return statement: return const Text('No posts yet');
L174 |                         }
  -> Code: }
L175 |
  -> Blank line
L176 |                         return StreamBuilder<List<Post>>(
  -> Return statement: return StreamBuilder<List<Post>>(
L177 |                           stream: context.read<PostRepo>().streamPostsByUserId(
  -> Code: stream: context.read<PostRepo>().streamPostsByUserId(
L178 |                             widget.uid,
  -> Code: widget.uid,
```

```
L179 |                             ),
  -> Code: ),
L180 |                             builder: (context, snapshot) {
  -> Code: builder: (context, snapshot) {
L181 |                               if (snapshot.connectionState ==
  -> Control flow statement: if (snapshot.connectionState ==
L182 |                                   ConnectionState.waiting) {
  -> Code: ConnectionState.waiting) {
L183 |                                 return const Center(
  -> Return statement: return const Center(
L184 |                                   child: CircularProgressIndicator(),
  -> Code: child: CircularProgressIndicator(),
L185 |                                 );
  -> Code: );
L186 |                               }
  -> Code: }
L187 |
  -> Blank line
L188 |                               if (snapshot.hasError) {
  -> Control flow statement: if (snapshot.hasError) {
L189 |                                 return Center(
  -> Return statement: return Center(
L190 |                                   child: Text('Error: ${snapshot.error}'),
  -> Code: child: Text('Error: ${snapshot.error}'),
L191 |                                 );
  -> Code: );
L192 |                               }
  -> Code: }
L193 |
  -> Blank line
L194 |                               if (!snapshot.hasData || snapshot.data!.isEmpty) {
  -> Control flow statement: if (!snapshot.hasData || snapshot.data!.isEmpty) {
L195 |                                 return const Center(child: Text('No posts yet'));
  -> Return statement: return const Center(child: Text('No posts yet'));
L196 |                               }
  -> Code: }
L197 |
  -> Blank line
L198 |                               final posts = snapshot.data!;
  -> Variable declaration: final posts = snapshot.data!;
L199 |
  -> Blank line
L200 |                               return GridView.builder(
  -> Return statement: return GridView.builder(
L201 |                                 itemCount: posts.length,
  -> Code: itemCount: posts.length,
L202 |                                 shrinkWrap: true,
  -> Code: shrinkWrap: true,
L203 |                                 physics: const NeverScrollableScrollPhysics(),
  -> Code: physics: const NeverScrollableScrollPhysics(),
L204 |                                 gridDelegate:
  -> Code: gridDelegate:
L205 |                                     const SliverGridDelegateWithFixedCrossAxisCount(
  -> Variable declaration: const SliverGridDelegateWithFixedCrossAxisCount(
L206 |                                       crossAxisCount: 3,
  -> Code: crossAxisCount: 3,
L207 |                                       crossAxisSpacing: 4,
  -> Code: crossAxisSpacing: 4,
L208 |                                       mainAxisSpacing: 4,
  -> Code: mainAxisSpacing: 4,
L209 |                                       childAspectRatio: 1,
  -> Code: childAspectRatio: 1,
L210 |                                     ),
  -> Code: ),
L211 |                                 itemBuilder: (context, index) {
  -> Code: itemBuilder: (context, index) {
L212 |                                   final post = posts[index];
  -> Variable declaration: final post = posts[index];
L213 |                                   return GestureDetector(
  -> Return statement: return GestureDetector(
L214 |                                     onTap: () {
  -> Code: onTap: () {
```

L215 | Navigator.push(
  -> Code: Navigator.push(
L216 | context,
  -> Code: context,
L217 | MaterialPageRoute(
  -> Code: MaterialPageRoute(
L218 | builder: (_) =>
  -> Code: builder: (_) =>
L219 | PostDetailPage(post: post),
  -> Code: PostDetailPage(post: post),
L220 |),
  -> Code:),
L221 |);
  -> Code:);
L222 | },
  -> Code: },
L223 | child: ClipRRect(
  -> Code: child: ClipRRect(
L224 | borderRadius: BorderRadius.circular(8),
  -> Code: borderRadius: BorderRadius.circular(8),
L225 | child:
  -> Code: child:
L226 | post.imageUrl != null &&
  -> Code: post.imageUrl != null &&
L227 | post.imageUrl!.isNotEmpty
  -> Code: post.imageUrl!.isNotEmpty
L228 | ? Image.network(
  -> Code: ? Image.network(
L229 | post.imageUrl!,
  -> Code: post.imageUrl!,
L230 | fit: BoxFit.cover,
  -> Code: fit: BoxFit.cover,
L231 |)
  -> Code:)
L232 | : Container(
  -> Code: : Container(
L233 | color: Colors.grey[300],
  -> Code: color: Colors.grey[300],
L234 | child: Center(
  -> Code: child: Center(
L235 | child: Text(
  -> Code: child: Text(
L236 | post.caption?.isNotEmpty == true
  -> Code: post.caption?.isNotEmpty == true
L237 | ? post.caption!
  -> Code: ? post.caption!
L238 | : "No Image",
  -> Code: : "No Image",
L239 | style: const TextStyle(
  -> Code: style: const TextStyle(
L240 | fontSize: 12,
  -> Code: fontSize: 12,
L241 | color: Colors.black54,
  -> Code: color: Colors.black54,
L242 |),
  -> Code:),
L243 | textAlign: TextAlign.center,
  -> Code: textAlign: TextAlign.center,
L244 |),
  -> Code:),
L245 |),
  -> Code:),
L246 |),
  -> Code:),
L247 |),
  -> Code:),
L248 |);
  -> Code:);
L249 | },
  -> Code: },
L250 |);
  -> Code:);

```
L251 |                             },
```
-> Code: },

```
L252 |                           );
```
-> Code:);

```
L253 |                         }
```
-> Code: }

```
L254 |
```
-> Blank line

```
L255 |                         return const SizedBox.shrink();
```
-> Return statement: return const SizedBox.shrink();

```
L256 |                       },
```
-> Code: },

```
L257 |                     ),
```
-> Code:),

```
L258 |                   ],
```
-> Code:],

```
L259 |                 ),
```
-> Code:),

```
L260 |               ),
```
-> Code:),

```
L261 |             );
```
-> Code:);

```
L262 |           }
```
-> Code: }

```
L263 |
```
-> Blank line

```
L264 |           return const Scaffold(body: Center(child: Text('No profile found.')));
```
-> Return statement: return const Scaffold(body: Center(child: Text('No profile found.')));

```
L265 |         },
```
-> Code: },

```
L266 |       );
```
-> Code:);

```
L267 |     }
```
-> Code: }

```
L268 |
```
-> Blank line

```
L269 |     ImageProvider _buildProfileImage(AppUser user) {
```
-> Code: ImageProvider _buildProfileImage(AppUser user) {

```
L270 |       if (_localImagePath != null && File(_localImagePath!).existsSync()) {
```
-> Control flow statement: if (_localImagePath != null && File(_localImagePath!).existsSync()) {

```
L271 |         return FileImage(File(_localImagePath!));
```
-> Return statement: return FileImage(File(_localImagePath!));

```
L272 |       } else if (user.profileImg.isNotEmpty) {
```
-> Code: } else if (user.profileImg.isNotEmpty) {

```
L273 |         return NetworkImage(user.profileImg);
```
-> Return statement: return NetworkImage(user.profileImg);

```
L274 |       } else {
```
-> Code: } else {

```
L275 |         return const AssetImage('images/defaultImage.jpeg');
```
-> Return statement: return const AssetImage('images/defaultImage.jpeg');

```
L276 |       }
```
-> Code: }

```
L277 |     }
```
-> Code: }

```
L278 | }
```
-> Code: }

lib/features/auth/presentation/pages/register_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L004 | import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';

```
L005 | import 'package:instproject/features/auth/presentation/components/my_button.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_button.dart';

```
L006 | import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_textfiled.dart';

```
L007 |
```
-> Blank line

```
L008 | class RegisterPage extends StatefulWidget {
```
-> Class declaration: class RegisterPage extends StatefulWidget {

```
L009 |   final void Function()? togglePages;
```
-> Variable declaration: final void Function()? togglePages;

```
L010 |   const RegisterPage({super.key, this.togglePages});
```
-> Variable declaration: const RegisterPage({super.key, this.togglePages});

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   State<RegisterPage> createState() => _RegisterPageState();
```
-> Short arrow function/expression: State<RegisterPage> createState() => _RegisterPageState();

```
L014 | }
```
-> Code: }

```
L015 |
```
-> Blank line

```
L016 | class _RegisterPageState extends State<RegisterPage> {
```
-> Class declaration: class _RegisterPageState extends State<RegisterPage> {

```
L017 |   final _formKey = GlobalKey<FormState>();
```
-> Variable declaration: final _formKey = GlobalKey<FormState>();

```
L018 |   final TextEditingController nameCon = TextEditingController();
```
-> Variable declaration: final TextEditingController nameCon = TextEditingController();

```
L019 |   final TextEditingController emailCon = TextEditingController();
```
-> Variable declaration: final TextEditingController emailCon = TextEditingController();

```
L020 |   final TextEditingController passCon = TextEditingController();
```
-> Variable declaration: final TextEditingController passCon = TextEditingController();

```
L021 |   final TextEditingController passConfirm = TextEditingController();
```
-> Variable declaration: final TextEditingController passConfirm = TextEditingController();

```
L022 |
```
-> Blank line

```
L023 |   bool isLoading = false;
```
-> Code: bool isLoading = false;

```
L024 |
```
-> Blank line

```
L025 |   void _register() {
```
-> Function/method declaration or async return type: void _register() {

```
L026 |     if (!_formKey.currentState!.validate()) return;
```
-> Control flow statement: if (!_formKey.currentState!.validate()) return;

```
L027 |
```
-> Blank line

```
L028 |     final name = nameCon.text.trim();
```
-> Variable declaration: final name = nameCon.text.trim();

```
L029 |     final email = emailCon.text.trim();
```
-> Variable declaration: final email = emailCon.text.trim();

```
L030 |     final pass = passCon.text.trim();
```
-> Variable declaration: final pass = passCon.text.trim();

```
L031 |     final confirm = passConfirm.text.trim();
```
-> Variable declaration: final confirm = passConfirm.text.trim();

```
L032 |
```
-> Blank line

```
L033 |     if (pass != confirm) {
```
-> Control flow statement: if (pass != confirm) {

```
L034 |       ScaffoldMessenger.of(
```
-> Code: ScaffoldMessenger.of(

```
L035 |         context,
```
-> Code: context,

```
L036 |       ).showSnackBar(const SnackBar(content: Text("Passwords don't match")));
```
-> Code:).showSnackBar(const SnackBar(content: Text("Passwords don't match")));

```
L037 |       return;
```
-> Code: return;

```
L038 |     }
```
-> Code: }

```
L039 |
```
-> Blank line

```
L040 |     context.read<AuthCubit>().register(name, email, pass);
```
-> Code: context.read<AuthCubit>().register(name, email, pass);

```
L041 |   }
```
-> Code: }

```
L042 |
```
-> Blank line

```
L043 |   @override
```
-> Annotation/Decorator: @override

```
L044 |   void dispose() {
```
-> Function/method declaration or async return type: void dispose() {

```
L045 |     nameCon.dispose();
```
-> Code: nameCon.dispose();

```
L046 |     emailCon.dispose();
```
-> Code: emailCon.dispose();

```
L047 |     passCon.dispose();
```
-> Code: passCon.dispose();

```
L048 |     passConfirm.dispose();
```
-> Code: passConfirm.dispose();

```
L049 |     super.dispose();
```
-> Code: super.dispose();

```
L050 |   }
```
-> Code: }

```
L051 |
```
-> Blank line

```
L052 |   @override
```
-> Annotation/Decorator: @override

```
L053 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L054 |     return BlocListener<AuthCubit, AuthState>(
```
-> Return statement: return BlocListener<AuthCubit, AuthState>(

```
L055 |       listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L056 |         if (state is AuthLoading) {
```
-> Control flow statement: if (state is AuthLoading) {

```
L057 |           setState(() => isLoading = true);
```
-> Short arrow function/expression: setState(() => isLoading = true);

```
L058 |         } else {
```
-> Code: } else {

```
L059 |           setState(() => isLoading = false);
```
-> Short arrow function/expression: setState(() => isLoading = false);

```
L060 |         }
```
-> Code: }

```
L061 |
```
-> Blank line

```
L062 |         if (state is Authenticated) {
```
-> Control flow statement: if (state is Authenticated) {

```
L063 |           Navigator.pushReplacementNamed(context, '/main');
```
-> Code: Navigator.pushReplacementNamed(context, '/main');

```
L064 |         } else if (state is AuthErorr) {
```
-> Code: } else if (state is AuthErorr) {

```
L065 |           ScaffoldMessenger.of(
```
-> Code: ScaffoldMessenger.of(

```
L066 |             context,
```
-> Code: context,

```
L067 |           ).showSnackBar(SnackBar(content: Text(state.message)));
```
-> Code:).showSnackBar(SnackBar(content: Text(state.message)));

```
L068 |         }
```
-> Code: }

```
L069 |       },
```
-> Code: },

```
L070 |       child: Scaffold(
```
-> Flutter UI widget usage: child: Scaffold(

```
L071 |         resizeToAvoidBottomInset: true,
  -> Code: resizeToAvoidBottomInset: true,
L072 |         body: SafeArea(
  -> Code: body: SafeArea(
L073 |           child: SingleChildScrollView(
  -> Code: child: SingleChildScrollView(
L074 |             padding: const EdgeInsets.all(16),
  -> Code: padding: const EdgeInsets.all(16),
L075 |             child: Form(
  -> Code: child: Form(
L076 |               key: _formKey,
  -> Code: key: _formKey,
L077 |               child: Column(
  -> Code: child: Column(
L078 |                 children: [
  -> Code: children: [
L079 |                   const SizedBox(height: 50),
  -> Variable declaration: const SizedBox(height: 50),
L080 |                   Image.asset('images/sg.png', width: 100, height: 100),
  -> Code: Image.asset('images/sg.png', width: 100, height: 100),
L081 |                   const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L082 |                   const Text('Create Account', style: TextStyle(fontSize: 24)),
  -> Variable declaration: const Text('Create Account', style: TextStyle(fontSize: 24)),
L083 |                   const SizedBox(height: 30),
  -> Variable declaration: const SizedBox(height: 30),
L084 |
  -> Blank line
L085 |                   MyTextfiled(
  -> Code: MyTextfiled(
L086 |                     controller: nameCon,
  -> Code: controller: nameCon,
L087 |                     hint: 'Your Name',
  -> Code: hint: 'Your Name',
L088 |                     obsecure: false,
  -> Code: obsecure: false,
L089 |                     validator: (v) => v == null || v.isEmpty
  -> Code: validator: (v) => v == null || v.isEmpty
L090 |                         ? 'Please enter your name'
  -> Code: ? 'Please enter your name'
L091 |                         : null,
  -> Code: : null,
L092 |                   ),
  -> Code: ),
L093 |                   const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L094 |
  -> Blank line
L095 |                   MyTextfiled(
  -> Code: MyTextfiled(
L096 |                     controller: emailCon,
  -> Code: controller: emailCon,
L097 |                     hint: 'Enter your Email',
  -> Code: hint: 'Enter your Email',
L098 |                     obsecure: false,
  -> Code: obsecure: false,
L099 |                     validator: (v) => v == null || !v.contains('@')
  -> Code: validator: (v) => v == null || !v.contains('@')
L100 |                         ? 'Enter valid email'
  -> Code: ? 'Enter valid email'
L101 |                         : null,
  -> Code: : null,
L102 |                   ),
  -> Code: ),
L103 |                   const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L104 |
  -> Blank line
L105 |                   MyTextfiled(
  -> Code: MyTextfiled(
L106 |                     controller: passCon,
  -> Code: controller: passCon,
```

```
L107 |                       hint: 'Enter your Password',
  -> Code: hint: 'Enter your Password',
L108 |                       obsecure: true,
  -> Code: obsecure: true,
L109 |                       validator: (v) =>
  -> Code: validator: (v) =>
L110 |                           v == null || v.length < 6 ? 'Min 6 characters' : null,
  -> Code: v == null || v.length < 6 ? 'Min 6 characters' : null,
L111 |                     ),
  -> Code: ),
L112 |                     const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L113 |
  -> Blank line
L114 |                     MyTextfiled(
  -> Code: MyTextfiled(
L115 |                       controller: passConfirm,
  -> Code: controller: passConfirm,
L116 |                       hint: 'Confirm your Password',
  -> Code: hint: 'Confirm your Password',
L117 |                       obsecure: true,
  -> Code: obsecure: true,
L118 |                       validator: (v) => v == null || v.isEmpty
  -> Code: validator: (v) => v == null || v.isEmpty
L119 |                           ? 'Please confirm password'
  -> Code: ? 'Please confirm password'
L120 |                           : null,
  -> Code: : null,
L121 |                     ),
  -> Code: ),
L122 |                     const SizedBox(height: 30),
  -> Variable declaration: const SizedBox(height: 30),
L123 |
  -> Blank line
L124 |                     SizedBox(
  -> Code: SizedBox(
L125 |                       width: 200,
  -> Code: width: 200,
L126 |                       child: MyButton(
  -> Code: child: MyButton(
L127 |                         function: isLoading ? null : _register,
  -> Code: function: isLoading ? null : _register,
L128 |                         text: isLoading ? 'Loading...' : 'Sign Up',
  -> Code: text: isLoading ? 'Loading...' : 'Sign Up',
L129 |                         minimumSize: const Size(140, 40),
  -> Code: minimumSize: const Size(140, 40),
L130 |                       ),
  -> Code: ),
L131 |                     ),
  -> Code: ),
L132 |                     const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L133 |
  -> Blank line
L134 |                     Row(
  -> Code: Row(
L135 |                       mainAxisAlignment: MainAxisAlignment.center,
  -> Code: mainAxisAlignment: MainAxisAlignment.center,
L136 |                       children: [
  -> Code: children: [
L137 |                         const Text("Already have an account? "),
  -> Variable declaration: const Text("Already have an account? "),
L138 |                         TextButton(
  -> Code: TextButton(
L139 |                           onPressed: widget.togglePages,
  -> Code: onPressed: widget.togglePages,
L140 |                           child: const Text('Login'),
  -> Code: child: const Text('Login'),
L141 |                         ),
  -> Code: ),
L142 |                       ],
  -> Code: ],
```

```
L143 |                     ),
```
-> Code:),

```
L144 |                   ],
```
-> Code:],

```
L145 |                 ),
```
-> Code:),

```
L146 |               ),
```
-> Code:),

```
L147 |             ),
```
-> Code:),

```
L148 |           ),
```
-> Code:),

```
L149 |         ),
```
-> Code:),

```
L150 |       );
```
-> Code:);

```
L151 |     }
```
-> Code: }

```
L152 | }
```
-> Code: }

lib/features/chatgroup/cubit/chat_cubit.dart

```
L001 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L002 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L003 | import 'package:instproject/core/rebos/appwrite_storage_api.dart';
```
-> Imports module or package: import 'package:instproject/core/rebos/appwrite_storage_api.dart';

```
L004 | import 'package:instproject/features/chatgroup/cubit/chat_state.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/chat_state.dart';

```
L005 | import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';

```
L006 | import 'package:instproject/features/chatgroup/models/message_model.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/models/message_model.dart';

```
L007 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L008 |
```
-> Blank line

```
L009 | class ChatCubit extends Cubit<ChatState> {
```
-> Class declaration: class ChatCubit extends Cubit<ChatState> {

```
L010 |   final FireChatRepo repo;
```
-> Variable declaration: final FireChatRepo repo;

```
L011 |   final String groupId;
```
-> Variable declaration: final String groupId;

```
L012 |
```
-> Blank line

```
L013 |   ChatCubit({required this.repo, required this.groupId}) : super(ChatLoading());
```
-> Code: ChatCubit({required this.repo, required this.groupId}) : super(ChatLoading());

```
L014 |
```
-> Blank line

```
L015 |   Stream<List<MessageModel>> get messagesStream => repo.streamMessages(groupId);
```
-> Function/method declaration or async return type: Stream<List<MessageModel>> get messagesStream => repo.streamMessages(groupId);

```
L016 |
```
-> Blank line

```
L017 |   Future<void> sendText(String text) async {
```
-> Function/method declaration or async return type: Future<void> sendText(String text) async {

```
L018 |     final user = FirebaseAuth.instance.currentUser!;
```
-> Variable declaration: final user = FirebaseAuth.instance.currentUser!;

```
L019 |     final msg = MessageModel(
```
-> Variable declaration: final msg = MessageModel(

```
L020 |       id: DateTime.now().millisecondsSinceEpoch.toString(),
```
-> Code: id: DateTime.now().millisecondsSinceEpoch.toString(),

```
L021 |       senderId: user.uid,
```
-> Code: senderId: user.uid,

```
L022 |       senderName: user.displayName ?? user.email ?? 'User',
```
-> Code: senderName: user.displayName ?? user.email ?? 'User',

```
L023 |       text: text,
```
-> Code: text: text,

```
L024 |       timestamp: DateTime.now(),
```
-> Code: timestamp: DateTime.now(),

```
L025 |     );
```
-> Code:);

```
L026 |     await repo.sendMessage(groupId, msg);
```
-> Code: await repo.sendMessage(groupId, msg);

```
L027 |   }
```
-> Code: }

```
L028 |
```
-> Blank line

```
L029 |   Future<void> sendImage(File file) async {
```
-> Function/method declaration or async return type: Future<void> sendImage(File file) async {

```
L030 |     try {
```
-> Code: try {

```
L031 |       emit(ChatSending());
```
-> Code: emit(ChatSending());

```
L032 |       final url = await AppwriteStorageAPI.uploadImage(
```
-> Variable declaration: final url = await AppwriteStorageAPI.uploadImage(

```
L033 |         file,
```
-> Code: file,

```
L034 |         file.path.split('/').last,
```
-> Code: file.path.split('/').last,

```
L035 |       );
```
-> Code:);

```
L036 |       if (url == null) throw Exception("Upload failed");
```
-> Control flow statement: if (url == null) throw Exception("Upload failed");

```
L037 |
```
-> Blank line

```
L038 |       final user = FirebaseAuth.instance.currentUser!;
```
-> Variable declaration: final user = FirebaseAuth.instance.currentUser!;

```
L039 |       final msg = MessageModel(
```
-> Variable declaration: final msg = MessageModel(

```
L040 |         id: DateTime.now().millisecondsSinceEpoch.toString(),
```
-> Code: id: DateTime.now().millisecondsSinceEpoch.toString(),

```
L041 |         senderId: user.uid,
```
-> Code: senderId: user.uid,

```
L042 |         senderName: user.displayName ?? user.email ?? 'User',
```
-> Code: senderName: user.displayName ?? user.email ?? 'User',

```
L043 |         text: '',
```
-> Code: text: '',

```
L044 |         imageUrl: url,
```
-> Code: imageUrl: url,

```
L045 |         timestamp: DateTime.now(),
```
-> Code: timestamp: DateTime.now(),

```
L046 |       );
```
-> Code:);

```
L047 |       await repo.sendMessage(groupId, msg);
```
-> Code: await repo.sendMessage(groupId, msg);

```
L048 |       emit(ChatSent());
```
-> Code: emit(ChatSent());

```
L049 |     } catch (e) {
```
-> Code: } catch (e) {

```
L050 |       emit(ChatError(e.toString()));
```
-> Code: emit(ChatError(e.toString()));

```
L051 |     }
```
-> Code: }

```
L052 |   }
```
-> Code: }

```
L053 | }
```
-> Code: }

lib/features/chatgroup/cubit/chat_state.dart

```
L001 | import 'package:equatable/equatable.dart';
```
-> Imports module or package: import 'package:equatable/equatable.dart';

```
L002 |
```
-> Blank line

```
L003 | abstract class ChatState extends Equatable {
```
-> Class declaration (complex): abstract class ChatState extends Equatable {

```
L004 |   const ChatState();
```
-> Variable declaration: const ChatState();

```
L005 |   @override
```
-> Annotation/Decorator: @override

```
L006 |   List<Object?> get props => [];
```
-> Short arrow function/expression: List<Object?> get props => [];

```
L007 | }
```
-> Code: }

```
L008 |
```
-> Blank line

```
L009 | class ChatLoading extends ChatState {}
```
-> Class declaration: class ChatLoading extends ChatState {}

```
L010 |
```
-> Blank line

```
L011 | class ChatSending extends ChatState {}
```
-> Class declaration: class ChatSending extends ChatState {}

```
L012 |
```
-> Blank line

```
L013 | class ChatSent extends ChatState {}
```
-> Class declaration: class ChatSent extends ChatState {}

```
L014 |
```
-> Blank line

```
L015 | class ChatError extends ChatState {
```
-> Class declaration: class ChatError extends ChatState {

```
L016 |   final String message;
```
-> Variable declaration: final String message;

```
L017 |   const ChatError(this.message);
```
-> Variable declaration: const ChatError(this.message);

```
L018 |   @override
```
-> Annotation/Decorator: @override

```
L019 |   List<Object?> get props => [message];
```
-> Short arrow function/expression: List<Object?> get props => [message];

```
L020 | }
```
-> Code: }

lib/features/chatgroup/cubit/group_cubit.dart

```
L001 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L002 | import 'package:equatable/equatable.dart';
  -> Imports module or package: import 'package:equatable/equatable.dart';
L003 | import '../domain/group_repo.dart';
  -> Imports module or package: import '../domain/group_repo.dart';
L004 | import '../models/group_model.dart';
  -> Imports module or package: import '../models/group_model.dart';
L005 |
  -> Blank line
L006 | part 'group_states.dart';
  -> Library part/export directive: part 'group_states.dart';
L007 |
  -> Blank line
L008 | class GroupCubit extends Cubit<GroupState> {
  -> Class declaration: class GroupCubit extends Cubit<GroupState> {
L009 |   final GroupRepo repo;
  -> Variable declaration: final GroupRepo repo;
L010 |
  -> Blank line
L011 |   List<GroupModel> _allGroups = [];
  -> Code: List<GroupModel> _allGroups = [];
L012 |
  -> Blank line
L013 |   GroupCubit(this.repo) : super(GroupLoading());
  -> Code: GroupCubit(this.repo) : super(GroupLoading());
L014 |
  -> Blank line
L015 |   Future<void> loadGroups() async {
  -> Function/method declaration or async return type: Future<void> loadGroups() async {
L016 |     try {
  -> Code: try {
L017 |       emit(GroupLoading());
  -> Code: emit(GroupLoading());
L018 |       final groups = await repo.getGroups();
  -> Variable declaration: final groups = await repo.getGroups();
L019 |       _allGroups = groups;
  -> Code: _allGroups = groups;
L020 |       emit(GroupLoaded(groups));
  -> Code: emit(GroupLoaded(groups));
L021 |     } catch (e) {
  -> Code: } catch (e) {
L022 |       emit(GroupError(e.toString()));
  -> Code: emit(GroupError(e.toString()));
L023 |     }
  -> Code: }
L024 |   }
  -> Code: }
L025 |
  -> Blank line
L026 |   Future<void> createGroup(
  -> Function/method declaration or async return type: Future<void> createGroup(
L027 |     String name,
  -> Code: String name,
L028 |     List<String> memberUids,
  -> Code: List<String> memberUids,
L029 |     String imageUrl,
  -> Code: String imageUrl,
L030 |   ) async {
  -> Code: ) async {
L031 |     emit(GroupLoading());
  -> Code: emit(GroupLoading());
L032 |     try {
  -> Code: try {
L033 |       await repo.createGroup(name, memberUids, imageUrl);
  -> Code: await repo.createGroup(name, memberUids, imageUrl);
L034 |       await loadGroups();
  -> Code: await loadGroups();
```

```
L035 |     } catch (e) {
```
-> Code: } catch (e) {

```
L036 |       emit(GroupError(e.toString()));
```
-> Code: emit(GroupError(e.toString()));

```
L037 |     }
```
-> Code: }

```
L038 |   }
```
-> Code: }

```
L039 |
```
-> Blank line

```
L040 |   Future<void> joinGroup(String groupId, String userId) async {
```
-> Function/method declaration or async return type: Future<void> joinGroup(String groupId, String userId) async {

```
L041 |     try {
```
-> Code: try {

```
L042 |       await repo.joinGroup(groupId, userId);
```
-> Code: await repo.joinGroup(groupId, userId);

```
L043 |       await loadGroups();
```
-> Code: await loadGroups();

```
L044 |     } catch (e) {
```
-> Code: } catch (e) {

```
L045 |       emit(GroupError(e.toString()));
```
-> Code: emit(GroupError(e.toString()));

```
L046 |     }
```
-> Code: }

```
L047 |   }
```
-> Code: }

```
L048 |
```
-> Blank line

```
L049 |   Future<void> refreshGroups() async {
```
-> Function/method declaration or async return type: Future<void> refreshGroups() async {

```
L050 |     try {
```
-> Code: try {

```
L051 |       final groups = await repo.getGroups();
```
-> Variable declaration: final groups = await repo.getGroups();

```
L052 |       _allGroups = groups;
```
-> Code: _allGroups = groups;

```
L053 |       emit(GroupLoaded(groups));
```
-> Code: emit(GroupLoaded(groups));

```
L054 |     } catch (e) {
```
-> Code: } catch (e) {

```
L055 |       emit(GroupError(e.toString()));
```
-> Code: emit(GroupError(e.toString()));

```
L056 |     }
```
-> Code: }

```
L057 |   }
```
-> Code: }

```
L058 |
```
-> Blank line

```
L059 |   void searchGroups(String query) {
```
-> Function/method declaration or async return type: void searchGroups(String query) {

```
L060 |     if (state is! GroupLoaded) return;
```
-> Control flow statement: if (state is! GroupLoaded) return;

```
L061 |     if (query.isEmpty) {
```
-> Control flow statement: if (query.isEmpty) {

```
L062 |       emit(GroupLoaded(_allGroups));
```
-> Code: emit(GroupLoaded(_allGroups));

```
L063 |       return;
```
-> Code: return;

```
L064 |     }
```
-> Code: }

```
L065 |     final filtered = _allGroups
```
-> Variable declaration: final filtered = _allGroups

```
L066 |         .where(
```
-> Code: .where(

```
L067 |           (g) =>
```
-> Code: (g) =>

```
L068 |               g.name.toLowerCase().contains(query.toLowerCase()) ||
```
-> Code: g.name.toLowerCase().contains(query.toLowerCase()) ||

```
L069 |               (g.description?.toLowerCase().contains(query.toLowerCase()) ??
```
-> Code: (g.description?.toLowerCase().contains(query.toLowerCase()) ??

```
L070 |                   false),
```
-> Code: false),

```
L071 |          )
```
-> Code:)

```
L072 |          .toList();
```
-> Code: .toList();

```
L073 |      emit(GroupLoaded(filtered));
```
-> Code: emit(GroupLoaded(filtered));

```
L074 |    }
```
-> Code: }

```
L075 | }
```
-> Code: }

lib/features/chatgroup/cubit/group_states.dart

```
L001 | part of 'group_cubit.dart';
  -> Library part/export directive: part of 'group_cubit.dart';
L002 |
  -> Blank line
L003 | abstract class GroupState extends Equatable {
  -> Class declaration (complex): abstract class GroupState extends Equatable {
L004 |   const GroupState();
  -> Variable declaration: const GroupState();
L005 |
  -> Blank line
L006 |   @override
  -> Annotation/Decorator: @override
L007 |   List<Object?> get props => [];
  -> Short arrow function/expression: List<Object?> get props => [];
L008 | }
  -> Code: }
L009 |
  -> Blank line
L010 | class GroupLoading extends GroupState {}
  -> Class declaration: class GroupLoading extends GroupState {}
L011 |
  -> Blank line
L012 | class GroupLoaded extends GroupState {
  -> Class declaration: class GroupLoaded extends GroupState {
L013 |   final List<GroupModel> groups;
  -> Variable declaration: final List<GroupModel> groups;
L014 |
  -> Blank line
L015 |   const GroupLoaded(this.groups);
  -> Variable declaration: const GroupLoaded(this.groups);
L016 |
  -> Blank line
L017 |   @override
  -> Annotation/Decorator: @override
L018 |   List<Object?> get props => [groups];
  -> Short arrow function/expression: List<Object?> get props => [groups];
L019 | }
  -> Code: }
L020 |
  -> Blank line
L021 | class GroupError extends GroupState {
  -> Class declaration: class GroupError extends GroupState {
L022 |   final String message;
  -> Variable declaration: final String message;
L023 |
  -> Blank line
L024 |   const GroupError(this.message);
  -> Variable declaration: const GroupError(this.message);
L025 |
  -> Blank line
L026 |   @override
  -> Annotation/Decorator: @override
L027 |   List<Object?> get props => [message];
  -> Short arrow function/expression: List<Object?> get props => [message];
L028 | }
  -> Code: }
```

lib/features/chatgroup/data/fire_chat_repo.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L002 | import 'package:instproject/features/chatgroup/models/message_model.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/models/message_model.dart';

```
L003 |
```
-> Blank line

```
L004 |
```
-> Blank line

```
L005 | class FireChatRepo {
```
-> Class declaration: class FireChatRepo {

```
L006 |   final _firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final _firestore = FirebaseFirestore.instance;

```
L007 |
```
-> Blank line

```
L008 |   Stream<List<MessageModel>> streamMessages(String groupId) {
```
-> Function/method declaration or async return type: Stream<List<MessageModel>> streamMessages(String groupId) {

```
L009 |     return _firestore
```
-> Return statement: return _firestore

```
L010 |         .collection('groups')
```
-> Code: .collection('groups')

```
L011 |         .doc(groupId)
```
-> Code: .doc(groupId)

```
L012 |         .collection('messages')
```
-> Code: .collection('messages')

```
L013 |         .orderBy('timestamp', descending: true)
```
-> Code: .orderBy('timestamp', descending: true)

```
L014 |         .snapshots()
```
-> Code: .snapshots()

```
L015 |         .map(
```
-> Code: .map(

```
L016 |           (snap) =>
```
-> Code: (snap) =>

```
L017 |               snap.docs.map((e) => MessageModel.fromMap(e.data())).toList(),
```
-> Code: snap.docs.map((e) => MessageModel.fromMap(e.data())).toList(),

```
L018 |         );
```
-> Code:);

```
L019 |   }
```
-> Code: }

```
L020 |
```
-> Blank line

```
L021 |   Future<void> sendMessage(String groupId, MessageModel msg) async {
```
-> Function/method declaration or async return type: Future<void> sendMessage(String groupId, MessageModel msg) async {

```
L022 |     await _firestore
```
-> Code: await _firestore

```
L023 |         .collection('groups')
```
-> Code: .collection('groups')

```
L024 |         .doc(groupId)
```
-> Code: .doc(groupId)

```
L025 |         .collection('messages')
```
-> Code: .collection('messages')

```
L026 |         .doc(msg.id)
```
-> Code: .doc(msg.id)

```
L027 |         .set(msg.toMap());
```
-> Code: .set(msg.toMap());

```
L028 |   }
```
-> Code: }

```
L029 | }
```
-> Code: }

lib/features/chatgroup/data/fire_group_repo.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L002 | import '../domain/group_repo.dart';
```
-> Imports module or package: import '../domain/group_repo.dart';

```
L003 | import '../models/group_model.dart';
```
-> Imports module or package: import '../models/group_model.dart';

```
L004 |
```
-> Blank line

```
L005 | class FireGroupRepo implements GroupRepo {
```
-> Class declaration: class FireGroupRepo implements GroupRepo {

```
L006 |   final _firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final _firestore = FirebaseFirestore.instance;

```
L007 |
```
-> Blank line

```
L008 |   @override
```
-> Annotation/Decorator: @override

```
L009 |   Future<List<GroupModel>> getGroups() async {
```
-> Function/method declaration or async return type: Future<List<GroupModel>> getGroups() async {

```
L010 |     final snap = await _firestore.collection('groups').get();
```
-> Variable declaration: final snap = await _firestore.collection('groups').get();

```
L011 |     return snap.docs.map((e) => GroupModel.fromMap(e.data())).toList();
```
-> Return statement: return snap.docs.map((e) => GroupModel.fromMap(e.data())).toList();

```
L012 |   }
```
-> Code: }

```
L013 |
```
-> Blank line

```
L014 |   @override
```
-> Annotation/Decorator: @override

```
L015 |   Future<void> createGroup(
```
-> Function/method declaration or async return type: Future<void> createGroup(

```
L016 |     String name,
```
-> Code: String name,

```
L017 |     List<String> memberUids,
```
-> Code: List<String> memberUids,

```
L018 |     String imageUrl,
```
-> Code: String imageUrl,

```
L019 |   ) async {
```
-> Code:) async {

```
L020 |     final groupRef = FirebaseFirestore.instance.collection('groups').doc();
```
-> Variable declaration: final groupRef = FirebaseFirestore.instance.collection('groups').doc();

```
L021 |
```
-> Blank line

```
L022 |     await groupRef.set({
```
-> Code: await groupRef.set({

```
L023 |       'id': groupRef.id,
```
-> Code: 'id': groupRef.id,

```
L024 |       'name': name,
```
-> Code: 'name': name,

```
L025 |       'members': memberUids,
```
-> Code: 'members': memberUids,

```
L026 |       'imageUrl': imageUrl,
```
-> Code: 'imageUrl': imageUrl,

```
L027 |       'createdAt': DateTime.now().millisecondsSinceEpoch,
```
-> Code: 'createdAt': DateTime.now().millisecondsSinceEpoch,

```
L028 |     });
```
-> Code: });

```
L029 |   }
```
-> Code: }

```
L030 |
```
-> Blank line

```
L031 |   @override
```
-> Annotation/Decorator: @override

```
L032 |   Future<void> joinGroup(String groupId, String userId) async {
```
-> Function/method declaration or async return type: Future<void> joinGroup(String groupId, String userId) async {

```
L033 |     final groupRef = _firestore.collection('groups').doc(groupId);
```
-> Variable declaration: final groupRef = _firestore.collection('groups').doc(groupId);

```
L034 |     final doc = await groupRef.get();
```
-> Variable declaration: final doc = await groupRef.get();

```
L035 |
```
-> Blank line

```
L036 |     if (!doc.exists) return;
```
-> Control flow statement: if (!doc.exists) return;

```
L037 |
```
-> Blank line

```
L038 |     final data = doc.data()!;
```
-> Variable declaration: final data = doc.data()!;

```
L039 |     final members = List<String>.from(data['members'] ?? []);
```
-> Variable declaration: final members = List<String>.from(data['members'] ?? []);

```
L040 |
```
-> Blank line

```
L041 |     if (!members.contains(userId)) {
```
-> Control flow statement: if (!members.contains(userId)) {

```
L042 |       members.add(userId);
```
-> Code: members.add(userId);

```
L043 |       await groupRef.update({'members': members});
```
-> Code: await groupRef.update({'members': members});

```
L044 |       print(' User $userId joined group $groupId');
```
-> Code: print(' User $userId joined group $groupId');

```
L045 |     } else {
```
-> Code: } else {

```
L046 |       print(' User $userId already in group $groupId');
```
-> Code: print(' User $userId already in group $groupId');

```
L047 |     }
```
-> Code: }

```
L048 |   }
```
-> Code: }

```
L049 | }
```
-> Code: }

lib/features/chatgroup/domain/group_repo.dart

```
L001 | import '../models/group_model.dart';
```
-> Imports module or package: import '../models/group_model.dart';

```
L002 |
```
-> Blank line

```
L003 | abstract class GroupRepo {
```
-> Class declaration (complex): abstract class GroupRepo {

```
L004 |   Future<List<GroupModel>> getGroups();
```
-> Function/method declaration or async return type: Future<List<GroupModel>> getGroups();

```
L005 |   Future<void> createGroup(
```
-> Function/method declaration or async return type: Future<void> createGroup(

```
L006 |     String name,
```
-> Code: String name,

```
L007 |     List<String> memberUids,
```
-> Code: List<String> memberUids,

```
L008 |     String imageUrl,
```
-> Code: String imageUrl,

```
L009 |   );
```
-> Code:);

```
L010 |   Future<void> joinGroup(String groupId, String userId);
```
-> Function/method declaration or async return type: Future<void> joinGroup(String groupId, String userId);

```
L011 | }
```
-> Code: }

lib/features/chatgroup/models/group_model.dart

```
L001 | import 'package:equatable/equatable.dart';
  -> Imports module or package: import 'package:equatable/equatable.dart';
L002 |
  -> Blank line
L003 | class GroupModel extends Equatable {
  -> Class declaration: class GroupModel extends Equatable {
L004 |   final String id;
  -> Variable declaration: final String id;
L005 |   final String name;
  -> Variable declaration: final String name;
L006 |   final String? description;
  -> Variable declaration: final String? description;
L007 |   final String imageUrl;
  -> Variable declaration: final String imageUrl;
L008 |   final String? lastMessage;
  -> Variable declaration: final String? lastMessage;
L009 |   final String? lastSender;
  -> Variable declaration: final String? lastSender;
L010 |   final List<String> members;
  -> Variable declaration: final List<String> members;
L011 |   final DateTime? createdAt;
  -> Variable declaration: final DateTime? createdAt;
L012 |
  -> Blank line
L013 |   const GroupModel({
  -> Variable declaration: const GroupModel({
L014 |     required this.id,
  -> Code: required this.id,
L015 |     required this.name,
  -> Code: required this.name,
L016 |     this.description,
  -> Code: this.description,
L017 |     required this.imageUrl,
  -> Code: required this.imageUrl,
L018 |     this.lastMessage,
  -> Code: this.lastMessage,
L019 |     this.lastSender,
  -> Code: this.lastSender,
L020 |     required this.members,
  -> Code: required this.members,
L021 |     this.createdAt,
  -> Code: this.createdAt,
L022 |   });
  -> Code: });
L023 |
  -> Blank line
L024 |
  -> Blank line
L025 |   Map<String, dynamic> toMap() => {
  -> Code: Map<String, dynamic> toMap() => {
L026 |     'id': id,
  -> Code: 'id': id,
L027 |     'name': name,
  -> Code: 'name': name,
L028 |     'description': description ?? '',
  -> Code: 'description': description ?? '',
L029 |     'imageUrl': imageUrl,
  -> Code: 'imageUrl': imageUrl,
L030 |     'lastMessage': lastMessage ?? '',
  -> Code: 'lastMessage': lastMessage ?? '',
L031 |     'lastSender': lastSender ?? '',
  -> Code: 'lastSender': lastSender ?? '',
L032 |     'members': members,
  -> Code: 'members': members,
L033 |     'createdAt': createdAt?.millisecondsSinceEpoch,
  -> Code: 'createdAt': createdAt?.millisecondsSinceEpoch,
L034 |   };
  -> Code: };
```

```
L035 |
```
-> Blank line

```
L036 |
```
-> Blank line

```
L037 |   factory GroupModel.fromMap(Map<String, dynamic> map, {String? id}) {
```
-> Code: factory GroupModel.fromMap(Map<String, dynamic> map, {String? id}) {

```
L038 |     return GroupModel(
```
-> Return statement: return GroupModel(

```
L039 |       id: id ?? map['id'] ?? '',
```
-> Code: id: id ?? map['id'] ?? '',

```
L040 |       name: map['name'] ?? '',
```
-> Code: name: map['name'] ?? '',

```
L041 |       description: (map['description'] is String) ? map['description'] : null,
```
-> Code: description: (map['description'] is String) ? map['description'] : null,

```
L042 |       imageUrl: map['imageUrl'] ?? '',
```
-> Code: imageUrl: map['imageUrl'] ?? '',

```
L043 |       lastMessage: (map['lastMessage'] is String) ? map['lastMessage'] : null,
```
-> Code: lastMessage: (map['lastMessage'] is String) ? map['lastMessage'] : null,

```
L044 |       lastSender: (map['lastSender'] is String) ? map['lastSender'] : null,
```
-> Code: lastSender: (map['lastSender'] is String) ? map['lastSender'] : null,

```
L045 |       members: List<String>.from(map['members'] ?? []),
```
-> Code: members: List<String>.from(map['members'] ?? []),

```
L046 |       createdAt: map['createdAt'] != null
```
-> Code: createdAt: map['createdAt'] != null

```
L047 |           ? DateTime.fromMillisecondsSinceEpoch(
```
-> Code: ? DateTime.fromMillisecondsSinceEpoch(

```
L048 |               (map['createdAt'] is int)
```
-> Code: (map['createdAt'] is int)

```
L049 |                   ? map['createdAt']
```
-> Code: ? map['createdAt']

```
L050 |                   : int.tryParse(map['createdAt'].toString()) ?? 0,
```
-> Code: : int.tryParse(map['createdAt'].toString()) ?? 0,

```
L051 |             )
```
-> Code:)

```
L052 |           : null,
```
-> Code: : null,

```
L053 |     );
```
-> Code:);

```
L054 |   }
```
-> Code: }

```
L055 |
```
-> Blank line

```
L056 |
```
-> Blank line

```
L057 |   bool matchesQuery(String query) {
```
-> Code: bool matchesQuery(String query) {

```
L058 |     final q = query.toLowerCase();
```
-> Variable declaration: final q = query.toLowerCase();

```
L059 |     final inName = name.toLowerCase().contains(q);
```
-> Variable declaration: final inName = name.toLowerCase().contains(q);

```
L060 |     final inDesc = (description?.toLowerCase().contains(q)) ?? false;
```
-> Variable declaration: final inDesc = (description?.toLowerCase().contains(q)) ?? false;

```
L061 |     final inLast = (lastMessage?.toLowerCase().contains(q)) ?? false;
```
-> Variable declaration: final inLast = (lastMessage?.toLowerCase().contains(q)) ?? false;

```
L062 |     return inName || inDesc || inLast;
```
-> Return statement: return inName || inDesc || inLast;

```
L063 |   }
```
-> Code: }

```
L064 |
```
-> Blank line

```
L065 |   @override
```
-> Annotation/Decorator: @override

```
L066 |   List<Object?> get props => [
```
-> Code: List<Object?> get props => [

```
L067 |     id,
```
-> Code: id,

```
L068 |     name,
```
-> Code: name,

```
L069 |     description,
```
-> Code: description,

```
L070 |     lastMessage,
```
-> Code: lastMessage,

```
L071 |     lastSender,
```
-> Code: lastSender,

```
L072 |     members,
```
-> Code: members,

```
L073 |   ];
```
-> Code:];

```
L074 | }
```
-> Code: }

lib/features/chatgroup/models/message_model.dart

```
L001 | import 'package:equatable/equatable.dart';
```
-> Imports module or package: import 'package:equatable/equatable.dart';

```
L002 |
```
-> Blank line

```
L003 | class MessageModel extends Equatable {
```
-> Class declaration: class MessageModel extends Equatable {

```
L004 |   final String id;
```
-> Variable declaration: final String id;

```
L005 |   final String senderId;
```
-> Variable declaration: final String senderId;

```
L006 |   final String senderName;
```
-> Variable declaration: final String senderName;

```
L007 |   final String text;
```
-> Variable declaration: final String text;

```
L008 |   final String? imageUrl;
```
-> Variable declaration: final String? imageUrl;

```
L009 |   final DateTime timestamp;
```
-> Variable declaration: final DateTime timestamp;

```
L010 |
```
-> Blank line

```
L011 |   const MessageModel({
```
-> Variable declaration: const MessageModel({

```
L012 |     required this.id,
```
-> Code: required this.id,

```
L013 |     required this.senderId,
```
-> Code: required this.senderId,

```
L014 |     required this.senderName,
```
-> Code: required this.senderName,

```
L015 |     required this.text,
```
-> Code: required this.text,

```
L016 |     this.imageUrl,
```
-> Code: this.imageUrl,

```
L017 |     required this.timestamp,
```
-> Code: required this.timestamp,

```
L018 |   });
```
-> Code: });

```
L019 |
```
-> Blank line

```
L020 |   Map<String, dynamic> toMap() => {
```
-> Code: Map<String, dynamic> toMap() => {

```
L021 |     'id': id,
```
-> Code: 'id': id,

```
L022 |     'senderId': senderId,
```
-> Code: 'senderId': senderId,

```
L023 |     'senderName': senderName,
```
-> Code: 'senderName': senderName,

```
L024 |     'text': text,
```
-> Code: 'text': text,

```
L025 |     'imageUrl': imageUrl,
```
-> Code: 'imageUrl': imageUrl,

```
L026 |     'timestamp': timestamp.toIso8601String(),
```
-> Code: 'timestamp': timestamp.toIso8601String(),

```
L027 |   };
```
-> Code: };

```
L028 |
```
-> Blank line

```
L029 |   factory MessageModel.fromMap(Map<String, dynamic> map) => MessageModel(
```
-> Code: factory MessageModel.fromMap(Map<String, dynamic> map) => MessageModel(

```
L030 |     id: map['id'] ?? '',
```
-> Code: id: map['id'] ?? '',

```
L031 |     senderId: map['senderId'] ?? '',
```
-> Code: senderId: map['senderId'] ?? '',

```
L032 |     senderName: map['senderName'] ?? '',
```
-> Code: senderName: map['senderName'] ?? '',

```
L033 |     text: map['text'] ?? '',
```
-> Code: text: map['text'] ?? '',

```
L034 |     imageUrl: map['imageUrl'],
```
-> Code: imageUrl: map['imageUrl'],

```
L035 |     timestamp: DateTime.parse(map['timestamp']),
```
-> Code: timestamp: DateTime.parse(map['timestamp']),

```
L036 |   );
```
-> Code:);

```
L037 |
```
-> Blank line

```
L038 |   @override
```
-> Annotation/Decorator: @override

```
L039 |   List<Object?> get props => [id, senderId, text, imageUrl, timestamp];
```
-> Short arrow function/expression: List<Object?> get props => [id, senderId, text, imageUrl, timestamp];

```
L040 | }
```
-> Code: }

lib/features/chatgroup/models/user_model.dart

```
L001 | class UserModel {
  -> Class declaration: class UserModel {
L002 |   final String id;
  -> Variable declaration: final String id;
L003 |   final String name;
  -> Variable declaration: final String name;
L004 |   final String email;
  -> Variable declaration: final String email;
L005 |   final String? imageUrl;
  -> Variable declaration: final String? imageUrl;
L006 |
  -> Blank line
L007 |
  -> Blank line
L008 |   UserModel({
  -> Code: UserModel({
L009 |     required this.id,
  -> Code: required this.id,
L010 |     required this.name,
  -> Code: required this.name,
L011 |     required this.email,
  -> Code: required this.email,
L012 |     this.imageUrl,
  -> Code: this.imageUrl,
L013 |   });
  -> Code: });
L014 |
  -> Blank line
L015 |
  -> Blank line
L016 |   Map<String, dynamic> toMap() => {
  -> Code: Map<String, dynamic> toMap() => {
L017 |         'id': id,
  -> Code: 'id': id,
L018 |         'name': name,
  -> Code: 'name': name,
L019 |         'email': email,
  -> Code: 'email': email,
L020 |         'imageUrl': imageUrl,
  -> Code: 'imageUrl': imageUrl,
L021 |       };
  -> Code: };
L022 |
  -> Blank line
L023 |
  -> Blank line
L024 |   factory UserModel.fromMap(Map<String, dynamic> map) => UserModel(
  -> Code: factory UserModel.fromMap(Map<String, dynamic> map) => UserModel(
L025 |         id: map['id'],
  -> Code: id: map['id'],
L026 |         name: map['name'],
  -> Code: name: map['name'],
L027 |         email: map['email'],
  -> Code: email: map['email'],
L028 |         imageUrl: map['imageUrl'],
  -> Code: imageUrl: map['imageUrl'],
L029 |       );
  -> Code: );
L030 | }
  -> Code: }
```

lib/features/chatgroup/pages/chat_page.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:image_picker/image_picker.dart';
```
-> Imports module or package: import 'package:image_picker/image_picker.dart';

```
L005 | import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';

```
L006 | import '../widgets/message_bubble.dart';
```
-> Imports module or package: import '../widgets/message_bubble.dart';

```
L007 | import '../../chatgroup/models/group_model.dart';
```
-> Imports module or package: import '../../chatgroup/models/group_model.dart';

```
L008 |
```
-> Blank line

```
L009 | class ChatPage extends StatefulWidget {
```
-> Class declaration: class ChatPage extends StatefulWidget {

```
L010 |   final GroupModel group;
```
-> Variable declaration: final GroupModel group;

```
L011 |   const ChatPage({super.key, required this.group});
```
-> Variable declaration: const ChatPage({super.key, required this.group});

```
L012 |
```
-> Blank line

```
L013 |   @override
```
-> Annotation/Decorator: @override

```
L014 |   State<ChatPage> createState() => _ChatPageState();
```
-> Short arrow function/expression: State<ChatPage> createState() => _ChatPageState();

```
L015 | }
```
-> Code: }

```
L016 |
```
-> Blank line

```
L017 | class _ChatPageState extends State<ChatPage> {
```
-> Class declaration: class _ChatPageState extends State<ChatPage> {

```
L018 |   final controller = TextEditingController();
```
-> Variable declaration: final controller = TextEditingController();

```
L019 |   File? _selectedImage;
```
-> Code: File? _selectedImage;

```
L020 |
```
-> Blank line

```
L021 |
```
-> Blank line

```
L022 |   Future<void> _pickImage() async {
```
-> Function/method declaration or async return type: Future<void> _pickImage() async {

```
L023 |     final picked = await ImagePicker().pickImage(source: ImageSource.gallery);
```
-> Variable declaration: final picked = await ImagePicker().pickImage(source: ImageSource.gallery);

```
L024 |     if (picked != null) {
```
-> Control flow statement: if (picked != null) {

```
L025 |       setState(() => _selectedImage = File(picked.path));
```
-> Short arrow function/expression: setState(() => _selectedImage = File(picked.path));

```
L026 |     }
```
-> Code: }

```
L027 |   }
```
-> Code: }

```
L028 |
```
-> Blank line

```
L029 |   @override
```
-> Annotation/Decorator: @override

```
L030 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L031 |     final chatCubit = context.read<ChatCubit>();
```
-> Variable declaration: final chatCubit = context.read<ChatCubit>();

```
L032 |
```
-> Blank line

```
L033 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L034 |       appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L035 |         titleSpacing: 0,
  -> Code: titleSpacing: 0,
L036 |         title: Row(
  -> Code: title: Row(
L037 |           children: [
  -> Code: children: [
L038 |             CircleAvatar(
  -> Code: CircleAvatar(
L039 |               backgroundImage:
  -> Code: backgroundImage:
L040 |                   widget.group.imageUrl != null &&
  -> Code: widget.group.imageUrl != null &&
L041 |                       widget.group.imageUrl!.isNotEmpty
  -> Code: widget.group.imageUrl!.isNotEmpty
L042 |                   ? NetworkImage(widget.group.imageUrl!)
  -> Code: ? NetworkImage(widget.group.imageUrl!)
L043 |                   : null,
  -> Code: : null,
L044 |               child:
  -> Code: child:
L045 |                   widget.group.imageUrl == null ||
  -> Code: widget.group.imageUrl == null ||
L046 |                       widget.group.imageUrl!.isEmpty
  -> Code: widget.group.imageUrl!.isEmpty
L047 |                   ? const Icon(Icons.group)
  -> Code: ? const Icon(Icons.group)
L048 |                   : null,
  -> Code: : null,
L049 |             ),
  -> Code: ),
L050 |             const SizedBox(width: 12),
  -> Variable declaration: const SizedBox(width: 12),
L051 |             Expanded(
  -> Code: Expanded(
L052 |               child: Text(
  -> Code: child: Text(
L053 |                 widget.group.name,
  -> Code: widget.group.name,
L054 |                 style: const TextStyle(
  -> Code: style: const TextStyle(
L055 |                   fontWeight: FontWeight.bold,
  -> Code: fontWeight: FontWeight.bold,
L056 |                   fontSize: 18,
  -> Code: fontSize: 18,
L057 |                 ),
  -> Code: ),
L058 |                 overflow: TextOverflow.ellipsis,
  -> Code: overflow: TextOverflow.ellipsis,
L059 |               ),
  -> Code: ),
L060 |             ),
  -> Code: ),
L061 |           ],
  -> Code: ],
L062 |         ),
  -> Code: ),
L063 |       ),
  -> Code: ),
L064 |
  -> Blank line
L065 |       body: Column(
  -> Code: body: Column(
L066 |         children: [
  -> Code: children: [
L067 |
  -> Blank line
L068 |           Expanded(
  -> Code: Expanded(
L069 |             child: StreamBuilder(
  -> Code: child: StreamBuilder(
L070 |               stream: chatCubit.messagesStream,
  -> Code: stream: chatCubit.messagesStream,
```

```
L071 |                builder: (context, snapshot) {
  -> Code: builder: (context, snapshot) {
L072 |                  if (!snapshot.hasData) {
  -> Control flow statement: if (!snapshot.hasData) {
L073 |                    return const Center(child: CircularProgressIndicator());
  -> Return statement: return const Center(child: CircularProgressIndicator());
L074 |                  }
  -> Code: }
L075 |                  final msgs = snapshot.data!;
  -> Variable declaration: final msgs = snapshot.data!;
L076 |                  return ListView.builder(
  -> Return statement: return ListView.builder(
L077 |                    reverse: true,
  -> Code: reverse: true,
L078 |                    itemCount: msgs.length,
  -> Code: itemCount: msgs.length,
L079 |                    itemBuilder: (_, i) => MessageBubble(msg: msgs[i]),
  -> Code: itemBuilder: (_, i) => MessageBubble(msg: msgs[i]),
L080 |                  );
  -> Code: );
L081 |                },
  -> Code: },
L082 |              ),
  -> Code: ),
L083 |            ),
  -> Code: ),
L084 |
  -> Blank line
L085 |
  -> Blank line
L086 |            if (_selectedImage != null)
  -> Control flow statement: if (_selectedImage != null)
L087 |              Stack(
  -> Code: Stack(
L088 |                alignment: Alignment.topRight,
  -> Code: alignment: Alignment.topRight,
L089 |                children: [
  -> Code: children: [
L090 |                  Container(
  -> Code: Container(
L091 |                    margin: const EdgeInsets.all(8),
  -> Code: margin: const EdgeInsets.all(8),
L092 |                    height: 150,
  -> Code: height: 150,
L093 |                    width: double.infinity,
  -> Code: width: double.infinity,
L094 |                    decoration: BoxDecoration(
  -> Code: decoration: BoxDecoration(
L095 |                      borderRadius: BorderRadius.circular(12),
  -> Code: borderRadius: BorderRadius.circular(12),
L096 |                      image: DecorationImage(
  -> Code: image: DecorationImage(
L097 |                        image: FileImage(_selectedImage!),
  -> Code: image: FileImage(_selectedImage!),
L098 |                        fit: BoxFit.cover,
  -> Code: fit: BoxFit.cover,
L099 |                      ),
  -> Code: ),
L100 |                    ),
  -> Code: ),
L101 |                ),
  -> Code: ),
L102 |
  -> Blank line
L103 |                IconButton(
  -> Code: IconButton(
L104 |                    icon: const Icon(Icons.close, color: Colors.red),
  -> Code: icon: const Icon(Icons.close, color: Colors.red),
L105 |                    onPressed: () {
  -> Code: onPressed: () {
L106 |                      setState(() => _selectedImage = null);
  -> Short arrow function/expression: setState(() => _selectedImage = null);
```

```
L107 |                     },
  -> Code: },
L108 |                   ),
  -> Code: ),
L109 |                 ],
  -> Code: ],
L110 |               ),
  -> Code: ),
L111 |
  -> Blank line
L112 |
  -> Blank line
L113 |             Padding(
  -> Code: Padding(
L114 |               padding: const EdgeInsets.all(8),
  -> Code: padding: const EdgeInsets.all(8),
L115 |               child: Row(
  -> Code: child: Row(
L116 |                 children: [
  -> Code: children: [
L117 |                   IconButton(
  -> Code: IconButton(
L118 |                     icon: const Icon(Icons.image),
  -> Code: icon: const Icon(Icons.image),
L119 |                     onPressed: _pickImage,
  -> Code: onPressed: _pickImage,
L120 |                   ),
  -> Code: ),
L121 |                   Expanded(
  -> Code: Expanded(
L122 |                     child: TextField(
  -> Code: child: TextField(
L123 |                       controller: controller,
  -> Code: controller: controller,
L124 |                       decoration: const InputDecoration(
  -> Code: decoration: const InputDecoration(
L125 |                         hintText: "Type a message...",
  -> Code: hintText: "Type a message...",
L126 |                         border: InputBorder.none,
  -> Code: border: InputBorder.none,
L127 |                       ),
  -> Code: ),
L128 |                     ),
  -> Code: ),
L129 |                   ),
  -> Code: ),
L130 |                   IconButton(
  -> Code: IconButton(
L131 |                     icon: const Icon(Icons.send),
  -> Code: icon: const Icon(Icons.send),
L132 |                     onPressed: () {
  -> Code: onPressed: () {
L133 |                       final text = controller.text.trim();
  -> Variable declaration: final text = controller.text.trim();
L134 |
  -> Blank line
L135 |                       if (_selectedImage != null) {
  -> Control flow statement: if (_selectedImage != null) {
L136 |
  -> Blank line
L137 |                         chatCubit.sendImage(_selectedImage!);
  -> Code: chatCubit.sendImage(_selectedImage!);
L138 |                         setState(() => _selectedImage = null);
  -> Short arrow function/expression: setState(() => _selectedImage = null);
L139 |                       }
  -> Code: }
L140 |
  -> Blank line
L141 |                       if (text.isNotEmpty) {
  -> Control flow statement: if (text.isNotEmpty) {
L142 |                         chatCubit.sendText(text);
  -> Code: chatCubit.sendText(text);
```

```
L143 |                         controller.clear();
```
-> Code: controller.clear();

```
L144 |                       }
```
-> Code: }

```
L145 |                     },
```
-> Code: },

```
L146 |                   ),
```
-> Code:),

```
L147 |                 ],
```
-> Code:],

```
L148 |               ),
```
-> Code:),

```
L149 |             ),
```
-> Code:),

```
L150 |           ],
```
-> Code:],

```
L151 |         ),
```
-> Code:),

```
L152 |       );
```
-> Code:);

```
L153 |     }
```
-> Code: }

```
L154 | }
```
-> Code: }

lib/features/chatgroup/pages/create_group_page.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L005 | import 'package:image_picker/image_picker.dart';
```
-> Imports module or package: import 'package:image_picker/image_picker.dart';

```
L006 | import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';

```
L007 | import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';

```
L008 |
```
-> Blank line

```
L009 | class CreateGroupPage extends StatefulWidget {
```
-> Class declaration: class CreateGroupPage extends StatefulWidget {

```
L010 |   const CreateGroupPage({super.key});
```
-> Variable declaration: const CreateGroupPage({super.key});

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   State<CreateGroupPage> createState() => _CreateGroupPageState();
```
-> Short arrow function/expression: State<CreateGroupPage> createState() => _CreateGroupPageState();

```
L014 | }
```
-> Code: }

```
L015 |
```
-> Blank line

```
L016 | class _CreateGroupPageState extends State<CreateGroupPage> {
```
-> Class declaration: class _CreateGroupPageState extends State<CreateGroupPage> {

```
L017 |   final nameController = TextEditingController();
```
-> Variable declaration: final nameController = TextEditingController();

```
L018 |   final Set<String> selectedUsers = {};
```
-> Variable declaration: final Set<String> selectedUsers = {};

```
L019 |   File? groupImage;
```
-> Code: File? groupImage;

```
L020 |   bool _isLoading = false;
```
-> Code: bool _isLoading = false;

```
L021 |
```
-> Blank line

```
L022 |   Future<void> pickImage() async {
```
-> Function/method declaration or async return type: Future<void> pickImage() async {

```
L023 |     final picker = ImagePicker();
```
-> Variable declaration: final picker = ImagePicker();

```
L024 |     final picked = await picker.pickImage(source: ImageSource.gallery);
```
-> Variable declaration: final picked = await picker.pickImage(source: ImageSource.gallery);

```
L025 |     if (picked != null) {
```
-> Control flow statement: if (picked != null) {

```
L026 |       setState(() => groupImage = File(picked.path));
```
-> Short arrow function/expression: setState(() => groupImage = File(picked.path));

```
L027 |     }
```
-> Code: }

```
L028 |   }
```
-> Code: }

```
L029 |
```
-> Blank line

```
L030 |   @override
```
-> Annotation/Decorator: @override

```
L031 |   void dispose() {
```
-> Function/method declaration or async return type: void dispose() {

```
L032 |     nameController.dispose();
```
-> Code: nameController.dispose();

```
L033 |     super.dispose();
```
-> Code: super.dispose();

```
L034 |   }
```
-> Code: }

```
L035 |
```
-> Blank line

```
L036 |   @override
```
-> Annotation/Decorator: @override

```
L037 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L038 |     final currentUid = FirebaseAuth.instance.currentUser!.uid;
```
-> Variable declaration: final currentUid = FirebaseAuth.instance.currentUser!.uid;

```
L039 |     final appwriteStorage = context.read<AppwriteStorageRepo>();
```
-> Variable declaration: final appwriteStorage = context.read<AppwriteStorageRepo>();

```
L040 |
```
-> Blank line

```
L041 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L042 |       appBar: AppBar(title: const Text("Create Group")),
```
-> Flutter UI widget usage: appBar: AppBar(title: const Text("Create Group")),

```
L043 |       body: Padding(
```
-> Code: body: Padding(

```
L044 |         padding: const EdgeInsets.all(16),
```
-> Code: padding: const EdgeInsets.all(16),

```
L045 |         child: Column(
```
-> Code: child: Column(

```
L046 |           children: [
```
-> Code: children: [

```
L047 |             GestureDetector(
```
-> Code: GestureDetector(

```
L048 |               onTap: pickImage,
```
-> Code: onTap: pickImage,

```
L049 |               child: CircleAvatar(
```
-> Code: child: CircleAvatar(

```
L050 |                 radius: 50,
```
-> Code: radius: 50,

```
L051 |                 backgroundImage: groupImage != null
```
-> Code: backgroundImage: groupImage != null

```
L052 |                     ? FileImage(groupImage!)
```
-> Code: ? FileImage(groupImage!)

```
L053 |                     : null,
```
-> Code: : null,

```
L054 |                 child: groupImage == null
```
-> Code: child: groupImage == null

```
L055 |                     ? const Icon(Icons.camera_alt, size: 32)
```
-> Code: ? const Icon(Icons.camera_alt, size: 32)

```
L056 |                     : null,
```
-> Code: : null,

```
L057 |               ),
```
-> Code:),

```
L058 |             ),
```
-> Code:),

```
L059 |             const SizedBox(height: 12),
```
-> Variable declaration: const SizedBox(height: 12),

```
L060 |             TextField(
```
-> Code: TextField(

```
L061 |               controller: nameController,
```
-> Code: controller: nameController,

```
L062 |               decoration: const InputDecoration(
```
-> Code: decoration: const InputDecoration(

```
L063 |                 labelText: "Group Name",
```
-> Code: labelText: "Group Name",

```
L064 |                 border: OutlineInputBorder(),
```
-> Code: border: OutlineInputBorder(),

```
L065 |               ),
```
-> Code:),

```
L066 |             ),
```
-> Code:),

```
L067 |             const SizedBox(height: 16),
```
-> Variable declaration: const SizedBox(height: 16),

```
L068 |             // const Align(
```
-> Comment: const Align(

```
L069 |             //   alignment: Alignment.centerLeft,
```
-> Comment: alignment: Alignment.centerLeft,

```
L070 |             //   child: Text(
```
-> Comment: child: Text(

```
L071 |              //     "Select Members",
  -> Comment:     "Select Members",
L072 |              //     style: TextStyle(fontWeight: FontWeight.bold),
  -> Comment:     style: TextStyle(fontWeight: FontWeight.bold),
L073 |              //   ),
  -> Comment:    ),
L074 |              // ),
  -> Comment:  ),
L075 |              // const SizedBox(height: 8),
  -> Comment:  const SizedBox(height: 8),
L076 |              // Expanded(
  -> Comment:  Expanded(
L077 |              //   child: StreamBuilder<QuerySnapshot>(
  -> Comment:    child: StreamBuilder<QuerySnapshot>(
L078 |              //     stream: FirebaseFirestore.instance
  -> Comment:     stream: FirebaseFirestore.instance
L079 |              //         .collection('users')
  -> Comment:       .collection('users')
L080 |              //         .snapshots(),
  -> Comment:       .snapshots(),
L081 |              //     builder: (context, snapshot) {
  -> Comment:     builder: (context, snapshot) {
L082 |              //       if (!snapshot.hasData) {
  -> Comment:      if (!snapshot.hasData) {
L083 |              //         return const Center(child: CircularProgressIndicator());
  -> Comment:        return const Center(child: CircularProgressIndicator());
L084 |              //       }
  -> Comment:      }
L085 |
  -> Blank line
L086 |              //       final users = snapshot.data!.docs
  -> Comment:      final users = snapshot.data!.docs
L087 |              //           .where((u) => u['uid'] != currentUid)
  -> Comment:        .where((u) => u['uid'] != currentUid)
L088 |              //           .toList();
  -> Comment:        .toList();
L089 |
  -> Blank line
L090 |              //       return ListView.builder(
  -> Comment:      return ListView.builder(
L091 |              //         itemCount: users.length,
  -> Comment:        itemCount: users.length,
L092 |              //         itemBuilder: (context, i) {
  -> Comment:        itemBuilder: (context, i) {
L093 |              //           final user = users[i];
  -> Comment:          final user = users[i];
L094 |              //           final uid = user['uid'];
  -> Comment:          final uid = user['uid'];
L095 |              //           final name = user['name'] ?? 'User';
  -> Comment:          final name = user['name'] ?? 'User';
L096 |              //           final photoUrl =
  -> Comment:          final photoUrl =
L097 |              //               user.data().toString().contains('photoUrl')
  -> Comment:            user.data().toString().contains('photoUrl')
L098 |              //               ? user['photoUrl']
  -> Comment:            ? user['photoUrl']
L099 |              //               : null;
  -> Comment:            : null;
L100 |
  -> Blank line
L101 |              //           return ListTile(
  -> Comment:          return ListTile(
L102 |              //             leading: CircleAvatar(
  -> Comment:           leading: CircleAvatar(
L103 |              //               backgroundImage: photoUrl != null
  -> Comment:            backgroundImage: photoUrl != null
L104 |              //                   ? NetworkImage(photoUrl)
  -> Comment:              ? NetworkImage(photoUrl)
L105 |              //                   : null,
  -> Comment:              : null,
L106 |              //               child: photoUrl == null
  -> Comment:            child: photoUrl == null
```

```
L107 |              //                    ? const Icon(Icons.person)
  -> Comment:              ? const Icon(Icons.person)
L108 |              //                    : null,
  -> Comment:              : null,
L109 |              //                ),
  -> Comment:            ),
L110 |              //                title: Text(name),
  -> Comment:            title: Text(name),
L111 |              //                trailing: Checkbox(
  -> Comment:            trailing: Checkbox(
L112 |              //                  value: selectedUsers.contains(uid),
  -> Comment:            value: selectedUsers.contains(uid),
L113 |              //                  onChanged: (v) {
  -> Comment:            onChanged: (v) {
L114 |              //                    setState(() {
  -> Comment:              setState(() {
L115 |              //                      if (v == true) {
  -> Comment:              if (v == true) {
L116 |              //                        selectedUsers.add(uid);
  -> Comment:                selectedUsers.add(uid);
L117 |              //                      } else {
  -> Comment:              } else {
L118 |              //                        selectedUsers.remove(uid);
  -> Comment:                selectedUsers.remove(uid);
L119 |              //                      }
  -> Comment:              }
L120 |              //                    });
  -> Comment:              });
L121 |              //                  },
  -> Comment:            },
L122 |              //                ),
  -> Comment:            ),
L123 |              //              );
  -> Comment:          );
L124 |              //            },
  -> Comment:        },
L125 |              //          );
  -> Comment:      );
L126 |              //      },
  -> Comment:    },
L127 |              //    ),
  -> Comment:    ),
L128 |              // ),
  -> Comment:  ),
L129 |              const SizedBox(height: 12),
  -> Variable declaration: const SizedBox(height: 12),
L130 |              _isLoading
  -> Code: _isLoading
L131 |                  ? const CircularProgressIndicator()
  -> Code: ? const CircularProgressIndicator()
L132 |                  : ElevatedButton.icon(
  -> Code: : ElevatedButton.icon(
L133 |                      icon: const Icon(Icons.group_add),
  -> Code: icon: const Icon(Icons.group_add),
L134 |                      label: const Text("Create Group"),
  -> Code: label: const Text("Create Group"),
L135 |                      onPressed: () async {
  -> Code: onPressed: () async {
L136 |                        final name = nameController.text.trim();
  -> Variable declaration: final name = nameController.text.trim();
L137 |                        if (name.isEmpty) {
  -> Control flow statement: if (name.isEmpty) {
L138 |                          ScaffoldMessenger.of(context).showSnackBar(
  -> Code: ScaffoldMessenger.of(context).showSnackBar(
L139 |                            const SnackBar(content: Text("Enter group name")),
  -> Variable declaration: const SnackBar(content: Text("Enter group name")),
L140 |                          );
  -> Code: );
L141 |                          return;
  -> Code: return;
L142 |                        }
  -> Code: }
```

```
L143 |
```
-> Blank line
```
L144 |                         // if (selectedUsers.isEmpty) {
```
-> Comment: if (selectedUsers.isEmpty) {
```
L145 |                         //   ScaffoldMessenger.of(context).showSnackBar(
```
-> Comment: ScaffoldMessenger.of(context).showSnackBar(
```
L146 |                         //     const SnackBar(
```
-> Comment: const SnackBar(
```
L147 |                         //       content: Text("Select at least one member"),
```
-> Comment: content: Text("Select at least one member"),
```
L148 |                         //     ),
```
-> Comment:),
```
L149 |                         //   );
```
-> Comment:);
```
L150 |                         //   return;
```
-> Comment: return;
```
L151 |                         // }
```
-> Comment: }
```
L152 |
```
-> Blank line
```
L153 |                         setState(() => _isLoading = true);
```
-> Short arrow function/expression: setState(() => _isLoading = true);
```
L154 |
```
-> Blank line
```
L155 |
```
-> Blank line
```
L156 |                         String? uploadedUrl;
```
-> Code: String? uploadedUrl;
```
L157 |                         if (groupImage != null) {
```
-> Control flow statement: if (groupImage != null) {
```
L158 |                           uploadedUrl = await appwriteStorage
```
-> Code: uploadedUrl = await appwriteStorage
```
L159 |                               .uploadProfileImageMobile(
```
-> Code: .uploadProfileImageMobile(
```
L160 |                                 groupImage!.path,
```
-> Code: groupImage!.path,
```
L161 |                                 currentUid,
```
-> Code: currentUid,
```
L162 |                               );
```
-> Code:);
```
L163 |                         }
```
-> Code: }
```
L164 |
```
-> Blank line
```
L165 |
```
-> Blank line
```
L166 |                         final imageUrl = uploadedUrl ?? '';
```
-> Variable declaration: final imageUrl = uploadedUrl ?? '';
```
L167 |
```
-> Blank line
```
L168 |                         final memberUids = [...selectedUsers, currentUid];
```
-> Variable declaration: final memberUids = [...selectedUsers, currentUid];
```
L169 |
```
-> Blank line
```
L170 |                         await context.read<GroupCubit>().createGroup(
```
-> Code: await context.read<GroupCubit>().createGroup(
```
L171 |                           name,
```
-> Code: name,
```
L172 |                           memberUids,
```
-> Code: memberUids,
```
L173 |                           imageUrl,
```
-> Code: imageUrl,
```
L174 |                         );
```
-> Code:);
```
L175 |
```
-> Blank line
```
L176 |                         if (context.mounted) {
```
-> Control flow statement: if (context.mounted) {
```
L177 |                           await context.read<GroupCubit>().refreshGroups();
```
-> Code: await context.read<GroupCubit>().refreshGroups();
```
L178 |                           Navigator.pop(context);
```
-> Code: Navigator.pop(context);

```
L179 |                         }
```
-> Code: }

```
L180 |
```
-> Blank line

```
L181 |                         setState(() => _isLoading = false);
```
-> Short arrow function/expression: setState(() => _isLoading = false);

```
L182 |                       },
```
-> Code: },

```
L183 |                     ),
```
-> Code:),

```
L184 |           ],
```
-> Code:],

```
L185 |         ),
```
-> Code:),

```
L186 |       ),
```
-> Code:),

```
L187 |     );
```
-> Code:);

```
L188 |   }
```
-> Code: }

```
L189 | }
```
-> Code: }

lib/features/chatgroup/pages/group_chat_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';

```
L004 | import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/cubit/chat_cubit.dart';

```
L005 | import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/data/fire_chat_repo.dart';

```
L006 | import 'package:instproject/features/chatgroup/pages/chat_page.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/pages/chat_page.dart';

```
L007 | import '../widgets/group_tile.dart';
```
-> Imports module or package: import '../widgets/group_tile.dart';

```
L008 | import 'create_group_page.dart';
```
-> Imports module or package: import 'create_group_page.dart';

```
L009 |
```
-> Blank line

```
L010 | class GroupsPage extends StatefulWidget {
```
-> Class declaration: class GroupsPage extends StatefulWidget {

```
L011 |   const GroupsPage({super.key});
```
-> Variable declaration: const GroupsPage({super.key});

```
L012 |
```
-> Blank line

```
L013 |   @override
```
-> Annotation/Decorator: @override

```
L014 |   State<GroupsPage> createState() => _GroupsPageState();
```
-> Short arrow function/expression: State<GroupsPage> createState() => _GroupsPageState();

```
L015 | }
```
-> Code: }

```
L016 |
```
-> Blank line

```
L017 | class _GroupsPageState extends State<GroupsPage> {
```
-> Class declaration: class _GroupsPageState extends State<GroupsPage> {

```
L018 |   final TextEditingController _searchController = TextEditingController();
```
-> Variable declaration: final TextEditingController _searchController = TextEditingController();

```
L019 |
```
-> Blank line

```
L020 |   @override
```
-> Annotation/Decorator: @override

```
L021 |   void dispose() {
```
-> Function/method declaration or async return type: void dispose() {

```
L022 |     _searchController.dispose();
```
-> Code: _searchController.dispose();

```
L023 |     super.dispose();
```
-> Code: super.dispose();

```
L024 |   }
```
-> Code: }

```
L025 |
```
-> Blank line

```
L026 |   @override
```
-> Annotation/Decorator: @override

```
L027 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L028 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L029 |       appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L030 |         title: const Text("Groups"),
```
-> Code: title: const Text("Groups"),

```
L031 |         actions: [
```
-> Code: actions: [

```
L032 |           IconButton(
```
-> Code: IconButton(

```
L033 |             icon: const Icon(Icons.refresh),
```
-> Code: icon: const Icon(Icons.refresh),

```
L034 |             onPressed: () => context.read<GroupCubit>().refreshGroups(),
```
-> Code: onPressed: () => context.read<GroupCubit>().refreshGroups(),

```
L035 |           ),
```
-> Code:),

```
L036 |         ],
```
-> Code:],

```
L037 |       ),
```
-> Code:),

```
L038 |
```
-> Blank line

```
L039 |       floatingActionButton: Padding(
```
-> Code: floatingActionButton: Padding(

```
L040 |         padding: const EdgeInsets.only(
```
-> Code: padding: const EdgeInsets.only(

```
L041 |           bottom: 70.0,
```
-> Code: bottom: 70.0,

```
L042 |           right: 8.0,
```
-> Code: right: 8.0,

```
L043 |         ),
```
-> Code:),

```
L044 |         child: FloatingActionButton(
```
-> Code: child: FloatingActionButton(

```
L045 |           backgroundColor: Theme.of(context).colorScheme.primary,
```
-> Code: backgroundColor: Theme.of(context).colorScheme.primary,

```
L046 |           onPressed: () {
```
-> Code: onPressed: () {

```
L047 |             Navigator.push(
```
-> Code: Navigator.push(

```
L048 |               context,
```
-> Code: context,

```
L049 |               MaterialPageRoute(builder: (_) => const CreateGroupPage()),
```
-> Code: MaterialPageRoute(builder: (_) => const CreateGroupPage()),

```
L050 |             );
```
-> Code:);

```
L051 |           },
```
-> Code: },

```
L052 |           child: const Icon(Icons.add, color: Colors.white),
```
-> Code: child: const Icon(Icons.add, color: Colors.white),

```
L053 |         ),
```
-> Code:),

```
L054 |       ),
```
-> Code:),

```
L055 |
```
-> Blank line

```
L056 |       floatingActionButtonLocation: FloatingActionButtonLocation.endFloat,
```
-> Code: floatingActionButtonLocation: FloatingActionButtonLocation.endFloat,

```
L057 |
```
-> Blank line

```
L058 |       body: Column(
```
-> Code: body: Column(

```
L059 |         children: [
```
-> Code: children: [

```
L060 |
```
-> Blank line

```
L061 |           Padding(
```
-> Code: Padding(

```
L062 |             padding: const EdgeInsets.all(12.0),
```
-> Code: padding: const EdgeInsets.all(12.0),

```
L063 |             child: TextField(
```
-> Code: child: TextField(

```
L064 |               controller: _searchController,
```
-> Code: controller: _searchController,

```
L065 |               onChanged: (query) {
```
-> Code: onChanged: (query) {

```
L066 |                 context.read<GroupCubit>().searchGroups(query);
```
-> Code: context.read<GroupCubit>().searchGroups(query);

```
L067 |               },
```
-> Code: },

```
L068 |               decoration: InputDecoration(
```
-> Code: decoration: InputDecoration(

```
L069 |                 hintText: 'Search groups...',
```
-> Code: hintText: 'Search groups...',

```
L070 |                 prefixIcon: const Icon(Icons.search),
```
-> Code: prefixIcon: const Icon(Icons.search),

```
L071 |                 filled: true,
  -> Code: filled: true,
L072 |                 fillColor: Theme.of(
  -> Code: fillColor: Theme.of(
L073 |                   context,
  -> Code: context,
L074 |                 ).colorScheme.surface.withOpacity(0.1),
  -> Code: ).colorScheme.surface.withOpacity(0.1),
L075 |                 border: OutlineInputBorder(
  -> Code: border: OutlineInputBorder(
L076 |                   borderRadius: BorderRadius.circular(12),
  -> Code: borderRadius: BorderRadius.circular(12),
L077 |                   borderSide: BorderSide.none,
  -> Code: borderSide: BorderSide.none,
L078 |                 ),
  -> Code: ),
L079 |               ),
  -> Code: ),
L080 |             ),
  -> Code: ),
L081 |           ),
  -> Code: ),
L082 |
  -> Blank line
L083 |
  -> Blank line
L084 |           Expanded(
  -> Code: Expanded(
L085 |             child: BlocBuilder<GroupCubit, GroupState>(
  -> Code: child: BlocBuilder<GroupCubit, GroupState>(
L086 |               builder: (context, state) {
  -> Code: builder: (context, state) {
L087 |                 if (state is GroupLoading) {
  -> Control flow statement: if (state is GroupLoading) {
L088 |                   return const Center(child: CircularProgressIndicator());
  -> Return statement: return const Center(child: CircularProgressIndicator());
L089 |                 }
  -> Code: }
L090 |
  -> Blank line
L091 |                 if (state is GroupError) {
  -> Control flow statement: if (state is GroupError) {
L092 |                   return Center(child: Text(state.message));
  -> Return statement: return Center(child: Text(state.message));
L093 |                 }
  -> Code: }
L094 |
  -> Blank line
L095 |                 if (state is GroupLoaded) {
  -> Control flow statement: if (state is GroupLoaded) {
L096 |                   final groups = state.groups;
  -> Variable declaration: final groups = state.groups;
L097 |
  -> Blank line
L098 |                   if (groups.isEmpty) {
  -> Control flow statement: if (groups.isEmpty) {
L099 |                     return const Center(
  -> Return statement: return const Center(
L100 |                       child: Text(
  -> Code: child: Text(
L101 |                         'No groups found',
  -> Code: 'No groups found',
L102 |                         style: TextStyle(fontSize: 16),
  -> Code: style: TextStyle(fontSize: 16),
L103 |                       ),
  -> Code: ),
L104 |                     );
  -> Code: );
L105 |                 }
  -> Code: }
L106 |
  -> Blank line
```

```
L107 |                     return ListView.builder(
  -> Return statement: return ListView.builder(
L108 |                       itemCount: groups.length,
  -> Code: itemCount: groups.length,
L109 |                       itemBuilder: (context, i) {
  -> Code: itemBuilder: (context, i) {
L110 |                         final group = groups[i];
  -> Variable declaration: final group = groups[i];
L111 |                         return GroupTile(
  -> Return statement: return GroupTile(
L112 |                           group: group,
  -> Code: group: group,
L113 |                           onTap: () {
  -> Code: onTap: () {
L114 |                             Navigator.push(
  -> Code: Navigator.push(
L115 |                               context,
  -> Code: context,
L116 |                               MaterialPageRoute(
  -> Code: MaterialPageRoute(
L117 |                                 builder: (_) => BlocProvider(
  -> Code: builder: (_) => BlocProvider(
L118 |                                   create: (_) => ChatCubit(
  -> Code: create: (_) => ChatCubit(
L119 |                                     repo: context.read<FireChatRepo>(),
  -> Code: repo: context.read<FireChatRepo>(),
L120 |                                     groupId: group.id,
  -> Code: groupId: group.id,
L121 |                                   ),
  -> Code: ),
L122 |                                   child: ChatPage(group: group),
  -> Code: child: ChatPage(group: group),
L123 |                                 ),
  -> Code: ),
L124 |                               ),
  -> Code: ),
L125 |                             );
  -> Code: );
L126 |                           },
  -> Code: },
L127 |                         );
  -> Code: );
L128 |                       },
  -> Code: },
L129 |                     );
  -> Code: );
L130 |                   }
  -> Code: }
L131 |
  -> Blank line
L132 |                   return const SizedBox();
  -> Return statement: return const SizedBox();
L133 |                 },
  -> Code: },
L134 |               ),
  -> Code: ),
L135 |             ),
  -> Code: ),
L136 |           ],
  -> Code: ],
L137 |         ),
  -> Code: ),
L138 |       );
  -> Code: );
L139 |     }
  -> Code: }
L140 | }
  -> Code: }
```

lib/features/chatgroup/widgets/group_tile.dart

```
L001 | import 'package:firebase_auth/firebase_auth.dart';
  -> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';
L002 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L004 | import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';
  -> Imports module or package: import 'package:instproject/features/chatgroup/cubit/group_cubit.dart';
L005 | import 'package:instproject/features/chatgroup/models/group_model.dart';
  -> Imports module or package: import 'package:instproject/features/chatgroup/models/group_model.dart';
L006 |
  -> Blank line
L007 | class GroupTile extends StatelessWidget {
  -> Class declaration: class GroupTile extends StatelessWidget {
L008 |   final GroupModel group;
  -> Variable declaration: final GroupModel group;
L009 |   final VoidCallback onTap;
  -> Variable declaration: final VoidCallback onTap;
L010 |
  -> Blank line
L011 |   const GroupTile({super.key, required this.group, required this.onTap});
  -> Variable declaration: const GroupTile({super.key, required this.group, required this.onTap});
L012 |
  -> Blank line
L013 |   @override
  -> Annotation/Decorator: @override
L014 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L015 |     final currentUserId = FirebaseAuth.instance.currentUser?.uid;
  -> Variable declaration: final currentUserId = FirebaseAuth.instance.currentUser?.uid;
L016 |
  -> Blank line
L017 |     return ListTile(
  -> Return statement: return ListTile(
L018 |       onTap: onTap,
  -> Code: onTap: onTap,
L019 |       leading: CircleAvatar(
  -> Code: leading: CircleAvatar(
L020 |         radius: 26,
  -> Code: radius: 26,
L021 |         backgroundImage: group.imageUrl.isNotEmpty
  -> Code: backgroundImage: group.imageUrl.isNotEmpty
L022 |             ? NetworkImage(group.imageUrl)
  -> Code: ? NetworkImage(group.imageUrl)
L023 |             : const AssetImage('assets/default_group.png') as ImageProvider,
  -> Code: : const AssetImage('assets/default_group.png') as ImageProvider,
L024 |         child: group.imageUrl.isEmpty
  -> Code: child: group.imageUrl.isEmpty
L025 |             ? const Icon(Icons.group, color: Colors.white)
  -> Code: ? const Icon(Icons.group, color: Colors.white)
L026 |             : null,
  -> Code: : null,
L027 |       ),
  -> Code: ),
L028 |       title: Text(
  -> Code: title: Text(
L029 |         group.name,
  -> Code: group.name,
L030 |         style: const TextStyle(fontWeight: FontWeight.w600),
  -> Code: style: const TextStyle(fontWeight: FontWeight.w600),
L031 |       ),
  -> Code: ),
L032 |       // subtitle: Text(
  -> Comment:  subtitle: Text(
L033 |       //   group.description?.isNotEmpty == true
  -> Comment:   group.description?.isNotEmpty == true
L034 |       //       ? group.description!
  -> Comment:      ? group.description!
```

```
L035 |       //       : (group.lastMessage?.isNotEmpty == true
  -> Comment:      : (group.lastMessage?.isNotEmpty == true
L036 |       //             ? group.lastMessage!
  -> Comment:          ? group.lastMessage!
L037 |       //             : 'No messages yet'),
  -> Comment:          : 'No messages yet'),
L038 |       //   maxLines: 1,
  -> Comment:    maxLines: 1,
L039 |       //   overflow: TextOverflow.ellipsis,
  -> Comment:    overflow: TextOverflow.ellipsis,
L040 |       // ),
  -> Comment:  ),
L041 |       // trailing: SizedBox(
  -> Comment:  trailing: SizedBox(
L042 |       //   width: 100,
  -> Comment:    width: 100,
L043 |       //   child: ElevatedButton(
  -> Comment:    child: ElevatedButton(
L044 |       //     style: ElevatedButton.styleFrom(
  -> Comment:      style: ElevatedButton.styleFrom(
L045 |       //       padding: const EdgeInsets.symmetric(horizontal: 12, vertical: 6),
  -> Comment:      padding: const EdgeInsets.symmetric(horizontal: 12, vertical: 6),
L046 |       //       textStyle: const TextStyle(fontSize: 13),
  -> Comment:      textStyle: const TextStyle(fontSize: 13),
L047 |       //     ),
  -> Comment:      ),
L048 |       //     onPressed: currentUserId == null
  -> Comment:      onPressed: currentUserId == null
L049 |       //         ? null
  -> Comment:          ? null
L050 |       //         : () {
  -> Comment:          : () {
L051 |       //             context.read<GroupCubit>().joinGroup(group.id, currentUserId);
  -> Comment:          context.read<GroupCubit>().joinGroup(group.id, currentUserId);
L052 |       //           },
  -> Comment:        },
L053 |       //     child: const Text('Join'),
  -> Comment:      child: const Text('Join'),
L054 |       //   ),
  -> Comment:    ),
L055 |       // ),
  -> Comment:  ),
L056 |     );
  -> Code: );
L057 |   }
  -> Code: }
L058 | }
  -> Code: }
```

lib/features/chatgroup/widgets/message_bubble.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:instproject/features/chatgroup/models/message_model.dart';
```
-> Imports module or package: import 'package:instproject/features/chatgroup/models/message_model.dart';

```
L003 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L004 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L005 |
```
-> Blank line

```
L006 | class MessageBubble extends StatelessWidget {
```
-> Class declaration: class MessageBubble extends StatelessWidget {

```
L007 |   final MessageModel msg;
```
-> Variable declaration: final MessageModel msg;

```
L008 |   const MessageBubble({super.key, required this.msg});
```
-> Variable declaration: const MessageBubble({super.key, required this.msg});

```
L009 |
```
-> Blank line

```
L010 |   Future<Map<String, dynamic>?> getUserData(String uid) async {
```
-> Function/method declaration or async return type: Future<Map<String, dynamic>?> getUserData(String uid) async {

```
L011 |     try {
```
-> Code: try {

```
L012 |       final doc = await FirebaseFirestore.instance
```
-> Variable declaration: final doc = await FirebaseFirestore.instance

```
L013 |           .collection('users')
```
-> Code: .collection('users')

```
L014 |           .doc(uid)
```
-> Code: .doc(uid)

```
L015 |           .get();
```
-> Code: .get();

```
L016 |       return doc.data();
```
-> Return statement: return doc.data();

```
L017 |     } catch (e) {
```
-> Code: } catch (e) {

```
L018 |       return null;
```
-> Return statement: return null;

```
L019 |     }
```
-> Code: }

```
L020 |   }
```
-> Code: }

```
L021 |
```
-> Blank line

```
L022 |   @override
```
-> Annotation/Decorator: @override

```
L023 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L024 |     final isMe = msg.senderId == FirebaseAuth.instance.currentUser?.uid;
```
-> Variable declaration: final isMe = msg.senderId == FirebaseAuth.instance.currentUser?.uid;

```
L025 |
```
-> Blank line

```
L026 |     return FutureBuilder<Map<String, dynamic>?>(
```
-> Return statement: return FutureBuilder<Map<String, dynamic>?>(

```
L027 |       future: getUserData(msg.senderId),
```
-> Code: future: getUserData(msg.senderId),

```
L028 |       builder: (context, snapshot) {
```
-> Code: builder: (context, snapshot) {

```
L029 |         final userData = snapshot.data;
```
-> Variable declaration: final userData = snapshot.data;

```
L030 |         final userName = userData?['name'] ?? 'User';
```
-> Variable declaration: final userName = userData?['name'] ?? 'User';

```
L031 |         final userImage = userData?['photoUrl'];
```
-> Variable declaration: final userImage = userData?['photoUrl'];

```
L032 |
```
-> Blank line

```
L033 |         return Align(
```
-> Return statement: return Align(

```
L034 |           alignment: isMe ? Alignment.centerRight : Alignment.centerLeft,
```
-> Code: alignment: isMe ? Alignment.centerRight : Alignment.centerLeft,

```
L035 |           child: Container(
  -> Code: child: Container(
L036 |             margin: const EdgeInsets.symmetric(horizontal: 8, vertical: 4),
  -> Code: margin: const EdgeInsets.symmetric(horizontal: 8, vertical: 4),
L037 |             child: Column(
  -> Code: child: Column(
L038 |               crossAxisAlignment: isMe
  -> Code: crossAxisAlignment: isMe
L039 |                   ? CrossAxisAlignment.end
  -> Code: ? CrossAxisAlignment.end
L040 |                   : CrossAxisAlignment.start,
  -> Code: : CrossAxisAlignment.start,
L041 |               children: [
  -> Code: children: [
L042 |                 if (!isMe)
  -> Control flow statement: if (!isMe)
L043 |                   Row(
  -> Code: Row(
L044 |                     crossAxisAlignment: CrossAxisAlignment.center,
  -> Code: crossAxisAlignment: CrossAxisAlignment.center,
L045 |                     children: [
  -> Code: children: [
L046 |                       CircleAvatar(
  -> Code: CircleAvatar(
L047 |                         radius: 14,
  -> Code: radius: 14,
L048 |                         backgroundImage: userImage != null
  -> Code: backgroundImage: userImage != null
L049 |                             ? NetworkImage(userImage)
  -> Code: ? NetworkImage(userImage)
L050 |                             : null,
  -> Code: : null,
L051 |                         child: userImage == null
  -> Code: child: userImage == null
L052 |                             ? const Icon(Icons.person, size: 16)
  -> Code: ? const Icon(Icons.person, size: 16)
L053 |                             : null,
  -> Code: : null,
L054 |                       ),
  -> Code: ),
L055 |                       const SizedBox(width: 6),
  -> Variable declaration: const SizedBox(width: 6),
L056 |                       Text(
  -> Code: Text(
L057 |                         userName,
  -> Code: userName,
L058 |                         style: const TextStyle(
  -> Code: style: const TextStyle(
L059 |                           fontSize: 13,
  -> Code: fontSize: 13,
L060 |                           fontWeight: FontWeight.w600,
  -> Code: fontWeight: FontWeight.w600,
L061 |                         ),
  -> Code: ),
L062 |                       ),
  -> Code: ),
L063 |                     ],
  -> Code: ],
L064 |                   ),
  -> Code: ),
L065 |                 const SizedBox(height: 4),
  -> Variable declaration: const SizedBox(height: 4),
L066 |                 Container(
  -> Code: Container(
L067 |                   padding: const EdgeInsets.symmetric(
  -> Code: padding: const EdgeInsets.symmetric(
L068 |                     vertical: 8,
  -> Code: vertical: 8,
L069 |                     horizontal: 12,
  -> Code: horizontal: 12,
L070 |                   ),
  -> Code: ),
```

```
L071 |                     decoration: BoxDecoration(
```
-> Code: decoration: BoxDecoration(

```
L072 |                       color: isMe ? Colors.brown : Colors.blueAccent,
```
-> Code: color: isMe ? Colors.brown : Colors.blueAccent,

```
L073 |                       borderRadius: BorderRadius.circular(12),
```
-> Code: borderRadius: BorderRadius.circular(12),

```
L074 |                     ),
```
-> Code:),

```
L075 |                     child: msg.imageUrl != null && msg.imageUrl!.isNotEmpty
```
-> Code: child: msg.imageUrl != null && msg.imageUrl!.isNotEmpty

```
L076 |                         ? Image.network(msg.imageUrl!, width: 180)
```
-> Code: ? Image.network(msg.imageUrl!, width: 180)

```
L077 |                         : Text(msg.text, style: const TextStyle(fontSize: 15, color: Colors.black)),
```
-> Code: : Text(msg.text, style: const TextStyle(fontSize: 15, color: Colors.black)),

```
L078 |                   ),
```
-> Code:),

```
L079 |                ],
```
-> Code:],

```
L080 |              ),
```
-> Code:),

```
L081 |            ),
```
-> Code:),

```
L082 |          );
```
-> Code:);

```
L083 |       },
```
-> Code: },

```
L084 |     );
```
-> Code:);

```
L085 |   }
```
-> Code: }

```
L086 | }
```
-> Code: }

lib/features/chatgroup/widgets/story_item.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class StoryItem extends StatelessWidget {
  -> Class declaration: class StoryItem extends StatelessWidget {
L004 |   final String? img;
  -> Variable declaration: final String? img;
L005 |   final VoidCallback onTap;
  -> Variable declaration: final VoidCallback onTap;
L006 |   final String title;
  -> Variable declaration: final String title;
L007 |   const StoryItem({
  -> Variable declaration: const StoryItem({
L008 |     super.key,
  -> Code: super.key,
L009 |     required this.img,
  -> Code: required this.img,
L010 |     required this.onTap,
  -> Code: required this.onTap,
L011 |     required this.title,
  -> Code: required this.title,
L012 |   });
  -> Code: });
L013 |   @override
  -> Annotation/Decorator: @override
L014 |   Widget build(BuildContext context) => GestureDetector(
  -> Flutter widget/typed UI code: Widget build(BuildContext context) => GestureDetector(
L015 |     onTap: onTap,
  -> Code: onTap: onTap,
L016 |     child: Column(
  -> Code: child: Column(
L017 |       children: [
  -> Code: children: [
L018 |         CircleAvatar(
  -> Code: CircleAvatar(
L019 |           radius: 30,
  -> Code: radius: 30,
L020 |           backgroundImage: img != null ? NetworkImage(img!) : null,
  -> Code: backgroundImage: img != null ? NetworkImage(img!) : null,
L021 |           child: img == null ? const Icon(Icons.person) : null,
  -> Code: child: img == null ? const Icon(Icons.person) : null,
L022 |         ),
  -> Code: ),
L023 |         const SizedBox(height: 4),
  -> Variable declaration: const SizedBox(height: 4),
L024 |         Text(title, style: const TextStyle(fontSize: 12)),
  -> Code: Text(title, style: const TextStyle(fontSize: 12)),
L025 |       ],
  -> Code: ],
L026 |     ),
  -> Code: ),
L027 |   );
  -> Code: );
L028 | }
  -> Code: }
```

lib/features/chatgroup/widgets/story_rowshow.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 |
  -> Blank line
L003 | class StoryItemShow extends StatelessWidget {
  -> Class declaration: class StoryItemShow extends StatelessWidget {
L004 |   final String? imageUrl;
  -> Variable declaration: final String? imageUrl;
L005 |   final String? quote;
  -> Variable declaration: final String? quote;
L006 |   const StoryItemShow({super.key, this.imageUrl, this.quote});
  -> Variable declaration: const StoryItemShow({super.key, this.imageUrl, this.quote});
L007 |
  -> Blank line
L008 |   @override
  -> Annotation/Decorator: @override
L009 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L010 |     return Container(
  -> Return statement: return Container(
L011 |       width: 110,
  -> Code: width: 110,
L012 |       margin: const EdgeInsets.all(8),
  -> Code: margin: const EdgeInsets.all(8),
L013 |       child: Column(
  -> Code: child: Column(
L014 |         children: [
  -> Code: children: [
L015 |           CircleAvatar(
  -> Code: CircleAvatar(
L016 |             radius: 36,
  -> Code: radius: 36,
L017 |             backgroundImage: imageUrl != null && imageUrl!.isNotEmpty
  -> Code: backgroundImage: imageUrl != null && imageUrl!.isNotEmpty
L018 |                 ? NetworkImage(imageUrl!)
  -> Code: ? NetworkImage(imageUrl!)
L019 |                 : null,
  -> Code: : null,
L020 |             child: imageUrl == null ? const Icon(Icons.format_quote) : null,
  -> Code: child: imageUrl == null ? const Icon(Icons.format_quote) : null,
L021 |           ),
  -> Code: ),
L022 |           const SizedBox(height: 6),
  -> Variable declaration: const SizedBox(height: 6),
L023 |           Expanded(
  -> Code: Expanded(
L024 |             child: Text(
  -> Code: child: Text(
L025 |               quote ?? '',
  -> Code: quote ?? '',
L026 |               maxLines: 2,
  -> Code: maxLines: 2,
L027 |               overflow: TextOverflow.ellipsis,
  -> Code: overflow: TextOverflow.ellipsis,
L028 |             ),
  -> Code: ),
L029 |           ),
  -> Code: ),
L030 |         ],
  -> Code: ],
L031 |       ),
  -> Code: ),
L032 |     );
  -> Code: );
L033 |   }
  -> Code: }
L034 | }
  -> Code: }
```

lib/features/institutes/presentation/pages/institutes_page.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 |
```
-> Blank line

```
L003 | class InstitutesPage extends StatelessWidget {
```
-> Class declaration: class InstitutesPage extends StatelessWidget {

```
L004 |   const InstitutesPage({super.key});
```
-> Variable declaration: const InstitutesPage({super.key});

```
L005 |
```
-> Blank line

```
L006 |   @override
```
-> Annotation/Decorator: @override

```
L007 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L008 |     final institutes = const [
```
-> Variable declaration: final institutes = const [

```
L009 |       'Institute of Technology',
```
-> Code: 'Institute of Technology',

```
L010 |       'National Institute of Arts',
```
-> Code: 'National Institute of Arts',

```
L011 |       'Regional Science Academy',
```
-> Code: 'Regional Science Academy',

```
L012 |       'College of Engineering',
```
-> Code: 'College of Engineering',

```
L013 |       'Business Institute',
```
-> Code: 'Business Institute',

```
L014 |     ];
```
-> Code:];

```
L015 |
```
-> Blank line

```
L016 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L017 |       appBar: AppBar(title: const Text('Institutes')),
```
-> Flutter UI widget usage: appBar: AppBar(title: const Text('Institutes')),

```
L018 |       body: ListView.separated(
```
-> Flutter UI widget usage: body: ListView.separated(

```
L019 |         padding: const EdgeInsets.all(12),
```
-> Code: padding: const EdgeInsets.all(12),

```
L020 |         itemCount: institutes.length,
```
-> Code: itemCount: institutes.length,

```
L021 |         separatorBuilder: (_, __) => const Divider(),
```
-> Code: separatorBuilder: (_, __) => const Divider(),

```
L022 |         itemBuilder: (context, index) {
```
-> Code: itemBuilder: (context, index) {

```
L023 |           final name = institutes[index];
```
-> Variable declaration: final name = institutes[index];

```
L024 |           return ListTile(
```
-> Return statement: return ListTile(

```
L025 |             leading: const Icon(Icons.school_outlined),
```
-> Code: leading: const Icon(Icons.school_outlined),

```
L026 |             title: Text(name),
```
-> Code: title: Text(name),

```
L027 |             subtitle: const Text('Tap to view details'),
```
-> Code: subtitle: const Text('Tap to view details'),

```
L028 |             onTap: () {
```
-> Code: onTap: () {

```
L029 |               // Placeholder for institute details/route
```
-> Comment: Placeholder for institute details/route

```
L030 |               ScaffoldMessenger.of(
```
-> Code: ScaffoldMessenger.of(

```
L031 |                 context,
```
-> Code: context,

```
L032 |               ).showSnackBar(SnackBar(content: Text('Open: $name')));
```
-> Code:).showSnackBar(SnackBar(content: Text('Open: $name')));

```
L033 |             },
```
-> Code: },

```
L034 |           );
```
-> Code:);

```
L035 |         },
```
-> Code: },

```
L036 |       ),
```
-> Code:),

```
L037 |     );
```
-> Code:);

```
L038 |   }
```
-> Code: }

```
L039 | }
```
-> Code: }

lib/features/posts/data/appwrite_storage_post_repo.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:instproject/core/rebos/appwrite_storage_api.dart';
```
-> Imports module or package: import 'package:instproject/core/rebos/appwrite_storage_api.dart';

```
L003 |
```
-> Blank line

```
L004 | class AppwritePostStorageRepo {
```
-> Class declaration: class AppwritePostStorageRepo {

```
L005 |   Future<String?> uploadPostImage(String imagePath, String userId) async {
```
-> Function/method declaration or async return type: Future<String?> uploadPostImage(String imagePath, String userId) async {

```
L006 |     final file = File(imagePath);
```
-> Variable declaration: final file = File(imagePath);

```
L007 |     final fileName = '${userId}_${DateTime.now().millisecondsSinceEpoch}.jpg';
```
-> Variable declaration: final fileName = '${userId}_${DateTime.now().millisecondsSinceEpoch}.jpg';

```
L008 |     return await AppwriteStorageAPI.uploadImage(file, fileName);
```
-> Return statement: return await AppwriteStorageAPI.uploadImage(file, fileName);

```
L009 |   }
```
-> Code: }

```
L010 | }
```
-> Code: }

lib/features/posts/data/fire_post_repo.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L002 | import '../domain/post_repo.dart';
```
-> Imports module or package: import '../domain/post_repo.dart';

```
L003 | import 'post_model.dart';
```
-> Imports module or package: import 'post_model.dart';

```
L004 |
```
-> Blank line

```
L005 | class FirePostRepo implements PostRepo {
```
-> Class declaration: class FirePostRepo implements PostRepo {

```
L006 |   final _firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final _firestore = FirebaseFirestore.instance;

```
L007 |
```
-> Blank line

```
L008 |   @override
```
-> Annotation/Decorator: @override

```
L009 |   Future<void> createPost(Post post) async {
```
-> Function/method declaration or async return type: Future<void> createPost(Post post) async {

```
L010 |     print(' [FirePostRepo] Creating new post for ${post.userName}');
```
-> Code: print(' [FirePostRepo] Creating new post for ${post.userName}');

```
L011 |     await FirebaseFirestore.instance.collection('posts').doc(post.id).set({
```
-> Code: await FirebaseFirestore.instance.collection('posts').doc(post.id).set({

```
L012 |       'id': post.id,
```
-> Code: 'id': post.id,

```
L013 |       'userId': post.userId,
```
-> Code: 'userId': post.userId,

```
L014 |       'userName': post.userName,
```
-> Code: 'userName': post.userName,

```
L015 |       'userProfileImage': post.userProfileImage,
```
-> Code: 'userProfileImage': post.userProfileImage,

```
L016 |       'caption': post.caption,
```
-> Code: 'caption': post.caption,

```
L017 |       'imageUrl': post.imageUrl,
```
-> Code: 'imageUrl': post.imageUrl,

```
L018 |       'likes': post.likes,
```
-> Code: 'likes': post.likes,

```
L019 |       'likeCount': post.likeCount,
```
-> Code: 'likeCount': post.likeCount,

```
L020 |       'isSaved': post.isSaved,
```
-> Code: 'isSaved': post.isSaved,

```
L021 |       'createdAt': post.createdAt,
```
-> Code: 'createdAt': post.createdAt,

```
L022 |     });
```
-> Code: });

```
L023 |
```
-> Blank line

```
L024 |   }
```
-> Code: }

```
L025 |
```
-> Blank line

```
L026 |   @override
```
-> Annotation/Decorator: @override

```
L027 |
```
-> Blank line

```
L028 |
```
-> Blank line

```
L029 |
```
-> Blank line

```
L030 |
```
-> Blank line

```
L031 |
```
-> Blank line

```
L032 |   Future<void> deletePost(String postId) async {
```
-> Function/method declaration or async return type: Future<void> deletePost(String postId) async {

```
L033 |     await _firestore.collection('posts').doc(postId).delete();
```
-> Code: await _firestore.collection('posts').doc(postId).delete();

```
L034 |   }
```
-> Code: }

L035 |
  -> Blank line

L036 |
  -> Blank line

L037 |
  -> Blank line

L038 | @override
  -> Annotation/Decorator: @override

L039 | Future<List<Post>> fetchAllPosts() async {
  -> Function/method declaration or async return type: Future<List<Post>> fetchAllPosts() async {

L040 | print(' [FirePostRepo] Getting all posts from Firestore...');
  -> Code: print(' [FirePostRepo] Getting all posts from Firestore...');

L041 | try {
  -> Code: try {

L042 | final snapshot = await _firestore
  -> Variable declaration: final snapshot = await _firestore

L043 | .collection('posts')
  -> Code: .collection('posts')

L044 | .orderBy('createdAt', descending: true)
  -> Code: .orderBy('createdAt', descending: true)

L045 | .get();
  -> Code: .get();

L046 |
  -> Blank line

L047 | print(' [FirePostRepo] Found ${snapshot.docs.length} docs');
  -> Code: print(' [FirePostRepo] Found ${snapshot.docs.length} docs');

L048 | return snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList();
  -> Return statement: return snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList();

L049 | } catch (e, st) {
  -> Code: } catch (e, st) {

L050 | print(' [FirePostRepo] Error while loading posts: $e');
  -> Code: print(' [FirePostRepo] Error while loading posts: $e');

L051 | print(st);
  -> Code: print(st);

L052 | return [];
  -> Return statement: return [];

L053 | }
  -> Code: }

L054 | }
  -> Code: }

L055 |
  -> Blank line

L056 | @override
  -> Annotation/Decorator: @override

L057 | Future<List<Post>> fetchPostsByUserId(String userId) async {
  -> Function/method declaration or async return type: Future<List<Post>> fetchPostsByUserId(String userId) async {

L058 | final snapshot = await _firestore
  -> Variable declaration: final snapshot = await _firestore

L059 | .collection('posts')
  -> Code: .collection('posts')

L060 | .where('userId', isEqualTo: userId)
  -> Code: .where('userId', isEqualTo: userId)

L061 | .orderBy('createdAt', descending: true)
  -> Code: .orderBy('createdAt', descending: true)

L062 | .get();
  -> Code: .get();

L063 | return snapshot.docs.map((d) => Post.fromMap(d.data())).toList();
  -> Return statement: return snapshot.docs.map((d) => Post.fromMap(d.data())).toList();

L064 | }
  -> Code: }

L065 |
  -> Blank line

L066 |
  -> Blank line

L067 | @override
  -> Annotation/Decorator: @override

L068 | Future<void> toggleLike(String postId, String userId) async {
  -> Function/method declaration or async return type: Future<void> toggleLike(String postId, String userId) async {

L069 | print(' Firestore toggleLike() updating post $postId');
  -> Code: print(' Firestore toggleLike() updating post $postId');

L070 | final likeRef = _firestore
  -> Variable declaration: final likeRef = _firestore

```
L071 |         .collection('posts')
```
-> Code: .collection('posts')

```
L072 |         .doc(postId)
```
-> Code: .doc(postId)

```
L073 |         .collection('likes')
```
-> Code: .collection('likes')

```
L074 |         .doc(userId);
```
-> Code: .doc(userId);

```
L075 |     final doc = await likeRef.get();
```
-> Variable declaration: final doc = await likeRef.get();

```
L076 |
```
-> Blank line

```
L077 |     if (doc.exists) {
```
-> Control flow statement: if (doc.exists) {

```
L078 |       await likeRef.delete();
```
-> Code: await likeRef.delete();

```
L079 |       await _firestore.collection('posts').doc(postId).update({
```
-> Code: await _firestore.collection('posts').doc(postId).update({

```
L080 |         'likeCount': FieldValue.increment(-1),
```
-> Code: 'likeCount': FieldValue.increment(-1),

```
L081 |       });
```
-> Code: });

```
L082 |     } else {
```
-> Code: } else {

```
L083 |       await likeRef.set({
```
-> Code: await likeRef.set({

```
L084 |         'userId': userId,
```
-> Code: 'userId': userId,

```
L085 |         'likedAt': DateTime.now().millisecondsSinceEpoch,
```
-> Code: 'likedAt': DateTime.now().millisecondsSinceEpoch,

```
L086 |       });
```
-> Code: });

```
L087 |       await _firestore.collection('posts').doc(postId).update({
```
-> Code: await _firestore.collection('posts').doc(postId).update({

```
L088 |         'likeCount': FieldValue.increment(1),
```
-> Code: 'likeCount': FieldValue.increment(1),

```
L089 |       });
```
-> Code: });

```
L090 |     }
```
-> Code: }

```
L091 |   }
```
-> Code: }

```
L092 |
```
-> Blank line

```
L093 |   @override
```
-> Annotation/Decorator: @override

```
L094 |   Future<bool> isPostLiked(String postId, String userId) async {
```
-> Function/method declaration or async return type: Future<bool> isPostLiked(String postId, String userId) async {

```
L095 |     final doc = await _firestore
```
-> Variable declaration: final doc = await _firestore

```
L096 |         .collection('posts')
```
-> Code: .collection('posts')

```
L097 |         .doc(postId)
```
-> Code: .doc(postId)

```
L098 |         .collection('likes')
```
-> Code: .collection('likes')

```
L099 |         .doc(userId)
```
-> Code: .doc(userId)

```
L100 |         .get();
```
-> Code: .get();

```
L101 |     return doc.exists;
```
-> Return statement: return doc.exists;

```
L102 |   }
```
-> Code: }

```
L103 |
```
-> Blank line

```
L104 |
```
-> Blank line

```
L105 |   @override
```
-> Annotation/Decorator: @override

```
L106 |   Future<void> addComment(String postId, String userId, String text, ) async {
```
-> Function/method declaration or async return type: Future<void> addComment(String postId, String userId, String text,) async {

```
L107 |     final commentRef = _firestore
  -> Variable declaration: final commentRef = _firestore
L108 |         .collection('posts')
  -> Code: .collection('posts')
L109 |         .doc(postId)
  -> Code: .doc(postId)
L110 |         .collection('comments')
  -> Code: .collection('comments')
L111 |         .doc();
  -> Code: .doc();
L112 |     await commentRef.set({
  -> Code: await commentRef.set({
L113 |       'id': commentRef.id,
  -> Code: 'id': commentRef.id,
L114 |       'userId': userId,
  -> Code: 'userId': userId,
L115 |       'text': text,
  -> Code: 'text': text,
L116 |       'createdAt': DateTime.now().millisecondsSinceEpoch,
  -> Code: 'createdAt': DateTime.now().millisecondsSinceEpoch,
L117 |     });
  -> Code: });
L118 |   }
  -> Code: }
L119 |
  -> Blank line
L120 |   @override
  -> Annotation/Decorator: @override
L121 |   Future<List<Map<String, dynamic>>> getComments(String postId) async {
  -> Function/method declaration or async return type: Future<List<Map<String, dynamic>>> getComments(String postId) async {
L122 |     final snapshot = await _firestore
  -> Variable declaration: final snapshot = await _firestore
L123 |         .collection('posts')
  -> Code: .collection('posts')
L124 |         .doc(postId)
  -> Code: .doc(postId)
L125 |         .collection('comments')
  -> Code: .collection('comments')
L126 |         .orderBy('createdAt', descending: true)
  -> Code: .orderBy('createdAt', descending: true)
L127 |         .get();
  -> Code: .get();
L128 |     return snapshot.docs.map((d) => d.data()).toList();
  -> Return statement: return snapshot.docs.map((d) => d.data()).toList();
L129 |   }
  -> Code: }
L130 |
  -> Blank line
L131 |
  -> Blank line
L132 |   @override
  -> Annotation/Decorator: @override
L133 |   Future<void> toggleSavePost(String postId, String userId) async {
  -> Function/method declaration or async return type: Future<void> toggleSavePost(String postId, String userId) async {
L134 |     final postRef = _firestore.collection('posts').doc(postId);
  -> Variable declaration: final postRef = _firestore.collection('posts').doc(postId);
L135 |     final doc = await postRef.get();
  -> Variable declaration: final doc = await postRef.get();
L136 |     if (!doc.exists) return;
  -> Control flow statement: if (!doc.exists) return;
L137 |
  -> Blank line
L138 |     final data = doc.data()!;
  -> Variable declaration: final data = doc.data()!;
L139 |     final savedBy = List<String>.from(data['savedBy'] ?? []);
  -> Variable declaration: final savedBy = List<String>.from(data['savedBy'] ?? []);
L140 |
  -> Blank line
L141 |     if (savedBy.contains(userId)) {
  -> Control flow statement: if (savedBy.contains(userId)) {
L142 |       savedBy.remove(userId);
  -> Code: savedBy.remove(userId);
```

```
L143 |     } else {
```
-> Code: } else {

```
L144 |       savedBy.add(userId);
```
-> Code: savedBy.add(userId);

```
L145 |     }
```
-> Code: }

```
L146 |
```
-> Blank line

```
L147 |     await postRef.update({'savedBy': savedBy});
```
-> Code: await postRef.update({'savedBy': savedBy});

```
L148 |   }
```
-> Code: }

```
L149 |
```
-> Blank line

```
L150 |
```
-> Blank line

```
L151 |   @override
```
-> Annotation/Decorator: @override

```
L152 |   Future<List<String>> getSavedPostsIds(String userId) async {
```
-> Function/method declaration or async return type: Future<List<String>> getSavedPostsIds(String userId) async {

```
L153 |     final snapshot = await _firestore
```
-> Variable declaration: final snapshot = await _firestore

```
L154 |         .collection('users')
```
-> Code: .collection('users')

```
L155 |         .doc(userId)
```
-> Code: .doc(userId)

```
L156 |         .collection('saved')
```
-> Code: .collection('saved')

```
L157 |         .get();
```
-> Code: .get();

```
L158 |     return snapshot.docs.map((d) => d.id).toList();
```
-> Return statement: return snapshot.docs.map((d) => d.id).toList();

```
L159 |   }
```
-> Code: }

```
L160 |
```
-> Blank line

```
L161 |   @override
```
-> Annotation/Decorator: @override

```
L162 |  Future<List<Post>> getSavedPosts(String userId) async {
```
-> Function/method declaration or async return type: Future<List<Post>> getSavedPosts(String userId) async {

```
L163 |     final snapshot = await _firestore
```
-> Variable declaration: final snapshot = await _firestore

```
L164 |         .collection('posts')
```
-> Code: .collection('posts')

```
L165 |         .where('savedBy', arrayContains: userId)
```
-> Code: .where('savedBy', arrayContains: userId)

```
L166 |         .get();
```
-> Code: .get();

```
L167 |     return snapshot.docs.map((d) => Post.fromMap(d.data())).toList();
```
-> Return statement: return snapshot.docs.map((d) => Post.fromMap(d.data())).toList();

```
L168 |   }
```
-> Code: }

```
L169 |
```
-> Blank line

```
L170 |
```
-> Blank line

```
L171 |   Stream<List<Post>> streamPostsByUserId(String userId) {
```
-> Function/method declaration or async return type: Stream<List<Post>> streamPostsByUserId(String userId) {

```
L172 |     return _firestore
```
-> Return statement: return _firestore

```
L173 |         .collection('posts')
```
-> Code: .collection('posts')

```
L174 |         .where('userId', isEqualTo: userId)
```
-> Code: .where('userId', isEqualTo: userId)

```
L175 |         .orderBy('createdAt', descending: true)
```
-> Code: .orderBy('createdAt', descending: true)

```
L176 |         .snapshots()
```
-> Code: .snapshots()

```
L177 |         .map(
```
-> Code: .map(

```
L178 |           (snapshot) =>
```
-> Code: (snapshot) =>

```
L179 |                snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList(),
```
-> Code: snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList(),

```
L180 |          );
```
-> Code:);

```
L181 |    }
```
-> Code: }

```
L182 |
```
-> Blank line

```
L183 |    Stream<List<Post>> streamAllPosts() {
```
-> Function/method declaration or async return type: Stream<List<Post>> streamAllPosts() {

```
L184 |      return _firestore
```
-> Return statement: return _firestore

```
L185 |          .collection('posts')
```
-> Code: .collection('posts')

```
L186 |          .orderBy('createdAt', descending: true)
```
-> Code: .orderBy('createdAt', descending: true)

```
L187 |          .snapshots()
```
-> Code: .snapshots()

```
L188 |          .map(
```
-> Code: .map(

```
L189 |            (snapshot) =>
```
-> Code: (snapshot) =>

```
L190 |                snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList(),
```
-> Code: snapshot.docs.map((doc) => Post.fromMap(doc.data())).toList(),

```
L191 |          );
```
-> Code:);

```
L192 |    }
```
-> Code: }

```
L193 | }
```
-> Code: }

```
L001 | class Post {
  -> Class declaration: class Post {
L002 |   final String id;
  -> Variable declaration: final String id;
L003 |   final String userId;
  -> Variable declaration: final String userId;
L004 |   final String userName;
  -> Variable declaration: final String userName;
L005 |   final String userProfileImage;
  -> Variable declaration: final String userProfileImage;
L006 |   final String caption;
  -> Variable declaration: final String caption;
L007 |   final String imageUrl;
  -> Variable declaration: final String imageUrl;
L008 |   final int createdAt;
  -> Variable declaration: final int createdAt;
L009 |   final int likeCount;
  -> Variable declaration: final int likeCount;
L010 |   final bool isSaved;
  -> Variable declaration: final bool isSaved;
L011 |   final List<String> likes;
  -> Variable declaration: final List<String> likes;
L012 |   final List<String> savedBy;
  -> Variable declaration: final List<String> savedBy;
L013 |
  -> Blank line
L014 |   Post({
  -> Code: Post({
L015 |     required this.id,
  -> Code: required this.id,
L016 |     required this.userId,
  -> Code: required this.userId,
L017 |     required this.userName,
  -> Code: required this.userName,
L018 |     required this.userProfileImage,
  -> Code: required this.userProfileImage,
L019 |     required this.caption,
  -> Code: required this.caption,
L020 |     required this.imageUrl,
  -> Code: required this.imageUrl,
L021 |     required this.createdAt,
  -> Code: required this.createdAt,
L022 |     this.likeCount = 0,
  -> Code: this.likeCount = 0,
L023 |     this.isSaved = false,
  -> Code: this.isSaved = false,
L024 |     this.likes = const [],
  -> Code: this.likes = const [],
L025 |     this.savedBy = const [],
  -> Code: this.savedBy = const [],
L026 |   });
  -> Code: });
L027 |
  -> Blank line
L028 |   Map<String, dynamic> toMap() => {
  -> Code: Map<String, dynamic> toMap() => {
L029 |     'id': id,
  -> Code: 'id': id,
L030 |     'userId': userId,
  -> Code: 'userId': userId,
L031 |     'userName': userName,
  -> Code: 'userName': userName,
L032 |     'userProfileImage': userProfileImage,
  -> Code: 'userProfileImage': userProfileImage,
L033 |     'caption': caption,
  -> Code: 'caption': caption,
L034 |     'imageUrl': imageUrl,
  -> Code: 'imageUrl': imageUrl,
```

```
L035 |     'createdAt': createdAt,
```
-> Code: 'createdAt': createdAt,

```
L036 |     'likeCount': likeCount,
```
-> Code: 'likeCount': likeCount,

```
L037 |     'likes': likes,
```
-> Code: 'likes': likes,

```
L038 |     'isSaved': isSaved,
```
-> Code: 'isSaved': isSaved,

```
L039 |     'savedBy': savedBy,
```
-> Code: 'savedBy': savedBy,

```
L040 |   };
```
-> Code: };

```
L041 |
```
-> Blank line

```
L042 |   factory Post.fromMap(Map<String, dynamic> map) => Post(
```
-> Code: factory Post.fromMap(Map<String, dynamic> map) => Post(

```
L043 |     id: map['id'] ?? '',
```
-> Code: id: map['id'] ?? '',

```
L044 |     userId: map['userId'] ?? '',
```
-> Code: userId: map['userId'] ?? '',

```
L045 |     userName: map['userName'] ?? '',
```
-> Code: userName: map['userName'] ?? '',

```
L046 |     userProfileImage: map['userProfileImage'] ?? '',
```
-> Code: userProfileImage: map['userProfileImage'] ?? '',

```
L047 |     caption: map['caption'] ?? '',
```
-> Code: caption: map['caption'] ?? '',

```
L048 |     imageUrl: map['imageUrl'] ?? '',
```
-> Code: imageUrl: map['imageUrl'] ?? '',

```
L049 |     createdAt: (map['createdAt'] is int)
```
-> Code: createdAt: (map['createdAt'] is int)

```
L050 |         ? map['createdAt']
```
-> Code: ? map['createdAt']

```
L051 |         : int.tryParse(map['createdAt'].toString()) ?? 0,
```
-> Code: : int.tryParse(map['createdAt'].toString()) ?? 0,

```
L052 |     likeCount: map['likeCount'] ?? 0,
```
-> Code: likeCount: map['likeCount'] ?? 0,

```
L053 |     likes: map['likes'] != null ? List<String>.from(map['likes']) : [],
```
-> Code: likes: map['likes'] != null ? List<String>.from(map['likes']) : [],

```
L054 |     isSaved: map['isSaved'] ?? false,
```
-> Code: isSaved: map['isSaved'] ?? false,

```
L055 |     savedBy: map['savedBy'] != null ? List<String>.from(map['savedBy']) : [],
```
-> Code: savedBy: map['savedBy'] != null ? List<String>.from(map['savedBy']) : [],

```
L056 |   );
```
-> Code:);

```
L057 |
```
-> Blank line

```
L058 |   Post copyWith({bool? isSaved, List<String>? likes, List<String>? savedBy}) {
```
-> Code: Post copyWith({bool? isSaved, List<String>? likes, List<String>? savedBy}) {

```
L059 |     return Post(
```
-> Return statement: return Post(

```
L060 |       id: id,
```
-> Code: id: id,

```
L061 |       userId: userId,
```
-> Code: userId: userId,

```
L062 |       userName: userName,
```
-> Code: userName: userName,

```
L063 |       userProfileImage: userProfileImage,
```
-> Code: userProfileImage: userProfileImage,

```
L064 |       caption: caption,
```
-> Code: caption: caption,

```
L065 |       imageUrl: imageUrl,
```
-> Code: imageUrl: imageUrl,

```
L066 |       createdAt: createdAt,
```
-> Code: createdAt: createdAt,

```
L067 |       likeCount: likeCount,
```
-> Code: likeCount: likeCount,

```
L068 |       isSaved: isSaved ?? this.isSaved,
```
-> Code: isSaved: isSaved ?? this.isSaved,

```
L069 |       likes: likes ?? this.likes,
```
-> Code: likes: likes ?? this.likes,

```
L070 |       savedBy: savedBy ?? this.savedBy,
```
-> Code: savedBy: savedBy ?? this.savedBy,

```
L071 |     );
```
-> Code:);

```
L072 |   }
```
-> Code: }

```
L073 |
```
-> Blank line

```
L074 |
```
-> Blank line

```
L075 |   bool isLikedBy(String uid) => likes.contains(uid);
```
-> Short arrow function/expression: bool isLikedBy(String uid) => likes.contains(uid);

```
L076 |   // bool isSavedBy(String uid) => savedBy.contains(uid);
```
-> Comment: bool isSavedBy(String uid) => savedBy.contains(uid);

```
L077 |   bool isSavedBy(String userId) => savedBy.contains(userId);
```
-> Short arrow function/expression: bool isSavedBy(String userId) => savedBy.contains(userId);

```
L078 |
```
-> Blank line

```
L079 | }
```
-> Code: }

lib/features/posts/domain/post_repo.dart

```
L001 | import '../data/post_model.dart';
```
-> Imports module or package: import '../data/post_model.dart';

```
L002 |
```
-> Blank line

```
L003 | abstract class PostRepo {
```
-> Class declaration (complex): abstract class PostRepo {

```
L004 |   Future<List<Post>> fetchAllPosts();
```
-> Function/method declaration or async return type: Future<List<Post>> fetchAllPosts();

```
L005 |   Future<void> createPost(Post post);
```
-> Function/method declaration or async return type: Future<void> createPost(Post post);

```
L006 |   Future<void> deletePost(String postId);
```
-> Function/method declaration or async return type: Future<void> deletePost(String postId);

```
L007 |   Future<List<Post>> fetchPostsByUserId(String userId);
```
-> Function/method declaration or async return type: Future<List<Post>> fetchPostsByUserId(String userId);

```
L008 |
```
-> Blank line

```
L009 |    Stream<List<Post>> streamPostsByUserId(String userId);
```
-> Function/method declaration or async return type: Stream<List<Post>> streamPostsByUserId(String userId);

```
L010 |    Stream<List<Post>> streamAllPosts();
```
-> Function/method declaration or async return type: Stream<List<Post>> streamAllPosts();

```
L011 |
```
-> Blank line

```
L012 |
```
-> Blank line

```
L013 |   Future<void> toggleLike(String postId, String userId);
```
-> Function/method declaration or async return type: Future<void> toggleLike(String postId, String userId);

```
L014 |   Future<bool> isPostLiked(String postId, String userId);
```
-> Function/method declaration or async return type: Future<bool> isPostLiked(String postId, String userId);

```
L015 |   Future<void> addComment(String postId, String userId, String text);
```
-> Function/method declaration or async return type: Future<void> addComment(String postId, String userId, String text);

```
L016 |   Future<List<Map<String, dynamic>>> getComments(String postId);
```
-> Function/method declaration or async return type: Future<List<Map<String, dynamic>>> getComments(String postId);

```
L017 |
```
-> Blank line

```
L018 |   Future<void> toggleSavePost(String postId, String userId);
```
-> Function/method declaration or async return type: Future<void> toggleSavePost(String postId, String userId);

```
L019 |   Future<List<String>> getSavedPostsIds(String userId);
```
-> Function/method declaration or async return type: Future<List<String>> getSavedPostsIds(String userId);

```
L020 |   Future<List<Post>> getSavedPosts(String userId);
```
-> Function/method declaration or async return type: Future<List<Post>> getSavedPosts(String userId);

```
L021 | }
```
-> Code: }

lib/features/posts/presentation/bloc/post_cubit.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
```
-> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';

```
L004 | import '../../domain/post_repo.dart';
```
-> Imports module or package: import '../../domain/post_repo.dart';

```
L005 | import '../../data/post_model.dart';
```
-> Imports module or package: import '../../data/post_model.dart';

```
L006 | import 'post_states.dart';
```
-> Imports module or package: import 'post_states.dart';

```
L007 |
```
-> Blank line

```
L008 | class PostCubit extends Cubit<PostStates> {
```
-> Class declaration: class PostCubit extends Cubit<PostStates> {

```
L009 |   final PostRepo postRepo;
```
-> Variable declaration: final PostRepo postRepo;

```
L010 |   final AppwritePostStorageRepo storageRepo;
```
-> Variable declaration: final AppwritePostStorageRepo storageRepo;

```
L011 |   final _firestore = FirebaseFirestore.instance;
```
-> Variable declaration: final _firestore = FirebaseFirestore.instance;

```
L012 |
```
-> Blank line

```
L013 |   List<Post> _posts = [];
```
-> Code: List<Post> _posts = [];

```
L014 |
```
-> Blank line

```
L015 |   PostCubit({required this.postRepo, required this.storageRepo})
```
-> Code: PostCubit({required this.postRepo, required this.storageRepo})

```
L016 |     : super(PostInitial());
```
-> Code: : super(PostInitial());

```
L017 |
```
-> Blank line

```
L018 |
```
-> Blank line

```
L019 |   Future<void> fetchAllPosts() async {
```
-> Function/method declaration or async return type: Future<void> fetchAllPosts() async {

```
L020 |     emit(PostLoading());
```
-> Code: emit(PostLoading());

```
L021 |     try {
```
-> Code: try {

```
L022 |       final posts = await postRepo.fetchAllPosts();
```
-> Variable declaration: final posts = await postRepo.fetchAllPosts();

```
L023 |       _posts = posts;
```
-> Code: _posts = posts;

```
L024 |       emit(PostLoaded(posts));
```
-> Code: emit(PostLoaded(posts));

```
L025 |     } catch (e, st) {
```
-> Code: } catch (e, st) {

```
L026 |       print(' [PostCubit] Fetch failed: $e');
```
-> Code: print(' [PostCubit] Fetch failed: $e');

```
L027 |       print(st);
```
-> Code: print(st);

```
L028 |       emit(PostError(e.toString()));
```
-> Code: emit(PostError(e.toString()));

```
L029 |     }
```
-> Code: }

```
L030 |   }
```
-> Code: }

```
L031 |
```
-> Blank line

```
L032 |
```
-> Blank line

```
L033 |   Future<void> fetchPostsByUserId(String userId) async {
```
-> Function/method declaration or async return type: Future<void> fetchPostsByUserId(String userId) async {

```
L034 |     emit(PostLoading());
```
-> Code: emit(PostLoading());

```
L035 |     try {
```
-> Code: try {

```
L036 |       final posts = await postRepo.fetchPostsByUserId(userId);
```
-> Variable declaration: final posts = await postRepo.fetchPostsByUserId(userId);

```
L037 |       emit(PostLoaded(posts));
```
-> Code: emit(PostLoaded(posts));

```
L038 |     } catch (e) {
```
-> Code: } catch (e) {

```
L039 |       emit(PostError(e.toString()));
```
-> Code: emit(PostError(e.toString()));

```
L040 |     }
```
-> Code: }

```
L041 |   }
```
-> Code: }

```
L042 |
```
-> Blank line

```
L043 |
```
-> Blank line

```
L044 |   Future<void> createPost({
```
-> Function/method declaration or async return type: Future<void> createPost({

```
L045 |     required String userId,
```
-> Code: required String userId,

```
L046 |     required String caption,
```
-> Code: required String caption,

```
L047 |     required String imagePath,
```
-> Code: required String imagePath,

```
L048 |   }) async {
```
-> Code: }) async {

```
L049 |     emit(PostLoading());
```
-> Code: emit(PostLoading());

```
L050 |     try {
```
-> Code: try {

```
L051 |       final userDoc = await _firestore.collection('users').doc(userId).get();
```
-> Variable declaration: final userDoc = await _firestore.collection('users').doc(userId).get();

```
L052 |       final userData = userDoc.data();
```
-> Variable declaration: final userData = userDoc.data();

```
L053 |       final userName = userData?['name'] ?? 'Unknown User';
```
-> Variable declaration: final userName = userData?['name'] ?? 'Unknown User';

```
L054 |       final userProfileImage = userData?['profileImg'] ?? '';
```
-> Variable declaration: final userProfileImage = userData?['profileImg'] ?? '';

```
L055 |
```
-> Blank line

```
L056 |       final imageUrl = await storageRepo.uploadPostImage(imagePath, userId);
```
-> Variable declaration: final imageUrl = await storageRepo.uploadPostImage(imagePath, userId);

```
L057 |
```
-> Blank line

```
L058 |       final post = Post(
```
-> Variable declaration: final post = Post(

```
L059 |         id: DateTime.now().millisecondsSinceEpoch.toString(),
```
-> Code: id: DateTime.now().millisecondsSinceEpoch.toString(),

```
L060 |         userId: userId,
```
-> Code: userId: userId,

```
L061 |         userName: userName,
```
-> Code: userName: userName,

```
L062 |         userProfileImage: userProfileImage,
```
-> Code: userProfileImage: userProfileImage,

```
L063 |         caption: caption,
```
-> Code: caption: caption,

```
L064 |         imageUrl: imageUrl ?? '',
```
-> Code: imageUrl: imageUrl ?? '',

```
L065 |         createdAt: DateTime.now().millisecondsSinceEpoch,
```
-> Code: createdAt: DateTime.now().millisecondsSinceEpoch,

```
L066 |         likeCount: 0,
```
-> Code: likeCount: 0,

```
L067 |         likes: [],
```
-> Code: likes: [],

```
L068 |         savedBy: [],
```
-> Code: savedBy: [],

```
L069 |         isSaved: false,
```
-> Code: isSaved: false,

```
L070 |       );
```
-> Code:);

L071 |
  -> Blank line

L072 | await postRepo.createPost(post);
  -> Code: await postRepo.createPost(post);

L073 | _posts.insert(0, post);
  -> Code: _posts.insert(0, post);

L074 | emit(PostLoaded(List.from(_posts)));
  -> Code: emit(PostLoaded(List.from(_posts)));

L075 | } catch (e, st) {
  -> Code: } catch (e, st) {

L076 | print(' [PostCubit] Create post failed: $e');
  -> Code: print(' [PostCubit] Create post failed: $e');

L077 | print(st);
  -> Code: print(st);

L078 | emit(PostError(e.toString()));
  -> Code: emit(PostError(e.toString()));

L079 | }
  -> Code: }

L080 | }
  -> Code: }

L081 |
  -> Blank line

L082 |
  -> Blank line

L083 | Future<void> deletePost(String postId) async {
  -> Function/method declaration or async return type: Future<void> deletePost(String postId) async {

L084 | try {
  -> Code: try {

L085 | await postRepo.deletePost(postId);
  -> Code: await postRepo.deletePost(postId);

L086 | _posts.removeWhere((p) => p.id == postId);
  -> Short arrow function/expression: _posts.removeWhere((p) => p.id == postId);

L087 | emit(PostLoaded(List.from(_posts)));
  -> Code: emit(PostLoaded(List.from(_posts)));

L088 | } catch (e) {
  -> Code: } catch (e) {

L089 | emit(PostError(e.toString()));
  -> Code: emit(PostError(e.toString()));

L090 | }
  -> Code: }

L091 | }
  -> Code: }

L092 |
  -> Blank line

L093 |
  -> Blank line

L094 | Future<void> toggleLike(String postId, String userId) async {
  -> Function/method declaration or async return type: Future<void> toggleLike(String postId, String userId) async {

L095 | try {
  -> Code: try {

L096 | final currentState = state;
  -> Variable declaration: final currentState = state;

L097 | if (currentState is PostLoaded) {
  -> Control flow statement: if (currentState is PostLoaded) {

L098 | final updatedPosts = currentState.posts.map((post) {
  -> Variable declaration: final updatedPosts = currentState.posts.map((post) {

L099 | if (post.id == postId) {
  -> Control flow statement: if (post.id == postId) {

L100 | final newLikes = List<String>.from(post.likes);
  -> Variable declaration: final newLikes = List<String>.from(post.likes);

L101 | if (newLikes.contains(userId)) {
  -> Control flow statement: if (newLikes.contains(userId)) {

L102 | newLikes.remove(userId);
  -> Code: newLikes.remove(userId);

L103 | } else {
  -> Code: } else {

L104 | newLikes.add(userId);
  -> Code: newLikes.add(userId);

L105 | }
  -> Code: }

L106 | return post.copyWith(likes: newLikes);
  -> Return statement: return post.copyWith(likes: newLikes);

```
L107 |           }
```
-> Code: }

```
L108 |           return post;
```
-> Return statement: return post;

```
L109 |         }).toList();
```
-> Code: }).toList();

```
L110 |
```
-> Blank line

```
L111 |         emit(PostLoaded(updatedPosts));
```
-> Code: emit(PostLoaded(updatedPosts));

```
L112 |       }
```
-> Code: }

```
L113 |
```
-> Blank line

```
L114 |       final postRef = _firestore.collection('posts').doc(postId);
```
-> Variable declaration: final postRef = _firestore.collection('posts').doc(postId);

```
L115 |       final doc = await postRef.get();
```
-> Variable declaration: final doc = await postRef.get();

```
L116 |       if (!doc.exists) return;
```
-> Control flow statement: if (!doc.exists) return;

```
L117 |
```
-> Blank line

```
L118 |       final data = doc.data()!;
```
-> Variable declaration: final data = doc.data()!;

```
L119 |       final likes = List<String>.from(data['likes'] ?? []);
```
-> Variable declaration: final likes = List<String>.from(data['likes'] ?? []);

```
L120 |
```
-> Blank line

```
L121 |       if (likes.contains(userId)) {
```
-> Control flow statement: if (likes.contains(userId)) {

```
L122 |         likes.remove(userId);
```
-> Code: likes.remove(userId);

```
L123 |       } else {
```
-> Code: } else {

```
L124 |         likes.add(userId);
```
-> Code: likes.add(userId);

```
L125 |       }
```
-> Code: }

```
L126 |
```
-> Blank line

```
L127 |       await postRef.update({'likes': likes, 'likeCount': likes.length});
```
-> Code: await postRef.update({'likes': likes, 'likeCount': likes.length});

```
L128 |     } catch (e, st) {
```
-> Code: } catch (e, st) {

```
L129 |       print(' [PostCubit] toggleLike error: $e');
```
-> Code: print(' [PostCubit] toggleLike error: $e');

```
L130 |       print(st);
```
-> Code: print(st);

```
L131 |       emit(PostError(e.toString()));
```
-> Code: emit(PostError(e.toString()));

```
L132 |     }
```
-> Code: }

```
L133 |   }
```
-> Code: }

```
L134 |
```
-> Blank line

```
L135 |
```
-> Blank line

```
L136 |   Future<void> addComment(String postId, String userId, String text) async {
```
-> Function/method declaration or async return type: Future<void> addComment(String postId, String userId, String text) async {

```
L137 |     try {
```
-> Code: try {

```
L138 |       await postRepo.addComment(postId, userId, text);
```
-> Code: await postRepo.addComment(postId, userId, text);

```
L139 |     } catch (e) {
```
-> Code: } catch (e) {

```
L140 |       emit(PostError(e.toString()));
```
-> Code: emit(PostError(e.toString()));

```
L141 |     }
```
-> Code: }

```
L142 |   }
```
-> Code: }

```
L143 |
```
-> Blank line

```
L144 |   Future<List<Map<String, dynamic>>> getComments(String postId) async {
```
-> Function/method declaration or async return type: Future<List<Map<String, dynamic>>> getComments(String postId) async {

```
L145 |     return await postRepo.getComments(postId);
```
-> Return statement: return await postRepo.getComments(postId);

```
L146 |   }
```
-> Code: }

```
L147 |
```
-> Blank line

```
L148 |
```
-> Blank line

```
L149 |   Future<void> toggleSavePost(String postId, String userId) async {
```
-> Function/method declaration or async return type: Future<void> toggleSavePost(String postId, String userId) async {

```
L150 |   try {
```
-> Code: try {

```
L151 |     final postRef = _firestore.collection('posts').doc(postId);
```
-> Variable declaration: final postRef = _firestore.collection('posts').doc(postId);

```
L152 |     final doc = await postRef.get();
```
-> Variable declaration: final doc = await postRef.get();

```
L153 |     if (!doc.exists) return;
```
-> Control flow statement: if (!doc.exists) return;

```
L154 |
```
-> Blank line

```
L155 |     final data = doc.data()!;
```
-> Variable declaration: final data = doc.data()!;

```
L156 |     final savedBy = List<String>.from(data['savedBy'] ?? []);
```
-> Variable declaration: final savedBy = List<String>.from(data['savedBy'] ?? []);

```
L157 |
```
-> Blank line

```
L158 |     if (savedBy.contains(userId)) {
```
-> Control flow statement: if (savedBy.contains(userId)) {

```
L159 |       savedBy.remove(userId);
```
-> Code: savedBy.remove(userId);

```
L160 |     } else {
```
-> Code: } else {

```
L161 |       savedBy.add(userId);
```
-> Code: savedBy.add(userId);

```
L162 |     }
```
-> Code: }

```
L163 |
```
-> Blank line

```
L164 |     await postRef.update({'savedBy': savedBy});
```
-> Code: await postRef.update({'savedBy': savedBy});

```
L165 |
```
-> Blank line

```
L166 |
```
-> Blank line

```
L167 |     final currentState = state;
```
-> Variable declaration: final currentState = state;

```
L168 |     if (currentState is PostLoaded) {
```
-> Control flow statement: if (currentState is PostLoaded) {

```
L169 |       final updatedPosts = currentState.posts.map((post) {
```
-> Variable declaration: final updatedPosts = currentState.posts.map((post) {

```
L170 |         if (post.id == postId) {
```
-> Control flow statement: if (post.id == postId) {

```
L171 |           return post.copyWith(savedBy: savedBy);
```
-> Return statement: return post.copyWith(savedBy: savedBy);

```
L172 |         }
```
-> Code: }

```
L173 |         return post;
```
-> Return statement: return post;

```
L174 |       }).toList();
```
-> Code: }).toList();

```
L175 |       emit(PostLoaded(List.from(updatedPosts)));
```
-> Code: emit(PostLoaded(List.from(updatedPosts)));

```
L176 |
```
-> Blank line

```
L177 |     }
```
-> Code: }

```
L178 |
```
-> Blank line

```
L179 |
```
-> Blank line

```
L180 |     emit(SavedPostsUpdated());
```
-> Code: emit(SavedPostsUpdated());

```
L181 |   } catch (e, st) {
```
-> Code: } catch (e, st) {

```
L182 |     print(' [PostCubit] toggleSavePost error: $e');
```
-> Code: print(' [PostCubit] toggleSavePost error: $e');

```
L183 |     print(st);
```
-> Code: print(st);

```
L184 |     emit(PostError(e.toString()));
```
-> Code: emit(PostError(e.toString()));

```
L185 |   }
```
-> Code: }

```
L186 | }
```
-> Code: }

```
L187 |
```
-> Blank line

```
L188 |
```
-> Blank line

```
L189 |
```
-> Blank line

```
L190 |   Future<List<Post>> getSavedPosts(String userId) async {
```
-> Function/method declaration or async return type: Future<List<Post>> getSavedPosts(String userId) async {

```
L191 |     try {
```
-> Code: try {

```
L192 |       final query = await _firestore
```
-> Variable declaration: final query = await _firestore

```
L193 |           .collection('posts')
```
-> Code: .collection('posts')

```
L194 |           .where('savedBy', arrayContains: userId)
```
-> Code: .where('savedBy', arrayContains: userId)

```
L195 |           .get();
```
-> Code: .get();

```
L196 |       return query.docs.map((doc) => Post.fromMap(doc.data())).toList();
```
-> Return statement: return query.docs.map((doc) => Post.fromMap(doc.data())).toList();

```
L197 |     } catch (e) {
```
-> Code: } catch (e) {

```
L198 |       print(' [PostCubit] getSavedPosts error: $e');
```
-> Code: print(' [PostCubit] getSavedPosts error: $e');

```
L199 |       return [];
```
-> Return statement: return [];

```
L200 |     }
```
-> Code: }

```
L201 |   }
```
-> Code: }

```
L202 | }
```
-> Code: }

lib/features/posts/presentation/bloc/post_states.dart

```
L001 | import 'package:equatable/equatable.dart';
```
-> Imports module or package: import 'package:equatable/equatable.dart';

```
L002 | import '../../data/post_model.dart';
```
-> Imports module or package: import '../../data/post_model.dart';

```
L003 |
```
-> Blank line

```
L004 | abstract class PostStates extends Equatable {
```
-> Class declaration (complex): abstract class PostStates extends Equatable {

```
L005 |   @override
```
-> Annotation/Decorator: @override

```
L006 |   List<Object?> get props => [];
```
-> Short arrow function/expression: List<Object?> get props => [];

```
L007 | }
```
-> Code: }

```
L008 |
```
-> Blank line

```
L009 | class PostInitial extends PostStates {}
```
-> Class declaration: class PostInitial extends PostStates {}

```
L010 |
```
-> Blank line

```
L011 | class PostLoading extends PostStates {}
```
-> Class declaration: class PostLoading extends PostStates {}

```
L012 |
```
-> Blank line

```
L013 | class PostLoaded extends PostStates {
```
-> Class declaration: class PostLoaded extends PostStates {

```
L014 |   final List<Post> posts;
```
-> Variable declaration: final List<Post> posts;

```
L015 |   PostLoaded(this.posts);
```
-> Code: PostLoaded(this.posts);

```
L016 |
```
-> Blank line

```
L017 |   @override
```
-> Annotation/Decorator: @override

```
L018 |   List<Object?> get props => [posts];
```
-> Short arrow function/expression: List<Object?> get props => [posts];

```
L019 | }
```
-> Code: }

```
L020 |
```
-> Blank line

```
L021 | class PostError extends PostStates {
```
-> Class declaration: class PostError extends PostStates {

```
L022 |   final String message;
```
-> Variable declaration: final String message;

```
L023 |   PostError(this.message);
```
-> Code: PostError(this.message);

```
L024 |
```
-> Blank line

```
L025 |   @override
```
-> Annotation/Decorator: @override

```
L026 |   List<Object?> get props => [message];
```
-> Short arrow function/expression: List<Object?> get props => [message];

```
L027 | }
```
-> Code: }

```
L028 |
```
-> Blank line

```
L029 | class PostSaving extends PostStates {
```
-> Class declaration: class PostSaving extends PostStates {

```
L030 |   final String postId;
```
-> Variable declaration: final String postId;

```
L031 |   PostSaving(this.postId);
```
-> Code: PostSaving(this.postId);

```
L032 | }
```
-> Code: }

```
L033 |
```
-> Blank line

```
L034 | class SavedPostsUpdated extends PostStates {
```
-> Class declaration: class SavedPostsUpdated extends PostStates {

```
L035 |   final List<String> savedIds;
```
-> Variable declaration: final List<String> savedIds;

```
L036 |   SavedPostsUpdated([this.savedIds = const []]);
```
-> Code: SavedPostsUpdated([this.savedIds = const []]);

```
L037 |
```
-> Blank line

```
L038 |   @override
```
-> Annotation/Decorator: @override

```
L039 |   List<Object?> get props => [savedIds];
```
-> Short arrow function/expression: List<Object?> get props => [savedIds];

```
L040 | }
```
-> Code: }

```
L041 |
```
-> Blank line

lib/features/posts/presentation/components/post_tile.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import '../../data/post_model.dart';
```
-> Imports module or package: import '../../data/post_model.dart';

```
L003 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L004 | import '../bloc/post_cubit.dart';
```
-> Imports module or package: import '../bloc/post_cubit.dart';

```
L005 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L006 | import '../../presentation/pages/comments_page.dart';
```
-> Imports module or package: import '../../presentation/pages/comments_page.dart';

```
L007 |
```
-> Blank line

```
L008 | class PostTile extends StatelessWidget {
```
-> Class declaration: class PostTile extends StatelessWidget {

```
L009 |   final Post post;
```
-> Variable declaration: final Post post;

```
L010 |   const PostTile({super.key, required this.post});
```
-> Variable declaration: const PostTile({super.key, required this.post});

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L014 |     final currentUser = FirebaseAuth.instance.currentUser;
```
-> Variable declaration: final currentUser = FirebaseAuth.instance.currentUser;

```
L015 |     final currentUid = currentUser?.uid ?? '';
```
-> Variable declaration: final currentUid = currentUser?.uid ?? '';

```
L016 |
```
-> Blank line

```
L017 |     final isLiked = post.likes.contains(currentUid);
```
-> Variable declaration: final isLiked = post.likes.contains(currentUid);

```
L018 |     final isMark = post.isSavedBy(currentUid);
```
-> Variable declaration: final isMark = post.isSavedBy(currentUid);

```
L019 |     final profileImage = post.userProfileImage.isNotEmpty
```
-> Variable declaration: final profileImage = post.userProfileImage.isNotEmpty

```
L020 |         ? post.userProfileImage
```
-> Code: ? post.userProfileImage

```
L021 |         : 'https://cdn-icons-png.flaticon.com/512/149/149071.png';
```
-> Code: : 'https://cdn-icons-png.flaticon.com/512/149/149071.png';

```
L022 |     final userName = post.userName.isNotEmpty ? post.userName : 'Unknown User';
```
-> Variable declaration: final userName = post.userName.isNotEmpty ? post.userName : 'Unknown User';

```
L023 |
```
-> Blank line

```
L024 |     return Card(
```
-> Return statement: return Card(

```
L025 |       margin: const EdgeInsets.symmetric(vertical: 8, horizontal: 12),
```
-> Code: margin: const EdgeInsets.symmetric(vertical: 8, horizontal: 12),

```
L026 |       shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(16)),
```
-> Code: shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(16)),

```
L027 |       elevation: 2,
```
-> Code: elevation: 2,

```
L028 |       child: Column(
```
-> Code: child: Column(

```
L029 |         crossAxisAlignment: CrossAxisAlignment.start,
```
-> Code: crossAxisAlignment: CrossAxisAlignment.start,

```
L030 |         children: [
```
-> Code: children: [

```
L031 |           ListTile(
```
-> Code: ListTile(

```
L032 |             leading: CircleAvatar(
```
-> Code: leading: CircleAvatar(

```
L033 |               backgroundImage: NetworkImage(profileImage),
```
-> Code: backgroundImage: NetworkImage(profileImage),

```
L034 |               radius: 22,
```
-> Code: radius: 22,

```
L035 |             ),
  -> Code: ),
L036 |             title: Text(
  -> Code: title: Text(
L037 |               userName,
  -> Code: userName,
L038 |               style: const TextStyle(fontWeight: FontWeight.bold),
  -> Code: style: const TextStyle(fontWeight: FontWeight.bold),
L039 |             ),
  -> Code: ),
L040 |             subtitle: Text(
  -> Code: subtitle: Text(
L041 |               DateTime.fromMillisecondsSinceEpoch(
  -> Code: DateTime.fromMillisecondsSinceEpoch(
L042 |                 post.createdAt,
  -> Code: post.createdAt,
L043 |               ).toLocal().toString().substring(0, 16),
  -> Code: ).toLocal().toString().substring(0, 16),
L044 |               style: const TextStyle(fontSize: 12, color: Colors.grey),
  -> Code: style: const TextStyle(fontSize: 12, color: Colors.grey),
L045 |             ),
  -> Code: ),
L046 |             // onTap: () {
  -> Comment:  onTap: () {
L047 |             //   Navigator.push(
  -> Comment:    Navigator.push(
L048 |             //     context,
  -> Comment:     context,
L049 |             //     MaterialPageRoute(builder: (_) => PostDetailPage(post: post)),
  -> Comment:     MaterialPageRoute(builder: (_) => PostDetailPage(post: post)),
L050 |             //   );
  -> Comment:    );
L051 |             // },
  -> Comment:  },
L052 |           ),
  -> Code: ),
L053 |           if (post.imageUrl.isNotEmpty)
  -> Control flow statement: if (post.imageUrl.isNotEmpty)
L054 |             ClipRRect(
  -> Code: ClipRRect(
L055 |               borderRadius: BorderRadius.circular(12),
  -> Code: borderRadius: BorderRadius.circular(12),
L056 |               child: Image.network(
  -> Code: child: Image.network(
L057 |                 post.imageUrl,
  -> Code: post.imageUrl,
L058 |                 height: 250,
  -> Code: height: 250,
L059 |                 width: double.infinity,
  -> Code: width: double.infinity,
L060 |                 fit: BoxFit.cover,
  -> Code: fit: BoxFit.cover,
L061 |                 loadingBuilder: (context, child, progress) {
  -> Code: loadingBuilder: (context, child, progress) {
L062 |                   if (progress == null) return child;
  -> Control flow statement: if (progress == null) return child;
L063 |                   return Container(
  -> Return statement: return Container(
L064 |                     height: 250,
  -> Code: height: 250,
L065 |                     color: Colors.brown,
  -> Code: color: Colors.brown,
L066 |                     child: const Center(
  -> Code: child: const Center(
L067 |                       child: CircularProgressIndicator(color: Colors.black),
  -> Code: child: CircularProgressIndicator(color: Colors.black),
L068 |                     ),
  -> Code: ),
L069 |                   );
  -> Code: );
L070 |                 },
  -> Code: },
```

```
L071 |                   errorBuilder: (context, error, stackTrace) {
  -> Code: errorBuilder: (context, error, stackTrace) {
L072 |                     debugPrint(' Failed to load ${post.imageUrl}');
  -> Code: debugPrint(' Failed to load ${post.imageUrl}');
L073 |                     debugPrint(error.toString());
  -> Code: debugPrint(error.toString());
L074 |                     return Container(
  -> Return statement: return Container(
L075 |                       height: 250,
  -> Code: height: 250,
L076 |                       color: Colors.black12,
  -> Code: color: Colors.black12,
L077 |                       child: const Icon(
  -> Code: child: const Icon(
L078 |                         Icons.broken_image,
  -> Code: Icons.broken_image,
L079 |                         size: 60,
  -> Code: size: 60,
L080 |                         color: Colors.grey,
  -> Code: color: Colors.grey,
L081 |                       ),
  -> Code: ),
L082 |                     );
  -> Code: );
L083 |                   },
  -> Code: },
L084 |                 ),
  -> Code: ),
L085 |               ),
  -> Code: ),
L086 |
  -> Blank line
L087 |             Padding(
  -> Code: Padding(
L088 |               padding: const EdgeInsets.symmetric(horizontal: 8.0, vertical: 6),
  -> Code: padding: const EdgeInsets.symmetric(horizontal: 8.0, vertical: 6),
L089 |               child: Row(
  -> Code: child: Row(
L090 |                 children: [
  -> Code: children: [
L091 |                   // IconButton(
  -> Comment:  IconButton(
L092 |                   //   icon: Icon(
  -> Comment:    icon: Icon(
L093 |                   //     isLiked ? Icons.favorite : Icons.favorite_border,
  -> Comment:      isLiked ? Icons.favorite : Icons.favorite_border,
L094 |                   //     color: isLiked ? Colors.red : null,
  -> Comment:      color: isLiked ? Colors.red : null,
L095 |                   //   ),
  -> Comment:    ),
L096 |                   //   onPressed: () =>
  -> Comment:    onPressed: () =>
L097 |                   //       context.read<PostCubit>().toggleLike(post.id, currentUid),
  -> Comment:       context.read<PostCubit>().toggleLike(post.id, currentUid),
L098 |                   // ),
  -> Comment:  ),
L099 |                   IconButton(
  -> Code: IconButton(
L100 |                     icon: const Icon(Icons.comment_outlined),
  -> Code: icon: const Icon(Icons.comment_outlined),
L101 |                     onPressed: () {
  -> Code: onPressed: () {
L102 |                       Navigator.push(
  -> Code: Navigator.push(
L103 |                         context,
  -> Code: context,
L104 |                         MaterialPageRoute(
  -> Code: MaterialPageRoute(
L105 |                           builder: (_) => CommentsPage(
  -> Code: builder: (_) => CommentsPage(
L106 |                             postId: post.id,
  -> Code: postId: post.id,
```

```
L107 |                             currentUserId: currentUid,
  -> Code: currentUserId: currentUid,
L108 |                           ),
  -> Code: ),
L109 |                         ),
  -> Code: ),
L110 |                       );
  -> Code: );
L111 |                     },
  -> Code: },
L112 |                   ),
  -> Code: ),
L113 |
  -> Blank line
L114 |                   const Spacer(),
  -> Variable declaration: const Spacer(),
L115 |                   IconButton(
  -> Code: IconButton(
L116 |                     icon: Icon(
  -> Code: icon: Icon(
L117 |                       isMark ? Icons.bookmark : Icons.bookmark_border,
  -> Code: isMark ? Icons.bookmark : Icons.bookmark_border,
L118 |                       color: isMark ? Colors.brown : null,
  -> Code: color: isMark ? Colors.brown : null,
L119 |                     ),
  -> Code: ),
L120 |                     onPressed: () => context.read<PostCubit>().toggleSavePost(
  -> Code: onPressed: () => context.read<PostCubit>().toggleSavePost(
L121 |                       post.id,
  -> Code: post.id,
L122 |                       currentUid,
  -> Code: currentUid,
L123 |                     ),
  -> Code: ),
L124 |                   ),
  -> Code: ),
L125 |                 ],
  -> Code: ],
L126 |               ),
  -> Code: ),
L127 |             ),
  -> Code: ),
L128 |
  -> Blank line
L129 |
  -> Blank line
L130 |             if (post.caption.isNotEmpty)
  -> Control flow statement: if (post.caption.isNotEmpty)
L131 |               Padding(
  -> Code: Padding(
L132 |                 padding: const EdgeInsets.symmetric(
  -> Code: padding: const EdgeInsets.symmetric(
L133 |                   horizontal: 12.0,
  -> Code: horizontal: 12.0,
L134 |                   vertical: 4,
  -> Code: vertical: 4,
L135 |                 ),
  -> Code: ),
L136 |                 child: Text(post.caption),
  -> Code: child: Text(post.caption),
L137 |               ),
  -> Code: ),
L138 |           ],
  -> Code: ],
L139 |         ),
  -> Code: ),
L140 |       );
  -> Code: );
L141 |     }
  -> Code: }
L142 | }
  -> Code: }
```

lib/features/posts/presentation/pages/comments_page.dart

```
L001 | import 'package:cloud_firestore/cloud_firestore.dart';
  -> Imports module or package: import 'package:cloud_firestore/cloud_firestore.dart';
L002 | import 'package:firebase_auth/firebase_auth.dart';
  -> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';
L003 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L004 |
  -> Blank line
L005 | class CommentsPage extends StatefulWidget {
  -> Class declaration: class CommentsPage extends StatefulWidget {
L006 |   final String postId;
  -> Variable declaration: final String postId;
L007 |   final String currentUserId;
  -> Variable declaration: final String currentUserId;
L008 |
  -> Blank line
L009 |   const CommentsPage({
  -> Variable declaration: const CommentsPage({
L010 |     super.key,
  -> Code: super.key,
L011 |     required this.postId,
  -> Code: required this.postId,
L012 |     required this.currentUserId,
  -> Code: required this.currentUserId,
L013 |   });
  -> Code: });
L014 |
  -> Blank line
L015 |   @override
  -> Annotation/Decorator: @override
L016 |   State<CommentsPage> createState() => _CommentsPageState();
  -> Short arrow function/expression: State<CommentsPage> createState() => _CommentsPageState();
L017 | }
  -> Code: }
L018 |
  -> Blank line
L019 | class _CommentsPageState extends State<CommentsPage> {
  -> Class declaration: class _CommentsPageState extends State<CommentsPage> {
L020 |   final _controller = TextEditingController();
  -> Variable declaration: final _controller = TextEditingController();
L021 |   final _firestore = FirebaseFirestore.instance;
  -> Variable declaration: final _firestore = FirebaseFirestore.instance;
L022 |   final _scrollController = ScrollController();
  -> Variable declaration: final _scrollController = ScrollController();
L023 |
  -> Blank line
L024 |   Future<void> _sendComment() async {
  -> Function/method declaration or async return type: Future<void> _sendComment() async {
L025 |     final text = _controller.text.trim();
  -> Variable declaration: final text = _controller.text.trim();
L026 |     if (text.isEmpty) return;
  -> Control flow statement: if (text.isEmpty) return;
L027 |
  -> Blank line
L028 |     final currentUser = FirebaseAuth.instance.currentUser;
  -> Variable declaration: final currentUser = FirebaseAuth.instance.currentUser;
L029 |     if (currentUser == null) return;
  -> Control flow statement: if (currentUser == null) return;
L030 |
  -> Blank line
L031 |     final userDoc = await _firestore
  -> Variable declaration: final userDoc = await _firestore
L032 |         .collection('users')
  -> Code: .collection('users')
L033 |         .doc(currentUser.uid)
  -> Code: .doc(currentUser.uid)
L034 |         .get();
  -> Code: .get();
```

```
L035 |     final userData = userDoc.data() ?? {};
  -> Variable declaration: final userData = userDoc.data() ?? {};
L036 |
  -> Blank line
L037 |     await _firestore
  -> Code: await _firestore
L038 |         .collection('posts')
  -> Code: .collection('posts')
L039 |         .doc(widget.postId)
  -> Code: .doc(widget.postId)
L040 |         .collection('comments')
  -> Code: .collection('comments')
L041 |         .add({
  -> Code: .add({
L042 |           'text': text,
  -> Code: 'text': text,
L043 |           'userId': currentUser.uid,
  -> Code: 'userId': currentUser.uid,
L044 |           'userName': userData['name'] ?? 'Unknown User',
  -> Code: 'userName': userData['name'] ?? 'Unknown User',
L045 |           'photoUrl': userData['profileImg'] ?? '',
  -> Code: 'photoUrl': userData['profileImg'] ?? '',
L046 |           'createdAt': FieldValue.serverTimestamp(),
  -> Code: 'createdAt': FieldValue.serverTimestamp(),
L047 |         });
  -> Code: });
L048 |
  -> Blank line
L049 |     _controller.clear();
  -> Code: _controller.clear();
L050 |
  -> Blank line
L051 |     // Auto-scroll to the latest comment
  -> Comment:  Auto-scroll to the latest comment
L052 |     Future.delayed(const Duration(milliseconds: 300), () {
  -> Function/method declaration or async return type: Future.delayed(const Duration(milliseconds: 300), () {
L053 |       if (_scrollController.hasClients) {
  -> Control flow statement: if (_scrollController.hasClients) {
L054 |         _scrollController.animateTo(
  -> Code: _scrollController.animateTo(
L055 |           0.0,
  -> Code: 0.0,
L056 |           duration: const Duration(milliseconds: 400),
  -> Code: duration: const Duration(milliseconds: 400),
L057 |           curve: Curves.easeOut,
  -> Code: curve: Curves.easeOut,
L058 |         );
  -> Code: );
L059 |       }
  -> Code: }
L060 |     });
  -> Code: });
L061 |   }
  -> Code: }
L062 |
  -> Blank line
L063 |   @override
  -> Annotation/Decorator: @override
L064 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L065 |     return Scaffold(
  -> Return statement: return Scaffold(
L066 |       appBar: AppBar(title: const Text('Comments')),
  -> Flutter UI widget usage: appBar: AppBar(title: const Text('Comments')),
L067 |       body: Column(
  -> Code: body: Column(
L068 |         children: [
  -> Code: children: [
L069 |           Expanded(
  -> Code: Expanded(
L070 |             child: StreamBuilder<QuerySnapshot>(
  -> Code: child: StreamBuilder<QuerySnapshot>(
```

```
L071 |               stream: _firestore
  -> Code: stream: _firestore
L072 |                   .collection('posts')
  -> Code: .collection('posts')
L073 |                   .doc(widget.postId)
  -> Code: .doc(widget.postId)
L074 |                   .collection('comments')
  -> Code: .collection('comments')
L075 |                   .orderBy('createdAt', descending: true)
  -> Code: .orderBy('createdAt', descending: true)
L076 |                   .snapshots(),
  -> Code: .snapshots(),
L077 |               builder: (context, snapshot) {
  -> Code: builder: (context, snapshot) {
L078 |                 if (snapshot.connectionState == ConnectionState.waiting) {
  -> Control flow statement: if (snapshot.connectionState == ConnectionState.waiting) {
L079 |                   return const Center(child: CircularProgressIndicator());
  -> Return statement: return const Center(child: CircularProgressIndicator());
L080 |                 }
  -> Code: }
L081 |
  -> Blank line
L082 |                 final comments = snapshot.data?.docs ?? [];
  -> Variable declaration: final comments = snapshot.data?.docs ?? [];
L083 |
  -> Blank line
L084 |                 if (comments.isEmpty) {
  -> Control flow statement: if (comments.isEmpty) {
L085 |                   return const Center(child: Text('No comments yet'));
  -> Return statement: return const Center(child: Text('No comments yet'));
L086 |                 }
  -> Code: }
L087 |
  -> Blank line
L088 |                 return ListView.builder(
  -> Return statement: return ListView.builder(
L089 |                   controller: _scrollController,
  -> Code: controller: _scrollController,
L090 |                   reverse: true,
  -> Code: reverse: true,
L091 |                   itemCount: comments.length,
  -> Code: itemCount: comments.length,
L092 |                   itemBuilder: (context, i) {
  -> Code: itemBuilder: (context, i) {
L093 |                     final c = comments[i].data() as Map<String, dynamic>;
  -> Variable declaration: final c = comments[i].data() as Map<String, dynamic>;
L094 |                     final name = c['userName'] ?? 'Unknown User';
  -> Variable declaration: final name = c['userName'] ?? 'Unknown User';
L095 |                     final text = c['text'] ?? '';
  -> Variable declaration: final text = c['text'] ?? '';
L096 |                     final photoUrl =
  -> Variable declaration: final photoUrl =
L097 |                         c['photoUrl'] ??
  -> Code: c['photoUrl'] ??
L098 |                         'https://cdn-icons-png.flaticon.com/512/149/149071.png';
  -> Code: 'https://cdn-icons-png.flaticon.com/512/149/149071.png';
L099 |
  -> Blank line
L100 |                     return ListTile(
  -> Return statement: return ListTile(
L101 |                       leading: CircleAvatar(
  -> Code: leading: CircleAvatar(
L102 |                         backgroundImage: NetworkImage(photoUrl),
  -> Code: backgroundImage: NetworkImage(photoUrl),
L103 |                       ),
  -> Code: ),
L104 |                       title: Text(name),
  -> Code: title: Text(name),
L105 |                       subtitle: Text(text),
  -> Code: subtitle: Text(text),
L106 |                     );
  -> Code: );
```

```
L107 |                   },
  -> Code: },
L108 |                 );
  -> Code: );
L109 |               },
  -> Code: },
L110 |             ),
  -> Code: ),
L111 |           ),
  -> Code: ),
L112 |           const Divider(height: 1),
  -> Variable declaration: const Divider(height: 1),
L113 |           Padding(
  -> Code: Padding(
L114 |             padding: const EdgeInsets.symmetric(horizontal: 8.0, vertical: 6.0),
  -> Code: padding: const EdgeInsets.symmetric(horizontal: 8.0, vertical: 6.0),
L115 |             child: Row(
  -> Code: child: Row(
L116 |               children: [
  -> Code: children: [
L117 |                 Expanded(
  -> Code: Expanded(
L118 |                   child: TextField(
  -> Code: child: TextField(
L119 |                     controller: _controller,
  -> Code: controller: _controller,
L120 |                     decoration: const InputDecoration(
  -> Code: decoration: const InputDecoration(
L121 |                       hintText: 'Add a comment...',
  -> Code: hintText: 'Add a comment...',
L122 |                       border: OutlineInputBorder(),
  -> Code: border: OutlineInputBorder(),
L123 |                     ),
  -> Code: ),
L124 |                   ),
  -> Code: ),
L125 |                 ),
  -> Code: ),
L126 |                 IconButton(
  -> Code: IconButton(
L127 |                   icon: const Icon(Icons.send, color: Colors.brown),
  -> Code: icon: const Icon(Icons.send, color: Colors.brown),
L128 |                   onPressed: _sendComment,
  -> Code: onPressed: _sendComment,
L129 |                 ),
  -> Code: ),
L130 |               ],
  -> Code: ],
L131 |             ),
  -> Code: ),
L132 |           ),
  -> Code: ),
L133 |         ],
  -> Code: ],
L134 |       ),
  -> Code: ),
L135 |     );
  -> Code: );
L136 |   }
  -> Code: }
L137 | }
  -> Code: }
```

lib/features/posts/presentation/pages/create_post_page.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:image_picker/image_picker.dart';
```
-> Imports module or package: import 'package:image_picker/image_picker.dart';

```
L005 | import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/appwrite_storage_post_repo.dart';

```
L006 | import 'package:instproject/features/posts/data/fire_post_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/fire_post_repo.dart';

```
L007 | import 'package:instproject/main_shell.dart';
```
-> Imports module or package: import 'package:instproject/main_shell.dart';

```
L008 | import '../../presentation/bloc/post_cubit.dart';
```
-> Imports module or package: import '../../presentation/bloc/post_cubit.dart';

```
L009 | import '../../presentation/bloc/post_states.dart';
```
-> Imports module or package: import '../../presentation/bloc/post_states.dart';

```
L010 |
```
-> Blank line

```
L011 | class CreatePostPage extends StatefulWidget {
```
-> Class declaration: class CreatePostPage extends StatefulWidget {

```
L012 |   final String userId;
```
-> Variable declaration: final String userId;

```
L013 |   final String? userName;
```
-> Variable declaration: final String? userName;

```
L014 |   final String? userProfileImage;
```
-> Variable declaration: final String? userProfileImage;

```
L015 |
```
-> Blank line

```
L016 |   const CreatePostPage({
```
-> Variable declaration: const CreatePostPage({

```
L017 |     super.key,
```
-> Code: super.key,

```
L018 |     required this.userId,
```
-> Code: required this.userId,

```
L019 |     this.userName,
```
-> Code: this.userName,

```
L020 |     this.userProfileImage,
```
-> Code: this.userProfileImage,

```
L021 |   });
```
-> Code: });

```
L022 |
```
-> Blank line

```
L023 |   @override
```
-> Annotation/Decorator: @override

```
L024 |   State<CreatePostPage> createState() => _CreatePostPageState();
```
-> Short arrow function/expression: State<CreatePostPage> createState() => _CreatePostPageState();

```
L025 | }
```
-> Code: }

```
L026 |
```
-> Blank line

```
L027 | class _CreatePostPageState extends State<CreatePostPage> {
```
-> Class declaration: class _CreatePostPageState extends State<CreatePostPage> {

```
L028 |   final captionController = TextEditingController();
```
-> Variable declaration: final captionController = TextEditingController();

```
L029 |   String? _imagePath;
```
-> Code: String? _imagePath;

```
L030 |   bool isUploading = false;
```
-> Code: bool isUploading = false;

```
L031 |
```
-> Blank line

```
L032 |   Future<void> pickImage() async {
```
-> Function/method declaration or async return type: Future<void> pickImage() async {

```
L033 |     final picker = ImagePicker();
```
-> Variable declaration: final picker = ImagePicker();

```
L034 |     final picked = await picker.pickImage(source: ImageSource.gallery);
```
-> Variable declaration: final picked = await picker.pickImage(source: ImageSource.gallery);

```
L035 |     if (picked != null) {
```
-> Control flow statement: if (picked != null) {

```
L036 |       setState(() => _imagePath = picked.path);
```
-> Short arrow function/expression: setState(() => _imagePath = picked.path);

```
L037 |     }
```
-> Code: }

```
L038 |   }
```
-> Code: }

```
L039 |
```
-> Blank line

```
L040 |   @override
```
-> Annotation/Decorator: @override

```
L041 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L042 |     return BlocProvider(
```
-> Return statement: return BlocProvider(

```
L043 |       create: (_) => PostCubit(
```
-> Code: create: (_) => PostCubit(

```
L044 |         postRepo: FirePostRepo(),
```
-> Code: postRepo: FirePostRepo(),

```
L045 |         storageRepo: AppwritePostStorageRepo(),
```
-> Code: storageRepo: AppwritePostStorageRepo(),

```
L046 |       ),
```
-> Code:),

```
L047 |       child: BlocConsumer<PostCubit, PostStates>(
```
-> Code: child: BlocConsumer<PostCubit, PostStates>(

```
L048 |         listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L049 |           if (state is PostLoaded) {
```
-> Control flow statement: if (state is PostLoaded) {

```
L050 |
```
-> Blank line

```
L051 |             ScaffoldMessenger.of(context).showSnackBar(
```
-> Code: ScaffoldMessenger.of(context).showSnackBar(

```
L052 |               const SnackBar(content: Text('Post uploaded successfully!')),
```
-> Variable declaration: const SnackBar(content: Text('Post uploaded successfully!')),

```
L053 |             );
```
-> Code:);

```
L054 |
```
-> Blank line

```
L055 |
```
-> Blank line

```
L056 |             Future.delayed(const Duration(milliseconds: 600), () {
```
-> Function/method declaration or async return type: Future.delayed(const Duration(milliseconds: 600), () {

```
L057 |               if (mounted)
```
-> Control flow statement: if (mounted)

```
L058 |                 Navigator.push(
```
-> Code: Navigator.push(

```
L059 |                   context,
```
-> Code: context,

```
L060 |                   MaterialPageRoute(
```
-> Code: MaterialPageRoute(

```
L061 |                     builder: (_) => MainShell(
```
-> Code: builder: (_) => MainShell(

```
L062 |
```
-> Blank line

```
L063 |
```
-> Blank line

```
L064 |                   ),
```
-> Code:),

```
L065 |                 ),
```
-> Code:),

```
L066 |               );
```
-> Code:);

```
L067 |             });
```
-> Code: });

```
L068 |           } else if (state is PostError) {
```
-> Code: } else if (state is PostError) {

```
L069 |             ScaffoldMessenger.of(
```
-> Code: ScaffoldMessenger.of(

```
L070 |               context,
```
-> Code: context,

```
L071 |             ).showSnackBar(SnackBar(content: Text(state.message)));
  -> Code: ).showSnackBar(SnackBar(content: Text(state.message)));
L072 |             setState(() => isUploading = false);
  -> Short arrow function/expression: setState(() => isUploading = false);
L073 |           }
  -> Code: }
L074 |         },
  -> Code: },
L075 |         builder: (context, state) {
  -> Code: builder: (context, state) {
L076 |           return Scaffold(
  -> Return statement: return Scaffold(
L077 |             backgroundColor: Colors.black,
  -> Code: backgroundColor: Colors.black,
L078 |             appBar: AppBar(
  -> Flutter UI widget usage: appBar: AppBar(
L079 |               title: const Text('Create Post'),
  -> Code: title: const Text('Create Post'),
L080 |               backgroundColor: Colors.brown.shade800,
  -> Code: backgroundColor: Colors.brown.shade800,
L081 |               elevation: 0,
  -> Code: elevation: 0,
L082 |               actions: [
  -> Code: actions: [
L083 |                 IconButton(
  -> Code: IconButton(
L084 |                   icon: const Icon(Icons.close),
  -> Code: icon: const Icon(Icons.close),
L085 |                   onPressed: () => Navigator.pop(context),
  -> Code: onPressed: () => Navigator.pop(context),
L086 |                 ),
  -> Code: ),
L087 |               ],
  -> Code: ],
L088 |             ),
  -> Code: ),
L089 |             body: SingleChildScrollView(
  -> Code: body: SingleChildScrollView(
L090 |               padding: const EdgeInsets.all(16),
  -> Code: padding: const EdgeInsets.all(16),
L091 |               child: Column(
  -> Code: child: Column(
L092 |                 crossAxisAlignment: CrossAxisAlignment.center,
  -> Code: crossAxisAlignment: CrossAxisAlignment.center,
L093 |                 children: [
  -> Code: children: [
L094 |                   // 🖼 Image picker
  -> Comment: 🖼 Image picker
L095 |                   GestureDetector(
  -> Code: GestureDetector(
L096 |                     onTap: pickImage,
  -> Code: onTap: pickImage,
L097 |                     child: _imagePath != null
  -> Code: child: _imagePath != null
L098 |                         ? ClipRRect(
  -> Code: ? ClipRRect(
L099 |                             borderRadius: BorderRadius.circular(16),
  -> Code: borderRadius: BorderRadius.circular(16),
L100 |                             child: Image.file(
  -> Code: child: Image.file(
L101 |                               File(_imagePath!),
  -> Code: File(_imagePath!),
L102 |                               height: 250,
  -> Code: height: 250,
L103 |                               width: double.infinity,
  -> Code: width: double.infinity,
L104 |                               fit: BoxFit.cover,
  -> Code: fit: BoxFit.cover,
L105 |                             ),
  -> Code: ),
L106 |                         )
  -> Code: )
```

```
L107 |                           : Container(
  -> Code: : Container(
L108 |                               height: 250,
  -> Code: height: 250,
L109 |                               width: double.infinity,
  -> Code: width: double.infinity,
L110 |                               decoration: BoxDecoration(
  -> Code: decoration: BoxDecoration(
L111 |                                 color: Colors.brown.shade800.withOpacity(0.3),
  -> Code: color: Colors.brown.shade800.withOpacity(0.3),
L112 |                                 borderRadius: BorderRadius.circular(16),
  -> Code: borderRadius: BorderRadius.circular(16),
L113 |                                 border: Border.all(
  -> Code: border: Border.all(
L114 |                                   color: Colors.brown.shade700,
  -> Code: color: Colors.brown.shade700,
L115 |                                   width: 1,
  -> Code: width: 1,
L116 |                                 ),
  -> Code: ),
L117 |                               ),
  -> Code: ),
L118 |                               child: const Center(
  -> Code: child: const Center(
L119 |                                 child: Column(
  -> Code: child: Column(
L120 |                                   mainAxisAlignment: MainAxisAlignment.center,
  -> Code: mainAxisAlignment: MainAxisAlignment.center,
L121 |                                   children: [
  -> Code: children: [
L122 |                                     Icon(
  -> Code: Icon(
L123 |                                       Icons.add_a_photo,
  -> Code: Icons.add_a_photo,
L124 |                                       color: Colors.white70,
  -> Code: color: Colors.white70,
L125 |                                       size: 40,
  -> Code: size: 40,
L126 |                                     ),
  -> Code: ),
L127 |                                     SizedBox(height: 8),
  -> Code: SizedBox(height: 8),
L128 |                                     Text(
  -> Code: Text(
L129 |                                       'Tap to select an image',
  -> Code: 'Tap to select an image',
L130 |                                       style: TextStyle(
  -> Code: style: TextStyle(
L131 |                                         color: Colors.white70,
  -> Code: color: Colors.white70,
L132 |                                         fontSize: 16,
  -> Code: fontSize: 16,
L133 |                                       ),
  -> Code: ),
L134 |                                     ),
  -> Code: ),
L135 |                                   ],
  -> Code: ],
L136 |                                 ),
  -> Code: ),
L137 |                               ),
  -> Code: ),
L138 |                           ),
  -> Code: ),
L139 |                     ),
  -> Code: ),
L140 |
  -> Blank line
L141 |                     const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L142 |
  -> Blank line
```

```
L143 |                     TextField(
  -> Code: TextField(
L144 |                       controller: captionController,
  -> Code: controller: captionController,
L145 |                       maxLines: 3,
  -> Code: maxLines: 3,
L146 |                       style: const TextStyle(color: Colors.white),
  -> Code: style: const TextStyle(color: Colors.white),
L147 |                       decoration: InputDecoration(
  -> Code: decoration: InputDecoration(
L148 |                         labelText: 'Write a caption...',
  -> Code: labelText: 'Write a caption...',
L149 |                         labelStyle: TextStyle(
  -> Code: labelStyle: TextStyle(
L150 |                           color: Colors.white.withOpacity(0.8),
  -> Code: color: Colors.white.withOpacity(0.8),
L151 |                         ),
  -> Code: ),
L152 |                         filled: true,
  -> Code: filled: true,
L153 |                         fillColor: Colors.brown.shade700.withOpacity(0.3),
  -> Code: fillColor: Colors.brown.shade700.withOpacity(0.3),
L154 |                         border: OutlineInputBorder(
  -> Code: border: OutlineInputBorder(
L155 |                           borderRadius: BorderRadius.circular(16),
  -> Code: borderRadius: BorderRadius.circular(16),
L156 |                           borderSide: BorderSide.none,
  -> Code: borderSide: BorderSide.none,
L157 |                         ),
  -> Code: ),
L158 |                       ),
  -> Code: ),
L159 |                     ),
  -> Code: ),
L160 |
  -> Blank line
L161 |                     const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L162 |
  -> Blank line
L163 |                     SizedBox(
  -> Code: SizedBox(
L164 |                       width: double.infinity,
  -> Code: width: double.infinity,
L165 |                       child: ElevatedButton.icon(
  -> Code: child: ElevatedButton.icon(
L166 |                         onPressed: (state is PostLoading || _imagePath == null)
  -> Code: onPressed: (state is PostLoading || _imagePath == null)
L167 |                             ? null
  -> Code: ? null
L168 |                             : () {
  -> Code: : () {
L169 |                                 setState(() => isUploading = true);
  -> Short arrow function/expression: setState(() => isUploading = true);
L170 |                                 context.read<PostCubit>().createPost(
  -> Code: context.read<PostCubit>().createPost(
L171 |                                   userId: widget.userId,
  -> Code: userId: widget.userId,
L172 |                                   caption: captionController.text.trim(),
  -> Code: caption: captionController.text.trim(),
L173 |                                   imagePath: _imagePath!,
  -> Code: imagePath: _imagePath!,
L174 |                                 );
  -> Code: );
L175 |                               },
  -> Code: },
L176 |                         icon: isUploading
  -> Code: icon: isUploading
L177 |                             ? const SizedBox(
  -> Code: ? const SizedBox(
L178 |                                 width: 20,
  -> Code: width: 20,
```

```
L179 |                                 height: 20,
  -> Code: height: 20,
L180 |                                 child: CircularProgressIndicator(
  -> Code: child: CircularProgressIndicator(
L181 |                                   strokeWidth: 2,
  -> Code: strokeWidth: 2,
L182 |                                   color: Colors.white,
  -> Code: color: Colors.white,
L183 |                                 ),
  -> Code: ),
L184 |                               )
  -> Code: )
L185 |                             : const Icon(Icons.cloud_upload),
  -> Code: : const Icon(Icons.cloud_upload),
L186 |                         label: Text(
  -> Code: label: Text(
L187 |                           state is PostLoading ? 'Uploading...' : 'Share Post',
  -> Code: state is PostLoading ? 'Uploading...' : 'Share Post',
L188 |                           style: const TextStyle(fontSize: 16),
  -> Code: style: const TextStyle(fontSize: 16),
L189 |                         ),
  -> Code: ),
L190 |                         style: ElevatedButton.styleFrom(
  -> Code: style: ElevatedButton.styleFrom(
L191 |                           backgroundColor: Colors.brown.shade800,
  -> Code: backgroundColor: Colors.brown.shade800,
L192 |                           foregroundColor: Colors.white,
  -> Code: foregroundColor: Colors.white,
L193 |                           padding: const EdgeInsets.symmetric(vertical: 14),
  -> Code: padding: const EdgeInsets.symmetric(vertical: 14),
L194 |                           shape: RoundedRectangleBorder(
  -> Code: shape: RoundedRectangleBorder(
L195 |                             borderRadius: BorderRadius.circular(16),
  -> Code: borderRadius: BorderRadius.circular(16),
L196 |                           ),
  -> Code: ),
L197 |                         ),
  -> Code: ),
L198 |                       ),
  -> Code: ),
L199 |                     ),
  -> Code: ),
L200 |                   ],
  -> Code: ],
L201 |                 ),
  -> Code: ),
L202 |               ),
  -> Code: ),
L203 |             );
  -> Code: );
L204 |           },
  -> Code: },
L205 |         ),
  -> Code: ),
L206 |       );
  -> Code: );
L207 |     }
  -> Code: }
L208 | }
  -> Code: }
```

lib/features/posts/presentation/pages/feed_page.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L003 | import 'package:instproject/features/aistudy/ai_study_page.dart';
  -> Imports module or package: import 'package:instproject/features/aistudy/ai_study_page.dart';
L004 | import 'package:instproject/features/auth/presentation/components/my_drawer.dart';
  -> Imports module or package: import 'package:instproject/features/auth/presentation/components/my_drawer.dart';
L005 | import 'package:instproject/features/posts/data/post_model.dart';
  -> Imports module or package: import 'package:instproject/features/posts/data/post_model.dart';
L006 | import 'package:instproject/features/posts/domain/post_repo.dart';
  -> Imports module or package: import 'package:instproject/features/posts/domain/post_repo.dart';
L007 | import 'package:instproject/features/storage/domain/storage_repo.dart';
  -> Imports module or package: import 'package:instproject/features/storage/domain/storage_repo.dart';
L008 | import '../bloc/post_cubit.dart';
  -> Imports module or package: import '../bloc/post_cubit.dart';
L009 | import '../components/post_tile.dart';
  -> Imports module or package: import '../components/post_tile.dart';
L010 |
  -> Blank line
L011 | class FeedPage extends StatefulWidget {
  -> Class declaration: class FeedPage extends StatefulWidget {
L012 |   final String userId;
  -> Variable declaration: final String userId;
L013 |   const FeedPage({super.key, required this.userId});
  -> Variable declaration: const FeedPage({super.key, required this.userId});
L014 |
  -> Blank line
L015 |   @override
  -> Annotation/Decorator: @override
L016 |   State<FeedPage> createState() => _FeedPageState();
  -> Short arrow function/expression: State<FeedPage> createState() => _FeedPageState();
L017 | }
  -> Code: }
L018 |
  -> Blank line
L019 | class _FeedPageState extends State<FeedPage> {
  -> Class declaration: class _FeedPageState extends State<FeedPage> {
L020 |   @override
  -> Annotation/Decorator: @override
L021 |   void initState() {
  -> Function/method declaration or async return type: void initState() {
L022 |     super.initState();
  -> Code: super.initState();
L023 |     context.read<PostCubit>().fetchAllPosts();
  -> Code: context.read<PostCubit>().fetchAllPosts();
L024 |   }
  -> Code: }
L025 |
  -> Blank line
L026 |   @override
  -> Annotation/Decorator: @override
L027 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L028 |     final postRepo = RepositoryProvider.of<PostRepo>(context);
  -> Variable declaration: final postRepo = RepositoryProvider.of<PostRepo>(context);
L029 |     final storageRepo = RepositoryProvider.of<StorageRepo>(context);
  -> Variable declaration: final storageRepo = RepositoryProvider.of<StorageRepo>(context);
L030 |
  -> Blank line
L031 |     return Scaffold(
  -> Return statement: return Scaffold(
L032 |       appBar: AppBar(
  -> Flutter UI widget usage: appBar: AppBar(
L033 |         title: Image.asset('images/sg.png', width: 100, height: 100),
  -> Code: title: Image.asset('images/sg.png', width: 100, height: 100),
L034 |         centerTitle: true,
  -> Code: centerTitle: true,
```

```
L035 |       ),
```
-> Code:),

```
L036 |       drawer: MyDrawer(),
```
-> Code: drawer: MyDrawer(),

```
L037 |
```
-> Blank line

```
L038 |       floatingActionButton: Padding(
```
-> Code: floatingActionButton: Padding(

```
L039 |         padding: const EdgeInsets.only(bottom: 70.0, right: 8.0),
```
-> Code: padding: const EdgeInsets.only(bottom: 70.0, right: 8.0),

```
L040 |         child: SizedBox(
```
-> Code: child: SizedBox(

```
L041 |           height: 60,
```
-> Code: height: 60,

```
L042 |           width: 60,
```
-> Code: width: 60,

```
L043 |           child: FloatingActionButton(
```
-> Code: child: FloatingActionButton(

```
L044 |             heroTag: null,
```
-> Code: heroTag: null,

```
L045 |             backgroundColor: Theme.of(context).colorScheme.primary,
```
-> Code: backgroundColor: Theme.of(context).colorScheme.primary,

```
L046 |             onPressed: () {
```
-> Code: onPressed: () {

```
L047 |               Navigator.push(
```
-> Code: Navigator.push(

```
L048 |                 context,
```
-> Code: context,

```
L049 |                 MaterialPageRoute(builder: (_) => const AiStudy()),
```
-> Code: MaterialPageRoute(builder: (_) => const AiStudy()),

```
L050 |               );
```
-> Code:);

```
L051 |             },
```
-> Code: },

```
L052 |             child: ClipOval(
```
-> Code: child: ClipOval(

```
L053 |               child: Image.asset('images/sai.png', fit: BoxFit.contain),
```
-> Code: child: Image.asset('images/sai.png', fit: BoxFit.contain),

```
L054 |             ),
```
-> Code:),

```
L055 |           ),
```
-> Code:),

```
L056 |         ),
```
-> Code:),

```
L057 |       ),
```
-> Code:),

```
L058 |       floatingActionButtonLocation: FloatingActionButtonLocation.endFloat,
```
-> Code: floatingActionButtonLocation: FloatingActionButtonLocation.endFloat,

```
L059 |
```
-> Blank line

```
L060 |       body: RefreshIndicator(
```
-> Code: body: RefreshIndicator(

```
L061 |         onRefresh: () async {
```
-> Code: onRefresh: () async {

```
L062 |           await context.read<PostCubit>().fetchAllPosts();
```
-> Code: await context.read<PostCubit>().fetchAllPosts();

```
L063 |         },
```
-> Code: },

```
L064 |         child: SingleChildScrollView(
```
-> Code: child: SingleChildScrollView(

```
L065 |           physics: const AlwaysScrollableScrollPhysics(),
```
-> Code: physics: const AlwaysScrollableScrollPhysics(),

```
L066 |           child: Column(
```
-> Code: child: Column(

```
L067 |             crossAxisAlignment: CrossAxisAlignment.start,
```
-> Code: crossAxisAlignment: CrossAxisAlignment.start,

```
L068 |             children: [
```
-> Code: children: [

```
L069 |
```
-> Blank line

```
L070 |               const Divider(height: 1),
```
-> Variable declaration: const Divider(height: 1),

```
L071 |
```
-> Blank line

```
L072 |                StreamBuilder<List<Post>>(
```
-> Function/method declaration or async return type: StreamBuilder<List<Post>>(

```
L073 |                  stream: postRepo.streamAllPosts(),
```
-> Code: stream: postRepo.streamAllPosts(),

```
L074 |                  builder: (context, snapshot) {
```
-> Code: builder: (context, snapshot) {

```
L075 |                    if (snapshot.connectionState == ConnectionState.waiting) {
```
-> Control flow statement: if (snapshot.connectionState == ConnectionState.waiting) {

```
L076 |                      return const Padding(
```
-> Return statement: return const Padding(

```
L077 |                        padding: EdgeInsets.all(16.0),
```
-> Code: padding: EdgeInsets.all(16.0),

```
L078 |                        child: Center(child: CircularProgressIndicator()),
```
-> Code: child: Center(child: CircularProgressIndicator()),

```
L079 |                      );
```
-> Code:);

```
L080 |                    }
```
-> Code: }

```
L081 |
```
-> Blank line

```
L082 |                    if (snapshot.hasError) {
```
-> Control flow statement: if (snapshot.hasError) {

```
L083 |                      return Padding(
```
-> Return statement: return Padding(

```
L084 |                        padding: const EdgeInsets.all(16.0),
```
-> Code: padding: const EdgeInsets.all(16.0),

```
L085 |                        child: Text('Error: ${snapshot.error}'),
```
-> Code: child: Text('Error: ${snapshot.error}'),

```
L086 |                      );
```
-> Code:);

```
L087 |                    }
```
-> Code: }

```
L088 |
```
-> Blank line

```
L089 |                    final posts = snapshot.data ?? [];
```
-> Variable declaration: final posts = snapshot.data ?? [];

```
L090 |
```
-> Blank line

```
L091 |                    if (posts.isEmpty) {
```
-> Control flow statement: if (posts.isEmpty) {

```
L092 |                      return const Padding(
```
-> Return statement: return const Padding(

```
L093 |                        padding: EdgeInsets.all(16.0),
```
-> Code: padding: EdgeInsets.all(16.0),

```
L094 |                        child: Center(child: Text('No posts yet.')),
```
-> Code: child: Center(child: Text('No posts yet.')),

```
L095 |                      );
```
-> Code:);

```
L096 |                    }
```
-> Code: }

```
L097 |
```
-> Blank line

```
L098 |
```
-> Blank line

```
L099 |                    return ListView.builder(
```
-> Return statement: return ListView.builder(

```
L100 |                      itemCount: posts.length,
```
-> Code: itemCount: posts.length,

```
L101 |                      shrinkWrap: true,
```
-> Code: shrinkWrap: true,

```
L102 |                      physics: const NeverScrollableScrollPhysics(),
```
-> Code: physics: const NeverScrollableScrollPhysics(),

```
L103 |                      itemBuilder: (context, index) {
```
-> Code: itemBuilder: (context, index) {

```
L104 |                        final post = posts[index];
```
-> Variable declaration: final post = posts[index];

```
L105 |                        return PostTile(post: post);
```
-> Return statement: return PostTile(post: post);

```
L106 |                      },
```
-> Code: },

```
L107 |                     );
```
-> Code:);

```
L108 |                   },
```
-> Code: },

```
L109 |                 ),
```
-> Code:),

```
L110 |               ],
```
-> Code:],

```
L111 |             ),
```
-> Code:),

```
L112 |           ),
```
-> Code:),

```
L113 |         ),
```
-> Code:),

```
L114 |       );
```
-> Code:);

```
L115 |     }
```
-> Code: }

```
L116 | }
```
-> Code: }

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 | import 'package:firebase_auth/firebase_auth.dart';
  -> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L004 | import 'package:instproject/features/posts/data/post_model.dart';
  -> Imports module or package: import 'package:instproject/features/posts/data/post_model.dart';
L005 | import 'package:instproject/features/posts/domain/post_repo.dart';
  -> Imports module or package: import 'package:instproject/features/posts/domain/post_repo.dart';
L006 | import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';
  -> Imports module or package: import 'package:instproject/features/storage/domain/appwrite_storage_repo.dart';
L007 |
  -> Blank line
L008 | class PostDetailPage extends StatelessWidget {
  -> Class declaration: class PostDetailPage extends StatelessWidget {
L009 |   final Post post;
  -> Variable declaration: final Post post;
L010 |
  -> Blank line
L011 |   const PostDetailPage({super.key, required this.post});
  -> Variable declaration: const PostDetailPage({super.key, required this.post});
L012 |
  -> Blank line
L013 |   @override
  -> Annotation/Decorator: @override
L014 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L015 |     final currentUid = FirebaseAuth.instance.currentUser?.uid;
  -> Variable declaration: final currentUid = FirebaseAuth.instance.currentUser?.uid;
L016 |     final isOwner = post.userId == currentUid;
  -> Variable declaration: final isOwner = post.userId == currentUid;
L017 |
  -> Blank line
L018 |     return Scaffold(
  -> Return statement: return Scaffold(
L019 |       appBar: AppBar(
  -> Flutter UI widget usage: appBar: AppBar(
L020 |         title: Text(post.userName ?? 'Post'),
  -> Code: title: Text(post.userName ?? 'Post'),
L021 |         actions: [
  -> Code: actions: [
L022 |           if (isOwner)
  -> Control flow statement: if (isOwner)
L023 |             IconButton(
  -> Code: IconButton(
L024 |               icon: const Icon(Icons.delete, color: Colors.redAccent),
  -> Code: icon: const Icon(Icons.delete, color: Colors.redAccent),
L025 |               onPressed: () async {
  -> Code: onPressed: () async {
L026 |                 final confirm = await showDialog<bool>(
  -> Variable declaration: final confirm = await showDialog<bool>(
L027 |                   context: context,
  -> Code: context: context,
L028 |                   builder: (_) => AlertDialog(
  -> Code: builder: (_) => AlertDialog(
L029 |                     title: const Text("Delete Post"),
  -> Code: title: const Text("Delete Post"),
L030 |                     content: const Text(
  -> Code: content: const Text(
L031 |                       "Are you sure you want to delete this post?",
  -> Code: "Are you sure you want to delete this post?",
L032 |                     ),
  -> Code: ),
L033 |                     actions: [
  -> Code: actions: [
L034 |                       TextButton(
  -> Code: TextButton(
```

```
L035 |                           onPressed: () => Navigator.pop(context, false),
  -> Code: onPressed: () => Navigator.pop(context, false),
L036 |                           child: const Text("Cancel"),
  -> Code: child: const Text("Cancel"),
L037 |                         ),
  -> Code: ),
L038 |                         ElevatedButton(
  -> Code: ElevatedButton(
L039 |                           onPressed: () => Navigator.pop(context, true),
  -> Code: onPressed: () => Navigator.pop(context, true),
L040 |                           child: const Text("Delete"),
  -> Code: child: const Text("Delete"),
L041 |                         ),
  -> Code: ),
L042 |                       ],
  -> Code: ],
L043 |                     ),
  -> Code: ),
L044 |                   );
  -> Code: );
L045 |
  -> Blank line
L046 |                   if (confirm == true) {
  -> Control flow statement: if (confirm == true) {
L047 |                     try {
  -> Code: try {
L048 |
  -> Blank line
L049 |                       await context.read<PostRepo>().deletePost(post.id);
  -> Code: await context.read<PostRepo>().deletePost(post.id);
L050 |
  -> Blank line
L051 |                       if (post.imageUrl != null && post.imageUrl!.isNotEmpty) {
  -> Control flow statement: if (post.imageUrl != null && post.imageUrl!.isNotEmpty) {
L052 |                         final storageRepo = context.read<AppwriteStorageRepo>();
  -> Variable declaration: final storageRepo = context.read<AppwriteStorageRepo>();
L053 |                         await storageRepo.deleteFileByUrl(post.imageUrl!);
  -> Code: await storageRepo.deleteFileByUrl(post.imageUrl!);
L054 |                       }
  -> Code: }
L055 |
  -> Blank line
L056 |                       if (context.mounted) {
  -> Control flow statement: if (context.mounted) {
L057 |                         Navigator.pop(context);
  -> Code: Navigator.pop(context);
L058 |                         ScaffoldMessenger.of(context).showSnackBar(
  -> Code: ScaffoldMessenger.of(context).showSnackBar(
L059 |                           const SnackBar(
  -> Variable declaration: const SnackBar(
L060 |                             content: Text('Post deleted successfully'),
  -> Code: content: Text('Post deleted successfully'),
L061 |                           ),
  -> Code: ),
L062 |                         );
  -> Code: );
L063 |                       }
  -> Code: }
L064 |                     } catch (e) {
  -> Code: } catch (e) {
L065 |                       ScaffoldMessenger.of(context).showSnackBar(
  -> Code: ScaffoldMessenger.of(context).showSnackBar(
L066 |                         SnackBar(content: Text('Failed to delete post: $e')),
  -> Code: SnackBar(content: Text('Failed to delete post: $e')),
L067 |                       );
  -> Code: );
L068 |                     }
  -> Code: }
L069 |                   }
  -> Code: }
L070 |                 },
  -> Code: },
```

```
L071 |             ),
  -> Code: ),
L072 |         ],
  -> Code: ],
L073 |       ),
  -> Code: ),
L074 |       body: SingleChildScrollView(
  -> Code: body: SingleChildScrollView(
L075 |         child: Column(
  -> Code: child: Column(
L076 |           crossAxisAlignment: CrossAxisAlignment.start,
  -> Code: crossAxisAlignment: CrossAxisAlignment.start,
L077 |           children: [
  -> Code: children: [
L078 |             if (post.imageUrl != null && post.imageUrl!.isNotEmpty)
  -> Control flow statement: if (post.imageUrl != null && post.imageUrl!.isNotEmpty)
L079 |               Image.network(post.imageUrl!, fit: BoxFit.cover),
  -> Code: Image.network(post.imageUrl!, fit: BoxFit.cover),
L080 |             Padding(
  -> Code: Padding(
L081 |               padding: const EdgeInsets.all(12.0),
  -> Code: padding: const EdgeInsets.all(12.0),
L082 |               child: Text(
  -> Code: child: Text(
L083 |                 post.caption ?? '',
  -> Code: post.caption ?? '',
L084 |                 style: const TextStyle(fontSize: 16),
  -> Code: style: const TextStyle(fontSize: 16),
L085 |               ),
  -> Code: ),
L086 |             ),
  -> Code: ),
L087 |             Padding(
  -> Code: Padding(
L088 |               padding: const EdgeInsets.all(12.0),
  -> Code: padding: const EdgeInsets.all(12.0),
L089 |               child: Text(
  -> Code: child: Text(
L090 |                 "Posted by ${post.userName ?? "User"}",
  -> Code: "Posted by ${post.userName ?? "User"}",
L091 |                 style: const TextStyle(color: Colors.grey),
  -> Code: style: const TextStyle(color: Colors.grey),
L092 |               ),
  -> Code: ),
L093 |             ),
  -> Code: ),
L094 |           ],
  -> Code: ],
L095 |         ),
  -> Code: ),
L096 |       ),
  -> Code: ),
L097 |     );
  -> Code: );
L098 |   }
  -> Code: }
L099 | }
  -> Code: }
```

lib/features/posts/presentation/pages/saved_posts_page.dart

```
L001 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
  -> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';
L003 | import '../bloc/post_cubit.dart';
  -> Imports module or package: import '../bloc/post_cubit.dart';
L004 | import '../bloc/post_states.dart';
  -> Imports module or package: import '../bloc/post_states.dart';
L005 | import '../../data/post_model.dart';
  -> Imports module or package: import '../../data/post_model.dart';
L006 | import '../components/post_tile.dart';
  -> Imports module or package: import '../components/post_tile.dart';
L007 |
  -> Blank line
L008 | class SavedPostsPage extends StatefulWidget {
  -> Class declaration: class SavedPostsPage extends StatefulWidget {
L009 |   final String userId;
  -> Variable declaration: final String userId;
L010 |   const SavedPostsPage({super.key, required this.userId});
  -> Variable declaration: const SavedPostsPage({super.key, required this.userId});
L011 |
  -> Blank line
L012 |   @override
  -> Annotation/Decorator: @override
L013 |   State<SavedPostsPage> createState() => _SavedPostsPageState();
  -> Short arrow function/expression: State<SavedPostsPage> createState() => _SavedPostsPageState();
L014 | }
  -> Code: }
L015 |
  -> Blank line
L016 | class _SavedPostsPageState extends State<SavedPostsPage> {
  -> Class declaration: class _SavedPostsPageState extends State<SavedPostsPage> {
L017 |   List<Post> savedPosts = [];
  -> Code: List<Post> savedPosts = [];
L018 |   bool _isLoading = false;
  -> Code: bool _isLoading = false;
L019 |   String? _error;
  -> Code: String? _error;
L020 |
  -> Blank line
L021 |   Future<void> loadSaved() async {
  -> Function/method declaration or async return type: Future<void> loadSaved() async {
L022 |     if (!mounted) return;
  -> Control flow statement: if (!mounted) return;
L023 |
  -> Blank line
L024 |     setState(() {
  -> Code: setState(() {
L025 |       _isLoading = true;
  -> Code: _isLoading = true;
L026 |       _error = null;
  -> Code: _error = null;
L027 |     });
  -> Code: });
L028 |
  -> Blank line
L029 |     try {
  -> Code: try {
L030 |       final cubit = context.read<PostCubit>();
  -> Variable declaration: final cubit = context.read<PostCubit>();
L031 |       final posts = await cubit.postRepo.getSavedPosts(widget.userId);
  -> Variable declaration: final posts = await cubit.postRepo.getSavedPosts(widget.userId);
L032 |
  -> Blank line
L033 |       if (!mounted) return;
  -> Control flow statement: if (!mounted) return;
L034 |
  -> Blank line
```

```
L035 |       setState(() {
```
-> Code: setState(() {

```
L036 |         savedPosts = posts;
```
-> Code: savedPosts = posts;

```
L037 |         _isLoading = false;
```
-> Code: _isLoading = false;

```
L038 |       });
```
-> Code: });

```
L039 |     } catch (e) {
```
-> Code: } catch (e) {

```
L040 |       if (!mounted) return;
```
-> Control flow statement: if (!mounted) return;

```
L041 |
```
-> Blank line

```
L042 |       setState(() {
```
-> Code: setState(() {

```
L043 |         _error = e.toString();
```
-> Code: _error = e.toString();

```
L044 |         _isLoading = false;
```
-> Code: _isLoading = false;

```
L045 |       });
```
-> Code: });

```
L046 |     }
```
-> Code: }

```
L047 |   }
```
-> Code: }

```
L048 |
```
-> Blank line

```
L049 |   @override
```
-> Annotation/Decorator: @override

```
L050 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L051 |     super.initState();
```
-> Code: super.initState();

```
L052 |     loadSaved();
```
-> Code: loadSaved();

```
L053 |   }
```
-> Code: }

```
L054 |
```
-> Blank line

```
L055 |   @override
```
-> Annotation/Decorator: @override

```
L056 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L057 |     return BlocListener<PostCubit, PostStates>(
```
-> Return statement: return BlocListener<PostCubit, PostStates>(

```
L058 |       listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L059 |         if (state is SavedPostsUpdated && mounted) {
```
-> Control flow statement: if (state is SavedPostsUpdated && mounted) {

```
L060 |           loadSaved();
```
-> Code: loadSaved();

```
L061 |         }
```
-> Code: }

```
L062 |       },
```
-> Code: },

```
L063 |       child: Scaffold(
```
-> Flutter UI widget usage: child: Scaffold(

```
L064 |         appBar: AppBar(title: const Text('Saved Posts')),
```
-> Flutter UI widget usage: appBar: AppBar(title: const Text('Saved Posts')),

```
L065 |         body: _isLoading
```
-> Code: body: _isLoading

```
L066 |             ? const Center(child: CircularProgressIndicator())
```
-> Code: ? const Center(child: CircularProgressIndicator())

```
L067 |             : _error != null
```
-> Code: : _error != null

```
L068 |             ? Center(child: Text('Error: $_error'))
```
-> Code: ? Center(child: Text('Error: $_error'))

```
L069 |             : savedPosts.isEmpty
```
-> Code: : savedPosts.isEmpty

```
L070 |             ? const Center(child: Text('No saved posts yet.'))
```
-> Code: ? const Center(child: Text('No saved posts yet.'))

```
L071 |             : RefreshIndicator(
```
-> Code: : RefreshIndicator(

```
L072 |                 onRefresh: loadSaved,
```
-> Code: onRefresh: loadSaved,

```
L073 |                 child: ListView.builder(
```
-> Flutter UI widget usage: child: ListView.builder(

```
L074 |                   padding: const EdgeInsets.symmetric(vertical: 8),
```
-> Code: padding: const EdgeInsets.symmetric(vertical: 8),

```
L075 |                   itemCount: savedPosts.length,
```
-> Code: itemCount: savedPosts.length,

```
L076 |                   itemBuilder: (context, i) => PostTile(post: savedPosts[i]),
```
-> Code: itemBuilder: (context, i) => PostTile(post: savedPosts[i]),

```
L077 |                 ),
```
-> Code:),

```
L078 |               ),
```
-> Code:),

```
L079 |       ),
```
-> Code:),

```
L080 |     );
```
-> Code:);

```
L081 |   }
```
-> Code: }

```
L082 | }
```
-> Code: }

lib/features/posts/presentation/pages/search_posts.dart

```
L001 | import 'package:firebase_auth/firebase_auth.dart';
```
-> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L004 | import 'package:instproject/features/auth/presentation/pages/profile_page.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/pages/profile_page.dart';

```
L005 | import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/bloc/post_cubit.dart';

```
L006 | import 'package:instproject/features/posts/presentation/bloc/post_states.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/presentation/bloc/post_states.dart';

```
L007 | import 'package:instproject/features/posts/data/post_model.dart';
```
-> Imports module or package: import 'package:instproject/features/posts/data/post_model.dart';

```
L008 |
```
-> Blank line

```
L009 |
```
-> Blank line

```
L010 | class SearchPostsPage extends StatefulWidget {
```
-> Class declaration: class SearchPostsPage extends StatefulWidget {

```
L011 |   const SearchPostsPage({super.key});
```
-> Variable declaration: const SearchPostsPage({super.key});

```
L012 |
```
-> Blank line

```
L013 |   @override
```
-> Annotation/Decorator: @override

```
L014 |   State<SearchPostsPage> createState() => _SearchPostsPageState();
```
-> Short arrow function/expression: State<SearchPostsPage> createState() => _SearchPostsPageState();

```
L015 | }
```
-> Code: }

```
L016 |
```
-> Blank line

```
L017 | class _SearchPostsPageState extends State<SearchPostsPage> {
```
-> Class declaration: class _SearchPostsPageState extends State<SearchPostsPage> {

```
L018 |   String searchQuery = '';
```
-> Code: String searchQuery = '';

```
L019 |   final TextEditingController _controller = TextEditingController();
```
-> Variable declaration: final TextEditingController _controller = TextEditingController();

```
L020 |
```
-> Blank line

```
L021 |   @override
```
-> Annotation/Decorator: @override

```
L022 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L023 |     super.initState();
```
-> Code: super.initState();

```
L024 |     // Load posts when the page opens
```
-> Comment: Load posts when the page opens

```
L025 |     context.read<PostCubit>().fetchAllPosts();
```
-> Code: context.read<PostCubit>().fetchAllPosts();

```
L026 |   }
```
-> Code: }

```
L027 |
```
-> Blank line

```
L028 |   @override
```
-> Annotation/Decorator: @override

```
L029 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L030 |     return Scaffold(
```
-> Return statement: return Scaffold(

```
L031 |       backgroundColor: Colors.black,
```
-> Code: backgroundColor: Colors.black,

```
L032 |       appBar: AppBar(
```
-> Flutter UI widget usage: appBar: AppBar(

```
L033 |         title: const Text("Search Posts"),
```
-> Code: title: const Text("Search Posts"),

```
L034 |         backgroundColor: Colors.brown.shade800,
```
-> Code: backgroundColor: Colors.brown.shade800,

```
L035 |         elevation: 0,
  -> Code: elevation: 0,
L036 |       ),
  -> Code: ),
L037 |       body: Column(
  -> Code: body: Column(
L038 |         children: [
  -> Code: children: [
L039 |
  -> Blank line
L040 |           Padding(
  -> Code: Padding(
L041 |             padding: const EdgeInsets.all(12.0),
  -> Code: padding: const EdgeInsets.all(12.0),
L042 |             child: TextField(
  -> Code: child: TextField(
L043 |               controller: _controller,
  -> Code: controller: _controller,
L044 |               style: const TextStyle(color: Colors.white),
  -> Code: style: const TextStyle(color: Colors.white),
L045 |               decoration: InputDecoration(
  -> Code: decoration: InputDecoration(
L046 |                 hintText: 'Search ',
  -> Code: hintText: 'Search ',
L047 |                 hintStyle: TextStyle(color: Colors.white.withOpacity(0.6)),
  -> Code: hintStyle: TextStyle(color: Colors.white.withOpacity(0.6)),
L048 |                 prefixIcon: const Icon(Icons.search, color: Colors.white),
  -> Code: prefixIcon: const Icon(Icons.search, color: Colors.white),
L049 |                 filled: true,
  -> Code: filled: true,
L050 |                 fillColor: Colors.brown.shade700.withOpacity(0.3),
  -> Code: fillColor: Colors.brown.shade700.withOpacity(0.3),
L051 |                 border: OutlineInputBorder(
  -> Code: border: OutlineInputBorder(
L052 |                   borderRadius: BorderRadius.circular(20),
  -> Code: borderRadius: BorderRadius.circular(20),
L053 |                   borderSide: BorderSide.none,
  -> Code: borderSide: BorderSide.none,
L054 |                 ),
  -> Code: ),
L055 |                 suffixIcon: _controller.text.isNotEmpty
  -> Code: suffixIcon: _controller.text.isNotEmpty
L056 |                     ? IconButton(
  -> Code: ? IconButton(
L057 |                         icon: const Icon(Icons.clear, color: Colors.white),
  -> Code: icon: const Icon(Icons.clear, color: Colors.white),
L058 |                         onPressed: () {
  -> Code: onPressed: () {
L059 |                           _controller.clear();
  -> Code: _controller.clear();
L060 |                           setState(() => searchQuery = '');
  -> Short arrow function/expression: setState(() => searchQuery = '');
L061 |                         },
  -> Code: },
L062 |                       )
  -> Code: )
L063 |                     : null,
  -> Code: : null,
L064 |               ),
  -> Code: ),
L065 |               onChanged: (query) {
  -> Code: onChanged: (query) {
L066 |                 setState(() => searchQuery = query.toLowerCase());
  -> Short arrow function/expression: setState(() => searchQuery = query.toLowerCase());
L067 |               },
  -> Code: },
L068 |             ),
  -> Code: ),
L069 |           ),
  -> Code: ),
L070 |
  -> Blank line
```

```
L071 |
```
-> Blank line

```
L072 |           Expanded(
```
-> Code: Expanded(

```
L073 |             child: BlocBuilder<PostCubit, PostStates>(
```
-> Code: child: BlocBuilder<PostCubit, PostStates>(

```
L074 |               builder: (context, state) {
```
-> Code: builder: (context, state) {

```
L075 |                 if (state is PostLoading) {
```
-> Control flow statement: if (state is PostLoading) {

```
L076 |                   return const Center(child: CircularProgressIndicator());
```
-> Return statement: return const Center(child: CircularProgressIndicator());

```
L077 |                 } else if (state is PostLoaded) {
```
-> Code: } else if (state is PostLoaded) {

```
L078 |                   final filteredPosts = state.posts.where((post) {
```
-> Variable declaration: final filteredPosts = state.posts.where((post) {

```
L079 |                     final query = searchQuery.toLowerCase();
```
-> Variable declaration: final query = searchQuery.toLowerCase();

```
L080 |                     return post.caption.toLowerCase().contains(query) ||
```
-> Return statement: return post.caption.toLowerCase().contains(query) ||

```
L081 |                         post.userName.toLowerCase().contains(query);
```
-> Code: post.userName.toLowerCase().contains(query);

```
L082 |                   }).toList();
```
-> Code: }).toList();

```
L083 |
```
-> Blank line

```
L084 |
```
-> Blank line

```
L085 |                   if (filteredPosts.isEmpty) {
```
-> Control flow statement: if (filteredPosts.isEmpty) {

```
L086 |                     return const Center(
```
-> Return statement: return const Center(

```
L087 |                       child: Text(
```
-> Code: child: Text(

```
L088 |                         'No posts found.',
```
-> Code: 'No posts found.',

```
L089 |                         style: TextStyle(color: Colors.white70),
```
-> Code: style: TextStyle(color: Colors.white70),

```
L090 |                       ),
```
-> Code:),

```
L091 |                     );
```
-> Code:);

```
L092 |                   }
```
-> Code: }

```
L093 |
```
-> Blank line

```
L094 |                   return ListView.builder(
```
-> Return statement: return ListView.builder(

```
L095 |                     padding: const EdgeInsets.symmetric(horizontal: 10),
```
-> Code: padding: const EdgeInsets.symmetric(horizontal: 10),

```
L096 |                     itemCount: filteredPosts.length,
```
-> Code: itemCount: filteredPosts.length,

```
L097 |                     itemBuilder: (context, index) {
```
-> Code: itemBuilder: (context, index) {

```
L098 |                       final post = filteredPosts[index];
```
-> Variable declaration: final post = filteredPosts[index];

```
L099 |                       return PostTile(post: post);
```
-> Return statement: return PostTile(post: post);

```
L100 |                     },
```
-> Code: },

```
L101 |                   );
```
-> Code:);

```
L102 |                 } else if (state is PostError) {
```
-> Code: } else if (state is PostError) {

```
L103 |                   return Center(
```
-> Return statement: return Center(

```
L104 |                     child: Text(
```
-> Code: child: Text(

```
L105 |                       state.message,
```
-> Code: state.message,

```
L106 |                       style: const TextStyle(color: Colors.redAccent),
```
-> Code: style: const TextStyle(color: Colors.redAccent),

```
L107 |                     ),
  -> Code: ),
L108 |                   );
  -> Code: );
L109 |                 }
  -> Code: }
L110 |                 return const SizedBox();
  -> Return statement: return const SizedBox();
L111 |               },
  -> Code: },
L112 |             ),
  -> Code: ),
L113 |           ),
  -> Code: ),
L114 |         ],
  -> Code: ],
L115 |       ),
  -> Code: ),
L116 |     );
  -> Code: );
L117 |   }
  -> Code: }
L118 | }
  -> Code: }
L119 |
  -> Blank line
L120 |
  -> Blank line
L121 | class PostTile extends StatelessWidget {
  -> Class declaration: class PostTile extends StatelessWidget {
L122 |   final Post post;
  -> Variable declaration: final Post post;
L123 |
  -> Blank line
L124 |   const PostTile({super.key, required this.post});
  -> Variable declaration: const PostTile({super.key, required this.post});
L125 |
  -> Blank line
L126 |   @override
  -> Annotation/Decorator: @override
L127 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L128 |     final userName = post.userName.isNotEmpty ? post.userName : 'Unknown User';
  -> Variable declaration: final userName = post.userName.isNotEmpty ? post.userName : 'Unknown User';
L129 |     final profileImage = post.userProfileImage.isNotEmpty
  -> Variable declaration: final profileImage = post.userProfileImage.isNotEmpty
L130 |         ? post.userProfileImage
  -> Code: ? post.userProfileImage
L131 |         : 'https://cdn-icons-png.flaticon.com/512/149/149071.png';
  -> Code: : 'https://cdn-icons-png.flaticon.com/512/149/149071.png';
L132 |          final currentUser = FirebaseAuth.instance.currentUser;
  -> Variable declaration: final currentUser = FirebaseAuth.instance.currentUser;
L133 |     final currentUid = currentUser?.uid ?? '';
  -> Variable declaration: final currentUid = currentUser?.uid ?? '';
L134 |
  -> Blank line
L135 |     final isLiked = post.likes.contains(currentUid);
  -> Variable declaration: final isLiked = post.likes.contains(currentUid);
L136 |     final isMark = post.isSaved;
  -> Variable declaration: final isMark = post.isSaved;
L137 |     return Card(
  -> Return statement: return Card(
L138 |       margin: const EdgeInsets.symmetric(vertical: 8, horizontal: 12),
  -> Code: margin: const EdgeInsets.symmetric(vertical: 8, horizontal: 12),
L139 |       shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(16)),
  -> Code: shape: RoundedRectangleBorder(borderRadius: BorderRadius.circular(16)),
L140 |       elevation: 2,
  -> Code: elevation: 2,
L141 |       child: Column(
  -> Code: child: Column(
L142 |         crossAxisAlignment: CrossAxisAlignment.start,
  -> Code: crossAxisAlignment: CrossAxisAlignment.start,
```

```
L143 |         children: [
```
-> Code: children: [

```
L144 |           ListTile(
```
-> Code: ListTile(

```
L145 |             leading: GestureDetector(
```
-> Code: leading: GestureDetector(

```
L146 |               onTap: () {
```
-> Code: onTap: () {

```
L147 |               Navigator.push(
```
-> Code: Navigator.push(

```
L148 |                 context,
```
-> Code: context,

```
L149 |                 MaterialPageRoute(builder: (_) => ProfilePage(uid: post.userId)),
```
-> Code: MaterialPageRoute(builder: (_) => ProfilePage(uid: post.userId)),

```
L150 |               );
```
-> Code:);

```
L151 |
```
-> Blank line

```
L152 |               },
```
-> Code: },

```
L153 |               child: CircleAvatar(
```
-> Code: child: CircleAvatar(

```
L154 |                 backgroundImage: NetworkImage(profileImage),
```
-> Code: backgroundImage: NetworkImage(profileImage),

```
L155 |                 radius: 22,
```
-> Code: radius: 22,

```
L156 |               ),
```
-> Code:),

```
L157 |             ),
```
-> Code:),

```
L158 |             title: GestureDetector(
```
-> Code: title: GestureDetector(

```
L159 |                onTap: () {
```
-> Code: onTap: () {

```
L160 |               Navigator.push(
```
-> Code: Navigator.push(

```
L161 |                 context,
```
-> Code: context,

```
L162 |                 MaterialPageRoute(builder: (_) => ProfilePage(uid: post.userId)),
```
-> Code: MaterialPageRoute(builder: (_) => ProfilePage(uid: post.userId)),

```
L163 |               );
```
-> Code:);

```
L164 |                },
```
-> Code: },

```
L165 |               child: Text(
```
-> Code: child: Text(

```
L166 |                 userName,
```
-> Code: userName,

```
L167 |                 style: const TextStyle(fontWeight: FontWeight.bold),
```
-> Code: style: const TextStyle(fontWeight: FontWeight.bold),

```
L168 |               ),
```
-> Code:),

```
L169 |             ),
```
-> Code:),

```
L170 |
```
-> Blank line

```
L171 |
```
-> Blank line

```
L172 |           ),
```
-> Code:),

```
L173 |
```
-> Blank line

```
L174 |
```
-> Blank line

```
L175 |         ],
```
-> Code:],

```
L176 |       ),
```
-> Code:),

```
L177 |     );
```
-> Code:);

```
L178 |   }
```
-> Code: }

```
L179 | }
```
-> Code: }

lib/features/storage/data/firebase_storge_repo.dart

```
L001 | import 'package:http/http.dart' as http;
```
-> Imports module or package: import 'package:http/http.dart' as http;

```
L002 | import 'dart:convert';
```
-> Imports module or package: import 'dart:convert';

```
L003 | import 'package:instproject/core/appconfig.dart';
```
-> Imports module or package: import 'package:instproject/core/appconfig.dart';

```
L004 | import 'package:instproject/features/storage/domain/storage_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/storage/domain/storage_repo.dart';

```
L005 |
```
-> Blank line

```
L006 | class StorageRepoAppWrite implements StorageRepo {
```
-> Class declaration: class StorageRepoAppWrite implements StorageRepo {

```
L007 |   final String bucketId = bucketId1;
```
-> Variable declaration: final String bucketId = bucketId1;

```
L008 |   final String projectId = projectId1;
```
-> Variable declaration: final String projectId = projectId1;

```
L009 |   final String endpoint = appwriteEndpoint;
```
-> Variable declaration: final String endpoint = appwriteEndpoint;

```
L010 |
```
-> Blank line

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   Future<String?> uploadProfileImageMobile(
```
-> Function/method declaration or async return type: Future<String?> uploadProfileImageMobile(

```
L014 |     String imagePath,
```
-> Code: String imagePath,

```
L015 |     String fileName,
```
-> Code: String fileName,

```
L016 |   ) async {
```
-> Code:) async {

```
L017 |     try {
```
-> Code: try {

```
L018 |       final url = Uri.parse('$endpoint/storage/buckets/$bucketId/files');
```
-> Variable declaration: final url = Uri.parse('$endpoint/storage/buckets/$bucketId/files');

```
L019 |
```
-> Blank line

```
L020 |       final request = http.MultipartRequest('POST', url)
```
-> Variable declaration: final request = http.MultipartRequest('POST', url)

```
L021 |         ..headers['X-Appwrite-Project'] = projectId
```
-> Code: ..headers['X-Appwrite-Project'] = projectId

```
L022 |         ..files.add(
```
-> Code: ..files.add(

```
L023 |           await http.MultipartFile.fromPath(
```
-> Code: await http.MultipartFile.fromPath(

```
L024 |             'file',
```
-> Code: 'file',

```
L025 |             imagePath,
```
-> Code: imagePath,

```
L026 |             filename: fileName,
```
-> Code: filename: fileName,

```
L027 |           ),
```
-> Code:),

```
L028 |         );
```
-> Code:);

```
L029 |
```
-> Blank line

```
L030 |       final response = await request.send();
```
-> Variable declaration: final response = await request.send();

```
L031 |       final resBody = await response.stream.bytesToString();
```
-> Variable declaration: final resBody = await response.stream.bytesToString();

```
L032 |
```
-> Blank line

```
L033 |       if (response.statusCode == 201) {
```
-> Control flow statement: if (response.statusCode == 201) {

```
L034 |         final data = jsonDecode(resBody);
```
-> Variable declaration: final data = jsonDecode(resBody);

```
L035 |         final fileId = data['\$id'];
```
-> Variable declaration: final fileId = data['\$id'];

```
L036 |         return '$endpoint/storage/buckets/$bucketId/files/$fileId/view?project=$projectId';
```
-> Return statement: return '$endpoint/storage/buckets/$bucketId/files/$fileId/view?project=$projectId';

```
L037 |       } else {
```
-> Code: } else {

```
L038 |         print(' Upload failed: $resBody');
```
-> Code: print(' Upload failed: $resBody');

```
L039 |         return null;
```
-> Return statement: return null;

```
L040 |       }
```
-> Code: }

```
L041 |     } catch (e) {
```
-> Code: } catch (e) {

```
L042 |       print(' Error uploading image: $e');
```
-> Code: print(' Error uploading image: $e');

```
L043 |       return null;
```
-> Return statement: return null;

```
L044 |     }
```
-> Code: }

```
L045 |   }
```
-> Code: }

```
L046 |
```
-> Blank line

```
L047 |
```
-> Blank line

```
L048 |   Future<void> deleteFileByUrl(String fileUrl) async {
```
-> Function/method declaration or async return type: Future<void> deleteFileByUrl(String fileUrl) async {

```
L049 |     try {
```
-> Code: try {

```
L050 |
```
-> Blank line

```
L051 |       final uri = Uri.parse(fileUrl);
```
-> Variable declaration: final uri = Uri.parse(fileUrl);

```
L052 |       final segments = uri.pathSegments;
```
-> Variable declaration: final segments = uri.pathSegments;

```
L053 |       final fileIdIndex = segments.indexOf('files') + 1;
```
-> Variable declaration: final fileIdIndex = segments.indexOf('files') + 1;

```
L054 |       final fileId = segments[fileIdIndex];
```
-> Variable declaration: final fileId = segments[fileIdIndex];

```
L055 |
```
-> Blank line

```
L056 |       final deleteUrl = Uri.parse(
```
-> Variable declaration: final deleteUrl = Uri.parse(

```
L057 |         '$endpoint/storage/buckets/$bucketId/files/$fileId',
```
-> Code: '$endpoint/storage/buckets/$bucketId/files/$fileId',

```
L058 |       );
```
-> Code:);

```
L059 |
```
-> Blank line

```
L060 |       final response = await http.delete(
```
-> Variable declaration: final response = await http.delete(

```
L061 |         deleteUrl,
```
-> Code: deleteUrl,

```
L062 |         headers: {
```
-> Code: headers: {

```
L063 |           'X-Appwrite-Project': projectId,
```
-> Code: 'X-Appwrite-Project': projectId,

```
L064 |           'Content-Type': 'application/json',
```
-> Code: 'Content-Type': 'application/json',

```
L065 |         },
```
-> Code: },

```
L066 |       );
```
-> Code:);

```
L067 |
```
-> Blank line

```
L068 |       if (response.statusCode == 204) {
```
-> Control flow statement: if (response.statusCode == 204) {

```
L069 |         print('File deleted successfully');
```
-> Code: print('File deleted successfully');

```
L070 |       } else {
```
-> Code: } else {

```
L071 |         print('Failed to delete file: ${response.body}');
```
-> Code: print('Failed to delete file: ${response.body}');

```
L072 |       }
```
-> Code: }

```
L073 |     } catch (e) {
```
-> Code: } catch (e) {

```
L074 |       print('Error deleting file: $e');
```
-> Code: print('Error deleting file: $e');

```
L075 |     }
```
-> Code: }

```
L076 |   }
```
-> Code: }

```
L077 | }
```
-> Code: }

lib/features/storage/domain/appwrite_storage_repo.dart

```
L001 | import 'dart:io';
```
-> Imports module or package: import 'dart:io';

```
L002 | import 'package:instproject/core/rebos/appwrite_storage_api.dart';
```
-> Imports module or package: import 'package:instproject/core/rebos/appwrite_storage_api.dart';

```
L003 | import 'package:instproject/features/storage/domain/storage_repo.dart';
```
-> Imports module or package: import 'package:instproject/features/storage/domain/storage_repo.dart';

```
L004 |
```
-> Blank line

```
L005 | class AppwriteStorageRepo implements StorageRepo {
```
-> Class declaration: class AppwriteStorageRepo implements StorageRepo {

```
L006 |   @override
```
-> Annotation/Decorator: @override

```
L007 |   Future<String?> uploadProfileImageMobile(String imagePath, String uid) async {
```
-> Function/method declaration or async return type: Future<String?> uploadProfileImageMobile(String imagePath, String uid) async {

```
L008 |     final file = File(imagePath);
```
-> Variable declaration: final file = File(imagePath);

```
L009 |     final fileName = '${uid}_profile.jpg';
```
-> Variable declaration: final fileName = '${uid}_profile.jpg';

```
L010 |     return await AppwriteStorageAPI.uploadImage(file, fileName);
```
-> Return statement: return await AppwriteStorageAPI.uploadImage(file, fileName);

```
L011 |   }
```
-> Code: }

```
L012 |
```
-> Blank line

```
L013 |
```
-> Blank line

```
L014 |   Future<void> deleteFileByUrl(String fileUrl) async {
```
-> Function/method declaration or async return type: Future<void> deleteFileByUrl(String fileUrl) async {

```
L015 |     try {
```
-> Code: try {

```
L016 |       await AppwriteStorageAPI.deleteFileByUrl(fileUrl);
```
-> Code: await AppwriteStorageAPI.deleteFileByUrl(fileUrl);

```
L017 |     } catch (e) {
```
-> Code: } catch (e) {

```
L018 |       throw Exception('Failed to delete file: $e');
```
-> Code: throw Exception('Failed to delete file: $e');

```
L019 |     }
```
-> Code: }

```
L020 |   }
```
-> Code: }

```
L021 |
```
-> Blank line

```
L022 |
```
-> Blank line

```
L023 |   Future<String?> uploadPostImage(String imagePath, String postId) async {
```
-> Function/method declaration or async return type: Future<String?> uploadPostImage(String imagePath, String postId) async {

```
L024 |     final file = File(imagePath);
```
-> Variable declaration: final file = File(imagePath);

```
L025 |     final fileName = '${postId}_post.jpg';
```
-> Variable declaration: final fileName = '${postId}_post.jpg';

```
L026 |     return await AppwriteStorageAPI.uploadImage(file, fileName);
```
-> Return statement: return await AppwriteStorageAPI.uploadImage(file, fileName);

```
L027 |   }
```
-> Code: }

```
L028 | }
```
-> Code: }

lib/features/storage/domain/storage_repo.dart

```
L001 | abstract class StorageRepo {
```
-> Class declaration (complex): abstract class StorageRepo {

```
L002 |   Future<String?> uploadProfileImageMobile(String imagePath, String uid);
```
-> Function/method declaration or async return type: Future<String?> uploadProfileImageMobile(String imagePath, String uid);

```
L003 | }
```
-> Code: }

```
L004 |
```
-> Blank line

lib/firebase_options.dart

```
L001 | // File generated by FlutterFire CLI.
  -> Comment:  File generated by FlutterFire CLI.
L002 | // ignore_for_file: type=lint
  -> Comment:  ignore_for_file: type=lint
L003 | import 'package:firebase_core/firebase_core.dart' show FirebaseOptions;
  -> Imports module or package: import 'package:firebase_core/firebase_core.dart' show FirebaseOptions;
L004 | import 'package:flutter/foundation.dart'
  -> Imports module or package: import 'package:flutter/foundation.dart'
L005 |     show defaultTargetPlatform, kIsWeb, TargetPlatform;
  -> Code: show defaultTargetPlatform, kIsWeb, TargetPlatform;
L006 |
  -> Blank line
L007 | /// Default [FirebaseOptions] for use with your Firebase apps.
  -> Comment:  Default [FirebaseOptions] for use with your Firebase apps.
L008 | ///
  -> Comment:
L009 | /// Example:
  -> Comment:  Example:
L010 | /// ```dart
  -> Comment:  ```dart
L011 | /// import 'firebase_options.dart';
  -> Comment:  import 'firebase_options.dart';
L012 | /// // ...
  -> Comment:  // ...
L013 | /// await Firebase.initializeApp(
  -> Comment:  await Firebase.initializeApp(
L014 | ///   options: DefaultFirebaseOptions.currentPlatform,
  -> Comment:   options: DefaultFirebaseOptions.currentPlatform,
L015 | /// );
  -> Comment:  );
L016 | /// ```
  -> Comment:  ```
L017 | class DefaultFirebaseOptions {
  -> Class declaration: class DefaultFirebaseOptions {
L018 |   static FirebaseOptions get currentPlatform {
  -> Code: static FirebaseOptions get currentPlatform {
L019 |     if (kIsWeb) {
  -> Control flow statement: if (kIsWeb) {
L020 |       return web;
  -> Return statement: return web;
L021 |     }
  -> Code: }
L022 |     switch (defaultTargetPlatform) {
  -> Code: switch (defaultTargetPlatform) {
L023 |       case TargetPlatform.android:
  -> Code: case TargetPlatform.android:
L024 |         return android;
  -> Return statement: return android;
L025 |       case TargetPlatform.iOS:
  -> Code: case TargetPlatform.iOS:
L026 |         return ios;
  -> Return statement: return ios;
L027 |       case TargetPlatform.macOS:
  -> Code: case TargetPlatform.macOS:
L028 |         throw UnsupportedError(
  -> Code: throw UnsupportedError(
L029 |           'DefaultFirebaseOptions have not been configured for macos - '
  -> Code: 'DefaultFirebaseOptions have not been configured for macos - '
L030 |           'you can reconfigure this by running the FlutterFire CLI again.',
  -> Code: 'you can reconfigure this by running the FlutterFire CLI again.',
L031 |         );
  -> Code: );
L032 |       case TargetPlatform.windows:
  -> Code: case TargetPlatform.windows:
L033 |         throw UnsupportedError(
  -> Code: throw UnsupportedError(
L034 |           'DefaultFirebaseOptions have not been configured for windows - '
  -> Code: 'DefaultFirebaseOptions have not been configured for windows - '
```

```
L035 |           'you can reconfigure this by running the FlutterFire CLI again.',
  -> Code: 'you can reconfigure this by running the FlutterFire CLI again.',
L036 |         );
  -> Code: );
L037 |       case TargetPlatform.linux:
  -> Code: case TargetPlatform.linux:
L038 |         throw UnsupportedError(
  -> Code: throw UnsupportedError(
L039 |           'DefaultFirebaseOptions have not been configured for linux - '
  -> Code: 'DefaultFirebaseOptions have not been configured for linux - '
L040 |           'you can reconfigure this by running the FlutterFire CLI again.',
  -> Code: 'you can reconfigure this by running the FlutterFire CLI again.',
L041 |         );
  -> Code: );
L042 |       default:
  -> Code: default:
L043 |         throw UnsupportedError(
  -> Code: throw UnsupportedError(
L044 |           'DefaultFirebaseOptions are not supported for this platform.',
  -> Code: 'DefaultFirebaseOptions are not supported for this platform.',
L045 |         );
  -> Code: );
L046 |     }
  -> Code: }
L047 |   }
  -> Code: }
L048 |
  -> Blank line
L049 |   static const FirebaseOptions web = FirebaseOptions(
  -> Code: static const FirebaseOptions web = FirebaseOptions(
L050 |     apiKey: 'AIzaSyD9nOPAGl-HTbH11jqME34Mh4c-3uSTnsQ',
  -> Code: apiKey: 'AIzaSyD9nOPAGl-HTbH11jqME34Mh4c-3uSTnsQ',
L051 |     appId: '1:572280814511:web:cb51c60f80af896504cd5a',
  -> Code: appId: '1:572280814511:web:cb51c60f80af896504cd5a',
L052 |     messagingSenderId: '572280814511',
  -> Code: messagingSenderId: '572280814511',
L053 |     projectId: 'blogapp-22e0c',
  -> Code: projectId: 'blogapp-22e0c',
L054 |     authDomain: 'blogapp-22e0c.firebaseapp.com',
  -> Code: authDomain: 'blogapp-22e0c.firebaseapp.com',
L055 |     storageBucket: 'blogapp-22e0c.firebasestorage.app',
  -> Code: storageBucket: 'blogapp-22e0c.firebasestorage.app',
L056 |     measurementId: 'G-9TFYK135Y9',
  -> Code: measurementId: 'G-9TFYK135Y9',
L057 |   );
  -> Code: );
L058 |
  -> Blank line
L059 |   static const FirebaseOptions android = FirebaseOptions(
  -> Code: static const FirebaseOptions android = FirebaseOptions(
L060 |     apiKey: 'AIzaSyBXT6jL0kd6Un6eIehLcjv8Jmv2Bbdaf8Q',
  -> Code: apiKey: 'AIzaSyBXT6jL0kd6Un6eIehLcjv8Jmv2Bbdaf8Q',
L061 |     appId: '1:572280814511:android:822051296ac0778704cd5a',
  -> Code: appId: '1:572280814511:android:822051296ac0778704cd5a',
L062 |     messagingSenderId: '572280814511',
  -> Code: messagingSenderId: '572280814511',
L063 |     projectId: 'blogapp-22e0c',
  -> Code: projectId: 'blogapp-22e0c',
L064 |     storageBucket: 'blogapp-22e0c.firebasestorage.app',
  -> Code: storageBucket: 'blogapp-22e0c.firebasestorage.app',
L065 |   );
  -> Code: );
L066 |
  -> Blank line
L067 |   static const FirebaseOptions ios = FirebaseOptions(
  -> Code: static const FirebaseOptions ios = FirebaseOptions(
L068 |     apiKey: 'AIzaSyACnUGdNK7veZBZGli3xAwkdLifIiX77VM',
  -> Code: apiKey: 'AIzaSyACnUGdNK7veZBZGli3xAwkdLifIiX77VM',
L069 |     appId: '1:572280814511:ios:b005bdafceb4556f04cd5a',
  -> Code: appId: '1:572280814511:ios:b005bdafceb4556f04cd5a',
L070 |     messagingSenderId: '572280814511',
  -> Code: messagingSenderId: '572280814511',
```

```
L071 |     projectId: 'blogapp-22e0c',
```
-> Code: projectId: 'blogapp-22e0c',

```
L072 |     storageBucket: 'blogapp-22e0c.firebasestorage.app',
```
-> Code: storageBucket: 'blogapp-22e0c.firebasestorage.app',

```
L073 |     iosBundleId: 'com.example.instproject',
```
-> Code: iosBundleId: 'com.example.instproject',

```
L074 |   );
```
-> Code:);

```
L075 | }
```
-> Code: }

lib/main.dart

```
L001 | import 'package:firebase_core/firebase_core.dart';
```
-> Imports module or package: import 'package:firebase_core/firebase_core.dart';

```
L002 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L003 | import 'package:instproject/app.dart';
```
-> Imports module or package: import 'package:instproject/app.dart';

```
L004 | import 'package:instproject/firebase_options.dart';
```
-> Imports module or package: import 'package:instproject/firebase_options.dart';

```
L005 |
```
-> Blank line

```
L006 |
```
-> Blank line

```
L007 | void main() async {
```
-> Function/method declaration or async return type: void main() async {

```
L008 |   WidgetsFlutterBinding.ensureInitialized();
```
-> Flutter widget/typed UI code: WidgetsFlutterBinding.ensureInitialized();

```
L009 |   await Firebase.initializeApp(options: DefaultFirebaseOptions.currentPlatform);
```
-> Code: await Firebase.initializeApp(options: DefaultFirebaseOptions.currentPlatform);

```
L010 |
```
-> Blank line

```
L011 |
```
-> Blank line

```
L012 |
```
-> Blank line

```
L013 |
```
-> Blank line

```
L014 |   runApp(MyApp());
```
-> Code: runApp(MyApp());

```
L015 | }
```
-> Code: }

```
L016 |
```
-> Blank line

```
L017 |
```
-> Blank line

lib/main_shell.dart

```
L001 | import 'package:firebase_auth/firebase_auth.dart';
  -> Imports module or package: import 'package:firebase_auth/firebase_auth.dart';
L002 | import 'package:flutter/material.dart';
  -> Imports module or package: import 'package:flutter/material.dart';
L003 | import 'package:instproject/features/chatgroup/pages/group_chat_page.dart';
  -> Imports module or package: import 'package:instproject/features/chatgroup/pages/group_chat_page.dart';
L004 | import 'package:instproject/features/auth/presentation/pages/profile_page.dart';
  -> Imports module or package: import 'package:instproject/features/auth/presentation/pages/profile_page.dart';
L005 | import 'package:instproject/features/posts/presentation/pages/create_post_page.dart';
  -> Imports module or package: import 'package:instproject/features/posts/presentation/pages/create_post_page.dart';
L006 | import 'package:instproject/features/posts/presentation/pages/feed_page.dart';
  -> Imports module or package: import 'package:instproject/features/posts/presentation/pages/feed_page.dart';
L007 | import 'package:instproject/features/institutes/presentation/pages/institutes_page.dart';
  -> Imports module or package: import 'package:instproject/features/institutes/presentation/pages/institutes_page.dart';
L008 | import 'package:instproject/features/posts/presentation/pages/search_posts.dart';
  -> Imports module or package: import 'package:instproject/features/posts/presentation/pages/search_posts.dart';
L009 |
  -> Blank line
L010 | class MainShell extends StatefulWidget {
  -> Class declaration: class MainShell extends StatefulWidget {
L011 |   const MainShell({super.key});
  -> Variable declaration: const MainShell({super.key});
L012 |
  -> Blank line
L013 |   @override
  -> Annotation/Decorator: @override
L014 |   State<MainShell> createState() => _MainShellState();
  -> Short arrow function/expression: State<MainShell> createState() => _MainShellState();
L015 | }
  -> Code: }
L016 |
  -> Blank line
L017 | class _MainShellState extends State<MainShell> {
  -> Class declaration: class _MainShellState extends State<MainShell> {
L018 |   int _currentIndex = 0;
  -> Code: int _currentIndex = 0;
L019 |   User? user = FirebaseAuth.instance.currentUser;
  -> Code: User? user = FirebaseAuth.instance.currentUser;
L020 |
  -> Blank line
L021 |   @override
  -> Annotation/Decorator: @override
L022 |   Widget build(BuildContext context) {
  -> Flutter widget/typed UI code: Widget build(BuildContext context) {
L023 |     final pages = [
  -> Variable declaration: final pages = [
L024 |       FeedPage(userId: user?.uid ?? 'defaultId'),
  -> Code: FeedPage(userId: user?.uid ?? 'defaultId'),
L025 |       const GroupsPage(),
  -> Variable declaration: const GroupsPage(),
L026 |       CreatePostPage(userId: user?.uid ?? ''),
  -> Code: CreatePostPage(userId: user?.uid ?? ''),
L027 |       SearchPostsPage(),
  -> Code: SearchPostsPage(),
L028 |       ProfilePage(uid: user?.uid ?? ''),
  -> Code: ProfilePage(uid: user?.uid ?? ''),
L029 |       const InstitutesPage(),
  -> Variable declaration: const InstitutesPage(),
L030 |     ];
  -> Code: ];
L031 |
  -> Blank line
L032 |     return Scaffold(
  -> Return statement: return Scaffold(
L033 |       extendBody: true,
  -> Code: extendBody: true,
L034 |       body: Container(
  -> Code: body: Container(
```

```
L035 |         decoration: const BoxDecoration(
  -> Code: decoration: const BoxDecoration(
L036 |           gradient: LinearGradient(
  -> Code: gradient: LinearGradient(
L037 |             colors: [Color(0xFF4E342E), Colors.black],
  -> Code: colors: [Color(0xFF4E342E), Colors.black],
L038 |             begin: Alignment.topCenter,
  -> Code: begin: Alignment.topCenter,
L039 |             end: Alignment.bottomCenter,
  -> Code: end: Alignment.bottomCenter,
L040 |           ),
  -> Code: ),
L041 |         ),
  -> Code: ),
L042 |         child: IndexedStack(index: _currentIndex, children: pages),
  -> Code: child: IndexedStack(index: _currentIndex, children: pages),
L043 |       ),
  -> Code: ),
L044 |       bottomNavigationBar: BottomNavigationBar(
  -> Code: bottomNavigationBar: BottomNavigationBar(
L045 |         currentIndex: _currentIndex,
  -> Code: currentIndex: _currentIndex,
L046 |         onTap: (i) => setState(() => _currentIndex = i),
  -> Code: onTap: (i) => setState(() => _currentIndex = i),
L047 |         type: BottomNavigationBarType.fixed,
  -> Code: type: BottomNavigationBarType.fixed,
L048 |         backgroundColor: Theme.of(
  -> Code: backgroundColor: Theme.of(
L049 |           context,
  -> Code: context,
L050 |         ).bottomNavigationBarTheme.backgroundColor,
  -> Code: ).bottomNavigationBarTheme.backgroundColor,
L051 |         selectedItemColor: Theme.of(
  -> Code: selectedItemColor: Theme.of(
L052 |           context,
  -> Code: context,
L053 |         ).bottomNavigationBarTheme.selectedItemColor,
  -> Code: ).bottomNavigationBarTheme.selectedItemColor,
L054 |         unselectedItemColor: Theme.of(
  -> Code: unselectedItemColor: Theme.of(
L055 |           context,
  -> Code: context,
L056 |         ).bottomNavigationBarTheme.unselectedItemColor,
  -> Code: ).bottomNavigationBarTheme.unselectedItemColor,
L057 |         items: const [
  -> Code: items: const [
L058 |           BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L059 |             icon: Icon(Icons.home_outlined),
  -> Code: icon: Icon(Icons.home_outlined),
L060 |             activeIcon: Icon(Icons.home),
  -> Code: activeIcon: Icon(Icons.home),
L061 |             label: 'Home',
  -> Code: label: 'Home',
L062 |           ),
  -> Code: ),
L063 |           BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L064 |             icon: Icon(Icons.groups_outlined),
  -> Code: icon: Icon(Icons.groups_outlined),
L065 |             activeIcon: Icon(Icons.groups),
  -> Code: activeIcon: Icon(Icons.groups),
L066 |             label: 'Groups',
  -> Code: label: 'Groups',
L067 |           ),
  -> Code: ),
L068 |           BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L069 |             icon: Icon(Icons.post_add_outlined),
  -> Code: icon: Icon(Icons.post_add_outlined),
L070 |             activeIcon: Icon(Icons.post_add),
  -> Code: activeIcon: Icon(Icons.post_add),
```

```
L071 |              label: 'Post',
  -> Code: label: 'Post',
L072 |            ),
  -> Code: ),
L073 |            BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L074 |              icon: Icon(Icons.search),
  -> Code: icon: Icon(Icons.search),
L075 |              activeIcon: Icon(Icons.search),
  -> Code: activeIcon: Icon(Icons.search),
L076 |              label: 'Search',
  -> Code: label: 'Search',
L077 |            ),
  -> Code: ),
L078 |
  -> Blank line
L079 |            BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L080 |              icon: Icon(Icons.person_outline),
  -> Code: icon: Icon(Icons.person_outline),
L081 |              activeIcon: Icon(Icons.person),
  -> Code: activeIcon: Icon(Icons.person),
L082 |              label: 'Me',
  -> Code: label: 'Me',
L083 |            ),
  -> Code: ),
L084 |            BottomNavigationBarItem(
  -> Code: BottomNavigationBarItem(
L085 |              icon: Icon(Icons.school_outlined),
  -> Code: icon: Icon(Icons.school_outlined),
L086 |              activeIcon: Icon(Icons.school),
  -> Code: activeIcon: Icon(Icons.school),
L087 |              label: 'Institutes',
  -> Code: label: 'Institutes',
L088 |            ),
  -> Code: ),
L089 |          ],
  -> Code: ],
L090 |        ),
  -> Code: ),
L091 |      );
  -> Code: );
L092 |    }
  -> Code: }
L093 | }
  -> Code: }
```

lib/splash_screen.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_cubit.dart';

```
L004 | import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/bloc/auth_states.dart';

```
L005 | import 'package:instproject/features/auth/presentation/pages/home_page.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/pages/home_page.dart';

```
L006 | import 'package:instproject/features/auth/presentation/pages/login_page.dart';
```
-> Imports module or package: import 'package:instproject/features/auth/presentation/pages/login_page.dart';

```
L007 | import 'package:instproject/main_shell.dart';
```
-> Imports module or package: import 'package:instproject/main_shell.dart';

```
L008 |
```
-> Blank line

```
L009 | class SplashScreen extends StatefulWidget {
```
-> Class declaration: class SplashScreen extends StatefulWidget {

```
L010 |   const SplashScreen({super.key});
```
-> Variable declaration: const SplashScreen({super.key});

```
L011 |
```
-> Blank line

```
L012 |   @override
```
-> Annotation/Decorator: @override

```
L013 |   State<SplashScreen> createState() => _SplashScreenState();
```
-> Short arrow function/expression: State<SplashScreen> createState() => _SplashScreenState();

```
L014 | }
```
-> Code: }

```
L015 |
```
-> Blank line

```
L016 | class _SplashScreenState extends State<SplashScreen> {
```
-> Class declaration: class _SplashScreenState extends State<SplashScreen> {

```
L017 |   @override
```
-> Annotation/Decorator: @override

```
L018 |   void initState() {
```
-> Function/method declaration or async return type: void initState() {

```
L019 |     super.initState();
```
-> Code: super.initState();

```
L020 |
```
-> Blank line

```
L021 |
```
-> Blank line

```
L022 |     context.read<AuthCubit>().checkAuth();
```
-> Code: context.read<AuthCubit>().checkAuth();

```
L023 |   }
```
-> Code: }

```
L024 |
```
-> Blank line

```
L025 |   @override
```
-> Annotation/Decorator: @override

```
L026 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L027 |     return BlocListener<AuthCubit, AuthState>(
```
-> Return statement: return BlocListener<AuthCubit, AuthState>(

```
L028 |       listener: (context, state) {
```
-> Code: listener: (context, state) {

```
L029 |
```
-> Blank line

```
L030 |         if (state is Authenticated) {
```
-> Control flow statement: if (state is Authenticated) {

```
L031 |           Navigator.pushReplacement(
```
-> Code: Navigator.pushReplacement(

```
L032 |             context,
```
-> Code: context,

```
L033 |             MaterialPageRoute(builder: (_) => const MainShell()),
```
-> Code: MaterialPageRoute(builder: (_) => const MainShell()),

```
L034 |           );
```
-> Code:);

```
L035 |         } else if (state is Unauthenticated) {
  -> Code: } else if (state is Unauthenticated) {
L036 |           Navigator.pushReplacement(
  -> Code: Navigator.pushReplacement(
L037 |             context,
  -> Code: context,
L038 |             MaterialPageRoute(builder: (_) => const LoginPage()),
  -> Code: MaterialPageRoute(builder: (_) => const LoginPage()),
L039 |           );
  -> Code: );
L040 |         }
  -> Code: }
L041 |       },
  -> Code: },
L042 |       child: Scaffold(
  -> Flutter UI widget usage: child: Scaffold(
L043 |         body: Container(
  -> Code: body: Container(
L044 |           decoration: BoxDecoration(
  -> Code: decoration: BoxDecoration(
L045 |             gradient: LinearGradient(
  -> Code: gradient: LinearGradient(
L046 |               colors: [ Colors.brown, Colors.black],
  -> Code: colors: [ Colors.brown, Colors.black],
L047 |               begin: Alignment.topLeft,
  -> Code: begin: Alignment.topLeft,
L048 |               end: Alignment.bottomRight,
  -> Code: end: Alignment.bottomRight,
L049 |             ),
  -> Code: ),
L050 |           ),
  -> Code: ),
L051 |           child: Center(
  -> Code: child: Center(
L052 |             child: Column(
  -> Code: child: Column(
L053 |               mainAxisSize: MainAxisSize.min,
  -> Code: mainAxisSize: MainAxisSize.min,
L054 |               children: [
  -> Code: children: [
L055 |                 Image.asset('images/sg.png', width: 100, height: 100),
  -> Code: Image.asset('images/sg.png', width: 100, height: 100),
L056 |                 const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L057 |
  -> Blank line
L058 |                 const SizedBox(height: 20),
  -> Variable declaration: const SizedBox(height: 20),
L059 |                 const CircularProgressIndicator(color: Colors.white),
  -> Variable declaration: const CircularProgressIndicator(color: Colors.white),
L060 |               ],
  -> Code: ],
L061 |             ),
  -> Code: ),
L062 |           ),
  -> Code: ),
L063 |         ),
  -> Code: ),
L064 |       ),
  -> Code: ),
L065 |     );
  -> Code: );
L066 |   }
  -> Code: }
L067 | }
  -> Code: }
```

lib/themes/theme.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 |
```
-> Blank line

```
L003 |
```
-> Blank line

```
L004 | final ThemeData lightMode = ThemeData(
```
-> Variable declaration: final ThemeData lightMode = ThemeData(

```
L005 |   brightness: Brightness.light,
```
-> Code: brightness: Brightness.light,

```
L006 |   scaffoldBackgroundColor: const Color(0xFF4E342E),
```
-> Code: scaffoldBackgroundColor: const Color(0xFF4E342E),

```
L007 |   appBarTheme: const AppBarTheme(
```
-> Code: appBarTheme: const AppBarTheme(

```
L008 |     backgroundColor: Color(0xFF3E2723),
```
-> Code: backgroundColor: Color(0xFF3E2723),

```
L009 |     foregroundColor: Colors.white,
```
-> Code: foregroundColor: Colors.white,

```
L010 |     elevation: 0,
```
-> Code: elevation: 0,

```
L011 |   ),
```
-> Code:),

```
L012 |   colorScheme: const ColorScheme.light(
```
-> Code: colorScheme: const ColorScheme.light(

```
L013 |     primary: Color(0xFF795548),
```
-> Code: primary: Color(0xFF795548),

```
L014 |     secondary: Colors.orangeAccent,
```
-> Code: secondary: Colors.orangeAccent,

```
L015 |     background: Color(0xFF4E342E),
```
-> Code: background: Color(0xFF4E342E),

```
L016 |   ),
```
-> Code:),

```
L017 |   bottomNavigationBarTheme: const BottomNavigationBarThemeData(
```
-> Code: bottomNavigationBarTheme: const BottomNavigationBarThemeData(

```
L018 |     backgroundColor: Color(0xFF5D4037),
```
-> Code: backgroundColor: Color(0xFF5D4037),

```
L019 |     selectedItemColor: Colors.orangeAccent,
```
-> Code: selectedItemColor: Colors.orangeAccent,

```
L020 |     unselectedItemColor: Colors.white70,
```
-> Code: unselectedItemColor: Colors.white70,

```
L021 |   ),
```
-> Code:),

```
L022 | );
```
-> Code:);

```
L023 |
```
-> Blank line

```
L024 |
```
-> Blank line

```
L025 | final ThemeData darkMode = ThemeData(
```
-> Variable declaration: final ThemeData darkMode = ThemeData(

```
L026 |   brightness: Brightness.dark,
```
-> Code: brightness: Brightness.dark,

```
L027 |   scaffoldBackgroundColor: Colors.black,
```
-> Code: scaffoldBackgroundColor: Colors.black,

```
L028 |   appBarTheme: const AppBarTheme(
```
-> Code: appBarTheme: const AppBarTheme(

```
L029 |     backgroundColor: Colors.black,
```
-> Code: backgroundColor: Colors.black,

```
L030 |     foregroundColor: Colors.white,
```
-> Code: foregroundColor: Colors.white,

```
L031 |     elevation: 0,
```
-> Code: elevation: 0,

```
L032 |   ),
```
-> Code:),

```
L033 |   colorScheme: const ColorScheme.dark(
```
-> Code: colorScheme: const ColorScheme.dark(

```
L034 |     primary: Color(0xFFBCAAA4),
```
-> Code: primary: Color(0xFFBCAAA4),

```
L035 |     secondary: Colors.orangeAccent,
```
-> Code: secondary: Colors.orangeAccent,

```
L036 |     background: Colors.black,
```
-> Code: background: Colors.black,

```
L037 |   ),
```
-> Code:),

```
L038 |   bottomNavigationBarTheme: const BottomNavigationBarThemeData(
```
-> Code: bottomNavigationBarTheme: const BottomNavigationBarThemeData(

```
L039 |     backgroundColor: Colors.black,
```
-> Code: backgroundColor: Colors.black,

```
L040 |     selectedItemColor: Colors.brown,
```
-> Code: selectedItemColor: Colors.brown,

```
L041 |     unselectedItemColor: Colors.white54,
```
-> Code: unselectedItemColor: Colors.white54,

```
L042 |   ),
```
-> Code:),

```
L043 | );
```
-> Code:);

lib/themes/theme_cubit.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:shared_preferences/shared_preferences.dart';
```
-> Imports module or package: import 'package:shared_preferences/shared_preferences.dart';

```
L004 |
```
-> Blank line

```
L005 | class ThemeCubit extends Cubit<ThemeMode> {
```
-> Class declaration: class ThemeCubit extends Cubit<ThemeMode> {

```
L006 |   static const String _themeKey = 'theme_mode';
```
-> Code: static const String _themeKey = 'theme_mode';

```
L007 |
```
-> Blank line

```
L008 |   ThemeCubit() : super(ThemeMode.system) {
```
-> Code: ThemeCubit() : super(ThemeMode.system) {

```
L009 |     _loadTheme();
```
-> Code: _loadTheme();

```
L010 |   }
```
-> Code: }

```
L011 |
```
-> Blank line

```
L012 |   void toggleTheme() async {
```
-> Function/method declaration or async return type: void toggleTheme() async {

```
L013 |     if (state == ThemeMode.light) {
```
-> Control flow statement: if (state == ThemeMode.light) {

```
L014 |       emit(ThemeMode.dark);
```
-> Code: emit(ThemeMode.dark);

```
L015 |       _saveTheme('dark');
```
-> Code: _saveTheme('dark');

```
L016 |     } else {
```
-> Code: } else {

```
L017 |       emit(ThemeMode.light);
```
-> Code: emit(ThemeMode.light);

```
L018 |       _saveTheme('light');
```
-> Code: _saveTheme('light');

```
L019 |     }
```
-> Code: }

```
L020 |   }
```
-> Code: }

```
L021 |
```
-> Blank line

```
L022 |   Future<void> _loadTheme() async {
```
-> Function/method declaration or async return type: Future<void> _loadTheme() async {

```
L023 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L024 |     final themeString = prefs.getString(_themeKey);
```
-> Variable declaration: final themeString = prefs.getString(_themeKey);

```
L025 |     if (themeString == 'dark') {
```
-> Control flow statement: if (themeString == 'dark') {

```
L026 |       emit(ThemeMode.dark);
```
-> Code: emit(ThemeMode.dark);

```
L027 |     } else if (themeString == 'light') {
```
-> Code: } else if (themeString == 'light') {

```
L028 |       emit(ThemeMode.light);
```
-> Code: emit(ThemeMode.light);

```
L029 |     } else {
```
-> Code: } else {

```
L030 |       emit(ThemeMode.system);
```
-> Code: emit(ThemeMode.system);

```
L031 |     }
```
-> Code: }

```
L032 |   }
```
-> Code: }

```
L033 |
```
-> Blank line

```
L034 |   Future<void> _saveTheme(String mode) async {
```
-> Function/method declaration or async return type: Future<void> _saveTheme(String mode) async {

```
L035 |     final prefs = await SharedPreferences.getInstance();
```
-> Variable declaration: final prefs = await SharedPreferences.getInstance();

```
L036 |     await prefs.setString(_themeKey, mode);
```
-> Code: await prefs.setString(_themeKey, mode);

```
L037 |   }
```
-> Code: }

```
L038 | }
```
-> Code: }

lib/themes/theme_mode_switcher.dart

```
L001 | import 'package:flutter/material.dart';
```
-> Imports module or package: import 'package:flutter/material.dart';

```
L002 | import 'package:flutter_bloc/flutter_bloc.dart';
```
-> Imports module or package: import 'package:flutter_bloc/flutter_bloc.dart';

```
L003 | import 'package:instproject/themes/theme_cubit.dart';
```
-> Imports module or package: import 'package:instproject/themes/theme_cubit.dart';

```
L004 |
```
-> Blank line

```
L005 | class ThemeSwitcherTile extends StatelessWidget {
```
-> Class declaration: class ThemeSwitcherTile extends StatelessWidget {

```
L006 |   const ThemeSwitcherTile({super.key});
```
-> Variable declaration: const ThemeSwitcherTile({super.key});

```
L007 |
```
-> Blank line

```
L008 |   @override
```
-> Annotation/Decorator: @override

```
L009 |   Widget build(BuildContext context) {
```
-> Flutter widget/typed UI code: Widget build(BuildContext context) {

```
L010 |     return BlocBuilder<ThemeCubit, ThemeMode>(
```
-> Return statement: return BlocBuilder<ThemeCubit, ThemeMode>(

```
L011 |       builder: (context, themeMode) {
```
-> Code: builder: (context, themeMode) {

```
L012 |         final isDark = themeMode == ThemeMode.dark;
```
-> Variable declaration: final isDark = themeMode == ThemeMode.dark;

```
L013 |         return ListTile(
```
-> Return statement: return ListTile(

```
L014 |           leading: Icon(isDark ? Icons.dark_mode : Icons.light_mode),
```
-> Code: leading: Icon(isDark ? Icons.dark_mode : Icons.light_mode),

```
L015 |           title: Text(isDark ? 'Switch to Light Mode' : 'Switch to Dark Mode'),
```
-> Code: title: Text(isDark ? 'Switch to Light Mode' : 'Switch to Dark Mode'),

```
L016 |           trailing: Switch(
```
-> Code: trailing: Switch(

```
L017 |             value: isDark,
```
-> Code: value: isDark,

```
L018 |             onChanged: (_) => context.read<ThemeCubit>().toggleTheme(),
```
-> Code: onChanged: (_) => context.read<ThemeCubit>().toggleTheme(),

```
L019 |           ),
```
-> Code:),

```
L020 |           onTap: () => context.read<ThemeCubit>().toggleTheme(),
```
-> Code: onTap: () => context.read<ThemeCubit>().toggleTheme(),

```
L021 |         );
```
-> Code:);

```
L022 |       },
```
-> Code: },

```
L023 |     );
```
-> Code:);

```
L024 |   }
```
-> Code: }

```
L025 | }
```
-> Code: }