

SportyShoes

An E-Commerce Website

Source Code

File 1: SportyshoesApplication.java

```
package com.project.sportyshoes;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class SportyshoesApplication {

    public static void main(String[] args) {

        SpringApplication.run(SportyshoesApplication.class, args);

    }

}
```

File 2: SecurityConfig.java

```
package com.project.sportyshoes.configuration;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
```

```
import
org.springframework.security.config.annotation.authentication.builders.AuthenticationMan
agerBuilder;

import org.springframework.security.config.annotation.web.builders.HttpSecurity;

import org.springframework.security.config.annotation.web.builders.WebSecurity;

import
org.springframework.security.config.annotation.web.configuration.EnableWebSecurity;

import
org.springframework.security.config.annotation.web.configuration.WebSecurityConfigurerA
dapter;

import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder;

import org.springframework.security.web.util.matcher.AntPathRequestMatcher;

import com.project.sportyshoes.service.CustomUserDetailsService;
```

@Configuration

@EnableWebSecurity

```
public class SecurityConfig extends WebSecurityConfigurerAdapter {
```

@Autowired

```
CustomUserDetailsService customUserDetailsService;
```

@Override

```
protected void configure(HttpSecurity http) throws Exception {
```

```
    http
```

```
        .authorizeRequests()
```

```
        .antMatchers("/", "/shop/**", "/forgotpassword", "/register"  
, "/h2-console/**").permitAll()
```

```
        .antMatchers("/admin/**").hasRole("ADMIN")
```

```
        .anyRequest()
```

```
        .authenticated()
```

```
        .and()
```

```
        .formLogin()
```

```
        .loginPage("/login")
```

```
        .permitAll()
```

```
        .failureUrl("/login?error=true")
```

```
        .defaultSuccessUrl("/")
```

```
        .usernameParameter("email")
```

```
        .passwordParameter("password")
```

```
        .and()
```

```
        .logout()
```

```
        .logoutRequestMatcher(new  
AntPathRequestMatcher("/logout"))
```

```
        .logoutSuccessUrl("/login")
```

```
        .invalidateHttpSession(true)
```

```
        .deleteCookies("JSESSIONID")
```

```
        .and()
```

```
        .exceptionHandling()
```

```
        .and()
```

```
        .csrf()
```

```
        .disable();
```

```
http.headers().frameOptions().disable();
```

```
}
```

```
@Bean
```

```
public BCryptPasswordEncoder bCryptPasswordEncoder() {  
    return new BCryptPasswordEncoder();  
}
```

```
@Override
```

```
protected void configure(AuthenticationManagerBuilder auth) throws Exception {  
  
    auth.userDetailsService(customUserDetailService);  
  
}
```

```
@Override
```

```
public void configure(WebSecurity web) throws Exception {  
  
    web.ignoring().antMatchers("/resources/**", "/static/**", "/images/**",  
    "/productImages/**", "/css/**", "/js/**")  
    ;  
}
```

```
}
```

File 3: AdminController.java

```
package com.project.sportyshoes.controller;  
  
import java.io.IOException;
```

```
import java.nio.file.Files;

import java.nio.file.Path;

import java.nio.file.Paths;

import java.util.ArrayList;

import java.util.List;

import java.util.Optional;
```

```
import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Controller;

import org.springframework.ui.Model;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.ModelAttribute;

import org.springframework.web.bind.annotation.PathVariable;

import org.springframework.web.bind.annotation.PostMapping;

import org.springframework.web.bind.annotation.RequestParam;

import org.springframework.web.multipart.MultipartFile;
```

```
import com.project.sportyshoes.dto.ProductDTO;

import com.project.sportyshoes.global.PurchaseReport;

import com.project.sportyshoes.model.Category;

import com.project.sportyshoes.model.Product;

import com.project.sportyshoes.model.Purchase;

import com.project.sportyshoes.model.User;

import com.project.sportyshoes.repository.UserRepository;

import com.project.sportyshoes.service.CategoryService;

import com.project.sportyshoes.service.ProductService;
```

```
import com.project.sportyshoes.service.PurchaseService;
```

```
@Controller
```

```
public class AdminController {
```

```
    public static String uploadDir = System.getProperty("user.dir") +  
    "/src/main/resources/static/productImages";
```

```
    @Autowired
```

```
    CategoryService categoryService;
```

```
    @Autowired
```

```
    ProductService productService;
```

```
    @Autowired
```

```
    PurchaseService purchaseService;
```

```
    @Autowired
```

```
    UserRepository userRepository;
```

```
    @GetMapping("/admin")
```

```
    public String adminHome() {
```

```
        return "adminHome";
```

```
    }
```

```
@GetMapping("/admin/categories")

public String getCat(Model model) {

    model.addAttribute("categories" , categoryService.getAllCategories());

    return "categories";

}
```

```
@GetMapping("/admin/categories/add")

public String getCatAdd(Model model) {

    model.addAttribute("category" , new Category());

    return "categoriesAdd";

}
```

```
@PostMapping("/admin/categories/add")

public String postCatAdd(@ModelAttribute("category") Category category) {

    categoryService.addCategory(category);

    return "redirect:/admin/categories";

}
```

```
@GetMapping("/admin/categories/delete/{id}")

public String deleteCat(@PathVariable int id) {

    categoryService.removeCategoryById(id);

    return "redirect:/admin/categories";

}
```

```

@GetMapping("/admin/categories/update/{id}")

public String updateCat(@PathVariable int id , Model model) {

    Optional<Category> category = categoryService.getCatById(id);

    if(category.isPresent()) {

        model.addAttribute("category" , category.get());

        return "categoriesAdd";

    }else {

        return "404";

    }

}

```

// Product Section

```

@GetMapping("/admin/products")

public String showProducts(Model model) {

    model.addAttribute("products" , productService.getAllProducts());

    return "products";

}

@GetMapping("/admin/products/add")

public String addProduct(Model model) {

```



```

        model.addAttribute("productDTO" , new ProductDTO());

        model.addAttribute("categories" , categoryService.getAllCategories());

        return "productsAdd";
    }

```

```

    @PostMapping("/admin/products/add")

```

```

    public String productAddPost(@ModelAttribute ("productDTO") ProductDTO
productDTO ,

```

```

    @RequestParam("productImage") MultipartFile file,

```

```

                                                                    @RequestParam("imgName")
String imgName) throws IOException {

```

```

        Product product = new Product();

```

```

        product.setId(productDTO.getId());

```

```

        product.setName(productDTO.getName());

```

```

        product.setCategory(categoryService.getCatById(productDTO.getCategoryId()).get());

```

```

        product.setPrice(productDTO.getPrice());

```

```

        product.setWeight(productDTO.getWeight());

```

```

        product.setDescription(productDTO.getDescription());

```

```

        String imageUUID;

```

```

        if (!file.isEmpty()) {

```

```

            imageUUID = file.getOriginalFilename();

```

```

            Path fileNameAndPath = Paths.get(uploadDir, imageUUID);

```

```
        Files.write(fileNameAndPath, file.getBytes());
    }else {

        imageUUID = imgName;
    }

    product.setImageName(imageUUID);
    productService.addProduct(product);

    return "redirect:/admin/products";
}

@GetMapping("/admin/product/delete/{id}")
public String deleteProd(@PathVariable long id) {

    productService.removeProductById(id);

    return "redirect:/admin/products";
}

@GetMapping("/admin/product/update/{id}")
public String updateProd(@PathVariable long id , Model model) {

    Product product = productService.getProductById(id).get();
```

```

        ProductDTO productDTO = new ProductDTO();

        productDTO.setId(product.getId());

        productDTO.setName(product.getName());

        productDTO.setCategoryId(product.getCategory().getId());

        productDTO.setPrice(product.getPrice());

        productDTO.setWeight(product.getWeight());

        productDTO.setDescription(product.getDescription());

        productDTO.setImageName(product.getImageName());


        model.addAttribute("productDTO" , productDTO);

        model.addAttribute("categories" , categoryService.getAllCategories());


        return "productsAdd";
    }

    //Purchase Report

    @GetMapping("/admin/purchaseReport")

    public String purchaseReport(Model model) {


        List<Purchase>purchaseList = purchaseService.getAllPurchases();


        List<PurchaseReport>purchaseReportList = new ArrayList<PurchaseReport>();


        for(Purchase pur : purchaseList) {

            Product product = new Product();

```

```

        User user = new User();

        Category category = new Category();

        PurchaseReport purchaseReport = new PurchaseReport();

        Long productId = pur.getProductId();

        int userId = pur.getUserId();


        product = productService.getProductById(productId).get();

        user = userRepository.findById(userId).get();

        category = product.getCategory();


        purchaseReport.setEmail(user.getEmail());

        purchaseReport.setName(user.getFirstName());

        purchaseReport.setProductId(product.getId());

        purchaseReport.setProductName(product.getName());

        purchaseReport.setPrice(product.getPrice());

        purchaseReport.setDate(pur.getOrderDate().toString());

        purchaseReport.setCategory(category.getName());

        //System.out.println(purchaseReport.getEmail() + " " +
purchaseReport.getProductId() + " " + purchaseReport.getDate());


        purchaseReportList.add(purchaseReport);

    }

    model.addAttribute("purchaseList" , purchaseReportList);

    return "purchaseReport";

}

```

```

    @GetMapping("/admin/users")

    public String listUsers(Model model) {

        List<User>userList = userRepository.findAll();

        model.addAttribute("userlist" , userList);


        return "userList";

    }
}

```

File 4: CartController.java

```

package com.project.sportyshoes.controller;

import java.time.LocalDate;
import java.util.ArrayList;
import java.util.List;
import java.util.Random;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.security.core.Authentication;
import org.springframework.security.core.context.SecurityContextHolder;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.PostMapping;

import com.project.sportyshoes.global.GlobalData;
import com.project.sportyshoes.model.Product;
import com.project.sportyshoes.model.Purchase;
import com.project.sportyshoes.model.User;
import com.project.sportyshoes.repository.PurchaseRepository;
import com.project.sportyshoes.repository.UserRepository;
import com.project.sportyshoes.service.ProductService;

@Controller
public class CartController {

    @Autowired
    ProductService productService;

```

```
@Autowired
UserRepository userRepository;
```

```
@Autowired
PurchaseRepository purchaseRepository;
```

```
@GetMapping("/addToCart/{id}")
public String addToCart(@PathVariable int id) {
    GlobalData.cart.add(productService.getProductById(id).get());
    return "redirect:/shop";
}
```

```
@GetMapping("/cart")
public String cartGet(Model model) {
    model.addAttribute("cartCount" , GlobalData.cart.size());
    model.addAttribute("total" ,
GlobalData.cart.stream().mapToDouble(Product::getPrice).sum());
    model.addAttribute("cart" , GlobalData.cart);
    return "cart";
}

}
```

```
@GetMapping("/cart/removeItem/{index}")
public String cartItemRemove(@PathVariable int index) {
    GlobalData.cart.remove(index);
    return "redirect:/cart";
}
```

```
@GetMapping("/checkout")
public String checkout(Model model) {
    model.addAttribute("total" ,
GlobalData.cart.stream().mapToDouble(Product::getPrice).sum());
    return "checkout";
}
```

```
@PostMapping("/payNow")
public String orderConfirmation(Model model) {
    model.addAttribute("total" ,
GlobalData.cart.stream().mapToDouble(Product::getPrice).sum());
    Authentication auth =
SecurityContextHolder.getContext().getAuthentication();
    String currentPrincipalName = auth.getName();

    List<Purchase>purchaseList = new ArrayList<Purchase>();
    //System.out.println(currentPrincipalName);
    User user = userRepository.findUserByEmail(currentPrincipalName).get();
    for(Product product: GlobalData.cart) {
        Purchase purchase = new Purchase();
        //System.out.println(product.getId() + " " + product.getName());
    }
}
```

```

        purchase.setProductId(product.getId());
        purchase.setUserId(user.getId());
        purchase.setOrderDate(LocalDate.now());
        purchaseList.add(purchase);
    }

    int n = 10000 + new Random().nextInt(90000);
    model.addAttribute("Reciept" , n);
    //System.out.println(purchaseList.toString());
    model.addAttribute("products" , GlobalData.cart);
    purchaseRepository.saveAll(purchaseList);

    return "orderPlaced";
}

}

```

File 5: HomeController.java

```

package com.project.sportyshoes.controller;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;

import com.project.sportyshoes.global.GlobalData;
import com.project.sportyshoes.service.CategoryService;
import com.project.sportyshoes.service.ProductService;

@Controller
public class HomeController {

    @Autowired
    CategoryService categoryService;

    @Autowired
    ProductService productService;

    @GetMapping("/{"/" , "/home"})
    public String home(Model model) {
        model.addAttribute("cartCount" , GlobalData.cart.size());
        return "index";
    }

    @GetMapping("/shop")
    public String shop(Model model) {

```

```

        model.addAttribute("cartCount" , GlobalData.cart.size());
        model.addAttribute("categories" , categoryService.getAllCategories());
        model.addAttribute("products" , productService.getAllProducts());

        return "shop";
    }

    @GetMapping("/shop/category/{id}")
    public String shopByCategory(Model model , @PathVariable int id) {
        model.addAttribute("cartCount" , GlobalData.cart.size());
        model.addAttribute("categories" , categoryService.getAllCategories());
        model.addAttribute("products" ,
productService.getAllProductsByCategoryId(id));

        return "shop";
    }

    @GetMapping("/shop/viewproduct/{id}")
    public String viewProduct(Model model , @PathVariable long id) {
        model.addAttribute("product" , productService.getProductById(id).get());
        model.addAttribute("cartCount" , GlobalData.cart.size());
        return "viewProduct";
    }
}

```

File 6: LoginController.java

```

package com.project.sportyshoes.controller;

import java.util.ArrayList;
import java.util.List;

import javax.servlet.ServletException;
import javax.servlet.http.HttpServletRequest;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;

import com.project.sportyshoes.global.GlobalData;
import com.project.sportyshoes.model.Role;
import com.project.sportyshoes.model.User;
import com.project.sportyshoes.repository.RoleRepository;
import com.project.sportyshoes.repository.UserRepository;

```



```

@Controller
public class LoginController {

    @Autowired
    private BCryptPasswordEncoder bCryptPasswordEncoder;

    @Autowired
    UserRepository userRepository;

    @Autowired
    RoleRepository roleRepository;

    @GetMapping("/login")
    public String login() {
        GlobalData.cart.clear();
        return "login";
    }

    @GetMapping("/register")
    public String registerGet() {
        return "register";
    }

    @PostMapping("/register")
    public String registerPost(@ModelAttribute("user") User user , HttpServletRequest
request) throws ServletException {

        String password = user.getPassword();

        user.setPassword(bCryptPasswordEncoder.encode(password));
        List<Role>roles = new ArrayList<Role>();
        roles.add(roleRepository.findById(2).get());
        user.setRoles(roles);
        userRepository.save(user);
        request.login(user.getEmail(), password);
        return "redirect:/";
    }
}

```

File 7: ProductDTO.java

```

package com.project.sportyshoes.dto;

public class ProductDTO {

    private Long id;

```

```
private String name;
private int categoryId;
private double price;
private double weight;
private String description;
private String imageName;

public Long getId() {
    return id;
}

public void setId(Long id) {
    this.id = id;
}

public String getName() {
    return name;
}

public void setName(String name) {
    this.name = name;
}

public int getCategoryId() {
    return categoryId;
}

public void setCategoryId(int categoryId) {
    this.categoryId = categoryId;
}

public double getPrice() {
    return price;
}

public void setPrice(double price) {
    this.price = price;
}

public double getWeight() {
    return weight;
}

public void setWeight(double weight) {
    this.weight = weight;
}

public String getDescription() {
    return description;
}
```

```

        public void setDescription(String description) {
            this.description = description;
        }

        public String getImageName() {
            return imageName;
        }

        public void setImageName(String imageName) {
            this.imageName = imageName;
        }
    }
}

```

File 8: GlobalData.java

```

package com.project.sportyshoes.global;

import java.util.ArrayList;
import java.util.List;

import com.project.sportyshoes.model.Product;

public class GlobalData {

    public static List<Product>cart;

    static {
        cart = new ArrayList<Product>();
    }

}

```

File 9: PurchaseReport.java

```

package com.project.sportyshoes.global;

import org.springframework.stereotype.Component;

@Component
public class PurchaseReport {

    private String email;

    private String name;
}

```

```
private Long productId;

private String productName;

private double price;

private String date;

private String category;

public String getCategory() {
    return category;
}

public void setCategory(String category) {
    this.category = category;
}

public String getEmail() {
    return email;
}

public void setEmail(String email) {
    this.email = email;
}

public String getName() {
    return name;
}

public void setName(String name) {
    this.name = name;
}

public Long getProductId() {
    return productId;
}

public void setProductId(Long productId) {
    this.productId = productId;
}

public String getProductName() {
    return productName;
}

public void setProductName(String productName) {
    this.productName = productName;
}
```

```

        public double getPrice() {
            return price;
        }

        public void setPrice(double price) {
            this.price = price;
        }

        public String getDate() {
            return date;
        }

        public void setDate(String date) {
            this.date = date;
        }
    }
}

```

File 10: Category.java

```

package com.project.sportyshoes.model;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;

@Entity
public class Category {

    @Id
    @GeneratedValue(strategy = GenerationType.AUTO)
    @Column(name = "category_id")
    private int id;

    private String name;

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }
}

```

```

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }
}

```

File 11: CustomUserDetail

```

package com.project.sportyshoes.model;

import java.util.ArrayList;
import java.util.Collection;
import java.util.List;

import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.authority.SimpleGrantedAuthority;
import org.springframework.security.core.userdetails.UserDetails;

public class CustomUserDetail extends User implements UserDetails {

    public CustomUserDetail(User user) {
        super(user);
    }

    @Override
    public Collection<? extends GrantedAuthority> getAuthorities() {

        List<GrantedAuthority> authorityList = new ArrayList<GrantedAuthority>();

        super.getRoles().forEach(role -> {
            authorityList.add(new SimpleGrantedAuthority(role.getName()));
        });

        return authorityList;
    }

    @Override
    public String getPassword() {
        // TODO Auto-generated method stub
        return super.getPassword();
    }

    @Override
    public String getUsername() {
        // TODO Auto-generated method stub

```

```

        return super.getEmail();
    }

    @Override
    public boolean isAccountNonExpired() {
        // TODO Auto-generated method stub
        return true;
    }

    @Override
    public boolean isAccountNonLocked() {
        // TODO Auto-generated method stub
        return true;
    }

    @Override
    public boolean isCredentialsNonExpired() {
        // TODO Auto-generated method stub
        return true;
    }

    @Override
    public boolean isEnabled() {
        // TODO Auto-generated method stub
        return true;
    }
}

```

File 12: Product.java

```

package com.project.sportyshoes.model;

import javax.persistence.Entity;
import javax.persistence.FetchType;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.JoinColumn;
import javax.persistence.ManyToOne;

@Entity
public class Product {

    @Id
    @GeneratedValue(strategy = GenerationType.AUTO)
    private Long id;
}

```

```
private String name;
```

```
@ManyToOne(fetch = FetchType.LAZY)
```

```
@JoinColumn(name = "category_id" , referencedColumnName = "category_id")
```

```
private Category category;
```

```
private double price;
```

```
private double weight;
```

```
private String description;
```

```
private String imageName;
```

```
public Long getId() {  
    return id;  
}
```

```
public void setId(Long id) {  
    this.id = id;  
}
```

```
public String getName() {  
    return name;  
}
```

```
public void setName(String name) {  
    this.name = name;  
}
```

```
public Category getCategory() {  
    return category;  
}
```

```
public void setCategory(Category category) {  
    this.category = category;  
}
```

```
public double getPrice() {  
    return price;  
}
```

```
public void setPrice(double price) {  
    this.price = price;  
}
```

```
public double getWeight() {  
    return weight;  
}
```



```
    }

    public void setWeight(double weight) {
        this.weight = weight;
    }

    public String getDescription() {
        return description;
    }

    public void setDescription(String description) {
        this.description = description;
    }

    public String getImageName() {
        return imageName;
    }

    public void setImageName(String imageName) {
        this.imageName = imageName;
    }
}
```

File 12: Purchase.java

```
package com.project.sportyshoes.model;

import java.time.LocalDate;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;

@Entity

public class Purchase {

    @Id

    @GeneratedValue(strategy = GenerationType.SEQUENCE)

    private long id;

    private int userId;

    private Long productId;

    @Column(name = "order_date")
    private LocalDate orderDate;

    public long getId() {

        return id;

    }

    public void setId(long id) {
```

```
        this.id = id;
    }

    public int getUserId() {
        return userId;
    }

    public void setUserId(int userId) {
        this.userId = userId;
    }

    public Long getProductId() {
        return productId;
    }

    public void setProductId(Long productId) {
        this.productId = productId;
    }

    public LocalDate getOrderDate() {
        return orderDate;
    }

    public void setOrderDate(LocalDate orderDate) {
        this.orderDate = orderDate;
    }
}
```

File 13: Role.java

```
package com.project.sportyshoes.model;

import java.util.List;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.ManyToMany;
import javax.persistence.Table;
import javax.validation.constraints.NotEmpty;

@Entity
@Table(name = "roles")
public class Role {

    @Id
    @GeneratedValue(strategy = GenerationType.AUTO)
    private Integer id;

    @Column(nullable = false , unique = true)
    @NotEmpty
    private String name;

    @ManyToMany(mappedBy = "roles")
    private List<User>users;

    public Integer getId() {
        return id;
    }

    public void setId(Integer id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public List<User> getUsers() {
        return users;
    }
}
```

```

        public void setUsers(List<User> users) {
            this.users = users;
        }
    }
}

```

File 14: User.java

```

package com.project.sportyshoes.model;

import java.util.List;

import javax.persistence.CascadeType;
import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.FetchType;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.JoinColumn;
import javax.persistence.JoinTable;
import javax.persistence.ManyToMany;
import javax.persistence.Table;
import javax.validation.constraints.Email;
import javax.validation.constraints.NotEmpty;

@Entity
@Table(name = "users")
public class User {

    @Id
    @GeneratedValue(strategy = GenerationType.AUTO)
    private Integer id;

    @NotEmpty
    @Column(nullable = false)
    private String firstName;

    private String lastName;

    @NotEmpty
    @Column(nullable = false , unique = true)
    @Email(message = "{errors.invalid_email}")
    private String email;

    private String password;

    @ManyToMany(cascade = CascadeType.MERGE , fetch = FetchType.EAGER)
    @JoinTable(

```

```
        name = "user_role",
        joinColumns = {@JoinColumn( name = "USER_ID" ,
referencedColumnName = "ID" )},
        inverseJoinColumns = {@JoinColumn( name = "ROLE_ID" ,
referencedColumnName = "ID" )}
```

```
    )
    private List<Role>roles;

    public Integer getId() {
        return id;
    }

    public void setId(Integer id) {
        this.id = id;
    }

    public String getFirstName() {
        return firstName;
    }

    public void setFirstName(String firstName) {
        this.firstName = firstName;
    }

    public String getLastName() {
        return lastName;
    }

    public void setLastName(String lastName) {
        this.lastName = lastName;
    }

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) {
        this.email = email;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }
}
```

```

    public List<Role> getRoles() {
        return roles;
    }

    public void setRoles(List<Role> roles) {
        this.roles = roles;
    }

    public User(User user) {
        super();
        this.firstName = user.getFirstName();
        this.lastName = user.getLastName();
        this.email = user.getEmail();
        this.password = user.getPassword();
        this.roles = user.getRoles();
    }

    public User() {}
}

```

File 15: CategoryRepository.java

```

package com.project.sportyshoes.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.sportyshoes.model.Category;

public interface CategoryRepository extends JpaRepository<Category, Integer> {

}

```

File 16: ProductRepository.java

```

package com.project.sportyshoes.repository;

import java.util.List;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.sportyshoes.model.Product;

public interface ProductRepository extends JpaRepository<Product, Long> {

    List<Product> findAllByCategory_Id(int id);
}

```

```
}
```

File 17: PurchaseRepository.java

```
package com.project.sportyshoes.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.sportyshoes.model.Purchase;

public interface PurchaseRepository extends JpaRepository<Purchase, Long> {

}
```

File 18: RoleRepository.java

```
package com.project.sportyshoes.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.sportyshoes.model.Role;

public interface RoleRepository extends JpaRepository<Role, Integer> {

}
```

File 19: UserRepository.java

```
package com.project.sportyshoes.repository;

import java.util.Optional;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.sportyshoes.model.User;

public interface UserRepository extends JpaRepository<User, Integer> {

    Optional<User>findUserByEmail(String email);

}
```



```
}
```

File 20: CategoryService.java

```
package com.project.sportyshoes.service;

import java.util.List;
import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import com.project.sportyshoes.model.Category;
import com.project.sportyshoes.repository.CategoryRepository;

@Service
public class CategoryService {

    @Autowired
    CategoryRepository categoryRepository;

    public List<Category> getAllCategories(){

        return categoryRepository.findAll();

    }

    public void addCategory(Category category) {

        categoryRepository.save(category);

    }

    public void removeCategoryById(int id) {
        categoryRepository.deleteById(id);
    }

    public Optional<Category> getCatById(int id) {

        return categoryRepository.findById(id);

    }

}
```

File 20: CustomUserDetailsService.java

```
package com.project.sportyshoes.service;
```

```

import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.core.userdetails.UsernameNotFoundException;
import org.springframework.stereotype.Service;

import com.project.sportyshoes.model.CustomUserDetail;
import com.project.sportyshoes.model.User;
import com.project.sportyshoes.repository.UserRepository;

@Service
public class CustomUserDetailsService implements UserDetailsService {

    @Autowired
    UserRepository userRepository;

    @Override
    public UserDetails loadUserByUsername(String username) throws
UsernameNotFoundException {

        Optional<User> user = userRepository.findUserByEmail(username);
        user.orElseThrow(() -> new UsernameNotFoundException("User Not
Found"));
        return user.map(CustomUserDetail::new).get();

    }

}

```

File 20: ProductService.java

```

package com.project.sportyshoes.service;

import java.util.List;
import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import com.project.sportyshoes.model.Product;
import com.project.sportyshoes.repository.ProductRepository;

@Service
public class ProductService {

```

```

    @Autowired
    ProductRepository productRepository;

    public List<Product> getAllProducts(){

        return productRepository.findAll();

    }

    public void addProduct(Product product) {

        productRepository.save(product);

    }

    public void removeProductById(long id) {

        productRepository.deleteById(id);

    }

    public Optional<Product> getProductById(long id){
        return productRepository.findById(id);
    }

    public List<Product> getAllProductsByCategoryId(int id){
        return productRepository.findAllByCategory_Id(id);

    }

}

```

File 21: PurchaseService.java

```

package com.project.sportyshoes.service;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import com.project.sportyshoes.model.Purchase;
import com.project.sportyshoes.repository.PurchaseRepository;

@Service
public class PurchaseService {

```

```

@Autowired
PurchaseRepository purchaseRepository;

public List<Purchase> getAllPurchases() {

    return purchaseRepository.findAll();

}

}

```

File 22: SportyshoesApplicationTests.java

```

package com.project.sportyshoes;

import org.junit.jupiter.api.Test;
import org.springframework.boot.test.context.SpringBootTest;

@SpringBootTest
class SportyshoesApplicationTests {

    @Test
    void contextLoads() {

    }

}

```

File 23: adminHome.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
        integrity="sha384-
IZN37f5QGtY3VHgisS14W3ExzMWZxybE1SJSesQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>SportyShoes</title>

```

```

</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
        </li>

        </ul>

      </div>
    </div>
</nav>
<div class="jumbotron text-center">
  <h1 class="display-4">Welcome back, Admin</h1>
  <p>Easily manage your data from this admin <mark>CMS</mark></p>
</div>
<div class="container-fluid">
  <div class="row">
    <div class="col-sm-3 pt-3" >
      <div class="card" style="background-color:white;">
        <div class="card-body">
          <h4 class="card-title">Categories</h4>
          <p class="card-text">Manage the categories section here.</p>
          <a href="#" th:href="@{/admin/categories}" class="card-link btn btn-
primary">Manage</a>
        </div>
      </div>
    </div>
    <div class="col-sm-3 pt-3" >
      <div class="card" style="background-color:white;">
        <div class="card-body">
          <h4 class="card-title">Products</h4>

```

```

        <p class="card-text">Manage all the products here.</p>
        <a href="#" th:href="@{/admin/products}" class="card-link btn btn-
primary">Manage</a>

    </div>
</div>
</div>

<div class="col-sm-3 pt-3" >
    <div class="card" style="background-color:white;">
        <div class="card-body">
            <h4 class="card-title">Registered Users</h4>
            <p class="card-text">See All Registered Users Here.</p>
            <a href="#" th:href="@{/admin/users}" class="card-link btn btn-primary">List
Users</a>

        </div>
    </div>
</div>

<div class="col-sm-3 pt-3" >
    <div class="card" style="background-color:white;">
        <div class="card-body">
            <h4 class="card-title">Purchase Report</h4>
            <p class="card-text">See Purchase Report Here</p>
            <a href="#" th:href="@{/admin/purchaseReport}" class="card-link btn btn-
primary">Purchase Report</a>

        </div>
    </div>
</div>

</div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtm13UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 23: cart.html

```
<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org"
  xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.11.2/css/all.css">

  <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/}" href="#">Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
        </li>
        <li class="nav-item active">
```

```

        <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
    </li>
    <li class="nav-item active">
        <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
    </li>
    <li class="nav-item active">
        <span class="nav-link" th:text="${cartCount}">0</span>
    </li>
</ul>

</div>
</div>
</nav>
<main>
    <div class="container">

        <!--Section: Block Content-->
        <section class="mt-5 mb-4">

            <!--Grid row-->
            <div class="row">

                <!--Grid column-->
                <div class="col-lg-8">

                    <!-- Card -->
                    <div class="card wish-list mb-4">
                        <div class="card-body">

                            <h5 class="mb-4">Cart (<span th:text="${cartCount}">2</span> items)</h5>

                            <div class="row mb-4" th:each="item, iStat : ${cart}">
                                <div class="col-md-5 col-lg-3 col-xl-3">
                                    <div class="mb-3 mb-md-0">
                                        

                                    </div>
                                </div>
                                <div class="col-md-7 col-lg-9 col-xl-9">
                                    <div>
                                        <div class="d-flex justify-content-between">
                                            <div>
                                                <h5 th:text="${item.name}">Blue denim shirt</h5>
                                                <p class="mb-3 text-uppercase small">Weight: <span th:text="${
{item.weight}}"></span> grams</p>
                                            </div>
                                            <div>
                                                <p class="mb-2 text-uppercase small">Category: <span
th:text="${item.category.name}"></span></p>
                                            </div>
                                        </div>
                                    </div>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>
            </div>
        </section>
    </div>
</main>

```



```

        </div>

    </div>
    <div class="mt-5 d-flex justify-content-between align-items-center">
        <div>
            <a href="#" th:href="@{/cart/removeItem/{index}(index=${iStat.index})}" type="button" class="card-link-secondary small text-uppercase mr-3"><i
                class="fas fa-trash-alt mr-1"></i> Remove item </a>

        </div>
        <p class="mb-0"><span><strong>₹<span th:text="$
{item.price}"></span></strong></span></p>
    </div>
</div>
</div>
</div>
<hr class="mb-4">

    <p class="text-primary mb-0"><i class="fas fa-info-circle mr-1"></i> Do not
delay the purchase, adding
    items to your cart does not mean booking them.</p>

</div>
</div>

</div>
<!--Grid column-->

<!--Grid column-->
<div class="col-lg-4">

    <!-- Card -->
    <div class="card mb-4">
        <div class="card-body">

            <h5 class="mb-3">The total amount </h5>

            <ul class="list-group list-group-flush">
                <li class="list-group-item d-flex justify-content-between align-items-center
border-0 px-0 pb-0">
                    Amount Payable
                    <span>₹<span th:text="$ {total}"></span></span>
                </li>
                <li class="list-group-item d-flex justify-content-between align-items-center px-
0">
                    Shipping
                    <span>Gratis</span>

```

```

        </li>
        <li class="list-group-item d-flex justify-content-between align-items-center
border-0 px-0 mb-3">
            <div>
                <strong>The total amount of</strong>
                <strong>
                    <p class="mb-0">(including VAT)</p>
                </strong>
            </div>
            <span><strong>₹<span th:text="{total}"></span></strong></span>
        </li>
    </ul>

    <a th:href="@{/checkout}" h class="btn btn-primary btn-block waves-effect
waves-light">go to
        checkout</a>

</div>
</div>
<!-- Card -->

<!-- Card -->
<div class="card mb-4">
    <div class="card-body">

        <a class="dark-grey-text d-flex justify-content-between" data-toggle="collapse"
href="#collapseExample"
            aria-expanded="false" aria-controls="collapseExample">
                Add a discount code (optional)
                <span><i class="fas fa-chevron-down pt-1"></i></span>
            </a>

            <div class="collapse" id="collapseExample">
                <div class="mt-3">
                    <div class="md-form md-outline mb-0">
                        <input type="text" id="discount-code" class="form-control font-weight-
light"
                            placeholder="Enter discount code">
                    </div>
                </div>
            </div>
        </div>
    </div>
<!-- Grid column-->

</div>
<!--Grid row-->

```

```

    </section>
    <!--Section: Block Content-->

  </div>
</main>
<!--Main layout-->

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 24: categories.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhvx8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
    integrity="sha384-
IZN37f5QGtY3VHgisS14W3ExzMWZxybE1SJSesQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
  <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      

```

```

SportyShoes.com
</a>
<button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
  <span class="navbar-toggler-icon"></span>
</button>

<div class="collapse navbar-collapse" id="navbarSupportedContent">
  <ul class="navbar-nav mr-auto"></ul>
  <ul class="navbar-nav">
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>
    </li>
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
    </li>
  </ul>

</div>
</div>
</nav>
<div class="container">

  <a th:href="@{/admin/categories/add}" style="margin: 20px 0" class="btn btn-primary">Add
Category</a>
  <table class="table">
    <thead class="thead-light">
      <tr>
        <th scope="col">SN</th>
        <th scope="col">Category Name</th>
        <th scope="col">Delete</th>
        <th scope="col">Update</th>
      </tr>
    </thead>
    <tbody>

    <tr th:each="category, iStat : ${categories}">
      <th scope="row" th:text="${iStat.index + 1}">1</th>
      <td th:text="${category.name}">Larry</td>

      <td><a href="" th:href="@{/admin/categories/delete/{id}(id=${category.id})}"
class="btn btn-danger">Delete</a></td>
      <td><a href="" th:href="@{/admin/categories/update/{id}(id=${category.id})}"
class="btn btn-warning">Update</a></td>

    </tr>
    </tbody>
  </table>
</div>

```

```

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 25: categoriesAdd.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
    integrity="sha384-
IZN37f5QGtY3VHgisS14W3ExzMWZxybE1SJSesQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
  <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

```

```

<div class="collapse navbar-collapse" id="navbarSupportedContent">
  <ul class="navbar-nav mr-auto"></ul>
  <ul class="navbar-nav">
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>
    </li>
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
    </li>
  </ul>
</div>
</div>
</nav>
<div class="container">
  <div class="row">
    <div class="col-sm-4">
      <form th:action="@{/admin/categories/add}" method="post" th:object="${category}">
        <input type="hidden" name="id" th:field="*{id}">
        <div class="form-group">
          <label for="name">Name</label>
          <input type="text" class="form-control" required th:field="*{name}" name="name"
id="name" placeholder="Enter name">
        </div>
        <button type="submit" class="btn btn-primary">Submit</button>
      </form>
    </div>
  </div>
</div>
<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj003uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 27: checkout.html

```
<!doctype html>
```

```

<html lang="en" xmlns:th="http://www.thymeleaf.org"
  xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.11.2/css/all.css">

  <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/}" href="#">Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
        </li>
        <li class="nav-item active">

```

```

        <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
    </li>
    <li class="nav-item active">
        <span class="nav-link" th:text="${cartCount}">0</span>
    </li>
</ul>

</div>
</div>
</nav>
<div class="container">

    <!--Section: Block Content-->
    <section class="mt-5 mb-4">

        <!--Grid row-->
        <div class="row">

            <!--Grid column-->
            <div class="col-lg-8 mb-4">

                <!-- Card -->
                <div class="card wish-list pb-1">
                    <div class="card-body">

                        <h5 class="mb-2">Billing details</h5>

                        <!-- Grid row -->
                        <div class="row">

                            <!-- Grid column -->
                            <div class="col-lg-6">

                                <!-- First name -->
                                <div class="md-form md-outline mb-0 mb-lg-4">
                                    <label for="firstName">First name</label>
                                    <input type="text" id="firstName" required class="form-control mb-0 mb-
lg-2">

                                </div>

                            </div>

                        </div>

                            <!-- Grid column -->
                            <div class="col-lg-6">

                                <!-- Last name -->
                                <div class="md-form md-outline">
                                    <label for="lastName">Last name</label>
                                    <input type="text" id="lastName" required class="form-control">

                                </div>

                            </div>

                        </div>

```



```

        </div>
        <!-- Grid column -->

</div>
<!-- Grid row -->

<!-- Country -->
<div class="d-flex flex-wrap">
    <div class="select-outline position-relative w-100">
        <label>Country - <strong>INDIA</strong></label>

    </div>
</div>

<!-- Address Part 1 -->
<div class="md-form md-outline mt-2">
    <label for="form14">Address (Line 1)</label>
    <input type="text" required id="form14" placeholder="House number and street
name" class="form-control">
</div>

<!-- Address Part 2 -->
<div class="md-form md-outline mt-2">
    <label for="form15">Address (Line 2)</label>
    <input type="text" id="form15" placeholder="Apartment, suite, unit etc.
(optional)"
        class="form-control">
</div>

<!-- Postcode / ZIP -->
<div class="md-form md-outline mt-3">
    <label for="form16">Postcode / ZIP</label>
    <input type="text" maxlength="6" minlength="6" required id="form16"
class="form-control">
</div>

<!-- Town / City -->
<div class="md-form md-outline mt-2">
    <label for="form17">Town / City</label>
    <input type="text" required id="form17" class="form-control">

</div>

<!-- Phone -->
<div class="md-form md-outline mt-2">
    <label for="form18">Phone</label>

```

```

        <input type="number" minlength="10" maxlength="10" required id="form18"
class="form-control">
    </div>

    <!-- Email address -->
    <div class="md-form md-outline mt-2">
        <label for="form19">Email address</label>
        <input type="email" required id="form19" class="form-control">
    </div>

    <!-- Additional information -->
    <div class="md-form md-outline mt-2">
        <label for="form76">Additional information</label>
        <textarea id="form76" class="md-textarea form-control" rows="4"></textarea>
    </div>

    </div>
</div>
<!-- Card -->

</div>
<!--Grid column-->

<!--Grid column-->
<div class="col-lg-4">

    <!-- Card -->
    <div class="card mb-4">
        <div class="card-body">

            <h5 class="mb-3">The total amount </h5>

            <ul class="list-group list-group-flush">
                <li class="list-group-item d-flex justify-content-between align-items-center
border-0 px-0 pb-0">
                    Amount Payable
                    <span>₹<span th:text="{total}"></span></span>
                </li>
                <li class="list-group-item d-flex justify-content-between align-items-center px-
0">
                    Shipping
                    <span>Gratis</span>
                </li>
                <li class="list-group-item d-flex justify-content-between align-items-center
border-0 px-0 mb-3">
                    <div>
                        <strong>The total amount of</strong>
                        <strong>
                            <p class="mb-0">(including VAT)</p>

```

```

        </strong>
      </div>
      <span><strong>₹<span th:text="{total}"></span></strong></span>
    </li>
  </ul>

  <form action="" method="post" th:action="@{/payNow}" >
    <button type="submit" class="btn btn-primary btn-block waves-effect waves-
light">Pay Now</button>
  </form>

</div>
</div>
<!-- Card -->

<!-- Card -->
<div class="card mb-4">
  <div class="card-body">

    <a class="dark-grey-text d-flex justify-content-between" data-toggle="collapse"
href="#collapseExample"
    aria-expanded="false" aria-controls="collapseExample">
      Add a discount code (optional)
      <span><i class="fas fa-chevron-down pt-1"></i></span>
    </a>

    <div class="collapse" id="collapseExample">
      <div class="mt-3">
        <div class="md-form md-outline mb-0">
          <input type="text" id="discount-code" class="form-control font-weight-
light"
            placeholder="Enter discount code">
        </div>
      </div>
    </div>
  </div>
</div>
<!-- Card -->

</div>
<!--Grid column-->

</div>
<!--Grid row-->

</section>
<!--Section: Block Content-->

</div>

```

```

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
j6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtm13UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 28: index.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org"
  xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
    integrity="sha384-
IZN37f5QGTy3VHgIS14W3ExzMWZxybE1SJSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
  <title>Sporty Shoes</title>

  <style th:inline="text">

    header {
      height: 90vh;
      background-image: linear-gradient(rgba(0, 0, 0, .4), rgba(0, 0, 0, .6)),
url([[@{/images/header.jpg}]]);
      background-position: center;
      background-size: cover;
      background-attachment: fixed;
      background-repeat: no-repeat;
    }

```

```

    .foot {
    position: fixed;
    left: 0;
    bottom: 0;
    width: 100%;
    background-color: rgb(186, 144, 238);
    color: black ;
    text-align: center;
    }

</style>

</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/}" href="#">Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
        </li>
        <li class="nav-item active">

```

```

        <span class="nav-link" th:text="{cartCount}">0</span>
    </li>
</ul>

</div>
</div>
</nav>
<header class="d-flex align-items-center pt-2 mt-2">
    <div class="container">

        <div class="row">
            <div class="col text-center">
                <h3
                    class="text-uppercase font-weight-bold display-4 text-light banner-
heading">Welcome
                    to sportyshoes.com </h3>
                <h3 class="display-4 text-light banner-heading pt-3 pb-4">Get the Style that suits
you the best</h3>
                <a th:href="@{/shop}" href="#"
                    class="btn btn-lg btn-outline-primary text-uppercase px-5">
                    Click to Buy Shoes</a>
            </div>
        </div>
    </div>
</header>
<div class="foot">
    <p>SportyShoes Ltd. All Rights Reserved. This Website is developed by Ashraf M. Husain
@2023</p>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtml3UksdQVRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 29: login.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">

```

```

    <meta name="viewport"
      content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhvx8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
      integrity="sha384-
IZN37f5QGtY3VHgisS14W3ExzMWZxybE1SJSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/}" href="#">Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" href="#">Sign Up</a>
        </li>

      </ul>

    </div>
  </div>
</nav>
<div class="container">
  <div class="row">

```



```

        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.11.2/css/all.css">

    <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
    <div class="container-fluid">
        <a class="navbar-brand" href="#">
            
            SportyShoes.com
        </a>
        <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
            <span class="navbar-toggler-icon"></span>
        </button>

        <div class="collapse navbar-collapse" id="navbarSupportedContent">
            <ul class="navbar-nav mr-auto"></ul>
            <ul class="navbar-nav">
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/}" href="#">Home</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
                </li>
                <!--
                <li class="nav-item active">-->
                <!--
                <span class="nav-link" th:text="${cartCount}">0</span>-->
                <!--
                </li>-->
            </ul>
        </div>
    </div>
</nav>

```



```

        </div>
    </div>
</div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtmI3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 31: products.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">

    <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
    <div class="container-fluid">
        <a class="navbar-brand" href="#">
            
            SportyShoes.com
        </a>
        <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">

```

```

        <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
        <ul class="navbar-nav mr-auto"></ul>
        <ul class="navbar-nav">
            <li class="nav-item active">
                <a class="nav-link" th:href="@{/admin}" href="#">Admin-HOme</a>
            </li>
            <li class="nav-item active">
                <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
            </li>

        </ul>

    </div>
</div>
</nav>
<div class="container-fluid">

    <a th:href="@{/admin/products/add}" style="margin: 20px 0" class="btn btn-primary">Add
Product</a>
    <table class="table">
        <thead class="thead-light">
            <tr>
                <th scope="col">SN</th>
                <th scope="col">Product Name</th>
                <th scope="col">Category</th>
                <th scope="col">Preview</th>
                <th scope="col">Delete</th>
                <th scope="col">Update</th>
            </tr>
        </thead>
        <tbody>

            <tr th:each="product, iStat : ${products}">
                <th scope="row" th:text="${iStat.index + 1}">1</th>
                <td th:text="${product.name}">Larry</td>
                <td th:text="${product.category.name}">Larry</td>
                <td></td>

                <td><a href="" th:href="@{/admin/product/delete/{id}(id=${product.id})}" class="btn
btn-danger">Delete</a></td>
                <td><a href="" th:href="@{/admin/product/update/{id}(id=${product.id})}" class="btn
btn-warning">Update</a></td>

            </tr>
        </tbody>
    </table>
</div>

```

```

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 32: productsAdd.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
    integrity="sha384-
IZN37f5QGtY3VHgIS14W3ExzMWZxybE1SJSesQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
  <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light">
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent"
      aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle
navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

```

```

<div class="collapse navbar-collapse" id="navbarSupportedContent">
  <ul class="navbar-nav mr-auto"></ul>
  <ul class="navbar-nav">
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>
    </li>
    <li class="nav-item active">
      <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
    </li>
  </ul>
</div>
</div>
</nav>
<div class="container">
  <h3>Add a new Product</h3>
  <form th:action="@{/admin/products/add}" method="post" th:object="${productDTO}"
  enctype="multipart/form-data">
    <div class="row">
      <div class="col-sm-5">

        <input type="hidden" name="id" th:field="*{id}">
        <div class="form-group">
          <label for="name">Name</label>
          <input type="text" class="form-control" required th:field="*{name}" name="name"
id="name"
          placeholder="Enter name">
        </div>
        <div class="form-group">
          <label for="category">Select Category</label>
          <select class="form-control" th:field="*{categoryId}" id="category"
name="category">
            <option th:each="category :${categories}"
              th:value="${category.id}"
              th:text="${category.name}"
            >
          </select>
        </div>
        <div class="form-group">
          <label for="price">Price</label>
          <input type="number" class="form-control" required th:field="*{price}"
name="price" id="price"
          placeholder="Price">
        </div>
        <div class="form-group">
          <label for="weight">Weight in grams</label>
          <input type="number" class="form-control" required th:field="*{weight}"
name="weight" id="weight"
          placeholder="Weight">

```

```

        </div>
        <div class="form-group">
            <label for="description">Product Description</label>
            <textarea class="form-control" rows="5" th:field="*{description}"
name="description" id="description"></textarea>
        </div>
    </div>
    <div class="col-sm-5">
        <p>Product Image</p>
        <div class="custom-file">
            <input type="file" class="custom-file-input" name="productImage"
accept="image/jpeg, image/png" id="productImage"/>
            <label class="custom-file-label" for="productImage">Choose file</label>
        </div>
        <div class="form-group">
            
        </div>
        <input type="hidden" name="imgName" th:value="${productDTO.imageName}">
        <button type="submit" class="btn btn-primary">Submit</button>
    </div>
</div>
</form>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js"
    integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
    crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
    integrity="sha384-
Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtmI3UksdQRVvoxMfooAo"
    crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
    integrity="sha384-
wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
    crossorigin="anonymous"></script>
<script>
    function readURL(input){
        if(input.files && input.files[0]){
            var reader = new FileReader();
            reader.onload = function(e){
                $('#imgPreview').attr('src', e.target.result).width(100).height(100);
            }
            reader.readAsDataURL(input.files[0])
        }
    }
    $('#productImage').change(function(){
        readURL(this);
    });

```

```

$(".custom-file-input").on("change", function() {
    var fileName = $(this).val().split("\\").pop();
    $(this).siblings(".custom-file-label").addClass("selected").html(fileName);
});
</script>
</body>
</html>

```

File 33: purchaseReport.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet" href="https://cdn.datatables.net/1.10.24/css/jquery.dataTables.min.css"
/>
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
        integrity="sha384-
IZN37f5QGTy3VHgIS14W3ExzMWZxybE1SJSesQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
    <div class="container-fluid">
        <a class="navbar-brand" href="#">
            
            SportyShoes.com
        </a>
        <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
            <span class="navbar-toggler-icon"></span>
        </button>

        <div class="collapse navbar-collapse" id="navbarSupportedContent">
            <ul class="navbar-nav mr-auto"></ul>
            <ul class="navbar-nav">
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>

```



```

        </li>
        <li class="nav-item active">
            <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
        </li>

    </ul>

</div>
</div>
</nav>
<div class="container">
    <div class="row">
        <div class="well col-xs-10 col-sm-10 col-md-10 col-xs-offset-1 col-sm-offset-1 col-md-offset-
3">

        <div class="row">
            <div class="text-center">
                <h1>Purchase Report</h1>
            </div>

            <table id="purchaseReport" class="table table-hover">
                <thead>
                    <tr>
                        <th scope="col">SN</th>
                        <th scope="col">User Email</th>
                        <th scope="col">User Name</th>
                        <th scope="col">Product Id</th>
                        <th scope="col">Category</th>
                        <th scope="col">Product Name</th>
                        <th scope="col">Product Price</th>
                        <th scope="col">Order Date</th>
                    </tr>
                </thead>
                <tbody>

                    <tr th:each="purchase, iStat : ${puchaseList}">
                        <th scope="row" th:text="${iStat.index + 1}">1</th>
                        <td th:text="${purchase.email}">Larry</td>
                        <td th:text="${purchase.name}">Larry</td>
                        <td th:text="${purchase.productId}">Larry</td>
                        <td th:text="${purchase.category}">Larry</td>
                        <td th:text="${purchase.productName}">Larry</td>
                        <td th:text="${purchase.price}">Larry</td>
                        <td th:text="${purchase.date}">Larry</td>

                    </tr>
                </tbody>
            </table>

        </div>
    </div>

```

```

        </div>
    </div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEwdlVL9IOWy5n3zV9zzTtml3UksdQVRvvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj003uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
<script src="https://cdn.datatables.net/1.10.24/js/jquery.dataTables.min.js"></script>
<script>
$(document).ready(function () {
    $('#purchaseReport').dataTable({
        "lengthMenu": [5, 7, 10, 12, 15, 20],
        "ordering": false
    });
    $('.dataTables_length').addClass('bs-select');
});
</script>
</body>
</html>

```

File 34: register.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
        integrity="sha384-
IZN37f5QGtY3VHgIsS14W3ExzMWZxybE1SJSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>Sporty Shoes</title>
</head>

```

```

<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/}" href="#">Home</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
        </li>
        <li class="nav-item active">
          <a class="nav-link" href="#">Sign Up</a>
        </li>

      </ul>

    </div>
  </div>
</nav>
<div class="container">
  <div class="col-sm-6">
    <h3 style="margin-top: 10px">Sign Up Now</h3>
    <p>Please fill out this to register</p>
    <form th:action="@{/register}" th:object="${user}" method="post">
      <div class="form-group">
        <label for="firstName">First Name</label>
        <input type="text" name="firstName" id="firstName" required placeholder="Your
Firstname" class="form-control form-control-lg">
      </div>
      <div class="form-group">
        <label for="lastName">Last Name</label>
        <input type="text" name="lastName" id="lastName" required placeholder="Your
Lastname" class="form-control form-control-lg">
      </div>
      <div class="form-group">
        <label for="email">Email address</label>

```

```

        <input type="email" class="form-control form-control-lg" required minlength="6"
placeholder="Email" name="email" id="email"
        aria-describedby="emailHelp">
        <small id="emailHelp" class="form-text text-muted">We'll never share your email with
        anyone else.</small>
    </div>
    <div class="form-group">
        <label for="password">Password</label>
        <input type="password" class="form-control form-control-lg" required
placeholder="Password" name="password"
        id="password">
    </div>

    <input type="submit" value="Register" class="btn btn-primary btn-block">
    <span style="margin-top: 10px">Already have an account <a class="linkControl"
href="/login.html"
                                th:href="@{/login}">Login here</a></span>

    </form>
</div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEwdlVL9IOWy5n3zV9zzTtm13UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 35: shop.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org"
        xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">

```

```

    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"

integrity="sha384-Vkoo8x4CGsO3+Hhvx8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
        integrity="sha384-
IZN37f5QGTy3VHgisS14W3ExzMWZxybE1SJSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light" >
    <div class="container-fluid">
        <a class="navbar-brand" href="#">
            
            SportyShoes.com
        </a>
        <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
            <span class="navbar-toggler-icon"></span>
        </button>

        <div class="collapse navbar-collapse" id="navbarSupportedContent">
            <ul class="navbar-nav mr-auto"></ul>
            <ul class="navbar-nav">
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/}" href="#">Home</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
                </li>
                <li class="nav-item active">
                    <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
                </li>
                <li class="nav-item active">
                    <span class="nav-link" th:text="{cartCount}">0</span>
                </li>
            </ul>

```

```

    </div>
  </div>
</nav>
<div class="container" style="margin-top: 30px">
  <div class="row">
    <div class="col-sm-3">
      <h4>Categories</h4>
      <ul class="list-group">
        <a th:href="@{/shop}"><li class="list-group-item">All Products</li></a>
        <a href="" th:each="category, iStat : ${categories}"
          th:href="@{/shop/category/{id}(id=${category.id})}"><li
            class="list-group-item" th:text="${category.name}"></li></a>

      </ul>
    </div>
    <div class="col-sm-9">
      <div class="card" style="margin-top: 20px" th:each="product : ${products}">
        <div class="row no-gutters">
          <div class="col-sm-5 d-flex justify-content-center">
            
          </div>
          <div class="col-sm-7 d-flex justify-content-center">
            <div class="card-body">
              <h5 class="card-title" th:text="${product.name}"></h5>
              <h4>₹ <span th:text="${product.price}"></span></h4>
              <p th:text="${product.description}" >Suresh Dasari is a founder and technical
lead developer in tutlane.</p>
              <a href="#" th:href="@{/shop/viewproduct/{id}(id=${product.id})}" class="btn
btn-primary">View Product</a>
            </div>
          </div>
        </div>
      </div>
    </div>
  </div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEwidl9IOYy5n3zV9zzTtml3UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>

```

```

<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
</body>
</html>

```

File 36: userList.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <link rel="stylesheet" href="https://cdn.datatables.net/1.10.24/css/jquery.dataTables.min.css"
/>
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
    integrity="sha384-
IZN37f5QGtY3VHgisS14W3ExzMWZxybE1SJSSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
  <title>Sporty Shoes</title>
</head>
<body>
<nav class="navbar navbar-expand-lg navbar-light bg-light" >
  <div class="container-fluid">
    <a class="navbar-brand" href="#">
      
      SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto"></ul>
      <ul class="navbar-nav">
        <li class="nav-item active">
          <a class="nav-link" th:href="@{/admin}" href="#">Admin-Home</a>
        </li>
        <li class="nav-item active">

```

```

        <a class="nav-link" th:href="@{/logout}" href="#">Logout</a>
    </li>

</ul>

</div>
</div>
</nav>
<div class="container">
    <div class="row">
        <div class="well col-xs-10 col-sm-10 col-md-10 col-xs-offset-1 col-sm-offset-1 col-md-offset-
3">

            <div class="row">

                <table id="userReport" class="table table-hover mt-3 pt-3">
                    <thead>
                        <tr>
                            <th scope="col">SN</th>
                            <th scope="col">User Id</th>
                            <th scope="col">Email</th>
                            <th scope="col">First Name</th>
                            <th scope="col">Last Name</th>
                        </tr>
                    </thead>
                    <tbody>

                        <tr th:each="user, iStat : ${userlist}">
                            <th scope="row" th:text="${iStat.index + 1}">1</th>
                            <td th:text="${user.id}">Larry</td>
                            <td th:text="${user.email}">Larry</td>
                            <td th:text="${user.firstName}">Larry</td>
                            <td th:text="${user.lastName}">Larry</td>

                        </tr>
                    </tbody>
                </table>

            </div>
        </div>
    </div>
</div>
</div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
crossorigin="anonymous"></script>

```



```

<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
integrity="sha384-Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtm13UksdQRVvoxMfooAo"
crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
integrity="sha384-wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Hh7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
crossorigin="anonymous"></script>
<script src="https://cdn.datatables.net/1.10.24/js/jquery.dataTables.min.js"></script>
<script>
$(document).ready(function () {
    $('#userReport').dataTable({
        "lengthMenu": [5, 7, 10, 12, 15, 20],
        "ordering": false
    });
    $('.dataTables_length').addClass('bs-select');
});
</script>

</body>
</html>

```

File 37: viewProduct.html

```

<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org"
    xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css"
integrity="sha384-Vkoo8x4CGsO3+Hhxv8T/Q5PaXtkKtu6ug5TOeNV6gBiFeWPGFN9MuhOf23Q9Ifjh"
crossorigin="anonymous">
    <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.0/css/all.css"
        integrity="sha384-
IZN37f5QGtY3VHgIsS14W3ExzMWZxybE1SJSEsQp9S+oqd12jhcu+A56Ebc1zFSJ"
crossorigin="anonymous">
    <title>Sporty Shoes</title>
</head>
<body>

<nav class="navbar navbar-expand-lg navbar-light bg-light">
    <div class="container-fluid">
        <a class="navbar-brand" href="#">

```

```

        
        SportyShoes.com
    </a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent"
        aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle
navigation">
        <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
        <ul class="navbar-nav mr-auto"></ul>
        <ul class="navbar-nav">
            <li class="nav-item active">
                <a class="nav-link" th:href="@{/}" href="#">Home</a>
            </li>
            <li class="nav-item active">
                <a class="nav-link" th:href="@{/shop}" href="#">Shop</a>
            </li>
            <li class="nav-item active">
                <a class="nav-link" sec:authorize="isAnonymous()" th:href="@{/login}"
href="#">Login</a>
            </li>
            <li class="nav-item active">
                <a class="nav-link" sec:authorize="isAuthenticated()" th:href="@{/logout}"
href="#">Logout</a>
            </li>
            <li class="nav-item active">
                <a class="nav-link" th:href="@{/cart}" href="#">Cart</a>
            </li>
            <li class="nav-item active">
                <span class="nav-link" th:text="${cartCount}"></span>
            </li>
        </ul>

    </div>
</div>
</nav>
<div class="container mt-5">
    <div class="row">
        <div class="col-sm-5 d-flex justify-content-center">
            
        </div>
        <div class="col-sm-7 mt-5">
            <h2 th:text="${product.name}"></h2>
            <p th:text="${product.category.name}"></p>
            <h2>₹ <span th:text="${product.price}"></span></h2>
            <h5>Weight:

```

```

        <span th:text="${product.weight}"></span> grams.
    </h5>
    <p th:text="${product.description}"></p>
    <a href="" th:href="@{/addToCart/{id}(id = ${product.id})}" class="btn btn-
primary">Add to cart</a>
    </div>
</div>
</div>

<script src="https://code.jquery.com/jquery-3.4.1.slim.min.js"
    integrity="sha384-
J6qa4849bIE2+poT4WnyKhv5vZF5SrPo0iEjwBvKU7imGFAV0wwj1yYfoRSJoZ+n"
    crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
    integrity="sha384-
Q6E9RHvblyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtmI3UksdQRVvoxMfooAo"
    crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js"
    integrity="sha384-
wfSDF2E50Y2D1uUdj0O3uMBJnjuUD4Ih7YwaYd1iqfktj0Uod8GCExl3Og8ifwB6"
    crossorigin="anonymous"></script>
</body>
</html>

```

File 37: application.properties

```
spring.h2.console.enabled=true
```

```
spring.datasource.url=jdbc:h2:file:./db
spring.datasource.driverClassName=org.h2.Driver
spring.datasource.username=sa
spring.datasource.password=
```

```
spring.jpa.database-platform=org.hibernate.dialect.H2Dialect
spring.jpa.hibernate.ddl-auto=update
```

```
server.port=8080
```

```
spring.jpa.properties.hibernate.jdbc.batch_size=100
```

File 38: pom.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"

```

```

    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>2.5.0</version>
        <relativePath /> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.project</groupId>
    <artifactId>sportyshoes</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>sportyshoes</name>
    <description>Spring boot E-Commerce Application</description>

    <dependencies>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-data-jpa</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-oauth2-client</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-security</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-thymeleaf</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>
        <dependency>
            <groupId>com.h2database</groupId>
            <artifactId>h2</artifactId>
            <scope>runtime</scope>
        </dependency>
        <dependency>
            <groupId>org.thymeleaf.extras</groupId>
            <artifactId>thymeleaf-extras-springsecurity5</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-devtools</artifactId>
            <scope>runtime</scope>

```

```

        <optional>true</optional>
    </dependency>
    <dependency>
        <groupId>org.projectlombok</groupId>
        <artifactId>lombok</artifactId>
        <optional>true</optional>
    </dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-test</artifactId>
        <scope>test</scope>
    </dependency>
    <dependency>
        <groupId>org.springframework.security</groupId>
        <artifactId>spring-security-test</artifactId>
        <scope>test</scope>
    </dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-validation</artifactId>
    </dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-configuration-processor</artifactId>
        <optional>true</optional>
    </dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
            <configuration>
                <excludes>
                    <exclude>
                        <groupId>org.projectlombok</groupId>
                        <artifactId>lombok</artifactId>
                    </exclude>
                    <exclude>
                        <groupId>org.springframework.boot</groupId>
                        <artifactId>spring-boot-configuration-processor</artifactId>
                    </exclude>
                </excludes>
            </configuration>
        </plugin>
    </plugins>
</build>

```

```
        <plugin>
          <artifactId>maven-compiler-plugin</artifactId>
          <configuration>
            <source>12</source>
            <target>12</target>
          </configuration>
        </plugin>
      </plugins>
    </build>
  </project>
```

