

# HTML Notes – Section 1: Document Structure

## <!DOCTYPE html>

**Explanation:** Declares document type. Ensures browser uses HTML5 standard mode (not quirks mode).

**Attributes:** None

**Attribute explanation:**

No attributes.

**Code snippet:**

```
<!DOCTYPE html>
<html>
  <head>
    <title>Doctype Example</title>
  </head>
  <body>
    <p>This page is using HTML5 doctype.</p>
  </body>
</html>
```

## <html>

**Explanation:** Root element that contains the entire document. Must wrap and .

**Attributes:** lang, dir, id, class, title, data-\*

**Attribute explanation:**

lang: Document language (e.g., en, hi).

dir: Text direction (ltr or rtl).

id: Unique identifier.

class: Grouping/styling.

title: Tooltip text.

data-\*: Custom data attributes.

**Code snippet:**

```
<!DOCTYPE html>
<html lang="en" dir="ltr">
  <head>
    <title>HTML Tag Example</title>
  </head>
  <body>
    <p>The root element defines the whole document.</p>
  </body>
</html>
```

## <head>

**Explanation:** Contains metadata (information about the page). Not displayed directly to users.

**Attributes:** id, class, title, data-\*

**Attribute explanation:**

Global attributes are rarely used here, but possible (id, class, title, data-\*).

**Code snippet:**

```
<!DOCTYPE html>
<html>
  <head>
    <title>Head Example</title>
    <meta charset="UTF-8">
  </head>
  <body>
    <p>Head section contains metadata only.</p>
```

```
</body>
</html>
```

## <title>

**Explanation:** Defines the title of the page (shown on browser tab & in search engine results). Must be inside .

**Attributes:** id, class, title, data-\*

**Attribute explanation:**

Typically no attributes are needed here except optional global ones.

**Code snippet:**

```
<!DOCTYPE html>
<html>
<head>
  <title>My Awesome Page</title>
</head>
<body>
  <p>The title is visible on the browser tab.</p>
</body>
</html>
```

## <body>

**Explanation:** Contains all visible content of the page (headings, paragraphs, images, links, etc.).

**Attributes:** onload, onunload, id, class, title, style, data-\*

**Attribute explanation:**

onload: Run script when page finishes loading.

onunload: Run script when page is closed.

style: Inline CSS styling.

id, class, title, data-\*: Global attributes for styling and scripting.

**Code snippet:**

```
<!DOCTYPE html>
<html>
<head>
  <title>Body Example</title>
</head>
<body onload="alert('Page loaded!')">
  <h1>Welcome!</h1>
  <p>This is content inside the body.</p>
</body>
</html>
```