



BBPS COU API Specification Document for Bank of Baroda

Version - 4.0.0



 www.iserveu.in

 Bhubaneswar
Bangalore
Mumbai

Document Revision History

Version	Date	Version Description	Approving Authority
1.0.0	18 APR 2025	Initial Draft	Product Manager
2.0.0	19 MAY 2025	Document Standardization - 1. Favorite Biller API details added. 2. Fetch and Pay API updated.	Product Manager
2.1.0	20 MAY 2025	Document Modification - 1. All Fetch APIs updated.	Product Manager
3.0.0	27 MAY 2025	Document Modification 1. Base URL updated.	Product Manager
3.1.0	09 JUL 2025	Document Standardization 1. Oneview API details added.	Product Manager
3.2.0	19 AUG 2025	Document Standardization. 1. Endpoints are updated.	Product Manager
4.0.0	24 FEB 2026	Document Standardization. 1. Fetch Prepaid Plans API added. 2. Feature-phone channel details added.	Product Manager

Disclaimer

- This document is the intellectual property of iServeU Technology Private Limited and should solely be used as a tool of knowledge exchange. We discourage any reproduction of the document under any circumstances.
- All the values corresponding to all the fields in the document are dummy data. Any resemblance with any real life data is purely coincidental. The data provided in the Request and Response Payloads are sample data. We encourage usage of own sample data for desired results.

Table of Contents

1	Introduction	5
1.1	Base URL(UAT)	5
2	Headers and Authentication	6
2.1	Request Header Attributes	6
2.2	HMAC Request Signature.....	6
2.3	Response Header Attributes	7
2.4	HMAC Response Signature.....	8
3	Generate Biller List File API	10
3.1	Headers	10
3.2	Request Body Parameters.....	10
3.3	Sample Request Body.....	11
3.4	Response Body Parameters.....	11
3.5	Sample Response Body.....	11
4	Get Biller Master File	12
4.1	Headers	12
4.2	Response Body Parameters.....	12
4.3	Sample Response Body.....	13
5	Fetch Bill	14
5.1	Headers	14
5.2	Request Body Parameters.....	14
5.3	Sample Request Body.....	16
5.4	Response Body Parameters.....	17
5.5	Sample Response Body.....	19
6	PayBill	22
6.1	Headers	22
6.2	Request Body Parameters.....	23
6.3	Sample Request Body.....	26
6.4	Response Body Parameters.....	28
6.5	Sample Response Body.....	30

7	ADD Favorite Biller API	33
7.1	Headers	33
7.2	Request Body Parameters	33
7.3	Sample Request Body	35
7.4	Response Body Parameters	37
7.5	Sample Response Body	39
7.5.1	Success	39
7.5.2	Failed	40
8	Update Favorite Biller API	41
8.1	Headers	41
8.2	Request Body Parameters	41
8.3	Sample Request Body	43
8.4	Response Body Parameters	44
8.5	Sample Response Body	46
8.5.1	Success	46
8.5.2	Failed	47
9	Get Favorite Billers API	48
9.1	Headers	48
9.2	Response Body Parameters	48
9.3	Sample Response Body	50
9.3.1	Success	50
9.3.2	Failed	56
10	Delete Favorite Biller API	57
10.1	Headers	57
10.2	Response Body Parameters	57
10.3	Sample Response Body	58
10.3.1	Success	58
11	Fetch by Billers ID API	60
11.1	Headers	60
11.2	Response Body Parameters	60
11.3	Sample Response Body	63
12	Oneview API	70

12.1	Headers	70
12.2	Response Body Parameters.....	70
12.3	Sample Response Body.....	73
12.3.1	Success	73
12.3.2	Failed	75
13	Fetch Prepaid Plans API	76
13.1	Headers	76
13.2	Request Details	77
13.3	Response Body Parameters.....	77
13.4	Sample Response Body.....	79
13.4.1	Success	79
13.4.2	Failed	80

1 Introduction

This API document provides the integration framework for Bank of Baroda as a BBPOU on the Bharat Bill Payment System (BBPS) through the Customer Onboarding Unit (COU). It includes API specifications, request/response formats, authentication methods, and compliance requirements to facilitate a secure and efficient PayBill, Fetch Bill, and Generate Biller List File API process.

1.1 Base URL(UAT)

Use these Base URLs for the following APIs.

mbanking: https://api-preprod.isampurna.com/mbanking
upi: https://api-preprod.isampurna.com/upi
fi: https://api-preprod.isampurna.com/fi
feature-phone: https://api-preprod.isampurna.com/feature-phone

NOTE:

Please change the Authorization, pass HMACSignature dynamically for all requests

Please use the below **clientId** & **secretKey** to generate HMACSignature

mbanking :

- client_id : bH1aI2Qgp7zJJFsmF01pPJtzawUBrafGklz9rWrYA06wNtNj
- client_secret: ugVz1hETNXUIwnWtpLafAASFPL0qGI5fAWybWMfuEsIL3HusiIRWO1AvVmBRe0Gy

fi:

- client_id :UG94ygc40cgWNF36y5BOWsKNaux9Kt1lyAikFdXV6LXC6mtp
- client_secret: rfAjcxaY4ZNjxpP2A63os4tXlIgOQ9mMoesrSs099wnEzWDAxGfBcC4qGJCIfqxA

upi:

- client_id : qpcklLfKX6JA7taczJfoJXvSglPy4jR5lmWx3YdQslaV1PVK
- client_secret: g8qZYnBjjd3FV0r8ZRpSci96W08DGEXFL3uScivt99XIRyGSSKxkBep5z9a11nfm

feature-phone:

- ClientID: OXYxrVdP8UNnwPGnEFRDwwSDCwYYTh051ItcknPT6aCKr8TT
- ClientSecret: GSOjY6fAaCYX8UVkdHGQTz1dHF6tdRADpPTuo94IJvREngalwdVpjquAdw6aTedk

2 Headers and Authentication

The details of Headers and Authentication process is given below:

2.1 Request Header Attributes

With each request, you will need to set request headers as below:

- **Content-Type**

Request Content-Type to take the values **application/json**

- **Accept**

Accept Response Content-Type to take the values **application/json**

- **BD-Traceid**

Traceid is used for idempotency and the request with the same Traceid within the day will be rejected. Traceid can be alphanumeric without any spaces or special characters and should be a maximum size of 30.

- **BD-Timestamp**

Transaction timestamp in the **yyymmddhh24miss** format

- **Authorization**

This will be generated by the client as explained in the steps below and validated by BillDesk prior to processing the request. Format of the header is HMACSignature **clientid: hmacvalue**

2.2 HMAC Request Signature

The process to generate the Authorization Request Signature is as below:

Step 1:

Receive a **clientid** and a **secretkey** from BillDesk. The **clientid** identifies the client sending the requests, and the **secretkey** is used to generate the hash for the request. **clientid** = client1 and **secretkey** = 3FF9CBF87A66A452

Step 2:

Create the data string that is input to generate the HMAC-SHA256 hash.

```
hmac_string = HTTP-Method + "|" + URI + "|" + Content-Type + "|" + Accept + "|" + BD-Traceid + "|" + BD-Timestamp + "|" + SHA256(Requestbody)
HTTP-Method = POST (Upper case)
```



```
URI = /hgpay/v2_1/abcd/customers/12345/billpay/billers
Content-Type = application/json
Accept = application/json
BD-Traceid = a453c1353
BD-Timestamp = 20160528121320
SHA256(Requestbody) =
170AE002EFA016D1AB3CC2CF82B4E2B57BE2E7FCE92D4DB1355D25718A039EBC
hmac_string = POST|/hgpay/v2_1/abcd/customers/12345/billpay/billers|application/json|application/json|
a453c1353|20160528121320|
170AE002EFA016D1AB3CC2CF82B4E2B57BE2E7FCE92D4DB1355D25718A039EBC
```

Step 3:

Generate the HMACValue

```
HMACValue = HMAC-SHA256(hmac_string, secretkey)
HMACValue =
HMAC-SHA256 (POST|/hgpay/v2_1/abcd/customers/12345/billpay/billers|application/json|application/
json|a453c1353|20160528121320|
170AE002EFA016D1AB3CC2CF82B4E2B57BE2E7FCE92D4DB1355D25718A039EBC, 3FF9CBF87A66A452)
HMACValue = 8C5963E4CA185C7F41F00C7EBA54D344A5717F56422EC6BF2C464DC7DBA02961
```

Step 4

Create the final Authentication HeaderAuthorization HMACSignature

```
client1:8C5963E4CA185C7F41F00C7EBA54D344A5717F56422EC6BF2C464DC7DBA02961
```

2.3 Response Header Attributes

With each response, you will receive the following response headers:

- **Content-Type**

Request Content-Type to take the values **application/json**

- **BD-Traceid**

Same Traceid as passed in request

- **BD-Timestamp**

Same timestamp value as passed in request

- **Server-Authorization**

This HMAC signature is generated by BillDesk and the client has to authenticate the signature. Only valid responses should be processed. Format of the header is HMACSignature **clientid:HMACValue**

2.4 HMAC Response Signature

The process to validate the Server-Authorization Response Signature is as below:

Step 1:

Use the same **clientid** and a **secretkey** that was used to generate the request. clientid = client1 and secretkey = 3FF9CBF87A66A452

Step 2:

Create the data string that is input to generate the HMAC-SHA256 hash

```
hmac_string = HTTP-Status + "|" + Content-Type + "|" + BD-Traceid + "|" + BD-Timestamp + "|" +  
SHA256(Responsebody)  
HTTP-Status = 200  
Content-Type = application/json  
BD-Traceid = a453c1353  
BD-Timestamp = 20160528121320  
SHA256(Responsebody) =  
C6ED656BCA63C0BE27128D54DEC93F9A615D6E06CD1BEDA5574FD33FCD25E90A  
hmac_string = 200|application/json|a453c1353|20160528121320|  
C6ED656BCA63C0BE27128D54DEC93F9A615D6E06CD1BEDA5574FD33FCD25E90A
```

Step 3:

Generate the HMACValue

```
HMACValue = HMAC-SHA256(hmac_string, secretkey)  
HMACValue = HMAC-SHA256 (200|application/json|a453c1353|20160528121320|  
C6ED656BCA63C0BE27128D54DEC93F9A615D6E06CD1BEDA5574FD33FCD25E90A,  
3FF9CBF87A66A452)  
HMACValue = A79844C1BC90E1E6A615FDFDCE56A3BD8BB344BCE1A75F0C6D1F9A69D3252B13
```

Step 4:

Validate generated hmacvalue with value received in Server-Authorization Header
Server-Authorization
HMACSignature

```
client1:A79844C1BC90E1E6A615FDFDCE56A3BD8BB344BCE1A75F0C6D1F9A69D3252B13
```

3 Generate Biller List File API

Description:

This API initiates the generation of a Biller Master File. Upon receiving the request, BillDesk returns an acknowledgement. The system will later post the generated file to the provided callback_url.

Method: POST**Endpoint:** /BOBCOU/BBPS/<sourceid>/billpay/billers/file**NOTE:**

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

3.1 Headers

Content-Type: application/json**Accept:** application/json**BD-Traceid:** a453c1353**BD-Timestamp:** 20160528121320**Authorization:** HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:4b3db0014df9b944ce289895b6f60e1f71cfdff0fc21119f126bd877423829bb

3.2 Request Body Parameters

Parameters	Parameter description	Data type	Mandatory/ Optional
callback_url	Callback URL The URL to which the callback response will be sent.	String	Mandatory

3.3 Sample Request Body

callback_url(string): The URL to which the callback response will be sent.

```
{
  "callback_url": "https://www.bobtest.com/bbps/billers"
}
```

3.4 Response Body Parameters

Parameters	Parameter description	Data type
objectid	Object ID.	String
fileid	File ID	String
file_status	File Status	String
callback_url	Particular Callback URL	String

3.5 Sample Response Body

```
{
  "objectid": "file",
  "fileid": "HGA178987978789",
  "file_status": "INPROCESS",
  "callback_url": "https://www.bobtest.com/bbps/billers"
}
```

4 Get Biller Master File

Description:

This API supports the download of the biller master file previously generated.

Endpoint: /BOBCOU/BBPS/<sourceid>/billpay/billers/file/<fileid>

Method: GET

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

4.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:5ff0351eae3c3ef5016d87d83d7a0c57c0ae2c61dddc7943350b0fc809f399ca

4.2 Response Body Parameters

Parameters	Parameter description	Data type
status	Status of the Operation.	String
message	Message describing the operation status.	String

filePath	File Path	String
fileName	File Name	String
fileContent	File Content	String

4.3 Sample Response Body

```
{
  "status": 0,
  "message": "Successfully fetched the zipped file",
  "filePath": "biller_list/96257f3a2fe9.zip",
  "fileName": "96257f3a2fe9.zip",
  "fileContent":
    "UESDBBQACAAIAEstkVoAAAAAAAAAAAAAAAAQAAAAOTYyNTdmM2EyZmU5LnR4dOzda3vaSJsv"
}
```

5 Fetch Bill

Description:

Prior to initiating a debit to the customer account, the validate payment request can be used to verify the biller authenticator details or fetch the latest available bill for the biller account. The validate payment request will return a validationid that is required to initiate payment.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/validate

Method: POST

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

5.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:4ccefc3585a55830610935ad3eaaf
a516bd09f6a4ff58c6886ff2d6f107e5a166

5.2 Request Body Parameters

Parameters	Parameter description	Data type	Mandatory/ Optional/ Conditional
sourceid	Fixed source ID provided by BillDesk to the client	String	Mandatory

customerid	Unique ID for the customer as provided by the source	String	Mandatory
billeraccountid	Represents the biller account ID associated with the registered biller	String	Conditional (Mandatory - if validation is done using billeraccountid)
billerid	Unique biller ID assigned to each biller by BillDesk	String	Conditional (Mandatory - if using a combination of billerid and authenticators)
authenticators Child Attributes - parameter_name - value	- List of specific parameters identifying the biller account - Fixed name identifying the parameter (e.g. "Consumer Number") - Value corresponding to the `parameter_name` (e.g. "20382028438")	Array String String	Conditional (Mandatory - If using a combination of billerid and authenticators.)
currency	Three-digit numeric ISO currency code	String	Conditional (Mandatory - If `payment_amount` is being sent)
payment_amount	Amount in decimal (up to two decimal places)	String	Conditional (Mandatory - If `paymentamount_validation` flag is "Y" for the billerid in the request)
additional_validation_details Child Attributes: - parameter_name - value	Additional parameters required for validation/payment - parameter_name: Name of the parameter (e.g. "Recharge Type") - value: Corresponding value (e.g. "1")	String	Optional
customer Child Attributes: - firstname - lastname - mobile	Parameters identifying the customer. - firstname- First name of the customer. - lastname: Last name of the customer - mobile: Primary mobile number of the customer. (It can be used to search for a transaction.)	String	Mandatory

metadata	Parameters identifying the source agent and device from which the request originated. (Details of child attributes can be added as needed.)	string	Mandatory
----------	---	--------	-----------

NOTE:

Either `billeraccountid` OR the combination of `billerid` and `authenticators` is mandatory.

5.3 Sample Request Body

```
{
  "billeraccountid": "RELEN155187",
  "billerid": "BBPS00000NAT01",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Customer Reference Field1",
      "value": "10"
    }
  ],
  "payment_amount": "920.00",
  "currency": "356",
  "sitxn": "yes",
  "pay_multiple_bills": "N",
  "customer": {
    "firstname": "Bikash",
    "lastname": "Sao",
    "mobile": "9012345006",
    "email": "dinesh.rout@iserveu.in"
  },
  "metadata": {
    "agent": {
      "agentid": "BD001MPY100000100001",
      "sub_agentid": "BD001MPY11"
    }
  },
}
```

```
"device": {
  "init_channel": "Internet",
  "ip": "124.124.1.1",
  "mac": "11-AC-58-21-1B-AA"
},
"risk": [
  {
    "score_provider": "OU01",
    "score_value": "030",
    "score_type": "TXNRISK"
  },
  {
    "score_provider": "BBPS",
    "score_value": "030",
    "score_type": "TXNRISK"
  }
]
```

5.4 Response Body Parameters

Parameters	Parameter description	Data type
objectid	Object ID	String
sourceid	Source ID	String
customerid	Customer ID	String
customer_name	Customer Name	String
validationid	Validation ID	String
validation_date	Validation date	String
valid_until	Last date till it is valid	String

billerid	Biller id	String
biller_name	Biller name	String
biller_category	Biller category	String
authenticators	- seq - parameter_name - value	String
currency	Currency (type of money)	String
billlist	- objected - validation_id - user_id - user_name - ref_id - agent_id - agent_tags[name,value]	String
biller_id	Biller Id	String
customer_params	Customer Parameters - name - value	String
amount	Amount	String
bill_date	Bill date	String
bill_number	Bill number	String
bill_period	Bill period	String
due_date	Due date	String
bill_amount	Bill Amount	String
ccf	CCF	String

ccf_desc	CCF Description	String
biller_response_tags	Billers response tags - name - value	String
additional_info	Additional information - name - value	String
planlist	Plan list	String
pay_multiple_bills	Pay multiple bills	String
additional_validation_details	- parameter_name - value	String
additional_info	Additional information	String

5.5 Sample Response Body

```
{
  "objectid": "validation",
  "sourceid": "mbanking",
  "customerid": "1234567890",
  "validationid": "2906285783064576",
  "status": 200,
  "error_code": "",
  "message": "Successful",
  "payment_amount": "920.00",
  "validation_date": "19-05-2025 11:15:40",
  "valid_until": "20-05-2025 00:00:00",
  "billerid": "UPPCL0000UTP02",
  "biller_name": "Uttar Pradesh Power Corp Ltd (UPPCL) - RURAL",
  "biller_category": "Electricity",
  "authenticators": [
    {
```

```
"seq": "1",
"parameter_name": "Consumer No",
"value": "111111111"
},
{
"seq": "2",
"parameter_name": "Billing cycle",
"value": "02"
}
],
"currency": "356",
"billlist": [
{
"objectid": "bill",
"billid": "123450001",
"billerid": "UPPCL0000UTP02",
"billperiod": "June",
"customer_name": "Ashish",
"billeraccountid": "RELEN155187",
"authenticators": [
{
"name": "Consumer No",
"value": "111111111"
},
{
"name": "Billing cycle",
"value": "02"
}
]
},
"billnumber": "123450001",
"billdate": "19-05-2025",
"billduedate": "19-05-2025",
"billamount": "20000",
"early_billduedate": "Invalid date",
"early_billdiscount": null,
"early_billamount": null,
"late_payment_charges": null,
"late_payment_amount": null,
```

```
"net_billamount": "20000",
"currency": "356",
"description": "Bill payment for Uttar Pradesh Power Corp Ltd (UPPCL) - RURAL",
"additional_details": [],
"line_items": [],
"billstatus": "UNPAID"
}
],
"planlist": [],
"pay_multiple_bills": "N",
"additional_validation_details": [
{
"parameter_name": "Recharge Type",
"value": "1"
}
],
"additional_info": []
}
```

6 PayBill

Description:

You can initiate a payment request in any of the following three ways. Payment based on a validated request, using a validationid and, billid when available. Payment against a presented bill, using a bill ID. An adhoc payment, using the billeraccountid or the authenticators and billerid (without a validationid or billid). The response will contain the payment object for valid payment requests.

- The payment workflow will need to be preconfigured for a source. The following workflow can be supported based on the value of the parameter `authorization_type` in the request:
- In case the payment is already authorized (debit completed by source), the parameter `authorization_type` is not required in the request. The request will create a successful payment resource in the BillPay system. The `payment_status` in the response is returned as "PAID".

Schedule: This value can be passed for the request parameter to schedule an auto payment for a future date. The payment will be processed as per the regular workflow of auto-payment

Authorize: This value can be passed for the request parameter to create a payment resource where debit is initiated by BillDesk. The response can have `payment_status` as "PAID", "FAILED", or "DELIVERED" based on the status of the debit process.

Onhold: The source can define a payment workflow to be completed in a two-step process, in which case this value can be passed to create a temporary payment resource. The `payment_status` in the response is to be returned as "PENDING". The source can then perform any other authentication, process the debit, and call the **"Approve Payment"** API to complete the payment process.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/payments

Method: POST

NOTE:

The `sourceid` parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi**, **fi**, or **feature-phone**.

6.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:580e61ff874032f20cf6638b1b186366aa2838f48f8258122a040d066201bf72

6.2 Request Body Parameters

Parameters	Parameter description	Data type	Mandatory/ Optional/ Conditional
sourceid	Fixed source ID provided by BillDesk to the client	String	Mandatory
customerid	Unique ID for the customer as provided by the source	String	Mandatory
billerid	Unique biller ID assigned to each biller by BillDesk	String	Conditional
validationid	Unique ID from the response to the Validate Payment request.	String	Conditional (Mandatory - If payment is based on a validated request)
billid	Unique ID from the Retrieve Bills response	String	Conditional (Mandatory - If payment is against a presented bill)
billeraccountid	Unique ID assigned by BillDesk for registered biller accounts.	String	Conditional (Mandatory - For adhoc payment using `billeraccountid` or `authenticators` & `billerid`, without `validationid` or `billid`)
authenticators Child Attributes - seq - parameter_name - value	List of parameters that uniquely identify the biller account `seq`: Order of appearance in frontend. `parameter_name`: Name identifying the parameter (e.g., Consumer Number). `value`: Corresponding value (e.g., 20382028438)	String	Mandatory

source_ref_no	Unique reference number generated by the source per payment request when the debit is processed.	String	Mandatory
payment_type Values: • instapay • billpay • adhoc	Type of payment • `instapay`: With prior validated request (`validationid` present). • `billpay`: Against a presented bill (`billid` present). • `adhoc`: Without `validationid` or `billid`.	String	Mandatory
payment_account	Customer's payment details. May contain `paymentaccountid` or necessary details for processing	Object	Mandatory
currency	3-digit numeric ISO code representing currency	String	Mandatory
payment_amount	Payment amount (in decimal, up to 2 places).	String	Mandatory
cou_conv_fee	A convenience fee is collected by COU from the customer. • If no fee, send `0.00`	String	Mandatory
bou_conv_fee	BOU-mandated convenience fee collected from customer. • If no fee, send `0.00`.	String	Mandatory
debit_amount	Total debit amount = `payment_amount` + `cou_conv_fee` + `bou_conv_fee`.	String	Mandatory
payment_remarks	Customer remarks for the payment.	String	Optional
schedule_date	Scheduled payment date.	String	Conditional (Mandatory - If `authorization_type` is set to `schedule`)

additional_validation_details Child Attributes: - parameter_name - value	Extra parameters needed by the biller. `parameter_name`: Name (e.g., Recharge Type). `value`: Value (e.g., 1).	String	Optional
customer Child Attributes: - firstname - lastname - mobile - mobile_alt - email - email_alt	Customer identification details. `firstname`: First name. `lastname`: Last name. `mobile`: Primary mobile (used for transaction lookup). `mobile_alt`: Alternate mobile. `email`: Email. `email_alt`: Alternate email.	String	Mandatory
metadata	Source agent and device details	String	Mandatory
agent - agentid - sub_agentid	Agent details	String	Mandatory
device - init_channel - Possible values - mobile - geocode - postal_code - ip - branch_code - terminalid - imei - mac - os - app - user_agent - device_fingerprint	List of devices Channel initiating request Internet, Mobile, POS, ATM, BankBranch, Kiosk, etc. `mobile`: Customer's mobile number. `geocode`: Geolocation of customer or agent. `postal_code`: Customer's postal code. `ip`: Customer's IP address. `branch_code`: Bank branch code. `terminalid`: POS/ATM terminal ID. `imei`: Mobile IMEI. `mac`: Machine MAC address. `os`: Operating system. `app`: Customer's app name. `user_agent`: Browser's user agent. `device_fingerprint`: Device fingerprint.	String	Mandatory

additional_info Attributes: - name - value	Additional information `name`: Parameter name. `value`: Corresponding value.	Object	Optional
risk - score_provider - score_value - score_type	Risk score details `score_provider`: Risk score provider. `score_value`: Risk metric value. `score_type`: Type of risk addressed.	String	Mandatory (for BBPS billers)
approval_details - requestid - makerid - maker_request_date - approverid - approval_date	Approval workflow details. `requestid`: Unique maker request ID `makerid`: Maker's user ID. `maker_request_date`: Maker creation date. `approverid`: Approver's user ID. `approval_date`: Approval date.	String	Optional

6.3 Sample Request Body

```
{
  "billerid": "BBPS00000NAT01",
  "billeraccountid": "RELEN155187",
  "validationid": "105107623578440111",
  "currency": "356",
  "payment_amount": "5.00",
  "cou_conv_fee": "0.00",
  "bou_conv_fee": "0.00",
  "debit_amount": "550.00",
  "payment_type": "instapay",
  "payment_remarks": "Free text",
  "source_ref_no": "acgtf22311100001",
  "customer": {
    "firstname": "Mayank",
    "lastname": "Trivedi",

```

```
"mobile": "9800000000",
"email": "mayan.trivedi@billdesk.com "
},
"metadata": {
  "agent": {
    "agentid": "BD001MPY100000100001",
    "sub_agentid": "BD001MPY11"
  },
  "device": {
    "init_channel": "Internet",
    "ip": "124.124.1.1",
    "os": "iOS"
  },
  "additional_info": [
    {
      "name": "loginid",
      "value": "AB45612"
    },
    {
      "name": "branch_code",
      "value": "8451321"
    }
  ]
},
"approval_details": {
  "requestid": "AB45612",
  "makerid": "userid",
  "maker_request_date": "22-08-2020 18:30:52",
  "approverid": "userid",
  "approval_date": "22-08-2020 18:30:52"
},
"payment_account": {
  "payment_method": "CreditCard",
  "cardholder_name": "John Doe",
```

```

"enc_card_number":
"WFwtM7n1wbNAIQ1VSmpxLx0d7qKodUflg+l2AXgQFN+RCviSAQnEUVBH2XrNpgt6uwL88+bAWARvb+4dd
dxnS5bcNi0WY3y611STn+hy5ctJGMuNcGgbNZD11KjFJ2gW0IQOy93EGGjSRHKb7+LPFM10xFiTHK/
bWwtxD/
1l6oEjszC8eg91aF307IYks3Nomgym9xuuj4vc+Aqbqrlg0ZfwcRQppyvOmD5oEOYJFxaTsoLxqZp2OpJpjJ8R
dVYRf1HxgKLftXmDGq5gfSf82++vNvxq7//
fTvshP1j0K2e388YUzLhPVJ7x+lpQYjBSH8TdMfVDxsPq1fWdYexeog==",
"enc_card_expiry": "jFi+FU+Sg1vQPglaS2r1GPQG7x2dWzzbKbCc6jfDPP/nvG4ljKHsbVfwjBhDTW6iJsy0/
qv4Lxn/cn9V0r1l/1Zq+4vUIXbs/UT1o3YMD02nGmQnp3cEqK/
1z8ozr0Bn1xYuRqBuOJeOlw0IFlezS2P8IHTE8p2wxFA6pJMFNNaiP73A0pbV0M1hxJy6FmkyS1k1LGpwKw
D89B9XdCuCx1WoWlda+/XbFZ0rl2ctVmGqGaZ5RKHGHZr1b/
9eSXFtjE6uq7ViXdao2KADkPx8x9SCxXYXmga8aBesjLz//wvo1R/
UOAqBKZ3huCINLnRcHqS5z1fC82BDQNFSdaRDSA=="
},
"auth_code": "0012"
}

```

6.4 Response Body Parameters

Parameters	Parameter description	Data type
objectid	Object id	String
sourceid	Source id	String
customerid	Customer Id	String
billerid	Biller Id	String
biller_name	Biller name	String
biller_category	Biller Category	String
billeraccountid	Biller Account ID	String
authenticators - parameter_name - value	Authenticators with parameter_name & value	String
validationid	Validation Id	String

billlist • billid • billperiod • objecteid • billnumber • billdate • billduedate • billamount • customer_name • early_billduedate • early_billdiscount • early_billamount • late_payment_charges • late_payment_amount • net_billamount • currency • description	Bill List with the following attributes Bill ID Bill period Object ID Bill number Bill date Due date for the bill Bill amount Customer name Early bill due date Early bill discount Early bill amount Late payment charges Late payment amount Net bill amount Currency Description	String
additional_details • seq • label • value	Additional Details with the following Attributes (seq, label, value)	String
line_items • description • amount	Line Items (description & amount)	String
billstatus	Bill Status	String
currency	Currency	String
payment_amount	Payment Amount	String
cou_conv_fee	COU Conv Fee	String
bou_conv_fee	BOU Conv Fee	String
debit_amount	Debit Amount	String
payment_type	Type of Payment	String

payment_remarks	Payment Remarks	String
source_ref_no	Source Reference Number	String
bbps_ref_no	BBPS Reference number	String
txn_date_time	Transaction Date and Time	String
schedule_date	Scheduled Date	String
payment_status	Status of the payment	String
biller_approval_code	Biller Approval Code	String
biller_status	Biller Status	String
biller_status_desc	Biller Status Description	String
payment_account • paymentaccountid • objectid • short_name • payment_method • card_start • card_end • cardholder_name	Payment Account With these attributes (paymentaccountid, objectid, short_name, payment_method, card_start, card_end, cardholder_name	String
auth_code	Authorized Code	String
additional_info • name • value	Additional Information with name and value attributes.	String

6.5 Sample Response Body

```
{
  "paymentid": "2906285783064576",
  "objectid": "payment",
  "sourceid": "mbanking",
```



```
"customerid": "1234567890",
"billerid": "UPPCL0000UTP02",
"biller_name": "Uttar Pradesh Power Corp Ltd (UPPCL) - RURAL",
"biller_category": "Electricity",
"billeraccountid": "RELEN155187",
"authenticators": [],
"validationid": "2906285783064576",
"billlist": [
  {
    "billid": "2906285783064576",
    "objectid": "bill",
    "billerid": "UPPCL0000UTP02",
    "sourceid": "mbanking",
    "billperiod": "June",
    "billnumber": "123450001",
    "billdate": "2015-06-14",
    "billduedate": "2017-06-30",
    "billamount": "20000",
    "customer_name": "Ashish",
    "early_billduedate": "",
    "early_billdiscount": "",
    "early_billamount": "",
    "late_payment_charges": "",
    "late_payment_amount": "",
    "authenticators": [],
    "validationid": "2906285783064576",
    "net_billamount": "",
    "currency": "356",
    "description": "Bill payment for Uttar Pradesh Power Corp Ltd (UPPCL) - RURAL",
    "additional_details": [],
    "line_items": [],
    "billstatus": "paid"
  }
],
"currency": "356",
"payment_amount": "550.00",
"cou_conv_fee": "0.00",
"bou_conv_fee": "0.00",
```

```
"debit_amount": "550.00",
"payment_type": "instapay",
"payment_remarks": "Free text",
"source_ref_no": "acgtf22311100001",
"bbps_ref_no": "IP115013160457090c87",
"txn_date_time": "",
"schedule_date": "",
"payment_status": "",
"biller_approval_code": "234323432",
"biller_status": "SUCCESS",
"biller_status_desc": "Successful",
"payment_account": {
  "payment_method": "CreditCard",
  "cardholder_name": "John Doe",
  "enc_card_number":
    "WFwtM7n1wbNAIQ1VSmpxLx0d7qKodUflg+l2AXgQFN+RCviSAQnEUVBH2XrNpgt6uwL88+bAWARvb+4dd
    dxnS5bcNi0WY3y611STn+hy5ctJGMuNcGgbNZD11KjFJ2gW0IQOy93EGGjSRHKb7+LPFM1OxFiTHK/
    bWwtxD/
    1l6oEjszC8eg91aF307lYks3Nomgym9xuuj4vc+Aqbqrlg0ZfwcRQppyyOmD5oEOYJFxaTsoLxqZp2OpJpjJ8R
    dVYRf1HxgKLftXmDGq5gfSf82++vNvxq7//
    fTvshP1j0K2e388YUzLhPVJ7x+lpQYjBSH8TdMfVDxsPq1fWdYexeog==",
  "enc_card_expiry": "jFi+FU+Sg1vQPglaS2r1GPQG7x2dWzzbKbCc6jfDPP/
    nvG4ljKHsbVfwjBhDTW6iJsy0/qv4Lxn/cn9V0r1l/1Zq+4vUIXbs/UT1o3YMD02nGmQnp3cEqK/
    1z8ozr0Bn1xYuRqBuOJeOlw0IFlezS2P8lHTE8p2wxFA6pJMFNNaiP73A0pbV0M1hxJy6FmkyS1k1LGpwKw
    D89B9XdCuCx1WoWlDa+/XbFZ0rl2ctVmQGaz5RKHGHR1b/
    9eSXFtjE6uq7ViXdao2KADkPx8x9SCxXYXmga8aBesjLz//wvo1R/
    UOAqBKZ3huCINLnRcHqS5z1fC82BDQNFSDaRDSA=="
},
"auth_code": "0012",
"additional_info": []
}
```

7 ADD Favorite Biller API

Description: This API facilitates adding a biller account for a biller and associating it with a specific customer.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/billeraccounts

Method: POST

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

7.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:9a7f42489a7bb156dfeae15a302f855049af87fb265bdd9af7a46e6f4ee8effb

7.2 Request Body Parameters

Parameters	Parameter description	Data type	Mandatory/ Optional/ Conditional
billerid	Unique Biller ID assigned to each biller	String	Mandatory
short_name	Short Name assigned by the customer	String	Optional

authenticators - parameter_name - value	Authenticators Parameter Name Value	Object String String	Mandatory
autopay_status	Represent autopay status	String	Optional
autopay_start_date	Autopay start date	String	Conditional (Mandatory - only if the autopay is to be set for the payment type of billers, i.e. when autopay_status flag is Y)
autopay_end_date	Represent autopay end date	String	Conditional (Mandatory - only if the autopay is to be set for the payment type of billers, i.e. when autopay_status flag is Y)
autopay_amount	Autopay amount	String	Conditional (Mandatory - when autopay_status flag is Y in the request)
currency	Currency type	String	Conditional
frequency	billing frequency or cycle of the biller account	String	Conditional (Mandatory - if the autopay_status value is Y in the request, and the biller is of payment type.
payment_account - short_name - payment_method - cardholder_name - enc_card_number - enc_card_expiry	Payment account details provided by the customer for making bill payment Short Name Payment Method Cardholder Name Encrypted card number Encrypted card expiry date	Object String String String String	Conditional (Mandatory - when autopay_status flag is Y in the request)

customer • firstname • lastname • mobile • email	Customer Details First Name last Name Mobile Number Email Address	Object String String String String	Mandatory
metadata • agent • agentid • sub_agentid	List of specific parameters that identify the source agent and device Agent Agent ID Sub Agent ID	Object String String String	Mandatory
device • init_channel • ip • mac	Device Channel Initialization IP Address MAC Address	Object String String String	Mandatory
additional_info • name • value	Additional Information Name Value	Object String String	Optional
approval_details • requestid • makerid • maker_request_date • approverid • approval_date	Approval Details related to approval workflow Request ID Maker ID Maker Request Date Approve ID Approval Date	String String String String String String	Optional

7.3 Sample Request Body

```
{
  "billerid": "AVVNL0000RAJ01",
  "short_name": "HOME2",
  "authenticators": [
    {
      "parameter_name": "Consumer number",
      "value": "111111111"
    }
  ],
}
```

```
{
  "parameter_name": "Billing cycle",
  "value": "02"
}
],
"autopay_status": "Y",
"autopay_start_date": "07-02-2017",
"autopay_end_date": "07-02-2018",
"autopay_amount": "2500.00",
"currency": "356",
"frequency": "Monthly",
"payment_account": {
  "short_name": "myCard",
  "payment_method": "CreditCard",
  "cardholder_name": "Deepankar Sr",
  "enc_card_number": "xxxx",
  "enc_card_expiry": "xxxx"
},
"customer": {
  "firstname": "Mayan",
  "lastname": "Trivedi",
  "mobile": "9800000000",
  "email": "mayan.trivedi@billdesk.com"
},
"metadata": {
  "agent": {
    "agentid": "BD001MPY100000100001",
    "sub_agentid": "BD001MPY11"
  },
  "device": {
    "init_channel": "Internet",
    "ip": "124.124.1.1",
    "mac": "11-AC-58-21-1B-AA"
  },
  "additional_info": [
    {
```

```
    "name": "loginid",
    "value": "AB45612"
  },
  {
    "name": "branch_code",
    "value": "8451321"
  },
  {}
]
},
"approval_details": {
  "requestid": "AB45612",
  "makerid": "userid",
  "maker_request_date": "22-08-2020 18:30:52",
  "approverid": "userid",
  "approval_date": "22-08-2020 18:30:52"
}
```

7.4 Response Body Parameters

Parameters	Parameter description	Data type
billeraccountid	Biller Account ID	String
objectid	Object ID	String
sourceid	Source ID	String
billerid	Biller ID	String
short_name	Short Name	String
authenticators	Authenticators	Object
seq	Sequence	String

parameter_name	Parameter Name	String
value	Value	String
status	Status of the Operation.	String
registration_date	Date of Registration.	String
autopay_status	Autopay Status.	String
autopay_start_date	Autopay Starting Date	String
autopay_end_date	Autopay Ending Date	String
autopay_amount	Autopay Amount	String
currency	Currency	String
frequency	Frequency	String
payment_account	Payment Account Details	Object
short_name	Short Name	String
payment_method	Payment Method	String
cardholder_name	Name of the Cardholder	String
enc_card_number	Card Number	String
enc_card_expiry	Card Expiry	String
activation_date	Date of Activation	String
cprn	Represent the customer presentment registration number	String
customer	Customer Detail	Object

mobile	Mobile Number of the Customer	String
Only for Failed Response		
statusCode	Status Code of the Operation.	String
statusDescription	Status Description of the Operation.	String
timeStamp	Timestamp of the Failed Operation.	Timestamp
traceId	Trace ID	String
data	Data.	String

7.5 Sample Response Body

7.5.1 Success

```
{
  "billeraccountid": "4181283386695680",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "AVVNL0000RAJ01",
  "short_name": "HOME2",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Billing cycle",
      "value": "02"
    },
    {
      "seq": "2",
      "parameter_name": "Consumer number",
      "value": "111111111"
    }
  ],
  "status": "ACTIVE",
}
```

```
"registration_date": "22-04-2025 16:40:08",
"autopay_status": "Y",
"autopay_start_date": "07-02-2017 00:00:00",
"autopay_end_date": "07-02-2018 00:00:00",
"autopay_amount": 2500,
"currency": "356",
"frequency": "Monthly",
"payment_account": {
  "short_name": "myCard",
  "payment_method": "CreditCard",
  "cardholder_name": "Deepankar Sr",
  "enc_card_number": "****",
  "enc_card_expiry": "****"
},
"activation_date": "22-04-2025 16:40:08",
"cprn": "ISU12345",
"customer": {
  "mobile": "9898990001"
}
}
```

7.5.2 Failed

```
{
  "status": "FAILED",
  "statusCode": "1",
  "statusDescription": "This biller is already marked as a favorite.",
  "timeStamp": 1745479528811,
  "traceId": "9af901afc0e646f0afc20a401d3e84f2",
  "data": null
}
```

8 Update Favorite Biller API

Description: This API facilitates updating all the biller accounts through a customer ID.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/billeraccounts/<billeraccountid>

Method: PUT

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

8.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:0f883fadcc19632e8c5a6e5c1c6b0043b35e2432a7480034f25aacc58ca68594

8.2 Request Body Parameters

Parameters	Parameter description	Data type	Mandatory/ Optional/ Conditional
short_name	Short nickname assigned by the customer for the biller account.	String	Optional
autopay_status	Whether the biller account is set up for autopay or not.	String	Optional

autopay_start_date	Autopay Starting Date	String	Conditional (Mandatory - when autopay_status flag is Y in the request)
autopay_end_date	Autopay Ending Date	String	Conditional (Mandatory - when autopay_status flag is Y in the request)
autopay_amount	Autopay Amount	String	Conditional (Mandatory - when biller_type is PAYEE for billerid in the request)
currency	Currency	String	Conditional - ISO currency code for any attribute in biller object where value is some amount.
frequency	Frequency	String	Conditional (Mandatory - the autopay_status value is Y in the request and the biller is of payment type.
payment_account paymentaccountid	Payment Account Details Payment Account ID	Object String	Conditional (Mandatory - when autopay_status flag is Y in the request)
customer - firstname - lastname - mobile - email	Customer Details First Name of the Customer Last Name of the Customer Mobile Number of the Customer Email ID of the Customer	Object String String String String	Mandatory
metadata agent - agentid - sub_agentid	Metadata Details of the Agents Agent ID Sub Agent ID	Object String String String	Mandatory

device - init_channel - ip - mac	Device Details Initialize Channel IP Address MAC Address	Object String String String	Mandatory
approval_details - requestid - makerid - maker_request_date - approverid - approval_date	Approval Details Request ID Maker ID Maker Request Date Approver ID Approval date	Object String String String String String	Optional

8.3 Sample Request Body

```
{
  "short_name": "HOME190",
  "autopay_status": "Y",
  "autopay_start_date": "07-02-2017",
  "autopay_end_date": "07-02-2018",
  "autopay_amount": "985.75",
  "currency": "356",
  "frequency": "Monthly",
  "payment_account": {
    "paymentaccountid": "789465464645"
  },
  "customer": {
    "firstname": "Mayan",
    "lastname": "Trivedi",
    "mobile": "9800000000",
    "email": "mayan.trivedi@billdesk.com "
  },
  "metadata": {
    "agent": {
      "agentid": "BD001MPY100000100001",
      "sub_agentid": "BD001MPY11"
    }
  }
}
```

```
"device": {  
  "init_channel": "Internet",  
  "ip": "124.124.1.1",  
  "mac": "11-AC-58-21-1B-AA"  
},  
"approval_details": {  
  "requestid": "AB45612",  
  "makerid": "userid",  
  "maker_request_date": "22-08-2020 18:30:52",  
  "approverid": "userid",  
  "approval_date": "22-08-2020 18:30:52"  
}  
}
```

8.4 Response Body Parameters

Parameters	Parameter description	Data type
data	Fetches Data.	Object
billeraccountid	Biller Account ID	String
objectid	Object ID	String
sourceid	Source ID	String
billerid	Biller ID	String
short_name	Short Name	String
authenticators	Authenticators	Object
seq	Sequence	String
parameter_name	Parameter Name	String

value	Value	String
status	Status of the Operation.	String
registration_date	Date of Registration.	String
modified_date	Date of Modification	String
autopay_status	Autopay Status.	String
autopay_start_date	Autopay Starting Date	String
autopay_end_date	Autopay Ending Date	String
autopay_amount	Autopay Amount	String
currency	Currency	String
frequency	Frequency	String
payment_account	Payment Account Details	Object
paymentaccountid	Payment Account ID.	String
Only for Failed Response		
statusCode	Status Code of the Operation.	String
statusDescription	Status Description of the Operation.	String
timeStamp	Timestamp of the Failed Operation.	Timestamp
traceld	Trace ID	String
data	Data.	String

8.5 Sample Response Body

8.5.1 Success

```
{
  "billeraccountid": "4181283386695680",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "AVVNL0000RAJ01",
  "short_name": "HOME190",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Billing cycle",
      "value": "02"
    },
    {
      "seq": "2",
      "parameter_name": "Consumer number",
      "value": "111111111"
    }
  ],
  "status": "ACTIVE",
  "registration_date": "22-04-2025 16:40:08",
  "modified_date": "24-04-2025 14:40:56",
  "autopay_status": "Y",
  "autopay_start_date": "07-02-2017 00:00:00",
  "autopay_end_date": "07-02-2018 00:00:00",
  "autopay_amount": 985.75,
  "currency": "356",
  "frequency": "Monthly",
  "payment_account": {
    "paymentaccountid": "789465464645"
  }
}
```


8.5.2 Failed

```
{
  "status": "FAILED",
  "statusCode": "1",
  "statusDescription": "Favourite biller not found for the given customer ID and biller ID",
  "timeStamp": 1745485709472,
  "traceId": "21633088583146679bd9335ac8b943c6",
  "data": null
}
```

9 Get Favorite Billers API

Description: This API facilitates fetching all the biller accounts through a customer ID.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/billeraccounts

Method: GET

9.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-timestamp: 20160528121320

Authorization: N/A

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

9.2 Response Body Parameters

Parameters	Parameter description	Data type
data	Fetches Data.	Object
billeraccountid	Biller Account ID	String
objectid	Object ID	String
sourceid	Source ID	String

billerid	Biller ID	String
short_name	Short Name	String
authenticators	Authenticators	Object
seq	Sequence	String
parameter_name	Parameter Name	String
value	Value	String
status	Status of the Operation.	String
registration_date	Date of Registration.	String
modified_date	Date of Modification	String
autopay_status	Autopay Status.	String
autopay_start_date	Autopay Starting Date	String
autopay_end_date	Autopay Ending Date	String
autopay_amount	Autopay Amount	String
currency	Currency	String
frequency	Frequency	String
payment_account	Payment Account Details	Object
paymentaccountid	Payment Account ID.	String
objectid	Object ID	String
customerid	Customer ID	String
short_name	Short Name of Customer	String

status	Status of the Operation.	String
payment_method	Payment Method.	String
card_start	Card Start	String
card_end	Card End	String
cardholder_name	Card Holder's Name	String
cprn	CPRN - Represent the customer presentment registration number	String
Only for Failed Response		
statusCode	Status Code of the Operation.	String
statusDescription	Status Description of the Operation.	String
timeStamp	Timestamp of the Failed Operation.	Timestamp
traceld	Trace ID	String
data	Data.	Object

9.3 Sample Response Body

9.3.1 Success

```
{
  "data": [
    {
      "billeraccountid": "4499774719401984",
      "objectid": "billeraccount",
      "sourceid": "SRC01",
      "billerid": "TATASKY00NAT01",
      "short_name": "Debjcet TV",
      "authenticators": [
```

```
{
  "seq": "1",
  "parameter_name": "Subscriber Number",
  "value": "7205504564"
}
],
"status": "ACTIVE",
"registration_date": "23-04-2025 12:47:48",
"autopay_status": "Y",
"autopay_start_date": "25-04-2025 00:00:00",
"autopay_end_date": "30-04-2025 00:00:00",
"payment_amount": "300.00",
"currency": "356",
"frequency": "Annually",
"payment_account": {
  "paymentaccountid": "4499774719401984",
  "objectid": "paymentaccount",
  "customerid": "1234567890",
  "short_name": "",
  "status": "ACTIVE",
  "payment_method": "Internet Banking",
  "card_start": "",
  "card_end": "",
  "cardholder_name": ""
},
"cprn": "ISU123456"
},
{
  "billeraccountid": "3857469620625408",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "TATASKY00NAT01",
  "short_name": "home tv",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Subscriber Number",
      "value": "8798797979"
```

```
    }
  ],
  "status": "ACTIVE",
  "registration_date": "22-04-2025 12:24:18",
  "autopay_status": "Y",
  "autopay_start_date": "24-04-2025 00:00:00",
  "autopay_end_date": "29-04-2025 00:00:00",
  "payment_amount": "9790.99",
  "currency": "356",
  "frequency": "Monthly",
  "payment_account": {
    "paymentaccountid": "3857469620625408",
    "objectid": "paymentaccount",
    "customerid": "1234567890",
    "short_name": "",
    "status": "ACTIVE",
    "payment_method": "Internet Banking",
    "card_start": "",
    "card_end": "",
    "cardholder_name": ""
  },
  "cprn": "ISU123456"
},
{
  "billeraccountid": "3761840781271040",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "BSNL00000NATHL",
  "short_name": "HOME20",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Billing cycle",
      "value": "02"
    },
    {
      "seq": "2",
      "parameter_name": "Consumer number",
```

```
        "value": "111111111"
      }
    ],
    "status": "ACTIVE",
    "registration_date": "21-04-2025 12:24:10",
    "autopay_status": "Y",
    "autopay_start_date": "09-02-2017 00:00:00",
    "autopay_end_date": "09-02-2018 00:00:00",
    "payment_amount": "2500.00",
    "currency": "356",
    "frequency": "Monthly",
    "payment_account": {
      "paymentaccountid": "3761840781271040",
      "objectid": "paymentaccount",
      "customerid": "1234567890",
      "short_name": "myCard",
      "status": "ACTIVE",
      "payment_method": "CreditCard",
      "card_start": "xxxx",
      "card_end": "xxxx",
      "cardholder_name": "Deepankar Sr"
    },
    "cprn": "ISU12345"
  },
  {
    "billeraccountid": "4176964159545344",
    "objectid": "billeraccount",
    "sourceid": "SRC01",
    "billerid": "CONBB0000PUN01",
    "short_name": "HOME19",
    "authenticators": [
      {
        "seq": "1",
        "parameter_name": "Billing cycle",
        "value": "02"
      },
      {
        "seq": "2",
```

```
      "parameter_name": "Consumer number",
      "value": "111111111"
    }
  ],
  "status": "ACTIVE",
  "registration_date": "22-04-2025 16:09:37",
  "autopay_status": "Y",
  "autopay_start_date": "09-02-2017 00:00:00",
  "autopay_end_date": "09-02-2018 00:00:00",
  "payment_amount": "2500.00",
  "currency": "356",
  "frequency": "Monthly",
  "payment_account": {
    "paymentaccountid": "4176964159545344",
    "objectid": "paymentaccount",
    "customerid": "1234567890",
    "short_name": "myCard",
    "status": "ACTIVE",
    "payment_method": "CreditCard",
    "card_start": "xxxx",
    "card_end": "xxxx",
    "cardholder_name": "Deepankar Sr"
  },
  "cprn": "ISU12345"
},
{
  "billeraccountid": "3761840793853952",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "CARI00000NATN8",
  "short_name": "gyan",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Bill Number",
      "value": "12345676"
    }
  ],
}
```



```
"status": "ACTIVE",
"registration_date": "21-04-2025 12:24:37",
"autopay_status": "N",
"autopay_start_date": null,
"autopay_end_date": null,
"payment_amount": "0.00",
"currency": "356",
"frequency": "Monthly",
"payment_account": {
  "paymentaccountid": "3761840793853952",
  "objectid": "paymentaccount",
  "customerid": "1234567890",
  "short_name": "",
  "status": "ACTIVE",
  "payment_method": "",
  "card_start": "",
  "card_end": "",
  "cardholder_name": ""
},
"cprn": ""
},
{
  "billeraccountid": "4181875832135680",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
  "billerid": "BESCOM000KAR01",
  "short_name": "HOME19",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Billing cycle",
      "value": "02"
    }
  ],
  "status": "ACTIVE",
  "registration_date": "22-04-2025 16:47:40",
  "autopay_status": "N",
  "autopay_start_date": null,
```

```
"autopay_end_date": null,
"payment_amount": "0.00",
"currency": "356",
"frequency": "Monthly",
"payment_account": {
  "paymentaccountid": "4181875832135680",
  "objectid": "paymentaccount",
  "customerid": "1234567890",
  "short_name": "",
  "status": "ACTIVE",
  "payment_method": "",
  "card_start": "",
  "card_end": "",
  "cardholder_name": ""
},
"cprn": ""
}
]
```

9.3.2 Failed

```
{
  "status": "FAILED",
  "statusCode": "1",
  "statusDescription": "No favorite billers have been added for this customer.",
  "timeStamp": 1745487217480,
  "traceId": "a1712aeb072a4eaf98a2e202dfafdf6b",
  "data": null
}
```

10 Delete Favorite Biller API

Description: This API facilitates deleting a biller account through the following request.

Endpoint: /BOBCOU/BBPS/<sourceid>/customers/<customerid>/billpay/billeraccounts/<billeraccountid>

Method: DELETE

10.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:0f883fadcc19632e8c5a6e5c1c6b0043b35e2432a7480034f25aacc58ca68594

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

10.2 Response Body Parameters

Parameters	Parameter description	Data type
billeraccountid	Biller Account ID	String
objectid	Object ID	String
sourceid	Source ID	String

billerid	Biller ID	String
short_name	Short Name	String
authenticators	Authenticators	Object
seq	Sequence	String
parameter_name	Parameter Name	String
value	Value	String
status	Status of the Operation.	String
registration_date	Date of Registration.	String
deletion_date	Date of Deletion.	String
Only for Failed Response		
statusCode	Status Code of the Operation.	String
statusDescription	Status Description of the Operation.	String
timeStamp	Timestamp of the Failed Operation.	Timestamp
traceld	Trace ID	String
data	Data.	String

10.3 Sample Response Body

10.3.1 Success

```
{
  "billeraccountid": "4181283386695680",
  "objectid": "billeraccount",
  "sourceid": "SRC01",
```

```
"billerid": "AVVNL0000RAJ01",
"short_name": "HOME190",
"authenticators": [
  {
    "seq": "1",
    "parameter_name": "Billing cycle",
    "value": "02"
  },
  {
    "seq": "2",
    "parameter_name": "Consumer number",
    "value": "111111111"
  }
],
"status": "DELETED",
"registration_date": "22-04-2025 16:40:08",
"deletion_date": "24-04-2025 15:08:11"
}
```

Failed

```
{
  "status": "FAILED",
  "statusCode": "1",
  "statusDescription": "Biller is already deleted or inactive.",
  "timeStamp": 1745487584344,
  "traceId": "824d29581a78448e8f45dff5ee85a4e6",
  "data": null
}
```

11 Fetch by Billers ID API

Description: This API used to retrieve detailed information about a specific biller using its unique Biller ID.

Endpoint: /BOBCOU/BBPS/<sourceid>/billpay/billers/<billerid>

Endpoint Example: /BOBCOU/BBPS/upi/billpay/billers/AIRT00000NAT87

Method: GET

NOTE:

The sourceid parameter must be provided by the API consumer, and its value may be one of the following based on the user's channel: **mbanking**, **upi fi**, or **feature-phone**.

11.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:5ff0351eae3c3ef5016d87d83d7a0c57c0ae2c61dddc7943350b0fc809f399ca

11.2 Response Body Parameters

Parameters	Parameter description	Data type
billerid	Unique Identifier for the Biller	String

objectid	Object ID	String
sourceid	Unique Identifier for the Source	String
biller_legal_name	Legal Name of the Biller	String
biller_name	Name of the Biller	String
biller_location	Biller Location	String
biller_location_desc	Biller Location Description	String
biller_category	Category under which the Biller falls.	String
biller_reg_address	Registered Address of the Biller	String
biller_reg_city	Registered City of the Biller.	String
biller_reg_pin	Biller's registered PIN (address)	String
biller_reg_state	Registered State of the Biller	String
biller_reg_country	Registered Country of the Biller.	String
isbillerbbps	Is Biller BBPS or not.	String
currency	Currency	String
biller_type	Biller Type	String
biller_mode	Biller Mode	String
allowed_payment_methods	Allowed Payment Methods	String
payment_method	Payment Method.	String
payment_method_category	Category of the Payment Method.	String
min_limit	Minimum payment amount	String

max_limit	Maximum payment amount	String
autopay_allowed	Autopay is allowed or not	String
paylater_allowed	Is Paylater allowed or not	String
payment_channels	Payment Channel Details	String
payment_channel	Payment Channel	String
min_limit	Minimum Limit	String
max_limit	Maximum Limit	String
biller_effective_from	Biller is Effective from (Date)	String
biller_effective_to	Biller is Effective up to (Date)	String
biller_status	Status of the Biller	String
temp_deactivation_start	Date when Temporary Deactivation Started.	String
temp_deactivation_end	Date when Temporary Deactivation Ended.	String
biller_created_date	Biller creation Date	String
biller_lastmodified_date	Date on which the Biller was last modified.	String
authenticators	Authenticators	Object
seq	Sequence	String
parameter_name	Parameter Name	String
data_type	Data type of the parameter	String
optional	Is optional or not	String
regex	REGEX	String

error_message	Error Message	String
encryption_required	Encryption is required or not	String
list_of_values	List of values	Object
biller_logo	Biller Logo	String
biller_bill_copy	Biller's copy of the Bill	String
biller_remarks	Biller Remarks	String
partial_pay	Partial Pay	String
partial_pay_amount	Partial Pay Amount	String
pay_after_duedate	Payment after due date	String
online_validation	Online Validation	String
customer_conv_fee	Customer Convenience Fee Charged	String
plan_available	Plans Available	String
paymentamount_validation	Payment Amount Validation	String
additional_validation_details	Other Additional Validation Details	String

11.3 Sample Response Body

Success

```
{
  "billerid": "AIRT00000NAT87",
  "objectid": "biller",
  "sourceid": "upi",
  "biller_legal_name": "Airtel DTH",
  "biller_name": "Airtel DTH",
```

```
"biller_location": "",
"biller_location_desc": "IND",
"biller_category": "DTH",
"biller_reg_address": "",
"biller_reg_city": "",
"biller_reg_pin": "",
"biller_reg_state": "",
"biller_reg_country": "",
"isbillerbbps": "",
"currency": "",
"biller_type": "Biller",
"biller_mode": "ONLINE",
"allowed_payment_methods": [
  {
    "payment_method": "Internet Banking",
    "payment_method_category": "Internet Banking",
    "min_limit": "5000",
    "max_limit": null,
    "autopay_allowed": "",
    "paylater_allowed": "Y"
  },
  {
    "payment_method": "Debit Card",
    "payment_method_category": "Debit Card",
    "min_limit": "5000",
    "max_limit": null,
    "autopay_allowed": "",
    "paylater_allowed": "Y"
  },
  {
    "payment_method": "Credit Card",
    "payment_method_category": "Credit Card",
    "min_limit": "5000",
    "max_limit": null,
    "autopay_allowed": "",
    "paylater_allowed": "Y"
  },
  {
```

```
"payment_method": "Prepaid Card",
"payment_method_category": "Prepaid Card",
"min_limit": "5000",
"max_limit": null,
"autopay_allowed": "",
"paylater_allowed": "Y"
},
{
  "payment_method": "IMPS",
  "payment_method_category": "IMPS",
  "min_limit": "5000",
  "max_limit": null,
  "autopay_allowed": "",
  "paylater_allowed": "Y"
},
{
  "payment_method": "Cash",
  "payment_method_category": "Cash",
  "min_limit": "5000",
  "max_limit": null,
  "autopay_allowed": "",
  "paylater_allowed": "N"
},
{
  "payment_method": "UPI",
  "payment_method_category": "UPI",
  "min_limit": "5000",
  "max_limit": null,
  "autopay_allowed": "",
  "paylater_allowed": "Y"
},
{
  "payment_method": "Wallet",
  "payment_method_category": "Wallet",
  "min_limit": "5000",
  "max_limit": null,
  "autopay_allowed": "",
  "paylater_allowed": "Y"
```

```
    },
    {
      "payment_method": "NEFT",
      "payment_method_category": "NEFT",
      "min_limit": "5000",
      "max_limit": null,
      "autopay_allowed": "",
      "paylater_allowed": "Y"
    },
    {
      "payment_method": "AEPS",
      "payment_method_category": "AEPS",
      "min_limit": "5000",
      "max_limit": null,
      "autopay_allowed": "",
      "paylater_allowed": "Y"
    },
    {
      "payment_method": "Account Transfer",
      "payment_method_category": "Account Transfer",
      "min_limit": "5000",
      "max_limit": null,
      "autopay_allowed": "",
      "paylater_allowed": "Y"
    }
  ],
  "payment_channels": [
    {
      "payment_channel": "INT",
      "min_limit": "5000",
      "max_limit": "1499900"
    },
    {
      "payment_channel": "INTB",
      "min_limit": "5000",
      "max_limit": "1499900"
    },
    {
```

```
"payment_channel": "MOB",
"min_limit": "5000",
"max_limit": "14999900"
},
{
  "payment_channel": "MOBB",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "POS",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "MPOS",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "ATM",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "BNKBRNCH",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "KIOSK",
  "min_limit": "5000",
  "max_limit": "14999900"
},
{
  "payment_channel": "AGT",
  "min_limit": "5000",
  "max_limit": "14999900"
```

```
    },
    {
      "payment_channel": "BSC",
      "min_limit": "5000",
      "max_limit": "1499900"
    }
  ],
  "biller_effective_from": "24-12-2019",
  "biller_effective_to": "24-12-2029",
  "biller_status": "ACTIVE",
  "temp_deactivation_start": "",
  "temp_deactivation_end": "",
  "biller_created_date": "",
  "biller_lastmodified_date": "",
  "authenticators": [
    {
      "seq": "1",
      "parameter_name": "Customer Id",
      "data_type": "NUMERIC",
      "optional": false,
      "regex": "^[0-9]{10}$",
      "error_message": "Please enter a valid Customer Id",
      "encryption_required": null,
      "list_of_values": []
    }
  ],
  "biller_logo": "",
  "biller_bill_copy": "",
  "biller_remarks": "",
  "partial_pay": "",
  "partial_pay_amount": "",
  "pay_after_duedate": "",
  "online_validation": "",
  "customer_conv_fee": null,
  "plan_available": null,
  "paymentamount_validation": null,
  "additional_validation_details": ""
}
```

Failed

```
{
  "status": 500,
  "error_type": "fetch_biller_by_billerid_error",
  "error_code": "ERR01FBB",
  "message": "Internal Server Error",
  "metadata": [
    {
      "name": "traceld",
      "value": "291348cb1fc6450ab516c3ba8f9dd382"
    }
  ]
}
```

12 Oneview API

Description: Oneview API under the BBPS framework provides a consolidated view of biller accounts and bill details for a given customerid. The goal is to streamline the registration and bill-fetching experience for clients by providing a single endpoint that aggregates biller account and corresponding bills data.

Endpoint: /BOBCOU/BBPS/mbanking/customers/<customerid>/billpay/oneview?
billeraccountid=<billeraccountid>&status=<status>&billid=<billid>

Endpoint Example: /BOBCOU/BBPS/mbanking/customers/1234567890/billpay/oneview?
billeraccountid=4958397710934016&status=EXPIRED&billid=BILL1

Method: GET

12.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:5ff0351eae3c3ef5016d87d83d7a0
c57c0ae2c61dddc7943350b0fc809f399ca

NOTE:

Change the Authorization and pass HMACSignature dynamically for all requests.

12.2 Response Body Parameters

Parameters	Parameter description	Data type
------------	-----------------------	-----------

objectid	Object ID	String
sourceid	Unique Identifier for the Source	String
customerid	Customer ID	String
billeraccount	Biller Account Details	Object
billeraccountid	Biller Account ID	String
objectid	Unique Identifier for the Object	String
billerid	Biller ID	String
short_name	Short Name	String
authenticators	Authenticators	Array
seq	Sequence	String
parameter_name	Parameter Name	String
value	Data type of the parameter	String
status	Status	String
registration_date	Registration Date	String
autopay_status	Status of Autopay	String
autopay_start_date	Date on which Autopay started	String
autopay_end_date	End date of the Autopay	String
autopay_amount	Amount to be paid through Autopay	String
frequency	Frequency of Autopay	String
payment_account	Payment Account	String

billlist	Bill List	Array
billid	Unique Identifier of the Bill. Bill ID	String
objectid	Object ID.	String
billnumber	Bill Number	String
billperiod	Bill period.	String
billdate	Date of the Bill	String
billduedate	Due date for the Bill	String
billamount	Amount to be paid against the Bill.	String
early_billduedate	Early Bill Due Date.	String
early_billdiscount	Discount on Bill against early payment.	String
early_billamount	Bill amount on early payment.	String
late_payment_charges	Charges for late bill payment.	String
late_payment_amount	Bill amount on late payment.	String
net_billamount	Net Bill Amount.	String
description	Description	String
additional_details	Bill additional details	Array
seq	Sequence	String
label	Label	String
value	Data type of the parameter	String
line_items	Line Items	Array

billstatus	Status of the Bill	String
------------	--------------------	--------

Exclusively for Failed Response

error_type	Error Type	String
error_code	Error Code	String
message	Message for the Operation. It signifies the result.	String
metadata	Metadata	Array
name	Name	String
value	Value	String

12.3 Sample Response Body

12.3.1 Success

```
{
  "objectid": "oneview",
  "sourceid": "mbanking",
  "customerid": "1234567890",
  "billeraccount": {
    "billeraccountid": "4958397710934016",
    "objectid": "billeraccount",
    "billerid": "TSTO00000NAT01",
    "short_name": "TSTO",
    "authenticators": [
      {
        "seq": 1,
        "parameter_name": "Billing cycle",
        "value": "02"
      },
      {
        "seq": 2,
        "parameter_name": "Consumer number",
        "value": "12345676"
      }
    ]
  },
  "status": "ACTIVE",
```

```
"registration_date": "Invalid date",
"autopay_status": "N",
"autopay_start_date": null,
"autopay_end_date": null,
"autopay_amount": null,
"frequency": null,
"payment_account": null
},
"billlist": [
  {
    "billid": "BILL1",
    "objectid": "bill",
    "billnumber": "123450001",
    "billperiod": "June",
    "billdate": "14-06-2015 05:30:00",
    "billduedate": "30-06-2017 05:30:00",
    "billamount": "20000.00",
    "early_billduedate": null,
    "early_billdiscount": null,
    "early_billamount": null,
    "late_payment_charges": null,
    "late_payment_amount": "300.00",
    "net_billamount": "20000.00",
    "description": "Bill payment for TSTO",
    "additional_details": [
      {
        "seq": 1,
        "label": "Customer Name",
        "value": "Ashish"
      },
      {
        "seq": 2,
        "label": "billnumber",
        "value": "123450001"
      },
      {
        "seq": 3,
        "label": "billfor",
        "value": "June 2015"
      }
    ],
    "line_items": [],
    "billstatus": "EXPIRED"
  }
]
```

12.3.2 Failed

```
{
  "status": 400,
  "error_type": "fetch_favourite_biller_accounts_error",
  "error_code": "ERR01FFBA",
  "message": "No favorite billers have been added for this customer.",
  "metadata": [
    {
      "name": "traceld",
      "value": "f8450cd6ce7a4d54913fc383c74fd666"
    }
  ]
}
```

13 Fetch Prepaid Plans API

Description: This API enables the system to retrieve available prepaid recharge plans for a selected operator & circle.

Endpoint: /BOBCOU/BBPS/<sourceid>/billpay/plans

Example - /BOBCOU/BBPS/<sourceid>/billpay/plans?billerid=BSNL00000NATHL&circle_name=Jammu And Kashmir&planid=6&plan_category_name=1month

Method: GET

NOTE:

Please change the Authorization, pass HMACSignature dynamically for the request.

INSTRUCTIONS:

Please use the clientId & secretKey provided below to generate HMACSignature -

Staging=>

clientId: K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ

secretKey:

de23da949cc44ed47cd30236089096e9576c2cc38695cf2127be804c4620c90be7ccf066d06b69767cf29377419c7cd6880aa3fc460ec200035034ecec8bf408

13.1 Headers

Content-Type: application/json

Accept: application/json

BD-Traceid: a453c1353

BD-Timestamp: 20160528121320

Authorization: HMACSignature

K3U4UPRTORN2HMHYGYCKRUBMLLTFKWIDZ6EJKYY2Z3FT72F3WIRQ:5ff0351eae3c3ef5016d87d83d7a0c57c0ae2c61dddc7943350b0fc809f399ca

Query Params Request body:**billerid=BSNL00000NATHL &circle_name=Jammu And Kashmir&planid=6&plan_category_name=1month**

13.2 Request Details

Parameters	Parameter description	Data type	Mandatory/ Optional/ Conditional
billerid	Unique Biller ID assigned to each biller	String	Mandatory
circle_name	Name of the circle	String	Mandatory
planid	Plan ID	String	Mandatory
plan_category_name	Name of the plan category	String	Mandatory

13.3 Response Body Parameters

Parameters	Parameter description	Data type
data	Fetches Data	Object
planid	Plan ID	String
objectid	Object ID	String
billerid	Unique Identifier for the Biller	String
biller_name	Name of the Biller	String
biller_category	Category under which the Biller falls.	String
circle_name	Name of the circle	String
circleid	Circle ID	String

plan_category_name	Name of the plan category	String
talktime	Talk time provided for a particular plan	String
amount	Amount	String
validity	Validity of the talk time	String
plan_description	Description of the selected plan	String
additional_info	Additional Information	Object
parameter_name	Name of the parameter	String
value	Value corresponding to the parameter	String
plan_created_on	When plan was created.	String
plan_status	Status of the plan	String
plan_validity	Validity of the plan	String
cat_seq	Category Sequence Number	String
plan_seq	Plan Sequence Number	String
plan_name	Name of the plan	String
For Failed Scenario		
error_type	Type of Error	Integer
error_code	Error Code	String
message	Message describing the error	String
metadata	Metadata	Object
name	Name	String

value	Value	String
-------	-------	--------

13.4 Sample Response Body

13.4.1 Success

```
{
  "data": [
    {
      "planid": "6",
      "objectid": "plan",
      "billerid": "BSNL00000NATHL",
      "biller_name": "BSNL",
      "biller_category": "Mobile Prepaid",
      "circle_name": "Jammu And Kashmir",
      "circleid": null,
      "plan_category_name": "1 Month",
      "talktime": "100",
      "amount": "999.0",
      "validity": "1 Month",
      "plan_description": "HD Quality Music 10 Million Songs and Music Videos Unlimited Downloads on the Hungama Music app Ad-Free Experience on the Hungama Music app Use your subscription on up to 5 devices",
      "additional_info": [
        {
          "parameter_name": "Talktime",
          "value": "100"
        },
        {
          "parameter_name": "Validity",
          "value": "1 Month"
        },
        {
          "parameter_name": "Data",
          "value": "1 GB per day"
        },
        {
          "parameter_name": "Circle",
          "value": "Jammu And Kashmir"
        },
        {
          "parameter_name": "Plan Type",
          "value": "Unlimited"
        },
        {
          "parameter_name": "Additional Benefits",
```

```
        "value": "Premium Customer Support and 14 OTT Apps"
      }
    ],
    "plan_created_on": null,
    "plan_status": "ACTIVE",
    "plan_validity": "1 Month",
    "cat_seq": null,
    "plan_seq": null,
    "plan_name": null
  }
]
```

13.4.2 Failed

13.4.2.1 Fetch Prepaid Plan Error

```
{
  "status": 400,
  "error_type": "fetch_prepaid_plan_error",
  "error_code": "104",
  "message": "No biller found for the provided IDs.",
  "metadata": [
    {
      "name": "traceld",
      "value": "4a6baeaeb93049ca8d7e6c365f9fef1b"
    }
  ]
}
```

13.4.2.2 No Plans Found

```
{
  "status": 404,
  "error_type": "no_plans_found",
  "error_code": "ERR01FPP",
  "message": "No prepaid plans found for the given criteria.",
  "metadata": [
    {
      "name": "traceld",
      "value": 1770618911946
    }
  ]
}
```

THANK YOU

iServeU Technology Pvt. Ltd.

www.iserveu.in | info@iserveu.in | support@iserveu.in