NAME- ASHUTOSH ARDU
REG NO.- 20BRS1262
DATE- 19-04-2021

CSE1004 LAB-5

ALGORITHM

- First establish a connection between a Client and a Server using socket programming.
- Then send a message from server to client and then receive that particular message at the client end.
- Then resend that previous message this time from client to server.
- Hence, echoing the message that was first sent from server to client back to the server from the client.

CODE

SERVER SIDE

```c
#include<stdio.h>
#include<sys/socket.h>
#include<netinet/in.h>
#include<stdlib.h>
#include<string.h>
// Server Side
int main()
{
    int s,b,sport,key;
    char mess[100];
    printf("Enter the message\n");
    scanf("%s",mess);
    struct sockaddr_in saddr,caddr;
    printf("Enter any Desired port number\n");
    scanf("%d",&sport);
    int clen=sizeof(caddr);
    s=socket(AF_INET,SOCK_STREAM,0);
    if(s<0)
    {
        printf("Error while socket creation\n");
    }
```

```
    else
        printf("Socket created successfully\n");
    saddr.sin_family=AF_INET;
    saddr.sin_addr.s_addr=htonl(INADDR_ANY);
    saddr.sin_port=htons(sport);
    b=bind(s,(struct sockaddr*)&saddr,sizeof(saddr));
    if(b==0)
        printf("Interface binded to the socket\n");
    else
        printf("Interface not binded to the socket\n");
    listen(s,5);
    key=accept(s,(struct sockaddr*)&caddr,&clen);
    if(key<0)
        printf("Error\n");
    else
        printf("Well Connected\n");
    send(key,mess,sizeof(mess),0);
    char buffer[100];
    recv(key,buffer,sizeof(buffer),0);
    printf("The echoed message is %s",buffer);

}
```

CLIENT SIDE

```
#include<stdio.h>
#include<sys/socket.h>
#include<netinet/in.h>
#include<string.h>
// Client Side
int main()
{
    int soc,port;
    char mess[100];
    struct sockaddr_in server,client;
    printf("Enter the port no.\n");
    scanf("%d",&port);
    soc=socket(AF_INET,SOCK_STREAM,0);
    if(soc<0)
        printf("Socket not created\n");
    else
        printf("Socket Created\n");
    server.sin_family=AF_INET;
    server.sin_addr.s_addr=htonl(INADDR_ANY);
```

```
        server.sin_port=htons(port);


        if(connect(soc,(struct sockaddr*)&server,sizeof(server))<0)
            printf("Can't connect\n");
        else
            printf("Connected\n");
        recv(soc,mess,sizeof(mess),0);
        printf("the message is \n%s\n",mess);
        char buffer[100];
        strcpy(buffer,mess);
        send(soc,buffer,sizeof(buffer),0);
        return 0;
}
```

OUTPUT

ENTER THE MESSAGE AND SELECT A PORT NUMBER
IN WHICH THE MESSAGE WILL GET TRANSFERRED.



AFTER ENTERING THE PORT NUMBER, WE CREATE A SOCKET
AND BIND OUR SERVER TO IT.

ON THE CLIENT SIDE WE CONNECT OUR CLIENT
TO THE PORT TO WHICH OUR SERVER IS BINDED TO.

AFTER THE CLIENT GETS CONNECTED TO THE SOCKET
IT SUDDENLY RECEIVES THE MESSAGE SENT BY THE SERVER
AFTER THAT CLIENT RESEND THE MESSAGE BACK TO THE SERVER.

ON THE SERVER SIDE
IT RECEIVES THE ECHOED MESSAGE FROM THE CLIENT