

SecureMailScope report

demo_enterprise.pcap · capture 2026-09-14T09:00:00+00:00 to 2026-09-14T09:09:00+00:00 · analysed 2026-10-01T16:24:09+00:00
Input SHA-256 a6849ca350a4aab167240d33e61f8c63b64bd297c083fbd41ee62bfcac9e9730

Posture F (0/100) · 19 sessions · critical 9 · high 17 · medium 5 · low 7 · info 5

#	Severity	Finding	Endpoint	Risk
1	CRITICAL	Credentials sent in cleartext (SMS-CRED-001) ×1	smtp.example.com:587	80
2	CRITICAL	Credentials sent in cleartext (SMS-CRED-001) ×1	203.0.113.12:143	80
3	CRITICAL	STARTTLS vanished versus endpoint baseline - possible active MITM (SMS-BASE-001) ×1	smtp.example.com:587	76
4	CRITICAL	STARTTLS stripping indicators (SMS-STRIP-001) ×1	smtp.example.com:587	76
5	CRITICAL	STARTTLS command/response injection (SMS-INJ-001) ×1	smtp.example.com:587	72
6	CRITICAL	STARTTLS vanished versus endpoint baseline - possible active MITM (SMS-BASE-001) ×1	mx.example.com:25	65
7	CRITICAL	STARTTLS stripping indicators (SMS-STRIP-001) ×1	mx.example.com:25	65
8	CRITICAL	Certificate changed versus endpoint baseline - possible MITM (SMS-BASE-002) ×1	mx.example.com:25	61
9	CRITICAL	Self-signed certificate (deviates from endpoint baseline: possible MITM with substitute certificate) (SMS-CERT-002) ×1	mx.example.com:25	58
10	HIGH	Message content transmitted in cleartext (SMS-DATA-001) ×1	smtp.example.com:587	56
11	HIGH	Message content transmitted in cleartext (SMS-DATA-001) ×1	203.0.113.12:143	56
12	HIGH	Server does not offer STARTTLS (SMS-PLAIN-001) ×1	203.0.113.12:143	56
13	HIGH	Server selected a cipher suite the client did not offer (SMS-TLS-013) ×2	203.0.113.11:465	53
14	HIGH	Message content transmitted in cleartext (SMS-DATA-001) ×1	printer-relay.corp.example.com:2525	50
15	HIGH	Certificate hostname mismatch (SMS-CERT-003) ×1	203.0.113.11:465	48
16	HIGH	Message content transmitted in cleartext (SMS-DATA-001) ×1	mx.example.com:25	48
17	HIGH	Protocol downgrade versus endpoint baseline (SMS-BASE-003) ×1	smtp.example.com:587	45
18	HIGH	Certificate expired (SMS-CERT-001) ×1	pop.oldmail.example.net:110	45
19	HIGH	Downgrade sentinel present (SMS-TLS-010) ×1	smtp.example.com:587	45
20	HIGH	Weak certificate key (RSA 1024) (SMS-CERT-004) ×1	pop.oldmail.example.net:110	42
21	HIGH	Obsolete protocol TLS 1.0 (SMS-TLS-001) ×1	pop.oldmail.example.net:110	42

#	Severity	Finding	Endpoint	Risk
22	HIGH	Weak cipher suite TLS_RSA_WITH_3DES_EDE_CBC_SHA (SMS-TLS-002) ×1	pop.oldmail.example.net: 110	42
23	HIGH	Weak Diffie-Hellman group (1024 bits) (SMS-TLS-005) ×2	203.0.113.11:465	42
24	HIGH	Weak certificate signature hash (SMS-CERT-005) ×1	pop.oldmail.example.net: 110	39
25	MEDIUM	Client ignored offered STARTTLS (SMS-PLAIN-002) ×1	printer-relay.corp.example.com:2525	29
26	MEDIUM	Certificate does not chain to a trusted root (SMS-CERT-007) ×1	pop.oldmail.example.net: 110	26
27	MEDIUM	No forward secrecy (SMS-TLS-003) ×1	pop.oldmail.example.net: 110	22
28	MEDIUM	Statistical outlier session (isolation forest) (SMS-ML-001) ×1	pop.oldmail.example.net: 110	21
29	MEDIUM	No secure renegotiation (RFC 5746) (SMS-TLS-009) ×1	pop.oldmail.example.net: 110	21
30	LOW	CBC-mode cipher negotiated (SMS-TLS-004) ×2	203.0.113.11:465	8
31	LOW	Client offers broken cipher suites (SMS-TLS-006) ×1	pop.oldmail.example.net: 110	7
32	LOW	No Extended Master Secret (SMS-TLS-012) ×2	203.0.113.11:465	7
33	LOW	SMTP on non-standard port 2525 (SMS-PORT-001) ×1	printer-relay.corp.example.com:2525	7
34	LOW	No Extended Master Secret (SMS-TLS-012) ×1	mx.example.com:25	6
35	INFO	Certificate not observable (TLS 1.3) (SMS-CERT-010) ×4	smtp.example.com:587	0
36	INFO	Certificate not observable (TLS 1.3) (SMS-CERT-010) ×1	203.0.113.12:993	0

Details

CRITICAL Credentials sent in cleartext — smtp.example.com:587 (S010)

- LOGIN for user 'ananya.sharma@example.com' (accepted); password/token crossed the wire unencrypted (secret not stored)

Fix: Refuse authentication before TLS: Postfix smtpd_tls_auth_only = yes; Dovecot disable_plaintext_auth = yes / auth_allow_cleartext = no. Rotate the exposed credentials listed in the evidence - they must be assumed compromised.

PCI DSS 4.0 Req. 8.3.2 (auth factors unreadable in transit); RFC 8314 §3; ISO/IEC 27001:2022 A.8.5

CRITICAL Credentials sent in cleartext — 203.0.113.12:143 (S017)

- IMAP-LOGIN for user 'rahul.verma' (accepted); password/token crossed the wire unencrypted (secret not stored)

Fix: Refuse authentication before TLS: Postfix smtpd_tls_auth_only = yes; Dovecot disable_plaintext_auth = yes / auth_allow_cleartext = no. Rotate the exposed credentials listed in the evidence - they must be assumed compromised.

PCI DSS 4.0 Req. 8.3.2 (auth factors unreadable in transit); RFC 8314 §3; ISO/IEC 27001:2022 A.8.5

CRITICAL STARTTLS vanished versus endpoint baseline - possible active MITM —

smtp.example.com:587 (S010)

- endpoint offered TLS in 7 of 7 baseline sessions; this session: capability absent
- EHLO capability 'XXXXXXXX' is a same-length rewrite of STARTTLS

Fix: Treat as a potential active interception: preserve this capture (hash recorded in the report), trace the network path between the client and the server (ARP/DHCP/DNS spoofing, rogue gateway, compromised middlebox), and verify the server's real certificate out-of-band. Long term: MTA-STS enforce / DANE for relays, implicit TLS with certificate validation for clients.

CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h); ISO/IEC 27001:2022 A.5.25 (assessment of security events)

CRITICAL STARTTLS stripping indicators — smtp.example.com:587 (S010)

- EHLO capability 'XXXXXXXX' is a same-length rewrite of STARTTLS
- capabilities seen: PIPELINING SIZE XXXXXXXX AUTH ENHANCEDSTATUSCODES 8BITMIME DSN

Fix: Move clients to implicit TLS (465 / 993 / 995, RFC 8314): there is no cleartext upgrade to strip. Postfix submission: smtpd_tls_security_level = encrypt, smtpd_tls_auth_only = yes. Dovecot: ssl = required and disable_plaintext_auth = yes (2.4: auth_allow_cleartext = no). Set mail clients to 'TLS required', never 'STARTTLS if available'.

RFC 3207 §6; RFC 8461 (MTA-STS); RFC 7672 (DANE); RFC 8314; CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h)

CRITICAL STARTTLS command/response injection — smtp.example.com:587 (S013)

- client sent 41 bytes of cleartext after STARTTLS before TLS (pipelined commands: RSET, MAIL)

Fix: Upgrade the server/client: the implementation must discard any buffered plaintext when TLS starts (CVE-2011-0411 class; 40+ implementations affected per Poddebniak et al. 2021). Check Postfix, Dovecot, Exim, Courier versions; prefer implicit TLS ports which have no upgrade step.

CVE-2011-0411 class; Poddebniak et al., USENIX Security 2021; CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h)

CRITICAL STARTTLS vanished versus endpoint baseline - possible active MITM — mx.example.com:25 (S011)

- endpoint offered TLS in 10 of 10 baseline sessions; this session: no TLS
- STARTTLS refused with '454 4.7.0 TLS not available due to local problem'

Fix: Treat as a potential active interception: preserve this capture (hash recorded in the report), trace the network path between the client and the server (ARP/DHCP/DNS spoofing, rogue gateway, compromised middlebox), and verify the server's real certificate out-of-band. Long term: MTA-STS enforce / DANE for relays, implicit TLS with certificate validation for clients.

CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h); ISO/IEC 27001:2022 A.5.25 (assessment of security events)

CRITICAL STARTTLS stripping indicators — mx.example.com:25 (S011)

- STARTTLS refused with '454 4.7.0 TLS not available due to local problem'
- capabilities seen: PIPELINING SIZE VRFY ETRN STARTTLS ENHANCEDSTATUSCODES 8BITMIME DSN SMTPUTF8 CHUNKING

Fix: Publish an MTA-STS policy in mode: enforce (RFC 8461) and/or DANE TLSA records (RFC 7672) so sending MTAs refuse to deliver without TLS. On Postfix senders use smtpd_tls_security_level = dane (or encrypt/verify per destination via smtpd_tls_policy_maps). Inspect the network path: a same-length rewrite of the capability is the signature of an inline stripping device or compromised middlebox.

RFC 3207 §6; RFC 8461 (MTA-STS); RFC 7672 (DANE); RFC 8314; CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h)

CRITICAL Certificate changed versus endpoint baseline - possible MITM — mx.example.com:25 (S012)

- presented 7c7e962c3b5898e7... (issuer CN=mx.example.com,O=Example Corp)
- baseline certificates: 978a2d879a6551c1... x9
- new certificate is self-signed

Fix: Treat as a potential active interception: preserve this capture (hash recorded in the report), trace the network path between the client and the server (ARP/DHCP/DNS spoofing, rogue gateway, compromised middlebox), and verify the server's real certificate out-of-band. Long term: MTA-STS enforce / DANE for relays, implicit TLS with certificate validation for clients.

CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h); ISO/IEC 27001:2022 A.5.25 (assessment of security events)

CRITICAL Self-signed certificate (deviates from endpoint baseline: possible MITM with substitute certificate) — mx.example.com:25 (S012)

- subject = issuer = CN=mx.example.com,O=Example Corp
- sha256 7c7e962c3b5898e788e37cb6da004920...

Fix: Replace with a certificate from a publicly trusted CA, or - for MX hosts that intentionally use a private certificate - publish a DANE-EE TLSA record (3 1 1) so senders can authenticate it.

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

HIGH Message content transmitted in cleartext — smtp.example.com:587 (S010)

- 1135 bytes of message data outside TLS (content not stored)

Fix: Message content crossed the network unencrypted. Require TLS for this path (see transport findings) and treat the listed messages as disclosed.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

HIGH Message content transmitted in cleartext — 203.0.113.12:143 (S017)

- 1135 bytes of message data outside TLS (content not stored)

Fix: Message content crossed the network unencrypted. Require TLS for this path (see transport findings) and treat the listed messages as disclosed.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

HIGH Server does not offer STARTTLS — 203.0.113.12:143 (S017)

- capabilities: IMAP4REV1 IDLE
- port class: access

Fix: Enable TLS and make it mandatory: Postfix smtpd_tls_security_level = encrypt; Dovecot ssl = required. Prefer implicit TLS ports 465/993/995 (RFC 8314) and close 110/143 to clients.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

HIGH Server selected a cipher suite the client did not offer — 203.0.113.11:465 (S015, S016)

- selected TLS_DHE_RSA_WITH_AES_128_CBC_SHA
- client offered 12 suites, not including it
- a conforming server cannot do this; the ServerHello did not come from the client's peer

Fix: A conforming server cannot answer outside what the client offered, so treat this as a possible in-path device rewriting the handshake. Capture again from the same tap point, compare against a capture taken adjacent to the server, and audit any TLS-inspecting proxy or load balancer between the two hosts.

RFC 3207 §6; RFC 8461 (MTA-STS); RFC 7672 (DANE); RFC 8314; CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h)

HIGH Message content transmitted in cleartext — printer-relay.corp.example.com:2525 (S019)

- 1122 bytes of message data outside TLS (content not stored)

Fix: Message content crossed the network unencrypted. Require TLS for this path (see transport findings) and treat the listed messages as disclosed.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

HIGH Certificate hostname mismatch — 203.0.113.11:465 (S016)

- expected 'mail.corp.example.com'
- certificate names: DNS:*.example.com, DNS:example.com

Fix: Reissue the certificate with the mail host's name (the MX / submission hostname) in subjectAltName.

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

HIGH Message content transmitted in cleartext — mx.example.com:25 (S011)

- 1136 bytes of message data outside TLS (content not stored)

Fix: Message content crossed the network unencrypted. Require TLS for this path (see transport findings) and treat the listed messages as disclosed.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

HIGH Protocol downgrade versus endpoint baseline — smtp.example.com:587 (S014)

- negotiated TLS 1.2; endpoint normally negotiates TLS 1.3 (6/6 sessions)

Fix: Treat as a potential active interception: preserve this capture (hash recorded in the report), trace the network path between the client and the server (ARP/DHCP/DNS spoofing, rogue gateway, compromised middlebox), and verify the server's real certificate out-of-band. Long term: MTA-STS enforce / DANE for relays, implicit TLS with certificate validation for clients.

CERT-In Directions 28 Apr 2022 (attack on mail server: report within 6 h); ISO/IEC 27001:2022 A.5.25 (assessment of security events)

HIGH Certificate expired — pop.oldmail.example.net:110 (S018)

- notAfter 2024-01-01T00:00:00+00:00 (988 days before capture)
- CN=pop.oldmail.example.net,O=OldMail Ltd

Fix: Renew the certificate and automate renewal (ACME: certbot / acme.sh with a deploy hook running postfix reload and doveadm reload).

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

HIGH Downgrade sentinel present — smtp.example.com:587 (S014)

- ServerHello.random ends with DOWNGRD marker (TLS1.2) while negotiating TLS 1.2
- client offered: TLS 1.3, TLS 1.2

Fix: A TLS 1.3-capable server negotiated a lower version and signalled it (RFC 8446 §4.1.3). Check the client's TLS library and any middlebox on the path; enable TLS 1.3 end to end.

NIST SP 800-52 Rev. 2 §3.1 (TLS 1.2 minimum, TLS 1.3 support); RFC 8996 (TLS 1.0/1.1 deprecated); PCI DSS 4.0 Req. 4.2.1

HIGH Weak certificate key (RSA 1024) — pop.oldmail.example.net:110 (S018)

- RSA 1024-bit public key

Fix: Reissue with RSA >= 2048 bits or ECDSA P-256.

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

HIGH Obsolete protocol TLS 1.0 — pop.oldmail.example.net:110 (S018)

- negotiated TLS 1.0 (ServerHello legacy_version 0x0301)
- TLS 1.0 is deprecated by RFC 8996 (BEAST, no AEAD suites, SHA-1/MD5 PRF)

Fix: Postfix: smtpd_tls_protocols = >=TLSv1.2 and smtpd_tls_mandatory_protocols = >=TLSv1.2 (same for smtp_ on the client side). Dovecot: ssl_min_protocol = TLSv1.2.

NIST SP 800-52 Rev. 2 §3.1 (TLS 1.2 minimum, TLS 1.3 support); RFC 8996 (TLS 1.0/1.1 deprecated); PCI DSS 4.0 Req. 4.2.1

HIGH Weak cipher suite TLS_RSA_WITH_3DES_EDE_CBC_SHA — pop.oldmail.example.net:110 (S018)

- negotiated 0x000A TLS_RSA_WITH_3DES_EDE_CBC_SHA (grade F)
- 64-bit block cipher: Sweet32 birthday attack (CVE-2016-2183)

Fix: Postfix: smtpd_tls_mandatory_ciphers = high, smtpd_tls_exclude_ciphers = aNULL, eNULL, EXPORT, RC4, 3DES, MD5, DES, IDEA, tls_preempt_cipherlist = yes. Dovecot: ssl_cipher_list = ECDHE+AESGCM:ECDHE+CHACHA20:DHE+AESGCM:!aNULL:!MD5:!RC4:!3DES, ssl_prefer_server_ciphers = yes.

NIST SP 800-52 Rev. 2 §3.3.1 (approved cipher suites); PCI DSS 4.0 Req. 4.2.1; ISO/IEC 27001:2022 A.8.24

HIGH Weak Diffie-Hellman group (1024 bits) — 203.0.113.11:465 (S015, S016)

- ServerKeyExchange DH prime is 1024 bits

Fix: Use a 2048-bit or larger DH group (openssl dhparam -out dh2048.pem 2048; Postfix smtpd_tls_dh1024_param_file = /etc/postfix/dh2048.pem, Dovecot ssl_dh = </etc/dovecot/dh.pem) or drop DHE in favour of ECDHE.

NIST SP 800-52 Rev. 2 §3.3.1 (approved cipher suites); PCI DSS 4.0 Req. 4.2.1; ISO/IEC 27001:2022 A.8.24

HIGH Weak certificate signature hash — pop.oldmail.example.net:110 (S018)

- cert #0 (CN=pop.oldmail.example.net,O=OldMail Ltd) signed with SHA1

Fix: Reissue with a SHA-256 (or stronger) signature.

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

MEDIUM Client ignored offered STARTTLS — printer-relay.corp.example.com:2525 (S019)

- server advertised STARTTLS; client continued with EHLO, MAIL, RCPT, DATA, QUIT

Fix: Server offered STARTTLS but the client did not use it. Configure the client (or sending MTA: smtp_tls_security_level = may at minimum) to always upgrade; for submission/access require TLS server-side so the client cannot proceed in cleartext.

RFC 8314 (cleartext submission/access deprecated); ISO/IEC 27001:2022 A.5.14; ISO/IEC 27001:2022 A.8.24

MEDIUM Certificate does not chain to a trusted root — pop.oldmail.example.net:110 (S018)

- a certificate in the path was outside its validity window at capture time, so the path could not be built
- issuer: CN=OldMail Internal CA,O=OldMail Ltd

Fix: Use a certificate chaining to a trusted root, or distribute the private CA to all clients / use DANE.

NIST SP 800-52 Rev. 2 §3.2 (server certificates); PCI DSS 4.0 Req. 4.2.1 (certificates valid, not expired); ISO/IEC 27001:2022 A.8.24

MEDIUM No forward secrecy — pop.oldmail.example.net:110 (S018)

- TLS_RSA_WITH_3DES_EDE_CBC_SHA uses RSA key transport

- all recorded sessions become decryptable if the server private key is ever exposed

Fix: Prefer ECDHE key exchange: put ECDHE suites first and remove static-RSA suites (smtpd_tls_exclude_ciphers = kRSA in Postfix; !kRSA in Dovecot ssl_cipher_list).

NIST SP 800-52 Rev. 2 §3.3.1 (approved cipher suites); PCI DSS 4.0 Req. 4.2.1; ISO/IEC 27001:2022 A.8.24

MEDIUM Statistical outlier session (isolation forest) — pop.oldmail.example.net:110 (S018)

- anomaly score 0.665
- proto_pop3=1 (population mean 0.03, z=+5.3)
- cert_weak_sig=1 (population mean 0.03, z=+5.3)
- cert_key_weakness=0.5 (population mean 0.02, z=+5.3)

Fix: Review this session against the endpoint's normal behaviour; outliers are leads, not verdicts.

MEDIUM No secure renegotiation (RFC 5746) — pop.oldmail.example.net:110 (S018)

- ServerHello lacks renegotiation_info

Fix: Upgrade OpenSSL / the TLS library to one supporting RFC 5746 secure renegotiation.

NIST SP 800-52 Rev. 2 §3.1 (TLS 1.2 minimum, TLS 1.3 support); RFC 8996 (TLS 1.0/1.1 deprecated); PCI DSS 4.0 Req. 4.2.1

LOW CBC-mode cipher negotiated — 203.0.113.11:465 (S015, S016)

- TLS_DHE_RSA_WITH_AES_128_CBC_SHA: MAC-then-encrypt

Fix: Prefer AEAD suites (AES-GCM, ChaCha20-Poly1305) ahead of CBC suites, or enable TLS 1.3.

NIST SP 800-52 Rev. 2 §3.3.1 (approved cipher suites); PCI DSS 4.0 Req. 4.2.1; ISO/IEC 27001:2022 A.8.24

LOW Client offers broken cipher suites — pop.oldmail.example.net:110 (S018)

- offered: TLS_RSA_EXPORT_WITH_RC4_40_MD5, TLS_RSA_WITH_RC4_128_MD5, TLS_RSA_WITH_RC4_128_SHA

Fix: Remove legacy suites from the client/sending MTA (smtpd_tls_exclude_ciphers, client TLS settings).

NIST SP 800-52 Rev. 2 §3.3.1 (approved cipher suites); PCI DSS 4.0 Req. 4.2.1; ISO/IEC 27001:2022 A.8.24

LOW No Extended Master Secret — 203.0.113.11:465 (S015, S016)

- TLS 1.2 without RFC 7627 EMS (triple-handshake class)

Fix: Upgrade to a TLS library supporting RFC 7627 Extended Master Secret (OpenSSL >= 1.1.0) or enable TLS 1.3.

NIST SP 800-52 Rev. 2 §3.1 (TLS 1.2 minimum, TLS 1.3 support); RFC 8996 (TLS 1.0/1.1 deprecated); PCI DSS 4.0 Req. 4.2.1

LOW SMTP on non-standard port 2525 — printer-relay.corp.example.com:2525 (S019)

- identified from banner: 'printer-relay.corp.example.com ESMTP Sendmail 8.14.4; Mon, 14 Sep 2026 09:40:00 '

Fix: A mail service answered on a non-standard port. Confirm it is sanctioned; if not, it is shadow infrastructure outside your TLS policy - inventory it or shut it down.

ISO/IEC 27001:2022 A.5.9 (asset inventory)

LOW No Extended Master Secret — mx.example.com:25 (S012)

- TLS 1.2 without RFC 7627 EMS (triple-handshake class)

Fix: Upgrade to a TLS library supporting RFC 7627 Extended Master Secret (OpenSSL >= 1.1.0) or enable TLS 1.3.

NIST SP 800-52 Rev. 2 §3.1 (TLS 1.2 minimum, TLS 1.3 support); RFC 8996 (TLS 1.0/1.1 deprecated); PCI DSS 4.0 Req. 4.2.1