



ACL Intermediate Hands-On Lab Tasks

◆ Task 1: Give Specific User Access Without Changing Ownership

1. Create a file `report.txt`
2. Set owner as your current user and group as `devops`
3. Give **read-only** permission to user `john` using ACL
4. Verify ACL
5. Confirm `+` symbol appears in `ls -l`

🎯 Goal: Practice basic Access ACL.

◆ Task 2: Modify User Permission and Observe Mask Effect

1. Create file `data.txt`
2. Give `john` full permission (rwx)
3. Change mask to read-only
4. Check effective permission
5. Explain why john cannot write now

🎯 Goal: Understand how **mask limits effective permission**

◆ Task 3: Assign ACL to a Group

1. Create file `team.txt`
2. Give group `qa` read/write access using ACL
3. Verify using `getfacl`
4. Modify mask to read-only
5. Observe change in effective permission

🎯 Goal: Practice group ACL + mask behavior.

◆ Task 4: Apply Recursive ACL to Directory

1. Create directory `project`
2. Inside it create 3 files
3. Apply `rx` permission for `john` recursively
4. Verify ACL for all files
5. Remove recursively

🎯 Goal: Practice `-R` option.

◆ Task 5: Configure Default ACL for Directory

1. Create directory `shared`
2. Set default ACL so `john` gets `rw` permission

3. Create a new file inside `shared`
4. Verify john automatically gets permission
5. Confirm default ACL entry in directory

🎯 Goal: Understand inheritance via Default ACL.

◆ Task 6: Remove Only Default ACL Recursively

1. Create directory `datafolder`
2. Set default ACL for `john`
3. Create subdirectories inside it
4. Remove only default ACL recursively
5. Verify default entries are removed but access ACL remains

🎯 Goal: Practice `-k` and `-x d:u:` usage.

◆ Task 7: Remove Specific User ACL Entry

1. Create file `finance.txt`
2. Give ACL access to users `john` and `mike`
3. Remove only `john` ACL
4. Verify `mike` ACL still exists

🎯 Goal: Practice selective ACL removal.

◆ Task 8: Backup and Restore ACL

1. Create directory `backup_test`
2. Apply multiple ACL entries
3. Backup ACL to file `acl_backup.txt`
4. Remove all ACL
5. Restore ACL from backup file
6. Verify restoration

🎯 Goal: Practice ACL backup & restore.

◆ Task 9: Identify Files Having ACL in a Directory

1. Create directory `audit`
2. Create multiple files
3. Apply ACL only to some files
4. Use `ls -l` to identify files with ACL
5. Confirm using `getfacl`

🎯 Goal: Learn how to detect ACL presence.

◆ Task 10: Enterprise Scenario Simulation

Scenario:

- Create directory `company`

- Dev group → rwx
- QA group → r-x
- User john → rwx
- Others → no access
- Ensure new files inherit same rule

Tasks:

1. Set required Access ACL
2. Configure Default ACL
3. Verify inheritance
4. Restrict using mask if needed

 Goal: Combine everything in one real-world scenario.

After Completing These Tasks You Should Be Able To:

- ✓ Apply Access ACL
 - ✓ Configure Default ACL
 - ✓ Understand mask behavior
 - ✓ Use recursive options
 - ✓ Remove ACL selectively
 - ✓ Backup and restore ACL
 - ✓ Implement enterprise-level access control
-