

User Management in Linux

Multiple Choice Questions (MCQs)

Instructions: Answer all questions. Each question carries **1 mark**.

Form Link: <https://forms.gle/6xHvTfUXCod7NGKQA>

1 What is the UID of the root user?

- A) 1000
- B) 1
- C) 0
- D) 999

Answer: C

2 Which file stores hashed passwords?

- A) /etc/passwd
- B) /etc/shadow
- C) /etc/group
- D) /etc/login.defs

Answer: B

3 What does **!** in /etc/shadow password field mean?

- A) Password expired
- B) Account locked
- C) Disabled permanently
- D) Guest account

Answer: B

4 Default home directory of regular users is:

- A) /root
- B) /users
- C) /home
- D) /var/home

Answer: C

5 Which command creates a home directory automatically?

- A) useradd username
- B) useradd -m username
- C) usermod username
- D) addgroup username

Answer: B

6 Which command forces password change at next login?

- A) passwd -l
- B) chage -E
- C) chage -d 0
- D) usermod -L

Answer: C

7 Which file controls default password aging?

- A) /etc/passwd
- B) /etc/security
- C) /etc/login.defs
- D) /etc/skel

Answer: C

8 UID range for normal users usually starts from:

- A) 0
- B) 1
- C) 500
- D) 1000

Answer: D

9 Command to lock user account:

- A) passwd -u
- B) usermod -L
- C) useradd -L
- D) chage -L

Answer: B

10 What does `chage -M 60` do?

- A) Lock user
- B) Set minimum days
- C) Set maximum password validity
- D) Set expiry date

Answer: C

11 Which directory contains default files for new users?

- A) /etc/default
- B) /etc/home
- C) /etc/skel
- D) /home/default

Answer: C

12 Command to delete user with home directory:

- A) userdel user
- B) userdel -m user

- C) userdel -r user
- D) rmuser -r user

Answer: C

13) Which option sets account expiry?

- A) -M
- B) -E
- C) -m
- D) -W

Answer: B

14) Which file controls password complexity?

- A) /etc/login.defs
- B) /etc/security/pwquality.conf
- C) /etc/shadow
- D) /etc/passwd

Answer: B

15) What does **PASS_WARN_AGE define?**

- A) Password length
- B) Password reuse
- C) Warning before expiry
- D) Password complexity

Answer: C

16) Which command switches to root login shell?

- A) su root
- B) su -
- C) sudo root
- D) login root

Answer: B

17 System users usually have UID:

- A) 1000+
- B) 5000+
- C) 1–999
- D) Only 0

Answer: C

18 `usermod -s /sbin/nologin` does what?

- A) Deletes user
- B) Locks password
- C) Disables login shell
- D) Changes home directory

Answer: C

19 `INACTIVE=-1` means:

- A) Account inactive
- B) Never disable after expiry
- C) Lock after 1 day
- D) Expire immediately

Answer: B

20 `whoami` shows:

- A) UID
- B) Logged-in users
- C) Current username
- D) All users

Answer: C

