

Design and Analysis of Algorithms

Week-2 Assignment

1. Bubble Sort

PROGRAM:

```
#include <stdio.h>
int main() {
    int n;
    printf("ENTER NO.OF.ELEMENTS:");
    scanf("%d",&n);
    int arr[n];
    printf("ENTER THE VALUES:");
    for(int i=0;i < n;i++){
        scanf("%d",&arr[i]);
    }
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (arr[j] > arr[j + 1]) {
                int temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;
            }
        }
    }
    printf("Sorted array: ");
    for (int i = 0; i < n; i++) {
        printf("\t%d\t",arr[i]);
    }
    return 0;
}
```

```
amma@amma11:~$ gcc bubble_sort.c -o bubble_sort
amma@amma11:~$ ./bubble_sort
enter element 0: 6
enter element 1: 9
enter element 2: 8
enter element 3: 1
enter element 4: 3
1
3
6
8
9
```

2. Insertion Sort

PROGRAM:

```
#include <stdio.h>

int main() {
    int n;
    printf("ENTER NO.OF ELEMENTS");
    scanf("%d",&n);
    int arr[n];
    printf("ENTER THE ELEMENTS:");
    for(int i=0; i < n; i++){
        scanf("%d",&arr[i]);
    }
    for (int i = 1; i < n; i++) {
```

```
int key = arr[i];  
int j = i - 1;  
while (j >= 0 && arr[j] > key) {  
    arr[j + 1] = arr[j];
```

```
        j--;  
    }  
    arr[j + 1] = key;  
}  
printf("Sorted array: ");  
for (int i = 0; i < n; i++) {  
    printf("%d ", arr[i]);  
}  
return 0;  
}
```

```
amma@amma11:~$ gcc insertion.c -o insertion  
amma@amma11:~$ ./insertion  
enter element 0: 7  
enter element 1: 9  
enter element 2: 1  
enter element 3: 0  
enter element 4: 4  
0  
1  
4  
7  
9
```

3. Selection Sort

PROGRAM:

```
#include <stdio.h>

int main() {
    int n;

    printf("ENTER NO. OF ELEMENTS: ");
    scanf("%d", &n);

    int arr[n];


    printf("ENTER THE VALUES: ");
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    for (int i = 0; i < n - 1; i++) {
        int minIndex = i;

        for (int j = i + 1; j < n; j++) {
            if (arr[j] < arr[minIndex]) {
                minIndex = j;
            }
        }

        int temp = arr[i];
        arr[i] = arr[minIndex];
        arr[minIndex] = temp;
    }
}
```

```
}  
printf("Sorted array: ");  
for (int i = 0; i < n; i++) {  
    printf("%d ", arr[i]);  
}  
return 0;  
}
```



A terminal window with a dark purple background. The prompt is 'amma@amma11:~\$'. The user enters 'gcc selection_sort.c -o selection_sort'. The prompt changes to 'amma@amma11:~\$' and the user enters './selection_sort'. The program then prompts for five elements: 'enter element 0: 9', 'enter element 1: 1', 'enter element 2: 0', 'enter element 3: 3', and 'enter element 4: 6'. Finally, it prints the sorted array: '0', '1', '3', '6', '9'.

```
amma@amma11:~$ gcc selection_sort.c -o selection_sort  
amma@amma11:~$ ./selection_sort  
enter element 0: 9  
enter element 1: 1  
enter element 2: 0  
enter element 3: 3  
enter element 4: 6  
0  
1  
3  
6  
9
```

4. Bucket Sort

PROGRAM:

```
#include <stdio.h>
```

```
int main() {  
    int n;  
    printf("ENTER NO. OF ELEMENTS: ");  
    scanf("%d", &n);  
    int arr[n];  
    printf("ENTER THE VALUES (0 to 100): ");  
    for (int i = 0; i < n; i++) {  
        scanf("%d", &arr[i]);  
    }  
    int bucket[101] = {0};  
    for (int i = 0; i < n; i++) {  
        bucket[arr[i]]++;  
    }  
    printf("Sorted array: ");  
    for (int i = 0; i <= 100; i++) {  
        while (bucket[i] > 0) {  
            printf("%d ", i);  
            bucket[i]--;  
        }  
    }  
    return 0;  
}
```

```
amma@amma11:~$ gcc bucket_sort.c -o bucket_sort
amma@amma11:~$ ./bucket_sort
enter element 0: 8
enter element 1: 2
enter element 2: 0
enter element 3: 1
enter element 4: 7
0
1
2
7
8
```

5. Heap Sort

PROGRAM:

```
#include<stdio.h>

int main() {
    int n;

    printf("ENTER NO. OF ELEMENTS: ");
    scanf("%d", &n);

    int arr[n];

    printf("ENTER THE VALUES: ");
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    for (int i = 1; i < n; i++) {
        int child = i;

        while (child > 0) {
            int parent = (child - 1) / 2;
```



```

    if (arr[parent] < arr[child]) {
        int temp = arr[parent];
        arr[parent] = arr[child];
        arr[child] = temp;
        child = parent;
    } else {
        break;
    }
}
}

for (int i = n - 1; i > 0; i--) {
    int temp = arr[0];
    arr[0] = arr[i];
    arr[i] = temp;
    int parent = 0;
    while (1) {
        int left = 2 * parent + 1;
        int right = 2 * parent + 2;
        int largest = parent;
        if (left < i && arr[left] > arr[largest])
            largest = left;
        if (right < i && arr[right] > arr[largest])

```

```
        largest = right;
    if (largest != parent) {
        int temp2 = arr[parent];
        arr[parent] = arr[largest];
        arr[largest] = temp2;
        parent = largest;
    } else {
        break;
    }
}

}

printf("Sorted array: ");
for (int i = 0; i < n; i++) {
    printf("%d ", arr[i]);
}

return 0;
}
```

```
amma@amma11:~$ gcc heap_sort.c -o heap_sort
amma@amma11:~$ ./heap_sort
enter element 0: 9
enter element 1: 1
enter element 2: 8
enter element 3: 3
enter element 4: 6
1
3
6
8
9
```

N.ASHWATH

CH.SC.U4CSE24133