

Experiment:17-Illustrate the deadlock avoidance concept by simulating Banker's algorithm with C.

Aim:

The aim of this program is to **illustrate the concept of deadlock avoidance** by simulating **Banker's Algorithm** in C. The Banker's Algorithm is a resource allocation and deadlock avoidance algorithm that checks whether the system is in a safe state before granting resources to a process.

Procedure:

1. **Define the Data Structures:** The system needs several matrices and vectors:
 - Allocation[][]: Keeps track of how many resources are currently allocated to each process.
 - Max[][]: Represents the maximum resources each process may need.
 - Available[]: Represents the available resources in the system.
 - Need[][]: Represents the remaining resources each process may need (calculated as $Need[i][j] = Max[i][j] - Allocation[i][j]$).
2. **Safety Check:** The algorithm checks if granting the request for resources leaves the system in a **safe state**. This is done by simulating the allocation and verifying if all processes can eventually finish with the available resources.
3. **Granting Resources:** Before granting a resource request, the system checks if the request is **less than or equal to the need of the process** and if the request is **less than or equal to the available resources**.
4. **Simulation:**
 - The algorithm simulates whether the system can proceed with all processes completing successfully (safe state).
 - If the system is in a safe state, the request is granted. Otherwise, the request is denied.

Banker's Algorithm C Program:

```
#include <stdio.h>
```

```
#include <stdbool.h>
```

```
#define P 5
```

```
#define R 3
```

```

bool isSafeState(int processes[], int avail[], int max[][R], int allot[][R]) {

    int work[R];

    bool finish[P];

    for (int i = 0; i < R; i++) {

        work[i] = avail[i];

    }

    for (int i = 0; i < P; i++) {

        finish[i] = false;

    }

    int count = 0;

    while (count < P) {

        bool progressMade = false;

        for (int p = 0; p < P; p++) {

            if (!finish[p]) {

                bool canAllocate = true;

                for (int r = 0; r < R; r++) {

                    if (max[p][r] - allot[p][r] > work[r]) {

                        canAllocate = false;

                        break;

                    }

                }

                if (canAllocate) {

                    for (int r = 0; r < R; r++) {

                        work[r] += allot[p][r];

                    }

                    finish[p] = true;

                    count++;

                }

            }

        }

    }

}

```

```

        progressMade = true;
    }
}
}
if (!progressMade) {
    return false;
}
}
return true;
}

```

```

bool requestResources(int processes[], int avail[], int max[][R], int allot[][R], int request[], int pid) {
    for (int i = 0; i < R; i++) {
        if (request[i] > max[pid][i] - allot[pid][i]) {
            printf("Error: Process has exceeded its maximum claim!\n");
            return false;
        }
    }
    for (int i = 0; i < R; i++) {
        if (request[i] > avail[i]) {
            printf("Resources are not available!\n");
            return false;
        }
    }
    for (int i = 0; i < R; i++) {
        avail[i] -= request[i];
        allot[pid][i] += request[i];
    }
}

```

```

    }

    if (isSafeState(processes, avail, max, allot)) {

        printf("Request can be granted safely.\n");

        return true;

    } else {

        for (int i = 0; i < R; i++) {

            avail[i] += request[i];

            allot[pid][i] -= request[i];

        }

        printf("Request cannot be granted safely.\n");

        return false;

    }

}

```

```

int main() {

    int processes[] = {0, 1, 2, 3, 4};

    int avail[] = {3, 3, 2};

    int max[][R] = {

        {7, 5, 3},

        {3, 2, 2},

        {9, 0, 2},

        {2, 2, 2},

        {4, 3, 3}

    };

    int allot[][R] = {

        {0, 1, 0},

        {2, 0, 0},

```

```

    {3, 0, 2},
    {2, 1, 1},
    {0, 0, 2}
};

int pid, request[R];

printf("Enter process ID for resource request (0-4): ");

scanf("%d", &pid);

printf("Enter request for resources (format: Request1 Request2 Request3): ");

for (int i = 0; i < R; i++) {
    scanf("%d", &request[i]);
}

if (requestResources(processes, avail, max, allot, request, pid)) {
    printf("Resources allocated successfully.\n");
} else {
    printf("Request denied.\n");
}

return 0;
}

```

Output:

Output

[Clear](#)

Enter process ID for resource request (0-4): 192372048

Enter request for resources (format: Request1 Request2 Request3): 1 0 2

Resources are not available!

Request denied.

Enter process ID for resource request (0-4): 3

Enter request for resources (format: Request1 Request2 Request3): 1 1 0

Request can be granted safely.

Resources allocated successfully.