2/11/26

Ashwini.P

SQL Mock.

1 CREATE TABLE SHOPPING (

ShopID INT NOT NULL AUTO_INCREMENT PRIMARY KEY,

ShopName VARCHAR (50) NOT NULL,

ProductName VARCHAR(50) NOT NULL:

Qty INT DEFAULT 0

);

INSERT INTO SHOPPING (ShopName, ProductName, Qty)

VALUES

('ABC Store', 'Soap', 10)

('XYZ Store', Rice', 20)

Output.

ShopID	ShopName	ProductName	Qty.
1	ABC	Soap	10
2	XYZ	Rice	20

2. INSERT INTO Shopping (ShopName, ProductName, Qty)
VALUES.

('ABC', 'Soap', 10),

('XYZ', 'Rice', 20),

('Sri Store', 'Sugar', 5);

```
Select * From Shopping
ORDER BY Qty DESC;
```

Output:

ShopID	Shop Name	Product Name.	Qty
2	XYZ	Rice	20
1	ABC	Soap	10
3	Sri	Sugar	5

3.
```
CREAT TABLE Products (
    ShopID INT.
    ProductID INT PRIMARY KEY,
    Product Name VARCHAR(50)
    Price INT
);

INSERT INTO Products
VALUES
  (1, 101, 'Soap', 50),
  (2, 102, Rice, 60);

SELECT * From Shopping.
FULL OUTER JOIN Products
ON Shopping.ShopID = Products.ShopID;
```

OUTPUT

ShopID	Shop Name	Product Name	Qty
1	ABL	Soap	10
2	XYZ	Rice	20

DELIMITER //
CREATE PROCEDURE GetProductDetails(IN Sname
VARCHAR(50))
BEGIN
SELECT ProductName, Qty
FROM Shopping
WHERE ShopName = Sname;
END //
DELIMITER ;

CALL Get productdetails('ABC Stores');
Output:

ProductName	Qty
Rice	500
Soap	10

5 CREATE TRIGGER trigger_Name
BEFORE INSERT ON table_name
FOR EACH ROW
BEGIN
SQL Statements
END;