


PHYC90045 Introduction to Quantum Computing

Week 11

Lecture 21
Python, IBM's QISKit

Lecture 22
- Further quantum algorithms


Lab 11
Implementing small algorithms on IBM's 16 qubit machine



PHYC90045 Introduction to Quantum Computing

QISKit and Python

Physics 90045
Lecture 21




PHYC90045 Introduction to Quantum Computing

Overview

In Friday's laboratory we will be programming IBM's 16 qubit quantum computer. This lecture introduces the tools you can use to access it on your computer:

- Python primer
- Jupyter notebooks
- Using QISKit




PHYC90045 Introduction to Quantum Computing

On your own machine: Installing Python

Install Python3

Install Anaconda with **Python 3.6** version, download from:
<https://www.anaconda.com/download/>


Reference:
<https://www.qiskit.org/documentation/install.html>



Quantum Computing and IBM Q #390

PHYC90045 Introduction to Quantum Computing

Install Qiskit




```

cshill ~ -bash --- 100x24
Last login: Fri Oct 11 09:21:55 on tty003
- > pip install qiskit jupyter
    
```


PHYC90045 Introduction to Quantum Computing


Jupyter notebook




```

cshill ~ -bash --- 100x24
Last login: Fri Oct 11 09:21:55 on tty003
- > jupyter notebook
    
```







PHYC90045 Introduction to Quantum Computing

Using IBM Quantum Experience

Go to IBM Quantum Experience website: quantum-computing.ibm.com

Sign in to IBM Q Experience

What is IBM Q Experience? [Learn more](#)

Log in with IBM, Google, Twitter, LinkedIn, or Email

Sign up. Sign in. If you haven't already, get yourself added to the list of users in the Melbourne Q-Hub.

PHYC90045 Introduction to Quantum Computing


IBM Q Experience Landing Page


PHYC90045 Introduction to Quantum Computing


Starting a new Workbook

To see your existing notebooks, tutorials or start a new one. Select "QISKIT Notebooks"

Or click on the button to create a new notebook







PHYC90045 Introduction to Quantum Computing

Defining and calling Functions

def keyword indicates a new function No types on parameters

Colon

Comment

```
def square(x):
    # This is a comment
    return x*x
```

Whitespace is significant in python.
Indentation indicates a new block.

No semicolons.
Newline is the end of a statement

Calling a function:

```
square(4)
square(x=4)
```

Named parameters

PHYC90045 Introduction to Quantum Computing

Lists and for loops

Lists store a sequence of values. Square brackets indicate a list:

```
["This", "is", "a", "list"]
primes = [2, 3, 5, 7, 11]
```

Eg. For loops often use lists:

```
for p in primes:
    print(p)
```

```
2
3
5
7
11
```

Accessing an individual element.
0-based!

```
primes[2]
```

```
5
```

PHYC90045 Introduction to Quantum Computing

Dictionaries

Dictionaries store key-value pairs.

Curly braces indicate a dictionary

key

value

```
me = {"name": "Charles", "height": 1.79, "favourite_food": "pizza"}
me["favourite_food"]
```

```
'pizza'
```

```
me["favourite_food"] = "sweet and sour pork"
me["favourite_food"]
```

```
'sweet and sour pork'
```

PHYC90045 Introduction to Quantum Computing

Importing other libraries

```
import numpy as np
x = np.matrix([[0,1],
               [1,0]])
```

Importing a module ("as np" is optional). numpy gives similar functionality to MATLAB

Calling functions from that module. Here creating an X matrix.

Or import individual functions and classes:

```
from qiskit import QuantumProgram
from qiskit import available_backends, execute, get_backend, compile
from qiskit import QuantumCircuit, ClassicalRegister, QuantumRegister, QISKitError
```


qiskit is an API for interacting with IBM's quantum computers remotely.

PHYC90045 Introduction to Quantum Computing

IBM's Qiskit


PHYC90045 Introduction to Quantum Computing

Terra, Aer, Ignis, Aqua



Terra (Earth): Access to IBM Q Devices through python interface
Aer (Air): Classical simulation of quantum algorithms/circuits
Ignis (Fire): Characterisation of errors, tomography
Aqua (Water): Large selection of quantum algorithms


PHYC90045 Introduction to Quantum Computing



QISKit Introduction

Introduction to Qiskit


PHYC90045 Introduction to Quantum Computing



Constructing a circuit in Qiskit

In this tutorial we will construct a circuit to create a Bell-state using Qiskit.

PHYC90045 Introduction to Quantum Computing



First we will load the required libraries from qiskit.

```

In [1]: %matplotlib inline
# Importing standard Qiskit libraries and configuring account
import numpy as np
from qiskit import *
from qiskit.compiler import transpile, assemble
from qiskit.tools.jupyter import *
from qiskit.visualization import *

# Loading your IBM Q account(s)
provider = IBMQ.load_account()

```

PHYC90045 Introduction to Quantum Computing

Now, we will construct a quantum circuit with two qubits.

```
In [3]: # Create a Quantum Register with 2 qubits.
q = QuantumRegister(2, 'q')
c = ClassicalRegister(2, 'c')

# Create a Quantum Circuit acting on the q register
cirq = QuantumCircuit(q, c)
```

PHYC90045 Introduction to Quantum Computing

Adding gates to our circuit.

```
In [4]: # Add a H gate on qubit 0, putting this qubit in superposition.
cirq.h(q[0])
# Add a CX (CNOT) gate on control qubit 0 and target qubit 1, putting
# the qubits in a Bell state.
cirq.cx(q[0], q[1])
# Measure the results
cirq.measure(q, c)
```

Out[4]: <qiskit.circuit.instructionset.InstructionSet at 0x1244de690>

```
In [5]: cirq.draw()
```

Out[5]:

```

q_0: |0>---[H]---●---[M]
               |
q_1: |0>---[X]---[M]
               |
c_0: 0
c_1: 0

```

PHYC90045 Introduction to Quantum Computing

Simulating the circuit

First, let's run the circuit on a simulator.

PHYC90045 Introduction to Quantum Computing

IBM's simulators are in a package called Aer. Let's get a backend which can simulate our circuit.

```
In [6]: backend = Aer.get_backend('qasm_simulator')
        job = execute(circ, backend)
```

PHYC90045 Introduction to Quantum Computing

We can obtain samples from this circuit (from the simulator). To do this:

```
In [7]: result_sim = job.result()
        counts_sim = result_sim.get_counts(circ)
        plot_histogram(counts_sim)
```

Out[7]:

Measurement Result (q)	Probability
0	0.501
1	0.499

PHYC90045 Introduction to Quantum Computing

Using a real IBM Q Device

Now, let us submit the circuit to a real quantum computer, and see how it performs.

PHYC90045 Introduction to Quantum Computing

A number of different machines are available for use. Note the machines available to you might be different.

```
In [27]: print("Available backends:")
provider.backends()

Available backends:

Out[27]: [QASM simulator('ibmq_qasm_simulator') from IBMQ(hub='ibm-q', group='open', pr
object='main')],
<IBMQBackend('ibmqx2') from IBMQ(hub='ibm-q', group='open', project='main')>,
<IBMQBackend('ibmq_16_melbourne') from IBMQ(hub='ibm-q', group='open', projec
t='main')>,
<IBMQBackend('ibmq_vigo') from IBMQ(hub='ibm-q', group='open', project='mai
n')>,
<IBMQBackend('ibmq_ourense') from IBMQ(hub='ibm-q', group='open', project='ma
in')>]
```

PHYC90045 Introduction to Quantum Computing

Let us find the least busy device and run on that.

```
In [9]: from qiskit.providers.ibmq import least_busy

large_enough_devices = provider.backends(filters=[lambda x: x.configuration().n_qub
its < 10 and not x.configuration().simul
ator])
backend = least_busy(large_enough_devices)
print("The best backend is " + backend.name())

The best backend is ibmq_vigo
```

PHYC90045 Introduction to Quantum Computing

```
In [10]: # Create a Classical Register with 2 bits.
q = QuantumRegister(2, 'q')
c = ClassicalRegister(2, 'c')

# Create a Quantum Circuit
qc = QuantumCircuit(q,c)

# Add gates
qc.h(q[0])
qc.cx(q[0],q[1])

qc.barrier(q)

# Map the quantum measurement to the classical bits
qc.measure(q,c)

# Drawing the circuit
qc.draw()
```

Out[10]:

PHYC90045 Introduction to Quantum Computing

Now, let us use the Qiskit API to submit job to IBM remotely.

```
In [11]: from qiskit.tools.monitor import job_monitor
shots = 1024 # Number of shots to run the program (experiment); maximum
is 1024 shots.
job_exp = execute(qc, backend=backend, shots=shots)
job_monitor(job_exp)

Job Status: job has successfully run
```

PHYC90045 Introduction to Quantum Computing

Once the job has run (we may need to wait), we can examine the results:

```
In [12]: result_exp = job_exp.result()
result_exp


Out[12]: Result(backend_name='ibmq_vigo', backend_version='1.0.1', date=datetime.datetime(2019, 10, 2, 12, 36, 26, tzinfo=timezone.utc), execution_id='f4831262-e516-11e9-9f14-ac1f6b47c318', header=Obj(backend_name='ibmq_vigo', backend_version='1.0.1'), job_id='5d9499415887060187d441f', qobj_id='6ad1a60c-df84-4b5c-9b75-a91a44af3b5', result=ExperimentResult(data=ExperimentResultData(counts=Obj(0x=543, 0x1=18, 0x2=18, 0x3=445)), header=Obj(circuit_labels=[['c', 0], ['c', 1]], creg_names=[['c', 2]]), memory_slots=2, n_qubits=5, name='circuit2', qreg_names=[['q', 5]]), qubit_labels=[['q', 0], ['q', 1], ['q', 2], ['q', 3], ['q', 4]]), meas_level=2, memory=False, shots=1024, success=True), status='Successful completion', success=True, time_taken=0.32990440216064)
```

PHYC90045 Introduction to Quantum Computing

Plotting the results:

```
In [13]: counts_exp = result_exp.get_counts(qc)
plot_histogram(counts_exp)

Out[13]:
```



Results	Probabilities
0	0.530
01	0.018
10	0.012
1	0.440

PHYC90045 Introduction to Quantum Computing

Now with more qubits

Let's go over that one more time with the five qubit GHZ state:

$$\frac{|00000\rangle + |11111\rangle}{\sqrt{2}}$$

```
In [14]: %matplotlib inline
# Importing standard Qiskit libraries and configuring account
import numpy as np
from qiskit import *

In [17]: # Loading your IBM Q account(s)
provider = IBMQ.load_account()
```

PHYC90045 Introduction to Quantum Computing

```
In [18]: # Create a Quantum Register with 5 qubits.
q = QuantumRegister(5, 'q')
c = ClassicalRegister(5, 'c')

# Create a Quantum Circuit acting on the q register
qc = QuantumCircuit(q, c)
```

PHYC90045 Introduction to Quantum Computing

```
qc.h(q[0])
qc.cx(q[0], q[1])
qc.cx(q[1], q[2])
qc.cx(q[2], q[3])
qc.cx(q[3], q[4])

qc.measure(q, c)
```

PHYC90045 Introduction to Quantum Computing

Draw the circuit, and check everything is correct!

```
In [21]: qc.draw()
```

Out[21]:

q_0: |0>
q_1: |0>
q_2: |0>
q_3: |0>
q_4: |0>
c_0: 0
c_1: 0
c_2: 0
c_3: 0
c_4: 0

PHYC90045 Introduction to Quantum Computing

Simulate the circuit and ensure you get correct results.

```
In [23]: backend = Aer.get_backend('qasm_simulator')
job = execute(qc, backend)
result_sim = job.result()
counts_sim = result_sim.get_counts(qc)
plot_histogram(counts_sim)
```

Out[23]:

Counts	Probability
0000	0.495
1111	0.505


PHYC90045 Introduction to Quantum Computing

When everything is correct, submit the job to IBM Q Device to run:

```
In [24]: from qiskit.providers.ibmq import least_busy
large_enough_devices = provider.backends(filters=lambda x: x.configuration().n_qubits < 10 and
not x.configuration().simulator)
backend = least_busy(large_enough_devices)
print("The best backend is " + backend.name())
The best backend is ibmq_vigo
```

PHYC90045 Introduction to Quantum Computing

```
In [25]: from qiskit.tools.monitor import job_monitor
shots = 1024 # Number of shots to run the program (experiment); maximum
           is 8192 shots.
max_credits = 3 # Maximum number of credits to spend on executions.
job_exp = execute(qc, backend=backend, shots=shots, max_credits=max_credits)
job_monitor(job_exp)
Job Status: job has successfully run
```




PHYC90045 Introduction to Quantum Computing

Qiskit Documentation

Make use of "Documentation and Support" in the left hand menu!

PHYC90045 Introduction to Quantum Computing



Week 11

Lecture 21
Python, IBM's QISKit

Lecture 22
- Further quantum algorithms

Lab 11
Implementing small algorithms on IBM's 16 qubit machine
