

SWEN30006 Software Modelling and Design

DOMAIN MODEL REFINEMENT

Larman Chapter 31

Crude classifications and false generalizations are the curse of the organized life.

—A generalization by H.G. Wells




Objectives

On completion of this topic you should be able to:

- Refine the domain model with generalizations, specializations, association classes, time intervals, composition, and packages.
- Identify when showing a subclass is worthwhile.




Generalization-Specialization Hierarchy






Notation: Separate/Shared Arrows






Payment Class Hierarchy






Abstract Class Notation






Abstract Conceptual Classes





Subclass Conformance






Generalization Sets

isCovering:


complete or incomplete
isDisjoint:

disjoint or overlapping
powerType (optional)

- semantically equivalent association











Legal, but is it Useful?






Justifying Payment Subclasses






Justifying the AuthorizationService Hierarchy






Possible Hierarchy: Transactions






Alternate Hierarchy: Transactions






Modelling Changing States





Inappropriate Use of an Attribute

Assigned by AuthorizationService to identify store




Guideline

In a domain model, if a class C can simultaneously have many values for the same kind of attribute A, do not place attribute A in C. Place attribute A in another class that is associated with C.




1st Attempt: merchantID Problem






Solution: merchantID Problem





Association Classes






Guideline: Association Classes

Clues that a domain assoc. class might be useful:

- 1. An attribute is related to an association
- Instances of (potential) assoc. class have lifetime dependency on the association
- 3. There is a many-to-many association between concepts, with other information to associate with the association.



Aggregation Examples: POS Application





Aggregation and Composition

Shared Aggregation (aka Aggregation)

Composite Aggregation (aka Composition)


Common properties:

- binary associations
- asymmetric: only one end of association can be aggregation
- transitive: aggregation links should form a directed, acyclic graph; no composite instance can be indirect part of itself



Aggregation (shared)

- shared part could be included in several composites; if some or all of the composites are deleted, shared part may still exist
- Kind of association that *loosely* suggests a whole-part relationship




Guideline: don't use shared aggregation



Composition

- □ it is a whole/part relationship,
- a part could be included in at most one composite (whole) at a time, and
- if a composite (whole) is deleted, all of its composite parts may be deleted with it
 - Hospital: yes; Department: depends





Composition Guidelines

Consider composition when:

- □ Lifetime of part is bound to lifetime of composite
 - Create/Delete dependency
- Obvious whole-part physical or logical assembly
- Some properties of the composite propagate to the parts, e.g. location
- Operations applied to composite propagate to the parts, e.g. destruction, movement, recording

If in doubt, leave it out.



History

Scenarios:


- 1. I did not receive my tax receipt; please reissue.
- 2. What was the effect of pricing on sales?

History:

- Required when current information is insufficient
- May be a simple attribute (e.g. pricing) or may be a complex structure (catalogue, pricing, availability)
- Right structure for history depends on usage




Product Prices and Time Intervals



Product Price	activeInterval.start	activeInterval.end
\$1.20	9:00am 1/1/2016	9:30am 1/1/2016
\$1.50	9:30am 1/1/2016	10:00am 1/1/2016
\$1.70	10:30am 1/1/2016	11:00am 1/1/2016
\$1.20	10:45am 1/1/2016	11:30am 1/1/2016




Product Prices and Change Time




Product Price	changeTime	
\$1.20	9:00am 1/1/2016	
\$1.50	9:30am 1/1/2016	
\$1.70	10:30am 1/1/2016	
\$1.20	10:45am 1/1/2016	




Role Names






М


Two Ways to Model Human Roles





Derived Attributes






Guideline: Avoid unless defining prominent domain terminology




Qualified Association (1)






Qualified Association (2)






Reflexive Association






Ternary Association





UML Packages: Organising the Domain Model





Package for top-level domain model with two subordinate packages.

Sales package shown to have a dependency on the Core Elements Package.



A Referenced Class in a Package





- □ Element is *owned* by the defining package.
- Element can be referenced in other packages
 - Qualified name: PackageName::ElementName
 - New associations but no other modifications



Partitioning the Domain Model

Guideline: Place elements together in a package that:

- are in the same subject area—closely related by subject or purpose
- are in a class hierarchy together
- participate in the same use cases
- are strongly associated

and:

- rooted in a package called Domain
- consider a package for widely shared concepts