

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Programming, Problem Solving, and Abstraction

Chapter Three

Selection

Lecture slides © Alistair Moffat, 2013

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls to watch for

3.4 Case study

3.5 The switch statement

Summary

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

- ▶ Logical expressions and precedence again.
- ▶ Selection via the `if` statement, with or without `else`
- ▶ Selection via the `switch` statement (discouraged)

3.1 Logical expressions

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Relational operators test for equality and ordering.

In C: `<`, `<=`, `>`, `>=`, `==`, and `!=`.

Note that the equality test uses `==` and not `=`.

All of these operators yield `int` as the result type.

3.1 Logical expressions

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

In C, expressions that evaluate to “true” generate **integer 1**.

Expressions that evaluate to “false” generate **integer 0**.

Logical expressions may appear anywhere: `num_neg+=(n<0)` is valid.

In general, where true/false values are required, any **non-zero** value is interpreted as being **true**; only **zero** is taken as **false**.

3.1 Logical operators

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Logical operators combine `int` true/false values to obtain `int` true/false values:

Operands		Operation		
e1	e2	e1 && e2	e1 e2	! e1
0	0	0	0	1
0	NZ	0	1	1
NZ	0	0	1	0
NZ	NZ	1	1	0

3.1 Exercise 1

When is each of these expressions true?

```
5<x
```

```
5<x && x<=10
```

```
5<x && x<=10 || 15<x && x<=20
```

```
month==4 || month==6 || month==9 || month==11
```

```
year%4==0 && (year%100!=0 || year%400==0)
```

3.1 Logical expressions and precedence

[Concepts](#)[3.1 Logical expressions](#)[3.2 Selection](#)[3.3 Pitfalls](#)[3.4 Case study](#)[3.5 Switch](#)[Summary](#)

The **precedence** rules specify default evaluation order.

Operators	Operation class	Precedence
<code>++, --</code>	postinc, postdec	Highest
<code>!, -, (type)</code>	not, negation, casting	
<code>*, /, %</code>	multiplication	
<code>+, -</code>	addition	
<code><, >, <=, >=</code>	comparison	
<code>==, !=</code>	equality	
<code>&&</code>	and	
<code> </code>	or	Lowest
<code>=, +=, *=, etc</code>	assignment	

3.1 Logical expressions and precedence

Unlike the other operators, the various assignment operators are evaluated from right to left. For example, the statements:

```
x = y = 0;  
s = n += 1;
```

have the operation ordering

```
x = (y = 0);  
s = (n += 1);
```

Including redundant parentheses costs nothing.

3.1 Logical expressions and precedence

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Within the overall ordering imposed by precedence, the C system may choose how to evaluate expressions.

In $a*b+c*d$ either of $a*b$ or $c*d$ might get evaluated first.

This means that you must be careful to avoid expressions that have **side effects**, including the $++$ and $--$ operators. Use such operators cautiously and sparingly.

3.1 Logical expressions and precedence

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Left-to-right evaluation order is **guaranteed** for the “and” (**&&**) and “or” (**||**) operators.

In addition, for “and” and “or”, evaluation is terminated as soon as the outcome is known. Expressions like **`x!=0 && y/x>5`** are safe.

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

The `if` statement has two forms:

```
if ( guard )  
    statement1  
else  
    statement2
```

and

```
if ( guard )  
    statement1
```

Either or both of *statement1* and *statement2* can be empty statements, or **compound** statements bracketed by “{” and “}” pairs.

3.2 Selection

Concepts

3.1 Logical expressions

3.2 Selection


3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

The flow of control through the two-branch `if` statement is:



Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Example 1:

```
if (n < 0)
    num_neg += 1;
```

Example 2:

```
if (scanf("%d%d%d", &n, &m, &r) != 3) {
    printf("scanf failed to read three items\n");
    exit(EXIT_FAILURE);
}
```

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

The function `exit` can be used at any point to terminate program execution. Return of a non-zero exit value signals an “abnormal” termination.

The constants `EXIT_SUCCESS` and `EXIT_FAILURE` are defined in the header file `stdlib.h`, and are accessed using

```
#include <stdlib.h>
```

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Example 3:

```
if (year%4==0 && (year%100!=0 || year%400==0)) {  
    /* need to allow for leap years */  
    length_of_year = 366;  
    length_of_feb = 29;  
} else {  
    /* not a leap year */  
    length_of_year = 365;  
    length_of_feb = 28;  
}
```


Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

Example 4:

```
if (month==2) {  
    length_of_month = length_of_feb;  
} else if (month==4 || month==6 ||  
           month==9 || month==11) {  
    /* thirty days hath september, april, june,  
       and november */  
    length_of_month = 30;  
} else {  
    /* all the rest have 31, except february... */  
    length_of_month = 31;  
}
```

Concepts

[3.1 Logical expressions](#)[3.2 Selection](#)[3.3 Pitfalls](#)[3.4 Case study](#)[3.5 Switch](#)[Summary](#)

Write a program that reads a date in dd/mm/yyyy format and prints, in the same format, the date that it will be tomorrow.

Remember, start with a very simple program, and then expand it incrementally.

3.3 Pitfalls to watch for

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

► `equalinif.c`

What is output by this program when `0` is entered? Why?

Using “`=`” where “`==`” is intended is a very common mistake.

3.3 Pitfalls to watch for

PPSAA

Concepts

3.1 Logical
expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

▶ `danglingelse.c`

What is the final value of variable `z`? Why?

The compiler provides optional warning messages; ask for them with `-Wall` and read them all carefully.

3.3 Pitfalls to watch for

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

► `threetest.c`

Is the final value of `z` going to be 9? Why not?

This one may not result in a warning message being generated.

A silent compiler does **not** guarantee that your program is correct. Programs should always be carefully **tested**.

3.4 Case study

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

The 2012/13 Australian tax rates stipulate that annual income between \$18,200 and \$37,000 is taxed at 19.0 cents in the dollar; income between \$37,000 and \$80,000 at 32.5 cents in the dollar; and income between \$80,000 and \$180,000 at 37.0 cents in the dollar. Any further income is taxed at 45.0 cents in the dollar. In addition, a Medicare levy of 1.5 cents in the dollar is applied to all income. For a given gross income, what net income is received?

► `taxation.c`

3.5 The switch statement

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

```
switch ( integer expression ) {  
  case ( integer1 ):  
    statement1  
    break;  
  case ( integer2 ):  
    statement2  
    break;  
    ...  
  case ( integern ):  
    statementn  
    break;  
  default:  
    statement  
}
```

3.5 The switch statement

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

A sensible `switch`:

► `switch1.c`

To manage the logic flow, each `case` should have a `break`.

3.5 The switch statement

PPSAA

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

A dangerous `switch`:

► `switch2.c`

Trace the final value for each input value of `x`. Was it easy?

Concepts

3.1 Logical expressions

3.2 Selection

3.3 Pitfalls

3.4 Case study

3.5 Switch

Summary

- ▶ Logical and relational expressions are integer valued.
- ▶ Be careful with precedence, be especially wary of side-effects.
- ▶ The `if` statement allows conditional execution based on an integer-valued guard.
- ▶ Switch statements should be avoided, they encourage poorly structured code. If for some reason you must use them, be disciplined, and use a `break` for every `case`.